

Ruby - Bug #646

tests for minunit have bad chemistry with other tests

10/14/2008 11:24 PM - mame (Yusuke Endoh)

Status:Closed Priority:Normal Assignee:zenspider (Ryan Davis) Target version: ruby -v:	Backport:
Description =begin Hi, The current tests for minitest seem to use at_exit, which lets the tests be run every time when forked ruby process exits. As a result, test log is hard to read: \$ make test-all TESTS="gdbm minitest" ./miniruby -I./lib -I./ext/common -I./- -r./ext/purelib.rb ./runruby.rb --extout=.ext -- "./test/runner.rb" gdbm minitest Loaded suite [gdbm, minitest] Started Loaded suite ./test/runner Started Finished in 0.160002 seconds. 114 tests, 350 assertions, 0 failures, 0 errors, 0 skips Loaded suite ./test/runner Started Finished in 0.120002 seconds. 114 tests, 350 assertions, 0 failures, 0 errors, 0 skips ..Loaded suite ./test/runner Started Finished in 0.140002 seconds. 114 tests, 350 assertions, 0 failures, 0 errors, 0 skips Loaded suite ./test/runner Started Finished in 0.050001 seconds. 114 tests, 350 assertions, 0 failures, 0 errors, 0 skips Loaded suite ./test/runner Started Finished in 0.080001 seconds. 114 tests, 350 assertions, 0 failures, 0 errors, 0 skips Finished in 9.150138028 seconds. 47 tests, 957 assertions, 0 failures, 0 errors Loaded suite ./test/runner Started Finished in 0.040001 seconds. 114 tests, 350 assertions, 0 failures, 0 errors, 0 skips	

In addition, as might be expected, the summary text at the last ("47 tests, 957 assertions , ..." does not include the test result of minitest. It is very inconvenience.

```
$ make test-all TESTS="gdbm"
./miniruby -I./lib -I.ext/common -I./-r./ext/purelib.rb
./runruby.rb --extout=.ext -- ./test/runner.rb" gdbm
Loaded suite gdbm
Started
```

```
.....
Finished in 8.420127015 seconds.
```

47 tests, 957 assertions, 0 failures, 0 errors

I think we must do something about this problem, but I have no good idea to solve this. Should the tests for minitest be separated from test/ directory?

```
--
Yusuke ENDOH mame@tsg.ne.jp
=end
```

History

#1 - 10/15/2008 01:17 PM - zenspider (Ryan Davis)

=begin

On Oct 14, 2008, at 07:24 , Yusuke ENDOH wrote:

The current tests for minitest seem to use at_exit, which lets the tests be run every time when forked ruby process exits. As a result, test log is hard to read:

```
$ make test-all TESTS="gdbm minitest"
./miniruby -I./lib -I.ext/common -I./-r./ext/purelib.rb
./runruby.rb --extout=.ext -- ./test/runner.rb" gdbm minitest
```

Fixed

=end

#2 - 10/15/2008 11:45 PM - mame (Yusuke Endoh)

- Priority changed from 3 to Normal

=begin

=end

#3 - 11/29/2008 04:22 PM - ko1 (Koichi Sasada)

- Status changed from Open to Closed

- Assignee set to zenspider (Ryan Davis)

=begin

=end