



User Guide

AWS CloudTrail



Version 1.0

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS CloudTrail: User Guide

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

What Is AWS CloudTrail?	1
Accessing CloudTrail	2
CloudTrail console	2
AWS CLI	3
CloudTrail APIs	3
AWS SDKs	4
How CloudTrail works	4
CloudTrail Event history	4
CloudTrail Lake and event data stores	5
CloudTrail Lake dashboards	8
CloudTrail trails	9
CloudTrail Insights events	13
CloudTrail channels	14
Concepts	15
CloudTrail events	16
Event history	45
Trails	45
Organization trails	47
CloudTrail Lake and event data stores	49
CloudTrail Insights	49
Tags	50
AWS Security Token Service and CloudTrail	50
Global service events	50
Supported Regions	52
Supported services and integrations	55
AWS service integrations with CloudTrail logs	56
CloudTrail integration with Amazon EventBridge	58
CloudTrail integration with AWS Organizations	59
CloudTrail integration with AWS Control Tower	59
CloudTrail integration with Amazon Security Lake	59
CloudTrail Lake integration with Amazon Athena	60
CloudTrail Lake integration with AWS Config	60
CloudTrail Lake integration with AWS Audit Manager	60
AWS service topics for CloudTrail	60

Unsupported services	84
Quotas in AWS CloudTrail	84
CloudTrail resource quotas	84
Transactions per second (TPS) quotas in CloudTrail	90
CloudTrail tutorials	91
Grant permissions to use CloudTrail	91
View event history	93
Create a trail to log management events	94
View your log files	98
Create an event data store for S3 data events	99
Viewing CloudTrail cost and usage	107
Using AWS Budgets to manage costs	111
Creating user-defined cost allocation tags for CloudTrail Lake event data stores	112
Managing CloudTrail trail costs	113
Trail configuration	113
See also	114
Managing CloudTrail Lake costs	115
Event data store pricing options	115
Understanding CloudTrail Lake charges	116
Recommendations for how you can reduce costs	118
See also	120
Working with CloudTrail event history	121
Limitations of Event history	122
Viewing recent management events with the console	123
Navigating between pages	124
Customizing the display	124
Filtering CloudTrail events	125
Viewing details for an event	127
Downloading events	128
Viewing resources referenced with AWS Config	129
Viewing recent management events with the AWS CLI	130
Prerequisites	131
Getting command line help	132
Looking up events	132
Specifying the number of events to return	133
Looking up events by time range	134

Looking up events by attribute	134
Specifying the next page of results	136
Getting JSON input from a file	136
Lookup output fields	138
Working with CloudTrail Insights	140
Costs for Insights events	141
Delivery of Insights events	143
Logging Insights events with the CloudTrail console	144
Enabling CloudTrail Insights on an existing trail with the console	144
Enabling CloudTrail Insights on an existing event data store with the console	145
Logging Insights events with the AWS CLI	146
Logging Insights events for a trail using the AWS CLI	146
Logging Insights events for an event data store using the AWS CLI	148
Viewing Insights events for trails	151
Viewing Insights events for trails with the console	152
Viewing Insights events for trails with the AWS CLI	160
Viewing Insights events for event data stores	170
Viewing the Insights dashboard for an event data store	171
Viewing sample queries for Insights events	172
Working with CloudTrail Lake	174
CloudTrail Lake event data stores	174
CloudTrail Lake queries	175
CloudTrail Lake dashboards	176
CloudTrail Lake integrations	177
Additional resources	177
CloudTrail Lake supported Regions	178
CloudTrail Lake concepts and terminology	179
Event data stores	180
Integrations	181
Queries	183
Dashboards	183
Event data stores	184
Create, update, and manage event data stores with the console	186
Create, update, and manage event data stores with the AWS CLI	237
Manage event data store lifecycles	269
Copy trail events to an event data store	270

Federate an event data store	290
Organization event data stores	302
Integrations	308
Create an integration with a CloudTrail partner with the console	310
Create a custom integration with the console	312
Create, update, and manage CloudTrail Lake integrations with the AWS CLI	316
Additional information about integration partners	325
CloudTrail Lake integrations event schema	327
Dashboards	335
Prerequisites	336
Limitations	336
Region support	337
Required permissions	337
View a managed dashboard	342
Enable the Highlights dashboard	357
Disable the Highlights dashboard	359
Create a custom dashboard	359
Set a refresh schedule for a custom dashboard	362
Disable the refresh schedule for a custom dashboard	363
Change termination protection	364
Delete a custom dashboard	365
Create, update, and manage dashboards with the AWS CLI	365
Queries	175
Query editor tools	383
Create CloudTrail Lake queries from natural language prompts	384
View sample queries	391
Create or edit a query	394
Run a query and save query results	396
View query results	400
Summarize query results in natural language	402
Download saved query results	403
Validate saved query results	406
Optimize queries	420
Run and manage CloudTrail Lake queries with the AWS CLI	424
CloudTrail Lake SQL constraints	429
Supported functions, condition and join operators	430

Advanced, multi-table query support	431
Supported SQL schemas for event data stores	432
Supported schema for CloudTrail event record fields	432
Supported schema for CloudTrail Insights event record fields	436
Supported schema for AWS Config configuration item record fields	438
Supported schema for AWS Audit Manager evidence record fields	439
Supported schema for non-AWS event fields	440
Supported CloudWatch metrics	442
Working with CloudTrail trails	445
Creating a trail for your AWS account	446
Creating and updating a trail with the console	447
Creating, updating, and managing trails with the AWS CLI	478
Creating multiple trails	509
Creating a trail for an organization	512
Moving from member account trails to organization trails	516
Prepare for creating a trail for your organization	516
Creating a trail for your organization in the console	520
Creating a trail for an organization with the AWS CLI	530
Troubleshooting	537
Understanding multi-Region trails and opt-in Regions	540
What are the advantages of multi-Region trails?	541
What happens when you create a multi-Region trail?	541
What happens when you enable an opt-in Region?	541
What happens when you disable an opt-in Region?	542
Copying trail events to CloudTrail Lake	542
Considerations for copying trail events	544
Required permissions for copying trail events	545
Copy trail events to an existing event data store using the CloudTrail console	549
Getting and viewing your CloudTrail log files	552
Finding your CloudTrail log files	553
Downloading your CloudTrail log files	555
Configuring Amazon SNS notifications for CloudTrail	556
Configuring CloudTrail to send notifications	556
Using AWS CloudTrail with interface VPC endpoints	558
Regions	559
Create a VPC endpoint for CloudTrail	559

Create a VPC endpoint policy for CloudTrail	559
Shared subnets	563
Naming requirements	563
CloudTrail resource naming requirements	564
Amazon S3 bucket naming requirements	564
AWS KMS alias naming requirements	565
AWS account closure and trails	565
Configure CloudTrail settings	567
Organization delegated administrator	567
Required permissions to assign a delegated administrator	571
Add a CloudTrail delegated administrator	572
Remove a CloudTrail delegated administrator	573
Service-linked channels	574
Viewing service-linked channels by using the console	574
Viewing service-linked channels by using the AWS CLI	575
Understanding CloudTrail events	579
Management events	579
Data events	582
Data events supported by AWS CloudTrail	583
Network activity events	610
Insights events	614
Management events	617
Management events	618
Read and write events	618
Logging management events with the AWS Management Console	619
Logging management events with the AWS CLI	623
Logging management events with the AWS SDKs	638
Data events	638
Data events	640
Read-only and write-only events	668
Logging data events with the AWS Management Console	669
Logging data events with the AWS Command Line Interface	679
Filtering data events by using advanced event selectors	691
Logging data events for AWS Config compliance	703
Logging data events with the AWS SDKs	703
Network activity events	704

Advanced event selector fields for network activity events	707
Logging network activity events with the AWS Management Console	710
Logging network activity events with the AWS Command Line Interface	713
Logging events with the AWS SDKs	735
Add resource tag keys and IAM global condition keys to events	736
AWS services supporting resource tags	737
AWS services supporting IAM global condition keys	739
Event examples	742
CloudTrail record contents for management, data, and network activity events	743
Field truncation order for maximum event size of 1 MB	757
Example sharedEventID	758
CloudTrail record contents for Insights events for trails	759
Example insightDetails block	764
CloudTrail record contents for Insights events for event data stores	766
CloudTrail userIdentity element	771
Examples	771
Fields	772
Values for AWS STS APIs with SAML and web identity federation	780
AWS STS source identity	782
Non-API events captured by CloudTrail	785
AWS service events	785
AWS Management Console sign-in events	786
CloudTrail log files	802
Receiving CloudTrail log files from multiple Regions	803
Managing data consistency	805
Monitoring CloudTrail log files with Amazon CloudWatch Logs	805
Sending events to CloudWatch Logs	806
Creating CloudWatch alarms for CloudTrail events: examples	815
Stopping CloudTrail from sending events to CloudWatch Logs	822
CloudWatch log group and log stream naming for CloudTrail	823
Role policy document for CloudTrail to use CloudWatch Logs for monitoring	824
Receiving CloudTrail log files from multiple accounts	826
Redacting bucket owner account IDs for data events called by other accounts	827
Setting bucket policy for multiple accounts	828
Create trails in additional accounts	830
Sharing CloudTrail log files between AWS accounts	832

Share log files between accounts by assuming a role	833
Validating CloudTrail log file integrity	843
Why use it?	843
How it works	843
Enabling log file integrity validation for CloudTrail	845
Validating CloudTrail log file integrity with the AWS CLI	845
CloudTrail digest file structure	854
Custom implementations of CloudTrail log file integrity validation	861
CloudTrail log file examples	873
CloudTrail log file name format	873
Log file examples	874
Using the CloudTrail Processing Library	887
Minimum requirements	887
Processing CloudTrail logs	887
Advanced topics	893
Additional resources	899
Security	900
Data protection	901
Identity and Access Management	902
Audience	903
Authenticating with identities	903
Managing access using policies	904
How AWS CloudTrail works with IAM	906
Identity-based policy examples	913
Resource-based policy examples	930
Amazon S3 bucket policy for CloudTrail	938
Amazon S3 bucket policy for CloudTrail Lake query results	946
Amazon SNS topic policy for CloudTrail	949
Troubleshooting	956
Using service-linked roles	960
AWS managed policies	966
Compliance validation	969
Resilience	969
Infrastructure security	970
Cross-service confused deputy prevention	971
Security best practices	972

CloudTrail detective security best practices	972
CloudTrail preventative security best practices	974
Encrypting CloudTrail log files, digest files, and event data stores with AWS KMS keys (SSE-KMS)	978
Enabling log file encryption	979
Granting permissions to create a KMS key	981
Configure AWS KMS key policies for CloudTrail	981
Updating a resource to use your KMS key with the console	996
Enabling and disabling encryption for CloudTrail log files, digest files and event data stores with the AWS CLI	1000
How AWS CloudTrail uses AWS KMS	1003
Document history	1010
Earlier updates	1069

What Is AWS CloudTrail?

AWS CloudTrail is an AWS service that helps you enable operational and risk auditing, governance, and compliance of your AWS account. Actions taken by a user, role, or an AWS service are recorded as events in CloudTrail. Events include actions taken in the AWS Management Console, AWS Command Line Interface, and AWS SDKs and APIs.

CloudTrail provides three ways to record events:

- **Event history** – The **Event history** provides a viewable, searchable, downloadable, and immutable record of the past 90 days of management events in an AWS Region. You can search events by filtering on a single attribute. You automatically have access to the **Event history** when you create your account. For more information, see [Working with CloudTrail event history](#).

There are no CloudTrail charges for viewing the **Event history**.

- **CloudTrail Lake** – [AWS CloudTrail Lake](#) is a managed data lake for capturing, storing, accessing, and analyzing user and API activity on AWS for audit and security purposes. CloudTrail Lake converts existing events in row-based JSON format to [Apache ORC](#) format. ORC is a columnar storage format that is optimized for fast retrieval of data. Events are aggregated into *event data stores*, which are immutable collections of events based on criteria that you select by applying advanced event selectors. You can keep the event data in an event data store for up to 3,653 days (about 10 years) if you choose the **One-year extendable retention pricing** option, or up to 2,557 days (about 7 years) if you choose the **Seven-year retention pricing** option. You can create an event data store for a single AWS account or for multiple AWS accounts by using AWS Organizations. You can import any existing CloudTrail logs from your S3 buckets into an existing or new event data store. You can also visualize top CloudTrail event trends with [Lake dashboards](#). For more information, see [Working with AWS CloudTrail Lake](#).

CloudTrail Lake event data stores and queries incur charges. When you create an event data store, you choose the [pricing option](#) you want to use for the event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention period for the event data store. When you run queries in Lake, you pay based upon the amount of data scanned. For information about CloudTrail pricing and managing Lake costs, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

- **Trails** – *Trails* capture a record of AWS activities, delivering and storing these events in an Amazon S3 bucket, with optional delivery to [CloudWatch Logs](#) and [Amazon EventBridge](#). You can input these events into your security monitoring solutions. You can also use your own third-

party solutions or solutions such as Amazon Athena to search and analyze your CloudTrail logs. You can create trails for a single AWS account or for multiple AWS accounts by using AWS Organizations. You can [log Insights events](#) to analyze your management events for anomalous behavior in API call rates and error rates. For more information, see [Creating a trail for your AWS account](#).

You can deliver one copy of your ongoing management events to your S3 bucket at no charge from CloudTrail by creating a trail, however, there are Amazon S3 storage charges. For more information about CloudTrail pricing, see [AWS CloudTrail Pricing](#). For information about Amazon S3 pricing, see [Amazon S3 Pricing](#).

Visibility into your AWS account activity is a key aspect of security and operational best practices. You can use CloudTrail to view, search, download, archive, analyze, and respond to account activity across your AWS infrastructure. You can identify who or what took which action, what resources were acted upon, when the event occurred, and other details to help you analyze and respond to activity in your AWS account.

You can integrate CloudTrail into applications using the API, automate trail or event data store creation for your organization, check the status of event data stores and trails you create, and control how users view CloudTrail events.

Accessing CloudTrail

You can work with CloudTrail in any of the following ways.

Topics

- [CloudTrail console](#)
- [AWS CLI](#)
- [CloudTrail APIs](#)
- [AWS SDKs](#)

CloudTrail console

Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.

The CloudTrail console provides a user interface for performing many CloudTrail tasks such as:

- Viewing recent events and event history for your AWS account.
- Downloading a filtered or complete file of the last 90 days of management events from **Event history**.
- Creating and editing CloudTrail trails.
- Creating and editing CloudTrail Lake event data stores.
- Running queries on event data stores.
- Configuring CloudTrail trails, including:
 - Selecting an Amazon S3 bucket for trails.
 - Setting a prefix.
 - Configuring delivery to CloudWatch Logs.
 - Using AWS KMS keys for encryption of trail data.
 - Enabling Amazon SNS notifications for log file delivery on trails.
 - Adding and managing tags for your trails.
- Configuring CloudTrail Lake event data stores, including:
 - Integrating event data stores with CloudTrail partners or with your own applications, to log events from sources outside of AWS.
 - Federating event data stores to run queries from Amazon Athena.
 - Using AWS KMS keys for encryption of event data store data.
 - Adding and managing tags for your event data stores.

For more information about the AWS Management Console, see [AWS Management Console](#).

AWS CLI

The AWS Command Line Interface is a unified tool that you can use to interact with CloudTrail from the command line. For more information, see the [AWS Command Line Interface User Guide](#). For a complete list of CloudTrail CLI commands, see [cloudtrail](#) and [cloudtrail-data](#) in the *AWS CLI Command Reference*.

CloudTrail APIs

In addition to the console and the CLI, you can also use the CloudTrail RESTful APIs to program CloudTrail directly. For more information, see the [AWS CloudTrail API Reference](#) and the [CloudTrail-Data API Reference](#).

AWS SDKs

As an alternative to using the CloudTrail API, you can use one of the AWS SDKs. Each SDK consists of libraries and sample code for various programming languages and platforms. The SDKs provide a convenient way to create programmatic access to CloudTrail. For example, you can use the SDKs to sign requests cryptographically, manage errors, and retry requests automatically. For more information, see the [Tools to Build on AWS](#) page.

How CloudTrail works

You automatically have access to the CloudTrail **Event history** when you create your AWS account. The **Event history** provides a viewable, searchable, downloadable, and immutable record of the past 90 days of recorded management events in an AWS Region.

For an ongoing record of events in your AWS account past 90 days, create a trail or a CloudTrail Lake event data store.

Topics

- [CloudTrail Event history](#)
- [CloudTrail Lake and event data stores](#)
- [CloudTrail Lake dashboards](#)
- [CloudTrail trails](#)
- [CloudTrail Insights events](#)
- [CloudTrail channels](#)

CloudTrail Event history

You can easily view the last 90 days of management events in the CloudTrail console by going to the **Event history** page. You can also view the event history by running the [aws cloudtrail lookup-events](#) command, or the [LookupEvents](#) API operation. You can search events in **Event history** by filtering for events on a single attribute. For more information, see [Working with CloudTrail event history](#).

The **Event history** is not connected to any trails or event data stores that exist in your account and is not affected by configuration changes you make to your trails and event data stores.

There are no CloudTrail charges for viewing the **Event history** page or running the `lookup-events` command.

CloudTrail Lake and event data stores

You can create an event data store to log [CloudTrail events](#) (management events, data events, network activity events), [CloudTrail Insights events](#), [AWS Audit Manager evidence](#), [AWS Config configuration items](#), or [events outside of AWS](#).

Event data stores can log events from the current AWS Region, or from all AWS Regions in your AWS account. Event data stores that you are using to log **Integration** events from outside AWS must be for a single Region only; they cannot be multi-Region event data stores.

If you have created an organization in AWS Organizations, you can create an *organization event data store* that logs all events for all AWS accounts in that organization. Organization event data stores can apply to all AWS Regions, or the current Region. Organization event data stores must be created using the management account or delegated administrator account, and when specified as applying to an organization, are automatically applied to all member accounts in the organization. Member accounts cannot see the organization event data store, nor can they modify or delete it. Organization event data stores cannot be used to collect events from outside of AWS. For more information, see [Understanding organization event data stores](#).

By default, all events in an event data store are encrypted by CloudTrail. When you configure an event data store, you can choose to use your own AWS KMS key. Using your own KMS key incurs AWS KMS costs for encryption and decryption. After you associate an event data store with a KMS key, the KMS key cannot be removed or changed. For more information, see [Encrypting CloudTrail log files, digest files, and event data stores with AWS KMS keys \(SSE-KMS\)](#).

The following table provides information about tasks you can perform on event data stores.

Task	Description
View and create dashboards	You can use CloudTrail Lake dashboards to see event trends for the event data stores in your account. You can view managed dashboards, create custom dashboards, and enable the Highlights dashboard to see highlights for your event data curated and managed by CloudTrail Lake.

Task	Description
Log management events	Configure your event data store to log read-only, write-only, or all management events. By default, event data stores log management events. You can filter management events on the following advanced event selector fields: <code>eventName</code> , <code>eventSource</code> , <code>eventType</code> , <code>readOnly</code> , <code>sessionCredentialFromConsole</code> , and <code>userIdentity.arn</code> .
Log data events	You can use advanced event selectors to create fine-grained selectors to log only those data events of interest. For example, you can filter on the <code>eventName</code> field to include or exclude logging of specific API calls, which can help control costs. For more information, see Filtering data events by using advanced event selectors.
Log network activity events	Configure your event data store to log network activity events. You can use advanced event selectors to filter on the <code>eventName</code> , <code>errorCode</code> , and <code>vpcEndpointId</code> fields to log only those events of interest.
Log Insights events	Configure your event data stores to log Insights events to help you identify and respond to unusual activity associated with management API calls. For more information, see Working with CloudTrail Insights. Additional charges apply for Insights events. You will be charged separately if you enable Insights for both trails and event data stores. For more information, see AWS CloudTrail Pricing.
Copy trail events	You can copy trail events to a new or existing event data store to create a point-in-time snapshot of events logged to the trail.

Task	Description
Enable federation on an event data store	You can federate an event data store to see the metadata associated with the event data store in the AWS Glue Data Catalog and run SQL queries on the event data using Amazon Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know how to find, read, and process the data that you want to query.
Stop or start event ingestion on an event data store	You can stop and start event ingestion on event data stores that collect CloudTrail management and data events, or AWS Config configuration items.
Create an integration with an event source outside of AWS	You can use CloudTrail Lake <i>integrations</i> to log and store user activity data from outside of AWS; from any source in your hybrid environments, such as in-house or SaaS applications hosted on-premises or in the cloud, virtual machines, or containers. For information about available integration partners, see AWS CloudTrail Lake Integrations .
View Lake sample queries in the CloudTrail console	The CloudTrail console provides a number of sample queries that can help you get started writing your own queries.
Create or edit a query	Queries in CloudTrail are authored in SQL. You can build a query on the CloudTrail Lake Editor tab by writing the query in SQL from scratch, or by opening a saved or sample query and editing it.
Save query results to an S3 bucket	When you run a query, you can save the query results to an S3 bucket.
Download saved query results	You can download a CSV file containing your saved CloudTrail Lake query results.
Validate saved query results	You can use CloudTrail query results integrity validation to determine whether the query results were modified, deleted, or unchanged after CloudTrail delivered the query results to the S3 bucket.

For more information about CloudTrail Lake, see [Working with AWS CloudTrail Lake](#).

CloudTrail Lake event data stores and queries incur charges. When you create an event data store, you choose the [pricing option](#) you want to use for the event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention period for the event data store. When you run queries in Lake, you pay based upon the amount of data scanned. For information about CloudTrail pricing and managing Lake costs, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

CloudTrail Lake dashboards

You can use CloudTrail Lake dashboards to see event trends for the event data stores in your account. CloudTrail Lake offers the following types of dashboards:

- **Managed dashboards** – You can view a managed dashboard to see event trends for an event data store that collects management events, data events, or Insights events. These dashboards are automatically available to you and are managed by CloudTrail Lake. CloudTrail offers 14 managed dashboards to choose from. You can manually refresh managed dashboards. You cannot modify, add, or remove the widgets for these dashboards, however, you can save a managed dashboard as a custom dashboard if you want to modify the widgets or set a refresh schedule.
- **Custom dashboards** – Custom dashboards allow you to query events in any event data store type. You can add up to 10 widgets to a custom dashboard. You can manually refresh a custom dashboard, or you can set a refresh schedule.
- **Highlights dashboards** – Enable the Highlights dashboard to view an at-a-glance overview of the AWS activity collected by the event data stores in your account. The Highlights dashboard is managed by CloudTrail and includes widgets that are relevant to your account. The widgets shown on the Highlights dashboard are unique to each account. These widgets could surface detected abnormal activity or anomalies. For example, your Highlights dashboard could include the **Total cross-account access widget**, which shows if there is an increase in abnormal cross-account activity. CloudTrail updates the Highlights dashboard every 6 hours. The dashboard shows the last 24 hours of data from the last update.

Each dashboard consists of one or more widgets and each widget represents a SQL query.

For more information, see [CloudTrail Lake dashboards](#).

CloudTrail trails

A *trail* is a configuration that enables delivery of events to an Amazon S3 bucket that you specify. You can also deliver and analyze events in a trail with [Amazon CloudWatch Logs](#) and [Amazon EventBridge](#).

Trails can log CloudTrail management events, data events, network activity events, and Insights events.

You can create both multi-Region and single-Region trails for your AWS account.

Multi-Region trails

When you create a multi-Region trail, CloudTrail records events in all AWS Regions that are [enabled](#) in your AWS account and delivers the CloudTrail event log files to an S3 bucket that you specify. As a best practice, we recommend creating a multi-Region trail because it captures activity in all enabled Regions. All trails created using the CloudTrail console are multi-Region trails. You can convert a single-Region trail to a multi-Region trail by using the AWS CLI. For more information, see [Understanding multi-Region trails and opt-in Regions](#), [Creating a trail with the console](#), and [Converting a single-Region trail to a multi-Region trail](#).

Single-Region trails

When you create a single-Region trail, CloudTrail records the events in that Region only. It then delivers the CloudTrail event log files to an Amazon S3 bucket that you specify. You can only create a single-Region trail by using the AWS CLI. If you create additional single trails, you can have those trails deliver CloudTrail event log files to the same S3 bucket or to separate buckets. This is the default option when you create a trail using the AWS CLI or the CloudTrail API. For more information, see [Creating, updating, and managing trails with the AWS CLI](#).

Note

For both types of trails, you can specify an Amazon S3 bucket from any Region.

If you have created an organization in AWS Organizations, you can create an *organization trail* that logs all events for all AWS accounts in that organization. Organization trails can apply to all AWS Regions, or the current Region. Organization trails must be created using the management account or delegated administrator account, and when specified as applying to an organization, are

automatically applied to all member accounts in the organization. Member accounts can see the organization trail, but cannot modify or delete it. By default, member accounts do not have access to the log files for an organization trail in the Amazon S3 bucket.

By default, when you create a trail in the CloudTrail console, your event log files and digest files are encrypted with a KMS key. If you choose not to enable **SSE-KMS encryption**, your event log files and digest files are encrypted using Amazon S3 server-side encryption (SSE). You can store your log files in your bucket for as long as you want. You can also define Amazon S3 lifecycle rules to archive or delete log files automatically. If you want notifications about log file delivery and validation, you can set up Amazon SNS notifications.

CloudTrail publishes log files multiple times an hour, about every 5 minutes. These log files contain API calls from services in the account that support CloudTrail. For more information, see [CloudTrail supported services and integrations](#).

Note

CloudTrail typically delivers logs within an average of about 5 minutes of an API call. This time is not guaranteed. Review the [AWS CloudTrail Service Level Agreement](#) for more information.

If you misconfigure your trail (for example, the S3 bucket is unreachable), CloudTrail will attempt to redeliver the log files to your S3 bucket for 30 days, and these attempted-to-deliver events will be subject to standard CloudTrail charges. To avoid charges on a misconfigured trail, you need to delete the trail.

CloudTrail captures actions made directly by the user or on behalf of the user by an AWS service. For example, an AWS CloudFormation `CreateStack` call can result in additional API calls to Amazon EC2, Amazon RDS, Amazon EBS, or other services as required by the AWS CloudFormation template. This behavior is normal and expected. You can identify if the action was taken by an AWS service with the `invokedby` field in the CloudTrail event.

The following table provides information about tasks you can perform on trails.

Task	Description
Logging management events	Configure your trails to log read-only, write-only, or all management events.

Task	Description
Log data events	You can use advanced event selectors to create fine-grained selectors to log only those data events of interest. For example, you can filter on the <code>eventName</code> field to include or exclude logging of specific API calls, which can help control costs. For more information, see Filtering data events by using advanced event selectors .
Log network activity events	Configure your trails to log network activity events. You can configure advanced event selectors to filter on the <code>eventName</code> , <code>errorCode</code> , and <code>vpcEndpointId</code> fields to log only those events of interest.
Log Insights events	Configure your trails to log Insights events to help you identify and respond to unusual activity associated with management API calls. Additional charges apply for Insights events. You will be charged separately if you enable Insights for both trails and event data stores. For more information, see AWS CloudTrail Pricing.
View Insights events	After you enable CloudTrail Insights on a trail, you can view up to 90 days of Insights events by using the CloudTrail console or the AWS CLI.
Download Insights events	After you enable CloudTrail Insights on a trail, you can download a CSV or JSON file containing up to the past 90 days of Insights events for your trail.

Task	Description
Copy trail events to CloudTrail Lake	You can copy existing trail events to a CloudTrail Lake event data store to create a point-in-time snapshot of events logged to the trail.
Create and subscribe to an Amazon SNS topic	Subscribe to a topic to receive notifications about log file delivery to your bucket. Amazon SNS can notify you in multiple ways, including programmatically with Amazon Simple Queue Service.  Note If you want to receive SNS notifications about log file deliveries from all Regions, specify only one SNS topic for your trail. If you want to programmatically process all events, see Using the CloudTrail Processing Library.
View your log files	Find and download your log files from the S3 bucket.
Monitor events with CloudWatch Logs	You can configure your trail to send events to CloudWatch Logs. You can then use CloudWatch Logs to monitor your account for specific API calls and events.  Note If you configure a multi-Region trail to send events to a CloudWatch Logs log group, CloudTrail sends events from all Regions to a single log group.

Task	Description
Enable SSE-KMS encryption	Encrypting your log files and digest files with a KMS key provides an extra layer of security for your CloudTrail data.
Enable log file integrity	Log file integrity validation helps you verify that log files have remained unchanged since CloudTrail delivered them.
Share log files with other AWS accounts	You can share log files between accounts.
Aggregate logs from multiple accounts	You can aggregate log files from multiple accounts to a single bucket.
Work with partner solutions	Analyze your CloudTrail output with a partner solution that integrates with CloudTrail. Partner solutions offer a broad set of capabilities, such as change tracking, troubleshooting, and security analysis.

You can deliver one copy of your ongoing management events to your S3 bucket at no charge from CloudTrail by creating a trail, however, there are Amazon S3 storage charges. For more information about CloudTrail pricing, see [AWS CloudTrail Pricing](#). For information about Amazon S3 pricing, see [Amazon S3 Pricing](#).

CloudTrail Insights events

AWS CloudTrail Insights help AWS users identify and respond to unusual activity associated with API call rates and API error rates by continuously analyzing CloudTrail management events. CloudTrail Insights analyzes your normal patterns of API call volume and API error rates, also called the *baseline*, and generates Insights events when the call volume or error rates are outside normal patterns. Insights events on API call rate are generated for write management APIs, and Insights events on API error rate are generated for both read and write management APIs.

By default, CloudTrail trails and event data stores don't log Insights events. You must configure your trail or event data store to log Insights events. For more information, see [Logging Insights events with the CloudTrail console](#) and [Logging Insights events with the AWS CLI](#).

Additional charges apply for Insights events. You will be charged separately if you enable Insights for both trails and event data stores. For more information, see [AWS CloudTrail Pricing](#).

Viewing Insights events for trails and event data stores

CloudTrail supports Insights events for both trails and event data stores, however, there are some differences in how you view and access Insights events.

Viewing Insights events for trails

If you have Insights events enabled on a trail, and CloudTrail detects unusual activity, Insights events are logged to a different folder or prefix in the destination S3 bucket for your trail. You can also see the type of insight and the incident time period when you view Insights events on the CloudTrail console. For more information, see [Viewing Insights events for trails with the console](#).

After you enable CloudTrail Insights for the first time on a trail, CloudTrail may take up to 36 hours to begin delivering Insights events after you enable Insights events on a trail, provided that unusual activity is detected during that time.

Viewing Insights events for event data stores

To log Insights events in CloudTrail Lake, you need a destination event data store that logs Insights events and a source event data store that enables Insights and logs management events. For more information, see [Create an event data store for Insights events with the console](#).

After you enable CloudTrail Insights for the first time on the source event data store, CloudTrail may take up to 7 days to begin delivering Insights events, provided that unusual activity is detected during that time.

If you have CloudTrail Insights enabled on a source event data store and CloudTrail detects unusual activity, CloudTrail delivers Insights events to your destination event data store. You can then query your destination event data store to get information about your Insights events and can optionally save the query results to an S3 bucket. For more information, see [Create or edit a query with the CloudTrail console](#) and [View sample queries with the CloudTrail console](#).

You can view the **Insights events** dashboard to visualize the Insights events in your destination event data store. For more information about Lake dashboards, see [CloudTrail Lake dashboards](#).

CloudTrail channels

CloudTrail supports two types of *channels*:

Channels for CloudTrail Lake integrations with event sources outside of AWS

CloudTrail Lake uses *channels* to bring events from outside of AWS into CloudTrail Lake from external partners that work with CloudTrail, or from your own sources. When you create a channel, you choose one or more event data stores to store events that arrive from the channel source. You can change the destination event data stores for a channel as needed, as long as the destination event data stores are set to log activity events. When you create a channel for events from an external partner, you provide a channel ARN to the partner or source application. The resource policy attached to the channel allows the source to transmit events through the channel. For more information, see [Create an integration with an event source outside of AWS](#) and [CreateChannel](#) in the *AWS CloudTrail API Reference*.

Service-linked channels

AWS services can create a service-linked channel to receive CloudTrail events on your behalf. The AWS service creating the service-linked channel configures advanced event selectors for the channel and specifies whether the channel applies to all Regions, or the current Region.

You can use the [CloudTrail console](#) or [AWS CLI](#) to view information about any CloudTrail service-linked channels created by AWS services.

CloudTrail concepts

This section summarizes basic concepts related to CloudTrail.

Concepts:

- [CloudTrail events](#)
- [Event history](#)
- [Trails](#)
- [Organization trails](#)
- [CloudTrail Lake and event data stores](#)
- [CloudTrail Insights](#)
- [Tags](#)
- [AWS Security Token Service and CloudTrail](#)
- [Global service events](#)

CloudTrail events

An event in CloudTrail is the record of an activity in an AWS account. This activity can be an action taken by an IAM identity, or service that is monitorable by CloudTrail. CloudTrail events provide a history of both API and non-API account activity made through the AWS Management Console, AWS SDKs, command line tools, and other AWS services.

CloudTrail log files aren't an ordered stack trace of the public API calls, so events don't appear in any specific order.

CloudTrail logs four types of events:

- [Management events](#)
- [Data events](#)
- [Network activity events](#)
- [Insights events](#)

All event types use a CloudTrail JSON log format.

By default, trails and event data stores log management events, but not data or Insights events.

For information about how AWS services integrate with CloudTrail, see [AWS service topics for CloudTrail](#).

Management events

Management events provide information about management operations that are performed on resources in your AWS account. These are also known as *control plane operations*.

Example management events include:

- Configuring security (for example, AWS Identity and Access Management AttachRolePolicy API operations).
- Registering devices (for example, Amazon EC2 CreateDefaultVpc API operations).
- Configuring rules for routing data (for example, Amazon EC2 CreateSubnet API operations).
- Setting up logging (for example, AWS CloudTrail CreateTrail API operations).

Management events can also include non-API events that occur in your account. For example, when a user signs in to your account, CloudTrail logs the `ConsoleLogin` event. For more information, see [Non-API events captured by CloudTrail](#).

By default, CloudTrail trails and CloudTrail Lake event data stores log management events. For more information about logging management events, see [Logging management events](#).

Data events

Data events provide information about the resource operations performed on or in a resource. These are also known as *data plane operations*. Data events are often high-volume activities.

Example data events include:

- [Amazon S3 object-level API activity](#) (for example, `GetObject`, `DeleteObject`, and `PutObject` API operations) on objects in S3 buckets.
- AWS Lambda function execution activity (the `Invoke` API).
- CloudTrail [PutAuditEvents](#) activity on a [CloudTrail Lake channel](#) that is used to log events from outside AWS.
- Amazon SNS [Publish](#) and [PublishBatch](#) API operations on topics.

The following table shows the resource types available for trails and event data stores.

The **Resource type (console)** column shows the appropriate selection in the console. The **resources.type value** column shows the `resources.type` value that you would specify to include data events of that type in your trail or event data store using the AWS CLI or CloudTrail APIs.

For trails, you can use basic or advanced event selectors to log data events for Amazon S3 objects in general purpose buckets, Lambda functions, and DynamoDB tables (shown in the first three rows of the table). You can use only advanced event selectors to log the resource types shown in the remaining rows.

For event data stores, you can use only advanced event selectors to include data events.

Data events supported by AWS CloudTrail

AWS service	Description	Resource type (console)	resources.type value
Amazon RDS	Amazon RDS API activity on a DB Cluster.	RDS Data API - DB Cluster	AWS::RDS::DBCluster
Amazon S3	Amazon S3 object-level API activity (for example, GetObject , DeleteObject , and PutObject API operations) on objects in general purpose buckets.	S3	AWS::S3::Object
Amazon S3	Amazon S3 API activity on access points.	S3 Access Point	AWS::S3::AccessPoint
Amazon S3	Amazon S3 object-level API activity (for example, GetObject , DeleteObject , and PutObject API operations) on objects in directory buckets.	S3 Express	AWS::S3Express::Object
Amazon S3	Amazon S3 Object Lambda access points API activity , such as calls to CompleteM	S3 Object Lambda	AWS::S3ObjectLambda::Access Point

AWS service	Description	Resource type (console)	resources.type value
	multipartUpload and GetObject .		
Amazon S3	Amazon FSx API activity on volumes.	FSx Volume	AWS::FSx::Volume
Amazon S3 Tables	Amazon S3 API activity on tables .	S3 table	AWS::S3Tables::Table
Amazon S3 Tables	Amazon S3 API activity on table buckets .	S3 table bucket	AWS::S3Tables::TableBucket
Amazon S3 Vectors	Amazon S3 API activity on vector buckets .	S3 vector bucket	AWS::S3Vectors::VectorBucket
Amazon S3 Vectors	Amazon S3 API activity on vector indexes .	S3 vector index	AWS::S3Vectors::Index
Amazon S3 on Outposts	Amazon S3 on Outposts object-level API activity .	S3 Outposts	AWS::S3Outposts::Object
Amazon SNS	Amazon SNS Publish API operations on platform endpoints.	SNS platform endpoint	AWS::SNS::PlatformEndpoint
Amazon SNS	Amazon SNS Publish and PublishBatch API operations on topics.	SNS topic	AWS::SNS::Topic

AWS service	Description	Resource type (console)	resources.type value
Amazon SQS	Amazon SQS API activity on messages.	SQS	AWS::SQS::Queue
AWS Supply Chain	AWS Supply Chain API activity on an instance.	Supply Chain	AWS::SCN::Instance
Amazon SWF	Amazon SWF API activity on domains .	SWF domain	AWS::SWF::Domain
AWS AppConfig	AWS AppConfig API activity for configuration operations such as calls to StartConfigurationSession and GetLatestConfiguration .	AWS AppConfig	AWS::AppConfig::Configuration
AWS AppSync	AWS AppSync API activity on AppSync GraphQL APIs.	AppSync GraphQL	AWS::AppSync::GraphQLApi
Amazon Aurora DSQL	Amazon Aurora DSQL API activity on cluster resources.	Amazon Aurora DSQL	AWS::DSQL::Cluster

AWS service	Description	Resource type (console)	resources.type value
AWS B2B Data Interchange	B2B Data Interchange API activity for Transformer operations such as calls to <code>GetTransformerJob</code> and <code>StartTransformerJob</code> .	B2B Data Interchange	<code>AWS::B2BI::Transformer</code>
AWS Backup	AWS Backup Search Data API activity on search jobs.	AWS Backup Search Data APIs	<code>AWS::Backup::SearchJob</code>
Amazon Bedrock	Amazon Bedrock API activity on an agent alias.	Bedrock agent alias	<code>AWS::Bedrock::AgentAlias</code>
Amazon Bedrock	Amazon Bedrock API activity on async invocations.	Bedrock async invoke	<code>AWS::Bedrock::AsyncInvoke</code>
Amazon Bedrock	Amazon Bedrock API activity on a flow alias.	Bedrock flow alias	<code>AWS::Bedrock::FlowAlias</code>
Amazon Bedrock	Amazon Bedrock API activity on guardrails.	Bedrock guardrail	<code>AWS::Bedrock::Guardrail</code>
Amazon Bedrock	Amazon Bedrock API activity on inline agents.	Bedrock Invoke Inline-Agent	<code>AWS::Bedrock::InlineAgent</code>

AWS service	Description	Resource type (console)	resources.type value
Amazon Bedrock	Amazon Bedrock API activity on a knowledge base.	Bedrock knowledge base	AWS::Bedrock::KnowledgeBase
Amazon Bedrock	Amazon Bedrock API activity on models.	Bedrock model	AWS::Bedrock::Model
Amazon Bedrock	Amazon Bedrock API activity on prompts.	Bedrock prompt	AWS::Bedrock::PromptVersion
Amazon Bedrock	Amazon Bedrock API activity on sessions.	Bedrock session	AWS::Bedrock::Session
Amazon Bedrock	Amazon Bedrock API activity on flow executions.	Bedrock flow execution	AWS::Bedrock::FlowExecution
Amazon Bedrock	Amazon Bedrock API activity on an automated reasoning policy.	Bedrock automated reasoning policy	AWS::Bedrock::AutomatedReasoningPolicy
Amazon Bedrock	Amazon Bedrock API activity on an automated reasoning policy version.	Bedrock automated reasoning policy version	AWS::Bedrock::AutomatedReasoningPolicyVersion
Amazon Bedrock	Amazon Bedrock data automation project API activity.	Bedrock Data Automation project	AWS::Bedrock::DataAutomationProject

AWS service	Description	Resource type (console)	resources.type value
Amazon Bedrock	Bedrock data automation invocation API activity.	Bedrock Data Automation invocation	AWS::Bedrock::DataAutomationInvocation
Amazon Bedrock	Amazon Bedrock data automation profile API activity.	Bedrock Data Automation profile	AWS::Bedrock::DataAutomationProfile
Amazon Bedrock	Amazon Bedrock blueprint API activity.	Bedrock blueprint	AWS::Bedrock::Blueprint
Amazon Bedrock	Amazon Bedrock Code-Interpreter API activity.	Bedrock-AgentCore Code-Interpreter	AWS::BedrockAgentCore::CodeInterpreter
Amazon Bedrock	Amazon Bedrock Browser API activity.	Bedrock-AgentCore Browser	AWS::BedrockAgentCore::Browser
Amazon Bedrock	Amazon Bedrock Workload Identity API activity.	Bedrock-AgentCore Workload Identity	AWS::BedrockAgentCore::WorkloadIdentity
Amazon Bedrock	Amazon Bedrock Workload Identity Directory API activity.	Bedrock-AgentCore Workload Identity Directory	AWS::BedrockAgentCore::WorkloadIdentityDirectory

AWS service	Description	Resource type (console)	resources.type value
Amazon Bedrock	Amazon Bedrock Token Vault API activity.	Bedrock-AgentCore Token Vault	AWS::BedrockAgentCore::TokenVault
Amazon Bedrock	Amazon Bedrock APIKey CredentialProvider API activity.	Bedrock-AgentCore APIKey CredentialProvider	AWS::BedrockAgentCore::APIKeyCredentialProvider
Amazon Bedrock	Amazon Bedrock Runtime API activity.	Bedrock-AgentCore Runtime	AWS::BedrockAgentCore::Runtime
Amazon Bedrock	Amazon Bedrock Runtime-Endpoint API activity.	Bedrock-AgentCore Runtime-Endpoint	AWS::BedrockAgentCore::RuntimeEndpoint
Amazon Bedrock	Amazon Bedrock Gateway API activity.	Bedrock-AgentCore Gateway	AWS::BedrockAgentCore::Gateway
Amazon Bedrock	Amazon Bedrock Memory API activity.	Bedrock-AgentCore Memory	AWS::BedrockAgentCore::Memory
Amazon Bedrock	Amazon Bedrock OAuth2 CredentialProvider API activity.	Bedrock-AgentCore OAuth2 CredentialProvider	AWS::BedrockAgentCore::OAuth2CredentialProvider

AWS service	Description	Resource type (console)	resources.type value
Amazon Bedrock	Amazon Bedrock Browser-Custom API activity.	Bedrock-AgentCore-Browser-Custom	AWS::BedrockAgentCore::BrowserCustom
Amazon Bedrock	Amazon Bedrock Code-Interpreter-Custom API activity.	Bedrock-AgentCore-Code-Interpreter-Custom	AWS::BedrockAgentCore::CodeInterpreterCustom
Amazon Bedrock	Amazon Bedrock Tool API activity.	Bedrock Tool	AWS::Bedrock::Tool
AWS Cloud Map	AWS Cloud Map API activity on a namespace .	AWS Cloud Map namespace	AWS::ServiceDiscovery::Namespace
AWS Cloud Map	AWS Cloud Map API activity on a service .	AWS Cloud Map service	AWS::ServiceDiscovery::Service
Amazon CloudFront	CloudFront API activity on a KeyValueStore .	CloudFront KeyValueStore	AWS::CloudFront::KeyValueStore
AWS CloudTrail	CloudTrail PutAuditEvents activity on a CloudTrail Lake channel that is used to log events from outside AWS.	CloudTrail channel	AWS::CloudTrail::Channel

AWS service	Description	Resource type (console)	resources.type value
Amazon CloudWatch	Amazon CloudWatch API activity on metrics.	CloudWatch metric	AWS::CloudWatch::Metric
Amazon CloudWatch Network Flow Monitor	Amazon CloudWatch Network Flow Monitor API activity on monitors.	Network Flow Monitor monitor	AWS::NetworkFlowMonitor::Monitor
Amazon CloudWatch Network Flow Monitor	Amazon CloudWatch Network Flow Monitor API activity on scopes.	Network Flow Monitor scope	AWS::NetworkFlowMonitor::Scope
Amazon CloudWatch RUM	Amazon CloudWatch RUM API activity on app monitors.	RUM app monitor	AWS::RUM::AppMonitor
Amazon CodeGuru Profiler	CodeGuru Profiler API activity on profiling groups.	CodeGuru Profiler profiling group	AWS::CodeGuruProfiler::ProfilingGroup
Amazon CodeWhisperer	Amazon CodeWhisperer API activity on a customization.	CodeWhisperer customization	AWS::CodeWhisperer::Customization
Amazon CodeWhisperer	Amazon CodeWhisperer API activity on a profile.	CodeWhisperer	AWS::CodeWhisperer::Profile

AWS service	Description	Resource type (console)	resources.type value
Amazon Cognito	Amazon Cognito API activity on Amazon Cognito identity pools .	Cognito Identity Pools	AWS::Cognito::IdentityPool
AWS Data Exchange	AWS Data Exchange API activity on assets.	Data Exchange asset	AWS::DataExchange::Asset
Amazon Data Firehose	Amazon Data Firehose delivery stream API activity.	Amazon Data Firehose	AWS::KinesisFirehose::DeliveryStream
AWS Deadline Cloud	Deadline Cloud API activity on fleets.	Deadline Cloud fleet	AWS::Deadline::Fleet
AWS Deadline Cloud	Deadline Cloud API activity on jobs.	Deadline Cloud job	AWS::Deadline::Job
AWS Deadline Cloud	Deadline Cloud API activity on queues.	Deadline Cloud queue	AWS::Deadline::Queue
AWS Deadline Cloud	Deadline Cloud API activity on workers.	Deadline Cloud worker	AWS::Deadline::Worker

AWS service	Description	Resource type (console)	resources.type value
Amazon DynamoDB	Amazon DynamoDB item-level API activity on tables (for example, PutItem, DeleteItem , and UpdateItem API operations).  Note For tables with streams enabled, the resources field in the data event contains both AWS::DynamoDB::Stream and AWS::DynamoDB::Table . If you specify AWS::DynamoDB::Table for the resources .type , it will log both DynamoDB table and DynamoDB	DynamoDB	AWS::DynamoDB::Table

AWS service	Description	Resource type (console)	resources.type value
	streams events by default. To exclude streams events , add a filter on the eventName field.		
Amazon DynamoDB	Amazon DynamoDB API activity on streams.	DynamoDB Streams	AWS::DynamoDB::Stream
Amazon Elastic Block Store	Amazon Elastic Block Store (EBS) direct APIs, such as PutSnapshotBlock , GetSnapshotBlock , and ListChangedBlocks on Amazon EBS snapshots.	Amazon EBS direct APIs	AWS::EC2::Snapshot
Amazon Elastic Compute Cloud	Amazon EC2 instance connect endpoint API activity.	EC2 instance connect endpoint	AWS::EC2::InstanceConnectEndpoint

AWS service	Description	Resource type (console)	resources.type value
Amazon Elastic Container Service	Amazon Elastic Container Service API activity on a container instance.	ECS container instance	AWS::ECS::ContainerInstance
Amazon Elastic Kubernetes Service	Amazon Elastic Kubernetes Service API activity on dashboards.	Amazon Elastic Kubernetes Service dashboard	AWS::EKS::Dashboard
Amazon EMR	Amazon EMR API activity on a write-ahead log workspace.	EMR write-ahead log workspace	AWS::EMRWAL::Workspace
AWS End User Messaging SMS	AWS End User Messaging SMS API activity on originations on identities.	SMS Voice origination identity	AWS::SMSVoice::OriginationIdentity
AWS End User Messaging SMS	AWS End User Messaging SMS API activity on messages.	SMS Voice message	AWS::SMSVoice::Message
AWS End User Messaging Social	AWS End User Messaging Social API activity on phone number IDs.	Social-Messaging Phone Number Id	AWS::SocialMessaging::PhoneNumberId
AWS End User Messaging Social	AWS End User Messaging Social API activity on Waba IDs.	Social-Messaging Waba ID	AWS::SocialMessaging::WabaId

AWS service	Description	Resource type (console)	resources.type value
Amazon FinSpace	Amazon FinSpace API activity on environments.	FinSpace	AWS::FinSpace::Environment
Amazon GameLift Streams	Amazon GameLift Streams streaming API activity on applications.	GameLift Streams application	AWS::GameLiftStreams::Application
Amazon GameLift Streams	Amazon GameLift Streams streaming API activity on stream groups.	GameLift Streams stream group	AWS::GameLiftStreams::StreamGroup
AWS Glue	AWS Glue API activity on tables that were created by Lake Formation.	Lake Formation	AWS::Glue::Table
Amazon GuardDuty	Amazon GuardDuty API activity for a detector .	GuardDuty detector	AWS::GuardDuty::Detector
AWS HealthImaging	AWS HealthImaging API activity on data stores.	MedicalImaging data store	AWS::MedicalImaging::Datastore
AWS HealthImaging	AWS HealthImaging image set API activity.	MedicalImaging image set	AWS::MedicalImaging::ImageSet
AWS IoT	AWS IoT API activity on certificates .	IoT certificate	AWS::IoT::Certificate

AWS service	Description	Resource type (console)	resources.type value
AWS IoT	AWS IoT API activity on things .	IoT thing	AWS::IoT::Thing
AWS IoT Greengrass Version 2	Greengrass API activity from a Greengrass core device on a component version.  Note Greengrass doesn't log access denied events.	IoT Greengrass component version	AWS::GreengrassV2::ComponentVersion
AWS IoT Greengrass Version 2	Greengrass API activity from a Greengrass core device on a deployment.  Note Greengrass doesn't log access denied events.	IoT Greengrass deployment	AWS::GreengrassV2::Deployment
AWS IoT SiteWise	IoT SiteWise API activity on assets .	IoT SiteWise asset	AWS::IoTSiteWise::Asset

AWS service	Description	Resource type (console)	resources.type value
AWS IoT SiteWise	IoT SiteWise API activity on time series .	IoT SiteWise time series	AWS::IoTSiteWise::TimeSeries
AWS IoT SiteWise Assistant	Sitewise Assistant API activity on conversations.	Sitewise Assistant conversation	AWS::SitewiseAssistant::Conversation
AWS IoT TwinMaker	IoT TwinMaker API activity on an entity .	IoT TwinMaker entity	AWS::IoTTwinMaker::Entity
AWS IoT TwinMaker	IoT TwinMaker API activity on a workspace .	IoT TwinMaker workspace	AWS::IoTTwinMaker::Workspace
Amazon Kendra Intelligent Ranking	Amazon Kendra Intelligent Ranking API activity on rescore execution plans .	Kendra Ranking	AWS::KendraRanking::ExecutionPlan
Amazon Keyspaces (for Apache Cassandra)	Amazon Keyspaces API activity on a table.	Cassandra table	AWS::Cassandra::Table
Amazon Keyspaces (for Apache Cassandra)	Amazon Keyspaces (for Apache Cassandra) API activity on Cassandra CDC streams.	Cassandra CDC streams	AWS::Cassandra::Stream

AWS service	Description	Resource type (console)	resources.type value
Amazon Kinesis Data Streams	Kinesis Data Streams API activity on streams .	Kinesis stream	AWS::Kinesis::Stream
Amazon Kinesis Data Streams	Kinesis Data Streams API activity on stream consumers .	Kinesis stream consumer	AWS::Kinesis::StreamConsumer
Amazon Kinesis Video Streams	Kinesis Video Streams API activity on video streams, such as calls to GetMedia and PutMedia.	Kinesis video stream	AWS::KinesisVideo::Stream
Amazon Kinesis Video Streams	Kinesis Video Streams video signaling channel API activity.	Kinesis video signaling channel	AWS::KinesisVideo::SignalingChannel
AWS Lambda	AWS Lambda function execution activity (the Invoke API).	Lambda	AWS::Lambda::Function
Amazon Location Maps	Amazon Location Maps API activity.	Geo Maps	AWS::GeoMaps::Provider
Amazon Location Places	Amazon Location Places API activity.	Geo Places	AWS::GeoPlaces::Provider
Amazon Location Routes	Amazon Location Routes API activity.	Geo Routes	AWS::GeoRoutes::Provider

AWS service	Description	Resource type (console)	resources.type value
Amazon Machine Learning	Machine Learning API activity on ML models.	Maching Learning MlModel	AWS::MachineLearning::MlModel
Amazon Managed Blockchain	Amazon Managed Blockchain API activity on a network.	Managed Blockchain network	AWS::ManagedBlockchain::Network
Amazon Managed Blockchain	Amazon Managed Blockchain JSON-RPC calls on Ethereum nodes, such as eth_getBalance or eth_getBlockByNumber .	Managed Blockchain	AWS::ManagedBlockchain::Node
Amazon Managed Blockchain Query	Amazon Managed Blockchain Query API activity.	Managed Blockchain Query	AWS::ManagedBlockchainQuery::QueryAPI
Amazon Managed Workflows for Apache Airflow	Amazon MWAA API activity on environments.	Managed Apache Airflow	AWS::MWAA::Environment
Amazon Neptune Graph	Data API activities, for example queries, algorithms, or vector search, on a Neptune Graph.	Neptune Graph	AWS::NeptuneGraph::Graph

AWS service	Description	Resource type (console)	resources.type value
Amazon One Enterprise	Amazon One Enterprise API activity on a UKey.	Amazon One UKey	AWS::One::UKey
Amazon One Enterprise	Amazon One Enterprise API activity on users.	Amazon One User	AWS::One::User
AWS Payment Cryptography	AWS Payment Cryptography API activity on aliases.	Payment Cryptography Alias	AWS::PaymentCryptography::Alias
AWS Payment Cryptography	AWS Payment Cryptography API activity on keys.	Payment Cryptography Key	AWS::PaymentCryptography::Key
Amazon Pinpoint	Amazon Pinpoint API activity on mobile targeting applications.	Mobile Targeting Application	AWS::Pinpoint::App
AWS Private CA	AWS Private CA Connector for Active Directory API activity.	AWS Private CA Connector for Active Directory	AWS::PCAConnectorAD::Connector
AWS Private CA	AWS Private CA Connector for SCEP API activity.	AWS Private CA Connector for SCEP	AWS::PCAConnectorSCEP::Connector

AWS service	Description	Resource type (console)	resources.type value
Amazon Q Apps	Data API activity on Amazon Q Apps .	Amazon Q Apps	AWS::QApps::QApp
Amazon Q Apps	Data API activity on Amazon Q App sessions.	Amazon Q App Session	AWS::QApps::QAppSession
Amazon Q Business	Amazon Q Business API activity on an application.	Amazon Q Business application	AWS::QBusiness::Application
Amazon Q Business	Amazon Q Business API activity on a data source.	Amazon Q Business data source	AWS::QBusiness::DataSource
Amazon Q Business	Amazon Q Business API activity on an index.	Amazon Q Business index	AWS::QBusiness::Index
Amazon Q Business	Amazon Q Business API activity on a web experience.	Amazon Q Business web experience	AWS::QBusiness::WebExperience
Amazon Q Business	Amazon Q Business integration API activity.	Amazon Q Business integration	AWS::QBusiness::Integration
Amazon Q Developer	Amazon Q Developer API activity on an integration.	Q Developer integration	AWS::QDeveloper::Integration

AWS service	Description	Resource type (console)	resources.type value
Amazon Q Developer	Amazon Q Developer API activity on operational investigations.	AI Ops Investigation Group	AWS::AIOps::InvestigationGroup
Amazon Quick Suite	Amazon Quick Suite API activity on an action connector.	AWS QuickSuite Actions	AWS::QuickSight::ActionConnector
Amazon Quick Suite	Amazon Quick Suite Flow API activity.	AWS::QuickSight::Flow	AWS::QuickSight::Flow
Amazon Quick Suite	Amazon Quick Suite FlowSession API activity.	AWS::QuickSight::FlowSession	AWS::QuickSight::FlowSession
Amazon SageMaker AI	Amazon SageMaker AI InvokeEndpointWithResponseStream activity on endpoints.	SageMaker AI endpoint	AWS::SageMaker::Endpoint
Amazon SageMaker AI	Amazon SageMaker AI API activity on feature stores.	SageMaker AI feature store	AWS::SageMaker::FeatureGroup
Amazon SageMaker AI	Amazon SageMaker AI API activity on experiment trial components .	SageMaker AI metrics experiment trial component	AWS::SageMaker::ExperimentTrialComponent

AWS service	Description	Resource type (console)	resources.type value
Amazon SageMaker AI;	Amazon SageMaker AI MLflow API activity.	SageMaker MLflow	AWS::SageMaker::MlflowTrackingServer
AWS Signer	Signer API activity on signing jobs.	Signer signing job	AWS::Signer::SigningJob
AWS Signer	Signer API activity on signing profiles.	Signer signing profile	AWS::Signer::SigningProfile
Amazon Simple Email Service	Amazon Simple Email Service (Amazon SES) API activity on configuration sets.	SES configuration set	AWS::SES::ConfigurationSet
Amazon Simple Email Service	Amazon Simple Email Service (Amazon SES) API activity on email identities.	SES identity	AWS::SES::EmailIdentity
Amazon Simple Email Service	Amazon Simple Email Service (Amazon SES) API activity on templates.	SES template	AWS::SES::Template
Amazon SimpleDB	Amazon SimpleDB API activity on domains.	SimpleDB domain	AWS::SDB::Domain
AWS Step Functions	Step Functions API activity on activities.	Step Functions	AWS::StepFunctions::Activity

AWS service	Description	Resource type (console)	resources.type value
AWS Step Functions	Step Functions API activity on state machines.	Step Functions state machine	AWS::StepFunctions::StateMachine
AWS Systems Manager	Systems Manager API activity on control channels.	Systems Manager	AWS::SSMMessages::ControlChannel
AWS Systems Manager	Systems Manager API activity on impact assessments.	SSM Impact Assessment	AWS::SSM::ExecutionPreview
AWS Systems Manager	Systems Manager API activity on managed nodes.	Systems Manager managed node	AWS::SSM::ManagedNode
Amazon Timestream	Amazon Timestream Query API activity on databases.	Timestream database	AWS::Timestream::Database
Amazon Timestream	Amazon Timestream API activity on regional endpoints.	Timestream regional endpoint	AWS::Timestream::RegionalEndpoint
Amazon Timestream	Amazon Timestream Query API activity on tables.	Timestream table	AWS::Timestream::Table
Amazon Verified Permissions	Amazon Verified Permissions API activity on a policy store.	Amazon Verified Permissions	AWS::VerifiedPermissions::PolicyStore

AWS service	Description	Resource type (console)	resources.type value
Amazon WorkSpaces Thin Client	WorkSpaces Thin Client API activity on a Device.	Thin Client Device	AWS::ThinClient::Device
Amazon WorkSpaces Thin Client	WorkSpaces Thin Client API activity on an Environment.	Thin Client Environment	AWS::ThinClient::Environment
AWS X-Ray	X-Ray API activity on traces .	X-Ray trace	AWS::XRay::Trace

Data events are not logged by default when you create a trail or event data store. To record CloudTrail data events, you must explicitly add each resource type for which you want to collect activity. For more information about logging data events, see [Logging data events](#).

Additional charges apply for logging data events. For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Network activity events

CloudTrail network activity events enable VPC endpoint owners to record AWS API calls made using their VPC endpoints from a private VPC to the AWS service. Network activity events provide visibility into the resource operations performed within a VPC.

You can log network activity events for the following services:

- AWS AppConfig
- AWS App Mesh
- Amazon Athena
- AWS B2B Data Interchange
- AWS Backup gateway
- Amazon Bedrock
- Billing and Cost Management

- [AWS Pricing Calculator](#)
- [AWS Cost Explorer](#)
- [AWS Cloud Control API](#)
- [AWS CloudHSM](#)
- [AWS Cloud Map](#)
- [AWS CloudFormation](#)
- [AWS CloudTrail](#)
- [Amazon CloudWatch](#)
- [CloudWatch Application Signals](#)
- [AWS CodeDeploy](#)
- [Amazon Comprehend Medical](#)
- [AWS Config](#)
- [AWS Data Exports](#)
- [Amazon Data Firehose](#)
- [AWS Directory Service](#)
- [Amazon DynamoDB](#)
- [Amazon EC2](#)
- [Amazon Elastic Container Service](#)
- [Amazon Elastic File System](#)
- [Elastic Load Balancing](#)
- [Amazon EventBridge](#)
- [Amazon EventBridge Scheduler](#)
- [Amazon Fraud Detector](#)
- [AWS Free Tier](#)
- [Amazon FSx](#)
- [AWS Glue](#)
- [AWS HealthLake](#)
- [AWS IoT FleetWise](#)
- [AWS IoT Secure Tunneling](#)

- AWS Invoicing
- Amazon Keyspaces (for Apache Cassandra)
- AWS KMS
- AWS Lake Formation
- AWS Lambda
- AWS License Manager
- Amazon Lookout for Equipment
- Amazon Lookout for Vision
- Amazon Personalize
- Amazon Q Business
- Amazon Rekognition
- Amazon Relational Database Service
- Amazon S3

 Note

Amazon S3 [Multi-Region Access Points](#) are not supported.

- Amazon SageMaker AI
- AWS Secrets Manager
- Amazon Simple Notification Service
- Amazon Simple Queue Service
- Amazon Simple Workflow Service
- AWS Storage Gateway
- AWS Systems Manager Incident Manager
- Amazon Textract
- Amazon Transcribe
- Amazon Translate
- AWS Transform
- Amazon Verified Permissions
- Amazon WorkMail

Network activity events are not logged by default when you create a trail or event data store. To record CloudTrail network activity events, you must explicitly set the event source for which you want to collect activity. For more information, see [Logging network activity events](#).

Additional charges apply for logging network activity events. For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Insights events

CloudTrail Insights events capture unusual API call rate or error rate activity in your AWS account by analyzing CloudTrail management activity. Insights events provide relevant information, such as the associated API, error code, incident time, and statistics, that help you understand and act on unusual activity. Unlike other types of events captured in a CloudTrail trail or event data store, Insights events are logged only when CloudTrail detects changes in your account's API usage or error rate logging that differ significantly from the account's typical usage patterns. For more information, see [Working with CloudTrail Insights](#).

Examples of activity that might generate Insights events include:

- Your account typically logs no more than 20 Amazon S3 deleteBucket API calls per minute, but your account starts to log an average of 100 deleteBucket API calls per minute. An Insights event is logged at the start of the unusual activity, and another Insights event is logged to mark the end of the unusual activity.
- Your account typically logs 20 calls per minute to the Amazon EC2 AuthorizeSecurityGroupIngress API, but your account starts to log zero calls to AuthorizeSecurityGroupIngress. An Insights event is logged at the start of the unusual activity, and ten minutes later, when the unusual activity ends, another Insights event is logged to mark the end of the unusual activity.
- Your account typically logs less than one AccessDeniedException error in a seven-day period on the AWS Identity and Access Management API, DeleteInstanceProfile. Your account starts to log an average of 12 AccessDeniedException errors per minute on the DeleteInstanceProfile API call. An Insights event is logged at the start of the unusual error rate activity, and another Insights event is logged to mark the end of the unusual activity.

These examples are provided for illustration purposes only. Your results may vary depending on your use case.

To log CloudTrail Insights events, you must explicitly enable Insights events on a new or existing trail or event data store. For more information about creating a trail, see [Creating a trail with the CloudTrail console](#). For more information about creating an event data store, see [Create an event data store for Insights events with the console](#).

Additional charges apply for Insights events. You will be charged separately if you enable Insights for both trails and event data stores. For more information, see [AWS CloudTrail Pricing](#).

Event history

CloudTrail event history provides a viewable, searchable, downloadable, and immutable record of the past 90 days of CloudTrail management events in an AWS Region. You can use this history to gain visibility into actions taken in your AWS account in the AWS Management Console, AWS SDKs, command line tools, and other AWS services. You can customize your view of event history in the CloudTrail console by selecting which columns are displayed. For more information, see [Working with CloudTrail event history](#).

Trails

A trail is a configuration that enables delivery of CloudTrail events to an S3 bucket, with optional delivery to [CloudWatch Logs](#) and [Amazon EventBridge](#). You can use a trail to choose the CloudTrail events you want delivered, encrypt your CloudTrail event log files with an AWS KMS key, and set up Amazon SNS notifications for log file delivery. For more information about how to create and manage a trail, see [Creating a trail for your AWS account](#).

Multi-Region and single-Region trails

You can create both multi-Region and single-Region trails for your AWS account.

Multi-Region trails

When you create a multi-Region trail, CloudTrail records events in all AWS Regions that are [enabled](#) in your AWS account and delivers the CloudTrail event log files to an S3 bucket that you specify. As a best practice, we recommend creating a multi-Region trail because it captures activity in all enabled Regions. All trails created using the CloudTrail console are multi-Region trails. You can convert a single-Region trail to a multi-Region trail by using the AWS CLI. For more information, see [Understanding multi-Region trails and opt-in Regions](#), [Creating a trail with the console](#), and [Converting a single-Region trail to a multi-Region trail](#).

Single-Region trails

When you create a single-Region trail, CloudTrail records the events in that Region only. It then delivers the CloudTrail event log files to an Amazon S3 bucket that you specify. You can only create a single-Region trail by using the AWS CLI. If you create additional single trails, you can have those trails deliver CloudTrail event log files to the same S3 bucket or to separate buckets. This is the default option when you create a trail using the AWS CLI or the CloudTrail API. For more information, see [Creating, updating, and managing trails with the AWS CLI](#).

Note

For both types of trails, you can specify an Amazon S3 bucket from any Region.

A multi-Region trail has the following advantages:

- The configuration settings for the trail apply consistently across all [enabled](#) AWS Regions.
- You receive CloudTrail events from all enabled AWS Regions in a single Amazon S3 bucket and, optionally, in a CloudWatch Logs log group.
- You manage trail configurations for all enabled AWS Regions from one location.

Creating a multi-Region trail, has the following effects:

- CloudTrail delivers log files for account activity from all [enabled](#) AWS Regions to the single Amazon S3 bucket that you specify, and, optionally, to a CloudWatch Logs log group.
- If you configured an Amazon SNS topic for the trail, SNS notifications about log file deliveries in all enabled AWS Regions are sent to that single SNS topic.
- You can see the multi-Region trail in all enabled AWS Regions, but you can only modify the trail in the home Region where it was created.

Regardless of whether a trail is multi-Region or single-Region, events sent to Amazon EventBridge are received in each Region's [event bus](#), rather than in one single event bus.

Multiple trails per Region

If you have different but related user groups, such as developers, security personnel, and IT auditors, you can create multiple trails per Region. This allows each group to receive its own copy of the log files.

CloudTrail supports five trails per Region. A multi-Region trail counts as one trail per Region.

The following is an example of a Region with five trails:

- You create two trails in the US West (N. California) Region that apply to this Region only.
- You create two more multi-Region trails in US West (N. California) Region.
- You create another multi-Region trail in the Asia Pacific (Sydney) Region. This trail also exists as a trail in the US West (N. California) Region.

You can view a list of trails in an AWS Region in the **Trails** page of the CloudTrail console. For more information, see [Updating a trail with the CloudTrail console](#). For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Organization trails

An organization trail is a configuration that enables delivery of CloudTrail events in the management account and all member accounts in an AWS Organizations organization to the same Amazon S3 bucket, CloudWatch Logs, and Amazon EventBridge. Creating an organization trail helps you define a uniform event logging strategy for your organization.

All organization trails created using the console are multi-Region organization trails that log events from the [enabled](#) AWS Regions in each member account in the organization. To log events in all AWS partitions in your organization, create a multi-Region organization trail in each partition. You can create either a single-Region or multi-Region organization trail by using the AWS CLI. If you create a single-Region trail, you log activity only in the trail's AWS Region (also referred to as the *Home Region*).

Although most AWS Regions are enabled by default for your AWS account, you must manually enable certain Regions (also referred to as *opt-in Regions*). For information about which Regions are enabled by default, see [Considerations before enabling and disabling Regions](#) in the *AWS Account Management Reference Guide*. For the list of Regions CloudTrail supports, see [CloudTrail supported Regions](#).

When you create an organization trail, a copy of the trail with the name that you give it is created in the member accounts that belongs to your organization.

- If the organization trail is for a **single-Region** and the trail's home Region is **not an opt-in Region**, a copy of the trail is created in the organization trail's home Region in each member account.
- If the organization trail is for a **single-Region** and the trail's home Region is **an opt-in Region**, a copy of the trail is created in the organization trail's home Region in the member accounts that have enabled that Region.
- If the organization trail is **multi-Region** and the trail's home Region is **not an opt-in Region**, a copy of the trail is created in each enabled AWS Region in each member account. When a member account enables an opt-in Region, a copy of the multi-Region trail is created in the newly opted in Region for the member account after activation of that Region is complete.
- If the organization trail is **multi-Region** and the home Region is **an opt-in Region**, member accounts will not send activity to the organization trail unless they opt into the AWS Region where the multi-Region trail was created. For example, if you create a multi-Region trail and choose the Europe (Spain) Region as the home Region for the trail, only member accounts that enabled the Europe (Spain) Region for their account will send their account activity to the organization trail.

Note

CloudTrail creates organization trails in member accounts even if a resource validation fails. Examples of validation failures include:

- an incorrect Amazon S3 bucket policy
- an incorrect Amazon SNS topic policy
- inability to deliver to a CloudWatch Logs log group
- insufficient permission to encrypt using a KMS key

A member account with CloudTrail permissions can see any validation failures for an organization trail by viewing the trail's details page on the CloudTrail console, or by running the AWS CLI [get-trail-status](#) command.

Users with CloudTrail permissions in member accounts will be able to see organization trails (including the trail ARN) when they log into the CloudTrail console from their AWS accounts, or when they run AWS CLI commands such as `describe-trails` (although member accounts must use the ARN for the organization trail, and not the name, when using the AWS CLI). However, users in member accounts will not have sufficient permissions to delete organization trails, turn logging on or off, change what types of events are logged, or otherwise alter organization trails in any way. For more information about AWS Organizations, see [Organizations Terminology and Concepts](#). For more information about creating and working with organization trails, see [Creating a trail for an organization](#).

CloudTrail Lake and event data stores

CloudTrail Lake lets you run fine-grained SQL-based queries on your events, and log events from sources outside AWS, including from your own applications, and from partners who are integrated with CloudTrail. You do not need to have a trail configured in your account to use CloudTrail Lake.

Events are aggregated into event data stores, which are immutable collections of events based on criteria that you select by applying [advanced event selectors](#). You can keep the event data in an event data store for up to 3,653 days (about 10 years) if you choose the **One-year extendable retention pricing** option, or up to 2,557 days (about 7 years) if you choose the **Seven-year retention pricing** option. You can save Lake queries for future use, and view results of queries for up to seven days. You can also save query results to an S3 bucket. CloudTrail Lake can also store events from an organization in AWS Organizations in an event data store, or events from multiple Regions and accounts. CloudTrail Lake is part of an auditing solution that helps you perform security investigations and troubleshooting. For more information, see [Working with AWS CloudTrail Lake](#) and [CloudTrail Lake concepts and terminology](#).

CloudTrail Insights

CloudTrail Insights help AWS users identify and respond to unusual volumes of API calls or errors logged on API calls by continuously analyzing CloudTrail management events. An Insights event is a record of unusual levels of `write` management API activity, or unusual levels of errors returned on management API activity. By default, trails and event data stores don't log CloudTrail Insights events. In the console, you can choose to log Insights events when you create or update a trail or event data store. When you use the CloudTrail API, you can log Insights events by editing the settings of an existing trail or event data store with the [PutInsightSelectors](#) API. Additional charges apply for logging CloudTrail Insights events. You will be charged separately if you enable

Insights for both trails and event data stores. For more information, see [Working with CloudTrail Insights](#) and [AWS CloudTrail Pricing](#).

Tags

A tag is a customer-defined key and optional value that can be assigned to AWS resources, such as CloudTrail trails, event data stores, and channels, S3 buckets used to store CloudTrail log files, AWS Organizations organizations and organizational units, and many more. By adding the same tags to trails and to the S3 buckets you use to store log files for trails, you can make it easier to manage, search for, and filter these resources with [AWS Resource Groups](#). You can implement tagging strategies to help you consistently, effectively, and easily find and manage your resources. For more information, see [Best Practices for Tagging AWS Resources](#).

AWS Security Token Service and CloudTrail

AWS Security Token Service (AWS STS) is a service that has a global endpoint and also supports Region-specific endpoints. An endpoint is a URL that is the entry point for web service requests. For example, `https://cloudtrail.us-west-2.amazonaws.com` is the US West (Oregon) regional entry point for the AWS CloudTrail service. Regional endpoints help reduce latency in your applications.

When you use an AWS STS Region-specific endpoint, the trail in that Region delivers only the AWS STS events that occur in that Region. For example, if you are using the endpoint `sts.us-west-2.amazonaws.com`, the trail in us-west-2 delivers only the AWS STS events that originate from us-west-2. For more information about AWS STS regional endpoints, see [Activating and Deactivating AWS STS in an AWS Region](#) in the *IAM User Guide*.

For a complete list of AWS regional endpoints, see [AWS Regions and Endpoints](#) in the *AWS General Reference*. For details about events from the global AWS STS endpoint, see [Global service events](#).

Global service events

Important

As of November 22, 2021, AWS CloudTrail changed how trails capture global service events. Now, events created by Amazon CloudFront, AWS Identity and Access Management, and AWS STS are recorded in the Region in which they were created, the US East (N. Virginia) Region, us-east-1. This makes how CloudTrail treats these services consistent with that of

other AWS global services. To continue receiving global service events outside of US East (N. Virginia), be sure to convert *single-Region trails* using global service events outside of US East (N. Virginia) into *multi-Region trails*. For more information about capturing global service events, see [Enabling and disabling global service event logging](#) later in this section. In contrast, the **Event history** in the CloudTrail console and the **aws cloudtrail lookup-events** command will show these events in the AWS Region where they occurred.

For most services, events are recorded in the Region where the action occurred. For global services such as AWS Identity and Access Management (IAM), AWS STS, and Amazon CloudFront, events are delivered to any trail that includes global services.

For most global services, events are logged as occurring in US East (N. Virginia) Region, but some global service events are logged as occurring in other Regions, such as US East (Ohio) Region or US West (Oregon) Region.

To avoid receiving duplicate global service events, remember the following:

- Global service events are delivered by default to trails that are created using the CloudTrail console. Events are delivered to the bucket for the trail.
- If you have multiple single Region trails, consider configuring your trails so that global service events are delivered in only one of the trails. For more information, see [Enabling and disabling global service event logging](#).
- If you convert a multi-Region trail to a single-Region trail, global service event logging is turned off automatically for that trail. Similarly, if you convert a single-Region trail to a multi-Region trail, global service event logging is turned on automatically for that trail.

For more information about changing global service event logging for a trail, see [Enabling and disabling global service event logging](#).

Example:

1. You create a trail in the CloudTrail console. By default, this trail logs global service events.
2. You have multiple single Region trails.
3. You do not need to include global services for the single Region trails. Global service events are delivered for the first trail. For more information, see [Creating, updating, and managing trails with the AWS CLI](#).

Note

When you create or update a trail with the AWS CLI, AWS SDKs, or CloudTrail API, you can specify whether to include or exclude global service events for trails. You cannot configure global service event logging from the CloudTrail console.

CloudTrail supported Regions

Note

For information about Regions supported by CloudTrail Lake, see [CloudTrail Lake supported Regions](#).

For information about data plane endpoints, see [Data plane endpoints](#) in the *AWS General Reference*.

Region name	Region	Control plane endpoint	Protocol	Support date
US East (N. Virginia)	us-east-1	cloudtrail.us-east-1.amazonaws.com	HTTPS	11/13/2013
US East (Ohio)	us-east-2	cloudtrail.us-east-2.amazonaws.com	HTTPS	10/17/2016
US West (N. California)	us-west-1	cloudtrail.us-west-1.amazonaws.com	HTTPS	05/13/2014
US West (Oregon)	us-west-2	cloudtrail.us-west-2.amazonaws.com	HTTPS	11/13/2013
Africa (Cape Town)	af-south-1	cloudtrail.af-south-1.amazonaws.com	HTTPS	04/22/2020
Asia Pacific (Hong Kong)	ap-east-1	cloudtrail.ap-east-1.amazonaws.com	HTTPS	04/24/2019

Region name	Region	Control plane endpoint	Protocol	Support date
Asia Pacific (Hyderabad)	ap-south-2	cloudtrail.ap-south-2.amazonaws.com	HTTPS	11/22/2022
Asia Pacific (Jakarta)	ap-southeast-3	cloudtrail.ap-southeast-3.amazonaws.com	HTTPS	12/13/2021
Asia Pacific (Malaysia)	ap-southeast-5	cloudtrail.ap-southeast-5.amazonaws.com	HTTPS	08/22/2024
Asia Pacific (Melbourne)	ap-southeast-4	cloudtrail.ap-southeast-4.amazonaws.com	HTTPS	01/23/2023
Asia Pacific (Mumbai)	ap-south-1	cloudtrail.ap-south-1.amazonaws.com	HTTPS	06/27/2016
Asia Pacific (Osaka)	ap-northeast-3	cloudtrail.ap-northeast-3.amazonaws.com	HTTPS	02/12/2018
Asia Pacific (Seoul)	ap-northeast-2	cloudtrail.ap-northeast-2.amazonaws.com	HTTPS	01/06/2016
Asia Pacific (Singapore)	ap-southeast-1	cloudtrail.ap-southeast-1.amazonaws.com	HTTPS	06/30/2014
Asia Pacific (Sydney)	ap-southeast-2	cloudtrail.ap-southeast-2.amazonaws.com	HTTPS	05/13/2014
Asia Pacific (Thailand)	ap-southeast-7	cloudtrail.ap-southeast-7.amazonaws.com	HTTPS	01/07/2025
Asia Pacific (Tokyo)	ap-northeast-1	cloudtrail.ap-northeast-1.amazonaws.com	HTTPS	06/30/2014
Canada (Central)	ca-central-1	cloudtrail.ca-central-1.amazonaws.com	HTTPS	12/08/2016

Region name	Region	Control plane endpoint	Protocol	Support date
Canada West (Calgary)	ca-west-1	cloudtrail.ca-west-1.amazonaws.com	HTTPS	12/20/2023
China (Beijing)	cn-north-1	cloudtrail.cn-north-1.amazonaws.com.cn	HTTPS	03/01/2014
China (Ningxia)	cn-northwest-1	cloudtrail.cn-northwest-1.amazonaws.com.cn	HTTPS	12/11/2017
Europe (Frankfurt)	eu-central-1	cloudtrail.eu-central-1.amazonaws.com	HTTPS	10/23/2014
Europe (Ireland)	eu-west-1	cloudtrail.eu-west-1.amazonaws.com	HTTPS	05/13/2014
Europe (London)	eu-west-2	cloudtrail.eu-west-2.amazonaws.com	HTTPS	12/13/2016
Europe (Milan)	eu-south-1	cloudtrail.eu-south-1.amazonaws.com	HTTPS	04/27/2020
Europe (Paris)	eu-west-3	cloudtrail.eu-west-3.amazonaws.com	HTTPS	12/18/2017
Europe (Spain)	eu-south-2	cloudtrail.eu-south-2.amazonaws.com	HTTPS	11/16/2022
Europe (Stockholm)	eu-north-1	cloudtrail.eu-north-1.amazonaws.com	HTTPS	12/11/2018
Europe (Zurich)	eu-central-2	cloudtrail.eu-central-2.amazonaws.com	HTTPS	11/09/2022
Israel (Tel Aviv)	il-central-1	cloudtrail.il-central-1.amazonaws.com	HTTPS	07/31/2023

Region name	Region	Control plane endpoint	Protocol	Support date
Mexico (Central)	mx-central-1	cloudtrail.mx-central-1.amazonaws.com	HTTPS	01/13/2025
Middle East (Bahrain)	me-south-1	cloudtrail.me-south-1.amazonaws.com	HTTPS	07/29/2019
Middle East (UAE)	me-central-1	cloudtrail.me-central-1.amazonaws.com	HTTPS	08/30/2022
South America (São Paulo)	sa-east-1	cloudtrail.sa-east-1.amazonaws.com	HTTPS	06/30/2014
AWS GovCloud (US-East)	us-gov-east-1	cloudtrail.us-gov-east-1.amazonaws.com	HTTPS	11/12/2018
AWS GovCloud (US-West)	us-gov-west-1	cloudtrail.us-gov-west-1.amazonaws.com	HTTPS	08/16/2011

For more information about using CloudTrail in the AWS GovCloud (US) Regions, see [Service Endpoints](#) in the *AWS GovCloud (US) User Guide*.

For more information about using CloudTrail in the China (Beijing) Region, see [Endpoints and ARNs for AWS in China](#) in the *Amazon Web Services General Reference*.

CloudTrail supported services and integrations

CloudTrail supports logging events for many AWS services. You can find the specifics for each supported service in that service's guide. For a list of service-specific topics, see [AWS service topics for CloudTrail](#). In addition, some AWS services can be used to analyze and act upon data collected in CloudTrail logs.

Note

To see the list of supported Regions for each service, see [Service endpoints and quotas](#) in the *Amazon Web Services General Reference*.

Topics

- [AWS service integrations with CloudTrail logs](#)
- [CloudTrail integration with Amazon EventBridge](#)
- [CloudTrail integration with AWS Organizations](#)
- [CloudTrail integration with AWS Control Tower](#)
- [CloudTrail integration with Amazon Security Lake](#)
- [CloudTrail Lake integration with Amazon Athena](#)
- [CloudTrail Lake integration with AWS Config](#)
- [CloudTrail Lake integration with AWS Audit Manager](#)
- [AWS service topics for CloudTrail](#)
- [CloudTrail unsupported services](#)

AWS service integrations with CloudTrail logs**Note**

You can also use CloudTrail Lake to query and analyze your events. CloudTrail Lake queries offer a deeper and more customizable view of events than simple key and value lookups in **Event history**, or running `LookupEvents`. CloudTrail Lake users can run complex Standard Query Language (SQL) queries across multiple fields in a CloudTrail event. For more information, see [Working with AWS CloudTrail Lake](#) and [Copying trail events to CloudTrail Lake](#).

CloudTrail Lake event data stores and queries incur CloudTrail charges. For more information about CloudTrail Lake pricing, see [AWS CloudTrail Pricing](#).

You can configure other AWS services to further analyze and act upon the event data collected in CloudTrail logs. For more information, see the following topics.

AWS Service	Topic	Description
Amazon Athena	Querying AWS CloudTrail Logs	Using Athena with CloudTrail logs is a powerful way to enhance your analysis of AWS service activity. For example, you can use queries to identify trends and further isolate activity by attribute, such as source IP address or user. You can automatically create tables for querying logs directly from the CloudTrail console, and use those tables to run queries in Athena. For more information, see Creating a Table for CloudTrail Logs in the CloudTrail Console in the Amazon Athena User Guide.  Note Running queries in Amazon Athena incurs additional costs. For more information, see Amazon Athena Pricing.
Amazon CloudWatch Logs	Monitoring CloudTrail Log Files with Amazon CloudWatch Logs	You can configure CloudTrail with CloudWatch Logs to monitor your trail logs and be notified when specific activity

AWS Service	Topic	Description
		occurs. For example, you can define CloudWatch Logs metric filters that will trigger CloudWatch alarms and send notifications to you when those alarms are triggered.  Note Standard pricing for Amazon CloudWatch and Amazon CloudWatch Logs applies. For more information, see Amazon CloudWatch Pricing.

CloudTrail integration with Amazon EventBridge

Amazon EventBridge is an AWS service that delivers a near real-time stream of system events that describe changes in AWS resources. In EventBridge, you can create rules that responds to events recorded by CloudTrail. For more information, see [Create a rule in Amazon EventBridge](#).

You can deliver events that you are subscribed to on your trail to EventBridge by creating a rule with the EventBridge console.

From the EventBridge console:

- Choose the `AWS API Call via CloudTrail` detail-type to deliver CloudTrail data and management events with an `eventType` of `AwsApiCall`. To record events with a detail-type value of `AWS API Call via CloudTrail`, you must have a trail that is currently logging management or data events.

- Choose the AWS Console Sign In via CloudTrail detail-type to deliver [AWS Management Console sign-in events](#). To record events with a detail-type of AWS Console Sign In via CloudTrail, you must have a trail that is currently logging management events.
- Choose the AWS Insight via CloudTrail detail-type to deliver Insights events. To record events with a detail-type value of AWS Insight via CloudTrail, you must have a trail that is currently logging Insights events. For information about logging Insights events, see [Working with CloudTrail Insights](#).

For more information about how to create a trail, see [Creating a trail with the CloudTrail console](#).

CloudTrail integration with AWS Organizations

The management account for an AWS Organizations organization can add a [delegated administrator](#) to manage the organization's CloudTrail resources. You can create an organization trail or organization event data store in the management account or delegated administrator account for an organization that collects all event data for all AWS accounts in an organization in AWS Organizations. Creating an [organization trail](#) or [organization event data store](#) helps you define a uniform event logging strategy for your organization.

CloudTrail integration with AWS Control Tower

AWS Control Tower sets up a new CloudTrail organization trail logging management events when you set up a landing zone. When you enroll an account into AWS Control Tower, your account is governed by the organization trail for the AWS Control Tower organization. If you have an existing organization trail in that account, you may see duplicate charges unless you delete the existing trail for the account before you enroll it in AWS Control Tower. You can view the **Trails** page on the CloudTrail console to see whether any organization trails have been created. For more information about AWS Control Tower, see [About logging in AWS Control Tower](#) in the *AWS CloudTrail User Guide*.

CloudTrail integration with Amazon Security Lake

Security Lake can collect logs associated with CloudTrail management events and CloudTrail data events for S3 and Lambda. For more information, see [CloudTrail event logs](#) in the *Amazon Security Lake User Guide*.

To collect CloudTrail management events in Security Lake, you must have at least one CloudTrail multi-Region organization trail that collects read and write CloudTrail management events.

CloudTrail Lake integration with Amazon Athena

You can federate an event data store to see the metadata associated with the event data store in the AWS Glue [Data Catalog](#) and run SQL queries on the event data using Amazon Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know how to find, read, and process the data that you want to query. For more information, see [Federate an event data store](#).

CloudTrail Lake integration with AWS Config

You can create an event data store to include [AWS Config configuration items](#), and use the event data store to investigate non-compliant changes to your production environments. For more information, see [Create an event data store for configuration items with the console](#).

CloudTrail Lake integration with AWS Audit Manager

You can create an event data store for AWS Audit Manager evidence by using the Audit Manager console. For more information about aggregating evidence in CloudTrail Lake using Audit Manager, see [Understanding how evidence finder works with CloudTrail Lake](#) in the *AWS Audit Manager User Guide*.

AWS service topics for CloudTrail

You can learn more about how the events for individual AWS services are recorded in CloudTrail logs, including example events for that service in log files. For more information about how specific AWS services integrate with CloudTrail, see the topic about integration in the individual guide for that service.

Services that are still in preview, or not yet released for general availability (GA), or which don't have public APIs, are not considered supported.

Note

To see the list of supported Regions for each service, see [Service endpoints and quotas](#) in the *Amazon Web Services General Reference*.

For information about which services log data events, see [Data events](#).

AWS Service	CloudTrail Topics	Support began
Amazon API Gateway	Log API management calls to Amazon API Gateway Using AWS CloudTrail	07/09/2015
Amazon AppFlow	Logging Amazon AppFlow API calls with AWS CloudTrail	04/22/2020
Amazon WorkSpaces Applications	Logging Amazon WorkSpaces Applications API Calls with AWS CloudTrail	04/25/2019
Amazon Athena	Logging Amazon Athena API Calls with AWS CloudTrail	05/19/2017
Amazon Aurora	Monitoring Amazon Aurora API calls in AWS CloudTrail	08/31/2018
Amazon Bedrock	Log Amazon Bedrock API calls using AWS CloudTrail	10/23/2023
Amazon Braket	Amazon Braket API logging with CloudTrail	08/12/2020
Amazon Chime	Log Amazon Chime Administration Calls Using AWS CloudTrail	09/27/2017
Amazon Cloud Directory	Logging Cloud Directory API Calls Using AWS CloudTrail	01/26/2017
Amazon CloudFront	Using AWS CloudTrail to Capture Requests Sent to the CloudFront API	05/28/2014
Amazon CloudSearch	Logging Amazon CloudSearch Configuration Service Calls Using AWS CloudTrail	10/16/2014

AWS Service	CloudTrail Topics	Support began
Amazon CloudWatch	Logging Amazon CloudWatch API Calls in AWS CloudTrail	04/30/2014
Amazon CloudWatch Logs	Logging Amazon CloudWatch Logs API Calls in AWS CloudTrail	03/10/2016
Amazon CodeCatalyst	Logging CodeCatalyst API calls in connected AWS accounts using AWS CloudTrail	12/01/2022
Amazon CodeGuru Reviewer	Logging Amazon CodeGuru Reviewer API Calls with AWS CloudTrail	12/02/2019
Amazon Cognito	Logging Amazon Cognito API Calls with AWS CloudTrail	02/18/2016
Amazon Comprehend	Logging Amazon Comprehend API Calls with AWS CloudTrail	01/17/2018
Amazon Comprehend Medical	Logging Amazon Comprehend Medical API Calls by Using AWS CloudTrail	11/27/2018
Amazon Connect	Logging Amazon Connect API Calls with AWS CloudTrail	12/11/2019
Amazon Data Firehose	Monitoring Amazon Data Firehose API Calls with AWS CloudTrail	03/17/2016
Amazon Data Lifecycle Manager	Logging Amazon Data Lifecycle Manager API Calls Using AWS CloudTrail	07/24/2018

AWS Service	CloudTrail Topics	Support began
Amazon Detective	Logging Amazon Detective API calls with AWS CloudTrail	03/31/2020
Amazon DevOps Guru	Logging Amazon DevOps Guru API calls with AWS CloudTrail	05/04/2021
Amazon DocumentDB (with MongoDB compatibility)	Logging Amazon DocumentDB API Calls with AWS CloudTrail	01/09/2019
Amazon DynamoDB	Logging DynamoDB Operations By Using AWS CloudTrail	05/28/2015
Amazon EC2	Log Amazon EC2 API calls using AWS CloudTrail	11/13/2013
Amazon EC2 Auto Scaling	Logging Auto Scaling API Calls By Using CloudTrail	07/16/2014
Amazon EC2 Capacity Blocks	Logging Capacity Blocks API calls with AWS CloudTrail	10/31/2023
Amazon EC2 Image Builder	Logging EC2 Image Builder API calls using CloudTrail	12/02/2019
Amazon Elastic Block Store (Amazon EBS)	Logging API Calls Using AWS CloudTrail	Amazon EBS: 11/13/2013
EBS direct APIs	Log API Calls for the EBS direct APIs with AWS CloudTrail	EBS direct APIs: 06/30/2020
Amazon Elastic Container Registry (Amazon ECR)	Logging Amazon ECR API Calls By Using AWS CloudTrail	12/21/2015

AWS Service	CloudTrail Topics	Support began
Amazon Elastic Container Service (Amazon ECS)	Logging Amazon ECS API Calls By Using AWS CloudTrail	04/09/2015
Amazon Elastic File System (Amazon EFS)	Logging Amazon EFS API Calls with AWS CloudTrail	06/28/2016
Amazon Elastic Kubernetes Service (Amazon EKS)	Logging Amazon EKS API Calls with AWS CloudTrail	06/05/2018
Amazon Elastic Transcoder	Logging Amazon Elastic Transcoder API Calls with AWS CloudTrail	10/27/2014
Amazon ElastiCache	Logging Amazon ElastiCache API Calls Using AWS CloudTrail	09/15/2014
Amazon EMR	Logging Amazon EMR API Calls using AWS CloudTrail	04/04/2014
Amazon EMR on EKS	Logging Amazon EMR on EKS API calls using AWS CloudTrail	12/09/2020
Amazon EventBridge	Logging Amazon EventBridge API calls using AWS CloudTrail	07/11/2019
Amazon FinSpace	Querying AWS CloudTrail logs	10/18/2022
Amazon Forecast	Logging Amazon Forecast API Calls with AWS CloudTrail	11/28/2018
Amazon Fraud Detector	Logging Amazon Fraud Detector API Calls with AWS CloudTrail	01/09/2020

AWS Service	CloudTrail Topics	Support began
Amazon FSx for Lustre	Logging Amazon FSx for Lustre API Calls with AWS CloudTrail	01/11/2019
Amazon FSx for Windows File Server	Monitoring with AWS CloudTrail	11/28/2018
Amazon GameLift Servers	Logging Amazon GameLift Servers API Calls with AWS CloudTrail	01/27/2016
Amazon GameLift Streams	Logging Amazon GameLift Streams API calls using AWS CloudTrail	03/05/2025
Amazon GuardDuty	Logging Amazon GuardDuty API Calls with AWS CloudTrail	02/12/2018
Amazon Inspector	Logging Amazon Inspector API calls using AWS CloudTrail	11/29/2021
Amazon Inspector Classic	Logging Amazon Inspector Classic API calls with AWS CloudTrail	04/20/2016
Amazon Inspector Scan	Amazon Inspector Scan information in CloudTrail	11/27/2023
Amazon Interactive Video Service	Logging Amazon IVS API Calls with AWS CloudTrail	07/15/2020
Amazon Kendra	Logging Amazon Kendra API calls with AWS CloudTrail and Logging Amazon Kendra Intelligent Ranking API calls with AWS CloudTrail logs	05/11/2020

AWS Service	CloudTrail Topics	Support began
Amazon Keyspaces (for Apache Cassandra)	Logging Amazon Keyspaces API calls with AWS CloudTrail	01/13/2020
Amazon Managed Service for Apache Flink	Logging Managed Service for Apache Flink API calls with AWS CloudTrail	03/22/2019
Amazon Kinesis Data Streams	Logging Amazon Kinesis Data Streams API Calls Using AWS CloudTrail	04/25/2014
Amazon Kinesis Video Streams	Logging Kinesis Video Streams API Calls with AWS CloudTrail	05/24/2018
Amazon Lex	Logging Amazon Lex API Calls with CloudTrail	08/15/2017
Amazon Lightsail	Logging Lightsail API Calls with AWS CloudTrail	12/23/2016
Amazon Location Service	Logging and monitoring with AWS CloudTrail	12/15/2020
Amazon Lookout for Equipment	Monitoring Amazon Lookout for Equipment	12/01/2020
Amazon Lookout for Metrics	Viewing Amazon Lookout for Metrics API activity in AWS CloudTrail	12/08/2020
Amazon Lookout for Vision	Logging Amazon Lookout for Vision calls with AWS CloudTrail	12/01/2020
Amazon Machine Learning	Logging Amazon ML API Calls By Using AWS CloudTrail	12/10/2015

AWS Service	CloudTrail Topics	Support began
Amazon Macie	Log Amazon Macie API calls using AWS CloudTrail	05/13/2020
Amazon Managed Blockchain	Logging Amazon Managed Blockchain API calls using AWS CloudTrail Logging Ethereum for Managed Blockchain API calls using AWS CloudTrail (Preview)	04/01/2019
Amazon Managed Grafana	Logging Amazon Managed Grafana API calls using AWS CloudTrail	12/15/2020
Amazon Managed Service for Prometheus	Logging Amazon Managed Service for Prometheus API calls using AWS CloudTrail	12/15/2020
Amazon Managed Streaming for Apache Kafka	Logging API Calls with AWS CloudTrail	12/11/2018
Amazon Managed Workflows for Apache Airflow	Viewing audit logs in AWS CloudTrail	11/24/2020
Amazon MemoryDB	Logging Amazon MemoryDB API calls with AWS CloudTrail	08/19/2021
Amazon MQ	Logging Amazon MQ API Calls Using AWS CloudTrail	07/19/2018
Amazon Neptune	Logging Amazon Neptune API Calls Using AWS CloudTrail	05/30/2018

AWS Service	CloudTrail Topics	Support began
Amazon One Enterprise	Logging Amazon One Enterprise API calls using AWS CloudTrail	11/27/2023
Amazon OpenSearch Service	Monitoring Amazon OpenSearch Service API calls with AWS CloudTrail	10/01/2015
Amazon Personalize	Logging Amazon Personalize API Calls with AWS CloudTrail	11/28/2018
Amazon Pinpoint	Logging Amazon Pinpoint API Calls with AWS CloudTrail	02/06/2018
Amazon Pinpoint SMS and Voice API	Logging Amazon Pinpoint API Calls with AWS CloudTrail	11/16/2018
Amazon Polly	Logging Amazon Polly API Calls with AWS CloudTrail	11/30/2016
Amazon Q Business	Logging Amazon Q Business API calls using AWS CloudTrail	11/28/2023
Amazon Q Developer	Logging Amazon Q Developer API calls using AWS CloudTrail	11/28/2023
Amazon Quantum Ledger Database (Amazon QLDB)	Logging Amazon QLDB API Calls with AWS CloudTrail	09/10/2019
Amazon Quick Suite	Logging Operations with CloudTrail	04/28/2017
Amazon Relational Database Service (Amazon RDS)	Logging Amazon RDS API Calls Using AWS CloudTrail	11/13/2013

AWS Service	CloudTrail Topics	Support began
Amazon RDS Performance Insights	Logging Amazon RDS API Calls Using AWS CloudTrail The Amazon RDS Performance Insights API is a subset of the Amazon RDS API.	06/21/2018
Amazon Redshift	Logging Amazon Redshift API Calls with AWS CloudTrail	06/10/2014
Amazon Rekognition	Logging Amazon Rekognition API Calls Using AWS CloudTrail	04/6/2018
Amazon Route 53	Using AWS CloudTrail to Capture Requests Sent to the Route 53 API	02/11/2015
Amazon Application Recovery Controller (ARC)	Logging Amazon Application Recovery Controller (ARC) API calls using AWS CloudTrail	07/27/2021
Amazon S3	Logging Amazon S3 API Calls By Using AWS CloudTrail	Management events: 09/01/2015 Data events: 11/21/2016
Amazon Glacier	Logging Amazon Glacier API Calls By Using AWS CloudTrail	12/11/2014
Amazon SageMaker AI	Logging Amazon SageMaker AI API Calls with AWS CloudTrail	01/11/2018
Amazon Security Lake	Logging Amazon Security Lake API calls using CloudTrail	05/30/2023

AWS Service	CloudTrail Topics	Support began
Amazon Simple Email Service (Amazon SES)	Logging Amazon SES API Calls By Using AWS CloudTrail	05/07/2015
Amazon Simple Notification Service (Amazon SNS)	Logging Amazon SNS API Calls using AWS CloudTrail	10/09/2014
Amazon Simple Queue Service (Amazon SQS)	Logging Amazon SQS API Actions Using AWS CloudTrail	07/16/2014
Amazon Simple Workflow Service (Amazon SWF)	Recording API calls with AWS CloudTrail	Management events: 05/13/2014 Data events: 02/14/2024
Amazon Textract	Logging Amazon Textract API Calls with AWS CloudTrail	05/29/2019
Amazon Timestream	Logging Timestream API calls with AWS CloudTrail	09/30/2020
Amazon Transcribe	Logging Amazon Transcribe API Calls with AWS CloudTrail	06/28/2018
Amazon Translate	Logging Amazon Translate API Calls with AWS CloudTrail	04/04/2018
Amazon Verified Permissions	Logging Amazon Verified Permissions API calls using AWS CloudTrail	06/13/2023
Amazon Virtual Private Cloud (Amazon VPC)	Logging API Calls Using AWS CloudTrail The Amazon VPC API is a subset of the Amazon EC2 API.	11/13/2013
Amazon VPC Lattice	CloudTrail logs	03/31/2023

AWS Service	CloudTrail Topics	Support began
Amazon VPC Reachability Analyzer	Logging Reachability Analyzer API calls using AWS CloudTrail	11/27/2023
Amazon WorkDocs	Logging Amazon WorkDocs API Calls By Using AWS CloudTrail	08/27/2014
Amazon WorkMail	Logging Amazon WorkMail API Calls Using AWS CloudTrail	12/12/2017
Amazon WorkSpaces	Logging Amazon WorkSpaces API Calls by Using CloudTrail	04/09/2015
Amazon WorkSpaces Thin Client	Logging Amazon WorkSpaces Thin Client API calls using AWS CloudTrail	11/26/2023
Amazon WorkSpaces Web	Logging Amazon WorkSpaces Web API calls using AWS CloudTrail	11/30/2021
Application Auto Scaling	Logging Application Auto Scaling API calls with AWS CloudTrail	10/31/2016
AWS Account Management	Logging AWS Account Management API calls using AWS CloudTrail	10/01/2021
AWS Amplify	Logging Amplify API calls using AWS CloudTrail	11/30/2020
AWS App Mesh	Logging App Mesh API Calls with AWS CloudTrail	AWS App Mesh 10/30/2019 App Mesh Envoy Management Service 03/18/2022

AWS Service	CloudTrail Topics	Support began
AWS App Runner	Logging App Runner API calls with AWS CloudTrail	05/18/2021
AWS AppConfig	Logging AWS AppConfig API calls using AWS CloudTrail	Management events: 07/31/2020 Data events: 01/04/2024
AWS AppFabric	Logging AWS AppFabric API calls using AWS CloudTrail	06/27/2023
AWS Application Discovery Service	Logging Application Discovery Service API Calls with AWS CloudTrail	05/12/2016
AWS Application Transformation Service	(Backend service used by AWS tools, such as AWS Microservice Extractor for .NET)	08/26/2023
AWS AppSync	Logging AWS AppSync API Calls with AWS CloudTrail	02/13/2018
AWS Artifact	Logging AWS Artifact API calls with AWS CloudTrail	01/27/2023
AWS Audit Manager	Logging AWS Audit Manager API calls with AWS CloudTrail	12/07/2020
AWS Auto Scaling	Logging AWS Auto Scaling API Calls By Using CloudTrail	08/15/2018
AWS B2B Data Interchange	Logging AWS B2B Data Interchange API calls using AWS CloudTrail	12/01/2023
AWS Backup	Logging AWS Backup API Calls with AWS CloudTrail	02/04/2019

AWS Service	CloudTrail Topics	Support began
AWS Batch	Logging AWS Batch API Calls with AWS CloudTrail	1/10/2018
AWS Billing and Cost Management	Logging AWS Billing and Cost Management API Calls with AWS CloudTrail	06/07/2018
AWS Billing Conductor	Logging AWS Billing Conductor API calls using AWS CloudTrail	03/12/2024
AWS BugBust	Logging BugBust API calls using CloudTrail	06/24/2021
AWS Certificate Manager	Using AWS CloudTrail	03/25/2016
AWS Clean Rooms	Logging AWS Clean Rooms API calls using AWS CloudTrail	03/21/2023
AWS Cloud Map	Logging AWS Cloud Map API Calls with AWS CloudTrail	11/28/2018
AWS Cloud9	Logging AWS Cloud9 API Calls with AWS CloudTrail	01/21/2019
AWS CloudFormation	Logging AWS CloudFormation API Calls in AWS CloudTrail	04/02/2014
AWS CloudHSM	Logging AWS CloudHSM API Calls By Using AWS CloudTrail	01/08/2015
AWS CloudShell	Logging and monitoring in AWS CloudShell	12/15/2020
AWS CloudTrail	AWS CloudTrail API Reference (All CloudTrail API calls are logged by CloudTrail.)	11/13/2013

AWS Service	CloudTrail Topics	Support began
AWS CodeArtifact	Logging CodeArtifact API calls with AWS CloudTrail	06/10/2020
AWS CodeBuild	Logging AWS CodeBuild API Calls with AWS CloudTrail	12/01/2016
AWS CodeCommit	Logging AWS CodeCommit API Calls with AWS CloudTrail	01/11/2017
AWS CodeDeploy	Monitoring Deployments with AWS CloudTrail	12/16/2014
AWS CodePipeline	Logging CodePipeline API calls with AWS CloudTrail	07/09/2015
AWS CodeStar	Logging AWS CodeStar API Calls with AWS CloudTrail	06/14/2017
AWS CodeStar Notifications	Logging AWS CodeStar Notifications API Calls with AWS CloudTrail	11/05/2019
AWS Config	Logging AWS Config API Calls By with AWS CloudTrail	02/10/2015
AWS Control Catalog	Logging AWS Control Catalog API calls using AWS CloudTrail	04/08/2024
AWS Control Tower	Logging AWS Control Tower Actions with AWS CloudTrail	08/12/2019
AWS Data Pipeline	Logging AWS Data Pipeline API Calls by using AWS CloudTrail	12/02/2014

AWS Service	CloudTrail Topics	Support began
AWS Database Migration Service (AWS DMS)	Logging AWS Database Migration Service API Calls Using AWS CloudTrail	02/04/2016
AWS DataSync	Logging AWS DataSync API Calls with AWS CloudTrail	11/26/2018
AWS Deadline Cloud	Logging Deadline Cloud API calls using AWS CloudTrail	04/02/2024
AWS Device Farm	Logging AWS Device Farm API Calls By Using AWS CloudTrail	07/13/2015
AWS Direct Connect	Logging AWS Direct Connect API Calls in AWS CloudTrail	03/08/2014
AWS Directory Service	Logging AWS Directory Service API Calls by Using CloudTrail	05/14/2015
AWS Directory Service Data	Logging AWS Directory Service Data API calls using AWS CloudTrail	09/18/2024
AWS Elastic Beanstalk (Elastic Beanstalk)	Using Elastic Beanstalk API Calls with AWS CloudTrail	03/31/2014
AWS Elastic Disaster Recovery	Logging AWS Elastic Disaster Recovery API calls using AWS CloudTrail	11/17/2021
AWS Elemental MediaConnect	Logging AWS Elemental MediaConnect API Calls with AWS CloudTrail	11/27/2018

AWS Service	CloudTrail Topics	Support began
AWS Elemental MediaConvert	Logging AWS Elemental MediaConvert API Calls with CloudTrail	11/27/2017
AWS Elemental MediaLive	Logging MediaLive API Calls with AWS CloudTrail	01/19/2019
AWS Elemental MediaPackage	Logging AWS Elemental MediaPackage API Calls with AWS CloudTrail	12/21/2018
AWS Elemental MediaStore	Logging AWS Elemental MediaStore API Calls with CloudTrail	11/27/2017
AWS Elemental MediaTailor	Logging AWS Elemental MediaTailor API Calls with AWS CloudTrail	02/11/2019
AWS End User Messaging SMS	Logging AWS End User Messaging SMS API calls using AWS CloudTrail	10/10/2024
AWS End User Messaging Social	Logging AWS End User Messaging Social API calls using AWS CloudTrail	10/10/2024
AWS Entity Resolution	Logging AWS Entity Resolution API calls using AWS CloudTrail	07/26/2023
AWS Fault Injection Service	Log API calls with AWS CloudTrail	03/15/2021
AWS Firewall Manager	Logging AWS Firewall Manager API Calls with AWS CloudTrail	04/05/2018

AWS Service	CloudTrail Topics	Support began
AWS Global Accelerator	Logging AWS Global Accelerator or API Calls with AWS CloudTrail	11/26/2018
AWS Glue	Logging AWS Glue Operations Using AWS CloudTrail	11/07/2017
AWS Ground Station	Logging AWS Ground Station API Calls with AWS CloudTrail	05/31/2019
AWS Health	Logging AWS Health API Calls with AWS CloudTrail	11/21/2016
AWS Health Dashboard	Logging AWS Health API Calls with AWS CloudTrail	12/01/2016
AWS HealthImaging	Logging AWS HealthImaging API calls using AWS CloudTrail	07/26/2023
AWS HealthLake	Logging AWS HealthLake API calls with AWS CloudTrail	12/07/2020
AWS HealthOmics	Logging AWS HealthOmics API calls using AWS CloudTrail	11/29/2022
AWS IAM Identity Center	Logging IAM Identity Center API Calls with AWS CloudTrail	12/07/2017
AWS IAM Identity Center – SCIM	Logging IAM Identity Center API Calls with AWS CloudTrail	10/28/2024
AWS Identity and Access Management (IAM)	Logging IAM Events with AWS CloudTrail	11/13/2013
AWS IoT	Logging AWS IoT API Calls with AWS CloudTrail	04/11/2016

AWS Service	CloudTrail Topics	Support began
AWS IoT Analytics	Logging AWS IoT Analytics API calls with AWS CloudTrail	04/23/2018
AWS IoT Events	Understanding AWS IoT Events log file entries	06/11/2019
AWS IoT Greengrass	Logging AWS IoT Greengrass API Calls with AWS CloudTrail	10/29/2018
AWS IoT Greengrass V2	Log AWS IoT Greengrass V2 API calls with AWS CloudTrail	12/14/2020
AWS IoT SiteWise	Logging AWS IoT SiteWise API calls with AWS CloudTrail	04/29/2020
AWS Key Management Service (AWS KMS)	Logging AWS KMS API Calls using AWS CloudTrail	11/12/2014
AWS Lake Formation	Logging AWS Lake Formation API Calls Using AWS CloudTrail	08/09/2019
AWS Lambda	Logging AWS Lambda API Calls By Using AWS CloudTrail	Management events: 04/09/2015 Data events: 11/30/2017
AWS Launch Wizard	Logging AWS Launch Wizard API calls using AWS CloudTrail	11/08/2023
AWS License Manager	Logging AWS License Manager API Calls with AWS CloudTrail	03/01/2019
AWS Mainframe Modernization	Logging AWS Mainframe Modernization API calls using AWS CloudTrail	06/08/2022

AWS Service	CloudTrail Topics	Support began
Managed integrations for AWS IoT Device Management	Logging Managed integrations API calls using AWS CloudTrail	03/03/2025
AWS Managed Services	Log management in AMS Accelerate	12/21/2016
AWS Marketplace Agreements	Logging Agreements API Calls using AWS CloudTrail	09/01/2023
AWS Marketplace Deployment Service	Logging AWS Marketplace Deployment Service calls with CloudTrail	11/29/2023
AWS Marketplace Discovery	Logging AWS Marketplace Discovery API calls using AWS CloudTrail	12/15/2022
AWS Marketplace Metering Service	Logging AWS Marketplace API Calls with AWS CloudTrail	08/22/2018
AWS Migration Hub	Logging AWS Migration Hub API Calls with AWS CloudTrail	08/14/2017
AWS Migration Hub Journeys	Logging AWS Migration Hub Journeys API calls with AWS CloudTrail	12/03/2024
Multi-party approval	Logging Multi-party approval API calls using AWS CloudTrail	06/17/2025
AWS Network Firewall	Logging calls to the AWS Network Firewall API with AWS CloudTrail	11/17/2020

AWS Service	CloudTrail Topics	Support began
AWS OpsWorks for Chef Automate	Logging AWS OpsWorks for Chef Automate API Calls with AWS CloudTrail	07/16/2018
AWS OpsWorks for Puppet Enterprise	Logging OpsWorks for Puppet Enterprise API Calls with AWS CloudTrail	07/16/2018
AWS OpsWorks Stacks	Logging AWS OpsWorks Stacks API Calls with AWS CloudTrail	06/04/2014
Oracle Database@AWS	Logging Oracle Database@AWS API Calls with AWS CloudTrail	12/01/2024
AWS Organizations	Logging AWS Organizations API calls with AWS CloudTrail	02/27/2017
AWS Outposts	Logging AWS Outposts API calls with AWS CloudTrail	02/04/2020
AWS Panorama	AWS Panorama API Reference	10/20/2021
AWS Payment Cryptography	Logging AWS Payment Cryptography API calls using AWS CloudTrail	06/08/2023
AWS Private 5G	Logging AWS Private 5G API calls using AWS CloudTrail	08/11/2022
AWS Private Certificate Authority (AWS Private CA)	Using CloudTrail	04/04/2018
AWS Proton	Logging and monitoring in AWS Proton	06/09/2021

AWS Service	CloudTrail Topics	Support began
AWS re:Post Private	Logging AWS re:Post Private API calls using AWS CloudTrail	11/26/2023
AWS Resilience Hub	AWS CloudTrail	11/10/2021
AWS Resource Access Manager (AWS RAM)	Logging AWS RAM API Calls with AWS CloudTrail	11/20/2018
AWS Resource Explorer	Logging AWS Resource Explorer API calls using AWS CloudTrail	11/07/2022
AWS Resource Groups	Logging and monitoring in Resource Groups	06/29/2018
AWS RoboMaker	Logging AWS RoboMaker API Calls with AWS CloudTrail	01/16/2019
AWS Secrets Manager	Monitor the Use of Your AWS Secrets Manager Secrets	04/05/2018
AWS Security Hub	Logging AWS Security Hub API Calls with AWS CloudTrail	11/27/2018
AWS Security Incident Response	Logging AWS Security Incident Response API calls using AWS CloudTrail	12/01/2024
AWS Security Token Service (AWS STS)	Logging IAM Events with AWS CloudTrail The IAM topic includes information for AWS STS.	11/13/2013
AWS Serverless Application Repository	Logging AWS Serverless Application Repository API Calls with AWS CloudTrail	02/20/2018

AWS Service	CloudTrail Topics	Support began
AWS Service Catalog	Logging Service Catalog API Calls with AWS CloudTrail	07/06/2016
AWS Shield	Logging Shield Advanced API Calls with AWS CloudTrail	02/08/2018
AWS Snowball Edge Edge	Logging AWS Snowball Edge Edge API Calls with AWS CloudTrail	01/25/2019
AWS Step Functions	Logging AWS Step Functions API Calls with AWS CloudTrail	12/01/2016
AWS Storage Gateway	Logging Storage Gateway API Calls by Using AWS CloudTrail	12/16/2014
AWS Support	Logging AWS Support API calls with AWS CloudTrail	04/21/2016
Support Recommendations (Preview)	Logging Support Recommendations API calls with AWS CloudTrail	05/22/2024
AWS Systems Manager	Logging AWS Systems Manager API Calls with AWS CloudTrail	11/29/2017
AWS Systems Manager Incident Manager	Logging AWS Systems Manager Incident Manager API calls using AWS CloudTrail	05/10/2021
AWS Telco Network Builder (AWS TNB)	Logging AWS Telco Network Builder API calls using AWS CloudTrail	02/21/2023

AWS Service	CloudTrail Topics	Support began
AWS Transfer for SFTP	Logging AWS Transfer for SFTP API Calls with AWS CloudTrail	01/08/2019
AWS Transit Gateway	Logging API Calls for Your Transit Gateway Using AWS CloudTrail	11/26/2018
AWS Trusted Advisor	Logging AWS Trusted Advisor console actions with AWS CloudTrail	10/22/2020
AWS Verified Access	Log AWS Verified Access API calls using AWS CloudTrail	04/27/2023
AWS WAF	Logging AWS WAF API Calls with AWS CloudTrail	04/28/2016
AWS Well-Architected Tool	Logging AWS Well-Architected Tool API Calls with AWS CloudTrail	12/15/2020
AWS X-Ray	Logging AWS X-Ray API Calls With CloudTrail	04/25/2018
Elastic Load Balancing	AWS CloudTrail Logging for Your Classic Load Balancer and AWS CloudTrail Logging for Your Application Load Balancer	04/04/2014
FreeRTOS Over-the-Air Updates (OTA)	Logging AWS IoT OTA API Calls with AWS CloudTrail	05/22/2019
Service Quotas	Logging Service Quotas API calls using AWS CloudTrail	06/24/2019

CloudTrail unsupported services

Services that are still in preview, or not yet released for general availability (GA), or which don't have public APIs, are not considered supported.

Additionally, the following AWS services and events are not supported:

- AWS Import/Export

For a list of supported AWS services, see [AWS service topics for CloudTrail](#).

Quotas in AWS CloudTrail

This section describes the resource quotas (formerly referred to as limits) in CloudTrail. For information about all quotas in CloudTrail, see [Service quotas](#) in the *AWS General Reference*.

Note

CloudTrail has no adjustable quotas.

CloudTrail resource quotas

The following table describes the resource quotas within CloudTrail.

Resource	Default quota	Comments
Trails per Region	5	The maximum number of trails per AWS Region. In shadow Regions, to get latest resource count metric, call the <code>ListTrails</code> API. This quota cannot be increased.
Event data stores	10	The maximum number of event data stores per AWS

Resource	Default quota	Comments
		Region. This includes single-Region event data stores for the Region, multi-Region event data stores across all AWS Regions, and organization event data stores. This includes event data stores in any lifecycle stage. In shadow Regions, to get latest resource count metric, call the <code>ListEventDataStores</code> API. This quota cannot be increased.
Channels	25	This quota applies to channels used for CloudTrail Lake integrations with event sources outside of AWS, and does not apply to service-linked channels. This quota cannot be increased.

Resource	Default quota	Comments
Dashboards per Region	100	The maximum number of CloudTrail Lake custom dashboards per AWS Region. In shadow Regions, to get the latest resource count metric, call the <code>ListDashboards</code> API. This quota cannot be increased.
Widgets per dashboard	10	This maximum number of widgets per CloudTrail Lake dashboard. This quota cannot be increased.
Concurrent dashboard refreshes	1	The maximum number of ongoing refreshes per dashboard. This quota cannot be increased.
Concurrent queries	10	The maximum number of queued or running queries that you can run simultaneously in CloudTrail Lake. This quota cannot be increased.

Resource	Default quota	Comments
Events per PutAuditEvents request	100	You can add up to 100 activity events (or up to 1 MB) per PutAuditEvents request. This quota cannot be increased.
Event selectors	5 per trail	This quota cannot be increased.
Advanced event selectors	500 conditions across all advanced event selectors	If a trail or event data store uses advanced event selectors , a maximum of 500 total values for all conditions in all advanced event selectors is allowed. This quota cannot be increased.

Resource	Default quota	Comments
Data resources in event selectors	250 across all event selectors in a trail	If you choose to limit data events by using event selectors, the total number of data resources cannot exceed 250 across all event selectors in a trail. The limit of number of resources on an individual event selector is configurable up to 250. This upper limit is allowed only if the total number of data resources does not exceed 250 across all event selectors. Examples: • A trail with 5 event selectors, each configured with 50 data resources, is allowed. ($5 \times 50 = 250$) • A trail with 5 event selectors, 3 of which are configured with 50 data resources, 1 of which is configured with 99 data resources, and 1 of which is configured with 1 data resource, is also allowed. ($(3 \times 50) + 1 + 99 = 250$) • A trail configured with 5 event selectors, all of which are configured with 100 data resources, is not allowed. ($5 \times 100 = 500$)

Resource	Default quota	Comments
		Event selectors apply only to trails. For event data stores, you must use advanced event selectors. This quota cannot be increased. The quota does not apply if you choose to log data events on all resources, such as all S3 buckets or all Lambda functions.
Event size	All event versions: events over 256 KB cannot be sent to CloudWatch Logs Event version 1.05 and newer: total event size limit of 256 KB	Amazon CloudWatch Logs and Amazon EventBridge each allow a maximum event size of 256 KB. CloudTrail does not send events over 256 KB to CloudWatch Logs or EventBridge. Starting with event version 1.05, events have a maximum size of 256 KB. This is to help prevent exploitation by malicious actors, and allow events to be consumed by other AWS services, such as CloudWatch Logs and EventBridge.

Resource	Default quota	Comments
CloudTrail file size sent to Amazon S3	50 MB before compression	For management, data, and network activity events, CloudTrail sends events to S3 in compressed gzip files. The maximum file size before compression is 50 MB. If enabled on the trail, log delivery notifications are sent by Amazon SNS after CloudTrail sends gzip files to S3.

Transactions per second (TPS) quotas in CloudTrail

The [AWS General Reference](#) lists the transactions per second (TPS) quota for AWS APIs. The transactions per second (TPS) quota for an API represents how many requests you can make per second for a given API without being throttled. For example, the TPS quota for the CloudTrail `LookupEvents` API is 2.

For information about the TPS quota for each CloudTrail API, see [Service quotas](#) in the *AWS General Reference*.

Getting started with AWS CloudTrail tutorials

If you're new to AWS CloudTrail, these tutorials can help you learn how to use its features. To use CloudTrail features, you need to have adequate permissions. This page describes the managed policies available for CloudTrail and provides information about how you can grant permissions.

Examples:

- [Grant permissions to use CloudTrail](#)
- [View event history](#)
- [Create a trail to log management events](#)
- [Create an event data store for S3 data events](#)

Grant permissions to use CloudTrail

To create, update, and manage CloudTrail resources like trails, event data stores, and channels, you need to grant permissions to use CloudTrail. This section provides information about the managed policies available for CloudTrail.

Note

The permissions you grant to users to perform CloudTrail administration tasks aren't the same as the permissions that CloudTrail requires to deliver log files to Amazon S3 buckets or send notifications to Amazon SNS topics. For more information about those permissions, see [Amazon S3 bucket policy for CloudTrail](#).

If you configure integration with Amazon CloudWatch Logs, CloudTrail also requires a role that it can assume to deliver events to an Amazon CloudWatch Logs log group. You must create the role that CloudTrail uses. For more information, see [Granting permission to view and configure Amazon CloudWatch Logs information on the CloudTrail console](#) and [Sending events to CloudWatch Logs](#).

The following AWS managed policies are available for CloudTrail:

- [AWSCloudTrail_FullAccess](#) – This policy provides full access to CloudTrail actions on CloudTrail resources, such as trails, event data stores, and channels. This policy provides the required permissions to create, update, and delete CloudTrail trails, event data stores, and channels.

This policy also provides permissions to manage the Amazon S3 bucket, the log group for CloudWatch Logs, and an Amazon SNS topic for a trail. However, the `AWSCloudTrail_FullAccess` managed policy doesn't provide permissions to delete the Amazon S3 bucket, the log group for CloudWatch Logs, or an Amazon SNS topic. For information about managed policies for other AWS services, see the [AWS Managed Policy Reference Guide](#).

 Note

The `AWSCloudTrail_FullAccess` policy isn't intended to be shared broadly across your AWS account. Users with this role can turn off or reconfigure the most sensitive and important auditing functions in their AWS accounts. For this reason, you must only apply this policy to account administrators. You must closely control and monitor use of this policy.

- [AWSCloudTrail_ReadOnlyAccess](#) – This policy grants permissions to view the CloudTrail console, including recent events and event history. This policy also allows you to view existing trails, event data stores, and channels. Roles and users with this policy can [download the event history](#), but they can't create or update trails, event data stores, or channels.

To provide access, add permissions to your users, groups, or roles:

- Users and groups in AWS IAM Identity Center:

Create a permission set. Follow the instructions in [Create a permission set](#) in the *AWS IAM Identity Center User Guide*.

- Users managed in IAM through an identity provider:

Create a role for identity federation. Follow the instructions in [Create a role for a third-party identity provider \(federation\)](#) in the *IAM User Guide*.


- IAM users:
 - Create a role that your user can assume. Follow the instructions in [Create a role for an IAM user](#) in the *IAM User Guide*.
 - (Not recommended) Attach a policy directly to a user or add a user to a user group. Follow the instructions in [Adding permissions to a user \(console\)](#) in the *IAM User Guide*.

View event history

This section describes how to use the CloudTrail **Event history** page on the CloudTrail console to view the last 90 days of management events for your AWS account for the current AWS Region.

To view the Event history

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, choose **Event history**. You see a filtered list of events, with the most recent events showing first. The default filter for events is **Read only**, set to **false**. You can clear that filter by choosing **X** at the right of the filter. You can search events in **Event history** by filtering for events on a single attribute



Event history (145+) Info


Event history shows you the last 90 days of management events.

Lookup attributes

Read-only ▼ X Filter by date and time < 1 2 ... > ⚙️

☐	Event name	Event time	User name	Event source	Resource type
☐	PutEvaluations	May 09, 2024, 15:29:17 (UTC+0...)	configLambdaExecution	config.amazonaws.com	-
☐	PutEvaluations	May 09, 2024, 14:29:28 (UTC+0...)	configLambdaExecution	config.amazonaws.com	-
☐	ConsoleLogin	May 09, 2024, 14:23:57 (UTC+0...)		signin.amazonaws.com	-
☐	GetSignInToken	May 09, 2024, 14:23:57 (UTC+0...)		signin.amazonaws.com	-

3. Choose an attribute to filter on and enter the full value for the attribute. CloudTrail can't filter on a partial value. For example, to view all console login events, choose the **Event name** filter, and specify **ConsoleLogin** for the attribute value.



Event history (14) Info

Event history shows you the last 90 days of management events.

Lookup attributes

Event name ▼ X Filter by date and time < 1 > ⚙️

☐	Event name	Event time	User name	Event source	Resource type
☐	ConsoleLogin	May 09, 2024, 16:27:50 (UTC+0...)		signin.amazonaws.com	-
☐	ConsoleLogin	May 09, 2024, 14:23:57 (UTC+0...)		signin.amazonaws.com	-
☐	ConsoleLogin	May 08, 2024, 18:52:17 (UTC+0...)		signin.amazonaws.com	-
☐	ConsoleLogin	May 07, 2024, 18:18:31 (UTC+0...)		signin.amazonaws.com	-

Or, to view recent CloudTrail management events, choose **Event source**, and specify `cloudtrail.amazonaws.com`. For information about the events a service logs to CloudTrail, refer to the service's API Reference.

Event history (50+) Info Download events Create Athena table


Event history shows you the last 90 days of management events.

Lookup attributes

Event source Filter by date and time < 1 2 ... > ⚙️

☐	Event name	Event time	User name	Event source	Resource type
☐	LookupEvents	May 09, 2024, 16:34:57 (UTC+0...)		cloudtrail.amazonaws.com	-
☐	LookupEvents	May 09, 2024, 16:34:57 (UTC+0...)		cloudtrail.amazonaws.com	-
☐	LookupEvents	May 09, 2024, 16:28:26 (UTC+0...)		cloudtrail.amazonaws.com	-
☐	LookupEvents	May 09, 2024, 16:28:23 (UTC+0...)		cloudtrail.amazonaws.com	-
☐	LookupEvents	May 09, 2024, 16:27:57 (UTC+0...)		cloudtrail.amazonaws.com	-
☐	LookupEvents	May 09, 2024, 16:27:57 (UTC+0...)		cloudtrail.amazonaws.com	-

- To view a specific management event, choose the event name. On the event details page, you can view details about the event, see any referenced resources, and view the event record.
- To compare events, select up to five events by filling their check boxes in the left margin of the **Event history** table. You can view details for selected events side-by-side in the **Compare event details** table.
- You can save event history by downloading it as a file in CSV or JSON format. Downloading your event history can take a few minutes.



For more information, see [Working with CloudTrail event history](#).

Create a trail to log management events

For your first trail, we recommend creating a trail that logs all [management events](#) and does not log any [data events](#) or Insights events. Examples of management events include security events such as IAM CreateUser and AttachRolePolicy events, resource events such as

RunInstances and CreateBucket, and many more. You will create an Amazon S3 bucket where you will store the log files for the trail as part of creating the trail in the CloudTrail console.

Note

AWS Control Tower sets up a new CloudTrail trail logging management events when you set up a landing zone. It is an organization-level trail, which means that it logs all management events for the management account and all member accounts in the organization. For more information, see [About logging in AWS Control Tower](#) in the *AWS CloudTrail User Guide*.

This tutorial assumes you are creating your first trail. Depending on the number of trails you have in your AWS account, and how those trails are configured, the following procedure might or might not incur expenses. CloudTrail stores log files in an Amazon S3 bucket, which incurs costs. For more information about pricing, see [AWS CloudTrail Pricing](#) and [Amazon S3 Pricing](#).

To create a trail

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the **Region** selector, choose the AWS Region where you want your trail to be created. This is the home Region for the trail.

Note

The home Region is the only AWS Region where you can update the trail after it is created.

3. On the CloudTrail service home page, the **Trails** page, or the **Trails** section of the **Dashboard** page, choose **Create trail**.
4. In **Trail name**, give your trail a name, such as *management-events*. As a best practice, use a name that quickly identifies the purpose of the trail. In this case, you're creating a trail that logs management events.
5. Leave the default setting for **Enable for all accounts in my organization**. This option won't be available to change unless you have accounts configured in Organizations.

6. For **Storage location**, choose **Create new S3 bucket** to create a bucket. When you create a bucket, CloudTrail creates and applies the required bucket policies. If you choose to create a new S3 bucket, your IAM policy needs to include permission for the `s3:PutEncryptionConfiguration` action because by default server-side encryption is enabled for the bucket. Give your bucket a name that makes it easy to identify.

To make it easier to find your logs, create a new folder (also known as a *prefix*) in an existing bucket to store your CloudTrail logs.

 Note

The name of your Amazon S3 bucket must be globally unique. For more information, see [Bucket naming rules](#) in the *Amazon Simple Storage Service User Guide*.

7. Clear the check box to disable **Log file SSE-KMS encryption**. By default, your log files are encrypted with SSE-S3 encryption. For more information about this setting, see [Using server-side encryption with Amazon S3 managed keys \(SSE-S3\)](#).
8. Leave default settings in **Additional settings**.
9. Leave the default settings for **CloudWatch Logs**. For now, do not send logs to Amazon CloudWatch Logs.
10. (Optional) In **Tags**, you can add up to 50 tag key pairs to help you identify, sort, and control access to your trail. Tags can help you identify your CloudTrail trails and other resources, such as the Amazon S3 buckets that contain CloudTrail log files. For example, you could attach a tag with the name **Compliance** and the value **Auditing**.

 Note

Though you can add tags to trails when you create them in the CloudTrail console, and you can create an Amazon S3 bucket to store your log files in the CloudTrail console, you cannot add tags to the Amazon S3 bucket from the CloudTrail console. For more information about viewing and changing the properties of an Amazon S3 bucket, including adding tags to a bucket, see the [Amazon S3 User Guide](#).

When you are finished creating tags, choose **Next**.

11. On the **Choose log events** page, select event types to log. For this trail, keep the default, **Management events**. In the **Management events** area, choose to log both **Read** and **Write**

events, if they are not already selected. Leave the check boxes for **Exclude AWS KMS events** and **Exclude Amazon RDS Data API events** empty, to log all management events.

Choose log events

Events [Info](#)

Record API activity for individual resources, or for all current and future resources in AWS account. [Additional charges apply](#)

Event type

Choose the type of events that you want to log.

☒ **Management events**
 Capture management operations performed on your AWS resources.

☐ **Data events**
 Log the resource operations performed on or within a resource.

☐ **Insights events**
 Identify unusual activity, errors, or user behavior in your account.

Management events [Info](#)

Management events show information about management operations performed on resources in your AWS account.

No additional charges apply to log management events on this trail because this is your first copy of management events.

API activity


Choose the activities you want to log.

☒ **Read**
☒ **Write**

☐ **Exclude AWS KMS events**

☐ **Exclude Amazon RDS Data API events**

- Leave default settings for **Data events**, **Insights events**, and **Network activity events**. This trail will not log any data events, Insights events, or network activity events. Choose **Next**.
- On the **Review and create** page, review the settings you've chosen for your trail. Choose **Edit** for a section to go back and make changes. When you are ready to create your trail, choose **Create trail**.
- The **Trails** page shows your new trail in the table. Note that the trail is set to **Multi-region trail** by default, and that logging is turned on for the trail by default.



The screenshot shows the AWS CloudTrail Trails console. At the top, there are buttons for 'Refresh', 'Delete', and 'Create trail'. Below is a table with columns: Name, Home region, Multi-region trail, Insights, Organization trail, S3 bucket, Log file prefix, CloudWatch Logs log group, and Status. A single trail is listed: 'My-Management-Events-Trail' in the 'Europe (Frankfurt)' region, with 'Multi-region trail' set to 'Yes', 'Insights' as 'Disabled', 'Organization trail' as 'No', 'S3 bucket' as 'aws-cloudtrail-logs-0813202-0-mytrail', and 'Status' as 'Logging' (indicated by a green checkmark icon).

Name	Home region	Multi-region trail	Insights	Organization trail	S3 bucket	Log file prefix	CloudWatch Logs log group	Status
My-Management-Events-Trail	Europe (Frankfurt)	Yes	Disabled	No	aws-cloudtrail-logs-0813202-0-mytrail			Logging

For more information about trails, see [Working with CloudTrail trails](#).

View your log files

Within an average of about 5 minutes of creating your first trail, CloudTrail delivers the first set of log files to the Amazon S3 bucket for your trail. You can look at these files and learn about the information they contain.

Note


CloudTrail typically delivers logs within an average of about 5 minutes of an API call. This time is not guaranteed. Review the [AWS CloudTrail Service Level Agreement](#) for more information.

If you misconfigure your trail (for example, the S3 bucket is unreachable), CloudTrail will attempt to redeliver the log files to your S3 bucket for 30 days, and these attempted-to-deliver events will be subject to standard CloudTrail charges. To avoid charges on a misconfigured trail, you need to delete the trail.

To view your log files

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, choose **Trails**. On the **Trails** page, find the name of the trail you just created (in the example, *management-events*).
3. In the row for the trail, choose the value for the S3 bucket.
4. The Amazon S3 console opens and shows two folders for the bucket: CloudTrail-Digest and CloudTrail. Choose the **CloudTrail** folder to view the log files.

- If you created a multi-Region trail, there is a folder for each AWS Region. Choose the folder for the AWS Region where you want to review log files. For example, if you want to review the log files for the US East (Ohio) Region, choose **us-east-2**.



- Navigate the bucket folder structure to the year, the month, and the day where you want to review logs of activity in that Region. In that day, there are a number of files. The name of the files begin with your AWS account ID, and end with the extension `.gz`. For example, if your account ID is **123456789012**, you would see files with names similar to this: **123456789012_CloudTrail_us-east-2_20240512T0000Z_EXAMPLE.json.gz**.

To view these files, you can download them, unzip them, and then view them in a plain-text editor or a JSON file viewer. Some browsers also support viewing `.gz` and JSON files directly. We recommend using a JSON viewer, as it makes it easier to parse the information in CloudTrail log files.

Create an event data store for S3 data events

You can create an event data store to log CloudTrail events (management events, data events), [CloudTrail Insights events](#), [AWS Audit Manager evidence](#), [AWS Config configuration items](#), or [non-AWS events](#).

When you create an event data store for data events, you choose the AWS services and resource types for which you want to log data events. For information about AWS services that log data events, see [Data events](#).

This walkthrough shows you how to create an event data store for Amazon S3 data events. In this tutorial, instead of logging all Amazon S3 data events, we'll choose a custom log selector template to log events only when an object is deleted from a specific S3 bucket.

To create an event data store for S3 data events

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose **Create event data store**.
4. On the **Configure event data store** page, in **General details**, give your event data store a name, such as *s3-data-events-eds*. As a best practice, use a name that quickly identifies the purpose of the event data store. For information about CloudTrail naming requirements, see [Naming requirements for CloudTrail resources, S3 buckets, and KMS keys](#).
5. Choose the **Pricing option** that you want to use for your event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention periods for your event data store. For more information, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

The following are the available options:

- **One-year extendable retention pricing** - Generally recommended if you expect to ingest less than 25 TB of event data per month and want a flexible retention period of up to 10 years. For the first 366 days (the default retention period), storage is included at no additional charge with ingestion pricing. After 366 days, extended retention is available at pay-as-you-go pricing. This is the default option.
 - **Default retention period:** 366 days
 - **Maximum retention period:** 3,653 days
- **Seven-year retention pricing** - Recommended if you expect to ingest more than 25 TB of event data per month and need a retention period of up to 7 years. Retention is included with ingestion pricing at no additional charge.
 - **Default retention period:** 2,557 days

- **Maximum retention period:** 2,557 days
6. Specify a retention period for the event data store. Retention periods can be between 7 days and 3,653 days (about 10 years) for the **One-year extendable retention pricing** option, or between 7 days and 2,557 days (about seven years) for the **Seven-year retention pricing** option.

CloudTrail Lake determines whether to retain an event by checking if the `eventTime` of the event is within the specified retention period. For example, if you specify a retention period of 90 days, CloudTrail will remove events when their `eventTime` is older than 90 days.

7. (Optional) In **Encryption**, choose whether you want to encrypt the event data store using your own KMS key. By default, all events in an event data store are encrypted by CloudTrail using a KMS key that AWS owns and manages for you.

To enable encryption using your own KMS key, choose **Use my own AWS KMS key**. Choose **New** to have an AWS KMS key created for you, or choose **Existing** to use an existing KMS key. In **Enter KMS alias**, specify an alias, in the format `alias/MyAliasName`. Using your own KMS key requires that you edit your KMS key policy to allow CloudTrail logs to be encrypted and decrypted. For more information, see [Configure AWS KMS key policies for CloudTrail](#). CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

Using your own KMS key incurs AWS KMS costs for encryption and decryption. After you associate an event data store with a KMS key, the KMS key cannot be removed or changed.

 Note

To enable AWS Key Management Service encryption for an organization event data store, you must use an existing KMS key for the management account.

8. (Optional) If you want to query against your event data using Amazon Athena, choose **Enable** in **Lake query federation**. Federation lets you view the metadata associated with the event data store in the AWS Glue [Data Catalog](#) and run SQL queries against the event data in Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know how to find, read, and process the data that you want to query. For more information, see [Federate an event data store](#).

To enable Lake query federation, choose **Enable** and then do the following:

- a. Choose whether you want to create a new role or use an existing IAM role. [AWS Lake Formation](#) uses this role to manage permissions for the federated event data store. When you create a new role using the CloudTrail console, CloudTrail automatically creates a role with the required permissions. If you choose an existing role, be sure the policy for the role provides the [required minimum permissions](#).
 - b. If you are creating a new role, enter a name to identify the role.
 - c. If you are using an existing role, choose the role you want to use. The role must exist in your account.
9. (Optional) Choose **Enable resource policy** to add a resource-based policy to your event data store. Resource-based policies allow you to control which principals can perform actions on your event data store. For example, you can add a resource based policy that allows the root users in other accounts to query this event data store and view the query results. For example policies, see [Resource-based policy examples for event data stores](#).

A resource-based policy includes one or more statements. Each statement in the policy defines the [principals](#) that are allowed or denied access to the event data store and the actions the principals can perform on the event data store resource.

The following actions are supported in resource-based policies for event data stores:

- `cloudtrail:StartQuery`
- `cloudtrail:CancelQuery`
- `cloudtrail:ListQueries`
- `cloudtrail:DescribeQuery`
- `cloudtrail:GetQueryResults`
- `cloudtrail:GenerateQuery`
- `cloudtrail:GenerateQueryResultsSummary`
- `cloudtrail:GetEventDataStore`

For [organization event data stores](#), CloudTrail creates a [default resource-based policy](#) that lists the actions that the delegated administrator accounts are allowed to perform on organization event data stores. The permissions in this policy are derived from the delegated administrator permissions in AWS Organizations. This policy is updated automatically following changes to

the organization event data store or to the organization (for example, a CloudTrail delegated administrator account is registered or removed).

10. (Optional) In **Tags**, add one or more custom tags (key-value pairs) to your event data store. Tags can help you identify your CloudTrail event data stores. For example, you could attach a tag with the name **stage** and the value **prod**. You can use tags to limit access to your event data store. You can also use tags to track the query and ingestion costs for your event data store.

For information about how to use tags to track costs, see [Creating user-defined cost allocation tags for CloudTrail Lake event data stores](#). For information about how to use IAM policies to authorize access to an event data store based on tags, see [Examples: Denying access to create or delete event data stores based on tags](#). For information about how you can use tags in AWS, see [Tagging your AWS resources](#) in the *Tagging AWS Resources User Guide*.

11. Choose **Next** to configure the event data store.
12. On the **Choose events** page, leave the default selections for **Event type**.

Event type [Info](#)
Choose the type of events you want to add to your event data store. [Additional charges apply](#)

Choose event types

☒ **AWS events**
Capture operations performed on or within your AWS resources.

☐ **Events from integrations**
Create an integration to get events that are logged by applications outside of your AWS resources.

Specify the type of AWS events

☒ **CloudTrail events**
CloudTrail events provide a record of activity in an AWS account.

☐ **CloudTrail Insights events**
Insights events help identify unusual activity, errors, or user behavior in your account. You will be charged separately if you enable Insights for both trails and event data stores.

☐ **Configuration items**
Configuration items show changes made to the configuration of a resource, and show the resource's compliance status.

13. For **CloudTrail events**, choose **Data events** and deselect **Management events**. For more information about data events, see [Logging data events](#).

CloudTrail events [Info](#)

☒ **Management events**
Capture management operations performed on your AWS resources.

☐ **Data events**
Log the resource operations performed on or within a resource.

☐ **Network activity event source - Preview**
Network activity events provide information about resource operations performed on a resource within a virtual private cloud endpoint.

☐ **Copy trail events**
Copy CloudTrail events logged in your trails or from S3 buckets.

☐ **Enable for all accounts in my organization**
To review accounts in your organization, open AWS Organizations. [See all accounts](#) [↗](#)

▶ **Additional settings**

14. Leave the default setting for **Copy trail events**. You'd use this option to copy existing trail events to your event data store. For more information, see [Copy trail events to an event data store](#).
15. Choose **Enable for all accounts in my organization** if this is an organization event data store. This option won't be available to change unless you have accounts configured in AWS Organizations.
16. For **Additional settings** leave the default selections. By default, an event data store collects events for all AWS Regions and starts ingesting events when it's created.
17. For **Data events**, make the following selections:
 - a. In **Resource type**, choose **S3**. The resource type identifies the AWS service and resource on which data events are logged.
 - b. In **Log selector template**, choose **Custom**. Choosing **Custom** lets you define a custom event selector to filter on the `eventName`, `resources.ARN`, and `readOnly` fields. For information about these fields, see [AdvancedFieldSelector](#) in the *AWS CloudTrail API Reference*.
 - c. (Optional) In **Selector name**, enter a name to identify your selector. The selector name is a descriptive name for an advanced event selector, such as "Log DeleteObject API calls for a specific S3 bucket". The selector name is listed as Name in the advanced event selector and is viewable if you expand the **JSON view**.

▼ JSON view

```
[
  {
    "Name": "Log DeleteObject API calls for a specific S3 bucket"
    "FieldSelectors": [
      {
        "Field": "eventCategory",
        "Equals": [
          "Data"
        ]
      },
      {
        "Field": "resources.type",
        "Equals": [
          "AWS::S3::Object"
        ]
      }
    ]
  }
]
```

- d. In **Advanced event selectors**, we'll build the custom event selector to filter on the `eventName` and `resources.ARN` fields. Advanced event selectors for an event data store work the same as advanced event selectors that you apply to a trail. For more information about how to build advanced event selectors, see [Logging data events with advanced event selectors](#).
 - i. For **Field** choose **eventName**. For **Operator**, choose **equals**. For **Value**, enter **DeleteObject**. Choose **+ Field** to filter on another field.
 - ii. For **Field**, choose **resources.ARN**. For **Operator**, choose **StartsWith**. For **Value**, enter the ARN for your bucket (for example, `arn:aws:s3:::amzn-s3-demo-bucket`). For information about how to get the ARN, see [Amazon S3 resources](#) in the *Amazon Simple Storage Service User Guide*.

Data events [Info](#)

Data events show information about the resource operations performed on or within a resource.

▼ Data event: S3

Remove

Resource type
Choose the resource type for which you want to log data events.

S3 ▼

Log selector template

Custom ▼

Selector name - optional

Log DeleteObject API calls for a specific bucket

1,000 character limit

Collect events
Log all events, or choose a template to log specific, filtered events to your event data store. You can edit templates later.

Advanced event selectors [Info](#)
Log or exclude events based on the values of advanced event selector fields.

Field	Operator	Value	
eventName ▼	equals ▼	DeleteObject	×
AND			
resources.ARN ▼	starts with ▼	arn:aws:s3:::amzn-s3-demo-bucket	×
+ Field + Condition			

► JSON view

Add data event type

18. Choose **Next** to review your choices.
19. On the **Review and create** page, review your choices. Choose **Edit** to make changes to a section. When you're ready to create the event data store, choose **Create event data store**.
20. The new event data store is visible in the **Event data stores** table on the **Event data stores** page.

From this point forward, the event data store captures events that match its advanced event selectors. Events that occurred before you created the event data store are not in the event data store, unless you opted to copy existing trail events.

You are now ready to run queries on your event data store. For information about how to view and run sample queries, see [View sample queries with the CloudTrail console](#).

For more information about CloudTrail Lake, see [Working with AWS CloudTrail Lake](#).

Viewing your CloudTrail cost and usage with AWS Cost Explorer


This section describes how you can view your CloudTrail costs and usage using [AWS Cost Explorer](#). Cost Explorer gives you the ability to visualize, understand, and manage your AWS costs and usage over time.

For details about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

To view CloudTrail cost and usage with Cost Explorer

1. Sign in to the AWS Management Console and open the Cost Explorer console at <https://console.aws.amazon.com/cost-management/home#/custom>.
2. Under **Time**, choose the date range you want to analyze.
3. Under **Group by**, for **Dimension**, choose **Usage type**.
4. Under **Filters**, for **Service**, choose **CloudTrail**.

The following image shows an example of a cost report filtered for CloudTrail and grouped by **Usage type**.



Review the **Usage type** to see which CloudTrail features generated the most cost. Each **Usage type** begins with the code for the AWS Region where the charge was incurred.

The following table describes the CloudTrail usage types for each CloudTrail feature.

CloudTrail feature	Usage type	Description
CloudTrail trails	<i>region</i> -FreeEventsRecorded	The first copy of management events delivered free of charge to an AWS Region.
CloudTrail trails	<i>region</i> -PaidEventsRecorded	The charge for additional copies of management events delivered to an AWS Region.
CloudTrail trails	<i>region</i> -DataEventsRecorded	The charge for delivery of data events to an AWS Region. Data events always incur charges.
CloudTrail trails	<i>region</i> -NetworkEventsRecorded	The charge for delivery of network activity events to an AWS Region. Network activity events always incur charges.

CloudTrail feature	Usage type	Description
CloudTrail Lake	<i>region</i> -Ingestion-Bytes	The charge for ingesting events into a CloudTrail Lake event data store using the Seven-year retention pricing option. Ingestion pricing is based on the volume of data ingested and is the same for all event types.
CloudTrail Lake	<i>region</i> -Ingestion-Bytes-1yearstore-Live-CloudTrail-Logs	The charge for ingesting CloudTrail data events, network activity events, and management events into a CloudTrail Lake event data store using the One-year extendable retention pricing option.

CloudTrail feature	Usage type	Description
CloudTrail Lake	<i>region</i> -Ingestion-Bytes-1yearstore-Other-data-sources	The charge for ingesting other event sources into a CloudTrail Lake event data store using the One-year extendable retention pricing option. This includes CloudTrail Insights events, configuration items from AWS Config, evidence from AWS Audit Manager, (uncompressed) historical CloudTrail logs imported from S3, and events outside of AWS.

CloudTrail feature	Usage type	Description
CloudTrail Lake	<i>region</i> -QueryScanned-Bytes	The charge for running CloudTrail Lake queries. When you run queries in CloudTrail Lake, you incur charges based on the amount of optimized and compressed data scanned.
CloudTrail Insights	<i>region</i> -InsightsEvents	The charge for CloudTrail Insights events. For Insights events, you incur charges based on the number of management events analyzed per Insight type. For more information, see Costs for Insights events .

Using AWS Budgets to manage costs

AWS Budgets a feature of AWS Billing and Cost Management, allows you to set custom budgets that alert you when your costs or usage exceed (or are forecasted to exceed) your budgeted amount.

Creating a budget for CloudTrail by using AWS Budgets is a recommended best practice, and can help you track your CloudTrail spending. Cost-based budgets help promote awareness of how much you might be billed for your CloudTrail use. [Budget alerts](#) notify you when your bill reaches a threshold that you define. When you receive a budget alert, you can make changes before the end of the billing cycle to manage your costs.

 Note

Though you can apply tags to CloudTrail trails, AWS Billing cannot currently use tags applied to trails for cost allocation. Cost Explorer can show costs for CloudTrail Lake event data stores and for the CloudTrail service as a whole.

To get started with AWS Budgets, open [AWS Billing and Cost Management](#), and then choose **Budgets** in the left navigation bar. We recommend configuring budget alerts as you create a budget to track CloudTrail spending. For more information about how to use AWS Budgets, see [Managing your costs with AWS Budgets](#) and [Best practices for AWS Budgets](#).

Creating user-defined cost allocation tags for CloudTrail Lake event data stores

You can create [user-defined cost allocation tags](#) to track the query and ingestion costs for your CloudTrail Lake event data stores. A *user-defined cost allocation tag* is a key-value pair that you can associate with an event data store. After you activate cost allocation tags, AWS uses the tags to organize your resource costs on your cost allocation report.

- To create tags in the console, see step 9 of the [To create an event data store for CloudTrail events](#) procedure.
- To create tags using the CloudTrail API, see [CreateEventDataStore](#) and [AddTags](#) in the *AWS CloudTrail API Reference*.
- To create tags using the AWS CLI, see [create-event-data-store](#) and [add-tags](#) in the *AWS CLI Command Reference*.

For more information about activating tags, see [Activating user-defined cost allocation tags](#).

Managing CloudTrail trail costs

You can configure and manage CloudTrail trails in ways that capture the data you need while remaining cost-effective. For more information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Trail configuration

CloudTrail offers flexibility in how you configure trails in your account. Some decisions that you make during the setup process require that you understand the impacts to your CloudTrail bill. The following are examples of how trail configurations can influence your CloudTrail bill.

Multiple trail creation

The first copy of management events within each region is delivered free of charge. For example, if your account has 2 single-Region trails, a trail in us-east-1 and another trail in us-west-2, there are no CloudTrail charges because there is only one trail logging events in each respective Region. However, if your account has a multi-Region trail and an additional single-Region trail, the single-Region trail will incur charges because the multi-Region trail is already logging events in each Region.

If you create more trails that deliver the same management events to other destinations, those subsequent deliveries incur CloudTrail costs. You can do this to allow different user groups (such as developers, security personnel, and IT auditors) to receive their own copies of log files. For data events, all deliveries incur CloudTrail costs, including the first.

As you create more trails, it is especially important to be familiar with your logs, and understand the types and volumes of events that are generated by resources in your account. This helps you anticipate the volume of events that are associated with an account, and plan for trail costs. For example, using AWS KMS-managed server-side encryption (SSE-KMS) on your S3 buckets can result in a large number of AWS KMS management events in CloudTrail. Larger volumes of events across multiple trails can also influence costs.

To help limit the number of events that are logged to your trail, you can filter out AWS KMS or Amazon RDS Data API events by choosing **Exclude AWS KMS events** or **Exclude Amazon RDS Data API events** on the **Create trail** or **Update trail** pages. When using basic event selectors, you can only filter management events. However, you can use advanced event selectors to filter both management and data events.

You can use advanced event selectors to include or exclude data events, giving you the ability to log only the data events of interest. For more information, see [Filtering data events by using advanced event selectors](#).

You can use advanced event selectors to include or exclude network activity events based on the `eventName`, `resources.type`, `resources.ARN`, `errorCode`, and `vpcEndpointId` fields, giving you the ability to log only the data events of interest. For more information, see [Logging network activity events](#).

For more information about creating and updating a trail, see [Creating a trail with the CloudTrail console](#) or [Updating a trail with the CloudTrail console](#) in this guide.

AWS Organizations

When you set up an Organizations trail with CloudTrail, CloudTrail replicates the trail to each member account within your organization. The new trail is created *in addition to* any existing trails in member accounts. Be sure that the configuration of your organization trail matches how you want trails configured for all accounts within an organization, because the organization trail configuration propagates to all accounts.

Because Organizations creates a trail in each member account, an individual member account that creates an additional trail to collect the same management events as the Organizations trail is collecting a second copy of events. The account is charged for the second copy. Similarly, if an account has a multi-Region trail, and creates a second trail in a single Region to collect the same management events as the multi-Region trail, the trail in the single Region is delivering a second copy of events. The second copy incurs charges.

See also

- [AWS CloudTrail Pricing](#)
- [Managing your costs with AWS Budgets](#)
- [Getting started with Cost Explorer](#)
- [Prepare for creating a trail for your organization](#)

Managing CloudTrail Lake costs

AWS CloudTrail Lake event data stores and queries incur charges. You can configure event data stores in ways that capture the data you need while remaining cost-effective. For information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Topics

- [Event data store pricing options](#)
- [Understanding CloudTrail Lake charges](#)
- [Recommendations for how you can reduce costs](#)
- [See also](#)

Event data store pricing options

When you create an event data store, you choose the pricing option that you want to use for the event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention periods for the event data store.

The following table describes the available pricing options. The table shows the **Pricing option** in the console and the corresponding `BillingMode` value for the API, and lists the default and maximum retention period for each option.

Pricing option (console)	BillingMode (API)	Description
One-year extendable retention pricing	EXTENDABLE_RETENTION_PRICING	Recommended if you expect to ingest less than 25 TB of event data per month and want a flexible retention period of up to 10 years. This option is also recommended if your event data store collects AWS Config configuration items, Audit Manager evidence, and events from outside of AWS. For the first 366 days (the default retention period), storage is included at no additional cost with ingestion pricing. After 366 days,

Pricing option (console)	BillingMode (API)	Description
		extended retention is available at pay-as-you-go pricing. This is the default option. Default retention period: 366 days Maximum retention period: 3,653 days
Seven-year retention pricing	FIXED_RETENTION_PRICING	Recommended if expect to ingest more than 25 TB of event data per month and need a retention period of up to 7 years. Retention is included with ingestion pricing at no additional charge. Default retention period: 2,557 days Maximum retention period: 2,557 days

Understanding CloudTrail Lake charges

The following tables provides information about how CloudTrail Lake event data stores and queries incur charges. For information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Charge type	How you incur charges
Data ingestion (uncompressed data)	For CloudTrail Lake, you pay based on the uncompressed data ingested. The pricing option for the event data store determines the cost of ingesting events: • One-year extendable retention pricing: Offers ingestion pricing based on event type. • Seven-year retention pricing: Offers ingestion pricing based on the volume of data ingested. The greatest savings are

Charge type	How you incur charges
	achieved when the volume of data ingested monthly exceeds 25 TB. Copying trail events When you copy trail events to CloudTrail Lake, CloudTrail unzips the logs that are stored in gzip (compressed) format. Then CloudTrail copies the events contained in the logs to your event data store. The size of the uncompressed data could be greater than the actual Amazon S3 storage size. To get a general estimate of the size of the uncompressed data, multiply the size of the logs in the S3 bucket by 10.  Note CloudTrail will not copy an event if its event time is older than the specified retention period. To determine the appropriate retention period, take the sum of the oldest event you want to copy in days and the number of days you want to retain the events in the event data store as demonstrated in this equation: Retention period = <i>oldest-event-in-days</i> + <i>number-days-to-retain</i> For example, if the oldest event you're copying is 45 days old and you want to keep the events in the event data store for a further 45 days, you would set the retention period to 90 days.

Charge type	How you incur charges
Data retention (optimized and compressed data)	CloudTrail Lake converts existing events in row-based JSON format to Apache ORC format. ORC is a columnar storage format that is optimized for fast retrieval of compressed data. An event data store's <i>retention period</i> determines how long event data is kept in the event data store. CloudTrail Lake determines whether to retain an event by checking if an event's event time is within the specified retention period. For example, if you specify a retention period of 90 days, CloudTrail Lake will remove events when their event time is older than 90 days. For event data stores using the Seven-year retention pricing option, storage is included with ingestion pricing at no additional charge. For event data stores using the One-year extendable retention pricing option, storage is included at no charge with ingestion pricing for the first 366 days (the default retention period). After 366 days, storage is offered at pay-as-you-price and is charged based on the optimized and compressed data in the event data store.
Running queries in CloudTrail Lake (optimized and compressed data)	When you run queries in CloudTrail Lake, you pay based on the amount of optimized and compressed data scanned.

Recommendations for how you can reduce costs

This section provides recommendations for how you can reduce costs when working with CloudTrail Lake.

Choose a pricing option based on the type of events your event data store will collect and your expected monthly ingestion

When creating an event data store, choose a pricing option based on the type of events your event data store will collect and your expected monthly ingestion.

If you expect to ingest less than 25 TB of event data on a monthly basis and want a flexible retention period of up to 10 years, choose the **One-year extendable retention pricing** option. We also generally recommend this option for event data stores that collect AWS Config configuration items, Audit Manager evidence, and events from outside of AWS.

If you expect to ingest more than 25 TB of event data on a monthly basis and need a 7-year retention period, choose the **Seven-year retention pricing** option.

Evaluate your event data store's monthly ingestion over time

Evaluate the historical monthly ingestion of your event data store to see if there's a pricing option better suited to your needs.

If you have an existing event data store that uses the **Seven-year retention pricing** option and you ingest less than 25 TB of data on a monthly basis, consider updating the event data store to use **One-year extendable retention pricing**. For event data stores using the **Seven-year retention pricing** option, you can change the pricing option using the [CloudTrail console](#), [AWS CLI](#), or [UpdateEventDataStore](#) API operation.

If you have an existing event data store that uses the **One-year extendable retention pricing** option and you ingest more than 25 TB of event data on a monthly basis, consider whether **Seven-year retention pricing** would better suit your needs. To use the new pricing option, [stop ingestion](#) on your event data store and create a new event data store with the **Seven-year retention pricing** option.

Use advanced event selectors to filter out events that aren't of interest

When configuring an event data store for CloudTrail management events, data events, or network activity events, you can filter out events that aren't of interest by using advanced event selectors.

You can filter management events on the following advanced event selector fields: `eventName`, `eventSource`, `eventType`, `readOnly`, `sessionCredentialFromConsole`, and `userIdentity.arn`.

You can filter data events on the following advanced event selector fields: `eventName`, `eventSource`, `eventType`, `resources.type`, `resources.ARN`, `readOnly`, `sessionCredentialFromConsole`, and `userIdentity.arn`. For more information, see [Filtering data events by using advanced event selectors](#).

You can filter network activity events on the following advanced event selector fields: `eventName`, `errorCode`, and `vpcEndpointId`. For more information, see [Logging network activity events](#).

Choose a narrower time range when copying trail events

When copying trail events to CloudTrail Lake, specify a narrower start event time and end event time to reduce the amount of data ingested.

If you are copying trail events to CloudTrail Lake for historical analysis and do not want to ingest future events, deselect the option to ingest events so that you do not incur charges on ingesting any additional events.

Format queries to use a starting and ending eventTime

When you run queries in Lake, you pay based upon the amount of data scanned. You can constrain costs by specifying a starting and ending eventTime for the query.

See also

- [AWS CloudTrail Pricing](#)
- [Supported CloudWatch metrics](#)
- [Managing your costs with AWS Budgets](#)
- [Getting started with Cost Explorer](#)

Working with CloudTrail event history

CloudTrail is enabled by default for your AWS account and you automatically have access to the CloudTrail event history. The event history provides a viewable, searchable, downloadable, and immutable record of the past 90 days of management events in an AWS Region. These events capture activity made through the AWS Management Console, AWS Command Line Interface, and AWS SDKs and APIs. The event history records events in the AWS Region where the event happened. There are no CloudTrail charges for viewing the event history.

You can look up events related to the creation, modification, or deletion of resources (such as IAM users or Amazon EC2 instances) in your AWS account on a by-Region basis on the CloudTrail console by viewing the **Event history** page. You can also look up these events by running the [aws cloudtrail lookup-events](#) command or by using the [LookupEvents](#) API.

You can use the **Event history** page on the CloudTrail console to view, search, download, archive, analyze, and respond to account activity across your AWS infrastructure. You can [customize the view](#) of the **Event history** page on the console by selecting how many events to display on each page and which columns to display or hide. You can also compare the details of events in event history side-by-side. You can programmatically [look up events](#) by using the AWS SDKs or AWS Command Line Interface.

Note

Over time, AWS services might add additional events. CloudTrail records these events in event history, but a full 90-day record of activity that includes added events won't be available until 90 days after it adds the events.

The event history is separate from any trails or event data stores that you create for your account. Changes you make to your event data stores or trails do not affect the event history.

The sections which follow describe how to look up recent management events by using the CloudTrail console and the AWS CLI, and describe how to download a file of events. For information about using the `LookupEvents` API to retrieve information from CloudTrail events, see [LookupEvents](#) in the *AWS CloudTrail API Reference*.

Topics

- [Limitations of Event history](#)
- [Viewing recent management events with the console](#)
- [Viewing recent management events with the AWS CLI](#)

Limitations of Event history

The following limitations apply to the event history.

- The **Event history** page on the CloudTrail console only shows management events. It does not show data events, Insights events, or network activity events.
- The event history is limited to the past 90 days of events. For an ongoing record of events in your AWS account, create an [event data store](#) or a [trail](#).
- When you download events from the **Event history** page on the CloudTrail console, you can download up to 200,000 events in a single file. If you reach the 200,000 event limit, the CloudTrail console will provide the option to download additional files.
- The event history doesn't provide organization level event aggregation. To record events across your organization, create an organization event data store or trail.
- An event history search is limited to a single AWS account, only returns events from a single AWS Region, and cannot query multiple attributes. You can only apply one attribute filter and a time range filter.

You can create a CloudTrail Lake event data store to query across multiple attributes and AWS Regions. You can also query across multiple AWS accounts in an AWS Organizations organization. In CloudTrail Lake, you can query multiple event types, including management events, data events, Insights events, AWS Config configuration items, Audit Manager evidence, and non-AWS events. CloudTrail Lake queries offer a deeper and more customizable view of events than simple key and value lookups on the **Event history** page, or by running `LookupEvents`. For more information, see [Working with AWS CloudTrail Lake](#) and [Create an event data store for CloudTrail events with the console](#).

- You cannot exclude AWS KMS or Amazon RDS Data API events from event history; settings that you apply to a trail or event data store do not apply to event history.

Viewing recent management events with the console

You can use the **Event history** page in the CloudTrail console to view the last 90 days of management events in an AWS Region. You can also download a file with that information, or a subset of information based on the filter and time range you choose. You can customize your view of **Event history** by selecting how many events to display on each page and choosing which columns to display on the console. You can also look up and filter events by the resource types available for a particular service. You can select up to five events in **Event history** and compare their details side-by-side.

Event history does not show data events. To view data events, create an [event data store](#) or a [trail](#).

After 90 days, events are no longer shown in event history. You cannot manually delete events from event history.

You can learn more about the specifics of how CloudTrail logs events for a specific service by consulting the documentation for that service. For more information, see [AWS service topics for CloudTrail](#).

Note

For an ongoing record of activity and events past 90 days, create an [event data store](#) or a [trail](#).

To view Event history

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, choose **Event history**. You see a filtered list of events, with the most recent events showing first. The default filter for events is **Read only**, set to **false**. You can clear that filter by choosing **X** at the right of the filter.
3. You can filter events on a single attribute, which you can choose from the drop-down list. To filter on an attribute, choose the attribute from the drop-down list and enter the full value for the attribute. For example, to view all console login events, choose the **Event name** filter, and specify **ConsoleLogin**. Or, to view recent S3 management events, choose the **Event source** filter, and specify **s3.amazonaws.com**.

4. To view a specific management event, choose the event name. On the event details page, you can view details about the event, see any referenced resources, and view the event record.
5. To compare events, select up to five events by filling their check boxes in the left margin of the **Event history** table. You can view details for the selected events side-by-side in the **Compare event details** table.
6. You can save event history by downloading it as a file in CSV or JSON format. Downloading your event history can take a few minutes.

Contents

- [Navigating between pages](#)
- [Customizing the display](#)
- [Filtering CloudTrail events](#)
- [Viewing details for an event](#)
- [Downloading events](#)
- [Viewing resources referenced with AWS Config](#)

Navigating between pages

You can navigate between pages in the **Event history** by choosing the page you want to view. You can also view the next and previous page in **Event history**.

Choose < to view the previous page of **Event history**.

Choose > to view the next page of **Event history**.

Customizing the display

You can customize the view of **Event history** on the CloudTrail console by selecting from the following preferences.

- **Page size** - Choose whether you want to display 10, 25, or 50 events on each page.
- **Wrap lines** - Wrap text so you can see all text for each event.
- **Striped rows** - Shade every other row in the table.
- **Event time display** - Choose whether to display the event time in UTC or the local time zone.

- **Select visible columns** - Select which columns to display. By default, the following columns are displayed:
 - **Event name**
 - **Event time**
 - **User name**
 - **Event source**
 - **Resource type**
 - **Resource name**

 Note

You cannot change the order of the columns, or manually delete events from **Event history**.

To customize the display

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, choose **Event history**.
3. Choose the gear icon.
4. For **Page size**, choose the number of events to display on a page.
5. Choose **Wrap lines** to see all text for each event.
6. Choose **Striped rows** to shade every other row in the table.
7. For **Event time display**, choose whether to display the event time in UTC or the local time zone. By default, UTC is selected.
8. In **Select visible columns**, select the columns you want to display. Turn off columns you do not want to display.
9. When you have finished making your changes, choose **Confirm**.

Filtering CloudTrail events

The default display of events in **Event history** uses an attribute filter to exclude read-only events from the list of displayed events. This attribute filter is named **Read-only**, and it is set to **false**.

You can remove this filter to display both read and write events. To view only **Read** events, you can change the filter value to **true**. You can also filter events by other attributes. You can additionally filter by time range.

 Note

You can only apply one attribute filter and a time range filter. You cannot apply multiple attribute filters.

AWS access key

The AWS access key ID that was used to sign the request. If the request was made with temporary security credentials, this is the access key ID of the temporary credentials.

Event ID

The CloudTrail ID of the event. Each event has a unique ID.

Event name

The name of the event. For example, you can filter on IAM events, such as `CreatePolicy`, or Amazon EC2 events, such as `RunInstances`.

Event source

The AWS service to which the request was made, such as `iam.amazonaws.com` or `s3.amazonaws.com`. You can scroll through a list of event sources after you choose the **Event source** filter.

Read only

The read type of the event. Events are categorized as read events or write events. If set to **false**, read events are not included in the list of displayed events. By default, this attribute filter is applied and the value is set to **false**.

Resource name

The name or ID of the resource referenced by the event. For example, the resource name might be "auto-scaling-test-group" for an Auto Scaling group or "i-12345678910" for an EC2 instance.

Resource type

The type of resource referenced by the event. For example, a resource type can be `Instance` for EC2 or `DBInstance` for RDS. Resource types vary for each AWS service.

Time range

The time range in which you want to filter events. You can choose either a **Relative range** or an **Absolute range**. You can filter events for the last 90 days.

User name

The identity referenced by the event. For example, this can be a user, a role name, or a service role.

If there are no events logged for the attribute or time that you choose, the results list is empty. You can apply only one attribute filter in addition to the time range. If you choose a different attribute filter, your specified time range is preserved.

The following steps describe how to filter by attribute.

To filter by attribute

1. To filter the results by an attribute, choose an attribute from the **Lookup attributes** drop-down list, and then type or choose a value for the attribute in the text box.
2. To remove an attribute filter, choose the **X** at the right of the attribute filter box.

The following steps describe how to filter by a start and end date and time.

To filter by a start and end date and time

1. To narrow the time range for the events that you want to see, choose a time range in the time range bar. You can choose either a **Relative range** or an **Absolute range**.

Choose **Relative range** to select from a preset value or choose a custom range. Preset values are 30 minutes, 1 hour, 12 hours, or 1 day. To specify a custom time range, choose **Custom**.

Choose **Absolute range** to specify a specific start and end time. You can also choose between the local time zone or UTC.

2. To remove a time range filter, choose **Clear and dismiss** in the time range bar.

Viewing details for an event

1. Choose an event in the results list to show its details.

2. Resources referenced in the event are shown in the **Resources referenced** table on the event details page.
3. Some referenced resources have links. Choose the link to open the console for that resource.
4. Scroll to **Event record** on the details page to see the JSON event record, also called the event *payload*.
5. Choose **Event history** in the page breadcrumb to close the event details page and return to **Event history**.

Downloading events

You can download recorded event history as a file in CSV or JSON format. You can download up to 200,000 events in a single file. If you reach the 200,000 event limit, the CloudTrail console will provide the option to download additional files. Use filters and time ranges to reduce the size of the file you download.

Note

CloudTrail event history files are data files that contain information (such as resource names) that can be configured by individual users. Some data can potentially be interpreted as commands in programs used to read and analyze this data (CSV injection). For example, when CloudTrail events are exported to CSV and imported to a spreadsheet program, that program might warn you about security concerns. You should choose to disable this content to keep your system secure. Always disable links or macros from downloaded event history files.

1. Add a filter and time range for events in **Event history** that you want to download. For example, you can specify the event name, `StartInstances`, and specify a time range for the last three days of activity.
2. Choose **Download events**, and then choose **Download as CSV** or **Download as JSON**. The download starts immediately.

Note

Your download might take some time to complete. For faster results, before you start the download process, use a more specific filter or a shorter time range to narrow

the results. You can cancel a download. If you cancel a download, a partial download including only some event data might be on your local computer. To download the full event history, restart the download.

3. After your download is complete, open the file to view the events that you specified.
4. To cancel your download, choose **Cancel**, and then confirm by choosing **Cancel download**. If you need to restart a download, wait until the earlier download is finished canceling.

Viewing resources referenced with AWS Config

AWS Config records configuration details, relationships, and changes to your AWS resources.

On the **Resources referenced** pane, choose the



in the **AWS Config resource timeline** column to view the resource in the AWS Config console.

If the



icon is gray, AWS Config isn't turned on, or it's not recording the resource type. Choose the icon to go to the AWS Config console to turn on the service or start recording that resource type. For more information, see [Set Up AWS Config Using the Console](#) in the *AWS Config Developer Guide*.

If **Link not available** appears in the column, the resource can't be viewed for one of the following reasons:

- AWS Config doesn't support the resource type. For more information, see [Supported Resources, Configuration Items, and Relationships](#) in the *AWS Config Developer Guide*.
- AWS Config recently added support for the resource type, but it's not yet available from the CloudTrail console. You can look up the resource in the AWS Config console to see the timeline for the resource.
- The resource is owned by another AWS account.
- The resource is owned by another AWS service, such as a managed IAM policy.
- The resource was created and then deleted immediately.
- The resource was recently created or updated.

To grant users read-only permission to view resources in the AWS Config console, see [Granting permission to view AWS Config information on the CloudTrail console](#).

For more information about AWS Config, see the [AWS Config Developer Guide](#).

Viewing recent management events with the AWS CLI

You can look up CloudTrail management events for the last 90 days for the current AWS Region using the **aws cloudtrail lookup-events** command. The **aws cloudtrail lookup-events** command shows events in the AWS Region where they occurred.

Lookup supports the following attributes for management events:

- AWS access key
- Event ID
- Event name
- Event source
- Read only
- Resource name
- Resource type
- User name

All attributes are optional.

The [lookup-events](#) command includes the following options:

- **--max-items** *<integer>* – The total number of items to return in the command's output. If the total number of items available is more than the value specified, a NextToken is provided in the command's output. To resume pagination, provide the NextToken value in the starting-token argument of a sub-sequent command. Do not use the NextToken response element directly outside of the AWS CLI.
- **--start-time** *<timestamp>* – Specifies that only events that occur after or at the specified time are returned. If the specified start time is after the specified end time, an error is returned.
- **--lookup-attributes** *<integer>* – Contains a list of lookup attributes. Currently the list can contain only one item.

- `--generate-cli-skeleton <string>` – Prints a JSON skeleton to standard output without sending an API request. If provided with no value or the value `input`, prints a sample input JSON that can be used as an argument for `--cli-input-json`. Similarly, if provided `yaml-input` it will print a sample input YAML that can be used with `--cli-input-yaml`. If provided with the value `output`, it validates the command inputs and returns a sample output JSON for that command. The generated JSON skeleton is not stable between versions of the AWS CLI and there are no backwards compatibility guarantees in the JSON skeleton generated.
- `--cli-input-json <string>` – Reads arguments from the JSON string provided. The JSON string follows the format provided by the `--generate-cli-skeleton` parameter. If other arguments are provided on the command line, those values will override the JSON-provided values. It is not possible to pass arbitrary binary values using a JSON-provided value as the string will be taken literally. This may not be specified along with the `--cli-input-yaml` parameter.

For general information about using the AWS Command Line Interface, see the [AWS Command Line Interface User Guide](#).

Contents

- [Prerequisites](#)
- [Getting command line help](#)
- [Looking up events](#)
- [Specifying the number of events to return](#)
- [Looking up events by time range](#)
- [Looking up events by attribute](#)
 - [Attribute lookup examples](#)
- [Specifying the next page of results](#)
- [Getting JSON input from a file](#)
- [Lookup output fields](#)

Prerequisites

- To run AWS CLI commands, you must install the AWS CLI. For information, see [Get started with the AWS CLI](#).
- Make sure your AWS CLI version is greater than 1.6.6. To verify the CLI version, run **aws --version** on the command line.

- To set the account, AWS Region, and default output format for an AWS CLI session, use the **aws configure** command. For more information, see [Configuring the AWS Command Line Interface](#).

Note

The CloudTrail AWS CLI commands are case-sensitive.

Getting command line help

To see the command line help for `lookup-events`, type the following command:

```
aws cloudtrail lookup-events help
```

Looking up events

Important

The rate of lookup requests is limited to two per second, per account, per Region. If this limit is exceeded, a throttling error occurs.

To see the ten latest events, type the following command:

```
aws cloudtrail lookup-events --max-items 10
```

A returned event looks similar to the following fictitious example, which has been formatted for readability:

```
{
  "NextToken": "kb0t5LlZe+
+mErCebpy2TgaMgmDvF1kYGFcH64JSjIbZFjsuvrSqq66b5YGssKutDYIyII4lrP4IDbeQdi0bkp9YA1ju3oXd12juy3CIZ
  "Events": [
    {
      "EventId": "0ebbaee4-6e67-431d-8225-ba0d81df5972",
      "Username": "root",
      "EventTime": 1424476529.0,
```

```

    "CloudTrailEvent": "{
      \"eventVersion\": \"1.02\",
      \"userIdentity\": {
        \"type\": \"Root\",
        \"principalId\": \"111122223333\",
        \"arn\": \"arn:aws:iam::111122223333:root\",
        \"accountId\": \"111122223333\"},
      \"eventTime\": \"2015-02-20T23:55:29Z\",
      \"eventSource\": \"signin.amazonaws.com\",
      \"eventName\": \"ConsoleLogin\",
      \"awsRegion\": \"us-east-2\",
      \"sourceIPAddress\": \"203.0.113.4\",
      \"userAgent\": \"Mozilla/5.0\",
      \"requestParameters\": null,
      \"responseElements\": {\"ConsoleLogin\": \"Success\"},
      \"additionalEventData\": {
        \"MobileVersion\": \"No\",
        \"LoginTo\": \"https://console.aws.amazon.com/console/home\",
        \"MFAUsed\": \"No\"},
      \"eventID\": \"0ebbaee4-6e67-431d-8225-ba0d81df5972\",
      \"eventType\": \"AwsApiCall\",
      \"recipientAccountId\": \"111122223333\"}",
    "EventName": "ConsoleLogin",
    "Resources": []
  }
}

```

For an explanation of the lookup-related fields in the output, see the section [Lookup output fields](#) later in this document. For an explanation of the fields in the CloudTrail event, see [CloudTrail record contents for management, data, and network activity events](#).

Specifying the number of events to return

To specify the number of events to return, type the following command:

```
aws cloudtrail lookup-events --max-items <integer>
```

Possible values are 1 through 50. The following example returns one event.

```
aws cloudtrail lookup-events --max-items 1
```

Looking up events by time range

Events from the past 90 days are available for lookup. To specify a time range, type the following command:

```
aws cloudtrail lookup-events --start-time <timestamp> --end-time <timestamp>
```

`--start-time <timestamp>` specifies, in UTC, that only events that occur after or at the specified time are returned. If the specified start time is after the specified end time, an error is returned.

`--end-time <timestamp>` specifies, in UTC, that only events that occur before or at the specified time are returned. If the specified end time is before the specified start time, an error is returned.

The default start time is the earliest date that data is available within the last 90 days. The default end time is the time of the event that occurred closest to the current time.

All timestamps are shown in UTC.

Looking up events by attribute

To filter by an attribute, type the following command:

```
aws cloudtrail lookup-events --lookup-attributes  
AttributeKey=<attribute>,AttributeValue=<string>
```

You can specify only one attribute key/value pair for each **lookup-events** command. The following are valid values for `AttributeKey`. Value names are case sensitive.

- AccessKeyId
- EventId
- EventName
- EventSource
- ReadOnly
- ResourceName
- ResourceType

- Username

The maximum length for the `AttributeValue` is 2000 characters. The following characters ('_', ' ', ',', '\n') count as two characters towards the 2000 character limit.

Attribute lookup examples

The following example command returns events in which the value of `AccessKeyId` is `AKIAIOSFODNN7EXAMPLE`.

```
aws cloudtrail lookup-events --lookup-attributes
  AttributeKey=AccessKeyId,AttributeValue=AKIAIOSFODNN7EXAMPLE
```

The following example command returns the event for the specified CloudTrail `EventId`.

```
aws cloudtrail lookup-events --lookup-attributes
  AttributeKey=EventId,AttributeValue=b5cc8c40-12ba-4d08-a8d9-2bceb9a3e002
```

The following example command returns events in which the value of `EventName` is `RunInstances`.

```
aws cloudtrail lookup-events --lookup-attributes
  AttributeKey=EventName,AttributeValue=RunInstances
```

The following example command returns events in which the value of `EventSource` is `iam.amazonaws.com`.

```
aws cloudtrail lookup-events --lookup-attributes
  AttributeKey=EventSource,AttributeValue=iam.amazonaws.com
```

The following example command returns write events. It excludes read events such as `GetBucketLocation` and `DescribeStream`.

```
aws cloudtrail lookup-events --lookup-attributes
  AttributeKey=ReadOnly,AttributeValue=false
```

The following example command returns events in which the value of `ResourceName` is `CloudTrail_CloudWatchLogs_Role`.

```
aws cloudtrail lookup-events --lookup-attributes
  AttributeKey=ResourceName,AttributeValue=CloudTrail_CloudWatchLogs_Role
```

The following example command returns events in which the value of `ResourceType` is `AWS::S3::Bucket`.

```
aws cloudtrail lookup-events --lookup-attributes
  AttributeKey=ResourceType,AttributeValue=AWS::S3::Bucket
```

The following example command returns events in which the value of `Username` is `root`.

```
aws cloudtrail lookup-events --lookup-attributes
  AttributeKey=Username,AttributeValue=root
```

Specifying the next page of results

To get the next page of results from a `lookup-events` command, type the following command:

```
aws cloudtrail lookup-events <same parameters as previous command> --next-token=<token>
```

where the value for `<token>` is taken from the first field of the output of the previous command.

When you use `--next-token` in a command, you must use the same parameters as in the previous command. For example, suppose you run the following command:

```
aws cloudtrail lookup-events --lookup-attributes
  AttributeKey=Username,AttributeValue=root
```

To get the next page of results, your next command would look like this:

```
aws cloudtrail lookup-events --lookup-attributes
  AttributeKey=Username,AttributeValue=root --next-token=kb0t5LlZe+
+mErCebpy2TgaMgmDvF1kYGFcH64JSjIbZFjsuvrSqq66b5YGssKutDYIyII4lrP4IDbeQdi0bkp9YA1ju3oXd12juy3CIZ
```

Getting JSON input from a file

The AWS CLI for some AWS services has two parameters, `--generate-cli-skeleton` and `--cli-input-json`, that you can use to generate a JSON template which you can modify and use as

input to the `--cli-input-json` parameter. This section describes how to use these parameters with `aws cloudtrail lookup-events`. For more general information, see [AWS CLI skeletons and input files](#).

To look up CloudTrail events by getting JSON input from a file

1. Create an input template for use with `lookup-events` by redirecting the `--generate-cli-skeleton` output to a file, as in the following example.

```
aws cloudtrail lookup-events --generate-cli-skeleton > LookupEvents.txt
```

The template file generated (in this case, `LookupEvents.txt`) looks like this:

```
{
  "LookupAttributes": [
    {
      "AttributeKey": "",
      "AttributeValue": ""
    }
  ],
  "StartTime": null,
  "EndTime": null,
  "MaxResults": 0,
  "NextToken": ""
}
```

2. Use a text editor to modify the JSON as needed. The JSON input must contain only values that are specified.

Important

All empty or null values must be removed from the template before you can use it.

The following example specifies a time range and maximum number of results to return.

```
{
  "StartTime": "2023-11-01",
  "EndTime": "2023-12-12",
  "MaxResults": 10
}
```



```
}
```

3. To use the edited file as input, use the syntax `--cli-input-json file://<filename>`, as in the following example:

```
aws cloudtrail lookup-events --cli-input-json file://LookupEvents.txt
```

Note

You can use other arguments on the same command line as `--cli-input-json`.

Lookup output fields

Events

A list of lookup events based on the lookup attribute and time range that were specified. The events list is sorted by time, with the latest event listed first. Each entry contains information about the lookup request and includes a string representation of the CloudTrail event that was retrieved.

The following entries describe the fields in each lookup event.

CloudTrailEvent

A JSON string that contains an object representation of the event returned. For information about each of the elements returned, see [Record Body Contents](#).

EventId

A string that contains the GUID of the event returned.

EventName

A string that contains the name of the event returned.

EventSource

The AWS service that the request was made to.

EventTime

The date and time, in UNIX time format, of the event.

Resources

A list of resources referenced by the event that was returned. Each resource entry specifies a resource type and a resource name.

ResourceName

A string that contains the name of the resource referenced by the event.

ResourceType

A string that contains the type of a resource referenced by the event. When the resource type cannot be determined, null is returned.

Username

A string that contains the user name of the account for the event returned.

NextToken

A string to get the next page of results from a previous `lookup-events` command. To use the token, the parameters must be the same as those in the original command. If no `NextToken` entry appears in the output, there are no more results to return.

Working with CloudTrail Insights

AWS CloudTrail Insights help AWS users identify and respond to unusual activity associated with API call rates and API error rates by continuously analyzing CloudTrail management events. CloudTrail Insights analyzes your past management events to establish your normal patterns of API call rates and API error rates, also called the *baseline*. CloudTrail then generates Insights events when the current API call rates or error rates deviate from the baseline.

You can collect two types of Insights:

- **API call rate** – A measurement of write-only management API calls that occur per minute against a baseline API call volume. To log Insights events on the API call rate, the trail or event data store must enable Insights and log `write` management events.
- **API error rate** – A measurement of management API calls that result in error codes. The error is shown if the API call is unsuccessful. To log Insights events on API error rate, the trail or event data store must enable Insights and log `read` or `write` management events, or both `read` and `write` management events.

CloudTrail Insights analyzes the management events that occur in each Region for the trail or event data store and generates an Insights event when unusual activity is detected that deviates from the baseline. A CloudTrail Insights event is generated in the same Region as its supporting management event is generated.

Additional charges apply for Insights events. You will be charged separately if you enable Insights for both trails and event data stores. For more information, see [AWS CloudTrail Pricing](#).

Topics

- [Costs for Insights events](#)
- [Delivery of Insights events](#)
- [Logging Insights events with the CloudTrail console](#)
- [Logging Insights events with the AWS CLI](#)
- [Viewing Insights events for trails](#)
- [Viewing Insights events for event data stores](#)

Costs for Insights events

When you enable Insights events on an existing trail or event data store, CloudTrail analyzes the past 28 days of management events collected by the trail or event data store to establish a baseline of normal activity. After the initial baseline is created, the baseline is recalculated every day on the past 28 days of data. There are no CloudTrail charges for the baseline analysis.

After the baseline analysis, you incur CloudTrail charges for any future management events analyzed by CloudTrail. You incur charges based on the number of management events analyzed for the enabled Insights types.

If you choose to log both Insights types for a trail or event data store that logs read and write management events, the total number of events analyzed will be greater than the total number of recorded management events. This is because CloudTrail will analyze the write-only management events twice, once for calculating the API call rate and again for determining the API error rate. The read-only management events will be analyzed once to calculate the API error rate.

You can identify the charges for Insights events on your bill by looking for the `InsightsEvents` usage type. For more information, see [Viewing your CloudTrail cost and usage with AWS Cost Explorer](#).

You will incur separate Insights events charges for each trail and event data store with Insights enabled. For more information about pricing, see [AWS CloudTrail Pricing](#).

Example 1 – Enable Insights for API call rate and API error rate on a trail

In this first example, you enable Insights on a trail and choose to collect both Insights types. The trail in this example is logging both read and write management events.

- CloudTrail analyzes the management events logged in the past 28 days to form a baseline. There are no CloudTrail charges for the analysis.
- After the baseline is created, the trail logs 300,000 management events, of which 270,000 are read management events and 30,000 are write management events.
 - The write management events are analyzed twice, once for the API call rate and once for the API error rate ($30,000 * 2 = 60,000$).
 - The read management events are analyzed once for the API error rate ($270,000 * 1 = 270,000$).
 - The total management events analyzed is 330,000 ($60,000 + 270,000$). You will incur costs for analyzing 330,000 management events for this trail. You will be charged separately if you enable Insights for another trail or an event data store.

Example 2 – Enable Insights for two trails

In this next example, you enable Insights on two trails, trail A and trail B. You choose to enable API call rate Insights only on trail A and API error rate Insights only on trail B. Both trails log read and write management events.

- CloudTrail analyzes the write management events logged in the past 28 days to form a baseline. There are no CloudTrail charges for the analysis.
- After the baseline is created, the trails log 800,000 management events, of which 710,000 are read events and 90,000 are write events.

For trail A, the following analysis occurs:

- The write management events are analyzed once for the API call rate ($90,000 * 1 = 90,000$).
- The read management events are not analyzed, because CloudTrail only analyzes write management events for API call rate Insights.
- The total management events analyzed is 90,000. You will incur costs for analyzing 90,000 management events for trail A.

For trail B, the following analysis occurs:

- The write management events are analyzed once for the API error rate ($90,000 * 1 = 90,000$).
- The read management events are analyzed once for the API error rate ($710,000 * 1 = 710,000$).
- The total management events analyzed is 800,000 ($90,000 + 710,000$). You will incur costs for analyzing 800,000 management events for trail B.

Example 3 – Enable Insights for API call rate and API error rate on a trail and an event data store

In this final example, you enable Insights for API call rate and API error rate on both a trail and an event data store. Both the trail and event data store are logging read and write management events. You will incur charges for CloudTrail Insights for the trail and event data store separately as you enabled Insights on both.

- CloudTrail analyzes the management events logged in the past 28 days to form a baseline. There are no CloudTrail charges for the analysis.
- After the baseline is created, the trail and event data store log 500,000 management events, of which 380,000 are read management events and 120,000 are write management events.

For the trail, the following analysis occurs:

- The `write` management events are analyzed twice for the trail, once for the API call rate and once for the API error rate ($120,000 * 2 = 240,000$).
- The `read` management events are analyzed once for the trail for the API error rate ($380,000 * 1 = 380,000$).
- The total management events analyzed for the trail is 620,000 ($240,000 + 380,000$). You will incur costs for analyzing 620,000 management events for the trail.

For the event data store, the following analysis occurs:

- The `write` management events are analyzed twice for the event data store, once for the API call rate and once for the API error rate ($120,000 * 2 = 240,000$).
- The `read` management events are analyzed once for the event data store for the API error rate ($380,000 * 1 = 380,000$).
- The total management events analyzed for the event data store is 620,000 ($240,000 + 380,000$). You will incur costs for analyzing 620,000 management events for the event data store.

Delivery of Insights events

Unlike other types of events that CloudTrail captures, Insights events are logged only when CloudTrail detects changes in your account's API usage that differ significantly from the account's typical usage patterns.

Where CloudTrail delivers events and how long it takes to receive Insights events differs between trails and event data stores.

Insights events delivery for trails

If you've enabled Insights events on a trail and CloudTrail detects unusual activity, CloudTrail delivers Insights events to the `/CloudTrail-Insight` folder in the chosen destination S3 bucket for your trail. After you enable CloudTrail Insights for the first time on a trail, CloudTrail may take up to 36 hours to begin delivering Insights events, provided that unusual activity is detected during that time.

If you turn off Insights events logging on a trail and then re-enable Insights events, or stop and restart logging on a trail, it can take up to 36 hours for CloudTrail to restart delivery of Insights events, provided that unusual activity is detected during that time.

Insights events delivery for event data stores

If you've enabled Insights events on a source event data store, CloudTrail delivers Insights events to the destination event data store. After you enable CloudTrail Insights for the first time on the source event data store, CloudTrail may take up to 7 days to begin delivering Insights events to the destination event data store, provided that unusual activity is detected during that time.

If you turn off Insights events logging on a source event data store and then re-enable Insights events, or stop and restart event ingestion on a source event data store, it can take up to 7 days for CloudTrail to restart delivery of Insights events, provided that unusual activity is detected during that time. Additional charges apply for ingesting Insights events in CloudTrail Lake. You will be charged separately if you enable Insights for both trails and event data stores. For information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Logging Insights events with the CloudTrail console

This section describes how you can enable Insights events on an existing trail or event data store using the CloudTrail console.

For more information about how to create a new trail to log Insights events, see [Creating a trail with the console](#).

For more information about how to create a new event data store to collect Insights events, see [Create an event data store for Insights events with the console](#).

Topics

- [Enabling CloudTrail Insights on an existing trail with the console](#)
- [Enabling CloudTrail Insights on an existing event data store with the console](#)

Enabling CloudTrail Insights on an existing trail with the console

Use the following procedure to enable CloudTrail Insights on an existing trail.

1. In the left navigation pane of the CloudTrail console, open the **Trails** page, and choose a trail name.

2. In **Insights events**, choose **Edit**.

 Note

Additional charges apply for logging Insights events. For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

3. In **Event type**, choose **Insights events**.
4. In **Insights events**, under **Choose Insights types**, choose **API call rate**, **API error rate**, or both. Your trail must be logging **Write** management events to log Insights events for **API call rate**. Your trail must be logging **Read** or **Write** management events to log Insights events for **API error rate**.
5. Choose **Save changes** to save your changes.

CloudTrail may take up to 36 hours to begin delivering Insights events after you enable Insights events on a trail, provided that unusual activity is detected during that time.

Enabling CloudTrail Insights on an existing event data store with the console

Use the following procedure to enable CloudTrail Insights on an existing event data store.

Additional charges apply for ingesting Insights events in CloudTrail Lake. You will be charged separately if you enable Insights for both trails and event data stores. For information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

 Note

You can only enable CloudTrail Insights on event data stores containing CloudTrail management events. You cannot enable CloudTrail Insights on other event data store types.

1. In the left navigation pane of the CloudTrail console, under **Lake**, choose **Event data stores**.
2. Choose the event data store name.
3. In **Management events**, choose **Edit**.

4. Choose **Enable Insights events capture**.
5. Choose the destination event store that will collect Insights events. The destination event data store will collect Insights events based upon the management event activity in this event data store. For information about how to create the destination event data store, see [To create a destination event data store that logs Insights events](#).
6. Choose the Insights types. You can choose **API call rate**, **API error rate**, or both. You must be logging **Write** management events to log Insights events for **API call rate**. You must be logging **Read** or **Write** management events to log Insights events for **API error rate**.
7. Choose **Save changes** to save your changes.

CloudTrail may take up to 7 days to begin delivering Insights events, provided that unusual activity is detected during that time.

Logging Insights events with the AWS CLI

You can configure your trails and event data stores to log Insights events using the AWS CLI.

Note

To log Insights events on the API call rate, the trail or event data store must log write management events. To log Insights events on the API error rate, the trail or event data store must log read or write management events.

Topics

- [Logging Insights events for a trail using the AWS CLI](#)
- [Logging Insights events for an event data store using the AWS CLI](#)

Logging Insights events for a trail using the AWS CLI

To return the current Insights selectors for a trail, run the `get-insight-selectors` command.

```
aws cloudtrail get-insight-selectors --trail-name TrailName
```

The following example response shows the Insights selectors for a trail named `insights-trail`.

```
{
  "TrailARN": "arn:aws:cloudtrail:us-east-1:123456789012:trail/insights-trail",
  "InsightSelectors": [
    {
      "InsightType": "ApiCallRateInsight"
    },
    {
      "InsightType": "ApiErrorRateInsight"
    }
  ]
}
```

If the trail does not have Insights enabled, the **get-insight-selectors** command returns the following error message: "An error occurred (InsightNotEnabledException) when calling the GetInsightSelectors operation: Trail arn:aws:cloudtrail:us-east-1:123456789012:trail/trailName does not have Insights enabled. Edit the trail settings to enable Insights, and then try the operation again."

To configure your trail to log Insights events, run the `put-insight-selectors` command. The following example shows how to configure your trail to include Insights events. Insights selector values can be `ApiCallRateInsight`, `ApiErrorRateInsight`, or both.

```
aws cloudtrail put-insight-selectors --trail-name TrailName --insight-selectors
'[{ "InsightType": "ApiCallRateInsight"}, { "InsightType": "ApiErrorRateInsight"}]'
```

The following result shows the Insights event selector that is configured for the trail.

```
{
  "TrailARN": "arn:aws:cloudtrail:us-east-1:123456789012:trail/TrailName",
  "InsightSelectors":
    [
      {
        "InsightType": "ApiErrorRateInsight"
      },
      {
        "InsightType": "ApiCallRateInsight"
      }
    ]
}
```

Logging Insights events for an event data store using the AWS CLI

To enable Insights on an event data store, you must have a source event data store that logs management events and a destination event data store that logs Insights events.

To view whether Insights events are enabled on an event data store, run the **get-insight-selectors** command.

```
aws cloudtrail get-insight-selectors --event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE
```

To view whether an event data store is configured to receive Insights events or management events, run the **get-event-data-store** command.

```
aws cloudtrail get-event-data-store --event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-d483-5c7d-4ac2-adb5dEXAMPLE
```

If an event data store is configured to receive Insights events, its `eventCategory` will be set to `Insight`.

The following procedure shows you how to create the destination and source event data stores and then enable Insights events.

1. Run the [aws cloudtrail create-event-data-store](#) command to create a destination event data store that collects Insights events. The value for `eventCategory` must be `Insight`. Replace *retention-period-days* with the number of days you would like to retain events in your event data store.

If you are signed in with the management account for an AWS Organizations organization, include the `--organization-enabled` parameter if you want to give your [delegated administrator](#) access to the event data store.

```
aws cloudtrail create-event-data-store \  
--name insights-event-data-store \  
--no-multi-region-enabled \  
--retention-period retention-period-days \  
--advanced-event-selectors '[  
  {  
    "Name": "Select Insights events",  
    "FieldSelectors": [  
      { "Field": "eventCategory", "Equals": ["Insight"]} ]  
  }  
' ]
```

```
    ]
  }
]'
```

The following is an example response.

```
{
  "Name": "insights-event-data-store",
  "ARN": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/
EXAMPLEf852-4e8f-8bd1-bcf6cEXAMPLE",
  "AdvancedEventSelectors": [
    {
      "Name": "Select Insights events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Insight"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": false,
  "OrganizationEnabled": false,
  "BillingMode": "EXTENDABLE_RETENTION_PRICING",
  "RetentionPeriod": "90",
  "TerminationProtectionEnabled": true,
  "CreatedTimestamp": "2023-11-08T15:22:33.578000+00:00",
  "UpdatedTimestamp": "2023-11-08T15:22:33.714000+00:00"
}
```

You will use the ARN (or ID suffix of the ARN) from the response as the value for the `--insights-destination` parameter in step 3.

2. Run the [aws cloudtrail create-event-data-store](#) command to create a source event data store that logs management events. By default, event data stores log all management events. You don't need to specify the advanced event selectors if you want to log all management events. Replace *retention-period-days* with the number of days you would like to retain events in your event data store. If you are creating an organization event data store, include the `--organization-enabled` parameter.

```
aws cloudtrail create-event-data-store --name source-event-data-store --retention-period retention-period-days
```

The following is an example response.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLE9952-4ab9-49c0-b788-f4f3EXAMPLE",
  "Name": "source-event-data-store",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Default management events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": true,
  "OrganizationEnabled": false,
  "BillingMode": "EXTENDABLE_RETENTION_PRICING",
  "RetentionPeriod": 90,
  "TerminationProtectionEnabled": true,
  "CreatedTimestamp": "2023-11-08T15:25:35.578000+00:00",
  "UpdatedTimestamp": "2023-11-08T15:25:35.714000+00:00"
}
```

You will use the ARN (or ID suffix of the ARN) from the response as the value for the `--event-data-store` parameter in step 3.

3. Run the [put-insight-selectors](#) command to enable Insights events. Insights selector values can be `ApiCallRateInsight`, `ApiErrorRateInsight`, or both. For the `--event-data-store` parameter, specify the ARN (or ID suffix of the ARN) of the source event data store that logs management events and will enable Insights. For the `--insights-destination` parameter, specify the ARN (or ID suffix of the ARN) of the destination event data store that will log Insights events.

```
aws cloudtrail put-insight-selectors --event-data-store arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLE9952-4ab9-49c0-b788-f4f3EXAMPLE --insights-destination arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLEf852-4e8f-8bd1-bcf6cEXAMPLE --insight-selectors '[{"InsightType": "ApiCallRateInsight"}, {"InsightType": "ApiErrorRateInsight"}]'
```

The following result shows the Insights event selector that is configured for the event data store.

```
{
  "EventDataStoreARN": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLE9952-4ab9-49c0-b788-f4f3EXAMPLE",
  "InsightsDestination": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLEf852-4e8f-8bd1-bcf6cEXAMPLE",
  "InsightSelectors":
    [
      {
        "InsightType": "ApiErrorRateInsight"
      },
      {
        "InsightType": "ApiCallRateInsight"
      }
    ]
}
```

After you enable CloudTrail Insights for the first time on an event data store, CloudTrail may take up to 7 days to begin delivering Insights events, provided that unusual activity is detected during that time.

Viewing Insights events for trails

This section describes how you can lookup the last 90 days of Insights events for a trail with CloudTrail Insights enabled. For information about how to view CloudTrail Insights for an event data store, see [Viewing the Insights dashboard for an event data store](#).

You can view, filter, and download the last 90 days of Insights events for a trail from the **Insights** page on the console.

You can lookup the last 90 days of Insights events programmatically by running the AWS CLI [lookup-events](#) command, or the [LookupEvents](#) API operation.

For descriptions of Insights events record fields for trails, see [CloudTrail record contents for Insights events for trails](#).

Note

The **Insights** page and AWS CLI `lookup-events` command only list Insights events if you've enabled Insights on a trail that is logging management events. For information about enabling Insights on a trail, see [Enabling CloudTrail Insights on an existing trail with the console](#) and [Logging Insights events for a trail using the AWS CLI](#).

To log Insights events on the API call rate, the trail must log write management events. To log Insights events on the API error rate, the trail must log read or write management events.

Topics

- [Viewing Insights events for trails with the console](#)
- [Viewing Insights events for trails with the AWS CLI](#)

Viewing Insights events for trails with the console

This section describes how to view, look up, and download the last 90 days of Insights events for a trail from the **Insights** page on the CloudTrail console. For information about how to view CloudTrail Insights for an event data store, see [Viewing the Insights dashboard for an event data store](#).

After Insights events are logged for a trail, the events are shown on the **Insights** page for 90 days. You cannot manually delete events from the **Insights** page. Since Insights events enabled for a trail are stored in the Amazon S3 bucket configured for that trail, removing the Insights events from the bucket will delete those events.

You can monitor your trail logs and be notified when specific Insights events occur by enabling CloudWatch Logs. For more information, see [Monitoring CloudTrail Log Files with Amazon CloudWatch Logs](#).

Note

CloudTrail Insights events must be enabled on your trail to see Insights events in the console. Allow up to 36 hours for CloudTrail to deliver the first Insights events, provided that unusual activity is detected during that time.

To log Insights events on the API call rate, the trail must log write management events.

To log Insights events on the API error rate, the trail must log read or write management events.

To view Insights events

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/home/>.
2. In the navigation pane, choose **Insights** to see all Insights events logged in your account in the last 90 days. You can also view the five most recent Insights events from the **Dashboards** page.
3. On the **Insights** page, you can filter Insights events by event source, event name, or event ID. For more information about filtering Insights events, see [Filtering Insights events](#).
4. You can further limit the list to a **Relative range** or **Absolute range**.

Contents

- [Filtering Insights events](#)
- [Viewing Insights events details](#)
- [Zoom, pan, and download graph](#)
- [Change graph time span settings](#)
- [Downloading Insights events](#)

Filtering Insights events

By default, events on the **Insights** page are shown in reverse chronological order by event start time.

You can filter the list by choosing from one of the following three attributes:

Event name


The name of the event, typically the AWS API on which unusual levels of activity were recorded.

Event source

The AWS service to which the request was made, such as `iam.amazonaws.com` or `s3.amazonaws.com`. If you choose to filter by event source, you can scroll through a list of event sources.

Event ID

The ID of the Insights event. Event IDs are not shown in the **Insights** page table, but they are an attribute on which you can filter Insights events. The event IDs of management events that are analyzed to generate Insights events are different from the event IDs of Insights events.



The following list describes the attributes of an event, which are not filterable:

Insight type

The type of CloudTrail Insights event, which is either **API call rate** or **API error rate**. The **API call rate** insight type analyzes write-only management API calls that are aggregated per minute against a baseline API call volume. The **API error rate** insight type analyzes management API calls that result in error codes. The error is shown if the API call is unsuccessful.

Event start time

The start time of the Insights event, measured as the first minute in which unusual activity was recorded. This attribute is shown in the **Insights** table, but you cannot filter on event start time in the console.

Baseline average

Baseline represents the normal pattern of API call rate or error rate activity, calculated daily. The baseline average is the average of these daily baselines over the seven days preceding the start of an Insights event. While this period is generally seven days, CloudTrail rounds the calculation period to a whole number of days, so the exact baseline duration may vary slightly.

Insight average

The average number of calls to an API, or the average number of a specific error that was returned on calls to an API, that triggered the Insights event. The CloudTrail Insights average for the start event is the rate of occurrences that triggered the Insights event. Typically, this is the first minute of unusual activity. The Insights average for the end event is the rate of occurrences over the duration of the unusual activity, between the start Insights event and the end Insights event.

Rate change

The difference between the value of **Baseline average** and **Insight average**, measured as a percentage. For example, if the baseline average of an AccessDenied error occurring is 1.0, and the Insight average is 3.0, the rate change is 300%. A rate change for an Insight average that exceeds a baseline average shows an up-arrow next to the value. If the Insights event was logged because the activity is below the baseline average, **Rate change** shows a down-arrow next to the percentage.

If there are no events logged for the attribute or time that you choose, the results list is empty. You can apply only one attribute filter in addition to the time range. If you choose a different attribute filter, your specified time range is preserved.

The following steps describe how to filter by attribute.

To filter by attribute

1. To filter the results by an attribute, choose a lookup attribute from the dropdown menu, and then type or choose a value in the **Enter a lookup value** box.

2. To remove an attribute filter, choose the **X** on the right of the attribute filter box.


The following steps describe how to filter by a start and end date and time.

To filter by a start and end date and time

1. From **Filter by date and time**, choose one of the following:
 - **Absolute range** - Lets you choose a specific time. Go on to the next step.
 - **Relative range** - Selected by default. Lets you choose a time period relative to the start time of an Insights event. Go on to step 3.
2. To set an **Absolute range**, do the following.
 - a. Choose the day that you want the time range to start. Enter a start time on the selected day. To enter a date manually, type the date in the format yyyy/mm/dd. The start and end times use a 24-hour clock, and values must be in the format hh:mm:ss. For example, to indicate a 6:30 p.m. start time, enter **18:30:00**.
 - b. Choose an end date for the range on the calendar, or specify an end date and time below the calendar. Choose **Apply**.
3. To set a **Relative range**, do the following.
 - a. Choose a preset time period relative to the start time of Insights events. Preset time ranges include 30 minutes, 1 hour, 12 hours, or 1 day. To specify a custom time range, choose **Custom**.
 - b. When you have set the relative time that you want, choose **Apply**.
4. To remove a time range filter, choose the calendar icon on the right of the **Filter by date and time** box, and then choose **Clear and dismiss**.

Viewing Insights events details

1. Choose an Insights event in the results list to show its details. The details page for an Insights event shows a graph of the unusual activity timeline.



- **Trigger.** This is a link to the **Cloudtrail events** tab, which lists the management events that were analyzed to determine that unusual activity occurred.
 - **API calls per minute or Errors per minute**
 - **Baseline average** - The typical rate of occurrences per minute on the API on which the Insights event was logged, as measured within approximately the preceding seven days, in a specific Region in your account.
 - **Insights average** - The rate of occurrences per minute on this API that triggered the Insights event. The CloudTrail Insights average for the start event is the rate of calls or errors per minute on the API that triggered the Insights event. Typically, this is the first minute of unusual activity. The Insights average for the end event is the rate of API calls or errors per minute over the duration of the unusual activity, between the start Insights event and the end Insights event.
 - **Event source.** The AWS service endpoint on which the unusual number of API calls or errors were logged. In the preceding image, the source is `ec2.amazonaws.com`, which is the service endpoint for Amazon EC2.
 - **Start event ID** - The ID of the Insights event that was logged at the start of unusual activity.
 - **End event ID** - The ID of the Insights event that was logged at the end of unusual activity.
 - **Shared event ID** - In Insights events, the **Shared event ID** is a GUID that is generated by CloudTrail Insights to uniquely identify a start and end pair of Insights events. **Shared event ID** is common between the start and the end Insights event, and helps to create a correlation between both events to uniquely identify unusual activity.
3. Choose the **Attributions** tab to view information about the user identities, user agents, and on API call rate Insights events, error codes correlated with unusual and baseline activity. A maximum of five user identities, five user agents, and five error codes are shown in tables on the **Attributions** tab, sorted by an average of the count of activity, in descending order from highest to lowest.
 4. On the **CloudTrail events** tab, view related events that CloudTrail analyzed to determine that unusual activity occurred. By default, a filter is already applied for the Insights event name, which is also the name of the related API. The **CloudTrail events** tab shows CloudTrail management events related to the subject API that occurred between the start time (minus one minute) and end time (plus one minute) of the Insights event.

As you select other Insights events in the graph, the events shown in the **CloudTrail events** table change. These events help you perform deeper analysis to determine the probable cause of an Insights event and reasons for unusual API activity.

To show all CloudTrail events that were logged during the Insights event duration, and not only those for the related API, turn off the filter.

5. Choose the **Insights event record** tab to view the Insights start and end events in JSON format.
6. Choosing the linked **Event source** returns you to the **Insights** page, filtered by that event source.

Zoom, pan, and download graph

You can zoom, pan, and reset the axes of the graph on the Insights event details page by using a toolbar in the upper right corner.




From left to right, the command buttons on the graph toolbar do the following:

- **Download plot as a PNG** - Download the graph image shown on the details page, and save it in PNG format.
- **Zoom** - Drag to select an area on the graph that you want to enlarge and see in greater detail.
- **Pan** - Shift the graph to see adjacent dates or times.
- **Reset axes** - Change graph axes back to the original, clearing zoom and pan settings.

Change graph time span settings

You can change the time span—the selected duration of the events shown on the x axis—that is shown in the graph by choosing a setting in the graph's upper right corner.



Downloading Insights events

You can download recorded Insights event history as a file in CSV or JSON format. Use filters and time ranges to reduce the size of the file you download.

Note

CloudTrail event history files are data files that contain information (such as resource names) that can be configured by individual users. Some data can potentially be interpreted as commands in programs used to read and analyze this data (CSV injection). For example, when CloudTrail events are exported to CSV and imported to a spreadsheet program, that program might warn you about security concerns. As a security best practice, disable links or macros from downloaded event history files.

1. Specify the filter and time range for events you want to download. For example, you can specify the event name, `StartInstances`, and specify a time range for the last 12 hours of activity.
2. Choose **Download events**, and then choose **Download as CSV** or **Download as JSON**. You are prompted to choose a location to save the file.

Note

Your download might take some time to finish. For faster results, before you start the download process, use a more specific filter or a shorter time range to narrow the results.

3. After your download is complete, open the file to view the events that you specified.
4. To cancel your download, choose **Cancel**. If you cancel a download before it is finished, a CSV or JSON file on your local computer might contain only part of your events.

Viewing Insights events for trails with the AWS CLI

This section describes how to use the AWS CLI `lookup-events` command to lookup the last 90 days of Insights events for a trail with Insights events enabled. For information about how to enable CloudTrail Insights on a trail, see [Logging Insights events for a trail using the AWS CLI](#).

Note

You cannot use the `lookup-events` command to lookup Insights events for an event data store, however, CloudTrail Lake offers a number of sample queries for Insights event data stores. For more information, see [Viewing sample queries for Insights events](#).

The `lookup-events` command has the following options:

- `--end-time`
- `--event-category`
- `--max-results`
- `--start-time`
- `--lookup-attributes`
- `--next-token`
- `--generate-cli-skeleton`
- `--cli-input-json`

For general information about using the AWS Command Line Interface, see the [AWS Command Line Interface User Guide](#).

Contents

- [Prerequisites](#)
- [Getting command line help](#)
- [Looking up Insights events](#)
- [Specifying the number of Insights events to return](#)
- [Looking up Insights events by time range](#)
- [Looking up Insights events by attribute](#)
 - [Attribute lookup examples](#)
- [Specifying the next page of results](#)
- [Getting JSON input from a file](#)
- [Lookup output fields](#)

Prerequisites

- To run AWS CLI commands, you must install the AWS CLI. For more information, see [Get started with the AWS CLI](#).
- Make sure your AWS CLI version is greater than 1.6.6. To verify the CLI version, run **aws --version** on the command line.
- To set the account, Region, and default output format for an AWS CLI session, use the **aws configure** command. For more information, see [Configuring the AWS Command Line Interface](#).
- To log Insights events on the API call rate, the trail must log write management events. To log Insights events on the API error rate, the trail must log read or write management events.

Note

The CloudTrail AWS CLI commands are case-sensitive.

Getting command line help

To see the command line help for lookup-events, type the following command.

```
aws cloudtrail lookup-events help
```

Looking up Insights events

To see the ten latest Insights events, type the following command.

```
aws cloudtrail lookup-events --event-category insight
```

A returned event looks similar to the following example,

```
{
  "NextToken": "kb0t5LlZe+
+mErCebpy2TgaMgmDvF1kYGFcH64JSjIbZFjsuvrSqq66b5YGssKutDYIyII4lrP4IDbeQdi0bkp9YA1ju3oXd12juEXAMP
  "Events": [
    {
      "eventVersion": "1.09",
      "eventTime": "2024-12-11T16:52:00Z",
      "awsRegion": "us-east-1",
      "eventID": "18378b1e-3653-433d-ba1e-aa11a5958f0c",
```

```

    "eventType": "AwsCloudTrailInsight",
    "recipientAccountId": "888888888888",
    "sharedEventID": "fccb064f-dd07-4822-97c0-11115d8b91d4",
    "insightDetails": {
      "state": "Start",
      "eventSource": "cloudtrail.amazonaws.com",
      "eventName": "DescribeQuery",
      "insightType": "ApiErrorRateInsight",
      "errorCode": "QueryIdNotFoundException",
      "insightContext": {
        "statistics": {
          "baseline": {
            "average": 0
          },
          "insight": {
            "average": 1.2
          },
          "insightDuration": 5,
          "baselineDuration": 11092
        },
        "attributions": [
          {
            "attribute": "userIdentityArn",
            "insight": [
              {
                "value": "arn:aws:sts::888888888888:assumed-role/
Admin",
                "average": 1.2
              }
            ],
            "baseline": []
          },
          {
            "attribute": "userAgent",
            "insight": [
              {
                "value": "Mozilla/5.0 (Macintosh; Intel Mac OS X
10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/131.0.0.0 Safari/537.36",
                "average": 1.2
              }
            ],
            "baseline": []
          }
        ]
      }
    }
  ]

```

```

    }
  },
  "eventCategory": "Insight"
},
{
  "eventVersion": "1.09",
  "eventTime": "2024-12-11T16:53:00Z",
  "awsRegion": "us-east-1",
  "eventID": "b32f10a0-f039-419a-bad7-e95468930a4f",
  "eventType": "AwsCloudTrailInsight",
  "recipientAccountId": "888888888888",
  "sharedEventID": "fccb064f-dd07-4822-97c0-11115d8b91d4",
  "insightDetails": {
    "state": "End",
    "eventSource": "cloudtrail.amazonaws.com",
    "eventName": "DescribeQuery",
    "insightType": "ApiErrorRateInsight",
    "errorCode": "QueryIdNotFoundException",
    "insightContext": {
      "statistics": {
        "baseline": {
          "average": 0
        },
        "insight": {
          "average": 6
        },
        "insightDuration": 1,
        "baselineDuration": 11092
      },
      "attributions": [
        {
          "attribute": "userIdentityArn",
          "insight": [
            {
              "value": "arn:aws:sts::888888888888:assumed-role/Admin",
              "average": 6
            }
          ],
          "baseline": []
        },
        {
          "attribute": "userAgent",
          "insight": [

```

```

        {
            "value": "Mozilla/5.0 (Macintosh; Intel Mac OS X
10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/131.0.0.0 Safari/537.36",
            "average": 6
        }
    ],
    "baseline": []
}
]
}
},
"eventCategory": "Insight"
}
]
}

```

For an explanation of the lookup-related fields in the output, see [Lookup output fields](#) in this topic. For an explanation of fields in the Insights event, see [CloudTrail record contents for Insights events for trails](#).

Specifying the number of Insights events to return

To specify the number of events to return, type the following command.

```
aws cloudtrail lookup-events --event-category insight --max-results <integer>
```

The default value for *<integer>*, if it is not specified, is 10. Possible values are 1 through 50. The following example returns one result.

```
aws cloudtrail lookup-events --event-category insight --max-results 1
```

Looking up Insights events by time range

Insights events from the past 90 days are available for lookup. To specify a time range, type the following command.

```
aws cloudtrail lookup-events --event-category insight --start-time <timestamp> --end-time <timestamp>
```

`--start-time <timestamp>` specifies, in UTC, that only Insights events that occur after or at the specified time are returned. If the specified start time is after the specified end time, an error is returned.

`--end-time <timestamp>` specifies, in UTC, that only Insights events that occur before or at the specified time are returned. If the specified end time is before the specified start time, an error is returned.

The default start time is the earliest date that data is available within the last 90 days. The default end time is the time of the event that occurred closest to the current time.

All timestamps are shown in UTC.

Looking up Insights events by attribute

To filter by an attribute, type the following command.

```
aws cloudtrail lookup-events --event-category insight --lookup-attributes
AttributeKey=<attribute>,AttributeValue=<string>
```

You can specify only one attribute key-value pair for each **lookup-events** command. The following are valid Insights event values for `AttributeKey`. Value names are case sensitive.

- `EventId`
- `EventName`
- `EventSource`

The maximum length for the `AttributeValue` is 2000 characters. The following characters (`'_'`, `'`, `,`, `'\n'`) count as two characters towards the 2000 character limit.

Attribute lookup examples

The following example command returns Insights events in which the value of `EventName` is `PutRule`.

```
aws cloudtrail lookup-events --event-category insight --lookup-attributes
AttributeKey=EventName, AttributeValue=PutRule
```

The following example command returns Insights events in which the value of `EventId` is `b5cc8c40-12ba-4d08-a8d9-2bceb9a3e002`.

```
aws cloudtrail lookup-events --event-category insight --lookup-attributes
  AttributeKey=EventId, AttributeValue=b5cc8c40-12ba-4d08-a8d9-2bceb9a3e002
```

The following example command returns Insights events in which the value of EventSource is iam.amazonaws.com.

```
aws cloudtrail lookup-events --event-category insight --lookup-attributes
  AttributeKey=EventSource, AttributeValue=iam.amazonaws.com
```

Specifying the next page of results

To get the next page of results from a lookup-events command, type the following command.

```
aws cloudtrail lookup-events --event-category insight <same parameters as previous
command> --next-token=<token>
```

In this command, the value for *<token>* is taken from the first field of the output of the previous command.

When you use --next-token in a command, you must use the same parameters as in the previous command. For example, suppose you run the following command.

```
aws cloudtrail lookup-events --event-category insight --lookup-attributes
  AttributeKey=EventName, AttributeValue=PutRule
```

To get the next page of results, your next command would look like the following.

```
aws cloudtrail lookup-events --event-category insight --lookup-attributes
  AttributeKey=EventName,AttributeValue=PutRule --next-token=EXAMPLEZe+
+mErCebpy2TgaMgmDvF1kYGFcH64JSjIbZfjsuvrSqq66b5YGssKutDYIyII4lrP4IDbeQdi0bkp9YA1ju3oXd12juEXAMP
```

Getting JSON input from a file

The AWS CLI for some AWS services has two parameters, --generate-cli-skeleton and --cli-input-json, that you can use to generate a JSON template, which you can modify and use as input to the --cli-input-json parameter. This section describes how to use these parameters with aws cloudtrail lookup-events. For more information, see [AWS CLI skeletons and input files](#).

To look up Insights events by getting JSON input from a file

1. Create an input template for use with `lookup-events` by redirecting the `--generate-cli-skeleton` output to a file, as in the following example.

```
aws cloudtrail lookup-events --event-category insight --generate-cli-skeleton >
LookupEvents.txt
```

The template file generated (in this case, `LookupEvents.txt`) looks like the following.

```
{
  "LookupAttributes": [
    {
      "AttributeKey": "",
      "AttributeValue": ""
    }
  ],
  "StartTime": null,
  "EndTime": null,
  "MaxResults": 0,
  "NextToken": ""
}
```

2. Use a text editor to modify the JSON as needed. The JSON input must contain only values that are specified.

Important

All empty or null values must be removed from the template before you can use it.

The following example specifies a time range and maximum number of results to return.

```
{
  "StartTime": "2023-11-01",
  "EndTime": "2023-12-12",
  "MaxResults": 10
}
```

3. To use the edited file as input, use the syntax `--cli-input-json file://<filename>`, as in the following example.

```
aws cloudtrail lookup-events --event-category insight --cli-input-json file://
LookupEvents.txt
```

Note

You can use other arguments on the same command line as `--cli-input-json`.

Lookup output fields

Events

A list of lookup events based on the lookup attribute and time range that were specified. The events list is sorted by time, with the latest event listed first. Each entry contains information about the lookup request and includes a string representation of the CloudTrail event that was retrieved.

The following entries describe the fields in each lookup event.

CloudTrailEvent

A JSON string that contains an object representation of the event returned. For information about each of the elements returned, see [Record Body Contents](#).

EventId

A string that contains the GUID of the event returned.

EventName

A string that contains the name of the event returned.

EventSource

The AWS service that the request was made to.

EventTime

The date and time, in UNIX time format, of the event.

Resources

A list of resources referenced by the event that was returned. Each resource entry specifies a resource type and a resource name.

ResourceName

A string that contains the name of the resource referenced by the event.

ResourceType

A string that contains the type of a resource referenced by the event. When the resource type cannot be determined, null is returned.

Username

A string that contains the user name of the account for the event returned.

NextToken

A string to get the next page of results from a previous `lookup-events` command. To use the token, the parameters must be the same as those in the original command. If no `NextToken` entry appears in the output, there are no more results to return.

For more information about CloudTrail Insights events, see [Working with CloudTrail Insights](#) in this guide.

Viewing Insights events for event data stores

This section describes how you can view Insights events for an Insights event data store by viewing the **Insights events dashboard** and running sample queries. For information about how to enable CloudTrail Insights on an event data store, see [Enabling CloudTrail Insights on an existing event data store with the console](#).

CloudTrail queries incur charges based upon the amount of data scanned. To help control costs, we recommend that you constrain queries by adding starting and ending `eventTime` time stamps to queries. For more information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

For descriptions of Insights events record fields for event data stores, see [CloudTrail record contents for Insights events for event data stores](#).

Topics

- [Viewing the Insights dashboard for an event data store](#)
- [Viewing sample queries for Insights events](#)

Viewing the Insights dashboard for an event data store

The **Insights events dashboard** shows the overall proportion of Insights events by Insights type, the proportion of Insights events by Insights type for the top users and services, and the number of Insights events per day. The dashboard also includes a widget that lists up to 30 days of Insights events.

Note

- After you enable CloudTrail Insights for the first time on the source event data store, CloudTrail may take up to 7 days to begin delivering Insights events, provided that unusual activity is detected during that time. For more information, see [Delivery of Insights events](#).
- The **Insights events dashboard** only displays information about the Insights events collected by the selected event data store, which is determined by the configuration of the source event data store. For example, if you configure the source event data store to enable Insights events on `ApiCallRateInsight` but not `ApiErrorRateInsight`, you won't see information about Insights events on `ApiErrorRateInsight`.

To view the Insights events dashboard

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the left navigation pane, under **Lake**, choose **Dashboard**.
3. Choose the **Managed and custom dashboards** tab.
4. From **AWS managed dashboards**, choose **Insights events dashboard**.
5. Choose your Insights event data store.
6. Choose to filter the dashboard data by an **Absolute range** or **Relative range**. Choose **Absolute range** to select a specific date and time range. Choose **Relative range** to select a predefined time range or a custom range. By default, the dashboard displays event data for the past 24 hours.

 Note

CloudTrail Lake queries incur costs based upon the amount of data scanned. To help control costs, you can filter on a narrower time range. For more information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

7. Choose the refresh icon to populate the graphics for the dashboard's widgets. Each widget indicates the status of the refresh.

For more information about Lake dashboards, see [CloudTrail Lake dashboards](#).

Viewing sample queries for Insights events

The CloudTrail console provides a number of sample queries for Insights events that can help you get started writing your own queries.

To view sample queries for Insights events

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Query**.
3. On the **Query** page, choose the **Sample queries** tab.
4. Search for queries for Insights events. Choose the **Query name** to open the query in the **Editor** tab.

Sample queries (202) Info		
Insights 5 found		
Query name	Query description	Query SQL
Top 10 Insights event sources	Find the top 10 event sources that generated the most Insights events within the past month.	<pre>SELECT insightEventSource, -- insightEventName, -- Group by event name COUNT(*) AS eventCount FROM \$INSIGHTS_EDS_ID WHERE insightState = 'End' AND insightType = 'ApiCallRateInsight' -- AND insightType = 'ApiErrorRateInsight' -- Filter on API error rate insights AND eventTime > DATE_ADD('month', -1, CURRENT_TIMESTAMP) GROUP BY insightEventSource -- insightEventName -- Group by event name ORDER BY eventCount DESC LIMIT 10</pre>
Top 10 Insights event errors	Find the top 10 errors that generated the most Insights events within the past month.	<pre>SELECT insightErrorCode, COUNT(*) AS eventCount FROM \$INSIGHTS_EDS_ID WHERE insightState = 'End' AND insightType = 'ApiCallErrorInsight' AND eventTime > DATE_ADD('month', -1, CURRENT_TIMESTAMP) GROUP BY insightErrorCode ORDER BY eventCount DESC LIMIT 10</pre>
Rank the number of Insights events per day	Query the Insights event data store over the past month to rank the number of Insights events generated each day.	<pre>SELECT DATE_TRUNC('day', eventTime) AS eventDate, COUNT(*) AS eventCount, DENSE_RANK() OVER(ORDER BY COUNT(*) DESC) AS eventRank FROM \$INSIGHTS_EDS_ID WHERE insightState = 'End' AND insightType = 'ApiCallRateInsight' -- AND insightType = 'ApiErrorRateInsight' -- Filter on API error rate insights AND eventTime > DATE_ADD('month', -1, CURRENT_TIMESTAMP) GROUP BY DATE_TRUNC('day', eventTime) ORDER BY eventRank</pre>
Investigate Insights events	Find all CloudTrail management events that generated an Insights event.	<pre>SELECT * FROM \$EDS_ID AS me INNER JOIN (SELECT awsRegion, recipientAccountId, insightEventSource, insightEventName, MIN(eventTime) AS insight_start, MAX(eventTime) AS insight_end FROM \$INSIGHTS_EDS_ID WHERE sharedEventID = '<sharedEventID>' GROUP BY 1, 2, 3, 4) AS ie ON me.awsRegion = ie.awsRegion AND me.recipientAccountId = ie.recipientAccountId AND me.eventSource = ie.insightEventSource AND me.eventName = ie.insightEventName AND me.eventTime >= ie.insight_start AND me.eventTime <= ie.insight_end ORDER BY me.eventTime</pre>
Insights events caused by a user	Find all Insights events caused by a particular user within the past month.	<pre>SELECT sharedEventID, eventTime, insightType, insightEventSource AS eventSource, insightEventName AS eventName, insightcontext.attributes [1].insightvalue AS user FROM \$INSIGHTS_EDS_ID WHERE insightState = 'End' AND insightcontext.attributes [1].insightvalue LIKE '%<username>%' AND eventTime > DATE_ADD('month', -1, CURRENT_TIMESTAMP) ORDER BY eventTime DESC</pre>

- On the **Editor** tab, choose the Insights event data store. When you choose the event data store from the list, CloudTrail automatically populates the event data store ID in the FROM line of the query editor.
- Choose **Run** to run the query. After the query completes, you can view the command output and query results.

The **Command output** tab shows you metadata about your query, such as whether the query was successful, the number of records matched, and the run time of the query.

The **Query results** tab shows you the event data in the selected event data store that matched your query.

For more information about editing a query, see [Create or edit a query with the CloudTrail console](#). For more information about running a query and saving query results, see [Run a query and save query results with the console](#).

Working with AWS CloudTrail Lake

AWS CloudTrail Lake lets you run SQL-based queries on your events. CloudTrail Lake converts existing events in row-based JSON format to [Apache ORC](#) format. ORC is a columnar storage format that is optimized for fast retrieval of data. Events are aggregated into event data stores, which are immutable collections of events based on criteria that you select by applying [advanced event selectors](#). You can keep the event data in an event data store for up to 3,653 days (about 10 years) if you choose the **One-year extendable retention pricing** option, or up to 2,557 days (about 7 years) if you choose the **Seven-year retention pricing** option. The selectors that you apply to an event data store control which events persist and are available for you to query. CloudTrail Lake is an auditing solution that can complement your compliance stack, and assist you with near real-time troubleshooting.

CloudTrail Lake event data stores

When you create an event data store, you choose the type of events to include in your event data store. You can create an event data store to include [CloudTrail events](#) (management events, data events, network activity events), [CloudTrail Insights events](#), [AWS Config configuration items](#), [AWS Audit Manager evidence](#), or [events from outside of AWS](#). Each event data store can only contain a specific event category (for example, AWS Config configuration items), because the [event schema](#) is unique to the event category. You can store events from an organization in AWS Organizations in an [organization event data store](#), including events from multiple Regions and accounts. You can also run SQL queries across multiple event data stores using the supported SQL JOIN keywords. For information about running queries across multiple event data stores, see [Advanced, multi-table query support](#).

You can copy trail events to a new or existing event data store to create a point-in-time snapshot of events logged to the trail. For more information, see [Copy trail events to an event data store](#).

You can federate an event data store to see the metadata associated with the event data store in the AWS Glue [Data Catalog](#) and run SQL queries on the event data using Amazon Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know how to find, read, and process the data that you want to query. For more information, see [Federate an event data store](#).

You can attach a resource-based policy to your event data store to provide cross-account access to selected principals. You can add a resource-based policy when you create or update an event data

store on the CloudTrail console, or by running the AWS CLI `put-resource-policy` command. For more information, see [Resource-based policy examples for event data stores](#).

By default, all events in an event data store are encrypted by CloudTrail. When you configure an event data store, you can choose to use your own AWS Key Management Service key. Using your own KMS key incurs AWS KMS costs for encryption and decryption. After you associate an event data store with a KMS key, the KMS key cannot be removed or changed.

You can control access to actions on event data stores by using authorization based on tags. For more information and examples, see [Examples: Denying access to create or delete event data stores based on tags](#) in this guide.

CloudTrail Lake event data stores incur charges. When you create an event data store, you choose the [pricing option](#) you want to use for the event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention period for the event data store. For information about CloudTrail pricing and managing Lake costs, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

CloudTrail Lake supports Amazon CloudWatch metrics, which provide information about data ingested and storage bytes. For more information about supported CloudWatch metrics, see [Supported CloudWatch metrics](#).

Note

CloudTrail typically delivers events within an average of about 5 minutes of an API call. This time is not guaranteed.

CloudTrail Lake queries

CloudTrail Lake queries offer a deeper and more customizable view of events than simple key and value lookups in **Event history**, or running `LookupEvents`. An **Event history** search is limited to a single AWS account, only returns events from a single AWS Region, and cannot query multiple attributes. In contrast, CloudTrail Lake users can run complex SQL queries across multiple event fields. CloudTrail Lake supports all valid Trino `SELECT` statements and functions. For more information about the supported SQL functions and operators, see [Functions and Operators](#) on the Trino documentation website.

You can build a query on the CloudTrail Lake **Editor** tab by writing the query in SQL from scratch, by opening a saved or sample query and editing it, or by using the query generator to produce a query from an English language prompt. For more information, see [Create or edit a query with the CloudTrail console](#) and [Create CloudTrail Lake queries from natural language prompts](#).

You can save CloudTrail Lake queries for future use, and view results of queries for up to seven days. When you run queries, you can save the query results to an Amazon S3 bucket.

The CloudTrail console provides a number of sample queries that can help you get started writing your own queries. For more information, see [View sample queries with the CloudTrail console](#).

CloudTrail Lake queries incur charges. When you run queries in Lake, you pay based upon the amount of data scanned. For information about CloudTrail pricing and managing Lake costs, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

CloudTrail Lake dashboards

You can use CloudTrail Lake dashboards to see event trends for the event data stores in your account. CloudTrail Lake offers the following types of dashboards:

- **Managed dashboards** – You can view a managed dashboard to see event trends for an event data store that collects management events, data events, or Insights events. These dashboards are automatically available to you and are managed by CloudTrail Lake. CloudTrail offers 14 managed dashboards to choose from. You can manually refresh managed dashboards. You cannot modify, add, or remove the widgets for these dashboards, however, you can save a managed dashboard as a custom dashboard if you want to modify the widgets or set a refresh schedule.
- **Custom dashboards** – Custom dashboards allow you to query events in any event data store type. You can add up to 10 widgets to a custom dashboard. You can manually refresh a custom dashboard, or you can set a refresh schedule.
- **Highlights dashboards** – Enable the Highlights dashboard to view an at-a-glance overview of the AWS activity collected by the event data stores in your account. The Highlights dashboard is managed by CloudTrail and includes widgets that are relevant to your account. The widgets shown on the Highlights dashboard are unique to each account. These widgets could surface detected abnormal activity or anomalies. For example, your Highlights dashboard could include the **Total cross-account access widget**, which shows if there is an increase in abnormal cross-account activity. CloudTrail updates the Highlights dashboard every 6 hours. The dashboard shows the last 24 hours of data from the last update.

Each dashboard consists of one or more widgets and each widget represents a SQL query.

For more information, see [CloudTrail Lake dashboards](#).

CloudTrail Lake integrations

You can use CloudTrail Lake *integrations* to log and store user activity data from outside of AWS; from any source in your hybrid environments, such as in-house or SaaS applications hosted on-premises or in the cloud, virtual machines, or containers. After you create event data stores in CloudTrail Lake and create a channel to log activity events, you call the `PutAuditEvents` API to ingest your application activity into CloudTrail. You can then use CloudTrail Lake to search, query, and analyze the data that is logged from your applications.

Integrations can also log events to your event data stores from over a dozen CloudTrail partners. In a partner integration, you create destination event data stores, a channel, and a resource policy. After you create the integration, you provide the channel ARN to the partner. There are two types of integrations: direct and solution. With direct integrations, the partner calls the `PutAuditEvents` API to deliver events to the event data store for your AWS account. With solution integrations, the application runs in your AWS account and the application calls the `PutAuditEvents` API to deliver events to the event data store for your AWS account.

For more information about integrations, see [Create an integration with an event source outside of AWS](#).

Additional resources

The following resources can help you get a better understanding of what CloudTrail Lake is and how you can use it.

- [Modernize Your Audit Log Management Using CloudTrail Lake](#) (YouTube video)
- [Log Activity Events from Non-AWS Sources in AWS CloudTrail Lake](#) (YouTube video)
- [Analyze Activity Logs with AWS CloudTrail Lake and Amazon Athena](#) (YouTube video)
- [Get visibility into the activity logs for your workforce and customer identities](#) (AWS blog)
- [Using AWS CloudTrail Lake to identify older TLS connections to AWS service endpoints](#) (AWS blog)
- [How Arctic Wolf uses AWS CloudTrail Lake to Simplify Security and Operations](#) (AWS blog)

- [CloudTrail Lake FAQs](#)
- [AWS CloudTrail API Reference](#)
- [AWS CloudTrail Data API Reference](#)
- [AWS CloudTrail Partner Onboarding Guide](#)

CloudTrail Lake supported Regions

Currently, CloudTrail Lake is supported in the following AWS Regions:

Region Name	Region
US East (N. Virginia)	us-east-1
US East (Ohio)	us-east-2
US West (N. California)	us-west-1
US West (Oregon)	us-west-2
Africa (Cape Town)	af-south-1
Asia Pacific (Hong Kong)	ap-east-1
Asia Pacific (Hyderabad)	ap-south-2
Asia Pacific (Jakarta)	ap-southeast-3
Asia Pacific (Melbourne)	ap-southeast-4
Asia Pacific (Mumbai)	ap-south-1
Asia Pacific (Osaka)	ap-northeast-3
Asia Pacific (Seoul)	ap-northeast-2
Asia Pacific (Singapore)	ap-southeast-1
Asia Pacific (Sydney)	ap-southeast-2
Asia Pacific (Tokyo)	ap-northeast-1

Region Name	Region
Canada (Central)	ca-central-1
Europe (Frankfurt)	eu-central-1
Europe (Ireland)	eu-west-1
Europe (London)	eu-west-2
Europe (Milan)	eu-south-1
Europe (Paris)	eu-west-3
Europe (Spain)	eu-south-2
Europe (Stockholm)	eu-north-1
Europe (Zurich)	eu-central-2
Israel (Tel Aviv)	il-central-1
Middle East (Bahrain)	me-south-1
Middle East (UAE)	me-central-1
South America (São Paulo)	sa-east-1
AWS GovCloud (US-East)	us-gov-east-1
AWS GovCloud (US-West)	us-gov-west-1

For information about CloudTrail service endpoints, see [AWS CloudTrail endpoints and quotas](#).

For more information about using CloudTrail in the AWS GovCloud (US) Regions, see [Service Endpoints](#) in the *AWS GovCloud (US) User Guide*.

CloudTrail Lake concepts and terminology

This section describes the key concepts and terms to help you use AWS CloudTrail Lake.

Concepts and terms

- [Event data stores](#)
- [Integrations](#)
- [Queries](#)
- [Dashboards](#)

Event data stores

Events are aggregated into *event data stores*, which are immutable collections of events based on criteria that you select by applying advanced event selectors.

You can create an event data store to log [CloudTrail events](#) (management events, data events, network activity events), [CloudTrail Insights events](#), [AWS Audit Manager evidence](#), [AWS Config configuration items](#), or [events outside of AWS](#).

Advanced event selectors

Advanced event selectors determine which events to include in an event data store. Advanced event selectors help you control costs by logging only those events that are important to you.

For management events, data events, and network activity events, you can use advanced event selectors to filter events. For example, if you're creating an event data store to collect management events, you can filter out AWS Key Management Service (AWS KMS) or Amazon Relational Database Service (Amazon RDS) Data API events. Typically, AWS KMS actions such as Encrypt, Decrypt, and GenerateDataKey generate more than 99 percent of events.

For AWS Config configuration items, Audit Manager evidence, or events outside of AWS, advanced event selectors are used only to include events of that type in the event data store.

Federation

Federation lets you see the metadata associated with an event data store in the AWS Glue [Data Catalog](#) and run SQL queries on the event data using Amazon Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know how to find, read, and process the data that you want to query.

When you enable Lake query federation, CloudTrail creates the federated resources on your behalf and registers those resources with [AWS Lake Formation](#). After Lake federation is enabled,

you can directly query your event data in Athena without needing to perform any additional steps. For more information, see [Federate an event data store](#).

Pricing option

When you create an event data store, you choose the *pricing option* that you want to use for the event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention periods for the event data store. For information about pricing, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

Retention period

An event data store's *retention period* determines how long event data is kept in the event data store. CloudTrail Lake determines whether to retain an event by checking if the `eventTime` of the event is within the specified retention period. For example, if you specify a retention period of 90 days, CloudTrail will remove events when their `eventTime` is older than 90 days.

Default retention period

An event data store's *default retention period* is the default number of days that event data is kept in the event data store. During an event data store's default retention period, storage is included with ingestion pricing at no additional charge. After the default retention period, pricing for storage is pay-as-you-go.

Maximum retention period

An event data store's *maximum retention period* represents the maximum number of days that you can keep data in an event data store.

Termination protection

By default, event data stores enable *termination protection*, which protects an event data store from being accidentally deleted. To delete an event data store with termination protection enabled, choose **Change termination protection** from the **Actions** menu on the event data store's details page. Then you can proceed with deleting the event data store. For more information, see [Change termination protection with the console](#).

Integrations

You can use CloudTrail Lake *integrations* to log and store user activity data from the following sources:

- Outside of AWS
- Any source in your hybrid environments, such as in-house or software as a service (SaaS) applications hosted on premises or in the cloud, virtual machines, or containers

An integration requires a channel to deliver the events and an event data store to receive the events. After you set up your integration, call the [PutAuditEvents](#) API operation to ingest your application activity into CloudTrail. Then, you can use CloudTrail Lake to search, query, and analyze the data that is logged from your applications. For more information, see [Create an integration with an event source outside of AWS](#).

Integration type

There are two types of integrations: *direct* and *solution*. With direct integrations, the partner calls the PutAuditEvents API operation to deliver events to the event data store for your AWS account. With solution integrations, the application runs in your AWS account and the application calls the PutAuditEvents API operation to deliver events to the event data store for your AWS account.

Channels

Activity events from sources outside of AWS work by using *channels* to bring events into CloudTrail Lake from external partners that work with CloudTrail, or from your own sources. When you create a channel, you choose one or more event data stores to store events that arrive from the channel source. You can change the destination event data stores for a channel as needed, as long as the destination event data stores are set to log `eventCategory="ActivityAuditLog"` events. When you create a channel for events from an external partner, you provide a channel Amazon Resource Name (ARN) to the partner or source application.

Resource-based policies

Resource-based policies are JSON policy documents that you attach to a resource. The resource-based policy attached to the channel allows the source to transmit events through the channel. If a channel doesn't have a resource policy, only the channel owner can call the PutAuditEvents API operation on the channel. For more information, see [AWS CloudTrail resource-based policy examples](#).

Queries

Queries in CloudTrail Lake are authored in SQL. You can build a query on the CloudTrail Lake **Editor** tab by writing the query in SQL from scratch, by opening a saved or sample query and editing it, or by using the query generator to produce a query from an English language prompt. For more information, see [Create or edit a query with the CloudTrail console](#) and [Create CloudTrail Lake queries from natural language prompts](#).

CloudTrail Lake supports all valid Trino SELECT statements and functions. For more information about the supported SQL functions and operators, see [Functions and Operators](#) on the Trino documentation website.

Dashboards

By using CloudTrail Lake *dashboards*, you can visualize the events in an event data store and see events trends, such as top AWS services, users, and errors. For more information, see [CloudTrail Lake dashboards](#).

Dashboard types

CloudTrail Lake offers the following types of dashboards:

- **Managed dashboards** – You can view a managed dashboard to see event trends for an event data store that collects management events, data events, or Insights events. These dashboards are automatically available to you and are managed by CloudTrail Lake. CloudTrail offers 14 managed dashboards to choose from. You can manually refresh managed dashboards. You cannot modify, add, or remove the widgets for these dashboards, however, you can save a managed dashboard as a custom dashboard if you want to modify the widgets or set a refresh schedule.
- **Custom dashboards** – Custom dashboards allow you to query events in any event data store type. You can add up to 10 widgets to a custom dashboard. You can manually refresh a custom dashboard, or you can set a refresh schedule.
- **Highlights dashboards** – Enable the Highlights dashboard to view an at-a-glance overview of the AWS activity collected by the event data stores in your account. The Highlights dashboard is managed by CloudTrail and includes widgets that are relevant to your account. The widgets shown on the Highlights dashboard are unique to each account. These widgets could surface detected abnormal activity or anomalies. For example, your Highlights dashboard could include the **Total cross-account access widget**, which shows if there is an increase in

abnormal cross-account activity. CloudTrail updates the Highlights dashboard every 6 hours. The dashboard shows the last 24 hours of data from the last update.

Widgets

Widgets are the components that make up a dashboard and provide a visualization, such as a line chart or bar chart. Each widget corresponds to a SQL query. When you refresh a dashboard, CloudTrail runs a query for each widget on the dashboard to populate the data for the widget.

CloudTrail Lake event data stores

When you create an event data store in CloudTrail Lake, you choose the type of events to include in your event data store. You can create an event data store to include CloudTrail events (management events, data events, or network activity events), CloudTrail Insights events, AWS Config configuration items, or events outside of AWS. Each event data store type can only contain specific event categories (for example, AWS Config configuration items), because the event schema is unique to the event category. You can run SQL queries across multiple event data stores using the supported SQL JOIN keywords. For information about running queries across multiple event data stores, see [Advanced, multi-table query support](#).

The following table shows the supported event categories for each event data store type. The **eventCategory** column shows the value that you would specify in the advanced event selectors to collect events of that type.

Event type (console)	eventCategory (API)	Description
CloudTrail events	Management Data NetworkActivity	This event data store type can collect CloudTrail management events, data events, and network activity events. For more information, see Create an event data store for CloudTrail events .
CloudTrail Insights events	Insight	This event data store type can collect CloudTrail Insights events. To receive Insights events, you need a source event data store that logs CloudTrail management events and enables Insights. For information about creating the source and destination event

Event type (console)	eventCategory (API)	Description
		data stores, see Create an event data store for CloudTrail Insights events .
Configuration items	ConfigurationItem	This event data store type can collect AWS Config configuration items. For more information, see Create an event data store for AWS Config configuration items .
Events from integration	ActivityAuditLog	This event data store type can collect non-AWS events from integrations. For more information, see Create an event data store for events outside of AWS .

You can also create an event data store for AWS Audit Manager evidence by using the Audit Manager console. For more information about aggregating evidence in CloudTrail Lake using Audit Manager, see [Understanding how evidence finder works with CloudTrail Lake](#) in the *AWS Audit Manager User Guide*.

CloudTrail Lake event data stores incur charges. When you create an event data store, you choose the [pricing option](#) you want to use for the event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention period for the event data store. For information about CloudTrail pricing and managing Lake costs, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

The sections which follow describe how to create, update, and manage event data stores.

Topics

- [Create, update, and manage event data stores with the console](#)
- [Create, update, and manage event data stores with the AWS CLI](#)
- [Manage event data store lifecycles](#)
- [Copy trail events to an event data store](#)
- [Federate an event data store](#)
- [Understanding organization event data stores](#)

Create, update, and manage event data stores with the console

You can use the CloudTrail console to create, update, delete, and restore event data stores.

You can update the following settings using the CloudTrail console:

- You can change the [pricing option](#) from **Seven-year retention pricing** to **One-year extendable retention pricing**.
- You can update the retention period for the event data store. The retention period determines how long event data is kept in the event data store.
- You can convert a multi-Region event data store to a single-Region event data store, or convert a single-Region event data store to a multi-Region event data store.
- The management account for an AWS Organizations organization can convert an account-level event data store to an organization event data store, or can convert an organization event data store to an account-level event data store. This setting is not available on event data stores that collect events outside of AWS.
- You can enable or disable [Lake query federation](#). Federating an event data store allows you to query your event data from Amazon Athena.
- You can add or edit the resource-based policy for an event data store to provide cross-account access to your event data store. For more information, see [Resource-based policy examples for event data stores](#).
- You can [stop event ingestion](#) and restart event ingestion on event data stores that collect management events, data events, or AWS Config configuration items.
- You can enable or disable [termination protection](#). Enabling termination protection protects an event data store from being accidentally deleted. Termination protection is enabled by default.
- You can [restore](#) an event data store that is pending deletion.
- You can add or remove tags. You can add up to 50 tag key pairs to help you identify, sort, and control access to your event data store.
- You can add a KMS key to encrypt your event data store. You can't remove a KMS key from an event data store.

Using the CloudTrail console to create or update a event data stores provides the following advantages:

- If you're configuring an event data store to collect data events, using the CloudTrail console allows you to view the available data event resource types. For more information, see [Logging data events](#).
- If you're configuring an event data store to collect network activity events, using the CloudTrail console allows you to view the event sources for which you can log network activity events. For more information, see [Logging network activity events](#).
- If you're configuring a event data store to collect events outside of AWS, using the CloudTrail console lets you view information about available partners. For more information, see [Create an event data store for events outside of AWS with the console](#).

Topics

- [Create an event data store for CloudTrail events with the console](#)
- [Create an event data store for Insights events with the console](#)
- [Create an event data store for configuration items with the console](#)
- [Create an event data store for events outside of AWS with the console](#)
- [Update an event data store with the console](#)
- [Stop and start event ingestion with the console](#)
- [Change termination protection with the console](#)
- [Delete an event data store with the console](#)
- [Restore an event data store with the console](#)

Create an event data store for CloudTrail events with the console

Event data stores for CloudTrail events can include CloudTrail management events, data events, and network activity events. You can keep the event data in an event data store for up to 3,653 days (about 10 years) if you choose the **One-year extendable retention pricing** option, or up to 2,557 days (about 7 years) if you choose the **Seven-year retention pricing** option..

CloudTrail Lake event data stores incur charges. When you create an event data store, you choose the [pricing option](#) you want to use for the event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention period for the event data store. For information about CloudTrail pricing and managing Lake costs, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

To create an event data store for CloudTrail events

Use this procedure to create an event data store that logs CloudTrail management events, data events, or network activity events.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose **Create event data store**.
4. On the **Configure event data store** page, in **General details**, enter a name for the event data store. A name is required.
5. Choose the **Pricing option** that you want to use for your event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention periods for your event data store. For more information, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

The following are the available options:

- **One-year extendable retention pricing** - Generally recommended if you expect to ingest less than 25 TB of event data per month and want a flexible retention period of up to 10 years. For the first 366 days (the default retention period), storage is included at no additional charge with ingestion pricing. After 366 days, extended retention is available at pay-as-you-go pricing. This is the default option.
 - **Default retention period:** 366 days
 - **Maximum retention period:** 3,653 days
 - **Seven-year retention pricing** - Recommended if you expect to ingest more than 25 TB of event data per month and need a retention period of up to 7 years. Retention is included with ingestion pricing at no additional charge.
 - **Default retention period:** 2,557 days
 - **Maximum retention period:** 2,557 days
6. Specify a retention period for the event data store. Retention periods can be between 7 days and 3,653 days (about 10 years) for the **One-year extendable retention pricing** option, or between 7 days and 2,557 days (about seven years) for the **Seven-year retention pricing** option.

CloudTrail Lake determines whether to retain an event by checking if the eventTime of the event is within the specified retention period. For example, if you specify a retention period of 90 days, CloudTrail will remove events when their eventTime is older than 90 days.

 Note

If you are copying trail events to this event data store, CloudTrail will not copy an event if its eventTime is older than the specified retention period. To determine the appropriate retention period, take the sum of the oldest event you want to copy in days and the number of days you want to retain the events in the event data store (**retention period** = *oldest-event-in-days* + *number-days-to-retain*). For example, if the oldest event you're copying is 45 days old and you want to keep the events in the event data store for a further 45 days, you would set the retention period to 90 days.

7. (Optional) To enable encryption using AWS Key Management Service, choose **Use my own AWS KMS key**. Choose **New** to have an AWS KMS key created for you, or choose **Existing** to use an existing KMS key. In **Enter KMS alias**, specify an alias, in the format *alias/MyAliasName*. Using your own KMS key requires that you edit your KMS key policy to allow your event data store to be encrypted and decrypted. For more information, see [Configure AWS KMS key policies for CloudTrail](#). CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

Using your own KMS key incurs AWS KMS costs for encryption and decryption. After you associate an event data store with a KMS key, the KMS key cannot be removed or changed.

 Note

To enable AWS Key Management Service encryption for an organization event data store, you must use an existing KMS key for the management account.

8. (Optional) If you want to query against your event data using Amazon Athena, choose **Enable** in **Lake query federation**. Federation lets you view the metadata associated with the event data store in the AWS Glue [Data Catalog](#) and run SQL queries against the event data in Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know

how to find, read, and process the data that you want to query. For more information, see [Federate an event data store](#).

To enable Lake query federation, choose **Enable** and then do the following:

- a. Choose whether you want to create a new role or use an existing IAM role. [AWS Lake Formation](#) uses this role to manage permissions for the federated event data store. When you create a new role using the CloudTrail console, CloudTrail automatically creates a role with the required permissions. If you choose an existing role, be sure the policy for the role provides the [required minimum permissions](#).
 - b. If you are creating a new role, enter a name to identify the role.
 - c. If you are using an existing role, choose the role you want to use. The role must exist in your account.
9. (Optional) Choose **Enable resource policy** to add a resource-based policy to your event data store. Resource-based policies allow you to control which principals can perform actions on your event data store. For example, you can add a resource based policy that allows the root users in other accounts to query this event data store and view the query results. For example policies, see [Resource-based policy examples for event data stores](#).

A resource-based policy includes one or more statements. Each statement in the policy defines the [principals](#) that are allowed or denied access to the event data store and the actions the principals can perform on the event data store resource.

The following actions are supported in resource-based policies for event data stores:

- `cloudtrail:StartQuery`
- `cloudtrail:CancelQuery`
- `cloudtrail:ListQueries`
- `cloudtrail:DescribeQuery`
- `cloudtrail:GetQueryResults`
- `cloudtrail:GenerateQuery`
- `cloudtrail:GenerateQueryResultsSummary`
- `cloudtrail:GetEventDataStore`

For [organization event data stores](#), CloudTrail creates a [default resource-based policy](#) that lists the actions that the delegated administrator accounts are allowed to perform on organization

event data stores. The permissions in this policy are derived from the delegated administrator permissions in AWS Organizations. This policy is updated automatically following changes to the organization event data store or to the organization (for example, a CloudTrail delegated administrator account is registered or removed).

10. (Optional) In the **Tags** section, you can add up to 50 tag key pairs to help you identify, sort, and control access to your event data store. For more information about how to use IAM policies to authorize access to an event data store based on tags, see [Examples: Denying access to create or delete event data stores based on tags](#). For more information about how you can use tags in AWS, see [Tagging AWS resources](#) in the *Tagging AWS Resources User Guide*.
11. Choose **Next** to configure the event data store.
12. On the **Choose events** page, choose **AWS events**, and then choose **CloudTrail events**.
13. For **CloudTrail events**, choose at least one event type. By default, **Management events** is selected. You can add [management events](#), [data events](#), and [network activity events](#) to your event data store.
14. (Optional) Choose **Copy trail events** if you want to copy events from an existing trail to run queries on past events. To copy trail events to an organization event data store, you must use the management account for the organization. The delegated administrator account cannot copy trail events to an organization event data store. For more information about considerations for copying trail events, see [Considerations for copying trail events](#).
15. To have your event data store collect events from all accounts in an AWS Organizations organization, select **Enable for all accounts in my organization**. You must be signed in to the management account or delegated administrator account for the organization to create an event data store that collects events for an organization.

 Note

To copy trail events or enable Insights events, you must be signed in to the management account for your organization.

16. Expand **Additional settings** to choose whether you want your event data store to collect events for all AWS Regions, or only the current AWS Region, and choose whether the event data store ingests events. By default, your event data store collects events from all Regions in your account and starts ingesting events when it's created.

- a. Select **Include only the current region in my event data store** to include only events that are logged in the current Region. If you do not choose this option, your event data store includes events from all Regions.
 - b. Deselect **Ingest events** if you do not want the event data store to start ingesting events. For example, you may want to deselect **Ingest events**, if you are copying trail events and do not want the event data store to include any future events. By default, the event data store starts ingesting events when it's created.
17. If your event data store includes management events, you can choose from the following options. For more information about management events, see [Logging management events](#).
 - a. Choose between **Simple event collection** or **Advanced event collection**:
 - Choose **Simple event collection** if you want to log all events, log only read events, or log only write events. You can choose also to exclude AWS Key Management Service and Amazon RDS Data API events.
 - Choose **Advanced event collection** if you want to include or exclude management events based on the values of advanced event selector fields, including the `eventName`, `eventType`, `eventSource`, `sessionCredentialFromConsole`, and `userIdentity.arn` fields.
 - b. If you selected **Simple event collection**, choose whether you want to log all events, log only read events, or log only write events. You can also choose to exclude AWS KMS and Amazon RDS Data API events.
 - c. If you selected **Advanced event collection**, make the following selections:
 - i. In **Log selector template**, choose a predefined template, or **Custom** to build a custom configuration based on advanced event selector field values.

You can choose from the following predefined templates:

- **Log all events** – Choose this template to log all events.
- **Log only read events** – Choose this template to log only read events. Read-only events are events that do not change the state of a resource, such as `Get*` or `Describe*` events.
- **Log only write events** – Choose this template to log only write events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events.

- **Log only AWS Management Console events** – Choose this template to log only events originating from the AWS Management Console.
 - **Exclude AWS service initiated events** – Choose this template to exclude AWS service events, which have an eventType of AwsServiceEvent, and events initiated with AWS service-linked roles (SLRs).
- ii. (Optional) In **Selector name**, enter a name to identify your selector. The selector name is a descriptive name for an advanced event selector, such as "Log management events from AWS Management Console sessions". The selector name is listed as Name in the advanced event selector and is viewable if you expand the **JSON view**.
- iii. If you chose **Custom**, in **Advanced event selectors** build an expression based on advanced event selector field values.

 Note

Selectors don't support the use of wildcards like *. To match multiple values with a single condition, you may use `StartsWith`, `EndsWith`, `NotStartsWith`, or `NotEndsWith` to explicitly match the beginning or end of the event field.

A. Choose from the following fields.

- **readOnly** – readOnly can be set to **equals** a value of true or false. When it is set to false, the event data store logs Write-only management events. Read-only management events are events that do not change the state of a resource, such as `Get*` or `Describe*` events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events. To log both **Read** and **Write** events, don't add a readOnly selector.
- **eventName** – eventName can use any operator. You can use it to include or exclude any management event, such as `CreateAccessPoint` or `GetAccessPoint`.
- **userIdentity.arn** – Include or exclude events for actions taken by specific IAM identities. For more information, see [CloudTrail userIdentity element](#).
- **sessionCredentialFromConsole** – Include or exclude events originating from an AWS Management Console session. This field can be set to **equals** or **not equals** with a value of true.

- **eventSource** – You can use it to include or exclude specific event sources. The eventSource is typically a short form of the service name without spaces plus .amazonaws.com. For example, you could set eventSource **equals** to ec2.amazonaws.com to log only Amazon EC2 management events.
 - **eventType** – The [eventType](#) to include or exclude. For example, you can set this field to **not equals** AwsServiceEvent to exclude [AWS service events](#).
- B. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions.

For information about how CloudTrail evaluates multiple conditions, see [How CloudTrail evaluates multiple conditions for a field](#).

 Note

You can have a maximum of 500 values for all selectors on an event data store. This includes arrays of multiple values for a selector such as eventName. If you have single values for all selectors, you can have a maximum of 500 conditions added to a selector.

- C. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields.
- iv. Optionally, expand **JSON view** to see your advanced event selectors as a JSON block.
- d. Choose **Enable Insights events capture** to enable Insights. To enable Insights, you need to set up a [destination event data store](#) to collect Insights events based upon the management event activity in this event data store.

If you choose to enable Insights, do the following.

- Choose the destination event store that will log Insights events. The destination event data store will collect Insights events based upon the management event activity in this event data store. For information about how to create the destination event data store, see [To create a destination event data store that logs Insights events](#).
- Choose the Insights types. You can choose **API call rate**, **API error rate**, or both. You must be logging **Write** management events to log Insights events for **API call rate**. You must be logging **Read** or **Write** management events to log Insights events for **API error rate**.

18. To include data events in your event data store, do the following.

- a. Choose a resource type. This is the AWS service and resource on which data events are logged.
- b. In **Log selector template**, choose a predefined template, or choose **Custom** to define your own event collection conditions based on the values of advanced event selector fields.

You can choose from the following predefined templates:

- **Log all events** – Choose this template to log all events.
 - **Log only read events** – Choose this template to log only read events. Read-only events are events that do not change the state of a resource, such as `Get*` or `Describe*` events.
 - **Log only write events** – Choose this template to log only write events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events.
 - **Log only AWS Management Console events** – Choose this template to log only events originating from the AWS Management Console.
 - **Exclude AWS service initiated events** – Choose this template to exclude AWS service events, which have an `eventType` of `AwsServiceEvent`, and events initiated with AWS service-linked roles (SLRs).
- c. (Optional) In **Selector name**, enter a name to identify your selector. The selector name is a descriptive name for an advanced event selector, such as "Log data events for only two S3 buckets". The selector name is listed as `Name` in the advanced event selector and is viewable if you expand the **JSON view**.
 - d. If you selected **Custom**, in **Advanced event selectors** build an expression based on the values of advanced event selector fields.

 Note

Selectors don't support the use of wildcards like `*`. To match multiple values with a single condition, you may use `StartsWith`, `EndsWith`, `NotStartsWith`, or `NotEndsWith` to explicitly match the beginning or end of the event field.

- i. Choose from the following fields.

- **readOnly** - readOnly can be set to **equals** a value of true or false. Read-only data events are events that do not change the state of a resource, such as Get* or Describe* events. Write events add, change, or delete resources, attributes, or artifacts, such as Put*, Delete*, or Write* events. To log both read and write events, don't add a readOnly selector.
- **eventName** - eventName can use any operator. You can use it to include or exclude any data event logged to CloudTrail, such as PutBucket, GetItem, or GetSnapshotBlock.
- **eventSource** – The event source to include or exclude. This field can use any operator.
- **eventType** – The event type to include or exclude. For example, you can set this field to **not equals** AwsServiceEvent to exclude [AWS service events](#). For a list of event types, see [eventType](#) in [CloudTrail record contents for management, data, and network activity events](#).
- **sessionCredentialFromConsole** – Include or exclude events originating from an AWS Management Console session. This field can be set to **equals** or **not equals** with a value of true.
- **userIdentity.arn** – Include or exclude events for actions taken by specific IAM identities. For more information, see [CloudTrail userIdentity element](#).
- **resources.ARN** - You can use any operator with resources.ARN, but if you use **equals** or **does not equal**, the value must exactly match the ARN of a valid resource of the type you've specified in the template as the value of resources.type.

 Note

You can't use the resources.ARN field to filter resource types that do not have ARNs.

For more information about the ARN formats of data event resources, see [Actions, resources, and condition keys for AWS services](#) in the *Service Authorization Reference*.

- ii. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions. For example, to exclude data events for two S3 buckets from data events that are logged on your event data store,

you can set the field to **resources.ARN**, set the operator for **does not start with**, and then paste in an S3 bucket ARN for which you do not want to log events.

To add the second S3 bucket, choose **+ Condition**, and then repeat the preceding instruction, pasting in the ARN for or browsing for a different bucket.

For information about how CloudTrail evaluates multiple conditions, see [How CloudTrail evaluates multiple conditions for a field](#).

 Note

You can have a maximum of 500 values for all selectors on an event data store. This includes arrays of multiple values for a selector such as `eventName`. If you have single values for all selectors, you can have a maximum of 500 conditions added to a selector.

- iii. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields. For example, do not specify an ARN in one selector to be equal to a value, then specify that the ARN not equal the same value in another selector.
 - e. Optionally, expand **JSON view** to see your advanced event selectors as a JSON block.
 - f. To add another resource type on which to log data events, choose **Add data event type**. Repeat steps a through this step to configure advanced event selectors for the resource type.
19. To include network activity events in your event data store, do the following.
- a. From **Network activity event source**, choose the source for network activity events.
 - b. In **Log selector template**, choose a template. You can choose to log all network activity events, log all network activity access denied events, or choose **Custom** to build a custom log selector to filter on multiple fields, such as `eventName` and `vpcEndpointId`.
 - c. (Optional) Enter a name to identify the selector. The selector name is listed as **Name** in the advanced event selector and is viewable if you expand the **JSON view**.
 - d. In **Advanced event selectors** build expressions by choosing values for **Field**, **Operator**, and **Value**. You can skip this step if you are using a predefined log template.
 - i. For excluding or including network activity events, you can choose from the following fields in the console.

- **eventName** – You can use any operator with eventName. You can use it to include or exclude any event, such as CreateKey.
 - **errorCode** – You can use it to filter on an error code. Currently, the only supported errorCode is VpceAccessDenied.
 - **vpcEndpointId** – Identifies the VPC endpoint that the operation passed through. You can use any operator with vpcEndpointId.
- ii. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions.
 - iii. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields.
- e. To add another event source for which you want to log network activity events, choose **Add network activity event selector**.
 - f. Optionally, expand **JSON view** to see your advanced event selectors as a JSON block.
20. To copy existing trail events to your event data store, do the following.
- a. Choose the trail that you want to copy. By default, CloudTrail only copies CloudTrail events contained in the S3 bucket's CloudTrail prefix and the prefixes inside the CloudTrail prefix, and does not check prefixes for other AWS services. If you want to copy CloudTrail events contained in another prefix, choose **Enter S3 URI**, and then choose **Browse S3** to browse to the prefix. If the source S3 bucket for the trail uses a KMS key for data encryption, ensure that the KMS key policy allows CloudTrail to decrypt the data. If your source S3 bucket uses multiple KMS keys, you must update each key's policy to allow CloudTrail to decrypt the data in the bucket. For more information about updating the KMS key policy, see [KMS key policy for decrypting data in the source S3 bucket](#).
 - b. Choose the time range for copying the events. CloudTrail checks the prefix and log file name to verify the name contains a date between the chosen start and end date before attempting to copy trail events. You can choose a **Relative range** or an **Absolute range**. To avoid duplicating events between the source trail and destination event data store, choose a time range that is earlier than the creation of the event data store.

 Note

CloudTrail only copies trail events that have an eventTime within the event data store's retention period. For example, if an event data store's retention period is 90

days, then CloudTrail will not copy any trail events with an eventTime older than 90 days.

- If you choose **Relative range**, you can choose to copy events logged in the last 6 months, 1 year, 2 years, 7 years, or a custom range. CloudTrail copies the events logged within the chosen time period.
 - If you choose **Absolute range**, you can choose a specific start and end date. CloudTrail copies the events that occurred between the chosen start and end dates.
- c. For **Permissions**, choose from the following IAM role options. If you choose an existing IAM role, verify that the IAM role policy provides the necessary permissions. For more information about updating the IAM role permissions, see [IAM permissions for copying trail events](#).
- Choose **Create a new role (recommended)** to create a new IAM role. For **Enter IAM role name**, enter a name for the role. CloudTrail automatically creates the necessary permissions for this new role.
 - Choose **Use a custom IAM role ARN** to use a custom IAM role that is not listed. For **Enter IAM role ARN**, enter the IAM ARN.
 - Choose an existing IAM role from the drop-down list.
21. Choose **Next** to enrich your events by adding resource tag keys and IAM global condition keys.
22. In **Enrich events**, add up to 50 resource tag keys and 50 IAM global condition keys to provide additional metadata about your events. This helps you categorize and group related events.

If you add resource tag keys, CloudTrail will include the selected tag keys associated with the resources that were involved in the API call. API events related to deleted resources will not have resource tags.

If you add IAM global condition keys, CloudTrail will include information about the selected condition keys that were evaluated during the authorization process, including additional details about the principal, session, network, and the request itself.

Information about the resource tag keys and IAM global condition keys is shown in the eventContext field of the event. For more information, see [Enrich CloudTrail events by adding resource tag keys and IAM global condition keys](#).

 Note

If an event contains a resource that doesn't belong to the event Region, CloudTrail will not populate tags for this resource because tag retrieval is limited to the event Region.

23. Choose **Expand event size** to expand the event payload up to 1 MB from 256 KB. This option is automatically enabled when you add resource tag keys or IAM global condition keys to ensure all of your added keys are included in the event.

Expanding the event size is helpful for analyzing and troubleshooting events because it allows you to see the full contents of the following fields as long as the event payload is less than 1 MB:

- `annotation`
- `requestID`
- `additionalEventData`
- `serviceEventDetails`
- `userAgent`
- `errorCode`
- `responseElements`
- `requestParameters`
- `errorMessage`

For more information about these fields, see [CloudTrail record contents](#).

24. Choose **Next** to review your choices.
25. On the **Review and create** page, review your choices. Choose **Edit** to make changes to a section. When you're ready to create the event data store, choose **Create event data store**.
26. The new event data store is visible in the **Event data stores** table on the **Event data stores** page.

From this point forward, the event data store captures events that match its advanced event selectors (if you kept the **Ingest events** option selected). Events that occurred before you created the event data store are not in the event data store, unless you opted to copy existing trail events.

You can now run queries on your new event data store. The **Sample queries** tab provides example queries to get you started. For more information about creating and editing queries, see [Create or edit a query with the CloudTrail console](#).

You can also view the [managed dashboards](#), or [create custom dashboards](#) to visualize event trends. For more information about Lake dashboards, see [CloudTrail Lake dashboards](#).

Create an event data store for Insights events with the console

AWS CloudTrail Insights help AWS users identify and respond to unusual activity associated with API call rates and API error rates by continuously analyzing CloudTrail management events. CloudTrail Insights analyze your normal patterns of API call rates and API error rates, also called the *baseline*, and generate Insights events when the call volume or error rates are outside normal patterns. Insights events on API call rate are generated for `write` management APIs, and Insights events on API error rate are generated for both `read` and `write` management APIs.

To log Insights events in CloudTrail Lake, you need a destination event data store that logs Insights events and a source event data store that enables Insights and logs management events.

Note

To log Insights events on the API call rate, the source event data store must log `write` management events. To log Insights events on the API error rate, the source event data store must log `read` or `write` management events.

If you have CloudTrail Insights enabled on a source event data store and CloudTrail detects unusual activity, CloudTrail delivers Insights events to your destination event data store. Unlike other types of events captured in a CloudTrail event data store, Insights events are logged only when CloudTrail detects changes in your account's API usage that differ significantly from the account's typical usage patterns.

After you enable CloudTrail Insights for the first time on an event data store, CloudTrail may take up to 7 days to begin delivering Insights events, provided that unusual activity is detected during that time.

CloudTrail Insights analyzes the management events that occur in each Region for the event data store and generates an Insights events when unusual activity is detected that deviates from the baseline. A CloudTrail Insights event is generated in the same Region as its supporting management event is generated.

For an organization event data store, CloudTrail Insights analyzes the management events from each member account in the organization for each Region and generates an Insights event when unusual activity is detected that deviates from the baseline for the account and the Region.

Additional charges apply for ingesting Insights events in CloudTrail Lake. You will be charged separately if you enable Insights for both trails and CloudTrail Lake event data stores. For information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Topics

- [To create a destination event data store that logs Insights events](#)
- [To create a source event data store that enables Insights events](#)

To create a destination event data store that logs Insights events

When you create an Insights event data store, you have the option to choose an existing source event data store that logs management events and then specify the Insights types you want to receive. Or, you can alternatively enable Insights on a new or existing event data store after you create your Insights event data store and then choose this event data store as the destination event data store.

This procedure shows you how to create a destination event data store that logs Insights events.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, open the **Lake** submenu, then choose **Event data stores**.
3. Choose **Create event data store**.
4. On the **Configure event data store** page, in **General details**, enter a name for the event data store. A name is required.
5. Choose the **Pricing option** that you want to use for your event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention periods for your event data store. For more information, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

The following are the available options:

- **One-year extendable retention pricing** - Generally recommended if you expect to ingest less than 25 TB of event data per month and want a flexible retention period of up to 10 years. For the first 366 days (the default retention period), storage is included at no

additional charge with ingestion pricing. After 366 days, extended retention is available at pay-as-you-go pricing. This is the default option.

- **Default retention period:** 366 days
 - **Maximum retention period:** 3,653 days
 - **Seven-year retention pricing** - Recommended if you expect to ingest more than 25 TB of event data per month and need a retention period of up to 7 years. Retention is included with ingestion pricing at no additional charge.
 - **Default retention period:** 2,557 days
 - **Maximum retention period:** 2,557 days
6. Specify a retention period for the event data store in days. Retention periods can be between 7 days and 3,653 days (about 10 years) for the **One-year extendable retention pricing** option, or between 7 days and 2,557 days (about seven years) for the **Seven-year retention pricing** option. The event data store retains event data for the specified number of days.
7. (Optional) To enable encryption using AWS Key Management Service, choose **Use my own AWS KMS key**. Choose **New** to have an AWS KMS key created for you, or choose **Existing** to use an existing KMS key. In **Enter KMS alias**, specify an alias, in the format `alias/MyAliasName`. Using your own KMS key requires that you edit your KMS key policy to allow your event data store to be encrypted and decrypted. For more information, see [Configure AWS KMS key policies for CloudTrail](#). CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

Using your own KMS key incurs AWS KMS costs for encryption and decryption. After you associate an event data store with a KMS key, the KMS key cannot be removed or changed.

 Note

To enable AWS Key Management Service encryption for an organization event data store, you must use an existing KMS key for the management account.

8. (Optional) If you want to query against your event data using Amazon Athena, choose **Enable** in **Lake query federation**. Federation lets you view the metadata associated with the event data store in the AWS Glue [Data Catalog](#) and run SQL queries against the event data in Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know how to find, read, and process the data that you want to query. For more information, see [Federate an event data store](#).

To enable Lake query federation, choose **Enable** and then do the following:

- a. Choose whether you want to create a new role or use an existing IAM role. [AWS Lake Formation](#) uses this role to manage permissions for the federated event data store. When you create a new role using the CloudTrail console, CloudTrail automatically creates a role with the required permissions. If you choose an existing role, be sure the policy for the role provides the [required minimum permissions](#).
 - b. If you are creating a new role, enter a name to identify the role.
 - c. If you are using an existing role, choose the role you want to use. The role must exist in your account.
9. (Optional) Choose **Enable resource policy** to add a resource-based policy to your event data store. Resource-based policies allow you to control which principals can perform actions on your event data store. For example, you can add a resource based policy that allows the root users in other accounts to query this event data store and view the query results. For example policies, see [Resource-based policy examples for event data stores](#).

A resource-based policy includes one or more statements. Each statement in the policy defines the [principals](#) that are allowed or denied access to the event data store and the actions the principals can perform on the event data store resource.

The following actions are supported in resource-based policies for event data stores:

- `cloudtrail:StartQuery`
- `cloudtrail:CancelQuery`
- `cloudtrail:ListQueries`
- `cloudtrail:DescribeQuery`
- `cloudtrail:GetQueryResults`
- `cloudtrail:GenerateQuery`
- `cloudtrail:GenerateQueryResultsSummary`
- `cloudtrail:GetEventDataStore`

For [organization event data stores](#), CloudTrail creates a [default resource-based policy](#) that lists the actions that the delegated administrator accounts are allowed to perform on organization event data stores. The permissions in this policy are derived from the delegated administrator permissions in AWS Organizations. This policy is updated automatically following changes to

the organization event data store or to the organization (for example, a CloudTrail delegated administrator account is registered or removed).

10. (Optional) In the **Tags** section, you can add up to 50 tag key pairs to help you identify, sort, and control access to your event data store. For more information about how to use IAM policies to authorize access to an event data store based on tags, see [Examples: Denying access to create or delete event data stores based on tags](#). For more information about how you can use tags in AWS, see [Tagging AWS resources](#) in the *Tagging AWS Resources User Guide*.
11. Choose **Next** to configure the event data store.
12. On the **Choose events** page, choose **AWS events**, and then choose **CloudTrail Insights events**.
13. In **CloudTrail Insights events**, do the following.
 - a. Choose **Allow delegated administrator access** if you want to give your organization's delegated administrator access to this event data store. This option is only available if you are signed in with the management account for an AWS Organizations organization.
 - b. (Optional) Choose an existing source event data store that logs management events and specify the Insights types you want to receive.

To add a source event data store, do the following.

- i. Choose **Add source event data store**.
 - ii. Choose the source event data store.
 - iii. Choose the **Insights type** that you want to receive.
 - **ApiCallRateInsight** – The **ApiCallRateInsight** Insights type analyzes write-only management API calls that are aggregated per minute against a baseline API call volume. To receive Insights on **ApiCallRateInsight**, the source event data store must log **Write** management events.
 - **ApiErrorRateInsight** – The **ApiErrorRateInsight** Insights type analyzes management API calls that result in error codes. The error is shown if the API call is unsuccessful. To receive Insights on **ApiErrorRateInsight**, the source event data store must log **Write** or **Read** management events.
 - iv. Repeat the previous two steps (ii and iii) to add any additional Insights types you want to receive.
14. Choose **Next** to review your choices.
 15. On the **Review and create** page, review your choices. Choose **Edit** to make changes to a section. When you're ready to create the event data store, choose **Create event data store**.

16. The new event data store is visible in the **Event data stores** table on the **Event data stores** page.
17. If you did not choose a source event data store in step 10, follow the steps in [To create a source event data store that enables Insights events](#) to create a source event data store.

To create a source event data store that enables Insights events

This procedure shows you how to create a source event data store that enables Insights events and logs management events.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, open the **Lake** submenu, then choose **Event data stores**.
3. Choose **Create event data store**.
4. On the **Configure event data store** page, in **General details**, enter a name for the event data store. A name is required.
5. Choose the **Pricing option** that you want to use for your event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention periods for your event data store. For more information, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

The following are the available options:

- **One-year extendable retention pricing** - Generally recommended if you expect to ingest less than 25 TB of event data per month and want a flexible retention period of up to 10 years. For the first 366 days (the default retention period), storage is included at no additional charge with ingestion pricing. After 366 days, extended retention is available at pay-as-you-go pricing. This is the default option.
 - **Default retention period:** 366 days
 - **Maximum retention period:** 3,653 days
- **Seven-year retention pricing** - Recommended if you expect to ingest more than 25 TB of event data per month and need a retention period of up to 7 years. Retention is included with ingestion pricing at no additional charge.
 - **Default retention period:** 2,557 days
 - **Maximum retention period:** 2,557 days

6. Specify a retention period for the event data store. Retention periods can be between 7 days and 3,653 days (about 10 years) for the **One-year extendable retention pricing** option, or between 7 days and 2,557 days (about seven years) for the **Seven-year retention pricing** option.

CloudTrail Lake determines whether to retain an event by checking if the `eventTime` of the event is within the specified retention period. For example, if you specify a retention period of 90 days, CloudTrail will remove events when their `eventTime` is older than 90 days.

7. (Optional) To enable encryption using AWS Key Management Service, choose **Use my own AWS KMS key**. Choose **New** to have an AWS KMS key created for you, or choose **Existing** to use an existing KMS key. In **Enter KMS alias**, specify an alias, in the format `alias/MyAliasName`. Using your own KMS key requires that you edit your KMS key policy to allow your event data store to be encrypted and decrypted. For more information, see [Configure AWS KMS key policies for CloudTrail](#). CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

Using your own KMS key incurs AWS KMS costs for encryption and decryption. After you associate an event data store with a KMS key, the KMS key cannot be removed or changed.

 Note

To enable AWS Key Management Service encryption for an organization event data store, you must use an existing KMS key for the management account.

8. (Optional) If you want to query against your event data using Amazon Athena, choose **Enable** in **Lake query federation**. Federation lets you view the metadata associated with the event data store in the AWS Glue [Data Catalog](#) and run SQL queries against the event data in Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know how to find, read, and process the data that you want to query. For more information, see [Federate an event data store](#).

To enable Lake query federation, choose **Enable** and then do the following:

- a. Choose whether you want to create a new role or use an existing IAM role. [AWS Lake Formation](#) uses this role to manage permissions for the federated event data store. When you create a new role using the CloudTrail console, CloudTrail automatically creates a role

with the required permissions. If you choose an existing role, be sure the policy for the role provides the [required minimum permissions](#).

- b. If you are creating a new role, enter a name to identify the role.
 - c. If you are using an existing role, choose the role you want to use. The role must exist in your account.
9. (Optional) Choose **Enable resource policy** to add a resource-based policy to your event data store. Resource-based policies allow you to control which principals can perform actions on your event data store. For example, you can add a resource based policy that allows the root users in other accounts to query this event data store and view the query results. For example policies, see [Resource-based policy examples for event data stores](#).

A resource-based policy includes one or more statements. Each statement in the policy defines the [principals](#) that are allowed or denied access to the event data store and the actions the principals can perform on the event data store resource.

The following actions are supported in resource-based policies for event data stores:

- `cloudtrail:StartQuery`
- `cloudtrail:CancelQuery`
- `cloudtrail:ListQueries`
- `cloudtrail:DescribeQuery`
- `cloudtrail:GetQueryResults`
- `cloudtrail:GenerateQuery`
- `cloudtrail:GenerateQueryResultsSummary`
- `cloudtrail:GetEventDataStore`

For [organization event data stores](#), CloudTrail creates a [default resource-based policy](#) that lists the actions that the delegated administrator accounts are allowed to perform on organization event data stores. The permissions in this policy are derived from the delegated administrator permissions in AWS Organizations. This policy is updated automatically following changes to the organization event data store or to the organization (for example, a CloudTrail delegated administrator account is registered or removed).

10. (Optional) In the **Tags** section, you can add up to 50 tag key pairs to help you identify, sort, and control access to your event data store. For more information about how to use IAM [policies to authorize access to an event data store based on tags](#), see [Examples: Denying access](#)

[to create or delete event data stores based on tags](#). For more information about how you can use tags in AWS, see [Tagging AWS resources](#) in the *Tagging AWS Resources User Guide*.

11. Choose **Next** to configure the event data store.
12. On the **Choose events** page, choose **AWS events**, and then choose **CloudTrail events**.
13. In **CloudTrail events**, leave **Management events** selected.
14. To have your event data store collect events from all accounts in an AWS Organizations organization, select **Enable for all accounts in my organization**. You must be signed in to the management account for the organization to create an event data store that enables Insights.
15. Expand **Additional settings** to choose whether you want your event data store to collect events for all AWS Regions, or only the current AWS Region, and choose whether the event data store ingests events. By default, your event data store collects events from all Regions in your account and starts ingesting events when it's created.
 - a. Choose **Include only the current region in my event data store** if you want to include only events that are logged in the current Region. If you do not choose this option, your event data store includes events from all Regions.
 - b. Leave **Ingest events** selected.
16. Choose between **Simple event collection** or **Advanced event collection**:
 - Choose **Simple event collection** if you want to log all events, log only read events, or log only write events. You can choose also to exclude AWS Key Management Service and Amazon RDS Data API events.
 - Choose **Advanced event collection** if you want to include or exclude management events based on the values of advanced event selector fields, including the `eventName`, `eventType`, `eventSource`, `sessionCredentialFromConsole`, and `userIdentity.arn` fields.
17. If you selected **Simple event collection**, choose whether you want to log all events, log only read events, or log only write events. You can also choose to exclude AWS KMS and Amazon RDS Data API events.
18. If you selected **Advanced event collection**, make the following selections:
 - a. In **Log selector template**, choose a predefined template, or choose **Custom** to write your own event collection conditions based on the values of advanced event selector fields.

You can choose from the following predefined templates:

- **Log all events** – Choose this template to log all events.
 - **Log only read events** – Choose this template to log only read events. Read-only events are events that do not change the state of a resource, such as `Get*` or `Describe*` events.
 - **Log only write events** – Choose this template to log only write events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events.
 - **Log only AWS Management Console events** – Choose this template to log only events originating from the AWS Management Console.
 - **Exclude AWS service initiated events** – Choose this template to exclude AWS service events, which have an `eventType` of `AwsServiceEvent`, and events initiated with AWS service-linked roles (SLRs).
- b. (Optional) In **Selector name**, enter a name to identify your selector. The selector name is a descriptive name for an advanced event selector, such as "Log management events from AWS Management Console sessions". The selector name is listed as `Name` in the advanced event selector and is viewable if you expand the **JSON view**.
- c. If you chose **Custom**, in **Advanced event selectors** build an expression based on advanced event selector field values.

 Note

Selectors don't support the use of wildcards like `*`. To match multiple values with a single condition, you may use `StartsWith`, `EndsWith`, `NotStartsWith`, or `NotEndsWith` to explicitly match the beginning or end of the event field.

- i. Choose from the following fields.
- **readOnly** – `readOnly` can be set to **equals** a value of `true` or `false`. When it is set to `false`, the event data store logs Write-only management events. Read-only management events are events that do not change the state of a resource, such as `Get*` or `Describe*` events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events. To log both **Read** and **Write** events, don't add a `readOnly` selector.

- **eventName** – eventName can use any operator. You can use it to include or exclude any management event, such as CreateAccessPoint or GetAccessPoint.
 - **userIdentity.arn** – Include or exclude events for actions taken by specific IAM identities. For more information, see [CloudTrail userIdentity element](#).
 - **sessionCredentialFromConsole** – Include or exclude events originating from an AWS Management Console session. This field can be set to **equals** or **not equals** with a value of true.
 - **eventSource** – You can use it to include or exclude specific event sources. The eventSource is typically a short form of the service name without spaces plus .amazonaws.com. For example, you could set eventSource **equals** to ec2.amazonaws.com to log only Amazon EC2 management events.
 - **eventType** – The [eventType](#) to include or exclude. For example, you can set this field to **not equals** AwsServiceEvent to exclude [AWS service events](#).
- ii. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions.

For information about how CloudTrail evaluates multiple conditions, see [How CloudTrail evaluates multiple conditions for a field](#).

 Note

You can have a maximum of 500 values for all selectors on an event data store. This includes arrays of multiple values for a selector such as eventName. If you have single values for all selectors, you can have a maximum of 500 conditions added to a selector.

- iii. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields.
- d. Optionally, expand **JSON view** to see your advanced event selectors as a JSON block.
19. Choose **Enable Insights events capture**.
20. Choose the destination event store that will log Insights events. The destination event data store will collect Insights events based upon the management event activity in this event data store. For information about how to create the destination event data store, see [To create a destination event data store that logs Insights events](#).

21. Choose the Insights types. You can choose **API call rate**, **API error rate**, or both. You must be logging **Write** management events to log Insights events for **API call rate**. You must be logging **Read** or **Write** management events to log Insights events for **API error rate**.
22. Choose **Next** to enrich your events by adding resource tag keys and IAM global condition keys.
23. In **Enrich events**, add up to 50 resource tag keys and 50 IAM global condition keys to provide additional metadata about your events. This helps you categorize and group related events.

If you add resource tag keys, CloudTrail will include the selected tag keys associated with the resources that were involved in the API call. API events related to deleted resources will not have resource tags.

If you add IAM global condition keys, CloudTrail will include information about the selected condition keys that were evaluated during the authorization process, including additional details about the principal, session, network, and the request itself.

Information about the resource tag keys and IAM global condition keys is shown in the `eventContext` field of the event. For more information, see [Enrich CloudTrail events by adding resource tag keys and IAM global condition keys](#).

 Note

If an event contains a resource that doesn't belong to the event Region, CloudTrail will not populate tags for this resource because tag retrieval is limited to the event Region.

24. Choose **Expand event size** to expand the event payload up to 1 MB from 256 KB. This option is automatically enabled when you add resource tag keys or IAM global condition keys to ensure all of your added keys are included in the event.

Expanding the event size is helpful for analyzing and troubleshooting events because it allows you to see the full contents of the following fields as long as the event payload is less than 1 MB:

- `annotation`
- `requestID`
- `additionalEventData`
- `serviceEventDetails`
- `userAgent`

- `errorCode`
- `responseElements`
- `requestParameters`
- `errorMessage`

For more information about these fields, see [CloudTrail record contents](#).

25. Choose **Next** to review your choices.
26. On the **Review and create** page, review your choices. Choose **Edit** to make changes to a section. When you're ready to create the event data store, choose **Create event data store**.
27. The new event data store is visible in the **Event data stores** table on the **Event data stores** page.

From this point forward, the event data store captures events that match its advanced event selectors. After you enable CloudTrail Insights for the first time on your source event data store, CloudTrail may take up to 7 days to begin delivering Insights events, provided that unusual activity is detected during that time.

You can view the CloudTrail Lake dashboard to visualize the Insights events in your destination event data store. For more information about Lake dashboards, see [CloudTrail Lake dashboards](#).

Additional charges apply for ingesting Insights events in CloudTrail Lake. You will be charged separately if you enable Insights for both trails and event data stores. For information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Create an event data store for configuration items with the console

You can create an event data store to include [AWS Config configuration items](#), and use the event data store to investigate non-compliant changes to your production environments. With an event data store, you can relate non-compliant rules to the users and resources associated with the changes. A configuration item represents a point-in-time view of the attributes of a supported AWS resource that exists in your account. AWS Config creates a configuration item whenever it detects a change to a resource type that it is recording. AWS Config also creates configuration items when a configuration snapshot is captured.

You can use both AWS Config and CloudTrail Lake to run queries against your configuration items. You can use AWS Config to query the current configuration state of AWS resources based on configuration properties for a single AWS account and AWS Region, or across multiple accounts and Regions. In contrast, you can use CloudTrail Lake to query across diverse data sources such as CloudTrail events, configuration items, and rule evaluations. CloudTrail Lake queries cover all AWS Config configuration items including resource configuration and compliance history.

Creating an event data store for configuration items doesn't impact existing AWS Config advanced queries, or any configured AWS Config aggregators. You can continue to run advanced queries using AWS Config, and AWS Config continues to deliver history files to your S3 buckets.

CloudTrail Lake event data stores incur charges. When you create an event data store, you choose the [pricing option](#) you want to use for the event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention period for the event data store. For information about CloudTrail pricing and managing Lake costs, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

Limitations

The following limitations apply to event data stores for configuration items.

- No support for custom configuration items
- No support for event filtering using advanced event selectors

Prerequisites

Before you create your event data store, set up AWS Config recording for all your accounts and Regions. You can use [Quick Setup](#), a capability of AWS Systems Manager, to quickly create a configuration recorder powered by AWS Config.

Note

You are charged service usage fees when AWS Config starts recording configurations. For more information about pricing, see [AWS Config Pricing](#). For information about managing the configuration recorder, see [Managing the Configuration Recorder](#) in the *AWS Config Developer Guide*.

Additionally, the following actions are recommended, but are not required to create an event data store.

- Set up an Amazon S3 bucket to receive a configuration snapshot on request and configuration history. For more information about snapshots, see [Managing the Delivery Channel](#) and [Delivering Configuration Snapshot to an Amazon S3 Bucket](#) in the *AWS Config Developer Guide*.
- Specify the rules that you want AWS Config to use to evaluate compliance information for the recorded resource types. Several of the CloudTrail Lake sample queries for AWS Config require AWS Config Rules to evaluate the compliance state of your AWS resources. For more information about AWS Config Rules, see [Evaluating Resources with AWS Config Rules](#) in the *AWS Config Developer Guide*.

To create an event data store for configuration items

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose **Create event data store**.
4. On the **Configure event data store** page, in **General details**, enter a name for the event data store. A name is required.
5. Choose the **Pricing option** that you want to use for your event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention periods for your event data store. For more information, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

The following are the available options:

- **One-year extendable retention pricing** - Generally recommended if you expect to ingest less than 25 TB of event data per month and want a flexible retention period of up to 10 years. For the first 366 days (the default retention period), storage is included at no additional charge with ingestion pricing. After 366 days, extended retention is available at pay-as-you-go pricing. This is the default option.
 - **Default retention period:** 366 days
 - **Maximum retention period:** 3,653 days

- **Seven-year retention pricing** - Recommended if you expect to ingest more than 25 TB of event data per month and need a retention period of up to 7 years. Retention is included with ingestion pricing at no additional charge.
 - **Default retention period:** 2,557 days
 - **Maximum retention period:** 2,557 days
6. Specify a retention period for the event data store. Retention periods can be between 7 days and 3,653 days (about 10 years) for the **One-year extendable retention pricing** option, or between 7 days and 2,557 days (about seven years) for the **Seven-year retention pricing** option.

CloudTrail Lake determines whether to retain an event by checking if the `eventTime` of the event is within the specified retention period. For example, if you specify a retention period of 90 days, CloudTrail will remove events when their `eventTime` is older than 90 days.

7. (Optional) To enable encryption using AWS Key Management Service, choose **Use my own AWS KMS key**. Choose **New** to have an AWS KMS key created for you, or choose **Existing** to use an existing KMS key. In **Enter KMS alias**, specify an alias, in the format `alias/MyAliasName`. Using your own KMS key requires that you edit your KMS key policy to allow your event data store to be encrypted and decrypted. For more information, see [Configure AWS KMS key policies for CloudTrail](#). CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

Using your own KMS key incurs AWS KMS costs for encryption and decryption. After you associate an event data store with a KMS key, the KMS key cannot be removed or changed.

 Note

To enable AWS Key Management Service encryption for an organization event data store, you must use an existing KMS key for the management account.

8. (Optional) If you want to query against your event data using Amazon Athena, choose **Enable** in **Lake query federation**. Federation lets you view the metadata associated with the event data store in the AWS Glue [Data Catalog](#) and run SQL queries against the event data in Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know how to find, read, and process the data that you want to query. For more information, see [Federate an event data store](#).

To enable Lake query federation, choose **Enable** and then do the following:

- a. Choose whether you want to create a new role or use an existing IAM role. [AWS Lake Formation](#) uses this role to manage permissions for the federated event data store. When you create a new role using the CloudTrail console, CloudTrail automatically creates a role with the required permissions. If you choose an existing role, be sure the policy for the role provides the [required minimum permissions](#).
 - b. If you are creating a new role, enter a name to identify the role.
 - c. If you are using an existing role, choose the role you want to use. The role must exist in your account.
9. (Optional) Choose **Enable resource policy** to add a resource-based policy to your event data store. Resource-based policies allow you to control which principals can perform actions on your event data store. For example, you can add a resource based policy that allows the root users in other accounts to query this event data store and view the query results. For example policies, see [Resource-based policy examples for event data stores](#).

A resource-based policy includes one or more statements. Each statement in the policy defines the [principals](#) that are allowed or denied access to the event data store and the actions the principals can perform on the event data store resource.

The following actions are supported in resource-based policies for event data stores:

- `cloudtrail:StartQuery`
- `cloudtrail:CancelQuery`
- `cloudtrail:ListQueries`
- `cloudtrail:DescribeQuery`
- `cloudtrail:GetQueryResults`
- `cloudtrail:GenerateQuery`
- `cloudtrail:GenerateQueryResultsSummary`
- `cloudtrail:GetEventDataStore`

For [organization event data stores](#), CloudTrail creates a [default resource-based policy](#) that lists the actions that the delegated administrator accounts are allowed to perform on organization event data stores. The permissions in this policy are derived from the delegated administrator permissions in AWS Organizations. This policy is updated automatically following changes to

the organization event data store or to the organization (for example, a CloudTrail delegated administrator account is registered or removed).

10. (Optional) In the **Tags** section, you can add up to 50 tag key pairs to help you identify, sort, and control access to your event data store. For more information about how to use IAM policies to authorize access to an event data store based on tags, see [Examples: Denying access to create or delete event data stores based on tags](#). For more information about how you can use tags in AWS, see [Tagging AWS resources](#) in the *Tagging AWS Resources User Guide*.
11. Choose **Next**.
12. On the **Choose events** page, choose **AWS events**, and then choose **Configuration items**.
13. CloudTrail stores the event data store resource in the Region in which you create it, but by default, the configuration items collected in the data store are from all Regions in your account that have recording enabled. Optionally, you can select **Include only the current region in my event data store** to include only configuration items that are captured in the current Region. If you do not choose this option, your event data store includes configuration items from all Regions that have recording enabled.
14. To have your event data store collect configuration items from all accounts in an AWS Organizations organization, select **Enable for all accounts in my organization**. You must be signed in to the management account or delegated administrator account for the organization to create an event data store that collects configuration items for an organization.
15. Choose **Next** to review your choices.
16. On the **Review and create** page, review your choices. Choose **Edit** to make changes to a section. When you're ready to create the event data store, choose **Create event data store**.
17. The new event data store is visible in the **Event data stores** table on the **Event data stores** page.

From this point forward, the event data store captures configuration items. Configuration items that occurred before you created the event data store are not in the event data store.

Configuration item schema

The following table describes the required and optional schema elements that match those in configuration item records. The contents of `eventData` are provided by your configuration items; other fields are provided by CloudTrail after ingestion.

CloudTrail event record contents are described in more detail in [CloudTrail record contents for management, data, and network activity events](#).

- [Fields that are provided by CloudTrail after ingestion](#)
- [Fields that are provided by your events](#)

Fields that are provided by CloudTrail after ingestion

Field name	Input type	Requirement	Description
eventVersion	string	Required	The version of the AWS event format.
eventCategory	string	Required	The event category. For configuration items, the valid value is ConfigurationItem .
eventType	string	Required	The event type. For configuration items, the valid value is AwsConfigurationItem .
eventId	string	Required	A unique ID for an event.
eventTime	string	Required	The event timestamp , in yyyy-MM-DDTHH:mm:ss format, in Universal Coordinated Time (UTC).
awsRegion	string	Required	The AWS Region to which to assign an event.

Field name	Input type	Requirement	Description
recipientAccountId	string	Required	Represents the AWS account ID that received this event.
addendum	addendum	Optional	Shows information about why an event was delayed. If information was missing from an existing event, the addendum block includes the missing information and a reason for why it was missing.

Fields in eventData are provided by your configuration items

Field name	Input type	Requirement	Description
eventData	-	Required	Fields in eventData are provided by your configuration items.
• configurationItemVersion	string	Optional	The version of the configuration item from its source.
• configurationItemCaptureTime	string	Optional	The time when the configuration recording was initiated.
• configurationItemStatus	string	Optional	The configuration item status.

Field name	Input type	Requirement	Description
			Valid values are OK, ResourceDiscovered, ResourceNotRecorded, ResourceDeleted, and ResourceDeletedNotRecorded.
• accountId	string	Optional	The 12-digit AWS account ID associated with the resource.
• resourceType	string	Optional	The type of AWS resource. For more information about valid resource types, see ConfigurationItem in the <i>AWS Config API Reference</i> .
• resourceId	string	Optional	The ID of the resource (for example, sg- xxxxxx).
• resourceName	string	Optional	The custom name of the resource, if available.
• arn	string	Optional	Amazon Resource Name (ARN) associated with the resource.

Field name	Input type	Requirement	Description
• awsRegion	string	Optional	The AWS Region where the resource resides.
• availabilityZone	string	Optional	The Availability Zone associated with the resource.
• resourceCreationTime	string	Optional	The time stamp when the resource was created.
• configuration	JSON	Optional	The description of the resource configuration.
• supplementaryConfiguration	JSON	Optional	Configuration attributes that AWS Config returns for certain resource types to supplement the information returned for the configuration parameter.
• relatedEvents	string	Optional	A list of CloudTrail event IDs.
• relationships	-	Optional	A list of related AWS resources.
• • name	string	Optional	The type of relationship with the related resource.
• • resourceType	string	Optional	The resource type of the related resource.

Field name	Input type	Requirement	Description
• resourceId	string	Optional	The ID of the related resource (for example, sg- xxxxxx).
• resourceName	string	Optional	The custom name of the related resource, if available.
• tags	JSON	Optional	A mapping of key value tags associated with the resource.

The following example shows the hierarchy of schema elements that match those in configuration item records.

```
{
  "eventVersion": String,
  "eventCategory": String,
  "eventType": String,
  "eventID": String,
  "eventTime": String,
  "awsRegion": String,
  "recipientAccountId": String,
  "addendum": Addendum,
  "eventData": {
    "configurationItemVersion": String,
    "configurationItemCaptureTime": String,
    "configurationItemStatus": String,
    "configurationStateId": String,
    "accountId": String,
    "resourceType": String,
    "resourceId": String,
    "resourceName": String,
    "arn": String,
    "awsRegion": String,
    "availabilityZone": String,
    "resourceCreationTime": String,
    "configuration": {
```

```

        JSON,
    },
    "supplementaryConfiguration": {
        JSON,
    },
    "relatedEvents": [
        String
    ],
    "relationships": [
        struct{
            "name" : String,
            "resourceType": String,
            "resourceId": String,
            "resourceName": String
        }
    ],
    "tags": {
        JSON
    }
}
}
}

```

Create an event data store for events outside of AWS with the console

You can create an event data store to include events outside of AWS, and then use CloudTrail Lake to search, query, and analyze the data that is logged from your applications.

You can use CloudTrail Lake *integrations* to log and store user activity data from outside of AWS; from any source in your hybrid environments, such as in-house or SaaS applications hosted on-premises or in the cloud, virtual machines, or containers.

When you create an event data store for an integration, you also create a channel, and attach a resource policy to the channel.

CloudTrail Lake event data stores incur charges. When you create an event data store, you choose the [pricing option](#) you want to use for the event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention period for the event data store. For information about CloudTrail pricing and managing Lake costs, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

To create an event data store for events outside of AWS

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose **Create event data store**.
4. On the **Configure event data store** page, in **General details**, enter a name for the event data store. A name is required.
5. Choose the **Pricing option** that you want to use for your event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention periods for your event data store. For more information, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

The following are the available options:

- **One-year extendable retention pricing** - Generally recommended if you expect to ingest less than 25 TB of event data per month and want a flexible retention period of up to 10 years. For the first 366 days (the default retention period), storage is included at no additional charge with ingestion pricing. After 366 days, extended retention is available at pay-as-you-go pricing. This is the default option.
 - **Default retention period:** 366 days
 - **Maximum retention period:** 3,653 days
 - **Seven-year retention pricing** - Recommended if you expect to ingest more than 25 TB of event data per month and need a retention period of up to 7 years. Retention is included with ingestion pricing at no additional charge.
 - **Default retention period:** 2,557 days
 - **Maximum retention period:** 2,557 days
6. Specify a retention period for the event data store. Retention periods can be between 7 days and 3,653 days (about 10 years) for the **One-year extendable retention pricing** option, or between 7 days and 2,557 days (about seven years) for the **Seven-year retention pricing** option.

CloudTrail Lake determines whether to retain an event by checking if the `eventTime` of the event is within the specified retention period. For example, if you specify a retention period of 90 days, CloudTrail will remove events when their `eventTime` is older than 90 days.

7. (Optional) To enable encryption using AWS Key Management Service, choose **Use my own AWS KMS key**. Choose **New** to have an AWS KMS key created for you, or choose **Existing** to use an existing KMS key. In **Enter KMS alias**, specify an alias, in the format `alias/MyAliasName`. Using your own KMS key requires that you edit your KMS key policy to allow your event data store to be encrypted and decrypted. For more information, see [Configure AWS KMS key policies for CloudTrail](#). CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

Using your own KMS key incurs AWS KMS costs for encryption and decryption. After you associate an event data store with a KMS key, the KMS key cannot be removed or changed.

 Note

To enable AWS Key Management Service encryption for an organization event data store, you must use an existing KMS key for the management account.

8. (Optional) If you want to query against your event data using Amazon Athena, choose **Enable** in **Lake query federation**. Federation lets you view the metadata associated with the event data store in the AWS Glue [Data Catalog](#) and run SQL queries against the event data in Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know how to find, read, and process the data that you want to query. For more information, see [Federate an event data store](#).

To enable Lake query federation, choose **Enable** and then do the following:

- a. Choose whether you want to create a new role or use an existing IAM role. [AWS Lake Formation](#) uses this role to manage permissions for the federated event data store. When you create a new role using the CloudTrail console, CloudTrail automatically creates a role with the required permissions. If you choose an existing role, be sure the policy for the role provides the [required minimum permissions](#).
 - b. If you are creating a new role, enter a name to identify the role.
 - c. If you are using an existing role, choose the role you want to use. The role must exist in your account.
9. (Optional) Choose **Enable resource policy** to add a resource-based policy to your event data store. Resource-based policies allow you to control which principals can perform actions on your event data store. For example, you can add a resource based policy that allows the root

users in other accounts to query this event data store and view the query results. For example policies, see [Resource-based policy examples for event data stores](#).

A resource-based policy includes one or more statements. Each statement in the policy defines the [principals](#) that are allowed or denied access to the event data store and the actions the principals can perform on the event data store resource.

The following actions are supported in resource-based policies for event data stores:

- `cloudtrail:StartQuery`
- `cloudtrail:CancelQuery`
- `cloudtrail:ListQueries`
- `cloudtrail:DescribeQuery`
- `cloudtrail:GetQueryResults`
- `cloudtrail:GenerateQuery`
- `cloudtrail:GenerateQueryResultsSummary`
- `cloudtrail:GetEventDataStore`

For [organization event data stores](#), CloudTrail creates a [default resource-based policy](#) that lists the actions that the delegated administrator accounts are allowed to perform on organization event data stores. The permissions in this policy are derived from the delegated administrator permissions in AWS Organizations. This policy is updated automatically following changes to the organization event data store or to the organization (for example, a CloudTrail delegated administrator account is registered or removed).

10. (Optional) In the **Tags** section, you can add up to 50 tag key pairs to help you identify, sort, and control access to your event data store. For more information about how to use IAM policies to authorize access to an event data store based on tags, see [Examples: Denying access to create or delete event data stores based on tags](#). For more information about how you can use tags in AWS, see [Tagging AWS resources](#) in the *Tagging AWS Resources User Guide*.
11. Choose **Next** to configure the event data store.
12. On the **Choose events** page, choose **Events from integrations**.
13. From **Events from integration**, choose the source to deliver events to the event data store.
14. Provide a name to identify the integration's channel. The name can be 3-128 characters. Only letters, numbers, periods, underscores, and dashes are allowed.

15. In **Resource policy**, configure the resource policy for the integration's channel. Resource policies are JSON policy documents that specify what actions a specified principal can perform on the resource and under what conditions. The accounts defined as principals in the resource policy can call the `PutAuditEvents` API to deliver events to your channel. The resource owner has implicit access to the resource if their IAM policy allows the `cloudtrail-data:PutAuditEvents` action.

The information required for the policy is determined by the integration type. For a direction integration, CloudTrail automatically adds the partner's AWS account IDs, and requires you to enter the unique external ID provided by the partner. For a solution integration, you must specify at least one AWS account ID as principal, and can optionally enter an external ID to prevent against confused deputy.

 Note

If you do not create a resource policy for the channel, only the channel owner can call the `PutAuditEvents` API on the channel.

- a. For a direct integration, enter the external ID provided by your partner. The integration partner provides a unique external ID, such as an account ID or a randomly generated string, to use for the integration to prevent against confused deputy. The partner is responsible for creating and providing a unique external ID.

You can choose **How to find this?** to view the partner's documentation that describes how to find the external ID.

External ID

Enter the unique account identifier provided by Nordcloud. [How to find this?](#) 

 Note

If the resource policy includes an external ID, all calls to the `PutAuditEvents` API must include the external ID. However, if the policy does not define an external ID, the partner can still call the `PutAuditEvents` API and specify an `externalId` parameter.

- b. For a solution integration, choose **Add AWS account** to specify each AWS account ID to add as a principal in the policy.
16. Choose **Next** to review your choices.
17. On the **Review and create** page, review your choices. Choose **Edit** to make changes to a section. When you're ready to create the event data store, choose **Create event data store**.
18. The new event data store is visible in the **Event data stores** table on the **Event data stores** page.
19. Provide the channel Amazon Resource Name (ARN) to the partner application. Instructions for providing the channel ARN to the partner application are found on the partner documentation website. For more information, choose the **Learn more** link for the partner on the **Available sources** tab of the **Integrations** page to open the partner's page in AWS Marketplace.

The event data store starts ingesting partner events into CloudTrail through the integration's channel when you, the partner, or the partner applications calls the PutAuditEvents API on the channel.

Update an event data store with the console

This section describes how to update an event data store's settings using the AWS Management Console. For information about how to update an event data store using the AWS CLI, see [Update an event data store with the AWS CLI](#).

To update an event data store

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose the event data store that you want to update. This action opens the event data store's details page.
4. In **General details**, choose **Edit** to change the following settings:
 - **Event data store name** - Change the name that identifies your event data store.
 - [Pricing option](#) - For event data stores using the **Seven-year retention pricing** option, you can choose to use **One-year extendable retention pricing** instead. We recommend one-year extendable retention pricing for event data stores that ingest less than 25 TB of event data on a monthly basis. We also recommend one-year extendable retention pricing if

you're seeking a flexible retention period of up to 10 years. For more information, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

 Note

You can't change the pricing option for event data stores that use **One-year extendable retention pricing**. If you want to use **Seven-year retention pricing**, [stop ingestion](#) on your current event data store. Then create a new event data store with the **Seven-year retention pricing** option.

- **Retention period** - Change the retention period for the event data store. The retention period determines how long event data is kept in the event data store. Retention periods can be between 7 days and 3,653 days (about 10 years) for the **One-year extendable retention pricing** option, or between 7 days and 2,557 days (about seven years) for the **Seven-year retention pricing** option.

 Note

If you decrease the retention period of an event data store, CloudTrail will remove any events with an `eventTime` older than the new retention period. For example, if the previous retention period was 365 days and you decrease it to 100 days, CloudTrail will remove events with an `eventTime` older than 100 days.

- **Encryption** - To encrypt your event data store using your own KMS key, choose **Use my own AWS KMS key**. By default, all events in an event data store are encrypted by CloudTrail. Using your own KMS key incurs AWS KMS costs for encryption and decryption.

 Note

After you associate an event data store with a KMS key, the KMS key can't be removed or changed.

- To include only events that are logged in the current AWS Region, choose **Include on the current region in my event data store**. If you don't choose this option, your event data store includes events from all Regions.
- To have your event data store collect events from all accounts in an AWS Organizations organization, choose **Enable for all accounts in my organization**. This option is only

available if you're signed in with the management account for your organization, and the **Event type** for the event data store is **CloudTrail events** or **Configuration items**.

Choose **Save changes** when you're finished.

5. In **Lake query federation**, choose **Edit** to enable or disable Lake query federation. [Enabling Lake query federation](#) lets you view the metadata for your event data store in the AWS Glue [Data Catalog](#) and run SQL queries on the event data using Amazon Athena. [Disabling Lake query federation](#) disables the integration with AWS Glue, AWS Lake Formation, and Amazon Athena. After disabling Lake query federation, you can no longer query your data in Athena. No CloudTrail Lake data is deleted when you disable federation and you can continue to run queries in CloudTrail Lake.

To enable federation, do the following:

- a. Choose **Enable**.
- b. Choose whether to create a new IAM role, or use an existing role. When you create a new role, CloudTrail automatically creates a role with the required permissions. If you're using an existing role, be sure the role's policy provides the [required minimum permissions](#).
- c. If you're creating a new IAM role, enter a name for the role.
- d. If you're choosing an existing IAM role, choose the role you want to use. The role must exist in your account.

Choose **Save changes** when you are finished.

6. In **Resource policy**, choose **Edit** to add or revise the resource-based policy for the event data store.

Resource-based policies allow you to control which principals can perform actions on your event data store. For example, you can add a resource based policy that allows the root users in other accounts to query this event data store and view the query results. For example policies, see [Resource-based policy examples for event data stores](#).

A resource-based policy includes one or more statements. Each statement in the policy defines the [principals](#) that are allowed or denied access to the event data store and the actions the principals can perform on the event data store resource.

The following actions are supported in resource-based policies for event data stores:

- `cloudtrail:StartQuery`
- `cloudtrail:CancelQuery`
- `cloudtrail:ListQueries`
- `cloudtrail:DescribeQuery`
- `cloudtrail:GetQueryResults`
- `cloudtrail:GenerateQuery`
- `cloudtrail:GenerateQueryResultsSummary`
- `cloudtrail:GetEventDataStore`

For [organization event data stores](#), CloudTrail creates a [default resource-based policy](#) that lists the actions that the delegated administrator accounts are allowed to perform on organization event data stores. The permissions in this policy are derived from the delegated administrator permissions in AWS Organizations. This policy is updated automatically following changes to the organization event data store or to the organization (for example, a CloudTrail delegated administrator account is registered or removed).

7. Edit any additional settings specific to your event data store's **Event type**.

Settings for CloudTrail events

- To change which events your event data store logs, choose **Edit** in **CloudTrail events**.
- In **Management events**, choose **Edit** to change the settings for management events. For more information, see [Updating the management event settings for an existing event data store](#).
- In **Data events**, choose **Edit** to change the settings for data events. You can choose which resource types you want to log and choose the log selector template you want to use. For more information, see [Updating an existing event data store to log data events using the console](#).
- In **Network activity events**, choose **Edit** to change the settings for network activity events. You can choose which network activity event type you want to log and choose the log selector template you want to use. For more information, see [Update an existing event data store to log network activity events](#).
- In **Enrich events, expand event size**, choose **Edit** to add or remove resource tags and IAM global condition keys, and expand the event size.

In **Enrich events**, add up to 50 resource tag keys and 50 IAM global condition keys to provide additional metadata about your events. This helps you categorize and group related events.

If you add resource tag keys, CloudTrail will include the selected tag keys associated with the resources that were involved in the API call. API events related to deleted resources will not have resource tags.

If you add IAM global condition keys, CloudTrail will include information about the selected condition keys that were evaluated during the authorization process, including additional details about the principal, session, network, and the request itself.

Information about the resource tag keys and IAM global condition keys is shown in the `eventContext` field of the event. For more information, see [Enrich CloudTrail events by adding resource tag keys and IAM global condition keys](#).

 Note

If an event contains a resource that doesn't belong to the event Region, CloudTrail will not populate tags for this resource because tag retrieval is limited to the event Region.

Choose **Expand event size** to expand the event payload up to 1 MB from 256 KB. This option is automatically enabled when you add resource tag keys or IAM global condition keys to ensure all of your added keys are included in the event.

Expanding the event size is helpful for analyzing and troubleshooting events because it allows you to see the full contents of the following fields as long as the event payload is less than 1 MB:

- `annotation`
- `requestID`
- `additionalEventData`
- `serviceEventDetails`
- `userAgent`
- `errorCode`
- `responseElements`

- `requestParameters`
- `errorMessage`

For more information about these fields, see [CloudTrail record contents](#).

Choose **Save changes** when you're finished.

Settings for Events from integration

In **Integrations**, choose your integration. Then choose **Edit** to change the following settings:

- In **Integration details**, change the name that identifies your integration's channel.
- In **Event delivery location**, choose the destination for your events.
- In **Resource policy**, configure the resource policy for the integration's channel.

Choose **Save changes** when you're finished.

For more information about these settings, see [Create an integration with a CloudTrail partner with the console](#).

8. To add, change, or remove tags, choose **Edit** in **Tags**. You can add up to 50 tag key pairs to help you identify, sort, and control access to your event data store. Choose **Save changes** when you're finished.

Stop and start event ingestion with the console

By default, event data stores are configured to ingest events. You can stop an event data store from ingesting events by using the console, AWS CLI, or APIs.

The options to **Start ingestion** and **Stop ingestion** are only available on event data stores containing either CloudTrail events (management events, data events, and network activity events), or AWS Config configuration items.

When you stop ingestion on an event data store, the event data store's state changes to `STOPPED_INGESTION`. You can still run queries on any events already in the event data store. You can also copy trail events to the event data store (if it contains only CloudTrail events).

To stop an event data store from ingesting events

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose the event data store.
4. From **Actions**, choose **Stop ingestion**.
5. When you are prompted to confirm, choose **Stop ingestion**. The event data store will stop ingesting live events.
6. To resume ingestion, choose **Start ingestion**.

To restart event ingestion

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose the event data store.
4. From **Actions**, choose **Start ingestion**.

Change termination protection with the console

By default, event data stores in AWS CloudTrail Lake are configured with termination protection enabled. Termination protection prevents an event data store from accidental deletion. If you want to delete the event data store, you must disable termination protection. You can disable termination protection by using the AWS Management Console, AWS CLI, or API operations.

To turn off termination protection

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose the event data store.
4. From **Actions**, choose **Change termination protection**.
5. Choose **Disabled**.
6. Choose **Save**. You can now [delete the event data store](#).

To turn on termination protection

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose the event data store.
4. From **Actions**, choose **Change termination protection**.
5. To turn on termination protection, choose **Enabled**.
6. Choose **Save**.

Delete an event data store with the console

This section describes how to delete an event data store using the CloudTrail console. For information about how to delete an event data store using the AWS CLI, see [Delete an event data store with the AWS CLI](#).

Note

You can't delete an event data store if either [termination protection](#) or [Lake query federation](#) is enabled. By default, CloudTrail enables termination protection to protect an event data store from being accidentally deleted.

To delete an event data store with an event type of **Events from integration**, you must first delete the integration's channel. You can delete the channel from the integration's details page or by using the **aws cloudtrail delete-channel** command. For more information, see [Delete a channel to delete an integration with the AWS CLI](#)

To delete an event data store

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose the event data store.
4. From **Actions**, choose **Delete**.
5. Type the name of the event data store to confirm that you want to delete it.

6. Choose **Delete**.

After you delete an event data store, the event data store's status changes to `PENDING_DELETION` and remains in that state for 7 days. You can [restore](#) an event data store during the 7-day wait period. While in the `PENDING_DELETION` state, an event data store isn't available for queries, and no other operations can be performed on the event data store except restore operations. An event data store that is pending deletion does not ingest events and does not incur costs. Event data stores that are pending deletion count toward the quota of event data stores that can exist in one AWS Region.

Restore an event data store with the console

After you delete an event data store in AWS CloudTrail Lake, its status changes to `PENDING_DELETION` and remains in that state for 7 days. During this time, you can restore the event data store by using the AWS Management Console, AWS CLI, or the [RestoreEventDataStore](#) API operation.

This section describes how to restore an event data store using the console. For information about how to restore an event data store using the AWS CLI, see [Restore an event data store with the AWS CLI](#).

To restore an event data store

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose the event data store.
4. From **Actions**, choose **Restore**.

Create, update, and manage event data stores with the AWS CLI

This section describes the AWS CLI commands you can use to create, update, and manage your CloudTrail Lake event data stores.

When using the AWS CLI, remember that your commands run in the AWS Region configured for your profile. If you want to run the commands in a different Region, either change the default Region for your profile, or use the `--region` parameter with the command.

Available commands for event data stores

Commands for creating and updating event data stores in CloudTrail Lake include:

- [create-event-data-store](#) to create an event data store.
- [get-event-data-store](#) to return information about the event data store including the advanced event selectors configured for the event data store.
- [update-event-data-store](#) to change the configuration of an existing event data store.
- [list-event-data-stores](#) to list the event data stores.
- [delete-event-data-store](#) to delete an event data store.
- [restore-event-data-store](#) to restore an event data store that is pending deletion.
- [start-import](#) to start an import of trail events to an event data store, or retry a failed import.
- [get-import](#) to return information about a specific import.
- [stop-import](#) to stop an import of trail events to an event data store.
- [list-imports](#) to return information on all imports, or a select set of imports by ImportStatus or Destination.
- [list-import-failures](#) to list import failures for the specified import.
- [stop-event-data-store-ingestion](#) to stop event ingestion on an event data store.
- [start-event-data-store-ingestion](#) to restart event ingestion on an event data store.
- [enable-federation](#) to enable federation on an event data store to query the event data store in Amazon Athena.
- [disable-federation](#) to disable federation on an event data store. After you disable federation, you can no longer query against the event data store's data in Amazon Athena. You can continue to query in CloudTrail Lake.
- [put-insight-selectors](#) to add or modify Insights event selectors for an existing event data store, and enable or disable Insights events.
- [get-insight-selectors](#) to return information about Insights event selectors configured for an event data store.
- [add-tags](#) to add one or more tags (key-value pairs) to an existing event data store.
- [remove-tags](#) to remove one or more tags from a event data store.
- [list-tags](#) to return a list of tags associated with a event data store.

- [get-event-configuration](#) to return any resource tag keys and IAM global conditions keys configured for the event data store. The command also returns whether the event data store is configured to collect Standard size events or Large size events.
- [put-event-configuration](#) to expand the event size and add or remove resource tag keys and IAM global condition keys. For more information, see [Enrich CloudTrail events by adding resource tag keys and IAM global condition keys](#).
- [put-resource-policy](#) to attach a resource-based policy to an event data store. Resource-based policies allow you to control which principals can perform actions on your event data store. For example policies, see [Resource-based policy examples for event data stores](#).
- [get-resource-policy](#) to get the resource-based policy attached to an event data store.
- [delete-resource-policy](#) to delete the resource-based policy attached to an event data store.

For a list of available commands for CloudTrail Lake queries, see [Available commands for CloudTrail Lake queries](#).

For a list of available commands for CloudTrail Lake dashboards, see [Available commands for dashboards](#).

For a list of available commands for CloudTrail Lake integrations, see [Available commands for CloudTrail Lake integrations](#).

Create an event data store with the AWS CLI

This section describes how to use the [create-event-data-store](#) command to create an event data store and provides examples of different types of event data stores that you can create.

When you create an event data store, the only required parameter is `--name`, which is used to identify the event data store. You can configure additional optional parameters, including:

- `--advanced-event-selectors` - Specifies the type of events to include in the event data store. By default, event data stores log all management events. For more information about advanced event selectors, see [AdvancedEventSelector](#) in the CloudTrail API Reference.
- `--kms-key-id` - Specifies the KMS key ID to use to encrypt the events delivered by CloudTrail. The value can be an alias name prefixed by `alias/`, a fully specified ARN to an alias, a fully specified ARN to a key, or a globally unique identifier.

- `--multi-region-enabled` - Creates a multi-Region event data store that logs events for all AWS Regions in your account. By default, `--multi-region-enabled` is set, even if the parameter is not added.
- `--organization-enabled` - Enables an event data store to collect events for all accounts in an organization. By default, the event data store is not enabled for all accounts in an organization.
- `--billing-mode` - Determines the cost for ingesting and storing events, and the default and maximum retention period for the event data store.

The following are the possible values:

- `EXTENDABLE_RETENTION_PRICING` - This billing mode is generally recommended if you ingest less than 25 TB of event data a month and want a flexible retention period of up to 3653 days (about 10 years). The default retention period for this billing mode is 366 days.
- `FIXED_RETENTION_PRICING` - This billing mode is recommended if you expect to ingest more than 25 TB of event data per month and need a retention period of up to 2557 days (about 7 years). The default retention period for this billing mode is 2557 days.

The default value is `EXTENDABLE_RETENTION_PRICING`.

- `--retention-period` - The number of days to keep events in the event data store. Valid values are integers between 7 and 3653 if the `--billing-mode` is `EXTENDABLE_RETENTION_PRICING`, or between 7 and 2557 if the `--billing-mode` is set to `FIXED_RETENTION_PRICING`. If you do not specify `--retention-period`, CloudTrail uses the default retention period for the `--billing-mode`.
- `--start-ingestion` - The `--start-ingestion` parameter starts event ingestion on the event data store when it's created. This parameter is set even if the parameter is not added.

Specify the `--no-start-ingestion` if you do not want the event data store to ingest live events. For example, you may want to set this parameter if you are copying events to the event data store and only plan to use the event data to analyze past events. The `--no-start-ingestion` parameter is only valid if the `eventCategory` is `Management`, `Data`, or `ConfigurationItem`.

The following examples show how to create different types of event data stores.

Examples:

- [Create an event data store for S3 data events with the AWS CLI](#)
- [Create an event data store for KMS network activity events with the AWS CLI](#)

- [Create an event data store for AWS Config configuration items with the AWS CLI](#)
- [Create an organization event data store for management events with the AWS CLI](#)
- [Create event data stores for Insights events with the AWS CLI](#)

Create an event data store for S3 data events with the AWS CLI

The following example AWS Command Line Interface (AWS CLI) **create-event-data-store** command creates an event data store named `my-event-data-store` that selects all Amazon S3 data events and is encrypted using a KMS key.

```
aws cloudtrail create-event-data-store \
--name my-event-data-store \
--kms-key-id "arn:aws:kms:us-east-1:123456789012:alias/KMS_key_alias" \
--advanced-event-selectors '[
    {
        "Name": "Select all S3 data events",
        "FieldSelectors": [
            { "Field": "eventCategory", "Equals": ["Data"] },
            { "Field": "resources.type", "Equals": ["AWS::S3::Object"] },
            { "Field": "resources.ARN", "StartsWith": ["arn:aws:s3"] }
        ]
    }
]
```

The following is an example response.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
EXAMPLE-ee54-4813-92d5-999aeEXAMPLE",
  "Name": "my-event-data-store",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Select all S3 data events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Data"
          ]
        }
      ],
    },
  ],
}
```



```

        {
            "Field": "resources.type",
            "Equals": [
                "AWS::S3::Object"
            ]
        },
        {
            "Field": "resources.ARN",
            "StartsWith": [
                "arn:aws:s3"
            ]
        }
    ]
}
],
"MultiRegionEnabled": true,
"OrganizationEnabled": false,
"BillingMode": "EXTENDABLE_RETENTION_PRICING",
"RetentionPeriod": 366,
"KmsKeyId": "arn:aws:kms:us-east-1:123456789012:alias/KMS_key_alias",
"TerminationProtectionEnabled": true,
"CreatedTimestamp": "2023-11-09T22:19:39.417000-05:00",
"UpdatedTimestamp": "2023-11-09T22:19:39.603000-05:00"
}

```

Create an event data store for KMS network activity events with the AWS CLI

The following example shows how to create an event data store to include `VpceAccessDenied` network activity events for AWS KMS. This example sets the `errorCode` field equal to `VpceAccessDenied` events and the `eventSource` field equal to `kms.amazonaws.com`.

```

aws cloudtrail create-event-data-store \
--name EventDataStoreName \
--advanced-event-selectors '[
    {
        "Name": "Audit AccessDenied AWS KMS events over a VPC endpoint",
        "FieldSelectors": [
            {
                "Field": "eventCategory",
                "Equals": ["NetworkActivity"]
            },
            {
                "Field": "eventSource",

```

```

        "Equals": ["kms.amazonaws.com"]
    },
    {
        "Field": "errorCode",
        "Equals": ["VpceAccessDenied"]
    }
]
}'

```

The command returns the following example output.

```

{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/
EXAMPLEb4a8-99b1-4ec2-9258-EXAMPLEc890",
  "Name": "EventDataStoreName",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Audit AccessDenied AWS KMS events over a VPC endpoint",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "NetworkActivity"
          ]
        },
        {
          "Field": "eventSource",
          "Equals": [
            "kms.amazonaws.com"
          ]
        },
        {
          "Field": "errorCode",
          "Equals": [
            "VpceAccessDenied"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": true,
}

```

```
"OrganizationEnabled": false,
"RetentionPeriod": 366,
"TerminationProtectionEnabled": true,
"CreatedTimestamp": "2024-05-20T21:00:17.673000+00:00",
"UpdatedTimestamp": "2024-05-20T21:00:17.820000+00:00"
}
```

For more information about network activity events, see [Logging network activity events](#).

Create an event data store for AWS Config configuration items with the AWS CLI

The following example AWS CLI **create-event-data-store** command creates an event data store named `config-items-eds` that selects AWS Config configuration items. To collect configuration items, specify that the `eventCategory` field Equals `ConfigurationItem` in the advanced event selectors.

```
aws cloudtrail create-event-data-store \
--name config-items-eds \
--advanced-event-selectors '[
  {
    "Name": "Select AWS Config configuration items",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["ConfigurationItem"] }
    ]
  }
]'
```

The following is an example response.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
EXAMPLE-ee54-4813-92d5-999aeEXAMPLE",
  "Name": "config-items-eds",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Select AWS Config configuration items",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "ConfigurationItem"
          ]
        }
      ]
    }
  ]
}
```

```

        }
    ]
}
],
"MultiRegionEnabled": true,
"OrganizationEnabled": false,
"BillingMode": "EXTENDABLE_RETENTION_PRICING",
"RetentionPeriod": 366,
"TerminationProtectionEnabled": true,
"CreatedTimestamp": "2023-11-07T19:03:24.277000+00:00",
"UpdatedTimestamp": "2023-11-07T19:03:24.468000+00:00"
}

```

Create an organization event data store for management events with the AWS CLI

The following example AWS CLI **create-event-data-store** command creates an organization event data store that collects all management events and sets the `--billing-mode` parameter to `FIXED_RETENTION_PRICING`.

```
aws cloudtrail create-event-data-store --name org-management-eds --organization-enabled
--billing-mode FIXED_RETENTION_PRICING
```

The following is an example response.

```

{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
EXAMPLE6-d493-4914-9182-e52a7934b207",
  "Name": "org-management-eds",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Default management events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": true,

```

```

    "OrganizationEnabled": true,
    "BillingMode": "FIXED_RETENTION_PRICING",
    "RetentionPeriod": 2557,
    "TerminationProtectionEnabled": true,
    "CreatedTimestamp": "2023-11-16T15:30:50.689000+00:00",
    "UpdatedTimestamp": "2023-11-16T15:30:50.851000+00:00"
  }

```

Create event data stores for Insights events with the AWS CLI

To log Insights events in CloudTrail Lake, you need a destination event data store that collects Insights events and a source event data store that enables Insights and logs management events.

This procedure shows you how to create the destination and source event data stores and then enable Insights events.

1. Run the [aws cloudtrail create-event-data-store](#) command to create a destination event data store that collects Insights events. The value for eventCategory must be Insight. Replace *retention-period-days* with the number of days you would like to retain events in your event data store. Valid values are integers between 7 and 3653 if the `--billing-mode` is `EXTENDABLE_RETENTION_PRICING`, or between 7 and 2557 if the `--billing-mode` is set to `FIXED_RETENTION_PRICING`. If you do not specify `--retention-period`, CloudTrail uses the default retention period for the `--billing-mode`.

If you are signed in with the management account for an AWS Organizations organization, include the `--organization-enabled` parameter if you want to give your [delegated administrator](#) access to the event data store.

```

aws cloudtrail create-event-data-store \
--name insights-event-data-store \
--no-multi-region-enabled \
--retention-period retention-period-days \
--advanced-event-selectors '[
  {
    "Name": "Select Insights events",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Insight"] }
    ]
  }
]'

```

The following is an example response.

```
{
  "Name": "insights-event-data-store",
  "ARN": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/
EXAMPLEf852-4e8f-8bd1-bcf6cEXAMPLE",
  "AdvancedEventSelectors": [
    {
      "Name": "Select Insights events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Insight"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": false,
  "OrganizationEnabled": false,
  "BillingMode": "EXTENDABLE_RETENTION_PRICING",
  "RetentionPeriod": "90",
  "TerminationProtectionEnabled": true,
  "CreatedTimestamp": "2023-05-08T15:22:33.578000+00:00",
  "UpdatedTimestamp": "2023-05-08T15:22:33.714000+00:00"
}
```

You will use the ARN (or ID suffix of the ARN) from the response as the value for the `--insights-destination` parameter in step 3.

2. Run the [aws cloudtrail create-event-data-store](#) command to create a source event data store that logs management events. By default, event data stores log all management events. You don't need to specify the advanced event selectors if you want to log all management events. Replace *retention-period-days* with the number of days you would like to retain events in your event data store. Valid values are integers between 7 and 3653 if the `--billing-mode` is `EXTENDABLE_RETENTION_PRICING`, or between 7 and 2557 if the `--billing-mode` is set to `FIXED_RETENTION_PRICING`. If you do not specify `--retention-period`, CloudTrail uses the default retention period for the `--billing-mode`. If you are creating an organization event data store, include the `--organization-enabled` parameter.

```
aws cloudtrail create-event-data-store --name source-event-data-store --retention-period retention-period-days
```

The following is an example response.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLE9952-4ab9-49c0-b788-f4f3EXAMPLE",
  "Name": "source-event-data-store",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Default management events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": true,
  "OrganizationEnabled": false,
  "BillingMode": "EXTENDABLE_RETENTION_PRICING",
  "RetentionPeriod": 90,
  "TerminationProtectionEnabled": true,
  "CreatedTimestamp": "2023-05-08T15:25:35.578000+00:00",
  "UpdatedTimestamp": "2023-05-08T15:25:35.714000+00:00"
}
```

You will use the ARN (or ID suffix of the ARN) from the response as the value for the `--event-data-store` parameter in step 3.

3. Run the [put-insight-selectors](#) command to enable Insights events. Insights selector values can be `ApiCallRateInsight`, `ApiErrorRateInsight`, or both. For the `--event-data-store` parameter, specify the ARN (or ID suffix of the ARN) of the source event data store that logs management events and will enable Insights. For the `--insights-destination` parameter, specify the ARN (or ID suffix of the ARN) of the destination event data store that will log Insights events.

```
aws cloudtrail put-insight-selectors --event-data-store arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLE9952-4ab9-49c0-b788-f4f3EXAMPLE --insights-destination arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLEf852-4e8f-8bd1-bcf6cEXAMPLE --insight-selectors '[{"InsightType": "ApiCallRateInsight"}, {"InsightType": "ApiErrorRateInsight"}]'
```

The following result shows the Insights event selector that is configured for the event data store.

```
{
  "EventDataStoreARN": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLE9952-4ab9-49c0-b788-f4f3EXAMPLE",
  "InsightsDestination": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLEf852-4e8f-8bd1-bcf6cEXAMPLE",
  "InsightSelectors":
    [
      {
        "InsightType": "ApiErrorRateInsight"
      },
      {
        "InsightType": "ApiCallRateInsight"
      }
    ]
}
```

After you enable CloudTrail Insights for the first time on an event data store, CloudTrail may take up to 7 days to begin delivering Insights events, provided that unusual activity is detected during that time.

CloudTrail Insights analyzes management events that occur in a single Region, not globally. A CloudTrail Insights event is generated in the same Region as its supporting management events are generated.

For an organization event data store, CloudTrail analyzes management events from each member's account instead of analyzing the aggregation of all management events for the organization.

Additional charges apply for ingesting Insights events in CloudTrail Lake. You will be charged separately if you enable Insights for both trails and event data stores. For information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Import trail events to an event data store with the AWS CLI

This section shows how to create and configure an event data store by running the [create-event-data-store](#) command and then how to import the events to that event data store by using the [start-import](#) command. For more information about importing trail events, see [Copy trail events to an event data store](#).

Preparing to import trail events

Before you import trail events, make the following preparations.

- Be sure you have a role with the [required permissions](#) to import trail events to an event data store.
- Determine the [--billing-mode](#) value you want to specify for the event data store. The `--billing-mode` determines the cost of ingesting and storing events, and the default and maximum retention period for the event data store.

When you import trail events to CloudTrail Lake, CloudTrail unzips the logs that are stored in gzip (compressed) format. Then CloudTrail copies the events contained in the logs to your event data store. The size of the uncompressed data could be greater than the actual Amazon S3 storage size. To get a general estimate of the size of the uncompressed data, multiply the size of the logs in the S3 bucket by 10. You can use this estimate to choose the `--billing-mode` value for your use case.

- Determine the value you want to specify for the `--retention-period`. CloudTrail will not copy an event if its `eventTime` is older than the specified retention period.

To determine the appropriate retention period, take the sum of the oldest event you want to copy in days and the number of days you want to retain the events in the event data store as demonstrated in this equation:

Retention period = *oldest-event-in-days* + *number-days-to-retain*

For example, if the oldest event you're copying is 45 days old and you want to keep the events in the event data store for a further 45 days, you would set the retention period to 90 days.

- Decide whether you want to use the event data store to analyze any future events. If you don't want to ingest any future events, include the `--no-start-ingestion` parameter when you create the event data store. By default, event data store's begin ingesting events when they're created.

To create an event data store and import trail events to that event data store

1. Run the **create-event-data-store** command to create the new event data store. In this example, the `--retention-period` is set to 120 because the oldest event being copied is 90 days old and we want to retain the events for 30 days. The `--no-start-ingestion` parameter is set because we don't want to ingest any future events. In this example, `--billing-mode` wasn't set, because we are using the default value `EXTENDABLE_RETENTION_PRICING` as we expect to ingest less than 25 TB of event data.

Note

If you're creating the event data store to replace your trail, we recommend configuring the `--advanced-event-selectors` to match the event selectors of your trail to ensure you have the same event coverage. By default, event data stores log all management events.

```
aws cloudtrail create-event-data-store --name import-trail-eds --retention-period
120 --no-start-ingestion
```

The following is the example response:

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
EXAMPLEa-4357-45cd-bce5-17ec652719d9",
  "Name": "import-trail-eds",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Default management events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
```

```

        "Equals": [
            "Management"
        ]
    }
]
},
"MultiRegionEnabled": true,
"OrganizationEnabled": false,
"BillingMode": "EXTENDABLE_RETENTION_PRICING",
"RetentionPeriod": 120,
"TerminationProtectionEnabled": true,
"CreatedTimestamp": "2023-11-09T16:52:25.444000+00:00",
"UpdatedTimestamp": "2023-11-09T16:52:25.569000+00:00"
}

```

The initial Status is CREATED so we'll run the **get-event-data-store** command to verify ingestion is stopped.

```
aws cloudtrail get-event-data-store --event-data-store eds-id
```

The response shows the Status is now STOPPED_INGESTION, which indicates the event data store is not ingesting live events.

```

{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLEa-4357-45cd-bce5-17ec652719d9",
  "Name": "import-trail-eds",
  "Status": "STOPPED_INGESTION",
  "AdvancedEventSelectors": [
    {
      "Name": "Default management events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        }
      ]
    }
  ]
},

```

```

    "MultiRegionEnabled": true,
    "OrganizationEnabled": false,
    "BillingMode": "EXTENDABLE_RETENTION_PRICING",
    "RetentionPeriod": 120,
    "TerminationProtectionEnabled": true,
    "CreatedTimestamp": "2023-11-09T16:52:25.444000+00:00",
    "UpdatedTimestamp": "2023-11-09T16:52:25.569000+00:00"
  }

```

2. Run the **start-import** command to import the trail events to the event data store created in step 1. Specify the ARN (or ID suffix of the ARN) of the event data store as the value for the `--destinations` parameter. For `--start-event-time` specify the `eventTime` for the oldest event you want to copy and for `--end-event-time` specify the `eventTime` of the newest event you want to copy. For `--import-source` specify the S3 URI for the S3 bucket containing your trail logs, the AWS Region for the S3 bucket, and the ARN of the role used for importing trail events.

```

aws cloudtrail start-import \
--destinations ["arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
EXAMPLEa-4357-45cd-bce5-17ec652719d9"] \
--start-event-time 2023-08-11T16:08:12.934000+00:00 \
--end-event-time 2023-11-09T17:08:20.705000+00:00 \
--import-source {"S3": {"S3LocationUri": "s3://aws-cloudtrail-
logs-123456789012-612ff1f6/AWSLogs/123456789012/CloudTrail/", "S3BucketRegion": "us-
east-1", "S3BucketAccessRoleArn": "arn:aws:iam::123456789012:role/service-role/
CloudTrailLake-us-east-1-copy-events-eds"}}

```

The following is an example response.

```

{
  "CreatedTimestamp": "2023-11-09T17:08:20.705000+00:00",
  "Destinations": [
    "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
EXAMPLEa-4357-45cd-bce5-17ec652719d9"
  ],
  "EndEventTime": "2023-11-09T17:08:20.705000+00:00",
  "ImportId": "EXAMPLEe-7be2-4658-9204-b38c3257fcd1",
  "ImportSource": {
    "S3": {
      "S3BucketAccessRoleArn": "arn:aws:iam::123456789012:role/service-role/
CloudTrailLake-us-east-1-copy-events-eds",

```

```

        "S3BucketRegion": "us-east-1",
        "S3LocationUri": "s3://aws-cloudtrail-logs-123456789012-111ff1f6/
AWSLogs/123456789012/CloudTrail/"
    },
    "ImportStatus": "INITIALIZING",
    "StartEventTime": "2023-08-11T16:08:12.934000+00:00",
    "UpdatedTimestamp": "2023-11-09T17:08:20.806000+00:00"
}

```

3. Run the [get-import](#) command to get information about the import.

```
aws cloudtrail get-import --import-id import-id
```

The following is an example response.

```

{
  "ImportId": "EXAMPLEe-7be2-4658-9204-b38c3EXAMPLE",
  "Destinations": [
    "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
EXAMPLEe-4357-45cd-bce5-17ec652719d9"
  ],
  "ImportSource": {
    "S3": {
      "S3LocationUri": "s3://aws-cloudtrail-logs-123456789012-111ff1f6/
AWSLogs/123456789012/CloudTrail/",
      "S3BucketRegion": "us-east-1",
      "S3BucketAccessRoleArn": "arn:aws:iam::123456789012:role/service-role/
CloudTrailLake-us-east-1-copy-events-eds"
    }
  },
  "StartEventTime": "2023-08-11T16:08:12.934000+00:00",
  "EndEventTime": "2023-11-09T17:08:20.705000+00:00",
  "ImportStatus": "COMPLETED",
  "CreatedTimestamp": "2023-11-09T17:08:20.705000+00:00",
  "ImportStatistics": {
    "PrefixesFound": 1548,
    "PrefixesCompleted": 1548,
    "FilesCompleted": 92845,
    "EventsCompleted": 577249,
    "FailedEntries": 0
  }
}

```

```
}
```

An import finishes with an `ImportStatus` of `COMPLETED` if there were no failures, or `FAILED` if there were failures.

If the import had `FailedEntries`, you can run the [list-import-failures](#) command to return a list of failures.

```
aws cloudtrail list-import-failures --import-id import-id
```

To retry an import that had failures, run the **start-import** command with only the `--import-id` parameter. When you retry an import, CloudTrail resumes the import at the location where the failure occurred.

```
aws cloudtrail start-import --import-id import-id
```

Update an event data store with the AWS CLI

This section provides examples that show how to update an event data store's settings by running the AWS CLI `update-event-data-store` command.

Examples:

- [Update the billing mode with the AWS CLI](#)
- [Update the retention mode, enable termination protection, and specify a AWS KMS key with the AWS CLI](#)
- [Disable termination protection with the AWS CLI](#)

Update the billing mode with the AWS CLI

The `--billing-mode` for the event data store determines the cost for ingesting and storing events, and the default and maximum retention period for the event data store. If an event data store's `--billing-mode` is set to `FIXED_RETENTION_PRICING`, you can change the value to `EXTENDABLE_RETENTION_PRICING`. `EXTENDABLE_RETENTION_PRICING` is generally recommended if your event data store ingests less than 25 TB of event data per month and you want a flexible retention period of up to 3653 days. For information about pricing, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

Note

You cannot change the `--billing-mode` value from `EXTENDABLE_RETENTION_PRICING` to `FIXED_RETENTION_PRICING`. If the event data store's billing mode is set to `EXTENDABLE_RETENTION_PRICING` and you want to use `FIXED_RETENTION_PRICING` instead, you can [stop ingestion](#) on the event data store and create a new event data store that uses `FIXED_RETENTION_PRICING`.

The following example AWS CLI **update-event-data-store** command changes the `--billing-mode` for the event data store from `FIXED_RETENTION_PRICING` to `EXTENDABLE_RETENTION_PRICING`. The required `--event-data-store` parameter value is an ARN (or the ID suffix of the ARN) and is required; other parameters are optional.

```
aws cloudtrail update-event-data-store \
--region us-east-1 \
--event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-
f852-4e8f-8bd1-bcf6cEXAMPLE \
--billing-mode EXTENDABLE_RETENTION_PRICING
```

The following is an example response.

```
{
  "EventDataStoreArn": "event-data-store arn:aws:cloudtrail:us-
east-1:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE",
  "Name": "management-events-eds",
  "Status": "ENABLED",
  "AdvancedEventSelectors": [
    {
      "Name": "Default management events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": true,
```

```
"OrganizationEnabled": false,  
"BillingMode": "EXTENDABLE_RETENTION_PRICING",  
"RetentionPeriod": 2557,  
"TerminationProtectionEnabled": true,  
"CreatedTimestamp": "2023-10-27T10:55:55.384000-04:00",  
"UpdatedTimestamp": "2023-10-27T10:57:05.549000-04:00"  
}
```

Update the retention mode, enable termination protection, and specify a AWS KMS key with the AWS CLI

The following example AWS CLI **update-event-data-store** command updates an event data store to change its retention period to 100 days, and enable termination protection. The required `--event-data-store` parameter value is an ARN (or the ID suffix of the ARN) and is required; other parameters are optional. In this example, the `--retention-period` parameter is added to change the retention period to 100 days. Optionally, you can choose to enable AWS Key Management Service encryption and specify an AWS KMS key by adding `--kms-key-id` to the command, and specifying a KMS key ARN as the value. `--termination-protection-enabled` is added to enable termination protection on an event data store that did not have termination protection enabled.

An event data store that logs events from outside AWS cannot be updated to log AWS events. Similarly, an event data store that logs AWS events cannot be updated to log events from outside AWS.

Note

If you decrease the retention period of an event data store, CloudTrail will remove any events with an `eventTime` older than the new retention period. For example, if the previous retention period was 365 days and you decrease it to 100 days, CloudTrail will remove events with an `eventTime` older than 100 days.

```
aws cloudtrail update-event-data-store \  
--event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-  
f852-4e8f-8bd1-bcf6cEXAMPLE \  
--retention-period 100 \  
--kms-key-id "arn:aws:kms:us-east-1:0123456789:alias/KMS_key_alias" \  
--termination-protection-enabled
```


The following is an example response.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
EXAMPLE-ee54-4813-92d5-999aeEXAMPLE",
  "Name": "my-event-data-store",
  "Status": "ENABLED",
  "AdvancedEventSelectors": [
    {
      "Name": "Select all S3 data events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Data"
          ]
        },
        {
          "Field": "resources.type",
          "Equals": [
            "AWS::S3::Object"
          ]
        },
        {
          "Field": "resources.ARN",
          "StartsWith": [
            "arn:aws:s3"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": true,
  "OrganizationEnabled": false,
  "BillingMode": "EXTENDABLE_RETENTION_PRICING",
  "RetentionPeriod": 100,
  "KmsKeyId": "arn:aws:kms:us-east-1:0123456789:alias/KMS_key_alias",
  "TerminationProtectionEnabled": true,
  "CreatedTimestamp": "2023-10-27T10:55:55.384000-04:00",
  "UpdatedTimestamp": "2023-10-27T10:57:05.549000-04:00"
}
```

Disable termination protection with the AWS CLI

By default, termination protection is enabled on an event data store to protect the event data store from accidental deletion. You cannot delete an event data store when termination protection is enabled. If you want to delete the event data store, you must first disable termination protection.

The following example AWS CLI **update-event-data-store** command disables termination protection by passing the `--no-termination-protection-enabled` parameter.

```
aws cloudtrail update-event-data-store \
--region us-east-1 \
--no-termination-protection-enabled \
--event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-
f852-4e8f-8bd1-bcf6cEXAMPLE
```

The following is an example response.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE",
  "Name": "management-events-eds",
  "Status": "ENABLED",
  "AdvancedEventSelectors": [
    {
      "Name": "Default management events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": true,
  "OrganizationEnabled": false,
  "BillingMode": "EXTENDABLE_RETENTION_PRICING",
  "RetentionPeriod": 366,
  "TerminationProtectionEnabled": false,
  "CreatedTimestamp": "2023-10-27T10:55:55.384000-04:00",
  "UpdatedTimestamp": "2023-10-27T10:57:05.549000-04:00"
```

```
}
```

Managing event data stores with the AWS CLI

This section describes several other commands that you can run to get information about your event data stores, start and stop ingestion on an event data store, and enable and disable [federation](#) on an event data store.

Topics

- [Get an event data store with the AWS CLI](#)
- [List all event data stores in an account with the AWS CLI](#)
- [Add resource tag keys and IAM global conditions keys, and expand event size](#)
- [Get the event configuration for an event data store](#)
- [Get the resource-based policy for an event data store with the AWS CLI](#)
- [Attach a resource-based policy to an event data store with the AWS CLI](#)
- [Delete the resource-based policy attached to an event data store with the AWS CLI](#)
- [Stop ingestion on an event data store with the AWS CLI](#)
- [Start ingestion on an event data store with the AWS CLI](#)
- [Enable federation on an event data store](#)
- [Disable federation on an event data store](#)
- [Restore an event data store with the AWS CLI](#)

Get an event data store with the AWS CLI

The following example AWS CLI **get-event-data-store** command returns information about the event data store specified by the required `--event-data-store` parameter, which accepts an ARN or the ID suffix of the ARN.

```
aws cloudtrail get-event-data-store \
--event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-
f852-4e8f-8bd1-bcf6cEXAMPLE
```

The following is an example response. Creation and last updated times are in timestamp format.

```
{
```

```

    "EventDataStoreARN": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE",
    "Name": "s3-data-events-eds",
    "Status": "ENABLED",
    "AdvancedEventSelectors": [
        {
            "Name": "Log DeleteObject API calls for a specific S3 bucket",
            "FieldSelectors": [
                {
                    "Field": "eventCategory",
                    "Equals": [
                        "Data"
                    ]
                },
                {
                    "Field": "eventName",
                    "Equals": [
                        "DeleteObject"
                    ]
                },
                {
                    "Field": "resources.ARN",
                    "StartsWith": [
                        "arn:aws:s3:::amzn-s3-demo-bucket"
                    ]
                },
                {
                    "Field": "readOnly",
                    "Equals": [
                        "false"
                    ]
                },
                {
                    "Field": "resources.type",
                    "Equals": [
                        "AWS::S3::Object"
                    ]
                }
            ]
        }
    ],
    "MultiRegionEnabled": true,
    "OrganizationEnabled": false,
    "BillingMode": "FIXED_RETENTION_PRICING",

```

```
"RetentionPeriod": 2557,
"TerminationProtectionEnabled": true,
"CreatedTimestamp": "2023-11-09T22:20:36.344000+00:00",
"UpdatedTimestamp": "2023-11-09T22:20:36.476000+00:00"
}
```

List all event data stores in an account with the AWS CLI

The following example AWS CLI **list-event-data-stores** command returns information about all event data stores in an account, in the current Region. Optional parameters include `--max-results`, to specify a maximum number of results that you want the command to return on a single page. If there are more results than your specified `--max-results` value, run the command again adding the returned `NextToken` value to get the next page of results.

```
aws cloudtrail list-event-data-stores
```

The following is an example response.

```
{
  "EventDataStores": [
    {
      "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE7-cad6-4357-a84b-318f9868e969",
      "Name": "management-events-eds"
    },
    {
      "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE6-88e1-43b7-b066-9c046b4fd47a",
      "Name": "config-items-eds"
    },
    {
      "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLEf-b314-4c85-964e-3e43b1e8c3b4",
      "Name": "s3-data-events"
    }
  ]
}
```

Add resource tag keys and IAM global conditions keys, and expand event size

Run the AWS CLI `put-event-configuration` command to expand the maximum event size and add up to 50 resource tag keys and 50 IAM global condition keys to provide additional metadata about your events.

The `put-event-configuration` command accepts the following arguments:

- `--event-data-store` – Specify the ARN of the event data store or the ID suffix of the ARN. This parameter is required.
- `--max-event-size` – Set to `Large` to set the maximum event size to 1 MB. By default, the value is `Standard`, which specifies a maximum event size of 256 KB.

Note

In order to add resource tag keys or IAM global conditions keys, you must set the event size to `Large` to ensure all of your added keys are included in the event.

- `--context-key-selectors` – Specify the type of keys you want included in the events collected by your event data store. You can include resource tag keys and IAM global condition keys. Information about the added resource tags and IAM global condition keys is shown in the `eventContext` field in the event. For more information, see [Enrich CloudTrail events by adding resource tag keys and IAM global condition keys](#).
 - Set the `Type` to `TagContext` to pass in an array of up to 50 resource tag keys. If you add resource tags, CloudTrail events will include the selected tag keys associated with the resources that were involved in the API call. API events related to deleted resources will not have resource tags.
 - Set the `Type` to `RequestContext` to pass in an array of up to 50 IAM global condition keys. If you add IAM global condition keys, CloudTrail events will include information about the selected condition keys that were evaluated during the authorization process, including additional details about the principal, session, network, and the request itself.

The following example sets the maximum event size to `Large` and adds two resource tag keys `myTagKey1` and `myTagKey2`.

```
aws cloudtrail put-event-configuration \  
--event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-  
f852-4e8f-8bd1-bcf6cEXAMPLE \  

```

```
--max-event-size Large \  
--context-key-selectors ' [{"Type": "TagContext", "Equals": ["myTagKey1", "myTagKey2"]} ] '
```

The next example sets the maximum event size to Large and adds an IAM; global condition key (aws:MultiFactorAuthAge).

```
aws cloudtrail put-event-configuration \  
--event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-  
f852-4e8f-8bd1-bcf6cEXAMPLE \  
--max-event-size Large \  
--context-key-selectors ' [{"Type": "RequestContext", "Equals":  
["aws:MultiFactorAuthAge"]} ] '
```

The final example removes all resource tag keys and IAM global condition keys and sets the maximum event size to Standard.

```
aws cloudtrail put-event-configuration \  
--event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-  
f852-4e8f-8bd1-bcf6cEXAMPLE \  
--max-event-size Standard \  
--context-key-selectors
```

Get the event configuration for an event data store

Run the AWS CLI `get-event-configuration` command to return the event configuration for an event data store that collects CloudTrail events. This command returns the maximum event size and lists the resource tag keys and IAM global condition keys (if any) that are included in CloudTrail events.

```
aws cloudtrail get-event-configuration \  
--event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-  
f852-4e8f-8bd1-bcf6cEXAMPLE
```

Get the resource-based policy for an event data store with the AWS CLI

The following example runs the `get-resource-policy` command on an organization event data store.

```
aws cloudtrail get-resource-policy --resource-arn arn:aws:cloudtrail:us-  
east-1:888888888888:eventdatastore/example6-d493-4914-9182-e52a7934b207
```

Because the command was run on an organization event data store, the output will show both the provided resource-based policy and the [DelegatedAdminResourcePolicy](#) generated for the delegated administrator accounts.

Attach a resource-based policy to an event data store with the AWS CLI

To run queries on a dashboard during a manual or scheduled refresh, you need to attach a resource-based policy to every event data store that is associated with a widget on the dashboard. This allows CloudTrail Lake to run the queries on your behalf. For more information about the resource-based policy, see [Example: Allow CloudTrail to run queries to refresh a dashboard](#).

The following example attaches a resource-based policy to an event data store that allows CloudTrail to run queries on a dashboard when the dashboard is refreshed. The policy is created in a separate file, *policy.json*, with the following example policy statement:

JSON

```
{ "Version": "2012-10-17",      "Statement": [{ "Sid": "EDSPolicy", "Effect":
    "Allow", "Principal": { "Service": "cloudtrail.amazonaws.com" }, "Resource":
    "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
    event_data_store_ID",
    "Action": "cloudtrail:StartQuery", "Condition": { "StringEquals":
    { "AWS:SourceArn":
    "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-
    f852-4e8f-8bd1-bcf6cEXAMPLE",
    "AWS:SourceAccount": "123456789012" } } } ] }
```

Replace *123456789012* with your account ID, *arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/event_data_store_ID* with the ARN of the event data store for which CloudTrail will run queries, and *arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE* with the ARN of the dashboard.

```
aws cloudtrail put-resource-policy \
--resource-arn eds-arn \
--resource-policy file://policy.json
```

The following is the example response.


```
{ "ResourceArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE", "ResourcePolicy": "policy-statement" }
```

For additional policy examples, see [Resource-based policy examples for event data stores](#).

Delete the resource-based policy attached to an event data store with the AWS CLI

The following examples deletes the resource-based policy attached to an event data store. Replace *eds-arn* with the ARN of the event data store.

```
aws cloudtrail delete-resource-policy --resource-arn eds-arn
```

This command produces no output if it's successful.

Stop ingestion on an event data store with the AWS CLI

The following example AWS CLI **stop-event-data-store-ingestion** command stops an event data store from ingesting events. To stop ingestion, the event data store Status must be ENABLED and the eventCategory must be Management, Data, or ConfigurationItem. The event data store is specified by `--event-data-store`, which accepts an event data store ARN, or the ID suffix of the ARN. After you run **stop-event-data-store-ingestion**, the state of the event data store changes to STOPPED_INGESTION.

The event data store does count towards your account maximum of ten event data stores when its state is STOPPED_INGESTION.

```
aws cloudtrail stop-event-data-store-ingestion \  
--event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE
```

There is no response if the operation is successful.

Start ingestion on an event data store with the AWS CLI

The following example AWS CLI **start-event-data-store-ingestion** command starts event ingestion on an event data store. To start ingestion, the event data store Status must be STOPPED_INGESTION and the eventCategory must be Management, Data, or ConfigurationItem. The event data store is specified by `--event-data-store`, which accepts an event data store ARN, or the ID suffix of the ARN. After you run **start-event-data-store-ingestion**, the state of the event data store changes to ENABLED.

```
aws cloudtrail start-event-data-store-ingestion --event-data-store
arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-
bcf6cEXAMPLE
```

There is no response if the operation is successful.

Enable federation on an event data store

To enable federation, run the **aws cloudtrail enable-federation** command, providing the required `--event-data-store` and `--role` parameters. For `--event-data-store`, provide the event data store ARN (or the ID suffix of the ARN). For `--role`, provide the ARN for your federation role. The role must exist in your account and provide the [required minimum permissions](#).

```
aws cloudtrail enable-federation \
--event-data-store arn:aws:cloudtrail:region:account-id:eventdatastore/eds-id
--role arn:aws:iam::account-id:role/federation-role-name
```

This example shows how a delegated administrator can enable federation on an organization event data store by specifying the ARN of the event data store in the management account and the ARN of the federation role in the delegated administrator account.

```
aws cloudtrail enable-federation \
--event-data-store arn:aws:cloudtrail:region:management-account-id:eventdatastore/eds-id
--role arn:aws:iam::delegated-administrator-account-id:role/federation-role-name
```

Disable federation on an event data store

To disable federation on the event data store, run the **aws cloudtrail disable-federation** command. The event data store is specified by `--event-data-store`, which accepts an event data store ARN or the ID suffix of the ARN.

```
aws cloudtrail disable-federation \
--event-data-store arn:aws:cloudtrail:region:account-id:eventdatastore/eds-id
```

Note

If this is an organization event data store, use the account ID for the management account.

Restore an event data store with the AWS CLI

The following example AWS CLI **restore-event-data-store** command restores an event data store that is pending deletion. The event data store is specified by `--event-data-store`, which accepts an event data store ARN or the ID suffix of the ARN. You can only restore a deleted event data store within the seven-day wait period after deletion.

```
aws cloudtrail restore-event-data-store \  
--event-data-store EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE
```

The response includes information about the event data store, including its ARN, advanced event selectors, and the status of restoration.

Delete an event data store with the AWS CLI

This section demonstrates how to delete an event data store by running the AWS CLI `delete-event-data-store` command

To delete an event data store, specify the `--event-data-store` by providing the event data store ARN, or the ID suffix of the ARN. After you run **delete-event-data-store**, the final state of the event data store is `PENDING_DELETION`, and the event data store is automatically deleted after a wait period of 7 days.

After you run **delete-event-data-store** on an event data store, you cannot run **list-queries**, **describe-query**, or **get-query-results** on queries that are using the disabled data store. The event data store does count towards your account maximum of ten event data stores in an AWS Region when it is pending deletion.

Note

You can't delete an event data store if `--termination-protection-enabled` is set or its `FederationStatus` is `ENABLED`.

To delete an event data store with an `eventCategory` of `ActivityAuditLog`, you must first delete the integration's channel. You can delete the channel by using the `aws cloudtrail delete-channel` command. For more information, see [Delete a channel to delete an integration with the AWS CLI](#).

```
aws cloudtrail delete-event-data-store \  

```

```
--event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE
```

There is no response if the operation is successful.

Manage event data store lifecycles

The following are the lifecycle stages of an event data store:


- **CREATED** – A short-term state indicating that the event data store has been created.
- **ENABLED** – The event data store is active and ingesting events. You can run queries and copy trail events to the event data store.
- **STARTING_INGESTION** – A short-term state indicating that the event data store will start ingesting live events.
- **STOPPING_INGESTION** – A short-term state indicating that the event data store will stop ingesting live events.
- **STOPPED_INGESTION** – The event data store is not ingesting live events. You can still run queries on any events already in the event data store and copy trail events to the event data store.
- **PENDING_DELETION** – The event data store was in an **ENABLED** or **STOPPED_INGESTION** state and has been deleted but is within the 7-day wait period before permanent deletion. You cannot run queries on the event data store, and no operations can be performed on the event data store except restoration.

You can only delete an event data store if both federation and termination protection are disabled. *Termination protection* prevents an event data store from getting accidentally deleted. By default, termination protection is enabled on an event data store. [Federation](#) lets you query your event data store data in Athena and is disabled by default.

After you delete an event data store, it remains in the **PENDING_DELETION** state for 7 days before it is permanently deleted. You can restore an event data store during the 7-day wait period. While in the **PENDING_DELETION** state, an event data store is not available for queries, and no other operations can be performed on the event data store except restore operations. An event data store that is pending deletion does not ingest events and does not incur costs. However, event data stores that are pending deletion count toward the quota of event data stores that can exist in one AWS Region.

Actions available on event data stores

To [delete](#) or [restore](#) an event data store, [copy trail events](#), start or stop ingesting events, or turn on or turn off an event data store's termination protection, use commands on the **Actions** menu of the event data store's details page.



The option to **Copy trail events** is only available on event data stores that contain CloudTrail events. The options to **Start ingestion** and **Stop ingestion** are only available on event data stores containing either CloudTrail events (management and data events), or AWS Config configuration items.

Copy trail events to an event data store

You can copy trail events to a CloudTrail Lake event data store to create a point-in-time snapshot of events logged to the trail. Copying a trail's events does not interfere with the trail's ability to log events and does not modify the trail in any way.

You can copy trail events to an existing event data store configured for CloudTrail events, or you can create a new CloudTrail event data store and choose the **Copy trail events** option as part of event data store creation. For more information about copying trail events to an existing event data store, see [Copy trail events to an existing event data store with the console](#). For more information about creating a new event data store, see [Create an event data store for CloudTrail events with the console](#).

If you are copying trail events to an organization event data store, you must use the management account for the organization. You cannot copy trail events using the delegated administrator account for an organization.

CloudTrail Lake event data stores incur charges. When you create an event data store, you choose the [pricing option](#) you want to use for the event data store. The pricing option determines the

cost for ingesting and storing events, and the default and maximum retention period for the event data store. For information about CloudTrail pricing and managing Lake costs, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

When you copy trail events to a CloudTrail Lake event data store, you incur charges based on the amount of uncompressed data the event data store ingests.

When you copy trail events to CloudTrail Lake, CloudTrail unzips the logs that are stored in gzip (compressed) format and then copies the events contained in the logs to your event data store. The size of the uncompressed data could be greater than the actual S3 storage size. To get a general estimate of the size of the uncompressed data, you can multiply the size of the logs in the S3 bucket by 10.

You can reduce costs by specifying a narrower time range for the copied events. If you are planning to only use the event data store to query your copied events, you can turn off event ingestion to avoid incurring charges on future events. For more information, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

Scenarios

The following table describes some common scenarios for copying trail events and how you accomplish each scenario using the console.

Scenario	How do I accomplish this in the console?
Analyze and query historical trail events in CloudTrail Lake without ingesting new events	Create a new event data store and choose the Copy trail events option as part of event data store creation. When creating the event data store, deselect Ingest events (step 15 of the procedure) to ensure the event data store contains only the historical events for your trail and no future events.
Replace your existing trail with a CloudTrail Lake event data store	Create an event data store with the same event selectors as your trail to ensure that the event data store has the same coverage as your trail. To avoid duplicating events between the source trail and destination event data store, choose a date range for the copied events that is earlier than the creation of the event data store.

Scenario	How do I accomplish this in the console?
	After your event data store is created, you can turn off logging for the trail to avoid additional charges.

Topics

- [Considerations for copying trail events](#)
- [Required permissions for copying trail events](#)
- [Copy trail events to an existing event data store with the console](#)
- [Copy trail events to a new event data store with the console](#)
- [View event copy details with the CloudTrail console](#)

Considerations for copying trail events

Consider the following factors when copying trail events.

- When copying trail events, CloudTrail uses the S3 [GetObject](#) API operation to retrieve the trail events in the source S3 bucket. There are some S3 archived storage classes, such as S3 Glacier Flexible Retrieval, S3 Glacier Deep Archive, S3 Outposts, and S3 Intelligent-Tiering Deep Archive tiers that are not accessible by using `GetObject`. To copy trail events stored in these archived storage classes, you must first restore a copy using the S3 `RestoreObject` operation. For information about restoring archived objects, see [Restoring Archived Objects](#) in the *Amazon S3 User Guide*.
- When you copy trail events to an event data store, CloudTrail copies all trail events regardless of the configuration of the destination event data store's event types, advanced event selectors, or AWS Region.
- Before copying trail events to an existing event data store, be sure the event data store's pricing option and retention period are configured appropriately for your use case.
 - **Pricing option:** The pricing option determines the cost for ingesting and storing events. For more information about pricing options, see [AWS CloudTrail Pricing](#) and [Event data store pricing options](#).
 - **Retention period:** The retention period determines how long event data is kept in the event data store. CloudTrail only copies trail events that have an `eventTime` within the event data store's retention period. To determine the appropriate retention period, take the sum of the oldest event you want to copy in days and the number of days you want to retain the events

in the event data store (**retention period** = *oldest-event-in-days* + *number-days-to-retain*). For example, if the oldest event you're copying is 45 days old and you want to keep the events in the event data store for a further 45 days, you would set the retention period to 90 days.

- If you are copying trail events to an event data store for investigation and do not want to ingest any future events, you can stop ingestion on the event data store. When creating the event data store, deselect the **Ingest events** option (step 15 of the [procedure](#)) to ensure the event data store contains only the historical events for your trail and no future events.
- Before copying trail events, disable any access control lists (ACLs) attached to the source S3 bucket, and update the S3 bucket policy for the destination event data store. For more information about updating the S3 bucket policy, see [Amazon S3 bucket policy for copying trail events](#). For more information about disabling ACLs, see [Controlling ownership of objects and disabling ACLs for your bucket](#).
- CloudTrail only copies trail events from Gzip compressed log files that are in the source S3 bucket. CloudTrail does not copy trail events from uncompressed log files, or log files that were compressed using a format other than Gzip.
- To avoid duplicating events between the source trail and destination event data store, choose a time range for the copied events that is earlier than the creation of the event data store.
- By default, CloudTrail only copies CloudTrail events contained in the S3 bucket's CloudTrail prefix and the prefixes inside the CloudTrail prefix, and does not check prefixes for other AWS services. If you want to copy CloudTrail events contained in another prefix, you must choose the prefix when you copy trail events.
- To copy trail events to an organization event data store, you must use the management account for the organization. You cannot use the delegated administrator account to copy trail events to an organization event data store.

Required permissions for copying trail events

Before copying trail events, ensure you have all the required permissions for your IAM role. You only need to update the IAM role permissions if you choose an existing IAM role to copy trail events. If you choose to create a new IAM role, CloudTrail provides all necessary permissions for the role.

If the source S3 bucket uses a KMS key for data encryption, ensure that the KMS key policy allows CloudTrail to decrypt data in the bucket. If the source S3 bucket uses multiple KMS keys, you must update each key's policy to allow CloudTrail to decrypt data in the bucket.

Topics

- [IAM permissions for copying trail events](#)
- [Amazon S3 bucket policy for copying trail events](#)
- [KMS key policy for decrypting data in the source S3 bucket](#)

IAM permissions for copying trail events

When copying trail events, you have the option to create a new IAM role, or use an existing IAM role. When you choose a new IAM role, CloudTrail creates an IAM role with the required permissions and no further action is required on your part.

If you choose an existing role, ensure the IAM role's policies allow CloudTrail to copy trail events from the source S3 bucket. This section provides examples of the required IAM role permission and trust policies.

The following example provides the permissions policy, which allows CloudTrail to copy trail events from the source S3 bucket. Replace *amzn-s3-demo-bucket*, *myAccountID*, *region*, *prefix*, and *eventDataStoreId* with the appropriate values for your configuration. The *myAccountID* is the AWS account ID used for CloudTrail Lake, which may not be the same as the AWS account ID for the S3 bucket.

Replace *key-region*, *keyAccountID*, and *keyID* with the values for the KMS key used to encrypt the source S3 bucket. You can omit the `AWSCloudTrailImportKeyAccess` statement if the source S3 bucket does not use a KMS key for encryption.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "AWSCloudTrailImportBucketAccess",
      "Effect": "Allow",
      "Action": ["s3:ListBucket", "s3:GetBucketAcl"],
      "Resource": [
        "arn:aws:s3:::amzn-s3-demo-bucket"
      ],
      "Condition": {
        "StringEquals": {
          "aws:SourceAccount": "myAccountID",
          "aws:SourceArn":
            "arn:aws:cloudtrail:region:myAccountID:eventdatastore/eventDataStoreId"
        }
      }
    }
  ]
}
```

```

    }
  },
  {
    "Sid": "AWSCloudTrailImportObjectAccess",
    "Effect": "Allow",
    "Action": ["s3:GetObject"],
    "Resource": [
      "arn:aws:s3:::amzn-s3-demo-bucket/prefix",
      "arn:aws:s3:::amzn-s3-demo-bucket/prefix/*"
    ],
    "Condition": {
      "StringEquals": {
        "aws:SourceAccount": "myAccountID",
        "aws:SourceArn":
"arn:aws:cloudtrail:region:myAccountID:eventdatastore/eventDataStoreId"
      }
    }
  },
  {
    "Sid": "AWSCloudTrailImportKeyAccess",
    "Effect": "Allow",
    "Action": ["kms:GenerateDataKey", "kms:Decrypt"],
    "Resource": [
      "arn:aws:kms:key-region:keyAccountID:key/keyID"
    ]
  }
]
}

```

The following example provides the IAM trust policy, which allows CloudTrail to assume an IAM role to copy trail events from the source S3 bucket. Replace *myAccountID*, *region*, and *eventDataStoreArn* with the appropriate values for your configuration. The *myAccountID* is the AWS account ID used for CloudTrail Lake, which may not be the same as the AWS account ID for the S3 bucket.

```

{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Principal": {
        "Service": "cloudtrail.amazonaws.com"
      }
    }
  ]
}

```

```

    },
    "Action": "sts:AssumeRole",
    "Condition": {
      "StringEquals": {
        "aws:SourceAccount": "myAccountID",
        "aws:SourceArn":
"arn:aws:cloudtrail:region:myAccountID:eventdatastore/eventDataStoreId"
      }
    }
  }
]
}

```

Amazon S3 bucket policy for copying trail events

By default, Amazon S3 buckets and objects are private. Only the resource owner (the AWS account that created the bucket) can access the bucket and objects it contains. The resource owner can grant access permissions to other resources and users by writing an access policy.

Before you copy trail events, you must update the S3 bucket policy to allow CloudTrail to copy trail events from the source S3 bucket.

You can add the following statement to the S3 bucket policy to grant these permissions. Replace *roleArn* and *amzn-s3-demo-bucket* with the appropriate values for your configuration.

```

{
  "Sid": "AWSCloudTrailImportBucketAccess",
  "Effect": "Allow",
  "Action": [
    "s3:ListBucket",
    "s3:GetBucketAcl",
    "s3:GetObject"
  ],
  "Principal": {
    "AWS": "roleArn"
  },
  "Resource": [
    "arn:aws:s3:::amzn-s3-demo-bucket",
    "arn:aws:s3:::amzn-s3-demo-bucket/*"
  ]
}

```

```
]
},
```

KMS key policy for decrypting data in the source S3 bucket

If the source S3 bucket uses a KMS key for data encryption, ensure the KMS key policy provides CloudTrail with the `kms:Decrypt` and `kms:GenerateDataKey` permissions required to copy trail events from an S3 bucket with SSE-KMS encryption enabled. If your source S3 bucket uses multiple KMS keys, you must update each key's policy. Updating the KMS key policy allows CloudTrail to decrypt data in the source S3 bucket, run validation checks to ensure that events conform to CloudTrail standards, and copy events into the CloudTrail Lake event data store.

The following example provides the KMS key policy, which allows CloudTrail to decrypt the data in the source S3 bucket. Replace *roleArn*, *amzn-s3-demo-bucket*, *myAccountID*, *region*, and *eventDataStoreId* with the appropriate values for your configuration. The *myAccountID* is the AWS account ID used for CloudTrail Lake, which may not be the same as the AWS account ID for the S3 bucket.

```
{
  "Sid": "AWSCloudTrailImportDecrypt",
  "Effect": "Allow",
  "Action": [
    "kms:Decrypt",
    "kms:GenerateDataKey"
  ],
  "Principal": {
    "AWS": "roleArn"
  },
  "Resource": "*",
  "Condition": {
    "StringLike": {
      "kms:EncryptionContext:aws:s3:arn": "arn:aws:s3:::amzn-s3-demo-bucket/*"
    },
    "StringEquals": {
      "aws:SourceAccount": "myAccountID",
      "aws:SourceArn":
        "arn:aws:cloudtrail:region:myAccountID:eventdatastore/eventDataStoreId"
    }
  }
}
```

Copy trail events to an existing event data store with the console

Use the following procedure to copy trail events to an existing event data store. For information about how to create a new event data store, see [Create an event data store for CloudTrail events with the console](#).

Note

Before copying trail events to an existing event data store, be sure the event data store's pricing option and retention period are configured appropriately for your use case.

- **Pricing option:** The pricing option determines the cost for ingesting and storing events. For more information about pricing options, see [AWS CloudTrail Pricing](#) and [Event data store pricing options](#).
- **Retention period:** The retention period determines how long event data is kept in the event data store. CloudTrail only copies trail events that have an eventTime within the event data store's retention period. To determine the appropriate retention period, take the sum of the oldest event you want to copy in days and the number of days you want to retain the events in the event data store (**retention period** = *oldest-event-in-days* + *number-days-to-retain*). For example, if the oldest event you're copying is 45 days old and you want to keep the events in the event data store for a further 45 days, you would set the retention period to 90 days.

To copy trail events to an event data store

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose **Copy trail events**.
4. On the **Copy trail events** page, for **Event source**, choose the trail that you want to copy. By default, CloudTrail only copies CloudTrail events contained in the S3 bucket's CloudTrail prefix and the prefixes inside the CloudTrail prefix, and does not check prefixes for other AWS services. If you want to copy CloudTrail events contained in another prefix, choose **Enter S3 URI**, and then choose **Browse S3** to browse to the prefix. If the source S3 bucket for the trail uses a KMS key for data encryption, ensure that the KMS key policy allows CloudTrail to decrypt the data. If your source S3 bucket uses multiple KMS keys, you must update each

key's policy to allow CloudTrail to decrypt the data in the bucket. For more information about updating the KMS key policy, see [KMS key policy for decrypting data in the source S3 bucket](#).

The S3 bucket policy must grant CloudTrail access to copy trail events from your S3 bucket. For more information about updating the S3 bucket policy, see [Amazon S3 bucket policy for copying trail events](#).

5. For **Specify a time range of events**, choose the time range for copying the events. CloudTrail checks the prefix and log file name to verify the name contains a date between the chosen start and end date before attempting to copy trail events. You can choose a **Relative range** or an **Absolute range**. To avoid duplicating events between the source trail and destination event data store, choose a time range that is earlier than the creation of the event data store.

 Note

CloudTrail only copies trail events that have an eventTime within the event data store's retention period. For example, if an event data store's retention period is 90 days, then CloudTrail will not copy any trail events with an eventTime older than 90 days.

- If you choose **Relative range**, you can choose to copy events logged in the last 6 months, 1 year, 2 years, 7 years, or a custom range. CloudTrail copies the events logged within the chosen time period.
 - If you choose **Absolute range**, you can choose a specific start and end date. CloudTrail copies the events that occurred between the chosen start and end dates.
6. For **Delivery location**, choose the destination event data store from the drop-down list.
 7. For **Permissions**, choose from the following IAM role options. If you choose an existing IAM role, verify that the IAM role policy provides the necessary permissions. For more information about updating the IAM role permissions, see [IAM permissions for copying trail events](#).
 - Choose **Create a new role (recommended)** to create a new IAM role. For **Enter IAM role name**, enter a name for the role. CloudTrail automatically creates the necessary permissions for this new role.
 - Choose **Use a custom IAM role ARN** to use a custom IAM role that is not listed. For **Enter IAM role ARN**, enter the IAM ARN.
 - Choose an existing IAM role from the drop-down list.

8. Choose **Copy events**.
9. You are prompted to confirm. When you are ready to confirm, choose **Copy trail events to Lake**, and then choose **Copy events**.
10. On the **Copy details** page, you can see the copy status and review any failures. When a trail event copy completes, its **Copy status** is set to either **Completed** if there were no errors, or **Failed** if errors occurred.

 Note

Details shown on the event copy details page are not in real-time. The actual values for details such as **Prefixes copied** may be higher than what is shown on the page. CloudTrail updates the details incrementally over the course of the event copy.

11. If the **Copy status** is **Failed**, fix any errors shown in **Copy failures**, and then choose **Retry copy**. When you retry a copy, CloudTrail resumes the copy at the location where the failure occurred.

For more information about viewing the details of a trail event copy, see [View event copy details with the CloudTrail console](#).

Copy trail events to a new event data store with the console

This walkthrough shows you how to copy trail events to a new CloudTrail Lake event data store for historical analysis. For more information about copying trail events, see [Copy trail events to an event data store](#).

To copy trail events to a new event data store

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose **Create event data store**.
4. On the **Configure event data store** page, in **General details**, give your event data store a name, such as *my-management-events-eds*. As a best practice, use a name that quickly identifies the purpose of the event data store. For information about CloudTrail naming requirements, see [Naming requirements for CloudTrail resources, S3 buckets, and KMS keys](#).
5. Choose the **Pricing option** that you want to use for your event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention

periods for your event data store. For more information, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

The following are the available options:

- **One-year extendable retention pricing** - Generally recommended if you expect to ingest less than 25 TB of event data per month and want a flexible retention period of up to 10 years. For the first 366 days (the default retention period), storage is included at no additional charge with ingestion pricing. After 366 days, extended retention is available at pay-as-you-go pricing. This is the default option.
 - **Default retention period:** 366 days
 - **Maximum retention period:** 3,653 days
 - **Seven-year retention pricing** - Recommended if you expect to ingest more than 25 TB of event data per month and need a retention period of up to 7 years. Retention is included with ingestion pricing at no additional charge.
 - **Default retention period:** 2,557 days
 - **Maximum retention period:** 2,557 days
6. Specify a retention period for the event data store. Retention periods can be between 7 days and 3,653 days (about 10 years) for the **One-year extendable retention pricing** option, or between 7 days and 2,557 days (about seven years) for the **Seven-year retention pricing** option.

CloudTrail Lake determines whether to retain an event by checking if the eventTime of the event is within the specified retention period. For example, if you specify a retention period of 90 days, CloudTrail will remove events when their eventTime is older than 90 days.

 Note

CloudTrail will not copy an event if its eventTime is older than the specified retention period.

To determine the appropriate retention period, take the sum of the oldest event you want to copy in days and the number of days you want to retain the events in the event data store (**retention period** = *oldest-event-in-days* + *number-days-to-retain*). For example, if the oldest event you're copying is 45 days old and you want to keep the events in the event data store for a further 45 days, you would set the retention period to 90 days.

7. (Optional) In **Encryption**, choose whether you want to encrypt the event data store using your own KMS key. By default, all events in an event data store are encrypted by CloudTrail using a KMS key that AWS owns and manages for you.

To enable encryption using your own KMS key, choose **Use my own AWS KMS key**. Choose **New** to have an AWS KMS key created for you, or choose **Existing** to use an existing KMS key. In **Enter KMS alias**, specify an alias, in the format `alias/MyAliasName`. Using your own KMS key requires that you edit your KMS key policy to allow CloudTrail logs to be encrypted and decrypted. For more information, see [Configure AWS KMS key policies for CloudTrail](#). CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

Using your own KMS key incurs AWS KMS costs for encryption and decryption. After you associate an event data store with a KMS key, the KMS key cannot be removed or changed.

 Note

To enable AWS Key Management Service encryption for an organization event data store, you must use an existing KMS key for the management account.

8. (Optional) If you want to query against your event data using Amazon Athena, choose **Enable** in **Lake query federation**. Federation lets you view the metadata associated with the event data store in the AWS Glue [Data Catalog](#) and run SQL queries against the event data in Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know how to find, read, and process the data that you want to query. For more information, see [Federate an event data store](#).

To enable Lake query federation, choose **Enable** and then do the following:

- a. Choose whether you want to create a new role or use an existing IAM role. [AWS Lake Formation](#) uses this role to manage permissions for the federated event data store. When you create a new role using the CloudTrail console, CloudTrail automatically creates a role with the required permissions. If you choose an existing role, be sure the policy for the role provides the [required minimum permissions](#).
- b. If you are creating a new role, enter a name to identify the role.
- c. If you are using an existing role, choose the role you want to use. The role must exist in your account.

9. (Optional) Choose **Enable resource policy** to add a resource-based policy to your event data store. Resource-based policies allow you to control which principals can perform actions on your event data store. For example, you can add a resource based policy that allows the root users in other accounts to query this event data store and view the query results. For example policies, see [Resource-based policy examples for event data stores](#).

A resource-based policy includes one or more statements. Each statement in the policy defines the [principals](#) that are allowed or denied access to the event data store and the actions the principals can perform on the event data store resource.

The following actions are supported in resource-based policies for event data stores:

- `cloudtrail:StartQuery`
- `cloudtrail:CancelQuery`
- `cloudtrail:ListQueries`
- `cloudtrail:DescribeQuery`
- `cloudtrail:GetQueryResults`
- `cloudtrail:GenerateQuery`
- `cloudtrail:GenerateQueryResultsSummary`
- `cloudtrail:GetEventDataStore`

For [organization event data stores](#), CloudTrail creates a [default resource-based policy](#) that lists the actions that the delegated administrator accounts are allowed to perform on organization event data stores. The permissions in this policy are derived from the delegated administrator permissions in AWS Organizations. This policy is updated automatically following changes to the organization event data store or to the organization (for example, a CloudTrail delegated administrator account is registered or removed).

10. (Optional) In **Tags**, add one or more custom tags (key-value pairs) to your event data store. Tags can help you identify your CloudTrail event data stores. For example, you could attach a tag with the name **stage** and the value **prod**. You can use tags to limit access to your event data store. You can also use tags to track the query and ingestion costs for your event data store.

For information about how to use tags to track costs, see [Creating user-defined cost allocation tags for CloudTrail Lake event data stores](#). For information about how to use IAM policies to authorize access to an event data store based on tags, see [Examples: Denying access to create](#)

[or delete event data stores based on tags](#). For information about how you can use tags in AWS, see [Tagging your AWS resources](#) in the *Tagging AWS Resources User Guide*.

11. Choose **Next** to configure the event data store.
12. On the **Choose events** page, leave the default selections for **Event type**.

Event type [Info](#)

Choose the type of events you want to add to your event data store. [Additional charges apply](#)

Choose event types

☒ **AWS events**
Capture operations performed on or within your AWS resources.

☐ **Events from integrations**
Create an integration to get events that are logged by applications outside of your AWS resources.

Specify the type of AWS events

☒ **CloudTrail events**
CloudTrail events provide a record of activity in an AWS account.

☐ **CloudTrail Insights events**
Insights events help identify unusual activity, errors, or user behavior in your account. You will be charged separately if you enable Insights for both trails and event data stores.

☐ **Configuration items**
Configuration items show changes made to the configuration of a resource, and show the resource's compliance status.

13. For **CloudTrail events**, we'll leave **Management events** selected and choose **Copy trail events**. In this example, we're not concerned about the event types because we are only using the event data store to analyze past events and are not ingesting future events.

If you're creating an event data store to replace an existing trail, choose the same event selectors as your trail to ensure the event data store has the same event coverage.

CloudTrail events [Info](#)

☒ **Management events**
Capture management operations performed on your AWS resources.

☐ **Data events**
Log the resource operations performed on or within a resource.

☐ **Network activity events**
Network activity events provide information about resource operations performed on a resource within a virtual private cloud endpoint.

☒ **Copy trail events**
Copy CloudTrail events logged in your trails or from S3 buckets.

☐ **Enable for all accounts in my organization**
To review accounts in your organization, open AWS Organizations. [See all accounts](#)

► **Additional settings**

14. Choose **Enable for all accounts in my organization** if this is an organization event data store. This option won't be available to change unless you have accounts configured in AWS Organizations.

 Note

If you are creating an organization event data store, you must be signed in with the management account for the organization because only the management account can copy trail events to an organization event data store.

15. For **Additional settings**, we'll deselect **Ingest events**, because in this example we don't want the event data store to ingest any future events as we're only interested in querying the copied events. By default, an event data store collects events for all AWS Regions and starts ingesting events when it's created.
16. For **Management events**, we'll leave the default settings.
17. In the **Copy trail events** area, complete the following steps.
 - a. Choose the trail that you want to copy. In this example, we'll choose a trail named *management-events*.

By default, CloudTrail only copies CloudTrail events contained in the S3 bucket's CloudTrail prefix and the prefixes inside the CloudTrail prefix, and does not check prefixes for other AWS services. If you want to copy CloudTrail events contained in another prefix, choose **Enter S3 URI**, and then choose **Browse S3** to browse to the prefix. If the source S3 bucket for the trail uses a KMS key for data encryption, ensure that the KMS key policy allows CloudTrail to decrypt the data. If your source S3 bucket uses multiple KMS keys, you must update each key's policy to allow CloudTrail to decrypt the data in the bucket. For more information about updating the KMS key policy, see [KMS key policy for decrypting data in the source S3 bucket](#).

- b. Choose a time range for copying the events. CloudTrail checks the prefix and log file name to verify the name contains a date between the chosen start and end date before attempting to copy trail events. You can choose a **Relative range** or an **Absolute range**. To avoid duplicating events between the source trail and destination event data store, choose a time range that is earlier than the creation of the event data store.
 - If you choose **Relative range**, you can choose to copy events logged in the last 6 months, 1 year, 2 years, 7 years, or a custom range. CloudTrail copies the events logged within the chosen time period.
 - If you choose **Absolute range**, you can choose a specific start and end date. CloudTrail copies the events that occurred between the chosen start and end dates.

In this example, we'll choose **Absolute range** and we'll select the entire month of May.

The screenshot shows the AWS CloudTrail console's date range selection interface. At the top, there are two tabs: 'Relative range' and 'Absolute range', with 'Absolute range' being the active tab. Below the tabs is a calendar view for May 2024 and June 2024. The calendar for May 2024 is shown, with the entire month highlighted by a blue border. The dates are as follows:

Sun	Mon	Tue	Wed	Thu	Fri	Sat
			1	2	3	4
5	6	7	8	9	10	11
12	13	14	15	16	17	18
19	20	21	22	23	24	25
26	27	28	29	30	31	

Below the calendar, there are four input fields for the date range:

- Start date:** 2024/05/01
- Start time:** 00:00:00
- End date:** 2024/05/31
- End time:** 23:59:59

At the bottom of the interface, there are three buttons: 'Clear and dismiss', 'Cancel', and 'Apply'.

- c. For **Permissions**, choose from the following IAM role options. If you choose an existing IAM role, verify that the IAM role policy provides the necessary permissions. For more information about updating the IAM role permissions, see [IAM permissions for copying trail events](#).
- Choose **Create a new role (recommended)** to create a new IAM role. For **Enter IAM role name**, enter a name for the role. CloudTrail automatically creates the necessary permissions for this new role.
 - Choose **Use a custom IAM role ARN** to use a custom IAM role that is not listed. For **Enter IAM role ARN**, enter the IAM ARN.
 - Choose an existing IAM role from the drop-down list.

In this example, we'll choose **Create a new role (recommended)** and will provide the name **copy-trail-events**.

Copy existing trail events [Info](#)

Choose trail event source

management-events ▼

S3 location of CloudTrail data (S3 URI)

s3://aws-cloudtrail-logs- /AWSLogs/ /CloudTr

Specify a time range of events

2023-06-01T00:00:00-05:00 — 2023-06-30T23:59:59-05:00

i All CloudTrail events in your event source are imported, regardless of your event data store's configuration.

Choose IAM role

Create a new role (recommended) ▼

Enter IAM role name

The new role name is prepended with CloudTrailLake-us-east-1-

copy-trail-events


► **Permission policies**

18. Choose **Next** to review your choices.
19. On the **Review and create** page, review your choices. Choose **Edit** to make changes to a section. When you're ready to create the event data store, choose **Create event data store**.
20. The new event data store is visible in the **Event data stores** table on the **Event data stores** page.

Event data stores (3)						Refresh	Copy trail events	Create event data store
Name ▲	Status ▼	All regions ▼	All accounts ▼	Event type ▼				
my-management-events-eds	Enabled	Yes	No	CloudTrail events				


21. Choose the event data store name to view its details page. The details page shows the details for your event data store and the status of the copy. The event copy status is shown in the **Event copy status** area.

When a trail event copy completes, its **Copy status** is set to either **Completed** if there were no errors, or **Failed** if errors occurred.



Event log S3 location	Copy status	Copy ID	Created time	Finish time
s3://aws-cloudtrail-logs-...	Completed	...	July 18, 2023, 15:50:06 (UTC-05:00)	July 18, 2023, 15:53:07 (UTC-05:00)

22. To view more details about the copy, choose the copy name in the **Event log S3 location** column, or choose the **View details** option from the **Actions** menu. For more information about viewing the details of a trail event copy, see [View event copy details with the CloudTrail console](#).



CloudTrail > Lake > Event data stores > my-management-events-trail-events >

Copy ID

Copy details info

Event log S3 location s3://aws-cloudtrail-logs- /AWSLogs/ /CloudTrail/	Prefixes copied 817/817 prefixes copied (0 failures)	Created time July 18, 2023, 15:50:06 (UTC-05:00)
Copy ID	Copy status Completed	Finish time July 18, 2023, 16:04:51 (UTC-05:00)

Copy failures (0)
Retry copying prefixes that failed to copy.

Event location	Error message	Error type
No failures There are currently no copy failures.		

23. The **Copy failures** area shows any errors that occurred when copying trail events. If the **Copy status** is **Failed**, fix any errors shown in **Copy failures**, and then choose **Retry copy**. When you retry a copy, CloudTrail resumes the copy at the location where the failure occurred.

View event copy details with the CloudTrail console

After a trail event copy starts, you can view the event copy details, including the status of the copy, and information on any copy failures.

Note

Details shown on the event copy details page are not in real-time. The actual values for details such as **Prefixes copied** may be higher than what is shown on the page. CloudTrail updates the details incrementally over the course of the event copy.

To access the event copy details page

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the left navigation pane, under **Lake**, choose **Event data stores**.
3. Choose the event data store.
4. Choose the event copy in the **Event copy status** section.

Copy details

From **Copy details**, you can view the following details about the trail event copy.

- **Event log S3 location** - The location of the source S3 bucket containing the trail event log files.
- **Copy ID** - The ID for the copy.
- **Prefixes copied** - Represents the number of S3 prefixes copied. During a trail event copy, CloudTrail copies the events in the trail log files that are stored in the prefixes.
- **Copy status** - The status of the copy.
 - **Initializing** - Initial status shown when the trail event copy starts.
 - **In progress** - Indicates the trail event copy is in progress.

Note

You cannot copy trail events if another trail event copy is **In progress**. To stop a trail event copy, choose **Stop copy**.

- **Stopped** - Indicates a **Stop copy** action occurred. To retry a trail event copy, choose **Retry copy**.

- **Failed** - The copy completed, but some trail events failed to copy. Review the error messages in **Copy failures**. To retry a trail event copy, choose **Retry copy**. When you retry a copy, CloudTrail resumes the copy at the location where the failure occurred.
- **Completed** - The copy completed without errors. You can query the copied trail events in the event data store.
- **Created time** - Indicates when the trail event copy started.
- **Finish time** - Indicates when the trail event copy completed or stopped.

Copy failures

From **Copy failures**, you can review the error location, error message, and error type for each copy failure. Common reasons for failure, include if an S3 prefix contained an uncompressed file, or contained a file delivered by a service other than CloudTrail. Another possible cause of failure relates to access issues. For example, if the event data store's S3 bucket did not grant CloudTrail access to import the events, you would get an `AccessDenied` error.

For each copy failure, review the following error information.

- The **Error location** - Indicates the location in the S3 bucket where the error occurred. If an error occurred because the source S3 bucket contained an uncompressed file, the **Error location** would include the prefix where you would find that file.
- The **Error message** - Provides an explanation for why the error occurred.
- The **Error type** - Provides the error type. For example, an **Error type** of `AccessDenied`, indicates that the error occurred because of a permissions issue. For more information about the required permissions for copying trail events, see [Required permissions for copying trail events](#).

After resolving any failures, choose **Retry copy**. When you retry a copy, CloudTrail resumes the copy at the location where the failure occurred.

Federate an event data store

Federating an event data store lets you view the metadata associated with the event data store in the AWS Glue [Data Catalog](#), registers the Data Catalog with AWS Lake Formation, and lets you run SQL queries against your event data using Amazon Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know how to find, read, and process the data that you want to query.

You can enable federation by using the CloudTrail console, AWS CLI, or [EnableFederation](#) API operation. When you enable Lake query federation, CloudTrail creates a managed database named `aws:cloudtrail` (if the database doesn't already exist) and a managed federated table in the AWS Glue Data Catalog. The event data store ID is used for the table name. CloudTrail registers the federation role ARN and event data store in [AWS Lake Formation](#), the service responsible for allowing fine-grained access control of the federated resources in the AWS Glue Data Catalog.

To enable Lake query federation, you must create a new IAM role or choose an existing role. Lake Formation uses this role to manage permissions for the federated event data store. When you create a new role using the CloudTrail console, CloudTrail automatically creates the required permissions for the role. If you choose an existing role, be sure that the role provides the [minimum permissions](#).

You can disable federation by using the CloudTrail console, AWS CLI, or [DisableFederation](#) API operation. When you disable federation, CloudTrail disables the integration with AWS Glue, AWS Lake Formation, and Amazon Athena. After disabling Lake query federation, you can no longer query your event data in Athena. No CloudTrail Lake data is deleted when you disable federation and you can continue to run queries in CloudTrail Lake.

There are no CloudTrail charges for federating a CloudTrail Lake event data store. There are costs for running queries in Amazon Athena. For more information about Athena pricing, see [Amazon Athena Pricing](#).

[Analyze Activity Logs with AWS CloudTrail Lake and Amazon Athena](#)

Topics

- [Considerations](#)
- [Required permissions for federation](#)
- [Enable Lake query federation](#)
- [Disable Lake query federation](#)
- [Managing CloudTrail Lake federation resources with AWS Lake Formation](#)

Considerations

Consider the following factors when federating an event data store:

- There are no CloudTrail charges for federating a CloudTrail Lake event data store. There are costs for running queries in Amazon Athena. For more information about Athena pricing, see [Amazon Athena Pricing](#).
- Lake Formation is used to manage permissions for the federated resources. If you delete the federation role, or revoke permissions to the resources from Lake Formation or AWS Glue, you can't run queries from Athena. For more information about working with Lake Formation, see [Managing CloudTrail Lake federation resources with AWS Lake Formation](#).
- Anyone using Amazon Athena to query data registered with Lake Formation must have an IAM permissions policy that allows the `lakeformation:GetDataAccess` action. The AWS managed policy: [AmazonAthenaFullAccess](#) allows this action. If you use inline policies, be sure to update permissions policies to allow this action. For more information, see [Managing Lake Formation and Athena user permissions](#).
- To create views on federated tables in Athena, you need a destination database other than `aws:cloudtrail`. This is because the `aws:cloudtrail` database is managed by CloudTrail.
- To create a dataset in Amazon Quick Suite, you must choose the **Use custom SQL** option. For more information, see [Creating a dataset using Amazon Athena data](#).
- If federation is enabled, you can't delete an event data store. To delete a federated event data store, you must first [disable federation](#) and [termination protection](#) if it's enabled.
- The following considerations apply to organization event data stores:
 - Only a single delegated administrator account or the management account can enable federation on an organization event data store. Other delegated administrator accounts can still query and share information using the [Lake Formation data sharing feature](#).
 - Any delegated administrator account or the organization's management account can disable federation.

Required permissions for federation

Before federating an event data store, be sure that you have all the required permissions for the federation role and for enabling and disabling federation. You only need to update the federation role permissions if you choose an existing IAM role to enable federation. If you choose to create a new IAM role using the CloudTrail console, CloudTrail provides all necessary permissions for the role.

Topics

- [IAM permissions for federating an event data store](#)

- [Required permissions for enabling federation](#)
- [Required permissions for disabling federation](#)

IAM permissions for federating an event data store

When you enable federation, you have the option to create a new IAM role, or use an existing IAM role. When you choose a new IAM role, CloudTrail creates an IAM role with the required permissions and no further action is required on your part.

If you choose an existing role, ensure the IAM role's policies provide the required permissions to enable federation. This section provides examples of the required IAM role permission and trust policies.

The following example provides the permissions policy for the federation role. For the first statement provide the full ARN of your event data store for the Resource.

The second statement in this policy allows Lake Formation to decrypt data for an event data store encrypted with a KMS key. Replace *key-region*, *account-id*, and *key-id* with the values for your KMS key. You can omit this statement if your event data store does not use a KMS key for encryption.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "LakeFederationEDSDataAccess",
      "Effect": "Allow",
      "Action": "cloudtrail:GetEventDataStoreData",
      "Resource": "arn:aws:cloudtrail:us-east-1:111111111111:eventdatastore/eds-id"
    },
    {
      "Sid": "LakeFederationKMSTransferAccess",
      "Effect": "Allow",
      "Action": [
        "kms:Decrypt",
        "kms:GenerateDataKey"
      ],
      "Resource": "arn:aws:kms:us-east-1:111111111111:key/key-id"
    }
  ]
}
```

```
    }  
  ]  
}
```

The following example provides the IAM trust policy, which allows AWS Lake Formation to assume an IAM role to manage permissions for the federated event data store.

JSON

```
{  
  "Version": "2012-10-17",  
  "Statement": [  
    {  
      "Effect": "Allow",  
      "Principal": {  
        "Service": "lakeformation.amazonaws.com"  
      },  
      "Action": "sts:AssumeRole"  
    }  
  ]  
}
```

Required permissions for enabling federation

The following example policy provides the minimum required permissions to enable federation on an event data store. This policy allows CloudTrail to enable federation on the event data store, AWS Glue to create the federated resources in the AWS Glue Data Catalog, and AWS Lake Formation to manage resource registration.

JSON

```
{  
  "Version": "2012-10-17",  
  "Statement": [  
    {  
      "Sid": "CloudTrailEnableFederation",  
      "Effect": "Allow",  
      "Action": "cloudtrail:EnableFederation",  
    }  
  ]  
}
```

```

        "Resource": "arn:aws:cloudtrail:us-
east-1:111111111111:eventdatastore/eds-id"
    },
    {
        "Sid": "FederationRoleAccess",
        "Effect": "Allow",
        "Action": [
            "iam:PassRole",
            "iam:GetRole"
        ],
        "Resource": "arn:aws:iam::111122223333:role/federation-role-name"
    },
    {
        "Sid": "GlueResourceCreation",
        "Effect": "Allow",
        "Action": [
            "glue:CreateDatabase",
            "glue:CreateTable",
            "glue:PassConnection"
        ],
        "Resource": [
            "arn:aws:glue:us-east-1:111111111111:catalog",
            "arn:aws:glue:us-east-1:111111111111:database/aws:cloudtrail",
            "arn:aws:glue:us-east-1:111111111111:table/aws:cloudtrail/eds-
id",
            "arn:aws:glue:us-east-1:111111111111:connection/aws:cloudtrail"
        ]
    },
    {
        "Sid": "LakeFormationRegistration",
        "Effect": "Allow",
        "Action": [
            "lakeformation:RegisterResource",
            "lakeformation:DeregisterResource"
        ],
        "Resource":
            "arn:aws:lakeformation:region:111111111111:catalog:111111111111"
    }
]
}

```

Required permissions for disabling federation

The following example policy provides the minimum required resources to disable federation on an event data store. This policy allows CloudTrail to disable federation on the event data store, AWS Glue to delete the managed federated table in the AWS Glue Data Catalog, and Lake Formation to deregister the federated resource.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "CloudTrailDisableFederation",
      "Effect": "Allow",
      "Action": "cloudtrail:DisableFederation",
      "Resource": "arn:aws:cloudtrail:us-east-1:111111111111:eventdatastore/eds-id"
    },
    {
      "Sid": "GlueTableDeletion",
      "Effect": "Allow",
      "Action": "glue:DeleteTable",
      "Resource": [
        "arn:aws:glue:us-east-1:111111111111:catalog",
        "arn:aws:glue:us-east-1:111111111111:database/aws:cloudtrail",
        "arn:aws:glue:us-east-1:111111111111:table/aws:cloudtrail/eds-id"
      ]
    },
    {
      "Sid": "LakeFormationDeregistration",
      "Effect": "Allow",
      "Action": "lakeformation:DeregisterResource",
      "Resource": "arn:aws:lakeformation:us-east-1:111111111111:catalog:111111111111"
    }
  ]
}
```

Enable Lake query federation

You can enable Lake query federation by using the CloudTrail console, AWS CLI, or [EnableFederation](#) API operation. When you enable Lake query federation, CloudTrail creates a managed database named `aws:cloudtrail` (if the database doesn't already exist) and a managed federated table in the AWS Glue Data Catalog. The event data store ID is used for the table name. CloudTrail registers the federation role ARN and event data store in [AWS Lake Formation](#), the service responsible for allowing fine-grained access control of the federated resources in the AWS Glue Data Catalog.

This section describes how to enable federation using the CloudTrail console and AWS CLI.

CloudTrail console

The following procedure shows you how to enable Lake query federation on an existing event data store.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose the event data store that you want to update. This opens the event data store's details page.
4. In **Lake query federation**, choose **Edit** and then choose **Enable**.
5. Choose whether to create a new IAM role, or use an existing role. When you create a new role, CloudTrail automatically creates a role with the required permissions. If you're using an existing role, be sure the role's policy provides the [required minimum permissions](#).
6. If you're creating a new IAM role, enter a name for the role.
7. If you're choosing an existing IAM role, choose the role you want to use. The role must exist in your account.
8. Choose **Save changes**. The **Federation status** changes to Enabled.

AWS CLI

To enable federation, run the **aws cloudtrail enable-federation** command, providing the required **--event-data-store** and **--role** parameters. For **--event-data-store**, provide the event data store ARN (or the ID suffix of the ARN). For **--role**, provide the ARN for your federation role. The role must exist in your account and provide the [required minimum permissions](#).


```
aws cloudtrail enable-federation
--event-data-store arn:aws:cloudtrail:region:account-id:eventdatastore/eds-id
--role arn:aws:iam::account-id:role/federation-role-name
```

This example shows how a delegated administrator can enable federation on an organization event data store by specifying the ARN of the event data store in the management account and the ARN of the federation role in the delegated administrator account.

```
aws cloudtrail enable-federation
--event-data-store arn:aws:cloudtrail:region:management-account-id:eventdatastore/eds-id
--role arn:aws:iam::delegated-administrator-account-id:role/federation-role-name
```

Disable Lake query federation

You can disable federation by using the CloudTrail console, AWS CLI, or [DisableFederation](#) API operation. When you disable federation, CloudTrail disables the integration with AWS Glue, AWS Lake Formation, and Amazon Athena. After disabling Lake query federation, you can no longer query your event data in Athena. No CloudTrail Lake data is deleted when you disable federation and you can continue to run queries in CloudTrail Lake.

This section describes how to disable federation using the CloudTrail console and AWS CLI.

CloudTrail console

The following procedure shows you how to disable Lake query federation on an existing event data store.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose the event data store that you want to update. This opens the event data store's details page.
4. In **Lake query federation**, choose **Edit** and then choose **Disable**.
5. Choose **Save changes**. The **Federation status** changes to Disabled.

AWS CLI

To disable federation on the event data store, run the **aws cloudtrail disable-federation** command. The event data store is specified by `--event-data-store`, which accepts an event data store ARN or the ID suffix of the ARN.

```
aws cloudtrail disable-federation
--event-data-store arn:aws:cloudtrail:region:account-id:eventdatastore/eds-id
```

Note

If this is an organization event data store, use the account ID for the management account.

Managing CloudTrail Lake federation resources with AWS Lake Formation

When you federate an event data store, CloudTrail registers the federation role ARN and event data store in AWS Lake Formation, the service responsible for allowing fine-grained access control of the federated resources in the AWS Glue Data Catalog. This section describes how you can use Lake Formation to manage the CloudTrail Lake federation resources.

When you enable federation, CloudTrail creates the following resources in the AWS Glue Data Catalog.

- **Managed database** – CloudTrail creates 1 database with the name `aws:cloudtrail` per account. CloudTrail manages the database. You can't delete or modify the database in AWS Glue.
- **Managed federated table** – CloudTrail creates 1 table for each federated event data store and uses the event data store ID for the table name. CloudTrail manages the tables. You can't delete or modify the tables in AWS Glue. To delete a table, you must [disable federation](#) on the event data store.

Controlling access to federated resources

You can use one of two permissions methods to control access to the managed database and tables.

- **IAM only access control** – With IAM only access control, all users in the account with the required IAM permissions are given access to all Data Catalog resources. For information about how AWS Glue works with IAM, see [How AWS Glue works with IAM](#).

On the Lake Formation console, this method appears as **Use only IAM access control**.

 Note

If you want to create data filters and use other Lake Formation features, you must use Lake Formation access control.

- **Lake Formation access control** – This method provides the following advantages.
 - You can implement column-level, row-level, and cell-level security by creating [data filters](#). For more information, see [Securing data lakes with row-level access control](#) in the *AWS Lake Formation Developer Guide*.
 - Database and tables are only visible to Lake Formation administrators and creators of the database and resources. If another user needs access to these resources, you must explicitly [grant access by using Lake Formation permissions](#).

For more information about access control, see [Methods for fine-grained access control](#).

Determining the permissions method for a federated resource

When you enable federation for the first time, CloudTrail creates a managed database and managed federated table using your Lake Formation data lake settings.

After CloudTrail enables federation, you can verify which permissions method you are using for the managed database and managed federated table by checking the permissions for those resources. If the ALL (*Super*) to IAM_ALLOWED_PRINCIPALS setting is present for the resource, the resource is managed exclusively by IAM permissions. If the setting is missing, the resource is managed by Lake Formation permissions. For more information about Lake Formation permissions, see [Lake Formation permissions reference](#).

The permissions method for the managed database and managed federated table can differ. For example, if you check the values for the database and table, you could see the following:

- For the database, the value that assigns ALL (*Super*) to IAM_ALLOWED_PRINCIPALS is present in the permissions indicating that the you're using IAM only access control for the database.

- For the table, the value that assigns ALL (*Super*) to IAM_ALLOWED_PRINCIPALS not present, which indicates access control by Lake Formation permissions.

You can switch between access methods at any time by adding or removing ALL (*Super*) to IAM_ALLOWED_PRINCIPALS permission on any federated resource in Lake Formation.

Cross-account sharing using Lake Formation

This section describes how to share a managed database and managed federated table across accounts by using Lake Formation.

You can share a managed database across accounts by taking these steps:

1. Update the [cross-account data sharing version](#) to version 4.
2. Remove Super to IAM_ALLOWED_PRINCIPALS permissions from the database if present to switch to Lake Formation access control.
3. Grant Describe permissions to the external account on the database.
4. If a Data Catalog resource is shared with your AWS account and your account is not in the same AWS organization as the sharing account, accept the resource share invitation from AWS Resource Access Manager (AWS RAM). For more information, see [Accepting a resource share invitation from AWS RAM](#).

After completing these steps, the database should be visible to the external account. By default, sharing the database does not give access to any tables in the database.

You can share all or individual managed federated tables with an external account by taking these steps:

1. Update the [cross-account data sharing version](#) to version 4.
2. Remove Super to IAM_ALLOWED_PRINCIPALS permissions from the table if present to switch to Lake Formation access control.
3. (Optional) Specify any [data filters](#) to restrict columns or rows.
4. Grant Select permissions to the external account on the table.
5. If a Data Catalog resource is shared with your AWS account and your account is not in the same AWS organization as the sharing account, accept the resource share invitation from AWS Resource Access Manager (AWS RAM). For an organization, you can auto accept using RAM settings. For more information, see [Accepting a resource share invitation from AWS RAM](#).

6. The table should now be visible. To enable Amazon Athena queries on this table, create a [resource link in this account](#) with the shared table.

The owning account can revoke sharing at any point by removing permissions for the external account from Lake Formation, or by [disabling federation](#) in CloudTrail.

Understanding organization event data stores

If you have created an organization in AWS Organizations, you can create an *organization event data store* that logs all events for all AWS accounts in that organization. Organization event data stores can apply to all AWS Regions, or the current Region. You can't use an organization event data store to collect events from outside of AWS.

You can [create an organization event data store](#) by using either the management account or the delegated administrator account. When a delegated administrator creates an organization event data store, the organization event data store exists in the management account for the organization. This approach is because the management account maintains ownership of all organization resources.

The management account for an organization can [update an account-level event data store](#) to apply it to an organization.

When the organization event data store is specified as applying to an organization, it's automatically applied to all member accounts in the organization. Member accounts can't see the organization event data store, nor can they modify or delete it. By default, member accounts don't have access to the organization event data store, nor can they run queries on organization event data stores.

The following table shows the capabilities of the management account and delegated administrator accounts within the AWS Organizations organization.

Capabilities	Management account	Delegated administrator account
Register or remove delegated administrator accounts.	Yes	No

Capabilities	Management account	Delegated administrator account
Create an organization event data store for AWS CloudTrail events or AWS Config configuration items.	Yes	Yes
Enable Insights on an organization event data store.	Yes	No
Update an organization event data store.	Yes	Yes ¹
Start and stop event ingestion on an organization event data store.	Yes	Yes
Enable Lake query federation on an organization event data store. ²	Yes	Yes
Disable Lake query federation on an organization event data store.	Yes	Yes
Delete an organization event data store.	Yes	Yes
Copy trail events to an event data store.	Yes	No
Run queries on organization event data stores.	Yes	Yes
View a managed dashboard for an organization event data store.	Yes	No
Enable the Highlights dashboard for organization event data stores.	Yes	No
Create a widget for a custom dashboard that queries an organization event data store.	Yes	No

¹Only the management account can convert an organization event data store to an account-level event data store, or convert an account-level event data store to an organization event data store. These actions are not allowed for the delegated administrator because organization event data stores only exist in the management account. When an organization event data store is converted to an account-level event data store, only the management account has access to the event data store. Likewise, only an account-level event data store in the management account can be converted to an organization event data store.

²Only a single delegated administrator account or the management account can enable federation on an organization event data store. Other delegated administrator accounts can query and share information using the [Lake Formation data sharing feature](#). Any delegated administrator account as well as the organization's management account can disable federation.

Create an organization event data store

The management account or delegated administrator account for an organization can create an organization event data store to collect either CloudTrail events (management events, data events) or AWS Config configuration items.

Note

Only the organization's management account can copy trail events to an event data store.

CloudTrail console

To create an organization event data store using the console

1. Follow the steps in the [create an event data store for CloudTrail events](#) procedure to create an organization event data store for CloudTrail management or data events.

OR

Follow the steps in the [create an event data store for AWS Config configuration items](#) procedure to create an organization event data store for AWS Config configuration items.

2. On the **Choose events** page, choose **Enable for all accounts in my organization**.

AWS CLI

To create an organization event data store run the [create-event-data-store](#) command and include the `--organization-enabled` option.

The following example AWS CLI `create-event-data-store` command creates an organization event data store that collects all management events. Because CloudTrail logs management events by default, you don't need to specify advanced event selectors if your event data store is logging all management events and is not collecting any data events.

```
aws cloudtrail create-event-data-store --name org-management-eds --organization-enabled
```

The following is an example response.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE6-d493-4914-9182-e52a7934b207",
  "Name": "org-management-eds",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Default management events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": true,
  "OrganizationEnabled": true,
  "BillingMode": "EXTENDABLE_RETENTION_PRICING",
  "RetentionPeriod": 366,
  "TerminationProtectionEnabled": true,
  "CreatedTimestamp": "2023-11-16T15:30:50.689000+00:00",
  "UpdatedTimestamp": "2023-11-16T15:30:50.851000+00:00"
}
```


The next example AWS CLI `create-event-data-store` command creates an organization event data store named `config-items-org-eds` that collects AWS Config configuration items. To collect configuration items, specify that the `eventCategory` field equals `ConfigurationItem` in the advanced event selectors.

```
aws cloudtrail create-event-data-store --name config-items-org-eds \
--organization-enabled \
--advanced-event-selectors '[
  {
    "Name": "Select AWS Config configuration items",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["ConfigurationItem"] }
    ]
  }
]'
```

Apply an account-level event data store to an organization

The organization's management account can convert an account-level event data store to apply it to an organization.

CloudTrail console

To update an account-level event data store using the console

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, under **Lake**, choose **Event data stores**.
3. Choose the event data store that you want to update. This action opens the event data store's details page.
4. In **General details**, choose **Edit**.
5. Choose **Enable for all accounts in my organization**.
6. Choose **Save changes**.

For additional information about updating an event data store, see [Update an event data store with the console](#).

AWS CLI

To update an account-level event data store to apply it to an organization, run the [update-event-data-store](#) command and include the `--organization-enabled` option.

```
aws cloudtrail update-event-data-store --region us-east-1 \  
--organization-enabled \  
--event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-  
f852-4e8f-8bd1-bcf6cEXAMPLE
```

Default resource policy for delegated administrators

CloudTrail automatically generates a resource policy named `DelegatedAdminResourcePolicy` for [organization event data stores](#) that lists the actions that the delegated administrator accounts are allowed to perform on organization event data stores. The permissions in `DelegatedAdminResourcePolicy` are derived from the delegated administrator permissions in AWS Organizations.

The purpose of `DelegatedAdminResourcePolicy` is to ensure that the delegated administrator accounts can manage the organization event data store on the behalf of the organization and are not unintentionally denied access to the organization event data store when a resource-based policy is attached to the organization event data store that allows or denies principals from performing an action on the organization event data store.

CloudTrail evaluates `DelegatedAdminResourcePolicy` in tandem with any resource-based policy provided for the organization event data store. The delegated administrator accounts would only be denied access if the provided resource-based policy included a statement that explicitly denied the delegated administrator accounts from performing an action on the organization event data store that the delegated administrator accounts would otherwise be able to perform.

This `DelegatedAdminResourcePolicy` policy is updated automatically when:

- The management account converts an organization event data store to an account-level event data store, or converts an account-level event data store to an organization event data store.
- There are organization changes. For example, the management account registers or removes a CloudTrail delegated administrator account.

You can view the up-to-date policy on the **Delegated administrator resource policy** section on the CloudTrail console, or by running the AWS CLI `get-resource-policy` command and passing the ARN of the organization event data store.

The following example runs the `get-resource-policy` command on an organization event data store.

```
aws cloudtrail get-resource-policy --resource-arn arn:aws:cloudtrail:us-east-1:888888888888:eventdatastore/example6-d493-4914-9182-e52a7934b207
```

The output of this command will show the resource-based policy and the `DelegatedAdminResourcePolicy` policy generated for the delegated administrator accounts.

Additional resources

- [Organization delegated administrator](#)
- [Add a CloudTrail delegated administrator](#)
- [Remove a CloudTrail delegated administrator](#)

Create an integration with an event source outside of AWS

You can use CloudTrail to log and store user activity data from any source in your hybrid environments, such as in-house or SaaS applications hosted on-premises or in the cloud, virtual machines, or containers. You can store, access, analyze, troubleshoot and take action on this data without maintaining multiple log aggregators and reporting tools.

Activity events from non-AWS sources work by using *channels* to bring events into CloudTrail Lake from external partners that work with CloudTrail, or from your own sources. When you create a channel, you choose one or more event data stores to store events that arrive from the channel source. You can change the destination event data stores for a channel as needed, as long as the destination event data stores are set to log `eventCategory="ActivityAuditLog"` events. When you create a channel for events from an external partner, you provide a channel ARN to the partner or source application. The resource policy attached to the channel allows the source to transmit events through the channel. If a channel does not have a resource policy, only the channel owner can call the `PutAuditEvents` API on the channel.

CloudTrail has partnered with many event source providers, such as Okta and LaunchDarkly. When you create an integration with an event source outside AWS, you can choose one of these partners

as your event source, or choose **My custom integration** to integrate events from your own sources into CloudTrail. A maximum of one channel is allowed per source.

There are two types of integrations: direct and solution. With direct integrations, the partner calls the `PutAuditEvents` API to deliver events to the event data store for your AWS account. With solution integrations, the application runs in your AWS account and the application calls the `PutAuditEvents` API to deliver events to the event data store for your AWS account.

From the **Integrations** page, you can choose the **Available sources** tab to view the **Integration type** for partners.

Browse available sources (18) [Info](#)

Find sources

< 1 >

My custom integration

Description
Add an integration with any application, container, virtual machine, database, or on-premises component that generates events compatible with the CloudTrail event schema.

Integration Type
Solution

[Add integration](#)

Cloud Storage Security

Description
Cloud Storage Security (CSS) provides antivirus and data classification services. Audit CSS events such as problem file discovery and bucket configuration changes in CloudTrail with this integration. [Learn more](#)

Integration Type
Solution

[Add integration](#)

Clumio

Description
This app allows you to seamlessly integrate your Clumio Audit logs directly into CloudTrail Lake. [Learn more](#)

Integration Type
Direct

[Add integration](#)

To get started, create an integration to log events from partner or other application sources using the CloudTrail console.

Topics

- [Create an integration with a CloudTrail partner with the console](#)
- [Create a custom integration with the console](#)
- [Create, update, and manage CloudTrail Lake integrations with the AWS CLI](#)
- [Additional information about integration partners](#)
- [CloudTrail Lake integrations event schema](#)

Create an integration with a CloudTrail partner with the console

When you create an integration with an event source outside AWS, you can choose one of these partners as your event source. When you create an integration in CloudTrail with a partner application, the partner needs the Amazon Resource Name (ARN) of the channel that you create in this workflow to send events to CloudTrail. After you create the integration, you finish configuring the integration by following the partner's instructions to provide the required channel ARN to the partner. The integration starts ingesting partner events into CloudTrail after the partner calls `PutAuditEvents` on the integration's channel.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Integrations**.
3. On the **Add integration** page, enter a name for your channel. The name can be 3-128 characters. Only letters, numbers, periods, underscores, and dashes are allowed.
4. Choose the partner application source from which you want to get events. If you're integrating with events from your own applications hosted on-premises or in the cloud, choose **My custom integration**.
5. From **Event delivery location**, choose to log the same activity events to existing event data stores, or create a new event data store.

If you choose to create a new event data store, enter a name for the event data store, choose the pricing option, and specify the retention period in days. The event data store retains event data for the specified number of days.

If you choose to log activity events to one or more existing event data stores, choose the event data stores from the list. The event data stores can only include activity events. The event type in the console must be **Events from integrations**. In the API, the `eventCategory` value must be `ActivityAuditLog`.

6. In **Resource policy**, configure the resource policy for the integration's channel. Resource policies are JSON policy documents that specify what actions a specified principal can perform on the resource and under what conditions. The accounts defined as principals in the resource policy can call the `PutAuditEvents` API to deliver events to your channel. The resource owner has implicit access to the resource if their IAM policy allows the `cloudtrail-data:PutAuditEvents` action.

The information required for the policy is determined by the integration type. For a direction integration, CloudTrail automatically adds the partner's AWS account IDs, and requires you to enter the unique external ID provided by the partner. For a solution integration, you must specify at least one AWS account ID as principal, and can optionally enter an external ID to prevent against confused deputy.

 Note

If you do not create a resource policy for the channel, only the channel owner can call the `PutAuditEvents` API on the channel.

- a. For a direct integration, enter the external ID provided by your partner. The integration partner provides a unique external ID, such as an account ID or a randomly generated string, to use for the integration to prevent against confused deputy. The partner is responsible for creating and providing a unique external ID.

You can choose **How to find this?** to view the partner's documentation that describes how to find the external ID.

External ID

Enter the unique account identifier provided by Nordcloud. [How to find this?](#) 

 Note

If the resource policy includes an external ID, all calls to the `PutAuditEvents` API must include the external ID. However, if the policy does not define an external ID, the partner can still call the `PutAuditEvents` API and specify an `externalId` parameter.

- b. For a solution integration, choose **Add AWS account** to specify an AWS account ID to add as a principal in the policy.
7. (Optional) In the **Tags** area, you can add up to 50 tag key and value pairs to help you identify, sort, and control access to your event data store and channel. For more information about how to use IAM policies to authorize access to an event data store based on tags, see [Examples:](#)

[Denying access to create or delete event data stores based on tags](#). For more information about how you can use tags in AWS, see [Tagging AWS resources](#) in the *AWS General Reference*.

8. When you are ready to create the new integration, choose **Add integration**. There is no review page. CloudTrail creates the integration, but you must provide the channel Amazon Resource Name (ARN) to the partner application. Instructions for providing the channel ARN to the partner application are found on the partner documentation website. For more information, choose the **Learn more** link for the partner on the **Available sources** tab of the **Integrations** page to open the partner's page in AWS Marketplace.

To finish the setup for your integration, provide the channel ARN to the partner or source application. Depending upon the integration type, either you, the partner, or the application runs the `PutAuditEvents` API to deliver activity events to the event data store for your AWS account. After your activity events are delivered, you can use CloudTrail Lake to search, query, and analyze the data that is logged from your applications. Your event data includes fields that match CloudTrail event payload, such as `eventVersion`, `eventSource`, and `userIdentity`.

Create a custom integration with the console

You can use CloudTrail to log and store user activity data from any source in your hybrid environments, such as in-house or SaaS applications hosted on-premises or in the cloud, virtual machines, or containers. Perform the first half of this procedure in the CloudTrail Lake console, then call the [PutAuditEvents](#) API to ingest events, providing your channel ARN and event payload. After you use the `PutAuditEvents` API to ingest your application activity into CloudTrail, you can use CloudTrail Lake to search, query, and analyze the data that is logged from your applications.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Integrations**.
3. On the **Add integration** page, enter a name for your channel. The name can be 3-128 characters. Only letters, numbers, periods, underscores, and dashes are allowed.
4. Choose **My custom integration**.
5. From **Event delivery location**, choose to log the same activity events to existing event data stores, or create a new event data store.

If you choose to create a new event data store, enter a name for the event data store and specify the retention period in days. You can keep the event data in an event data store for up to 3,653 days (about 10 years) if you choose the **One-year extendable retention pricing** option, or up to 2,557 days (about 7 years) if you choose the **Seven-year retention pricing** option.

If you choose to log activity events to one or more existing event data stores, choose the event data stores from the list. The event data stores can only include activity events. The event type in the console must be **Events from integrations**. In the API, the `eventCategory` value must be `ActivityAuditLog`.

6. In **Resource policy**, configure the resource policy for the integration's channel. Resource policies are JSON policy documents that specify what actions a specified principal can perform on the resource and under what conditions. The accounts defined as principals in the resource policy can call the `PutAuditEvents` API to deliver events to your channel.

 Note

If you do not create a resource policy for the channel, only the channel owner can call the `PutAuditEvents` API on the channel.

- a. (Optional) Enter a unique external ID to provide an extra layer of protection. The external ID is a unique string such as an account ID or a randomly generated string, to prevent against confused deputy.

 Note

If the resource policy includes an external ID, all calls to the `PutAuditEvents` API must include the external ID. However, if the policy does not define an external ID, you can still call the `PutAuditEvents` API and specify an `externalId` parameter.

- b. Choose **Add AWS account** to specify each AWS account ID to add as a principal in the resource policy for the channel.
7. (Optional) In the **Tags** area, you can add up to 50 tag key and value pairs to help you identify, sort, and control access to your event data store and channel. For more information about how

to use IAM policies to authorize access to an event data store based on tags, see [Examples: Denying access to create or delete event data stores based on tags](#). For more information about how you can use tags in AWS, see [Tagging your AWS resources](#) in the *AWS General Reference*.

8. When you are ready to create the new integration, choose **Add integration**. There is no review page. CloudTrail creates the integration, but to integrate your custom events, you must specify the channel ARN in a [PutAuditEvents](#) request.
9. Call the `PutAuditEvents` API to ingest your activity events into CloudTrail. You can add up to 100 activity events (or up to 1 MB) per `PutAuditEvents` request. You'll need the channel ARN that you created in preceding steps, the payload of events that you want CloudTrail to add, and the external ID (if specified for your resource policy). Be sure that there is no sensitive or personally-identifying information in event payload before ingesting it into CloudTrail. Events that you ingest into CloudTrail must follow the [CloudTrail Lake integrations event schema](#).

 Tip

Use [AWS CloudShell](#) to be sure you are running the most current AWS APIs.

The following examples show how to use the **put-audit-events** CLI command. The **--audit-events** and **--channel-arn** parameters are required. You need the ARN of the channel that you created in the preceding steps, which you can copy from the integration details page. The value of **--audit-events** is a JSON array of event objects. **--audit-events** includes a required ID from the event, the required payload of the event as the value of `EventData`, and an [optional checksum](#) to help validate the integrity of the event after ingestion into CloudTrail.

```
aws cloudtrail-data put-audit-events \  
--region region \  
--channel-arn $ChannelArn \  
--audit-events \  
id="event_ID",eventData='"{event_payload}"' \  
id="event_ID",eventData='"{event_payload}"',eventDataChecksum="optional_checksum"
```

The following is an example command with two event examples.

```
aws cloudtrail-data put-audit-events \  
--region us-east-1 \  
--audit-events
```

```
--channel-arn arn:aws:cloudtrail:us-east-1:01234567890:channel/EXAMPLE8-0558-4f7e-
a06a-43969EXAMPLE \
--audit-events \
id="EXAMPLE3-0f1f-4a85-9664-d50a3EXAMPLE",eventData="{\"eventVersion\":\0.01\",
\"eventSource\":\\"custom1.domain.com\", ...
}\"" \
id="EXAMPLE7-a999-486d-b241-b33a1EXAMPLE",eventData="{\"eventVersion\":\0.02\",
\"eventSource\":\\"custom2.domain.com\", ...
}\"",eventDataChecksum="EXAMPLE6e7dd61f3ead...93a691d8EXAMPLE"
```

The following example command adds the `--cli-input-json` parameter to specify a JSON file (`custom-events.json`) of event payload.

```
aws cloudtrail-data put-audit-events \
--channel-arn $channelArn \
--cli-input-json file://custom-events.json \
--region us-east-1
```

The following are the sample contents of the example JSON file, `custom-events.json`.

```
{
  "auditEvents": [
    {
      "eventData": "{\"version\": \"eventData.version\", \"UID\": \"UID\",
        \"userIdentity\": {\"type\": \"CustomUserIdentity\", \"principalId\":
        \"principalId\",
        \"details\": {\"key\": \"value\"}}, \"eventTime\": \"2021-10-27T12:13:14Z\",
        \"eventName\": \"eventName\",
        \"userAgent\": \"userAgent\", \"eventSource\": \"eventSource\",
        \"requestParameters\": {\"key\": \"value\"}, \"responseElements\": {\"key\":
        \"value\"},
        \"additionalEventData\": {\"key\": \"value\"},
        \"sourceIPAddress\": \"source_IP_address\", \"recipientAccountId\":
        \"recipient_account_ID\"}",
      "id": "1"
    }
  ]
}
```

(Optional) Calculate a checksum value

The checksum that you specify as the value of `EventDataChecksum` in a `PutAuditEvents` request helps you verify that CloudTrail receives the event that matches with the checksum; it helps verify the integrity of events. The checksum value is a base64-SHA256 algorithm that you calculate by running the following command.

```
printf %s '{"eventData": {"\version\":"eventData.version\","\UID\":"UID\","\userIdentity\":{"type\":"CustomUserIdentity\","\principalId\":"principalId\","\details\":{"key\":"value\"}},\eventTime\":"2021-10-27T12:13:14Z\","\eventName\":"eventName\","\userAgent\":"userAgent\","\eventSource\":"eventSource\","\requestParameters\":{"key\":"value\"},"responseElements\":{"key\":"value\"},"additionalEventData\":{"key\":"value\"},"sourceIPAddress\":"source_IP_address\","\recipientAccountId\":"recipient_account_ID\"},"id": "1"}' \
| openssl dgst -binary -sha256 | base64
```

The command returns the checksum. The following is an example.

```
EXAMPLEHjkI8iehvCUCWTIAbNYk0gO/t0YNw+7rrQE=
```

The checksum value becomes the value of `EventDataChecksum` in your `PutAuditEvents` request. If the checksum doesn't match with the one for the provided event, CloudTrail rejects the event with an `InvalidChecksum` error.

Create, update, and manage CloudTrail Lake integrations with the AWS CLI

This section describes the commands you can use to create, update and manage your CloudTrail Lake integrations using the AWS CLI.

When using the AWS CLI, remember that your commands run in the AWS Region configured for your profile. If you want to run the commands in a different Region, either change the default Region for your profile, or use the `--region` parameter with the command.

Available commands for CloudTrail Lake integrations

Commands for creating, updating, and managing integrations in CloudTrail Lake include:

- [create-event-data-store](#) to create an event data store for events outside of AWS.
- [delete-channel](#) to delete a channel used for an integration.
- [delete-resource-policy](#) to delete the resource policy attached to a channel for a CloudTrail Lake integration.
- [get-channel](#) to return information about a CloudTrail channel.
- [get-resource-policy](#) to retrieve the JSON text of the resource-based policy document attached to the CloudTrail channel.
- [list-channels](#) to list the channels in the current account, and their source names.
- [put-audit-events](#) to ingest your application events into CloudTrail Lake. A required parameter, `auditEvents`, accepts the JSON records (also called payload) of events that you want CloudTrail to ingest. You can add up to 100 of these events (or up to 1 MB) per `PutAuditEvents` request.
- [put-resource-policy](#) to attach a resource-based permission policy to a CloudTrail channel that is used for an integration with an event source outside of AWS. For more information about resource-based policies, see [AWS CloudTrail resource-based policy examples](#).
- [update-channel](#) to update a channel specified by a required channel ARN or UUID.

For a list of available commands for CloudTrail Lake event data stores, see [Available commands for event data stores](#).

For a list of available commands for CloudTrail Lake queries, see [Available commands for CloudTrail Lake queries](#).

For a list of available commands for CloudTrail Lake dashboards, see [Available commands for dashboards](#).

Create an integration to log events from outside AWS with the AWS CLI

This section describes how you can use the AWS CLI to create a CloudTrail Lake integration to log events from outside of AWS.

In the AWS CLI, you create an integration in four commands (three if you already have an event data store that meets the criteria). Event data stores that you use as the destinations for

an integration must be for a single Region and single account; they cannot be multi-region, they cannot log events for organizations in AWS Organizations, and they can only include activity events. The event type in the console must be **Events from integrations**. In the API, the `eventCategory` value must be `ActivityAuditLog`. For more information about integrations, see [Create an integration with an event source outside of AWS](#).

1. Run [create-event-data-store](#) to create an event data store, if you do not already have one or more event data stores that you can use for the integration.

The following example AWS CLI command creates an event data store that logs events from outside AWS. For activity events, the `eventCategory` field selector value is `ActivityAuditLog`. The event data store has a retention period of 90 days set. By default, the event data store collects events from all Regions, but because this is collecting non-AWS events, set it to a single Region by adding the `--no-multi-region-enabled` option. Termination protection is enabled by default, and the event data store does not collect events for accounts in an organization.

```
aws cloudtrail create-event-data-store \
--name my-event-data-store \
--no-multi-region-enabled \
--retention-period 90 \
--advanced-event-selectors '[
  {
    "Name": "Select all external events",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["ActivityAuditLog"] }
    ]
  }
]'
```

The following is an example response.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
EXAMPLEf852-4e8f-8bd1-bcf6cEXAMPLE",
  "Name": "my-event-data-store",
  "AdvancedEventSelectors": [
    {
      "Name": "Select all external events",
      "FieldSelectors": [
```

```
        {
            "Field": "eventCategory",
            "Equals": [
                "ActivityAuditLog"
            ]
        }
    ]
},
"MultiRegionEnabled": true,
"OrganizationEnabled": false,
"BillingMode": "EXTENDABLE_RETENTION_PRICING",
"RetentionPeriod": 90,
"TerminationProtectionEnabled": true,
"CreatedTimestamp": "2023-10-27T10:55:55.384000-04:00",
"UpdatedTimestamp": "2023-10-27T10:57:05.549000-04:00"
}
```

You'll need the event data store ID (the suffix of the ARN, or EXAMPLEf852-4e8f-8bd1-bcf6cEXAMPLE in the preceding response example) to go on to the next step and create your channel.

2. Run the [create-channel](#) command to create a channel that allows a partner or source application to send events to an event data store in CloudTrail.

A channel has the following components:

Source

CloudTrail uses this information to determine the partners that are sending event data to CloudTrail on your behalf. A source is required, and can be either Custom for all valid non-AWS events, or the name of a partner event source. A maximum of one channel is allowed per source.

For information about the Source values for available partners, see [Additional information about integration partners](#).

Ingestion status

The channel status shows when the last events were received from a channel source.

Destinations

The destinations are the CloudTrail Lake event data stores that are receiving events from the channel. You can change destination event data stores for a channel.

To stop receiving events from a source, delete the channel.

You need the ID of at least one destination event data store to run this command. The valid type of destination is `EVENT_DATA_STORE`. You can send ingested events to more than one event data store. The following example command creates a channel that sends events to two event data stores, represented by their IDs in the `Location` attribute of the `--destinations` parameter. The `--destinations`, `--name`, and `--source` parameters are required. To ingest events from a CloudTrail partner, specify the name of the partner as the value of `--source`. To ingest events from your own applications outside AWS, specify `Custom` as the value of `--source`.

```
aws cloudtrail create-channel \
  --region us-east-1 \
  --destinations '[{"Type": "EVENT_DATA_STORE", "Location":
"EXAMPLEf852-4e8f-8bd1-bcf6cEXAMPLE"}, {"Type": "EVENT_DATA_STORE", "Location":
"EXAMPLEg922-5n2l-3vz1- apqw8EXAMPLE"}]'
```

```
  --name my-partner-channel \
  --source $partnerSourceName \
```

In the response to your **create-channel** command, copy the ARN of the new channel. You need the ARN to run the `put-resource-policy` and `put-audit-events` commands in the next steps.

3. Run the **put-resource-policy** command to attach a resource policy to the channel. Resource policies are JSON policy documents that specify what actions a specified principal can perform on the resource and under what conditions. The accounts defined as principals in the channel's resource policy can call the `PutAuditEvents` API to deliver events.

Note

If you do not create a resource policy for the channel, only the channel owner can call the `PutAuditEvents` API on the channel.

The information required for the policy is determined by the integration type.

- For a direction integration, CloudTrail requires the policy to contain the partner's AWS account IDs, and requires you to enter the unique external ID provided by the partner. CloudTrail automatically adds the partner's AWS account IDs to the resource policy when you create an integration using the CloudTrail console. Refer to the [partner's documentation](#) to learn how to get the AWS account numbers required for the policy.
- For a solution integration, you must specify at least one AWS account ID as principal, and can optionally enter an external ID to prevent against confused deputy.

The following are requirements for the resource policy:

- The resource ARN defined in the policy must match the channel ARN the policy is attached to.
- The policy contains only one action: `cloudtrail-data:PutAuditEvents`
- The policy contains at least one statement. The policy can have a maximum of 20 statements.
- Each statement contains at least one principal. A statement can have a maximum of 50 principals.

```
aws cloudtrail put-resource-policy \  
  --resource-arn "channelARN" \  
  --policy "{  
    "Version": "2012-10-17",  
    "Statement":  
    [  
      {  
        "Sid": "ChannelPolicy",  
        "Effect": "Allow",  
        "Principal":  
        {  
          "AWS":  
          [  
            "arn:aws:iam::111122223333:root",  
            "arn:aws:iam::444455556666:root",  
            "arn:aws:iam::123456789012:root"  
          ]  
        }  
      ]  
    }
```



```

    },
    "Action": "cloudtrail-data:PutAuditEvents",
    "Resource": "arn:aws:cloudtrail:us-east-1:777788889999:channel/
EXAMPLE-80b5-40a7-ae65-6e099392355b",
    "Condition":
    {
        "StringEquals":
        {
            "cloudtrail:ExternalId": "UniqueExternalIDFromPartner"
        }
    }
}
]
}"

```

For more information about resource policies, see [AWS CloudTrail resource-based policy examples](#).

4. Run the [PutAuditEvents](#) API to ingest your activity events into CloudTrail. You'll need the payload of events that you want CloudTrail to add. Be sure that there is no sensitive or personally-identifying information in event payload before ingesting it into CloudTrail. Note that the PutAuditEvents API uses the `cloudtrail-data` CLI endpoint, not the `cloudtrail` endpoint.

The following examples show how to use the **put-audit-events** CLI command. The **--audit-events** and **--channel-arn** parameters are required. The **--external-id** parameter is required if an external ID is defined in the resource policy. You need the ARN of the channel that you created in the preceding step. The value of **--audit-events** is a JSON array of event objects. **--audit-events** includes a required ID from the event, the required payload of the event as the value of `EventData`, and an [optional checksum](#) to help validate the integrity of the event after ingestion into CloudTrail.

```

aws cloudtrail-data put-audit-events \
--channel-arn $ChannelArn \
--external-id $UniqueExternalIDFromPartner \
--audit-events \
id="event_ID",eventData='"{event_payload}"' \
id="event_ID",eventData='"{event_payload}"',eventDataChecksum="optional_checksum"

```

The following is an example command with two event examples.

```
aws cloudtrail-data put-audit-events \
--channel-arn arn:aws:cloudtrail:us-east-1:123456789012:channel/EXAMPLE8-0558-4f7e-
a06a-43969EXAMPLE \
--external-id UniqueExternalIDFromPartner \
--audit-events \
id="EXAMPLE3-0f1f-4a85-9664-d50a3EXAMPLE",eventData="{\"eventVersion\": \"0.01\",
\"eventSource\": \"custom1.domain.com\", ...
}\"" \
id="EXAMPLE7-a999-486d-b241-b33a1EXAMPLE",eventData="{\"eventVersion\": \"0.02\",
\"eventSource\": \"custom2.domain.com\", ...
}\"",eventDataChecksum="EXAMPLE6e7dd61f3ead...93a691d8EXAMPLE"
```

The following example command adds the `--cli-input-json` parameter to specify a JSON file (`custom-events.json`) of event payload.

```
aws cloudtrail-data put-audit-events --channel-arn $channelArn --external-id
$UniqueExternalIDFromPartner --cli-input-json file://custom-events.json --region
us-east-1
```

The following are the sample contents of the example JSON file, `custom-events.json`.

```
{
  "auditEvents": [
    {
      "eventData": "{\"version\": \"eventData.version\", \"UID\": \"UID\",
        \"userIdentity\": {\"type\": \"CustomUserIdentity\", \"principalId\":
        \"principalId\",
        \"details\": {\"key\": \"value\"}}, \"eventTime\": \"2021-10-27T12:13:14Z\",
        \"eventName\": \"eventName\",
        \"userAgent\": \"userAgent\", \"eventSource\": \"eventSource\",
        \"requestParameters\": {\"key\": \"value\"}, \"responseElements\": {\"key\":
        \"value\"},
        \"additionalEventData\": {\"key\": \"value\"},
        \"sourceIPAddress\": \"12.34.56.78\", \"recipientAccountId\":
        \"152089810396\"}",
      "id": "1"
    }
  ]
}
```

You can verify that the integration is working, and CloudTrail is ingesting events from the source correctly, by running the [get-channel](#) command. The output of **get-channel** shows the most recent time stamp that CloudTrail received events.

```
aws cloudtrail get-channel --channel arn:aws:cloudtrail:us-east-1:01234567890:channel/EXAMPLE8-0558-4f7e-a06a-43969EXAMPLE
```

(Optional) Calculate a checksum value

The checksum that you specify as the value of `EventDataChecksum` in a `PutAuditEvents` request helps you verify that CloudTrail receives the event that matches with the checksum; it helps verify the integrity of events. The checksum value is a base64-SHA256 algorithm that you calculate by running the following command.

```
printf %s '{"eventData": {"\version\":"eventData.version\","\UID\":"UID\","\userIdentity\":{"type\":"CustomUserIdentity\","\principalId\":"principalId\","\details\":{"key\":"value\"}},\eventTime\":"2021-10-27T12:13:14Z\","\eventName\":"eventName\","\userAgent\":"userAgent\","\eventSource\":"eventSource\","\requestParameters\":{"key\":"value\"},"responseElements\":{"key\":"value\"},"additionalEventData\":{"key\":"value\"},"sourceIPAddress\":"source_IP_address\","\recipientAccountId\":"recipient_account_ID\"},"id": "1"}' \
| openssl dgst -binary -sha256 | base64
```

The command returns the checksum. The following is an example.

```
EXAMPLEDHjkI8iehvCUCWTIAbNYk0g0/t0YNw+7rrQE=
```

The checksum value becomes the value of `EventDataChecksum` in your `PutAuditEvents` request. If the checksum doesn't match with the one for the provided event, CloudTrail rejects the event with an `InvalidChecksum` error.

Update a channel with the AWS CLI

This section describes how you can use the AWS CLI to update a channel for a CloudTrail Lake integration. You can run the `update-channel` command to update the name of the channel or to specify a different destination event data store. You cannot update the source of a channel.

When you run the command, the `--channel` parameter is required.

The following is an example that demonstrates how to update the channel name and destination.

```
aws cloudtrail update-channel \
--channel aws:cloudtrail:us-east-1:123456789012:channel/EXAMPLE8-0558-4f7e-
a06a-43969EXAMPLE \
--name "new-channel-name" \
--destinations '[{"Type": "EVENT_DATA_STORE", "Location": "EXAMPLEf852-4e8f-8bd1-
bcf6cEXAMPLE"}, {"Type": "EVENT_DATA_STORE", "Location": "EXAMPLEg922-5n2l-3vz1-
apqw8EXAMPLE"}]'
```

Delete a channel to delete an integration with the AWS CLI

This section describes how to run the `delete-channel` command to delete the channel for a CloudTrail Lake integration. You would delete a channel, if you wanted to stop ingesting partner or other activity events outside of AWS. The ARN or channel ID (the ARN suffix) of the channel that you want to delete is required.

The following example shows how to delete the channel.

```
aws cloudtrail delete-channel \
--channel EXAMPLE8-0558-4f7e-a06a-43969EXAMPLE
```

Additional information about integration partners

The table in this section provides the source name for each integration partner and identifies the integration type (direct or solution).

The information in the **Source name** column is required when calling the `CreateChannel` API. You specify the source name as the value for the `Source` parameter.

Partner name (console)	Source name (API)	Integration type
My custom integration	Custom	solution
Cloud Storage Security	CloudStorageSecurityConsole	solution
Clumio	Clumio	direct

Partner name (console)	Source name (API)	Integration type
CrowdStrike	CrowdStrike	solution
CyberArk	CyberArk	solution
GitHub	GitHub	solution
Kong Inc	KongGatewayEnterprise	solution
LaunchDarkly	LaunchDarkly	direct
Netskope	NetskopeCloudExchange	solution
Nordcloud, an IBM Company	IBMMulticloud	direct
MontyCloud	MontyCloud	direct
Okta	OktaSystemLogEvents	solution
One Identity	OneLogin	solution
Shoreline.io	Shoreline	solution
Snyk.io	Snyk	direct
Wiz	WizAuditLogs	solution

View partner documentation

You can learn more about a partner's integration with CloudTrail Lake by viewing their documentation.

To view partner documentation

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Integrations**.

3. From the **Integrations** page, choose **Available sources**, then choose **Learn more** for the partner whose documentation you want to view.

CloudTrail Lake integrations event schema

The following table describes the required and optional schema elements that match those in CloudTrail event records. The contents of eventData are provided by your events; other fields are provided by CloudTrail after ingestion.

CloudTrail event record contents are described in more detail in [CloudTrail record contents for management, data, and network activity events](#).

- [Fields that are provided by CloudTrail after ingestion](#)
- [Fields that are provided by your events](#)

The following fields are provided by CloudTrail after ingestion:

Field name	Input type	Requirement	Description
eventVersion	string	Required	The event version.
eventCategory	string	Required	The event category. For non-AWS events, the value is ActivityAuditLog .
eventType	string	Required	The event type. For non-AWS events, the valid value is ActivityLog .
eventId	string	Required	A unique ID for an event.
eventTime	string	Required	Event timestamp , in yyyy-MM-D

Field name	Input type	Requirement	Description
			DTHH:mm:ss format, in Universal Coordinated Time (UTC).
awsRegion	string	Required	The AWS Region where the PutAuditEvents call was made.
recipientAccountId	string	Required	Represents the account ID that received this event. CloudTrail populates this field by calculating it from event payload.
addendum	-	Optional	Shows information about why event processing was delayed. If information was missing from an existing event, the addendum block includes the missing information and a reason for why it was missing.
reason	string	Optional	The reason that the event or some of its contents were missing.

Field name	Input type	Requirement	Description
updatedFields	string	Optional	The event record fields that are updated by the addendum. This is only provided if the reason is UPDATED_DATA .
originalUID	string	Optional	The original event UID from the source. This is only provided if the reason is UPDATED_DATA .
originalEventID	string	Optional	The original event ID. This is only provided if the reason is UPDATED_DATA .
metadata	-	Required	Information about the channel that the event used.
ingestionTime	string	Required	The timestamp when the event was processed, in yyyy-MM-DDTHH:mm:ss format, in Universal Coordinated Time (UTC).
channelARN	string	Required	The ARN of the channel that the event used.

The following fields are provided by customer events:

Field name	Input type	Requirement	Description
eventData	-	Required	The audit data sent to CloudTrail in a PutAuditEvents call.
• version	string	Required	The version of the event from its source. Length constraints: Maximum length of 256.
• userIdentity	-	Required	Information about the user who made a request.
• • type	string	Required	The type of user identity. Length constraints: Maximum length of 128.
• • principalId	string	Required	A unique identifier for the actor of the event. Length constraints: Maximum length of 1024.
• • details	JSON object	Optional	Additional information about the identity.

Field name	Input type	Requirement	Description
• userAgent	string	Optional	The agent through which the request was made. Length constraints: Maximum length of 1024.
• eventSource	string	Required	This is the partner event source, or the custom application about which events are logged. Length constraints: Maximum length of 1024.
• eventName	string	Required	The requested action, one of the actions in the API for the source service or application. Length constraints: Maximum length of 1024.
• eventTime	string	Required	Event timestamp , in yyyy-MM-DDTHH:mm:ss format, in Universal Coordinated Time (UTC).

Field name	Input type	Requirement	Description
UID	string	Required	The UID value that identifies the request. The service or application that is called generates this value. Length constraints: Maximum length of 1024.
requestParameters	JSON object	Optional	The parameters, if any, that were sent with the request. This field has a maximum size of 100 kB, and content exceeding the limit is rejected.
responseElements	JSON object	Optional	The response element for actions that make changes (create, update, or delete actions). This field has a maximum size of 100 kB, and content exceeding the limit is rejected.
errorCode	string	Optional	A string representing an error for the event. Length constraints: Maximum length of 256.

Field name	Input type	Requirement	Description
errorMessage	string	Optional	The description of the error. Length constraints: Maximum length of 256.
sourceIPAddress	string	Optional	The IP address from which the request was made. Both IPv4 and IPv6 addresses are accepted.
recipientAccountId	string	Required	Represents the account ID that received this event. The account ID must be the same as the AWS account ID that owns the channel.
additionalEventData	JSON object	Optional	Additional data about the event that was not part of the request or response. This field has a maximum size of 28 kB, and content exceeding that limit is rejected.

The following example shows the hierarchy of schema elements that match those in CloudTrail event records.

```
{
```

```
"eventVersion": String,
"eventCategory": String,
"eventType": String,
"eventID": String,
"eventTime": String,
"awsRegion": String,
"recipientAccountId": String,
"addendum": {
  "reason": String,
  "updatedFields": String,
  "originalUID": String,
  "originalEventID": String
},
"metadata" : {
  "ingestionTime": String,
  "channelARN": String
},
"eventData": {
  "version": String,
  "userIdentity": {
    "type": String,
    "principalId": String,
    "details": {
      JSON
    }
  },
  "userAgent": String,
  "eventSource": String,
  "eventName": String,
  "eventTime": String,
  "UID": String,
  "requestParameters": {
    JSON
  },
  "responseElements": {
    JSON
  },
  "errorCode": String,
  "errorMessage": String,
  "sourceIPAddress": String,
  "recipientAccountId": String,
  "additionalEventData": {
    JSON
  }
}
```

```
}  
}
```

CloudTrail Lake dashboards

You can use CloudTrail Lake dashboards to see event trends for the event data stores in your account. CloudTrail Lake offers the following types of dashboards:

- **Managed dashboards** – You can view a managed dashboard to see event trends for an event data store that collects management events, data events, or Insights events. These dashboards are automatically available to you and are managed by CloudTrail Lake. CloudTrail offers 14 managed dashboards to choose from. You can manually refresh managed dashboards. You cannot modify, add, or remove the widgets for these dashboards, however, you can save a managed dashboard as a custom dashboard if you want to modify the widgets or set a refresh schedule.
- **Custom dashboards** – Custom dashboards allow you to query events in any event data store type. You can add up to 10 widgets to a custom dashboard. You can manually refresh a custom dashboard, or you can set a refresh schedule.
- **Highlights dashboards** – Enable the Highlights dashboard to view an at-a-glance overview of the AWS activity collected by the event data stores in your account. The Highlights dashboard is managed by CloudTrail and includes widgets that are relevant to your account. The widgets shown on the Highlights dashboard are unique to each account. These widgets could surface detected abnormal activity or anomalies. For example, your Highlights dashboard could include the **Total cross-account access widget**, which shows if there is an increase in abnormal cross-account activity. CloudTrail updates the Highlights dashboard every 6 hours. The dashboard shows the last 24 hours of data from the last update.

Each dashboard consists of one or more widgets and each widget provides a graphical representation of the results of a SQL query. To view the query for a widget, choose **View and edit query** to open up the query editor.

When a dashboard is refreshed, CloudTrail Lake runs queries to populate the dashboard's widgets. Because running queries incurs costs, CloudTrail asks you to acknowledge the costs associated with running queries. For more information about CloudTrail pricing, see [CloudTrail Pricing](#).

Topics

- [Prerequisites](#)

- [Limitations](#)
- [Region support](#)
- [Required permissions](#)
- [View a managed dashboard with the CloudTrail console](#)
- [Enable the Highlights dashboard with the CloudTrail console](#)
- [Disable the Highlights dashboard with the CloudTrail console](#)
- [Create a custom dashboard with the CloudTrail console](#)
- [Set a refresh schedule for a custom dashboard with the CloudTrail console](#)
- [Disable the refresh schedule for a custom dashboard with the CloudTrail console](#)
- [Change termination protection with the CloudTrail console](#)
- [Delete a custom dashboard with the CloudTrail console](#)
- [Create, update, and manage dashboards with the AWS CLI](#)

Prerequisites

The following prerequisites apply to CloudTrail Lake dashboards:

- To view and use Lake dashboards, you must create at least one CloudTrail Lake event data store. You can create event data stores using the console, AWS CLI, or SDKs. For information about creating an event data store using the console, see [Create an event data store for CloudTrail events with the console](#). For information about creating an event data store using the AWS CLI, see [Create an event data store with the AWS CLI](#).
- You must have adequate permissions to view, create, update, and refresh dashboards. For more information, see [Required permissions](#).

Limitations

The following limitations apply to CloudTrail Lake dashboards:

- You can only enable the Highlights dashboard for event data stores that exist in your account.
- You can only view managed dashboards for event data stores that exist in your account.
- For custom dashboards, you can only add sample widgets or create new widgets that query event data stores that exist in your account.

- Delegated administrators for a AWS Organizations organization cannot view or manage dashboards that are owned by the management account.

Region support

The CloudTrail Lake dashboards are supported in all AWS Regions where CloudTrail Lake is supported.

The **Activity summary** widget on the **Highlights** dashboard is supported in the following Regions:

- Asia Pacific (Tokyo) Region (ap-northeast-1)
- US East (N. Virginia) (us-east-1)
- US West (Oregon) Region (us-west-1)

All other widgets are supported in all AWS Regions where CloudTrail Lake is supported.

For information about CloudTrail Lake supported Regions, see [CloudTrail Lake supported Regions](#).

Required permissions

This section describes the required permissions for CloudTrail Lake dashboards and discusses two types of IAM policies:

- Identity-based policies which allow you to perform actions to create, manage, and delete dashboards.
- Resource-based policies that allow CloudTrail to run queries on your event data store when the dashboard is refreshed and perform scheduled refreshes of custom dashboards and the Highlights dashboard on your behalf. When you create dashboards using the CloudTrail console, you are given the option to attach resource-based policies. You can also run the AWS CLI [put-resource-policy](#) command to add a resource-based policy to your event data stores or dashboards.

Identity-based policy requirements

Identity-based policies are JSON permissions policy documents that you can attach to an identity, such as an IAM user, group of users, or role. These policies control what actions users and roles can

perform, on which resources, and under what conditions. To learn how to create an identity-based policy, see [Define custom IAM permissions with customer managed policies](#) in the *IAM User Guide*.

To view and manage CloudTrail Lake dashboards, you need one of the following policies:

- The [CloudTrailFullAccess](#) managed policy.
- The [AdministratorAccess](#) managed policy.
- A custom policy that includes one or more of the specific permissions described in the sections which follow.

Topics

- [Required permissions for creating dashboards](#)
- [Required permissions for updating dashboards](#)
- [Required permissions for refreshing dashboards](#)

Required permissions for creating dashboards

The following sample policy provides the required minimum permissions for creating dashboards. Replace *partition*, *region*, *account-id*, and *eds-id* with the values for your configuration.

- StartQuery permission is required only if the request contains widgets. Provide StartQuery permissions for all event data stores included in a widget query.
- StartDashboardRefresh permission is required only if the dashboard has a refresh schedule.
- For the Highlights dashboard, the caller must have StartQuery permission on all the event data stores in the account.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "Statement1",
      "Effect": "Allow",
      "Action": [
        "cloudtrail:CreateDashboard",
```

```

        "cloudtrail:StartDashboardRefresh",
        "cloudtrail:StartQuery"
    ],
    "Resource": [
        "arn:aws:cloudtrail:us-east-1:111111111111:dashboard/*",
        "arn:aws:cloudtrail:us-east-1:111111111111:eventdatastore/eds-id"
    ]
}

```

Required permissions for updating dashboards

The following sample policy provides the required minimum permissions for updating dashboards. Replace *partition*, *region*, *account-id*, and *eds-id* with the values for your configuration.

- StartQuery permission is required only if the request contains widgets. Provide StartQuery permissions for all event data stores included in a widget query.
- StartDashboardRefresh permission is required only if the dashboard has a refresh schedule.
- For the Highlights dashboard, the caller must have StartQuery permission on all the event data stores in the account.

JSON

```

{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "Statement1",
      "Effect": "Allow",
      "Action": [
        "cloudtrail:UpdateDashboard",
        "cloudtrail:StartDashboardRefresh",
        "cloudtrail:StartQuery"
      ],
      "Resource": [
        "arn:aws:cloudtrail:us-east-1:111111111111:dashboard/*",
        "arn:aws:cloudtrail:us-east-1:111111111111:eventdatastore/eds-id"
      ]
    }
  ]
}

```

```
    }
  ]
}
```

Required permissions for refreshing dashboards

The following sample policy provides the required minimum permissions for refreshing dashboards. Replace *partition*, *region*, *account-id*, *dashboard-name*, and *eds-id* with the values for your configuration.

- For custom dashboards and the Highlights dashboards, the caller must have `cloudtrail:StartDashboardRefresh` permissions.
- For managed dashboards, the caller must have `cloudtrail:StartDashboardRefresh` permission and `cloudtrail:StartQuery` permissions for the event data store involved in the refresh.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "Statement1",
      "Effect": "Allow",
      "Action": [
        "cloudtrail:StartDashboardRefresh",
        "cloudtrail:StartQuery"
      ],
      "Resource": [
        "arn:aws:cloudtrail:us-east-1:111111111111:dashboard/dashboard-  
name",
        "arn:aws:cloudtrail:us-east-1:111111111111:eventdatastore/eds-id"
      ]
    }
  ]
}
```

Resource-based policies for dashboards and event data stores

Resource-based policies are JSON policy documents that you attach to a resource. Examples of resource-based policies are IAM role trust policies and Amazon S3 bucket policies. For the resource where the policy is attached, the policy defines what actions a specified principal can perform on that resource and under what conditions. You must specify a principal in a resource-based policy.

To run queries on a dashboard during a manual or scheduled refresh, you must attach a resource-based policy to every event data store that is associated with a widget on the dashboard. This allows CloudTrail Lake to run the queries on your behalf. When you create a custom dashboard, or enable the **Highlights** dashboard using the CloudTrail console, CloudTrail gives you the option to choose which event data stores you want to apply permissions to. For more information about the resource-based policy, see [Example: Allow CloudTrail to run queries to refresh a dashboard](#).

To set a refresh schedule for a dashboard, you must attach a resource-based policy to the dashboard to allow CloudTrail Lake to refresh the dashboard on your behalf. When you set a refresh schedule for a custom dashboard, or enable the **Highlights** dashboard using the CloudTrail console, CloudTrail gives you the option to attach a resource-based policy to your dashboard. For an example policy, see [Resource-based policy example for a dashboard](#).

You can attach a resource-based policy using the CloudTrail console, the [AWS CLI](#), or the [PutResourcePolicy](#) API operation.

KMS key permissions to decrypt data in an event data store

If an event data store being queried is encrypted with a KMS key, ensure the KMS key policy allows CloudTrail to decrypt the data in the event data store. The following example policy statement allows the CloudTrail service principal to decrypt the event data store.

```
{
  "Sid": "AllowCloudTrailDecryptAccess",
  "Effect": "Allow",
  "Principal": {
    "Service": "cloudtrail.amazonaws.com"
  },
  "Action": "kms:Decrypt",
  "Resource": "*"
}
```

View a managed dashboard with the CloudTrail console

CloudTrail Lake provides managed dashboards that show event trends for event data stores that collect management events, data events, and Insights events. These dashboards are managed by CloudTrail Lake. You cannot modify, add, or remove the widgets for these dashboards, however, you can save a managed dashboard as a custom dashboard if you want to modify the widgets or set a refresh schedule.

Note

You can only view managed dashboards for event data stores that exist in your account.

To view a managed dashboard

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the left navigation pane, under **Lake**, choose **Dashboard**.
3. Choose the **Managed and custom dashboards** tab.
4. From **Managed dashboards**, choose the dashboard you want to view. For more information, see [Available managed dashboards](#).

Note

The dropdown shows only relevant event data stores for the selected dashboard. For example, if you choose dashboards focused on data events, like S3 data events, the dropdown will only show event data stores that are configured to collect data events.

5. Choose the event data store for the dashboard. CloudTrail will run queries on this dashboard when the dashboard is refreshed.
6. To view the query for a widget, choose **View and edit query** at the bottom of the widget.
7. Choose to filter the dashboard data by an **Absolute range** or **Relative range**. Choose **Absolute range** to select a specific date and time range. Choose **Relative range** to select a predefined time range or a custom range. By default, the dashboard displays event data for the past 24 hours.

Note

CloudTrail Lake queries incur costs based upon the amount of data scanned. To help control costs, you can filter on a narrower time range. For more information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

8. Choose the refresh icon to populate the graphics for the dashboard's widgets. Each widget indicates the status of the refresh.

Save a managed dashboard as a custom dashboard

You cannot modify a managed dashboard, but you can save a copy as a custom dashboard. This allows you to set a refresh schedule for the dashboard and modify the widgets.

To save a managed dashboard as a custom dashboard

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the left navigation pane, under **Lake**, choose **Dashboard**.
3. Choose the **Managed and custom dashboards** tab.
4. Choose the managed dashboard that you want to create a copy of.
5. Choose **Save as new dashboard**.
6. Provide a name to identify the dashboard.
7. (Optional) In the **Tags** section, you can add up to 50 tag key pairs to help you identify and sort your dashboards. For more information about how you can use tags in AWS, see [Tagging AWS resources](#) in the *Tagging AWS Resources User Guide*.
8. For **Permissions**, choose the event data stores that you want to apply permissions to. Because CloudTrail runs queries to populate data for the widgets on a dashboard, CloudTrail requires permissions to run queries on the event data store associated with the dashboard's widgets. For each event data store selected in this step, CloudTrail attaches a resource-based policy to the event data store that allows CloudTrail to run queries. You can deselect an event data store if you do not want to allow permissions.
9. Choose **Create dashboard**.

After you create the custom dashboard, you can [add widgets](#), [remove widgets](#), and [set a refresh schedule](#) for the dashboard.

Available managed dashboards

The section provides information about the available managed dashboards and provides information about the widgets featured on each dashboard.

Available managed dashboards:

- [Security monitoring dashboard](#)
- [IAM activity dashboard](#)
- [User activity dashboard](#)
- [Enriched events dashboard](#)
- [Error analysis dashboard](#)
- [EC2 activity dashboard](#)
- [Organizations activity dashboard](#)
- [Resource changes dashboard](#)
- [Data events overview dashboard](#)
- [Lambda data events dashboard](#)
- [DynamoDB data events dashboard](#)
- [S3 data events dashboard](#)
- [Insights events dashboard](#)
- [Management events dashboard](#)
- [Overview dashboard](#)

Security monitoring dashboard

This dashboard provides a centralized view of critical security focused widgets, such as top access denied events, failed console login attempts and their associated IP addresses, root user console login attempts, destructive actions, cross-account access and other critical security focused widgets. It provides quick incident detection and response to enhance your overall security posture.

This dashboard is available for event data stores that collect management events and includes the following widgets:

Top access denied events

Tracks the most frequently occurring access-denied events, grouped by API.

Failed ConsoleLogin attempts

Tracks the trend of failed console login attempts over time, with breakdowns on MFA vs Non-MFA authenticated callers.

Failed ConsoleLogin attempts by IP address

Tracks the IP addresses associated with failed console login attempts and displays the top offending IP addresses by failed login count.

Root user ConsoleLogin attempts

Tracks the frequency of console login attempts made by root users over time.

Destructive actions

Tracks the frequency of delete operations over time.

Top cross-account access

Tracks the top cross-account activity by caller account ID and action.

Users who disabled MFA

Tracks the most recent users who disabled MFA.

Recent EC2 SecurityGroup and NetworkAcl changes

Tracks the most recent EC2 SecurityGroup and NetworkAcl changes.

Recent EC2 SecurityGroup changes that allow public access

Tracks the most recent EC2 security groups that have rules allowing public (0.0.0.0/0) access.

Potential CloudTrail disabling actions

Tracks recent actions that risk disrupting CloudTrail logging.

IAM activity dashboard

This dashboard provides visibility into commonly used IAM APIs, API errors, changes to IAM entities, and top caller IP addresses, enabling the identification of unintended IAM actions and compliance issues.

This dashboard is available for event data stores that collect management events and includes the following widgets:

Top IAM APIs

Tracks the most frequently used IAM APIs.

Top IAM callers

Tracks the most frequent IAM API callers.

IAM success vs failure trend

Tracks the trend of success and failed IAM API calls over time.

Top IAM API errors

Tracks the most frequent errors in calling IAM APIs.

Top AccessDenied IAM APIs

Tracks the most frequent IAM API calls that failed with access denied errors.

Top IP addresses of IAM calls

Tracks the top source IP addresses from which IAM API calls were made.

Recent IAM policy changes

Tracks the most recent changes to IAM policies, categorized by the specific IAM API operation that facilitated the change, the IAM resource (user, role, or group) associated with the policy change, and the policy name or ARN that was used.

Recent IAM user changes

Tracks the most recent changes to IAM users, categorized by the specific IAM API that facilitates user management, the IAM user affected by the change, and the event time.

Top assumed IAM roles

Tracks the most frequently assumed IAM roles.

User activity dashboard

This dashboard provides visibility into user activity trends, insights into key areas such as top active users, user traffic patterns, users with access denied errors, recent user operations, users who performed destructive activities and IAM policy changes, as well as privileged user actions. It helps detect unintended user actions and security risks.

This dashboard is available for event data stores that collect management events and includes the following widgets:

User activity trends by user ARN

Tracks the user activity trend over time by user ARN.

User activity trends by API

Tracks the user activity trend over time by API.

Most recent user activity

Tracks the most recent user actions.

Top users with errors

Tracks the users that have the highest number of errors.

Top users with AccessDenied errors

Tracks the users that have the highest number of AccessDenied errors.

Top users making destructive actions

Tracks the users that are making the highest number of destructive actions.

Top users changing IAM policies

Tracks the IAM users who are frequently performing changes to IAM policies.

Top actions performed by potential IAM privileged users

Tracks the most frequent actions by highly privileged IAM users, such as administrators.

Enriched events dashboard

This enriched events dashboard provides insights on trends across tagged resources, principal activities, and AWS global condition keys. These insights help you analyze the most frequent resource and principal tag distributions as well as frequently used global condition keys in role sessions, requests, and principals in request context.

This dashboard is available for event data stores that collect management events and includes the following widgets:

Enriched events over time

Tracks the count of enriched events over time.

Most frequent resource tag key value pairs

Displays the most frequently used resource tag key-value pairs across enriched events.

Most frequent resource tag key value pairs with associated resources and users

Displays the most frequently used resource tag key-value pairs, showing which resources use these tags and which users are associated with them.

Most frequent principal tag key value pairs

Displays the most frequently used principal tag key-value pairs across enriched events.

Most frequent access denied actions grouped by principal tag key value pairs

Displays the most frequent access-denied actions grouped by principal tag key-value pairs across enriched events.

Most frequent principal properties in IAM global condition keys

Displays the most frequently used IAM global condition keys for principal properties, showing their key-value pairs and counts across all events.

Most frequent request properties in IAM global condition keys

Displays the most frequently used IAM global condition keys for request properties, showing their key-value pairs and counts across all events.

Most frequent role session properties in IAM global condition keys

Displays the most frequently used IAM global condition keys for role session properties, showing their key-value pairs and counts across all events.

Error analysis dashboard

This dashboard provides comprehensive insights into error trends across services, APIs, users, error codes, and throttled APIs. The visibility enables prompt identification and troubleshooting of potential availability issues for optimal system performance.

This dashboard is available for event data stores that collect management events and includes the following widgets:

Error count by service

Tracks the error count of activities by service.

Error count by API

Tracks the error count of activities by API.

Top errors by error code

Tracks the most frequent errors by error code.

Top errors by error message

Tracks the most frequent errors by error message.

Top AccessDenied errors by API

Tracks the APIs with the most frequently reported access denied errors.

Top throttled errors by API

Tracks the APIs with the most frequently reported throttled errors.

Top users with errors

Tracks the users with the most frequently reported errors.

EC2 activity dashboard

This dashboard provides comprehensive visibility into EC2 management activities, like API trends, access errors, top instance launchers, security changes, and network modifications. The insights help identify security risks and operational issues.

This dashboard is available for event data stores that collect management events and includes the following widgets:

EC2 instance management activity overview

Monitors an overview of EC2 instance management activities over a specified time, highlighting key operations such as launches, stops, and terminations.

EC2 API success vs failure trends

Tracks the trend of success and failed EC2 API calls over time.

Top EC2 errors

Tracks the most frequent error codes that occur during EC2 API calls.

Top EC2 AccessDenied events

Tracks EC2 APIs with the most access denied errors.

Top users launching EC2 instances

Tracks the users who are the most active in launching new EC2 instances.

Recent EC2 SecurityGroup and NetworkInterface changes

Tracks the most recent EC2 security group and network interface changes.

Recent VPC management and route table changes

Tracks the most recent VPC management activities and route table changes.

Recent EC2 actions by root user

Tracks the most recent EC2 actions performed by root users with highly privileged permissions.

Organizations activity dashboard

Designed for organization event data stores, this dashboard offers visibility into organizational activities and trends, including insights on active members, account management, access patterns, policy changes, and top services and APIs utilized.

This dashboard is available for organization event data stores and includes the following widgets:

Activity trend in the organization

Tracks the overall activity trend across the entire AWS Organizations organization over time, providing visibility into periods of high or low activity levels.

Member account management summary

Tracks the distribution of member account management activities within the organization, categorized based on the counts of each activity type.

Most used services across organization

Tracks the AWS services that have been utilized the most across the organization.

Most active accounts by service

Tracks the most active accounts utilizing an AWS service across the organization.

Most used APIs across organization

Highlights the AWS APIs that have been invoked most frequently across the entire organization.

Most active member accounts

Tracks the member accounts within the organization that have exhibited the highest count of activity.

Access denied errors trend across the organization

Tracks the pattern of access denied errors occurring within the organization over time.

Accounts with most access denied errors

Tracks the accounts within the organization that have experienced the highest number of access denied errors.

Recent service control policy changes

Tracks the most recent changes made to service control policies (SCPs) within the organization.

Resource changes dashboard

This dashboard provides a comprehensive view of resource management activities, monitoring trends in provisioning, deletion, and modifications across services. It highlights critical changes, including those made through AWS CloudFormation, manually, and to policies like S3 bucket and KMS access.

This dashboard is available for event data stores that collect management events and includes the following widgets:

Resource creation and deletion trends

Tracks the creation and deletion of resources within the account over time.

Top users performing resource creation

Tracks the users who are most actively creating new resources.

Top APIs used for resource creation

Tracks the APIs that are most frequently used for creating new resources within the account.

Top APIs used for resource deletion

Tracks the APIs that are most frequently used for deleting resources within the account.

Most recent resources created outside CloudFormation

Tracks new resources created outside of CloudFormation governance, emphasizing changes not managed through CloudFormation templates.

Most recent resource changes made using console

Tracks the most recent changes made to resources via the AWS Management Console.

Most recent S3 bucket access changes

Tracks the most recent S3 bucket access changes.

Most recent KMS key access changes

Tracks the most recent KMS key policy changes.

Data events overview dashboard

This dashboard offers a centralized view of data events in the event data store, including overall activity trends, top services, APIs, regions, throttled data plane APIs, and leading data plane users. This dashboard helps you monitor data plane API activity for auditing and troubleshooting.

This dashboard is available for event data stores that collect data events and includes the following widgets:

Overall data events trend

Tracks the trend in overall data events occurring within the account over time.

Top services generating data events

Tracks the services generating the highest volume of data activity within the account.

Top APIs generating data events

Tracks the APIs generating the highest volume of data activity within the account.

Top regions generating data events

Tracks the regions generating the highest volume of data activity within the account.

Top throttled data plane APIs

Tracks the data plane APIs that are experiencing frequent throttling within the account.

Top users of data plane APIs

Tracks the top users who utilize data plane APIs most across the account.

Lambda data events dashboard

This dashboard provides visibility into Lambda data plane API activity, including top users, frequently invoked functions, common API errors. These insights help you audit Lambda usage, detect abnormalities, and mitigate operational or security risks.

This dashboard is available for event data stores that collect Lambda data events and includes the following widgets:

Lambda data plane API activity

Tracks the trend in Lambda data plane API activity within the account over time.

Lambda invocations success vs failure trend

Tracks the trend of success and failed Lambda invocations over time.

Top users of Lambda invocations

Tracks the users who make the most invocations of Lambda functions across the account.

Top invoked Lambda functions

Tracks the Lambda functions that are invoked most frequently within the account.

Top 10 Lambda Invoke API errors

Tracks the top 10 errors encountered during Lambda Invoke API calls.

Most throttled users of Lambda invocations

Tracks the users who experience the highest number of throttling events for Lambda invocations.

DynamoDB data events dashboard

This dashboard provides visibility into DynamoDB data plane API activity, including usage trends, top APIs, and throttling patterns involving users and tables. These insights help you audit DynamoDB usage, detect abnormalities, and mitigate operational or security risks.

This dashboard is available for event data stores that collect DynamoDB data events and includes the following widgets:

DynamoDB account data activity

Tracks the trend in DynamoDB data events occurring within the account over time.

DynamoDB data plane APIs success vs failure trend

Tracks the trend of success and failed DynamoDB data plane API calls over time.

Top 10 DynamoDB data plane APIs

Lists the top 10 DynamoDB data plane API calls.

Top users of DynamoDB data plane APIs

Tracks the users who make the highest number of calls to DynamoDB data plane APIs within the account.

Top 10 DynamoDB data plane API errors

Tracks the top 10 errors in calling DynamoDB data plane APIs.

Most throttled users of DynamoDB data plane APIs

Tracks the users with most frequent throttling when calling DynamoDB data plane APIs.

Top throttled DynamoDB data plane APIs

Tracks the DynamoDB data plane APIs that are experiencing frequent throttling within the account.

Top throttled DynamoDB tables

Tracks the DynamoDB tables experiencing the highest rates of throttling within the account.

S3 data events dashboard

This dashboard provides visibility into S3 data plane API activity, including usage trends, most accessed S3 objects, top S3 users, and top S3 actions. These insights help you audit S3 usage, detect abnormalities, and mitigate operational or security risks.

This dashboard is available for event data stores that collect Amazon S3 data events and includes the following widgets:

S3 account activity

Tracks S3 account activity.

Most accessed objects

Lists the most accessed S3 objects.

S3 top users

Tracks the top S3 users.

Top S3 actions

Tracks the top S3 actions.

Insights events dashboard

This dashboard provides visibility into the overall breakdown of Insights events by type, as well as the top users and services generating these event types. Additionally, it shows the daily count of Insights events and a 30-day historical view of Insights metrics.

Note

- After you enable CloudTrail Insights for the first time on the source event data store, it can take up to 7 days for CloudTrail to deliver the first Insights event, if unusual activity is detected.
- The **Insights Events** dashboard only displays information about the Insights events collected by the selected event data store, which is determined by the configuration of the source event data store. For example, if you configure the source event data store to enable Insights events on `ApiCallRateInsight` but not `ApiErrorRateInsight`, you won't see information about Insights events on `ApiErrorRateInsight`.

This dashboard is available for event data stores that collect Insights events and includes the following widgets:

Insight types

Tracks events by Insights type.

Insights by date

Tracks Insights events by date.

API call rate Insights by event source

Tracks API call rate Insights by event source. To view data for this widget, your Insights event data store must be configured to collect Insights on API call rate.

API error rate Insights by event source

Tracks API error rate Insights by event source. To view this widget, your Insights event data store must be configured to collect Insights on API error rate.

Insights by top users

Lists the top users with requests resulting in Insights events.

Insights events

Lists recent Insights events.

Management events dashboard

This dashboard highlights insights on access denied events, destructive actions, console sign-in events, top errors by user, TLS version usage, and outdated TLS calls by user.

This dashboard is available for event data stores that collect management events and includes the following widgets:

Top access denied events

Tracks the top events that resulted in access denied errors.

Top errors by user

Tracks the top errors by user.

Console sign-in events

Shows console sign-in events.

Destructive actions

Tracks actions that resulted in destructive actions.

TLS version

Shows the TLS versions.

Outdated TLS calls by user

Tracks calls using outdated TLS versions by user.

Overview dashboard

This dashboard highlights insights on access denied events, destructive actions, console sign-in events, top errors by user, TLS version usage, and outdated TLS calls by user.

This dashboard is available for event data stores that collect management events and includes the following widgets:

Account activity

Tracks read and write activity for your account.

Top errors

Lists the most frequent errors.

Most active regions

Shows the most active AWS Regions.

Top services

Shows the top services.

Most throttled events

Lists the most throttled events.

Top users

Lists the top users.

Enable the Highlights dashboard with the CloudTrail console

Enable the Highlights dashboard to view an at-a-glance overview of the AWS activity collected by the event data stores in your account. The Highlights dashboard is managed by CloudTrail

and includes widgets that are relevant to your account. The widgets shown on the Highlights dashboard are unique to each account. These widgets could surface detected abnormal activity or anomalies. For example, your Highlights dashboard could include the **Total cross-account access widget**, which shows if there is an increase in abnormal cross-account activity.

CloudTrail updates the Highlights dashboard every 6 hours. The dashboard shows the last 24 hours of data from the last update.

Note

You can only enable the Highlights dashboard for event data stores that exist in your account.

You cannot set a refresh schedule for the Highlights dashboard, or add or remove widgets.

To enable the Highlights dashboard

Use the following procedure to enable the Highlights dashboard.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the left navigation pane, under **Lake**, choose **Dashboard**.
3. Choose the **Highlights** tab.
4. Because running queries incurs CloudTrail charges, CloudTrail asks you to review the cost information before enabling the **Highlights** dashboard. For information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Choose **Agree and enable Highlights** to enable the Highlights dashboard.

5. For **Permissions**, choose the event data stores that you want to apply permissions to. CloudTrail requires permissions to run queries on your event data stores and refresh the dashboard on your behalf. To provide permissions, CloudTrail attaches a default resource-based policy to each event data store selected in this step to allow CloudTrail to run queries on the event data store. CloudTrail attaches a resource-based policy to the dashboard to allow CloudTrail to refresh the dashboard every 6 hours.

You can modify the resource-based policy for an event data store from its details page. You can modify the resource-based policy for a dashboard by selecting **Edit policy** from the **Actions** menu for the dashboard.

6. Choose **Confirm**.

When you enable the **Highlights** dashboard, termination protection is automatically enabled. Termination protection protects a dashboard from being accidentally deleted. You'll need to disable termination protection, if you want to disable the dashboard.

Disable the Highlights dashboard with the CloudTrail console

This section describes how to disable the Highlights dashboard. Because termination protection is automatically enabled for the Highlights dashboard, you'll need to first disable termination protection and then disable the Highlights dashboard.

To disable the Highlights dashboard

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the left navigation pane, under **Lake**, choose **Dashboard**.
3. Choose the **Highlights** tab.
4. From **Actions**, choose **Change termination protection**.
5. Choose **Disabled**.
6. Choose **Save**.
7. From **Actions**, choose **Disable Highlights**.

Create a custom dashboard with the CloudTrail console

You can create custom dashboards and add up to 10 widgets to each custom dashboard. You can choose to add sample widgets or create new widgets from SQL queries.

After you're done adding widgets, you can manually refresh the dashboard or set a refresh schedule.

To create a custom dashboard

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the left navigation pane, under **Lake**, choose **Dashboard**.

3. Choose the **Managed and custom dashboards** tab.
4. Choose **Build my own dashboard**.
5. Provide a dashboard name to identify your dashboard.
6. For **Permissions**, choose the event data stores that you want to apply permissions to. Because CloudTrail runs queries to populate data for the widgets on a dashboard, CloudTrail requires permissions to run queries on the event data stores associated with the dashboard's widgets. For each event data store selected in this step, CloudTrail attaches a resource-based policy to the event data store that allows CloudTrail to run queries on the event data store for this dashboard.
7. (Optional) In the **Tags** section, you can add up to 50 tag key pairs to help you identify and sort your dashboards. For more information about how you can use tags in AWS, see [Tagging AWS resources](#) in the *Tagging AWS Resources User Guide*.
8. Choose **Create dashboard**.

Next, you can add widgets and [set a refresh schedule](#).

Topics

- [Add a sample widget with the CloudTrail console](#)
- [Create a new widget from a SQL query with the CloudTrail console](#)
- [Remove a widget from a dashboard with the CloudTrail console](#)

Add a sample widget with the CloudTrail console

This section describes how to add a sample widget to your dashboard. You can add a maximum of 10 widgets to a custom dashboard.

Note

Sample widgets are limited to a single event data store that exists in your account. To query across multiple event data stores in your account, [create a new widget](#).

To add a sample widget to a dashboard

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.

2. In the left navigation pane, under **Lake**, choose **Dashboard**.
3. Choose the **Managed and custom dashboards** tab.
4. In **Custom dashboards**, choose the dashboard that you want to add a widget to.
5. From **Actions**, choose **Edit dashboard**.
6. From **Actions**, choose **Add sample widget**.
7. Choose the event data store you'd like to run the query on. You can only choose event data stores that exist in your account.
8. Choose the sample widget you'd like to add. By default, all sample widgets are shown. You can filter by a widget type (for example, IAM widgets).
9. Choose **View query** to view the query for the selected widget.
10. Choose **Add to dashboard** to add the widget to the dashboard.
11. Choose **Save** to save the dashboard.

Create a new widget from a SQL query with the CloudTrail console

This section describes how to create a new widget by writing or pasting a SQL query and choosing a chart type. You can add a maximum of 10 widgets to a custom dashboard.

To create a new widget from a SQL query

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the left navigation pane, under **Lake**, choose **Dashboard**.
3. Choose the **Managed and custom dashboards** tab.
4. In **Custom dashboards**, choose the dashboard that you want to create a widget for.
5. From **Actions**, choose **Edit dashboard**.
6. From **Actions**, choose **Create new widget**.
7. Choose the event data store you'd like to run the query on. You can query across multiple event data stores as long as the event data stores exist in your account.
8. Write or copy the SQL query.

You can also provide a natural language prompt in English and choose **Generate query** to produce a SQL query from your prompt. For more information, see [Create CloudTrail Lake queries from natural language prompts](#).

9. Choose **Run** to run the query and preview the query results.

 Note

When you run queries, you incur charges based on the amount of optimized and compressed data scanned. To help control costs, we recommend that you constrain queries by adding starting and ending eventTime timestamps to queries.

10. Choose the **Visualizer** tab to select the chart type for the widget. You can choose from these chart types: table, bar chart, line chart, and pie chart.
11. Choose **Add to dashboard** to add the widget to the dashboard.
12. Choose **Save** to save the dashboard.

Remove a widget from a dashboard with the CloudTrail console

This section describes to remove a widget from a custom dashboard.

To remove a widget from a dashboard

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the left navigation pane, under **Lake**, choose **Dashboard**.
3. Choose the **Managed and custom dashboards** tab.
4. In **Custom dashboards**, choose the dashboard for which you want to remove a widget.
5. From **Actions**, choose **Edit dashboard**.
6. On the widget you want to remove, choose the remove icon
()
and then choose **Remove**.
7. Choose **Save** to save the dashboard.

Set a refresh schedule for a custom dashboard with the CloudTrail console

This section describes how to set a dashboard refresh schedule. You can set a refresh schedule to allow CloudTrail Lake to refresh a dashboard every 1 hour, 6 hours, 12 hours, or 24 hours (1 day).

When you set a refresh schedule using the CloudTrail console, CloudTrail attaches a resource-based policy to the dashboard that allows CloudTrail to refresh the dashboard on your behalf.

To set a refresh schedule


1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the left navigation pane, under **Tools**, choose **Dashboard**.
3. Choose the **Managed and custom dashboards** tab.
4. In **Custom dashboards**, choose the dashboard that you want to set a refresh schedule for.
5. Choose the refresh frequency from the dropdown list.
6. To create a refresh schedule, CloudTrail attaches a resource-based policy to the dashboard to allow CloudTrail to refresh the dashboard on your behalf. Expand **Dashboard resource policy** to view the resource-based policy that CloudTrail will attach to the dashboard.
7. Because running queries incurs costs, CloudTrail asks you to confirm that you want CloudTrail to run queries for the scheduled frequency. Choose **Confirm** to set a refresh schedule.

Disable the refresh schedule for a custom dashboard with the CloudTrail console

You can disable the refresh schedule if you no longer want CloudTrail to automatically refresh your dashboard, and instead wish to manually refresh your dashboard.

To disable a refresh schedule

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the left navigation pane, under **Tools**, choose **Dashboard**.
3. Choose the **Managed and custom dashboards** tab.
4. In **Custom dashboards**, choose the dashboard that you want to disable a refresh schedule for.
5. Choose **Disable refresh schedule** from the dropdown list.



Change termination protection with the CloudTrail console

Termination protection prevents a dashboard from accidental deletion. If you want to delete a custom dashboard, or disable the Highlights dashboard, you must disable termination protection.

To turn off termination protection

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, under **Lake**, choose **Dashboard**.
3. Choose the dashboard you want to disable termination protection for.
4. From **Actions**, choose **Change termination protection**.
5. Choose **Disabled**.
6. Choose **Save**.

To turn on termination protection

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, under **Lake**, choose **Dashboard**.
3. Choose the dashboard you want to enable termination protection for.
4. From **Actions**, choose **Change termination protection**.
5. To turn on termination protection, choose **Enabled**.
6. Choose **Save**.

Delete a custom dashboard with the CloudTrail console

This section describes how to delete a dashboard using the CloudTrail.

Note

You can't delete an event data store if [termination protection](#) is enabled.

To delete a dashboard

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, under **Lake**, choose **Dashboard**.
3. Choose the **Managed and custom dashboards** tab.
4. Choose the custom dashboard you want to delete.
5. From **Actions**, choose **Delete**.
6. Choose **Delete** to confirm you want to delete the dashboard.

Create, update, and manage dashboards with the AWS CLI

This section describes the AWS CLI commands you can use to create, update, and manage your CloudTrail Lake dashboards.

When using the AWS CLI, remember that your commands run in the AWS Region configured for your profile. If you want to run the commands in a different Region, either change the default Region for your profile, or use the `--region` parameter with the command.

Available commands for dashboards

Commands for creating and updating dashboards in CloudTrail Lake include:

- `create-dashboard` to create a custom dashboard or enable the Highlights dashboard.
- `update-dashboard` to update a custom dashboard or the Highlights dashboard.
- `delete-dashboard` to delete a custom dashboard or the Highlights dashboard.
- `get-dashboard` returns information about the specified dashboard.
- `list-dashboards` lists all dashboards for your AWS account, or for the specified filter.

- `start-dashboard-refresh` starts a refresh of the dashboard.
- `get-resource-policy` gets the resource-based policy attached to the dashboard.
- `put-resource-policy` attaches a resource-based policy to a dashboard to allow CloudTrail to refresh the dashboard asynchronously on your behalf. You also attach a resource-based policy to an event data store to allow CloudTrail to run queries on the event data store to populate the data for dashboard widgets.
- `delete-resource-policy` removes the resource-based policy attached to a dashboard.
- `add-tags` adds tags to identify the dashboard.
- `remove-tags` removes tags from a dashboard.
- `list-tags` lists tags for a dashboard.

For a list of available commands for CloudTrail Lake event data stores, see [Available commands for event data stores](#).

For a list of available commands for CloudTrail Lake queries, see [Available commands for CloudTrail Lake queries](#).

For a list of available commands for CloudTrail Lake integrations, see [Available commands for CloudTrail Lake integrations](#).

Topics:

- [Create a dashboard with the AWS CLI](#)
- [Manage dashboards with the AWS CLI](#)
- [Delete a dashboard with the AWS CLI](#)

Create a dashboard with the AWS CLI

This section describes how to use the `create-dashboard` command to create a custom dashboard or the Highlights dashboard.

When using the AWS CLI, remember that your commands run in the AWS Region configured for your profile. If you want to run the commands in a different Region, either change the default Region for your profile, or use the `--region` parameter with the command.

CloudTrail runs queries to populate the dashboard's widgets during a manual or scheduled refresh. CloudTrail must be granted permissions to run the `StartQuery` operation on each event data

store associated with a dashboard widget. To provide permissions, run the `put-resource-policy` command to attach a resource-based policy to each event data store, or edit the event data store's policy on the CloudTrail console. For an example policy, see [Example: Allow CloudTrail to run queries to refresh a dashboard](#).

To set a refresh schedule, CloudTrail must be granted permissions to run the `StartDashboardRefresh` operation to refresh the dashboard on your behalf. To provide permissions, run the `put-resource-policy` operation to attach a resource-based policy to the dashboard, or edit the dashboard's policy on the CloudTrail console. For an example policy, see [Resource-based policy example for a dashboard](#).

Examples:

- [Create a custom dashboard with the AWS CLI](#)
- [Enable the Highlights dashboard with the AWS CLI](#)
- [View properties for widgets](#)

Create a custom dashboard with the AWS CLI

The following procedure shows how to create a custom dashboard, attach the required resource-based policies to event data stores and the dashboard, and update the dashboard to set and enable a refresh schedule.

1. Run the `create-dashboard` to create a dashboard.

When you create a custom dashboard, you can pass in an array with up to 10 widgets. A widget provides a graphical representation of the results for a query. Each widget consists of `ViewProperties`, `QueryStatement`, and `QueryParameters`.

- `ViewProperties` – Specifies the properties for the view type. For more information, see [View properties for widgets](#).
- `QueryStatement` – The query CloudTrail runs when the dashboard is refreshed. You can query across multiple event data stores as long as the event data stores exist in your account.
- `QueryParameters` – The following `QueryParameters` values are supported for custom dashboards: `$Period$`, `$StartTime$`, and `$EndTime$`. To use `QueryParameters` place a `?` in the `QueryStatement` where you want to substitute the parameter. CloudTrail will fill in the parameters when the query is run.

The following example creates a dashboard with four widgets, one of each view type.

Note

In this example, `?` is surrounded with single quotes because it is used with `eventTime`. Depending on the operating system you are running on, you may need to surround single quotes with escape quotes. For more information, see [Using quotation marks and literals with strings in the AWS CLI](#).

```
aws cloudtrail create-dashboard --name AccountActivityDashboard \
--widgets '[
  {
    "ViewProperties": {
      "Height": "2",
      "Width": "4",
      "Title": "TopErrors",
      "View": "Table"
    },
    "QueryStatement": "SELECT errorCode, COUNT(*) AS eventCount FROM eds WHERE
eventTime > '?' AND eventTime < '?' AND (errorCode is not null) GROUP BY errorCode
ORDER BY eventCount DESC LIMIT 100",
    "QueryParameters": ["$StartTime$", "$EndTime$"]
  },
  {
    "ViewProperties": {
      "Height": "2",
      "Width": "4",
      "Title": "MostActiveRegions",
      "View": "PieChart",
      "LabelColumn": "awsRegion",
      "ValueColumn": "eventCount",
      "FilterColumn": "awsRegion"
    },
    "QueryStatement": "SELECT awsRegion, COUNT(*) AS eventCount FROM eds where
eventTime > '?' and eventTime < '?' GROUP BY awsRegion ORDER BY eventCount LIMIT
100",
    "QueryParameters": ["$StartTime$", "$EndTime$"]
  },
  {
    "ViewProperties": {
      "Height": "2",
      "Width": "4",
      "Title": "MostActiveRegions",
      "View": "PieChart",
      "LabelColumn": "awsRegion",
      "ValueColumn": "eventCount",
      "FilterColumn": "awsRegion"
    },
    "QueryStatement": "SELECT awsRegion, COUNT(*) AS eventCount FROM eds where
eventTime > '?' and eventTime < '?' GROUP BY awsRegion ORDER BY eventCount LIMIT
100",
    "QueryParameters": ["$StartTime$", "$EndTime$"]
  },
  {
    "ViewProperties": {
      "Height": "2",
      "Width": "4",
      "Title": "MostActiveRegions",
      "View": "PieChart",
      "LabelColumn": "awsRegion",
      "ValueColumn": "eventCount",
      "FilterColumn": "awsRegion"
    },
    "QueryStatement": "SELECT awsRegion, COUNT(*) AS eventCount FROM eds where
eventTime > '?' and eventTime < '?' GROUP BY awsRegion ORDER BY eventCount LIMIT
100",
    "QueryParameters": ["$StartTime$", "$EndTime$"]
  }
]
```

```

    "ViewProperties": {
      "Height": "2",
      "Width": "4",
      "Title": "AccountActivity",
      "View": "LineChart",
      "YAxisColumn": "eventCount",
      "XAxisColumn": "eventDate",
      "FilterColumn": "readOnly"
    },
    "QueryStatement": "SELECT DATE_TRUNC('?', eventTime) AS eventDate,
IF(readOnly, 'read', 'write') AS readOnly, COUNT(*) as eventCount FROM eds WHERE
eventTime > '?' AND eventTime < '?' GROUP BY DATE_TRUNC('?', eventTime), readOnly
ORDER BY DATE_TRUNC('?', eventTime), readOnly",
    "QueryParameters": ["$Period$", "$StartTime$", "$EndTime$", "$Period$",
"$Period$"]
  },
  {
    "ViewProperties": {
      "Height": "2",
      "Width": "4",
      "Title": "TopServices",
      "View": "BarChart",
      "LabelColumn": "service",
      "ValueColumn": "eventCount",
      "FilterColumn": "service",
      "Orientation": "Horizontal"
    },
    "QueryStatement": "SELECT REPLACE(eventSource, '.amazonaws.com') AS service,
COUNT(*) AS eventCount FROM eds WHERE eventTime > '?' AND eventTime < '?' GROUP BY
eventSource ORDER BY eventCount DESC LIMIT 100",
    "QueryParameters": ["$StartTime$", "$EndTime$"]
  }
]'
```

2. Create a separate file with the resource policy needed for each event data store that is included in a widget's QueryStatement. Name the file *policy.json*, with the following example policy statement:

Replace *123456789012* with your account ID, *arn:aws:cloudtrail:us-east-1:123456789012:dashboard/exampleDashboard* with the ARN of the dashboard.

For more information about resource-based policies for dashboards, see [Example: Allow CloudTrail to run queries to refresh a dashboard](#).

3. Run the `put-resource-policy` command to attach the policy. You can also update an event data store's resource-based policy on the CloudTrail console.

The following example attaches a resource-based policy to an event data store.

```
aws cloudtrail put-resource-policy \  
--resource-arn eds-arn \  
--resource-policy file://policy.json
```

4. Run the `put-resource-policy` command to attach a resource-based policy to the dashboard. For an example policy, see [Resource-based policy example for a dashboard](#).

The following example attaches a resource-based policy to a dashboard. Replace *account-id* with your account ID and *dashboard-arn* with the ARN of the dashboard.

```
aws cloudtrail put-resource-policy \  
--resource-arn dashboard-arn \  
--resource-policy '{"Version": "2012-10-17", "Statement":  
  [{"Sid": "DashboardPolicy", "Effect": "Allow", "Principal": { "Service":  
    "cloudtrail.amazonaws.com" }, "Action": "cloudtrail:StartDashboardRefresh",  
    "Condition": { "StringEquals": { "AWS:SourceArn": "dashboard-arn",  
      "AWS:SourceAccount": "account-id"}}}]}'
```

5. Run the `update-dashboard` command to set and enable a refresh schedule by configuring the `--refresh-schedule` parameter.

The `--refresh-schedule` consists of the following optional parameters:

- Frequency – The Unit and Value for the schedule.

For custom dashboards, the unit can be HOURS or DAYS.

For custom dashboards, the following values are valid when the unit is HOURS: 1, 6, 12, 24

For custom dashboards, the only valid value when the unit is DAYS is 1.

- Status – Specifies whether the refresh schedule is enabled. Set the value to ENABLED to enable the refresh schedule, or to DISABLED to turn off the refresh schedule.
- TimeOfDay – The time of day in UTC to run the schedule; for hourly only refer to minutes; default is 00:00.

The following example sets a refresh schedule for every six hours and enables the schedule.

```
aws cloudtrail update-dashboard --dashboard-id AccountActivityDashboard \
--refresh-schedule '{"Frequency": {"Unit": "HOURS", "Value": 6}, "Status":
"ENABLED"}'
```

Enable the Highlights dashboard with the AWS CLI

The following procedure shows how to create the Highlights dashboard, attach the required resource-based policies to your event data stores and the dashboard, and update the dashboard to set and enable the refresh schedule.

1. Run the `create-dashboard` command to create the Highlights dashboard. To create this dashboard, the `--name` must be `AWSCloudTrail-Highlights`.

```
aws cloudtrail create-dashboard --name AWSCloudTrail-Highlights
```

2. For each event data store in your account, run the `put-resource-policy` command to attach a resource-based policy to the event data store. You can also update an event data store's resource-based policy on the CloudTrail console. For an example policy, see [Example: Allow CloudTrail to run queries to refresh a dashboard](#).

The following example attaches a resource-based policy to an event data store. Replace *account-id* with your account ID, *eds-arn* with the ARN of the event data store, and *dashboard-arn* with the ARN of the dashboard.

```
aws cloudtrail put-resource-policy \
--resource-arn eds-arn \
--resource-policy '{"Version": "2012-10-17", "Statement":
[{"Sid": "EDSPolicy", "Effect": "Allow", "Principal": { "Service":
"cloudtrail.amazonaws.com" }, "Action": "cloudtrail:StartQuery", "Condition":
{ "StringEquals": { "AWS:SourceArn": "dashboard-arn", "AWS:SourceAccount":
"account-id"}}} ]}'
```

3. Run the `put-resource-policy` command to attach a resource-based policy to the dashboard. For an example policy, see [Resource-based policy example for a dashboard](#).

The following example attaches a resource-based policy to a dashboard. Replace *account-id* with your account ID and *dashboard-arn* with the ARN of the dashboard.

```
aws cloudtrail put-resource-policy \  
--resource-arn dashboard-arn \  
--resource-policy '{"Version": "2012-10-17", "Statement": [  
  [{"Sid": "DashboardPolicy", "Effect": "Allow", "Principal": { "Service":  
    "cloudtrail.amazonaws.com" }, "Action": "cloudtrail:StartDashboardRefresh",  
    "Condition": { "StringEquals": { "AWS:SourceArn": "dashboard-arn",  
      "AWS:SourceAccount": "account-id"}}}]]}'
```

4. Run the `update-dashboard` command to set and enable a refresh schedule by configuring the `--refresh-schedule` parameter. For the Highlights dashboard, the only valid UNIT is HOURS and the only valid Value is 6.

```
aws cloudtrail update-dashboard --dashboard-id AWSCloudTrail-Highlights \  
--refresh-schedule '{"Frequency": {"Unit": "HOURS", "Value": 6}, "Status":  
  "ENABLED"}'
```

View properties for widgets

This section describes the configurable view properties for the 4 view types: table, line chart, pie chart, and bar chart.

View types:

- [Table](#)
- [Line chart](#)
- [Pie chart](#)
- [Bar chart](#)

Table

The following example shows a widget configured as a table.

```
{  
  "ViewProperties": {  
    "Height": "2",  
    "Width": "4",
```

```
    "Title": "TopErrors",
    "View": "Table"
  },
  "QueryStatement": "SELECT errorCode, COUNT(*) AS eventCount FROM eds WHERE
eventTime > '?' AND eventTime < '?' AND (errorCode is not null) GROUP BY errorCode
ORDER BY eventCount DESC LIMIT 100",
  "QueryParameters": ["$StartTime$", "$EndTime$"]
}
```

The following table describes the configurable view properties for a table.

Parameter	Required	Value
Height	Yes	The height of the table in inches.
Width	Yes	The width of the table in inches.
Title	Yes	The title of the table.
View	Yes	The widget view type. For a table, the value is Table.

Line chart

The following example shows a widget configured as a line chart.

```
{
  "ViewProperties": {
    "Height": "2",
    "Width": "4",
    "Title": "AccountActivity",
    "View": "LineChart",
    "YAxisColumn": "eventCount",
    "XAxisColumn": "eventDate",
    "FilterColumn": "readOnly"
  },
  "QueryStatement": "SELECT DATE_TRUNC('?', eventTime) AS eventDate, IF(readOnly,
'read', 'write') AS readOnly, COUNT(*) as eventCount FROM eds WHERE eventTime >
```

```
'?' AND eventTime < '?' GROUP BY DATE_TRUNC('?', eventTime), readOnly ORDER BY
DATE_TRUNC('?', eventTime), readOnly",
  "QueryParameters": ["$Period$", "$StartTime$", "$EndTime$", "$Period$", "$Period$"]
}
```

The following table describes the configurable view properties for a line chart.

Parameter	Required	Value
Height	Yes	The height of the line chart in inches.
Width	Yes	The width of the line chart in inches.
Title	Yes	The title of the line chart.
View	Yes	The widget view type. For a line chart, the value is <code>LineChart</code> .
YAxisColumn	Yes	The field from the query results that you want to use for the Y axis column. For example, <code>eventCount</code> .
XAxisColumn	Yes	The field from the query results that you want to use for the X axis column. For example, <code>eventDate</code> .
FilterColumn	No	The field from the query results that you want to filter on. For example, <code>readOnly</code> .

Pie chart

The following example shows a widget configured as a pie chart.

```
{
  "ViewProperties": {
    "Height": "2",
    "Width": "4",
    "Title": "MostActiveRegions",
    "View": "PieChart",
    "LabelColumn": "awsRegion",
    "ValueColumn": "eventCount",
    "FilterColumn": "awsRegion"
  },
  "QueryStatement": "SELECT awsRegion, COUNT(*) AS eventCount FROM eds where eventTime > '?' and eventTime < '?' GROUP BY awsRegion ORDER BY eventCount LIMIT 100",
  "QueryParameters": ["$StartTime$", "$EndTime$"]
}
```

The following table describes configurable view properties for a pie chart.

Parameter	Required	Value
Height	Yes	The height of the pie chart in inches.
Width	Yes	The width of the pie chart in inches.
Title	Yes	The title of the pie chart.
View	Yes	The widget view type. For a pie chart, the value is <code>PieChart</code> .
LabelColumn	Yes	The label for segments in the pie chart. For example, <code>awsRegion</code> .
ValueColumn	Yes	The value for the segments in the pie chart. For example, <code>ValueColumn</code> .

Parameter	Required	Value
FilterColumn	No	The field from the query results that you want to filter on. For example, awsRegion .

Bar chart

The following example shows a widget configured as a bar chart.

```
{
  "ViewProperties": {
    "Height": "2",
    "Width": "4",
    "Title": "TopServices",
    "View": "BarChart",
    "LabelColumn": "service",
    "ValueColumn": "eventCount",
    "FilterColumn": "service",
    "Orientation": "Horizontal"
  },
  "QueryStatement": "SELECT REPLACE(eventSource, '.amazonaws.com') AS service,
COUNT(*) AS eventCount FROM eds WHERE eventTime > '?' AND eventTime < '?' GROUP BY
eventSource ORDER BY eventCount DESC LIMIT 100",
  "QueryParameters": ["$StartTime$", "$EndTime$"]
}
```

The following table describes the configurable view properties for a bar chart.

Parameter	Required	Value
Height	Yes	The height of the bar chart in inches.
Width	Yes	The width of the bar chart in inches.
Title	Yes	The title of the bar chart.

Parameter	Required	Value
View	Yes	The widget view type. For a bar chart, the value is <code>BarChart</code> .
LabelColumn	Yes	The label for bars in the bar chart. For example, <code>service</code> .
ValueColumn	Yes	The value for the bars in the bar chart. For example, <code>eventCount</code> .
FilterColumn	No	The field from the query results that you want to filter on. For example, <code>service</code> .
Orientation	No	The orientation of the bar chart, either <code>Horizontal</code> or <code>Vertical</code> .

Manage dashboards with the AWS CLI

This section describes several other commands that you can run to manage your dashboards, including getting a dashboard, listing your dashboards, refreshing a dashboard, and updating a dashboard.

When using the AWS CLI, remember that your commands run in the AWS Region configured for your profile. If you want to run the commands in a different Region, either change the default Region for your profile, or use the `--region` parameter with the command.

Examples:

- [Get a dashboard with the AWS CLI](#)
- [List dashboards with the AWS CLI](#)
- [Attach a resource-based policy to an event data store or dashboard with the AWS CLI](#)
- [Manually refresh a dashboard with the AWS CLI](#)
- [Update a dashboard with the AWS CLI](#)

Get a dashboard with the AWS CLI

Run the `get-dashboard` command to return a dashboard. Specify the `--dashboard-id` by providing the dashboard ARN, or the dashboard name.

```
aws cloudtrail get-dashboard --dashboard-id arn:aws:cloudtrail:us-east-1:123456789012:dashboard/exampleDash
```

List dashboards with the AWS CLI

Run the `list-dashboards` command to list the dashboards for your account.

- Include the `--type` parameter, to view only the CUSTOM or MANAGED dashboards.
- Include the `--max-results` parameter to limit the number of results. Valid values are 1-100.
- Include the `--name-prefix` to return dashboards matching the specified prefix.

The following example lists all dashboards.

```
aws cloudtrail list-dashboards
```

This example lists only the CUSTOM dashboards.

```
aws cloudtrail list-dashboards --type CUSTOM
```

The next example lists only the MANAGED dashboards.

```
aws cloudtrail list-dashboards --type MANAGED
```

The final example lists the dashboards matching the specified prefix.

```
aws cloudtrail list-dashboards --name-prefix ExamplePrefix
```

Attach a resource-based policy to an event data store or dashboard with the AWS CLI

Run the `put-resource-policy` command to apply a resource-based policy to an event data store or dashboard.

Attach a resource-based policy to an event data store

To run queries on a dashboard during a manual or scheduled refresh, you need to attach a resource-based policy to every event data store that is associated with a widget on the dashboard. This allows CloudTrail Lake to run the queries on your behalf. For more information about the resource-based policy, see [Example: Allow CloudTrail to run queries to refresh a dashboard](#).

The following example attaches a resource-based policy to an event data store. Replace *account-id* with your account ID, *eds-arn* with the ARN of the event data store for which CloudTrail will run queries, and *dashboard-arn* with the ARN of the dashboard.

```
aws cloudtrail put-resource-policy \
--resource-arn eds-arn \
--resource-policy '{"Version": "2012-10-17", "Statement": [{"Sid": "EDSPolicy",
"Effect": "Allow", "Principal": { "Service": "cloudtrail.amazonaws.com" }, "Action":
"cloudtrail:StartQuery", "Condition": { "StringEquals": { "AWS:SourceArn": "dashboard-arn", "AWS:SourceAccount": "account-id"}}} ]}'
```

Attach a resource-based policy to a dashboard

To set a refresh schedule for a dashboard, you need to attach a resource-based policy to the dashboard to allow CloudTrail Lake to refresh the dashboard on your behalf. For more information about the resource-based policy, see [Resource-based policy example for a dashboard](#).

The following example attaches a resource-based policy to a dashboard. Replace *account-id* with your account ID and *dashboard-arn* with the ARN of the dashboard.

```
aws cloudtrail put-resource-policy \
--resource-arn dashboard-arn \
--resource-policy '{"Version": "2012-10-17", "Statement":
[{"Sid": "DashboardPolicy", "Effect": "Allow", "Principal": { "Service":
"cloudtrail.amazonaws.com" }, "Action": "cloudtrail:StartDashboardRefresh",
"Condition": { "StringEquals": { "AWS:SourceArn": "dashboard-arn",
"AWS:SourceAccount": "account-id"}}} ]}'
```

Manually refresh a dashboard with the AWS CLI

Run the `start-dashboard-refresh` command to manually refresh the dashboard. Before you can run this command, you must [attach a resource-based policy](#) to every event data store associated with a dashboard widget.

The following example shows how to manually refresh a custom dashboard.

```
aws cloudtrail start-dashboard-refresh \  
--dashboard-id dashboard-id \  
--query-parameter-values '{"$StartTime$": "2024-11-05T10:45:24.00Z"}'
```

The next example shows how to manually refresh a managed dashboard. Because managed dashboards are configured by CloudTrail, the refresh request needs to include the ID of the event data store that the queries will run on.

```
aws cloudtrail start-dashboard-refresh \  
--dashboard-id dashboard-id \  
--query-parameter-values '{"$StartTime$": "2024-11-05T10:45:24.00Z", "$EventDataStoreId$": "eds-id"}'
```

Update a dashboard with the AWS CLI

Run the `update-dashboard` command to update a dashboard. You can update the dashboard to set a refresh schedule, enable or disable a refresh schedule, modify the widgets, and enable or disable termination protection.

Update the refresh schedule with the AWS CLI

The following example updates the refresh schedule for a custom dashboard named `AccountActivityDashboard`.

```
aws cloudtrail update-dashboard --dashboard-id AccountActivityDashboard \  
--refresh-schedule '{"Frequency": {"Unit": "HOURS", "Value": 6}, "Status": "ENABLED"}'
```

Disable termination protection and the refresh schedule on a custom dashboard with the AWS CLI

The following example disables termination protection for a custom dashboard named `AccountActivityDashboard` to allow the dashboard to be deleted. It also turns off the refresh schedule.

```
aws cloudtrail update-dashboard --dashboard-id AccountActivityDashboard \  
--refresh-schedule '{"Status": "DISABLED"}' \  
--no-termination-protection-enabled
```

Add a widget to a custom dashboard

The following example adds a new widget named TopServices to the custom dashboard named AccountActivityDashboard. The widgets array includes the two widgets that were already created for the dashboard and the new widget.

Note

In the this example, ? is surrounded with single quotes because it is used with eventTime. Depending on the operating system you are running on, you may need to surround single quotes with escape quotes. For more information, see [Using quotation marks and literals with strings in the AWS CLI](#).

```
aws cloudtrail update-dashboard --dashboard-id AccountActivityDashboard \
--widgets '[
  {
    "ViewProperties": {
      "Height": "2",
      "Width": "4",
      "Title": "TopErrors",
      "View": "Table"
    },
    "QueryStatement": "SELECT errorCode, COUNT(*) AS eventCount FROM eds WHERE
eventTime > '?' AND eventTime < '?' AND (errorCode is not null) GROUP BY errorCode
ORDER BY eventCount DESC LIMIT 100",
    "QueryParameters": ["$StartTime$", "$EndTime$"]
  },
  {
    "ViewProperties": {
      "Height": "2",
      "Width": "4",
      "Title": "MostActiveRegions",
      "View": "PieChart",
      "LabelColumn": "awsRegion",
      "ValueColumn": "eventCount",
      "FilterColumn": "awsRegion"
    },
    "QueryStatement": "SELECT awsRegion, COUNT(*) AS eventCount FROM eds where
eventTime > '?' and eventTime < '?' GROUP BY awsRegion ORDER BY eventCount LIMIT 100",
    "QueryParameters": ["$StartTime$", "$EndTime$"]
  },
]
```

```
{
  "ViewProperties": {
    "Height": "2",
    "Width": "4",
    "Title": "TopServices",
    "View": "BarChart",
    "LabelColumn": "service",
    "ValueColumn": "eventCount",
    "FilterColumn": "service",
    "Orientation": "Vertical"
  },
  "QueryStatement": "SELECT replace(eventSource, '.amazonaws.com') AS service,
COUNT(*) as eventCount FROM eds WHERE eventTime > '?' AND eventTime < '?' GROUP BY
eventSource ORDER BY eventCount DESC LIMIT 100",
  "QueryParameters": ["$StartTime$", "$EndTime$"]
}
```

Delete a dashboard with the AWS CLI

This section describes how to use the AWS CLI `delete-dashboard` command to delete a CloudTrail Lake dashboard.

To delete a dashboard, specify the `--dashboard-id` by providing the dashboard ARN, or the dashboard name.

```
aws cloudtrail delete-dashboard --dashboard-id arn:aws:cloudtrail:us-
east-1:123456789012:dashboard/exampleDash
```

There is no response if the operation is successful.

Note

You can't delete a dashboard if `--termination-protection-enabled` is set.

CloudTrail Lake queries

Queries in CloudTrail Lake are authored in SQL. You can build a query on the CloudTrail Lake **Editor** tab by writing the query in SQL from scratch, by opening a saved or sample query and editing it, or by using the query generator to produce a query from an English language prompt. You

cannot overwrite an included sample query with your changes, but you can save it as a new query. For more information about the SQL query language that is allowed, see [CloudTrail Lake SQL constraints](#).

An unbounded query (such as `SELECT * FROM edsID`) scans all data in your event data store. To help control costs, we recommend that you constrain queries by adding starting and ending eventTime time stamps to queries. The following is an example that searches for all events in a specified event data store where the event time is after (>) January 5, 2023 at 1:51 p.m. and before (<) January 19, 2023 at 1:51 p.m. Because an event data store has a minimum retention period of seven days, the minimum time span between starting and ending eventTime values is also seven days.

```
SELECT *  
FROM eds-ID  
WHERE  
    eventtime >='2023-01-05 13:51:00' and eventtime < ='2023-01-19 13:51:00'
```

For information about how to optimize your queries, see [Optimize CloudTrail Lake queries](#).

Topics

- [Query editor tools](#)
- [Create CloudTrail Lake queries from natural language prompts](#)
- [View sample queries with the CloudTrail console](#)
- [Create or edit a query with the CloudTrail console](#)
- [Run a query and save query results with the console](#)
- [View query results with the console](#)
- [Summarize query results in natural language](#)
- [Download saved query results](#)
- [Validate CloudTrail Lake saved query results](#)
- [Optimize CloudTrail Lake queries](#)
- [Run and manage CloudTrail Lake queries with the AWS CLI](#)

Query editor tools

A toolbar at the upper right of the query editor offers commands to help author and format your SQL query.



The following list describes the commands on the toolbar.

- **Undo** – Reverts the last content change made in the query editor.
- **Redo** – Repeats the last content change made in the query editor.
- **Format selected** – Arranges the query editor content according to SQL formatting and spacing conventions.
- **Comment/uncomment selected** - Comments the selected portion of the query if it is not already commented. If the selected portion is already commented, choosing this option removes the comment.

Create CloudTrail Lake queries from natural language prompts

You can use the CloudTrail Lake query generator to produce a query from an English language prompt that you provide. The query generator uses generative artificial intelligence (generative AI) to produce a ready-to-use SQL query from your prompt, which you can then choose to run in Lake's query editor, or further fine tune. You don't need to have extensive knowledge of SQL or CloudTrail event fields to use the query generator.

The prompt can be a question or a statement about the event data in your CloudTrail Lake event data store. For example, you can enter prompts like "What are my top errors in the past month?" and "Give me a list of users that used SNS."

A prompt can have a minimum of 3 characters and a maximum of 500 characters.

There are no charges for generating queries; however, when you run queries, you incur charges based on the amount of optimized and compressed data scanned. To help control costs, we recommend that you constrain queries by adding starting and ending eventTime timestamps to queries.

Note

You can provide feedback about a generated query by choosing the thumbs up or thumbs down button that appears below the generated query. When you provide feedback, CloudTrail saves your prompt and the generated query.

Do not include any personally identifying, confidential, or sensitive information in your prompts.

This feature uses generative AI large language models (LLMs); we recommend double-checking the LLM response.

You can access the query generator using the CloudTrail console and AWS CLI.

CloudTrail console

To use the query generator on the CloudTrail console

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Query**.
3. On the **Query** page, choose the **Editor** tab.
4. Choose the event data store you want to create a query for.
5. In the **Query generator** area, enter a prompt in plain English. For examples, see [Example prompts](#).
6. Choose **Generate query**. The query generator will attempt to generate a query from your prompt. If successful, the query generator provides the SQL query in the editor. If the prompt is unsuccessful, rephrase your prompt and try again.
7. (Optional) You can provide feedback about the generated query. To provide feedback, choose the thumbs up or thumbs down button that appears below the prompt. When you provide feedback, CloudTrail saves your prompt and the generated query.
8. (Optional) Choose **Run** to run the query.

Note

When you run queries, you incur charges based on the amount of optimized and compressed data scanned. To help control costs, we recommend that you constrain queries by adding starting and ending eventTime timestamps to queries.

9. (Optional) If you run the query and there are results, you can choose **Summarize results** to generate a natural language summary in English of the query results. This option uses generative artificial intelligence (generative AI) to produce the summary. For more information about this option, see [Summarize query results in natural language](#).

You can provide feedback about the summary by choosing the thumbs up or thumbs down button that appears below the generated summary.

 Note

The query summarization feature is in preview release for CloudTrail Lake and is subject to change. This feature is available in the following regions: Asia Pacific (Tokyo), US East (N. Virginia), and US West (Oregon).

AWS CLI

To generate a query with the AWS CLI

Run the `generate-query` command to generate a query from an English prompt. For `--event-data-stores`, provide the ARN (or ID suffix of the ARN) of the event data store you want to query. You can only specify one event data store. For `--prompt`, provide the prompt in English.

```
aws cloudtrail generate-query
--event-data-stores arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
EXAMPLE-ee54-4813-92d5-999aeEXAMPLE \
--prompt "Show me all console login events for the past week?"
```

If successful, the command outputs a SQL statement and provides a `QueryAlias` that you will use with the `start-query` command to run the query against your event data store.

```
{
  "QueryStatement": "SELECT * FROM $EDS_ID WHERE eventname = 'ConsoleLogin' AND
eventtime >= timestamp '2024-09-16 00:00:00' AND eventtime <= timestamp '2024-09-23
00:00:00' AND eventSource = 'signin.amazonaws.com'",
  "QueryAlias": "AWSCloudTrail-UUID"
}
```

To run a query with the AWS CLI

Run the [start-query](#) command with the `QueryAlias` outputted by the `generate-query` command in the previous example. You also have the option of running the `start-query` command by providing the `QueryStatement`.

```
aws cloudtrail start-query --query-alias AWSCloudTrail-UUID
```

The response is a `QueryId` string. To get the status of a query, run `describe-query` using the `QueryId` value returned by `start-query`. If the query is successful, you can run `get-query-results` to get results.

```
{
  "QueryId": "EXAMPLE2-0add-4207-8135-2d8a4EXAMPLE"
}
```

Note

Queries that run for longer than one hour might time out. You can still get partial results that were processed before the query timed out.

If you are delivering the query results to an S3 bucket using the optional `--delivery-s3uri` parameter, the bucket policy must grant CloudTrail permission to deliver query results to the bucket. For information about manually editing the bucket policy, see [Amazon S3 bucket policy for CloudTrail Lake query results](#).

Required permissions

The [AWSCloudTrail_FullAccess](#) and [AdministratorAccess](#) managed policies both provide the necessary permissions to use this feature.

You can also include the `cloudtrail:GenerateQuery` action in a new or existing customer managed or inline policy.

Region support

This feature is supported in the following AWS Regions:

- Asia Pacific (Mumbai) Region (ap-south-1)
- Asia Pacific (Sydney) Region (ap-southeast-2)
- Asia Pacific (Tokyo) Region (ap-northeast-1)
- Canada (Central) Region (ca-central-1)
- Europe (London) Region (eu-west-2)

- US East (N. Virginia) Region (us-east-1)
- US West (Oregon) Region (us-west-2)

Limitations

The following are limitations of the query generator:

- The query generator can only accept prompts in English.
- The query generator can only generate queries for event data stores that collect CloudTrail events (management events, data events, network activity events).
- The query generator cannot generate queries for prompts that do not pertain to CloudTrail Lake event data.

Example prompts

This section provides example prompts and the resulting SQL queries generated from the prompts.

If you choose to run the example queries in this section, replace *eds-id* with the ID of the event data store that you want to query and replace the timestamps with the appropriate timestamps for your use case. Timestamps have the following format: YYYY-MM-DD HH:MM:SS.

Prompt: What are my top errors in the past month?

SQL query:

```
SELECT
    errorMessage,
    COUNT(*) as eventCount
FROM
    eds-id
WHERE
    errorMessage IS NOT NULL
AND eventTime >= timestamp '2024-05-01 00:00:00'
AND eventTime <= timestamp '2024-05-31 23:59:59'
GROUP BY 1
ORDER BY 2 DESC
LIMIT 2;
```

Prompt: Give me a list of users that used Amazon SNS.

SQL query:

```
SELECT
    DISTINCT userIdentity.arn AS user
FROM
    eds-id
WHERE
    eventSource = 'sns.amazonaws.com'
```

Prompt: What are my API counts each day for read and write events in the past month?

SQL query:

```
SELECT date(eventTime) AS event_date,
    SUM(
        CASE
            WHEN readonly = true THEN 1
            ELSE 0
        END
    ) AS read_events,
    SUM(
        CASE
            WHEN readonly = false THEN 1
            ELSE 0
        END
    ) AS write_events
FROM
    eds-id
WHERE
    eventTime >= timestamp '2024-05-04 00:00:00'
AND eventTime <= timestamp '2024-06-04 23:59:59'
GROUP BY 1
ORDER BY 1 ASC;
```

Prompt: Show any events with access denied errors for the past three weeks.

SQL query:

```
SELECT *
FROM
    eds-id
WHERE
```

```
WHERE (errorCode = 'AccessDenied' OR errorMessage = 'Access Denied')
AND eventTime >= timestamp '2024-05-16 01:00:00'
AND eventTime <= timestamp '2024-06-06 01:00:00'
```

Prompt: Query the number of calls each operator performed on the date 2024-05-01. The operator is a principal tag.

SQL query:

```
SELECT element_at(
    eventContext.tagContext.principalTags,
    'operator'
) AS operator,
COUNT(*) AS eventCount
FROM
    eds-id
WHERE eventtime >= '2024-05-01 00:00:00'
    AND eventtime < '2024-05-01 23:59:59'
GROUP BY 1
ORDER BY 2 DESC;
```

Prompt: Give me all event IDs that touched resources within the AWS CloudFormation stack with name *myStack* on the date 2024-05-01.

SQL query:

```
SELECT eventID
FROM
    eds-id
WHERE any_match(
    eventContext.tagcontext.resourcetags,
    rt->element_at(rt.tags, 'aws:cloudformation:stack-name') = 'myStack'
)
AND eventtime >= '2024-05-01 00:00:00'
AND eventtime < '2024-05-01 23:59:59'
```

Prompt: Count the number of events grouped by resource tag *'solution'* values, listing them in descending order of count.

SQL query:

```
SELECT element_at(rt.tags, 'solution'),
```

```
count(*) as event_count
FROM
    eds-id,
    unnest(eventContext.tagContext.resourceTags) as rt
WHERE eventtime < '2025-05-14 19:00:00'
GROUP BY 1
ORDER BY 2 DESC;
```

Prompt: Find all Amazon S3 data events where resource tag Environment has value *prod*.

SQL query:

```
SELECT *
FROM
    eds-id
WHERE eventCategory = 'Data'
    AND eventSource = 's3.amazonaws.com'
    AND eventtime >= '2025-05-14 00:00:00'
    AND eventtime < '2025-05-14 20:00:00'
    AND any_match(
        eventContext.tagContext.resourceTags,
        rt->element_at(rt.tags, 'Environment') = 'prod'
    )
```

View sample queries with the CloudTrail console

The CloudTrail console provides a number of sample queries that can help you get started writing your own queries.

CloudTrail queries incur charges based upon the amount of data scanned. To help control costs, we recommend that you constrain queries by adding starting and ending eventTime time stamps to queries. For more information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Note

You can also view queries created by the GitHub community. For more information, see [CloudTrail Lake sample queries](#) on the GitHub website. AWS CloudTrail has not evaluated the queries in GitHub.

To view and run a sample query

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Query**.
3. On the **Query** page, choose the **Sample queries** tab.
4. Choose a sample query from the list or enter a phrase to search by. In this example, we'll open the query **Investigate who made console changes** by choosing the **Query name**. This opens the query in the **Editor** tab.

Note

By default, this page uses basic search functionality. You can improve the search functionality by adding permissions for the `cloudtrail:SearchSampleQueries` action, if it is not already provided by your permissions policy. The [AWSCloudTrail_FullAccess](#) managed policy provides permissions to perform the `cloudtrail:SearchSampleQueries` action.

Query Info

Editor | Results history | Saved queries | **Sample queries** | How it works

Sample queries (202) Info

< 1 2 3 4 5 6 7 ... 21 >

Query name	Query description	Query SQL
Investigate who called an API	Find all principal IDs who called a particular API on a particular day.	SELECT userIdentity.arn AS user, eventName FROM \$EDS_ID WHERE userIdentity.arn IS NOT NULL AND eventName = 'CreateBucket' AND eventTime > DATE_ADD('week', -1, CURRENT_TIMESTAMP) AND eventTime < DATE_ADD('day', -6, CURRENT_TIMESTAMP)
Investigate user actions	Find all the APIs that a particular user called in a specified date range.	SELECT eventId, eventName, eventSource, eventTime, userIdentity.arn AS user FROM \$EDS_ID WHERE userIdentity.arn LIKE '%<username>%' AND eventTime > DATE_ADD('week', -1, CURRENT_TIMESTAMP) AND eventTime < DATE_ADD('day', -4, CURRENT_TIMESTAMP)
Top APIs aggregated by source	Find the number of API calls grouped by event name and event source within the past week	SELECT eventSource, eventName, COUNT(*) AS apiCount FROM \$EDS_ID WHERE eventTime > DATE_ADD('week', -1, CURRENT_TIMESTAMP) GROUP BY eventSource, eventName ORDER BY apiCount DESC

5. On the **Editor** tab, choose the event data store for which you want to run the query. When you choose the event data store from the list, CloudTrail automatically populates the event data store ID in the FROM line of the query editor.

Query [Info](#)

[Editor](#) | [Results history](#) | [Saved queries](#) | [Sample queries](#) | [How it works](#)

Event data store [Info](#)

Choose an event data store.

my-management-events-eds

Event data store ID



Event properties

< 1 2 >

- additionalEventData
- annotation
- apiVersion
- awsRegion
- edgeDeviceDetails
- errorCode
- errorMessage
- eventID
- eventJson
- eventName
- eventSource

[Investigate who made console changes](#) +

```

1 SELECT
2   userIdentity.arn AS user, eventName, eventTime, awsRegion, requestParameters AS resourceChangedManually
3 FROM
4   [redacted]
5 WHERE
6   sessionCredentialFromConsole='true' AND errorCode IS NULL
7   AND eventTime > '2023-06-23 00:00:00'

```

[Run](#) [Save](#) [Clear](#) ☐ Save results to S3

[Query results](#) | [Command output](#)

Output

< 1 > ⚙

Time stamp	Status	Delivery status	Response	Query SQL	Query ID	Event data st...

6. Choose **Run** to run the query.

The **Command output** tab shows you metadata about your query, such as whether the query was successful, the number of records matched, and the run time of the query.

[Query results](#) | [Command output](#)

Output

< 1 > ⚙

Time stamp	Status	Delivery status	Response	Query SQL	Query ID	Event data st...
June 30, 2023, 2...	✓ Successful		1467 records ma...	SELECT userIdentity.ar		my-management-ever

The **Query results** tab shows you the event data in the selected event data store that matched your query.

Query results

Command output

Results

Info

Copy

Search queries

<1...>

☐	user	eventName	eventTime	awsRegion
☐	arn:aws:sts::[redacted]:assumed-role/Admin/[redacted]	UpdateEventDataStore	2023-07-10 14:35:00.000	us-east-1
☐	arn:aws:sts::[redacted]:assumed-role/Admin/[redacted]	LookupEvents	2023-07-07 23:10:14.000	us-east-1
☐	arn:aws:sts::[redacted]:assumed-role/Admin/[redacted]	LookupEvents	2023-07-07 23:10:13.000	us-east-1

For more information about editing a query, see [Create or edit a query with the CloudTrail console](#). For more information about running a query and saving query results, see [Run a query and save query results with the console](#).

Create or edit a query with the CloudTrail console

In this walkthrough, we open one of the sample queries, edit it to find actions taken by a specific user named Alice, and save it as a new query. You can also edit a saved query on the **Saved queries** tab, if you have saved queries. To help control costs, we recommend that you constrain queries by adding starting and ending eventTime time stamps to queries.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Query**.
3. On the **Query** page, choose the **Sample queries** tab.
4. Open a sample query by choosing the **Query name**. This opens the query in the **Editor** tab. In this example, we'll select the query named **Investigate user actions** and edit the query to find the actions for a specific user named Alice.
5. In the **Editor** tab, edit the WHERE line to specify the user that you want to investigate and update the eventTime values as needed. The value of FROM is the ID portion of the event data store's ARN and is automatically populated by CloudTrail when you choose the event data store.

```
SELECT
    eventID, eventName, eventSource, eventTime, userIdentity.arn AS user
FROM
```

```
event-data-store-id
```

```
WHERE
```

```
  userIdentity.arn LIKE '%Alice%'
```

```
  AND eventTime > '2023-06-23 00:00:00' AND eventTime < '2023-06-26 00:00:00'
```

6. You can run a query before you save it, to verify that the query works. To run a query, choose an event data store from the **Event data store** drop-down list, and then choose **Run**. View the **Status** column of the **Command output** tab for the active query to verify that a query ran successfully.
7. When you have updated the sample query, choose **Save**.
8. In **Save query**, enter a name and description for the query. Choose **Save query** to save your changes as the new query. To discard changes to a query, choose **Cancel**, or close the **Save query** window.

Save query



Query name

3-64 characters. Only letters, numbers, periods, underscores, hyphens, and spaces are allowed.

Query description

3-256 characters. Only letters, numbers, periods, underscores, hyphens, and spaces are allowed.


Cancel

Save query

Note

Saved queries are tied to your browser; if you use a different browser or a different device to access the CloudTrail console, the saved queries are not available.

9. Open the **Saved queries** tab to see the new query in the table.



Run a query and save query results with the console

After you choose or save a query, you can run a query on an event data store.

When you run a query, you have the option to save the query results to an Amazon S3 bucket. When you run queries in CloudTrail Lake, you incur charges based on the amount of data scanned by the query. There are no additional CloudTrail Lake charges for saving query results to an S3 bucket, however, there are S3 storage charges. For more information about S3 pricing, see [Amazon S3 pricing](#).

When you save query results, the query results may display in the CloudTrail console before they are viewable in the S3 bucket since CloudTrail delivers the query results after the query scan completes. While most queries complete within a few minutes, depending on the size of your event data store, it can take considerably longer for CloudTrail to deliver query results to your S3 bucket. CloudTrail delivers the query results to the S3 bucket in compressed gzip format. On average, after the query scan completes you can expect a latency of 60 to 90 seconds for every GB of data delivered to the S3 bucket.

To run a query using CloudTrail Lake

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Query**.
3. On the **Saved queries** or **Sample queries** tabs, choose a query to run by choosing the **Query name**.
4. On the **Editor** tab, for **Event data store**, choose an event data store from the drop-down list.

5. (Optional) On the **Editor** tab, choose **Save results to S3** to save the query results to an S3 bucket. When you choose the default S3 bucket, CloudTrail creates and applies the required bucket policies. If you choose the default S3 bucket, your IAM policy needs to include permission for the `s3:PutEncryptionConfiguration` action because by default server-side encryption is enabled for the bucket. For more information about saving query results, see [Additional information about saved query results](#).

 Note

To use a different bucket, specify a bucket name, or choose **Browse S3** to choose a bucket. The bucket policy must grant CloudTrail permission to deliver query results to the bucket. For information about manually editing the bucket policy, see [Amazon S3 bucket policy for CloudTrail Lake query results](#).

6. On the **Editor** tab, choose **Run**.

Depending on the size of your event data store, and the number of days of data it includes, a query can take several minutes to run. The **Command output** tab shows the status of a query, and whether a query is finished running. When a query has finished running, open the **Query results** tab to see a table of results for the active query (the query currently shown in the editor).

 Note

Queries that run for longer than one hour might time out. You can still get partial results that were processed before the query timed out. CloudTrail does not deliver partial query results to an S3 bucket. To avoid a time out, you can refine your query to limit the amount of data scanned by specifying a narrower time range.

Additional information about saved query results

After you save query results, you can download the saved query results from the S3 bucket. For more information about finding and downloading saved query results, see [Download saved query results](#).

You can also validate saved query results to determine whether the query results were modified, deleted, or unchanged after CloudTrail delivered the query results. For more information about validating saved query results, see [Validate CloudTrail Lake saved query results](#).

Example: Save query results to an Amazon S3 bucket

This walkthrough shows how you can save query results to an S3 bucket and then download those query results.

To save query results to an Amazon S3 bucket

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Query**.
3. On the **Sample queries** or **Saved queries** tabs, choose a query to run by choosing the **Query name**. In this example, we'll choose the sample query named **Investigate user actions**.
4. On the **Editor** tab, for **Event data store**, choose an event data store from the drop-down list. When you choose the event data store from the list, CloudTrail automatically populates the event data store ID in the **From** line.
5. In this sample query, we'll edit the `userIdentity.arn` value to specify a user named Admin, and we'll leave the default values for `eventTime`. When you run a query, you're charged for the amount of data scanned. To help control costs, we recommend that you constrain queries by adding starting and ending `eventTime` time stamps to queries.

The screenshot shows the AWS CloudTrail console's query editor. The title bar says "Investigate user actions" with a plus icon. The query is as follows:

```
1 SELECT
2   eventID, eventName, eventSource, eventTime, userIdentity.arn AS user
3 FROM
4   2a8f2138-0caa-46c8-a194-
5 WHERE
6   userIdentity.arn LIKE '%Admin%'
7   AND eventTime > '2023-07-21 00:00:00' AND eventTime < '2023-07-24 00:00:00'
```


At the bottom, there are three buttons: "Run" (orange), "Save", and "Clear". On the far right, there is a checkbox labeled "Save results to S3" which is currently unchecked.

6. Choose **Save results to S3** to save the query results to an S3 bucket. When you choose the default S3 bucket, CloudTrail creates and applies the required bucket policies. If you choose the default S3 bucket, your IAM policy needs to include permission for the

s3:PutEncryptionConfiguration action because by default server-side encryption is enabled for the bucket. In this example, we'll use the default S3 bucket.

Note

To use a different bucket, specify a bucket name, or choose **Browse S3** to choose a bucket. The bucket policy must grant CloudTrail permission to deliver query results to the bucket. For information about manually editing the bucket policy, see [Amazon S3 bucket policy for CloudTrail Lake query results](#).



7. Choose **Run**. Depending on the size of your event data store, and the number of days of data it includes, a query can take several minutes to run. The **Command output** tab shows the status of a query, and whether a query is finished running. When a query has finished running, open the **Query results** tab to see a table of results for the active query (the query currently shown in the editor).
8. When CloudTrail completes delivery of the saved query results to your S3 bucket, the **Delivery status** column provides a link to the S3 bucket that contains your saved query result files as well as a [sign file](#) that you can use to verify your saved query results. Choose **View in S3** to view the query result files and sign files in the S3 bucket.

Note

When you save query results, the query results may display in the CloudTrail console before they are viewable in the S3 bucket because CloudTrail delivers the query results

after the query scan completes. While most queries complete within a few minutes, depending on the size of your event data store, it can take considerably longer for CloudTrail to deliver query results to your S3 bucket. CloudTrail delivers the query results to the S3 bucket in compressed gzip format. On average, after the query scan completes you can expect a latency of 60 to 90 seconds for every GB of data delivered to the S3 bucket.

Query results

Command output

Output

< 1 > ⚙

Time stamp	Status	Delivery status	Response	Query SQL	Query ID	Event data store
July 28, 2023, 18:20...	✔ Successful	View in S3	468 records matche...	SELECT eventID, eventNar	52ab2728-06de-4dac-8c5	my-management-events-

9. To download your query results, choose the query result file (in this example, `result_1.csv.gz`) and then choose **Download**.

52ab2728-06de-4dac-8c53- /

Copy S3 URI

Objects | Properties

Objects (2)

Objects are the fundamental entities stored in Amazon S3. You can use [Amazon S3 Inventory](#) to get a list of all objects in your bucket. For others to access your objects, you'll need to explicitly grant them permissions. [Learn more](#)

↺

Copy S3 URI

Copy URL

Download

Open

Delete

Actions

Create folder

Upload

Find objects by prefix

Show versions

☐	Name	Type	Last modified	Size	Storage class
☒	result_1.csv.gz	gz	July 28, 2023, 13:20:12 (UTC-05:00)	13.8 KB	Standard
☐	result_sign.json	json	July 28, 2023, 13:20:18 (UTC-05:00)	929.0 B	Standard

For information about validating saved query results, see [Validate CloudTrail Lake saved query results](#).

View query results with the console

After your query finishes, you can view its results. The results of a query are available for seven days after the query finishes. You can view results for the active query on the **Query results** tab, or you can access results for all recent queries on the **Results history** tab on the **Lake** home page.

Query results can change from older runs of a query to newer ones, as later events in the query period can be logged between queries.

When you save query results, the query results may display in the CloudTrail console before they are viewable in the S3 bucket since CloudTrail delivers the query results after the query scan completes. While most queries complete within a few minutes, depending on the size of your event data store, it can take considerably longer for CloudTrail to deliver query results to your S3 bucket. CloudTrail delivers the query results to the S3 bucket in compressed gzip format.

On average, after the query scan completes you can expect a latency of 60 to 90 seconds for every GB of data delivered to the S3 bucket. For more information about finding and downloading saved query results, see [Download saved query results](#).

Note

Queries that run for longer than one hour might time out. You can still get partial results that were processed before the query timed out. CloudTrail does not deliver partial query results to an S3 bucket. To avoid a time out, you can refine your query to limit the amount of data scanned by specifying a narrower time range.

To view query results

1. Choose the **Query results** tab on the query editor if it is not already selected. On the **Query results** tab for an active query, each row represents an event result that matched the query. Filter results by entering all or part of an event field value in the search bar. To copy an event, choose the event you want to copy and then choose **Copy**.
2. (Optional) Choose **Summarize results** to generate a natural language summary of the query results. The summary is provided in English. This option uses generative artificial intelligence (generative AI) to produce the summary. For more information about this option, see [Summarize query results in natural language](#).

You can provide feedback about the summary by choosing the thumbs up or thumbs down button that appears below the generated summary.

Note

The query summarization feature is in preview release for CloudTrail Lake and is subject to change. This feature is available in the following regions: Asia Pacific (Tokyo), US East (N. Virginia), and US West (Oregon).

3. On the **Command output** tab, view metadata about the query that was run, such as the event data store ID, run time, number of results scanned, and whether or not the query was successful. If you saved the query results to an Amazon S3 bucket, the metadata also includes a link to the S3 bucket containing the saved query results.

Summarize query results in natural language

Note

The query summarization feature is in preview release for CloudTrail Lake and is subject to change.

After your query finishes, you can get a summary of your query results in natural language from the **Query results** tab in the query editor. This option uses generative artificial intelligence (generative AI) to produce the summary.

To summarize query results

1. From the **Query results** tab of the query editor, choose **Summarize results** to generate a natural language summary of the query results. The summary is provided in English.
2. (Optional) Provide feedback about the summary by choosing the thumbs up or thumbs down button that appears below the generated summary.

If the related event data store is encrypted using a KMS key, you cannot use the KMS key to encrypt the query results and summary. The query results and summary are instead encrypted by CloudTrail.

Access to the generated summary is authorized against the `GetQueryResults`, `GenerateQueryResultsSummary`, and KMS permissions (if the related event data store is encrypted with a KMS key). When a summary is generated, CloudTrail records an event named `GenerateQueryResultsSummary` for visibility.

Required permissions

The [AWSCloudTrail_FullAccess](#) and [AdministratorAccess](#) managed policies both provide the necessary permissions to use this feature.

You can also include the `cloudtrail:GenerateQueryResultsSummary` and `cloudtrail:GetQueryResults` actions in a new or existing customer managed or inline policy.

If the event data store related to the query results being summarized is encrypted with a KMS key, you also need permissions for the KMS key.

Region support

This feature is available in the following AWS Regions:

- Asia Pacific (Tokyo) Region (ap-northeast-1)
- US East (N. Virginia) Region (us-east-1)
- US West (Oregon) Region (us-west-2)

Limitations

The following are limitations of this feature:

- Summaries are in English only.
- Summaries are limited to event data stores that collect CloudTrail events (management events, data events, network activity events).
- Each summary is for the results of a single query.
- The query results size must be less than 250 KB.
- The monthly quota of query results that can be summarized is 3 MB.

Download saved query results

After you save query results, you need to be able to locate the file containing the query results. CloudTrail delivers your query results to an Amazon S3 bucket that you specify when you save the query results.

Note

When you save query results, the query results may display in the console before they are viewable in the S3 bucket since CloudTrail delivers the query results after the query scan completes. While most queries complete within a few minutes, depending on the size of your event data store, it can take considerably longer for CloudTrail to deliver query results

to your S3 bucket. CloudTrail delivers the query results to the S3 bucket in compressed gzip format. On average, after the query scan completes you can expect a latency of 60 to 90 seconds for every GB of data delivered to the S3 bucket.

Topics

- [Find your CloudTrail Lake saved query results](#)
- [Download your CloudTrail Lake saved query results](#)

Find your CloudTrail Lake saved query results

CloudTrail publishes query result and sign files to your S3 bucket. The query result file contains the output of the saved query and the sign file provides the signature and hash value for the query results. You can use the sign file to validate the query results. For more information about validating query results, see [Validate CloudTrail Lake saved query results](#).

To retrieve a query result or sign file, you can use the Amazon S3 console, the Amazon S3 command line interface (CLI), or the API.

To find your query results and sign files with the Amazon S3 console

1. Open the Amazon S3 console.
2. Choose the bucket you specified.
3. Navigate through the object hierarchy until you find the query result and sign files. The query result file has a .csv.gz extension and the sign file has a .json extension.

You will navigate through an object hierarchy that is similar to the following example, but with a different bucket name, account ID, date, and query ID.

```
All Buckets
  amzn-s3-demo-bucket
    AWSLogs
      Account_ID;
        CloudTrail-Lake
          Query
            2022
              06
```

20

Query_ID

Download your CloudTrail Lake saved query results

When you save query results, CloudTrail delivers two types of files to your Amazon S3 bucket.


- A sign file in JSON format that you can use to validate the query result files. The sign file is named `result_sign.json`. For more information about the sign file, see [CloudTrail sign file structure](#).
- One or more query result files in CSV format, which contain the results from the query. The number of query result files delivered is dependent upon the total size of the query results. The maximum file size for a query result file is 1 TB. Each query result file is named `result_number.csv.gz`. For example, if the total size of the query results was 2 TB, you would have two query result files, `result_1.csv.gz` and `result_2.csv.gz`.

CloudTrail query result and sign files are Amazon S3 objects. You can use the S3 console, the AWS Command Line Interface (CLI), or the S3 API to retrieve query result and sign files.

The following procedure describes how to download the query result and sign files with the Amazon S3 console.

To download your query result or sign file with the Amazon S3 console

1. Open the Amazon S3 console.
2. Choose the bucket and choose the file that you want to download.



The screenshot shows the Amazon S3 console interface. At the top, it says 'Objects (2)'. Below this, there's a search bar and several action buttons: 'Copy S3 URI', 'Copy URL', 'Download', 'Open', 'Delete', 'Actions', 'Create folder', and 'Upload'. A table lists the objects:

	Name	Type	Last modified	Size	Storage class
☐	result_1.csv.gz	gz	October 17, 2022, 16:18:17 (UTC-05:00)	5.4 KB	Standard
☐	result_sign.json	json	October 17, 2022, 16:18:19 (UTC-05:00)	929.0 B	Standard

3. Choose **Download** and follow any prompts to save the file.

Note

Some browsers, such as Chrome, automatically extract the query result file for you. If your browser does this for you, skip to step 5.

4. Use a product such as [7-Zip](#) to extract the query result file.
5. Open the query result or sign file.

Validate CloudTrail Lake saved query results

To determine whether the query results were modified, deleted, or unchanged after CloudTrail delivered the query results, you can use CloudTrail query results integrity validation. This feature is built using industry standard algorithms: SHA-256 for hashing and SHA-256 with RSA for digital signing. This makes it computationally infeasible to modify, delete or forge CloudTrail query result files without detection. You can use the command line to validate the query result files.

Why use it?

Validated query result files are invaluable in security and forensic investigations. For example, a validated query result file enables you to assert positively that the query result file itself has not changed. The CloudTrail query result file integrity validation process also lets you know if a query result file has been deleted or changed.

Topics

- [Validate saved query results with the AWS CLI](#)
- [CloudTrail sign file structure](#)
- [Custom implementations of CloudTrail query result file integrity validation](#)

Validate saved query results with the AWS CLI

You can validate the integrity of the query result files and sign file by using the [aws cloudtrail verify-query-results](#) command.

Prerequisites

To validate query results integrity with the command line, the following conditions must be met:

- You must have online connectivity to AWS.
- You must use AWS CLI version 2.
- To validate query result files and sign file locally, the following conditions apply:
 - You must put the query result files and sign file in the specified file path. Specify the file path as the value for the **--local-export-path** parameter.

- You must not rename the query result files and sign file.
- To validate the query result files and sign file in the S3 bucket, the following conditions apply:
 - You must not rename the query result files and sign file.
 - You must have read access to the Amazon S3 bucket that contains the query result files and sign file.
 - The specified S3 prefix must contain the query result files and sign file. Specify the S3 prefix as the value for the **--s3-prefix** parameter.

verify-query-results

The **verify-query-results** command verifies the hash value of each query result file by comparing the value with the `fileHashValue` in the sign file, and then validating the `hashSignature` in the sign file.

When you verify query results, you can use either the **--s3-bucket** and **--s3-prefix** command line options to validate the query result files and sign file stored in an S3 bucket, or you can use the **--local-export-path** command line option to perform a local validation of the downloaded query result files and sign file.

Note

The **verify-query-results** command is Region specific. You must specify the **--region** global option to validate query results for a specific AWS Region.

The following are the options for the **verify-query-results** command.

--s3-bucket *<string>*

Specifies the S3 bucket name that stores the query result files and sign file. You cannot use this parameter with **--local-export-path**.

--s3-prefix *<string>*

Specifies the S3 path of the S3 folder that contains the query result files and sign file (for example, `s3/path/`). You cannot use this parameter with **--local-export-path**. You do not need to provide this parameter if the files are located in the root directory of the S3 bucket.

--local-export-path *<string>*

Specifies the local directory that contains the query result files and sign file (for example, /local/path/to/export/file/). You cannot use this parameter with **--s3-bucket** or **--s3-prefix**.

Examples

The following example validates query results using the **--s3-bucket** and **--s3-prefix** command line options to specify the S3 bucket name and prefix containing the query result files and sign file.

```
aws cloudtrail verify-query-results --s3-bucket amzn-s3-demo-bucket --s3-prefix prefix
--region region
```

The following example validates downloaded query results using the **--local-export-path** command line option to specify the local path for the query result files and sign file. For more information about downloading query result files, see [Download your CloudTrail Lake saved query results](#).

```
aws cloudtrail verify-query-results --local-export-path local_file_path --region region
```

Validation results

The following table describes the possible validation messages for query result files and sign file.

File Type	Validation Message	Description
Sign file	Successfully validated sign and query result files	The sign file signature is valid. The query result files it references can be checked.
Query result file	ValidationError: "File <i>file_name</i> has inconsistent hash value with hash value recorded in sign file, hash value in sign file is <i>expected_</i>	Validation failed because the hash value for the query result file did not match the <code>fileHashValue</code> in the sign file.

File Type	Validation Message	Description
	<i>hash</i> , but get <i>computed_hash</i>	
Sign file	ValidationError: Invalid signature in sign file	Validation for the sign file failed because the signature is not valid.

CloudTrail sign file structure

The sign file contains the name of each query result file that was delivered to your Amazon S3 bucket when you saved the query results, the hash value for each query result file, and the digital signature of the file. The digital signature and hash values are used for validating the integrity of the query result files and of the sign file itself.

Sign file location

The sign file is delivered to an Amazon S3 bucket location that follows this syntax.

```
s3://amzn-s3-demo-bucket/optional-prefix/AWSLogs/aws-account-ID/CloudTrail-Lake/
Query/year/month/date/query-ID/result_sign.json
```

Sample sign file contents

The following example sign file contains information for CloudTrail Lake query results.

```
{
  "version": "1.0",
  "region": "us-east-1",
  "files": [
    {
      "fileHashValue" :
"de85a48b8a363033c891abd723181243620a3af3b6505f0a44db77e147e9c188",
      "fileName" : "result_1.csv.gz"
    }
  ],
  "hashAlgorithm" : "SHA-256",
  "signatureAlgorithm" : "SHA256withRSA",
  "queryCompleteTime": "2022-05-10T22:06:30Z",
}
```



```
"hashSignature" :  
  "7664652aaf1d5a17a12ba50abe6aca77c0ec76264bdf7dce71ac6d1c7781117c2a412e5820bccf473b1361306dff6"  
  "publicKeyFingerprint" : "67b9fa73676d86966b449dd677850753"  
}
```

Sign file field descriptions

The following are descriptions for each field in the sign file:

version

The version of the sign file.

region

The Region for the AWS account used for saving the query results.

files.fileHashValue

The hexadecimal encoded hash value of the compressed query result file content.

files.fileName

The name of the query result file.

hashAlgorithm

The hash algorithm used to hash the query result file.

signatureAlgorithm

The algorithm used to sign the file.

queryCompleteTime

Indicates when CloudTrail delivered the query results to the S3 bucket. You can use this value to find the public key.

hashSignature

The hash signature for the file.

publicKeyFingerprint

The hexadecimal encoded fingerprint of the public key used to sign the file.

Custom implementations of CloudTrail query result file integrity validation

Because CloudTrail uses industry standard, openly available cryptographic algorithms and hash functions, you can create your own tools to validate the integrity of the CloudTrail query result files. When you save query results to an Amazon S3 bucket, CloudTrail delivers a sign file to your S3 bucket. You can implement your own validation solution to validate the signature and query result files. For more information about the sign file, see [CloudTrail sign file structure](#).

This topic describes how the sign file is signed, and then details the steps that you will need to take to implement a solution that validates the sign file and the query result files that the sign file references.

Understanding how CloudTrail sign files are signed

CloudTrail sign files are signed with RSA digital signatures. For each sign file, CloudTrail does the following:

1. Creates a hash list containing the hash value for each query result file.
2. Gets a private key unique to the Region.
3. Passes the SHA-256 hash of the string and the private key to the RSA signing algorithm, which produces a digital signature.
4. Encodes the byte code of the signature into hexadecimal format.
5. Puts the digital signature into the sign file.

Contents of the data signing string

The data signing string consists of the hash value for each query result file separated by a space. The sign file lists the `fileHashValue` for each query result file.

Custom validation implementation steps

When implementing a custom validation solution, you will need to validate the sign file and the query result files that it references.

Validate the sign file

To validate a sign file, you need its signature, the public key whose private key was used to sign it, and a data signing string that you compute.

1. Get the sign file.
2. Verify that the sign file has been retrieved from its original location.
3. Get the hexadecimal-encoded signature of the sign file.
4. Get the hexadecimal-encoded fingerprint of the public key whose private key was used to sign the sign file.
5. Retrieve the public key for the time range corresponding to `queryCompleteTime` in the sign file. For the time range, choose a `StartTime` earlier than the `queryCompleteTime` and an `EndTime` later than the `queryCompleteTime`.
6. From among the public keys retrieved, choose the public key whose fingerprint matches the `publicKeyFingerprint` value in the sign file.
7. Using a hash list containing the hash value for each query result file separated by a space, recreate the data signing string used to verify the sign file signature. The sign file lists the `fileHashValue` for each query result file.

For example, if your sign file's `files` array contains the following three query result files, your hash list is "aaa bbb ccc".

```
"files": [  
  {  
    "fileHashValue" : "aaa",  
    "fileName" : "result_1.csv.gz"  
  },  
  {  
    "fileHashValue" : "bbb",
```

```
    "fileName" : "result_2.csv.gz"

  },
  {

    "fileHashValue" : "ccc",

    "fileName" : "result_3.csv.gz"

  }
],
```

8. Validate the signature by passing in the SHA-256 hash of the string, the public key, and the signature as parameters to the RSA signature verification algorithm. If the result is true, the sign file is valid.

Validate the query result files

If the sign file is valid, validate the query result files that the sign file references. To validate the integrity of a query result file, compute its SHA-256 hash value on its compressed content and compare the results with the `fileHashValue` for the query result file recorded in the sign file. If the hashes match, the query result file is valid.

The following sections describe the validation process in detail.

A. Get the sign file

The first steps are to get the sign file and get the fingerprint of the public key.

1. Get the sign file from your Amazon S3 bucket for the query results that you want to validate.
2. Next, get the `hashSignature` value from the sign file.
3. In the sign file, get the fingerprint of the public key whose private key was used to sign the file from the `publicKeyFingerprint` field.

B. Retrieve the public key for validating the sign file

To get the public key to validate the sign file, you can use either the AWS CLI or the CloudTrail API. In both cases, you specify a time range (that is, a start time and end time) for the sign file that you want to validate. Use a time range corresponding to the `queryCompleteTime` in the sign file. One

or more public keys may be returned for the time range that you specify. The returned keys may have validity time ranges that overlap.

Note

Because CloudTrail uses different private/public key pairs per Region, each sign file is signed with a private key unique to its Region. Therefore, when you validate a sign file from a particular Region, you must retrieve its public key from the same Region.

Use the AWS CLI to retrieve public keys

To retrieve a public key for a sign file by using the AWS CLI, use the `cloudtrail list-public-keys` command. The command has the following format:

```
aws cloudtrail list-public-keys [--start-time <start-time>] [--end-time <end-time>]
```

The start-time and end-time parameters are UTC timestamps and are optional. If not specified, the current time is used, and the currently active public key or keys are returned.

Sample Response

The response will be a list of JSON objects representing the key (or keys) returned:

Use the CloudTrail API to retrieve public keys

To retrieve a public key for a sign file by using the CloudTrail API, pass in start time and end time values to the `ListPublicKeys` API. The `ListPublicKeys` API returns the public keys whose private keys were used to sign the file within the specified time range. For each public key, the API also returns the corresponding fingerprint.

ListPublicKeys

This section describes the request parameters and response elements for the `ListPublicKeys` API.

Note

The encoding for the binary fields for `ListPublicKeys` is subject to change.

Request Parameters

Name	Description
StartTime	Optionally specifies, in UTC, the start of the time range to look up the public key for CloudTrail sign file. If StartTime is not specified, the current time is used, and the current public key is returned. Type: DateTime
EndTime	Optionally specifies, in UTC, the end of the time range to look up public keys for CloudTrail sign files. If EndTime is not specified, the current time is used. Type: DateTime

Response Elements

PublicKeyList, an array of PublicKey objects that contains:

Name	Description
Value	The DER encoded public key value in PKCS #1 format. Type: Blob
ValidityStartTime	The starting time of validity of the public key. Type: DateTime
ValidityEndTime	The ending time of validity of the public key. Type: DateTime
Fingerprint	The fingerprint of the public key. The fingerprint can be used to identify the public key that you must use to validate the sign file. Type: String

C. Choose the public key to use for validation

From among the public keys retrieved by `list-public-keys` or `ListPublicKeys`, choose the public key whose fingerprint matches the fingerprint recorded in the `publicKeyFingerprint` field of the sign file. This is the public key that you will use to validate the sign file.

D. Recreate the data signing string

Now that you have the signature of the sign file and the associated public key, you need to calculate the data signing string. After you have calculated the data signing string, you will have the inputs needed to verify the signature.

The data signing string consists of the hash value for each query result file separated by a space. After you recreate this string, you can validate the sign file.

E. Validate the sign file

Pass the recreated data signing string, digital signature, and public key to the RSA signature verification algorithm. If the output is true, the signature of the sign file is verified and the sign file is valid.

F. Validate the query result files

After you have validated the sign file, you can validate the query result files it references. The sign file contains the SHA-256 hashes of the query result files. If one of the query result files was modified after CloudTrail delivered it, the SHA-256 hashes will change, and the signature of the sign file will not match.

Use the following procedure to validate the query result files listed in the sign file's `files` array.

1. Retrieve the original hash of the file from the `files.fileHashValue` field in the sign file.
2. Hash the compressed contents of the query result file with the hashing algorithm specified in `hashAlgorithm`.
3. Compare the hash value that you generated for each query result file with the `files.fileHashValue` in the sign file. If the hashes match, the query result files are valid.

Validating signature and query result files offline

When validating sign and query result files offline, you can generally follow the procedures described in the previous sections. However, you must take into account the following information about public keys.

Public keys

In order to validate offline, the public key that you need for validating query result files in a given time range must first be obtained online (by calling `ListPublicKeys`, for example) and then stored offline. This step must be repeated whenever you want to validate additional files outside the initial time range that you specified.

Sample validation snippet

The following sample snippet provides skeleton code for validating CloudTrail sign and query result files. The skeleton code is online/offline agnostic; that is, it is up to you to decide whether to implement it with or without online connectivity to AWS. The suggested implementation uses the [Java Cryptography Extension \(JCE\)](#) and [Bouncy Castle](#) as a security provider.

The sample snippet shows:

- How to create the data signing string used to validate the sign file signature.
- How to verify the sign file's signature.
- How to calculate the hash value for the query result file and compare it with the `fileHashValue` listed in the sign file to verify the authenticity of the query result file.

```
import org.apache.commons.codec.binary.Hex;
import org.bouncycastle.asn1.pkcs.PKCSObjectIdentifiers;
import org.bouncycastle.asn1.pkcs.RSAPublicKey;
import org.bouncycastle.asn1.x509.AlgorithmIdentifier;
import org.bouncycastle.asn1.x509.SubjectPublicKeyInfo;
import org.bouncycastle.jce.provider.BouncyCastleProvider;
import org.json.JSONArray;
import org.json.JSONObject;

import java.security.KeyFactory;
import java.security.MessageDigest;
import java.security.PublicKey;
import java.security.Security;
import java.security.Signature;
import java.security.spec.X509EncodedKeySpec;
import java.util.ArrayList;
import java.util.Arrays;
import java.util.List;
import java.util.stream.Collectors;
```



```

public class SignFileValidationSampleCode {

    public void validateSignFile(String s3Bucket, String s3PrefixPath) throws Exception
    {
        MessageDigest messageDigest = MessageDigest.getInstance("SHA-256");

        // Load the sign file from S3 (using Amazon S3 Client) or from your local copy
        JSONObject signFile = loadSignFileToMemory(s3Bucket, String.format("%s/%s",
s3PrefixPath, "result_sign.json"));

        // Using the Bouncy Castle provider as a JCE security provider - http://
www.bouncycastle.org/
        Security.addProvider(new BouncyCastleProvider());

        List<String> hashList = new ArrayList<>();

        JSONArray jsonArray = signFile.getJSONArray("files");

        for (int i = 0; i < jsonArray.length(); i++) {
            JSONObject file = jsonArray.getJSONObject(i);
            String fileS3objectKey = String.format("%s/%s", s3PrefixPath,
file.getString("fileName"));

            // Load the export file from S3 (using Amazon S3 Client) or from your local
copy
            byte[] exportFileContent = loadCompressedExportFileInMemory(s3Bucket,
fileS3objectKey);
            messageDigest.update(exportFileContent);
            byte[] exportFileHash = messageDigest.digest();
            messageDigest.reset();
            byte[] expectedHash = Hex.decodeHex(file.getString("fileHashValue"));

            boolean signaturesMatch = Arrays.equals(expectedHash, exportFileHash);
            if (!signaturesMatch) {
                System.err.println(String.format("Export file: %s/%s hash doesn't
match.\tExpected: %s Actual: %s",
                    s3Bucket, fileS3objectKey,
                    Hex.encodeHexString(expectedHash),
Hex.encodeHexString(exportFileHash)));
            } else {
                System.out.println(String.format("Export file: %s/%s hash match",
                    s3Bucket, fileS3objectKey));
            }
        }
    }
}

```

```

        hashList.add(file.getString("fileHashValue"));
    }
    String hashListString = hashList.stream().collect(Collectors.joining(" "));

    /*
    NOTE:
    To find the right public key to verify the signature, call CloudTrail
    ListPublicKey API to get a list
    of public keys, then match by the publicKeyFingerprint in the sign file.
    Also, the public key bytes
    returned from ListPublicKey API are DER encoded in PKCS#1 format:

    PublicKeyInfo ::= SEQUENCE {
        algorithm      AlgorithmIdentifier,
        PublicKey      BIT STRING
    }

    AlgorithmIdentifier ::= SEQUENCE {
        algorithm      OBJECT IDENTIFIER,
        parameters     ANY DEFINED BY algorithm OPTIONAL
    }
    */
    byte[] pkcs1PublicKeyBytes =
    getPublicKey(signFile.getString("queryCompleteTime"),
        signFile.getString("publicKeyFingerprint"));
    byte[] signatureContent = Hex.decodeHex(signFile.getString("hashSignature"));

    // Transform the PKCS#1 formatted public key to x.509 format.
    RSAPublicKey rsaPublicKey = RSAPublicKey.getInstance(pkcs1PublicKeyBytes);
    AlgorithmIdentifier rsaEncryption = new
    AlgorithmIdentifier(PKCSObjectIdentifiers.rsaEncryption, null);
    SubjectPublicKeyInfo publicKeyInfo = new SubjectPublicKeyInfo(rsaEncryption,
    rsaPublicKey);

    // Create the PublicKey object needed for the signature validation
    PublicKey publicKey = KeyFactory.getInstance("RSA", "BC")
        .generatePublic(new X509EncodedKeySpec(publicKeyInfo.getEncoded()));

    // Verify signature
    Signature signature = Signature.getInstance("SHA256withRSA", "BC");
    signature.initVerify(publicKey);
    signature.update(hashListString.getBytes("UTF-8"));

```

```
    if (signature.verify(signatureContent)) {  
        System.out.println("Sign file signature is valid.");  
    } else {  
        System.err.println("Sign file signature failed validation.");  
    }  
  
    System.out.println("Sign file validation completed.");  
}  
}
```

Optimize CloudTrail Lake queries

This page provides guidance about how to optimize CloudTrail Lake queries to improve performance and reliability. It covers specific optimization techniques as well as workarounds for common query failures.

Topics

- [Recommendations for optimizing queries](#)
- [Workarounds for query failures](#)

Recommendations for optimizing queries

Follow the recommendations in this section to optimize your queries.

Recommendations:

- [Optimize aggregations](#)
- [Use approximation techniques](#)
- [Limit query results](#)
- [Optimize LIKE queries](#)
- [Use UNION ALL instead of UNION](#)
- [Include only required columns](#)
- [Reduce window function scope](#)

Optimize aggregations

Excluding redundant columns in GROUP BY clauses can improve performance as fewer columns require less memory. For example, in the following query, we can use the arbitrary function on

a redundant column like `eventType` to improve the performance. The `arbitrary` function on `eventType` is used to pick the field value randomly from the group as the value is the same and doesn't need to be included in the `GROUP BY` clause.

```
SELECT eventName, eventSource, arbitrary(eventType), count(*)
FROM $EDS_ID
GROUP BY eventName, eventSource
```

It's possible to improve the performance of the `GROUP BY` function by ordering the list of fields within the `GROUP BY` in decreasing order of their unique value count (cardinality). For example, while getting the number of events of a type in each AWS Region, performance can be improved by using the `eventName, awsRegion` order in the `GROUP BY` function instead of `awsRegion, eventName` as there are more unique values of `eventName` than there are of `awsRegion`.

```
SELECT eventName, awsRegion, count(*)
FROM $EDS_ID
GROUP BY eventName, awsRegion
```

Use approximation techniques

Whenever exact values are not needed for counting distinct values, use [approximate aggregate functions](#) to find the most frequent values. For example, [approx_distinct](#) uses much less memory and runs faster than the `COUNT(DISTINCT fieldName)` operation.

Limit query results

If only a sample response is needed for a query, restrict the results to a small number of rows by using the `LIMIT` condition. Otherwise, the query will return large results and take more time for query execution.

Using `LIMIT` along with `ORDER BY` can provide results for the top or bottom N records faster as it reduces the amount of memory needed and time taken to sort.

```
SELECT * FROM $EDS_ID
ORDER BY eventTime
LIMIT 100;
```

Optimize LIKE queries

You can use LIKE to find matching strings, but with long strings, this is compute intensive. The [regexp_like](#) function is in most cases a faster alternative.

Often, you can optimize a search by anchoring the substring that you're looking for. For example, if you're looking for a prefix, it's better to use 'substr%' instead of '%substr%' with the LIKE operator and '^substr' with the `regexp_like` function.

Use UNION ALL instead of UNION

UNION ALL and UNION are two ways to combine the results of two queries into one result but UNION removes duplicates. UNION needs to process all the records and find the duplicates, which is memory and compute intensive, but UNION ALL is a relatively quick operation. Unless you need to deduplicate records, use UNION ALL for the best performance.

Include only required columns

If you don't need a column, don't include it in your query. The less data a query has to process, the faster it will run. If you have queries that do `SELECT *` in the outermost query, you should change the `*` to a list of columns that you need.

The `ORDER BY` clause returns the results of a query in sorted order. When sorting larger amount of data, if required memory is not available, intermediate sorted results are written to disk which can slow down query execution. If you don't strictly need your result to be sorted, avoid adding an `ORDER BY` clause. Also, avoid adding `ORDER BY` to inner queries if it is not strictly necessary.

Reduce window function scope

[Window functions](#) keep all the records that they operate on in memory in order to calculate their result. When the window is very large, the window function can run out of memory. To make sure that queries run within the available memory limits, reduce the size of the windows that your window functions operate over by adding a `PARTITION BY` clause.

Sometimes queries with window functions can be rewritten without window functions. For example, instead of using `row_number` or `rank`, you can use aggregate functions like [max_by](#) or [min_by](#).

The following query finds the alias most recently assigned to each KMS key using `max_by`.

```
SELECT element_at(requestParameters, 'targetKeyId') as keyId,
```

```
max_by(element_at(requestParameters, 'aliasName'), eventTime) as mostRecentAlias
FROM $EDS_ID
WHERE eventsource = 'kms.amazonaws.com'
AND eventName in ('CreateAlias', 'UpdateAlias')
AND eventTime > DATE_ADD('week', -1, CURRENT_TIMESTAMP)
GROUP BY element_at(requestParameters, 'targetKeyId')
```

In this case, the `max_by` function returns the alias for the record with the latest event time within the group. This query runs faster and uses less memory than an equivalent query with a window function.

Workarounds for query failures

This section provides workarounds for common query failures.

Query failures:

- [Query fails because response is too large](#)
- [Query fails due to resource exhaustion](#)

Query fails because response is too large

A query can fail if the response is too large resulting in the message **Query response is too large**. If this occurs, you can reduce the aggregation scope.

Aggregation functions like `array_agg` can cause at least one row in the query response to be very large causing the query to fail. For example, using `array_agg(eventName)` instead of `array_agg(DISTINCT eventName)` will increase the response size a lot due to duplicated event names from the selected CloudTrail events.

Query fails due to resource exhaustion

If sufficient memory is not available during the execution of memory intensive operations like joins, aggregations and window functions, intermediate results are spilled to disk, but spilling slows query execution and can be insufficient to prevent the query from failing with **Query exhausted resources at this scale factor**. This can be fixed by retrying the query.

If the above errors persist even after optimizing the query, you can scope down the query using the `eventTime` of the events and execute the query multiple times in smaller intervals of the original query time range.

Run and manage CloudTrail Lake queries with the AWS CLI

You can use the AWS CLI to run and manage your CloudTrail Lake queries. When using the AWS CLI, remember that your commands run in the AWS Region configured for your profile. If you want to run the commands in a different Region, either change the default Region for your profile, or use the `--region` parameter with the command.

Available commands for CloudTrail Lake queries

Commands for running and managing queries in CloudTrail Lake include:

- [start-query](#) to run a query.
- [describe-query](#) to return metadata about a query.
- [generate-query](#) to produce a query from an English language prompt. For more information, see [Create CloudTrail Lake queries from natural language prompts](#).
- [get-query-results](#) to return query results for the specified query ID.
- [list-queries](#) to get a list queries for the specified event data store.
- [cancel-query](#) to cancel a running query.

For a list of available commands for CloudTrail Lake event data stores, see [Available commands for event data stores](#).

For a list of available commands for CloudTrail Lake dashboards, see [Available commands for dashboards](#).

For a list of available commands for CloudTrail Lake integrations, see [Available commands for CloudTrail Lake integrations](#).

Produce a query from a natural language prompt with the AWS CLI

Run the `generate-query` command to generate a query from an English prompt. For `--event-data-stores`, provide the ARN (or ID suffix of the ARN) of the event data store you want to query. You can only specify one event data store. For `--prompt`, provide the prompt in English.

```
aws cloudtrail generate-query
--event-data-stores arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-
ee54-4813-92d5-999aeEXAMPLE \
```

```
--prompt "Show me all console login events for the past week?"
```

If successful, the command outputs a SQL statement and provides a QueryAlias that you will use with the `start-query` command to run the query against your event data store.

```
{
  "QueryStatement": "SELECT * FROM $EDS_ID WHERE eventname = 'ConsoleLogin' AND
eventtime >= timestamp '2024-09-16 00:00:00' AND eventtime <= timestamp '2024-09-23
00:00:00' AND eventSource = 'signin.amazonaws.com'",
  "QueryAlias": "AWSCloudTrail-UUID"
}
```

Start a query with the AWS CLI

The following example AWS CLI **start-query** command runs a query on the event data store specified as an ID in the query statement and delivers the query results to a specified S3 bucket. The `--query-statement` parameter provides a SQL query, enclosed in single quotation marks. Optional parameters include `--delivery-s3-uri`, to deliver the query results to a specified S3 bucket. For more information about the query language you can use in CloudTrail Lake, see [CloudTrail Lake SQL constraints](#).

```
aws cloudtrail start-query
--query-statement 'SELECT eventID, eventTime FROM EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE
LIMIT 10'
--delivery-s3-uri "s3://aws-cloudtrail-lake-query-results-123456789012-us-east-1"
```

The response is a QueryId string. To get the status of a query, run **describe-query** using the QueryId value returned by **start-query**. If the query is successful, you can run **get-query-results** to get results.

Output

```
{
  "QueryId": "EXAMPLE2-0add-4207-8135-2d8a4EXAMPLE"
}
```

Note

Queries that run for longer than one hour might time out. You can still get partial results that were processed before the query timed out.

If you are delivering the query results to an S3 bucket using the optional `--delivery-s3-uri` parameter, the bucket policy must grant CloudTrail permission to deliver query results to the bucket. For information about manually editing the bucket policy, see [Amazon S3 bucket policy for CloudTrail Lake query results](#).

Get metadata about a query with the AWS CLI

The following example AWS CLI **describe-query** command gets metadata about a query, including query run time in milliseconds, number of events scanned and matched, total number of bytes scanned, and query status. The BytesScanned value matches the number of bytes for which your account is billed for the query, unless the query is still running. If the query results were delivered to an S3 bucket, the response also provides the S3 URI and the delivery status.

You must specify a value for either the `--query-id` or the `--query-alias` parameter. Specifying the `--query-alias` parameter returns information about the last query run for the alias.

```
aws cloudtrail describe-query --query-id EXAMPLEd-17a7-47c3-a9a1-eccf7EXAMPLE
```

The following is an example response.

```
{
  "QueryId": "EXAMPLE2-0add-4207-8135-2d8a4EXAMPLE",
  "QueryString": "SELECT eventID, eventTime FROM EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE
LIMIT 10",
  "QueryStatus": "RUNNING",
  "QueryStatistics": {
    "EventsMatched": 10,
    "EventsScanned": 1000,
    "BytesScanned": 35059,
    "ExecutionTimeInMillis": 3821,
    "CreationTime": "1598911142"
  }
}
```

Get query results with the AWS CLI

The following example AWS CLI **get-query-results** command gets event data results of a query. You must specify the `--query-id` returned by the **start-query** command. The BytesScanned value matches the number of bytes for which your account is billed for the query, unless the query

is still running. Optional parameters include `--max-query-results`, to specify a maximum number of results that you want the command to return on a single page. If there are more results than your specified `--max-query-results` value, run the command again adding the returned `NextToken` value to get the next page of results.

```
aws cloudtrail get-query-results
--query-id EXAMPLEd-17a7-47c3-a9a1-eccf7EXAMPLE
```

Output

```
{
  "QueryStatus": "RUNNING",
  "QueryStatistics": {
    "ResultsCount": 244,
    "TotalResultsCount": 1582,
    "BytesScanned": 27044
  },
  "QueryResults": [
    {
      "key": "eventName",
      "value": "StartQuery",
    }
  ],
  "QueryId": "EXAMPLE2-0add-4207-8135-2d8a4EXAMPLE",
  "QueryString": "SELECT eventID, eventTime FROM EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE
LIMIT 10",
  "NextToken": "20add42078135EXAMPLE"
}
```

List all queries on an event data store with the AWS CLI

The following example AWS CLI **list-queries** command returns a list of queries and query statuses on a specified event data store for the past seven days. You must specify an ARN or the ID suffix of an ARN value for `--event-data-store`. Optionally, to shorten the list of results, you can specify a time range, formatted as timestamps, by adding `--start-time` and `--end-time` parameters, and a `--query-status` value. Valid values for `QueryStatus` include `QUEUED`, `RUNNING`, `FINISHED`, `FAILED`, or `CANCELLED`.

list-queries also has optional pagination parameters. Use `--max-results` to specify a maximum number of results that you want the command to return on a single page. If there are more

results than your specified `--max-results` value, run the command again adding the returned `NextToken` value to get the next page of results.

```
aws cloudtrail list-queries
--event-data-store EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE
--query-status CANCELLED
--start-time 1598384589
--end-time 1598384602
--max-results 10
```

Output

```
{
  "Queries": [
    {
      "QueryId": "EXAMPLE2-0add-4207-8135-2d8a4EXAMPLE",
      "QueryStatus": "CANCELLED",
      "CreationTime": 1598911142
    },
    {
      "QueryId": "EXAMPLE2-4e89-9230-2127-5dr3aEXAMPLE",
      "QueryStatus": "CANCELLED",
      "CreationTime": 1598296624
    }
  ],
  "NextToken": "20add42078135EXAMPLE"
}
```

Cancel a running query with the AWS CLI

The following example AWS CLI **cancel-query** command cancels a query with a status of **RUNNING**. You must specify a value for `--query-id`. When you run **cancel-query**, the query status might show as **CANCELLED** even if the **cancel-query** operation is not yet finished.

Note

A canceled query can incur charges. Your account is still charged for the amount of data that was scanned before you canceled the query.

The following is a CLI example.

```
aws cloudtrail cancel-query
--query-id EXAMPLEd-17a7-47c3-a9a1-ecccf7EXAMPLE
```

Output

```
QueryId -> (string)
QueryStatus -> (string)
```

CloudTrail Lake SQL constraints

CloudTrail Lake queries are SQL strings. This section provides information about the supported functions, operators, and schemas.

Only SELECT statements are allowed. No query strings can change or mutate data.

The CloudTrail Lake syntax for a SELECT statement is as follows. The event data store ID—the ID portion of the event data store's ARN—is specified for the FROM value.

```
SELECT [ DISTINCT ] columns [ Aggregate ]
[ FROM table event_data_store_ID ]
[ WHERE columns [ Conditions ] ]
[ GROUP BY columns [ DISTINCT | Aggregate ] ]
[ HAVING columns [ Aggregate | Conditions ] ]
[ ORDER BY columns [ Aggregate | ASC | DESC | NULLS | FIRST | LAST ] ]
[ LIMIT [ INT ] ]
```

CloudTrail Lake supports all valid Trino SQL SELECT statements, functions, and operators. For more information about the supported SQL functions and operators, see [Functions and Operators](#) on the Trino documentation website.

The CloudTrail console provides a number of sample queries that can help you get started writing your own queries. For more information, see [View sample queries with the CloudTrail console](#).

For information about how to optimize your queries, see [Optimize CloudTrail Lake queries](#).

Topics

- [Supported functions, condition and join operators](#)
- [Advanced, multi-table query support](#)

Supported functions, condition and join operators

Supported functions

CloudTrail Lake supports all Trino functions. For more information about the supported functions, see [Functions and Operators](#) on the Trino documentation website.

Supported condition operators

The following are supported condition operators.

```
AND
OR
IN
NOT
IS (NOT) NULL
LIKE
BETWEEN
GREATEST
LEAST
IS DISTINCT FROM
IS NOT DISTINCT FROM
<
>
<=
>=
<>
!=
( conditions ) #parenthesised conditions
```

Supported join operators

The following are the supported JOIN operators. For more information about running multi-table queries, see [Advanced, multi-table query support](#).

```
UNION
UNION ALL
EXCEPT
INTERSECT
LEFT JOIN
RIGHT JOIN
INNER JOIN
```

Advanced, multi-table query support

CloudTrail Lake supports advanced query language across multiple event data stores.

- [UNION | UNION ALL | EXCEPT | INTERSECT](#)
- [LEFT | RIGHT | INNER JOIN](#)

To run your query, use the **start-query** command in the AWS CLI. The following is an example, using one of the sample queries in this section.

```
aws cloudtrail start-query
--query-statement "Select eventId, eventName from EXAMPLEf852-4e8f-8bd1-bcf6cEXAMPLE
UNION Select eventId, eventName from EXAMPLEg741-6y1x-9p3v-bnh6iEXAMPLE UNION ALL
Select eventId, eventName from EXAMPLEb529-4e8f913d-6m2z-1kp5sEXAMPLE ORDER BY eventId
LIMIT 10;"
```

The response is a QueryId string. To get the status of a query, run `describe-query`, using the QueryId value returned by `start-query`. If the query is successful, you can run `get-query-results` to get results.

UNION | UNION ALL | EXCEPT | INTERSECT

The following is an example query that uses `UNION` and `UNION ALL` to find events by their event ID and event name in three event data stores, EDS1, EDS2, and EDS3. The results are selected from each event data store first, then results are concatenated, ordered by event ID, and limited to ten events.

```
Select eventId, eventName from EDS1
UNION
Select eventId, eventName from EDS2
UNION ALL
Select eventId, eventName from EDS3
ORDER BY eventId LIMIT 10;
```

LEFT | RIGHT | INNER JOIN

The following is an example query that uses `LEFT JOIN` to find all events from an event data store named `eds2`, mapped to `edsB`, that match those in a primary (left) event data store, `edsA`. The returned events occur on or before January 1, 2020, and only the event names are returned.

```
SELECT edsA.eventName, edsB.eventName, element_at(edsA.map, 'test')
FROM eds1 as edsA
LEFT JOIN eds2 as edsB
ON edsA.eventId = edsB.eventId
WHERE edsA.eventtime <= '2020-01-01'
ORDER BY edsB.eventName;
```

Supported SQL schemas for event data stores

The following sections provide the supported SQL schema for each event data store type.

Topics

- [Supported schema for CloudTrail event record fields](#)
- [Supported schema for CloudTrail Insights event record fields](#)
- [Supported schema for AWS Config configuration item record fields](#)
- [Supported schema for AWS Audit Manager evidence record fields](#)
- [Supported schema for non-AWS event fields](#)

Supported schema for CloudTrail event record fields

The following is the valid SQL schema for CloudTrail management, data, and network activity event record fields. For more information about CloudTrail event record fields, see [CloudTrail record contents for management, data, and network activity events](#).

```
[
  {
    "Name": "eventversion",
    "Type": "string"
  },
  {
    "Name": "useridentity",
    "Type":
      "struct<type:string,principalid:string,arn:string,accountid:string,accesskeyid:string,
      username:string,sessioncontext:struct<attributes:struct<creationdate:timestamp,
      mfaauthenticated:string>,sessionissuer:struct<type:string,principalid:string,arn:string,
```

```

accountid:string,username:string>,webidfederateddata:struct<federatedprovider:string,
attributes:map<string,string>>,sourceidentity:string,ec2roledelivery:string,
ec2issuedinvpc:string>,onbehalfof:struct<userid:string,identitystorearn:string>,
inscopeof:struct<sourcearn:string,sourceaccount:string,issuertype:string,
credentialissuedto:string>,invokedby:string,identityprovider:string>"
  },
  {
    "Name": "eventtime",
    "Type": "timestamp"
  },
  {
    "Name": "eventsources",
    "Type": "string"
  },
  {
    "Name": "eventname",
    "Type": "string"
  },
  {
    "Name": "awsregion",
    "Type": "string"
  },
  {
    "Name": "sourceipaddress",
    "Type": "string"
  },
  {
    "Name": "useragent",
    "Type": "string"
  },
  {
    "Name": "errorcode",
    "Type": "string"
  },
  {
    "Name": "errormessage",
    "Type": "string"
  },
  {
    "Name": "requestparameters",

```



```

        "Type": "map<string,string>"
    },
    {
        "Name": "responseelements",
        "Type": "map<string,string>"
    },
    {
        "Name": "additionaleventdata",
        "Type": "map<string,string>"
    },
    {
        "Name": "requestid",
        "Type": "string"
    },
    {
        "Name": "eventid",
        "Type": "string"
    },
    {
        "Name": "readonly",
        "Type": "boolean"
    },
    {
        "Name": "resources",
        "Type":
"array<struct<accountid:string,type:string,arn:string,arnprefix:string>>"
    },
    {
        "Name": "eventtype",
        "Type": "string"
    },
    {
        "Name": "apiversion",
        "Type": "string"
    },
    {
        "Name": "managementevent",
        "Type": "boolean"
    },
    {
        "Name": "recipientaccountid",
        "Type": "string"
    },
    {

```

```

        "Name": "sharedeventid",
        "Type": "string"
    },
    {
        "Name": "annotation",
        "Type": "string"
    },
    {
        "Name": "vpcendpointid",
        "Type": "string"
    },
    {
        "Name": "vpcendpointaccountid",
        "Type": "string"
    },
    {
        "Name": "serviceeventdetails",
        "Type": "map<string,string>"
    },
    {
        "Name": "addendum",
        "Type": "map<string,string>"
    },
    {
        "Name": "edgedevicedetails",
        "Type": "map<string,string>"
    },
    {
        "Name": "insightdetails",
        "Type": "map<string,string>"
    },
    {
        "Name": "eventcategory",
        "Type": "string"
    },
    {
        "Name": "tlsdetails",
        "Type":
"struct<tlsversion:string,ciphersuite:string,clientprovidedhostheader:string>"
    },
    {
        "Name": "sessioncredentialfromconsole",
        "Type": "string"
    },
    },

```

```
[
  {
    "Name": "eventjson",
    "Type": "string"
  },
  {
    "Name": "eventjsonchecksum",
    "Type": "string"
  }
]
```

Supported schema for CloudTrail Insights event record fields

The following is the valid SQL schema for Insights event record fields. For Insights events, the value of `eventcategory` is `Insight`, and the value of `eventtype` is `AwsCloudTrailInsight`. For descriptions of these fields, see [CloudTrail record contents for Insights events for event data stores](#).

Note

The `insightvalue`, `insightaverage`, `baselinevalue`, and `baselineaverage` fields within the `attributions` field of `insightContext` will begin to be deprecated on June 23, 2025.

```
[
  {
    "Name": "eventversion",
    "Type": "string"
  },
  {
    "Name": "eventcategory",
    "Type": "string"
  },
  {
    "Name": "eventtype",
    "Type": "string"
  },
  {
    "Name": "eventid",
    "Type": "string"
  },
  {
    "Name": "eventtime",
```

```
    "Type": "timestamp"
  },
  {
    "Name": "awsregion",
    "Type": "string"
  },
  {
    "Name": "recipientaccountid",
    "Type": "string"
  },
  {
    "Name": "sharedeventid",
    "Type": "string"
  },
  {
    "Name": "addendum",
    "Type": "map<string,string>"
  },
  {
    "Name": "insightssource",
    "Type": "string"
  },
  {
    "Name": "insightstate",
    "Type": "string"
  },
  {
    "Name": "insighteventsources",
    "Type": "string"
  },
  {
    "Name": "insighteventname",
    "Type": "string"
  },
  {
    "Name": "insighterrorcode",
    "Type": "string"
  },
  {
    "Name": "insighttype",
    "Type": "string"
  },
  {
    "Name": "insightContext",
```

```

        "Type": "struct<baselineaverage:double,insightaverage:double,
            baselineduration:integer,insightduration:integer,
            attributions:struct<attribute:string,insightvalue:string,
            insightaverage:double,baselinevalue:string,baselineaverage:double,
            insight:struct<value:string,average:double>,
            baseline:struct<value:string,average:double>>>"
    }
]

```

Supported schema for AWS Config configuration item record fields

The following is the valid SQL schema for configuration item record fields. For configuration items, the value of eventcategory is ConfigurationItem, and the value of eventtype is AwsConfigurationItem.

```

[
  {
    "Name": "eventversion",
    "Type": "string"
  },
  {
    "Name": "eventcategory",
    "Type": "string"
  },
  {
    "Name": "eventtype",
    "Type": "string"
  },
  {
    "Name": "eventid",
    "Type": "string"
  },
  {
    "Name": "eventtime",
    "Type": "timestamp"
  },
  {
    "Name": "awsregion",
    "Type": "string"
  },
  {
    "Name": "recipientaccountid",
    "Type": "string"
  },
]

```

```

{
  "Name": "addendum",
  "Type": "map<string,string>"
},
{
  "Name": "eventdata",
  "Type": "struct<configurationitemversion:string,configurationitemcapturetime:
string,configurationitemstatus:string,configurationitemstateid:string,accountid:string,
resourcetype:string,resourceid:string,resourcename:string,arn:string,awsregion:string,
availabilityzone:string,resourcecreationtime:string,configuration:map<string,string>,
supplementaryconfiguration:map<string,string>,relatedevents:string,
relationships:struct<name:string,resourcetype:string,resourceid:string,
resourcename:string>,tags:map<string,string>>"
}
]

```

Supported schema for AWS Audit Manager evidence record fields

The following is the valid SQL schema for Audit Manager evidence record fields. For Audit Manager evidence record fields, the value of `eventcategory` is `Evidence`, and the value of `eventtype` is `AwsAuditManagerEvidence`. For more information about aggregating evidence in CloudTrail Lake using Audit Manager, see [Evidence finder](#) in the *AWS Audit Manager User Guide*.

```

[
  {
    "Name": "eventversion",
    "Type": "string"
  },
  {
    "Name": "eventcategory",
    "Type": "string"
  },
  {
    "Name": "eventtype",
    "Type": "string"
  },
  {
    "Name": "eventid",
    "Type": "string"
  },
]

```

```

{
  "Name": "eventtime",
  "Type": "timestamp"
},
{
  "Name": "awsregion",
  "Type": "string"
},
{
  "Name": "recipientaccountid",
  "Type": "string"
},
{
  "Name": "addendum",
  "Type": "map<string,string>"
},
{
  "Name": "eventdata",
  "Type":
"struct<attributes:map<string,string>,awsaccountid:string,awsorganization:string,
compliancecheck:string,datasource:string,eventname:string,eventsources:string,
evidenceawsaccountid:string,evidencebytype:string,iamid:string,evidenceid:string,
time:timestamp,assessmentid:string,controlsetid:string,controlid:string,
controlname:string,controldomainname:string,frameworkname:string,frameworkid:string,
service:string,servicecategory:string,resourcearn:string,resourcetype:string,
evidencefolderid:string,description:string,manualevidences3resourcepath:string,
evidencefoldername:string,resourcecompliancecheck:string>"
}
]

```

Supported schema for non-AWS event fields

The following is the valid SQL schema for non-AWS events. For non-AWS events, the value of eventcategory is ActivityAuditLog, and the value of eventtype is ActivityLog.

```

[
  {

```

```

        "Name": "eventversion",
        "Type": "string"
    },
    {
        "Name": "eventcategory",
        "Type": "string"
    },
    {
        "Name": "eventtype",
        "Type": "string"
    },
    {
        "Name": "eventid",
        "Type": "string"
    },
    {
        "Name": "eventtime",
        "Type": "timestamp"
    },
    {
        "Name": "awsregion",
        "Type": "string"
    },
    {
        "Name": "recipientaccountid",
        "Type": "string"
    },
    {
        "Name": "addendum",
        "Type":
"struct<reason:string,updatedfields:string,originalUID:string,originaleventid:string>"
    },
    {
        "Name": "metadata",
        "Type": "struct<ingestiontime:string,channelarn:string>"
    },
    {
        "Name": "eventdata",
        "Type": "struct<version:string,useridentity:struct<type:string,
principalid:string,details:map<string,string>>,useragent:string,eventsource:string,
eventname:string,eventtime:string,uid:string,requestparameters:map<string,string>>,
responseelements":map<string,string>>,errorcode:string,errormessage:string,sourceipaddress:stri

```



```
    recipientaccountid:string,additionalEventData":map<string,string>>"
  }
]
```

Supported CloudWatch metrics

CloudTrail Lake supports Amazon CloudWatch metrics. CloudWatch is a monitoring service for AWS resources. You can use CloudWatch to collect and track metrics, set alarms, and automatically react to changes in your AWS resources.

The AWS/CloudTrail namespace includes the following metrics for CloudTrail Lake.

Metric	Description	Units
HourlyDataIngested	The amount of data ingested into the event data store during the last hour. This metric is updated every hour. This metric is available for all event data store types.	Bytes
TotalDataRetained	The amount of data retained in the event data store during its entire retention period. This metric is updated nightly. This metric is available for all event data store types.	Bytes
TotalStorageBytes	The total compressed bytes in the event data store as of the current day. This metric is available for all event data store types.	Bytes
TotalPaidStorageBytes	For event data stores using the one-year extendable	Bytes

Metric	Description	Units
	retention pricing option, this is the total compressed bytes after 366 days to the maximum retention period configured for the event data store. For event data stores using the one-year extendable retention pricing option, storage is included at no additional cost with ingestion pricing for the first 366 days, which is the default retention period for the event data store. After 366 days, storage is pay-as-you-go. For information about pricing, see AWS CloudTrail Pricing. This metric is only available for event data stores using the one-year extendable retention pricing option.	
HourlyEventsAnalyzed	The total number of events analyzed by CloudTrail Insights in the event data store. This metric is updated every hour. This metric is for CloudTrail event data stores that enable CloudTrail Insights.	Count

For more information about CloudWatch metrics, see the following topics.

- [Using Amazon CloudWatch metrics](#)
- [Using Amazon CloudWatch alarms](#)

Working with CloudTrail trails

Trails capture a record of AWS activities, delivering and storing these events in an Amazon S3 bucket, with optional delivery to [CloudWatch Logs](#) and [Amazon EventBridge](#).

You can deliver one copy of your ongoing management events to your S3 bucket at no charge from CloudTrail by creating a trail, however, there are Amazon S3 storage charges. For more information about CloudTrail pricing, see [AWS CloudTrail Pricing](#). For information about Amazon S3 pricing, see [Amazon S3 Pricing](#).

You can create both multi-Region and single-Region trails for your AWS account.

Multi-Region trails

When you create a multi-Region trail, CloudTrail records events in all AWS Regions that are [enabled](#) in your AWS account and delivers the CloudTrail event log files to an S3 bucket that you specify. As a best practice, we recommend creating a multi-Region trail because it captures activity in all enabled Regions. All trails created using the CloudTrail console are multi-Region trails. You can convert a single-Region trail to a multi-Region trail by using the AWS CLI. For more information, see [Understanding multi-Region trails and opt-in Regions](#), [Creating a trail with the console](#), and [Converting a single-Region trail to a multi-Region trail](#).

Single-Region trails

When you create a single-Region trail, CloudTrail records the events in that Region only. It then delivers the CloudTrail event log files to an Amazon S3 bucket that you specify. You can only create a single-Region trail by using the AWS CLI. If you create additional single trails, you can have those trails deliver CloudTrail event log files to the same S3 bucket or to separate buckets. This is the default option when you create a trail using the AWS CLI or the CloudTrail API. For more information, see [Creating, updating, and managing trails with the AWS CLI](#).

Note

For both types of trails, you can specify an Amazon S3 bucket from any Region.

If you have created an organization in AWS Organizations, you can create an *organization trail* that logs all events for all AWS accounts in that organization. Organization trails can apply to all

AWS Regions, or the current Region. Organization trails must be created using the management account or delegated administrator account, and when specified as applying to an organization, are automatically applied to all member accounts in the organization. Member accounts can see the organization trail, but cannot modify or delete it. By default, member accounts do not have access to the log files for an organization trail in the Amazon S3 bucket. For more information, see [Creating a trail for an organization](#).

Topics

- [Creating a trail for your AWS account](#)
- [Creating a trail for an organization](#)
- [Understanding multi-Region trails and opt-in Regions](#)
- [Copying trail events to CloudTrail Lake](#)
- [Getting and viewing your CloudTrail log files](#)
- [Configuring Amazon SNS notifications for CloudTrail](#)
- [Using AWS CloudTrail with interface VPC endpoints](#)
- [Naming requirements for CloudTrail resources, S3 buckets, and KMS keys](#)
- [AWS account closure and trails](#)

Creating a trail for your AWS account

When you create a trail, you enable ongoing delivery of events as log files to an Amazon S3 bucket that you specify. Creating a trail has many benefits, including:

- A record of events that extends past 90 days.
- The option to automatically monitor and alarm on specified events by sending log events to Amazon CloudWatch Logs.
- The option to query logs and analyze AWS service activity with Amazon Athena.

Beginning on April 12, 2019, you can view trails only in the AWS Regions where they log events. If you create a [multi-Region](#) trail, it appears in the console in all AWS Regions that are [enabled](#) in your account. If you create a trail that only logs events in a single Region, you can view and manage it only in that Region. As a best practice, we recommend creating a multi-Region trail because it captures activity in all enabled Regions. All trails created using the CloudTrail console are multi-Region trails. To create a single-Region trail, you must use the AWS CLI.

If you use AWS Organizations, you can create a trail that will log events for all AWS accounts in the organization. A trail with the same name will be created in each member account, and events from each trail will be delivered to the Amazon S3 bucket that you specify.

Note

Only the management account or delegated administrator account for an organization can create a trail for the organization. Creating a trail for an organization automatically enables integration between CloudTrail and Organizations. For more information, see [Creating a trail for an organization](#).

If you misconfigure your trail (for example, the S3 bucket is unreachable), CloudTrail will attempt to redeliver the log files to your S3 bucket for 30 days, and these attempted-to-deliver events will be subject to standard CloudTrail charges. To avoid charges on a misconfigured trail, you need to delete the trail.

Topics

- [Creating and updating a trail with the console](#)
- [Creating, updating, and managing trails with the AWS CLI](#)
- [Creating multiple trails](#)

Creating and updating a trail with the console

You can use the CloudTrail console to create, update, or delete your trails. Trails created using the console are multi-Region. To create a trail that logs events in only one AWS Region, [use the AWS CLI](#).

You can create up to five trails for each Region. After you create a trail, CloudTrail automatically starts logging API calls and related events in your account to the Amazon S3 bucket that you specify.

You can change the following settings for your trail using the CloudTrail console:

- You can change the S3 bucket location and specify a prefix.
- The management account for an AWS Organizations organization can convert an account-level trail to an organization trail, or can convert an organization trail to an account-level trail.

- You can enable or disable KMS key encryption.
- You can enable or disable [log file validation](#). Log file validation allows you to determine whether a log file was modified, deleted, or unchanged after CloudTrail delivered it. By default, log file validation is enabled.
- You can configure a trail to send notifications to an Amazon SNS topic.
- You can configure a trail to send events to a CloudWatch Logs log group. Both the log group and IAM role must exist in your own account.
- You can update settings for management events, data events, network activity events, and Insights events.
- You can add or remove tags. You can add up to 50 tag key pairs to help you identify your trails.

Using the CloudTrail console to create or update a trail provides the following advantages.

- If this is your first time creating a trail, using the CloudTrail console allows you to view the available feature and options.
- If you are configuring a trail to log data events, using the CloudTrail console allows you to view the available data types. For more information, see [Logging data events](#).
- If you are configuring a trail to network activity events, using the CloudTrail console allows you to view the available event sources. For more information, see [Logging network activity events](#).

For information specific to creating a trail for an organization in AWS Organizations, see [Creating a trail for an organization](#).

Topics

- [Creating a trail with the CloudTrail console](#)
- [Updating a trail with the CloudTrail console](#)
- [Deleting a trail with the CloudTrail console](#)
- [Turning off logging for a trail](#)

Creating a trail with the CloudTrail console

A trail can be applied to all AWS Regions that are [enabled](#) in your AWS account, or can be applied to a single Region. A trail that applies to all AWS Regions that are enabled in your AWS account is referred to as a *multi-Region trail*. As a best practice, we recommend creating a multi-Region

trail because it captures activity in all enabled Regions. All trails created using the CloudTrail console are multi-Region trails. You can only create a single-Region trail using the AWS CLI or [CreateTrail](#) API operation.

 Note

After you create a trail, you can configure other AWS services to further analyze and act upon the event data collected in CloudTrail logs. For more information, see [AWS service integrations with CloudTrail logs](#).

Topics

- [Creating a trail with the console](#)
- [Next steps](#)

Creating a trail with the console

Use the following procedure to create a multi-Region trail. To log events in a single Region (not recommended), [use the AWS CLI](#).

To create a CloudTrail trail with the AWS Management Console

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. On the CloudTrail service home page, the **Trails** page, or the **Trails** section of the **Dashboard** page, choose **Create trail**.
3. On the **Create Trail** page, for **Trail name**, type a name for your trail. For more information, see [Naming requirements for CloudTrail resources, S3 buckets, and KMS keys](#).
4. If this is an AWS Organizations organization trail, you can enable the trail for all accounts in your organization. To see this option, you must sign in to the console with a user or role in the management or delegated administrator account. To successfully create an organization trail, be sure that the user or role has [sufficient permissions](#). For more information, see [Creating a trail for an organization](#).
5. For **Storage location**, choose **Create new S3 bucket** to create a bucket. When you create a bucket, CloudTrail creates and applies the required bucket policies. If you choose to create a new S3 bucket, your IAM policy needs to include permission for the

s3:PutEncryptionConfiguration action because by default server-side encryption is enabled for the bucket.

 Note

If you chose **Use existing S3 bucket**, specify a bucket in **Trail log bucket name**, or choose **Browse** to choose a bucket in your own account. If you want to use a bucket in another account, you'll need to specify the bucket name. The bucket policy must grant CloudTrail permission to write to it. For information about manually editing the bucket policy, see [Amazon S3 bucket policy for CloudTrail](#).

To make it easier to find your logs, create a new folder (also known as a *prefix*) in an existing bucket to store your CloudTrail logs. Enter the prefix in **Prefix**.

- For **Log file SSE-KMS encryption**, choose **Enabled** if you want to encrypt your log files and digest files using SSE-KMS encryption instead of SSE-S3 encryption. The default is **Enabled**. If you don't enable SSE-KMS encryption, your log files and digest files are encrypted using SSE-S3 encryption. For more information about SSE-KMS encryption, see [Using server-side encryption with AWS Key Management Service \(SSE-KMS\)](#). For more information about SSE-S3 encryption, see [Using Server-Side Encryption with Amazon S3-Managed Encryption Keys \(SSE-S3\)](#).

If you enable SSE-KMS encryption, choose a **New** or **Existing** AWS KMS key. In **AWS KMS Alias**, specify an alias, in the format `alias/MyAliasName`. For more information, see [Updating a resource to use your KMS key with the console](#). CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

 Note

You can also type the ARN of a key from another account. For more information, see [Updating a resource to use your KMS key with the console](#). The key policy must allow CloudTrail to use the key to encrypt your log files and digest files, and allow the users you specify to read log files or digest files in unencrypted form. For information about manually editing the key policy, see [Configure AWS KMS key policies for CloudTrail](#).

- In **Additional settings**, configure the following.

- a. For **Log file validation**, choose **Enabled** to have log digests delivered to your S3 bucket. You can use the digest files to verify that your log files did not change after CloudTrail delivered them. For more information, see [Validating CloudTrail log file integrity](#).
- b. For **SNS notification delivery**, choose **Enabled** to be notified each time a log is delivered to your bucket. CloudTrail stores multiple events in a log file. SNS notifications are sent for every log file, not for every event. For more information, see [Configuring Amazon SNS notifications for CloudTrail](#).

If you enable SNS notifications, for **Create a new SNS topic**, choose **New** to create a topic, or choose **Existing** to use an existing topic. If you are creating a multi-Region trail, SNS notifications for log file deliveries from all enabled Regions are sent to the single SNS topic that you create.

If you choose **New**, CloudTrail specifies a name for the new topic for you, or you can type a name. If you choose **Existing**, choose an SNS topic from the drop-down list. You can also enter the ARN of a topic from another Region or from an account with appropriate permissions. For more information, see [Amazon SNS topic policy for CloudTrail](#).

If you create a topic, you must subscribe to the topic to be notified of log file delivery. You can subscribe from the Amazon SNS console. Due to the frequency of notifications, we recommend that you configure the subscription to use an Amazon SQS queue to handle notifications programmatically. For more information, see [Getting started with Amazon SNS](#) in the *Amazon Simple Notification Service Developer Guide*.

8. Optionally, configure CloudTrail to send log files to CloudWatch Logs by choosing **Enabled** in **CloudWatch Logs**. For more information, see [Sending events to CloudWatch Logs](#).
 - a. If you enable integration with CloudWatch Logs, choose **New** to create a new log group, or **Existing** to use an existing one. If you choose **New**, CloudTrail specifies a name for the new log group for you, or you can type a name.
 - b. If you choose **Existing**, choose a log group from the drop-down list.
 - c. Choose **New** to create a new IAM role for permissions to send logs to CloudWatch Logs. Choose **Existing** to choose an existing IAM role from the drop-down list. The policy statement for the new or existing role is displayed when you expand **Policy document**. For more information about this role, see [Role policy document for CloudTrail to use CloudWatch Logs for monitoring](#).

 Note

- When you configure a trail, you can choose an S3 bucket and SNS topic that belong to another account. However, if you want CloudTrail to deliver events to a CloudWatch Logs log group, you must choose a log group that exists in your current account.
- Only the management account can configure a CloudWatch Logs log group for an organization trail using the console. The delegated administrator can configure a CloudWatch Logs log group using the AWS CLI or CloudTrail `CreateTrail` or `UpdateTrail` API operations.

9. For **Tags**, you can add up to 50 tag key pairs to help you identify, sort, and control access to your trail. Tags can help you identify both your CloudTrail trails and the Amazon S3 buckets that contain CloudTrail log files. You can then use resource groups for your CloudTrail resources. For more information, see [AWS Resource Groups](#) and [Tags](#).
10. On the **Choose log events** page, choose the event types that you want to log. For **Management events**, do the following.
 - a. For **API activity**, choose if you want your trail to log **Read** events, **Write** events, or both. For more information, see [Management events](#).
 - b. Choose **Exclude AWS KMS events** to filter AWS Key Management Service (AWS KMS) events out of your trail. The default setting is to include all AWS KMS events.

The option to log or exclude AWS KMS events is available only if you log management events on your trail. If you choose not to log management events, AWS KMS events are not logged, and you cannot change AWS KMS event logging settings.

AWS KMS actions such as `Encrypt`, `Decrypt`, and `GenerateDataKey` typically generate a large volume (more than 99%) of events. These actions are now logged as **Read** events. Low-volume, relevant AWS KMS actions such as `Disable`, `Delete`, and `ScheduleKey` (which typically account for less than 0.5% of AWS KMS event volume) are logged as **Write** events.

To exclude high-volume events like `Encrypt`, `Decrypt`, and `GenerateDataKey`, but still log relevant events such as `Disable`, `Delete` and `ScheduleKey`, choose to log **Write** management events, and clear the check box for **Exclude AWS KMS events**.

- c. Choose **Exclude Amazon RDS Data API events** to filter Amazon Relational Database Service Data API events out of your trail. The default setting is to include all Amazon RDS Data API events. For more information about Amazon RDS Data API events, see [Logging Data API calls with AWS CloudTrail](#) in the *Amazon RDS User Guide for Aurora*.
11. To log data events, choose **Data events**. Additional charges apply for logging data events. For more information, see [AWS CloudTrail Pricing](#).

12.

⚠ Important

Steps 12-16 are for configuring data events using advanced event selectors, which is the default. Advanced event selectors let you configure more [resource types](#) and offer fine-grained control over which data events your trail captures. If you opted to use basic event selectors, complete the steps in [Configure data event settings using basic event selectors](#), then return to step 17 of this procedure.

For **Resource type**, choose the resource type on which you want to log data events. For more information about available resource types, see [Data events](#).

13. Choose a log selector template. You can choose a predefined template, or choose **Custom** to define your own event collection conditions.

You can choose from the following predefined templates:

- **Log all events** – Choose this template to log all events.
- **Log only read events** – Choose this template to log only read events. Read-only events are events that do not change the state of a resource, such as `Get*` or `Describe*` events.
- **Log only write events** – Choose this template to log only write events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events.
- **Log only AWS Management Console events** – Choose this template to log only events originating from the AWS Management Console.
- **Exclude AWS service initiated events** – Choose this template to exclude AWS service events, which have an `eventType` of `AwsServiceEvent`, and events initiated with AWS service-linked roles (SLRs).

 Note

Choosing a predefined template for S3 buckets enables data event logging for all buckets currently in your AWS account and any buckets you create after you finish creating the trail. It also enables logging of data event activity performed by any IAM identity in your AWS account, even if that activity is performed on a bucket that belongs to another AWS account.

If the trail applies only to one Region, choosing a predefined template that logs all S3 buckets enables data event logging for all buckets in the same Region as your trail and any buckets you create later in that Region. It will not log data events for Amazon S3 buckets in other Regions in your AWS account.

If you are creating a multi-Region trail choosing a predefined template for Lambda functions enables data event logging for all functions currently in your AWS account, and any Lambda functions you might create in any Region after you finish creating the trail. If you are creating a trail for a single Region (done by using the AWS CLI), this selection enables data event logging for all functions currently in that Region in your AWS account, and any Lambda functions you might create in that Region after you finish creating the trail. It does not enable data event logging for Lambda functions created in other Regions.

Logging data events for all functions also enables logging of data event activity performed by any IAM identity in your AWS account, even if that activity is performed on a function that belongs to another AWS account.

14. (Optional) In **Selector name**, enter a name to identify your selector. The selector name is a descriptive name for an advanced event selector, such as "Log data events for only two S3 buckets". The selector name is listed as Name in the advanced event selector and is viewable if you expand the **JSON view**.
15. If you selected **Custom**, in **Advanced event selectors** build an expression based on the values of advanced event selector fields.

 Note

Selectors don't support the use of wildcards like * . To match multiple values with a single condition, you may use `StartsWith`, `EndsWith`, `NotStartsWith`, or `NotEndsWith` to explicitly match the beginning or end of the event field.

- a. Choose from the following fields.
- **readOnly** - readOnly can be set to **equals** a value of true or false. Read-only data events are events that do not change the state of a resource, such as Get* or Describe* events. Write events add, change, or delete resources, attributes, or artifacts, such as Put*, Delete*, or Write* events. To log both read and write events, don't add a readOnly selector.
 - **eventName** - eventName can use any operator. You can use it to include or exclude any data event logged to CloudTrail, such as PutBucket, GetItem, or GetSnapshotBlock.
 - **eventSource** – The event source to include or exclude. This field can use any operator.
 - **eventType** – The event type to include or exclude. For example, you can set this field to **not equals** AwsServiceEvent to exclude [AWS service events](#). For a list of event types, see [eventType](#) in [CloudTrail record contents for management, data, and network activity events](#).
 - **sessionCredentialFromConsole** – Include or exclude events originating from an AWS Management Console session. This field can be set to **equals** or **not equals** with a value of true.
 - **userIdentity.arn** – Include or exclude events for actions taken by specific IAM identities. For more information, see [CloudTrail userIdentity element](#).
 - **resources.ARN** - You can use any operator with resources.ARN, but if you use **equals** or **does not equal**, the value must exactly match the ARN of a valid resource of the type you've specified in the template as the value of resources.type.

 Note

You can't use the resources.ARN field to filter resource types that do not have ARNs.

For more information about the ARN formats of data event resources, see [Actions, resources, and condition keys for AWS services](#) in the *Service Authorization Reference*.

- b. For each field, choose + **Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions. For example, to exclude data events

for two S3 buckets from data events that are logged on your event data store, you can set the field to **resources.ARN**, set the operator for **does not start with**, and then paste in an S3 bucket ARN for which you do not want to log events.

To add the second S3 bucket, choose **+ Condition**, and then repeat the preceding instruction, pasting in the ARN for or browsing for a different bucket.

For information about how CloudTrail evaluates multiple conditions, see [How CloudTrail evaluates multiple conditions for a field](#).

 Note

You can have a maximum of 500 values for all selectors on an event data store. This includes arrays of multiple values for a selector such as `eventName`. If you have single values for all selectors, you can have a maximum of 500 conditions added to a selector.

- c. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields. For example, do not specify an ARN in one selector to be equal to a value, then specify that the ARN not equal the same value in another selector.
16. To add another resource type on which to log data events, choose **Add data event type**. Repeat steps 12 through this step to configure advanced event selectors for the resource type.
17. To log network activity events, choose **Network activity events**. Network activity events enable VPC endpoint owners to record AWS API calls made using their VPC endpoints from a private VPC to the AWS service. Additional charges apply for logging network activity events. For more information, see [AWS CloudTrail Pricing](#).

To log network activity events, do the following:

- a. From **Network activity event source**, choose the source for network activity events.
- b. In **Log selector template**, choose a template. You can choose to log all network activity events, log all network activity access denied events, or choose **Custom** to build a custom log selector to filter on multiple fields, such as `eventName` and `vpcEndpointId`.
- c. (Optional) Enter a name to identify the selector. The selector name is listed as **Name** in the advanced event selector and is viewable if you expand the **JSON view**.
- d. In **Advanced event selectors** build expressions by choosing values for **Field**, **Operator**, and **Value**. You can skip this step if you are using a predefined log template.

- i. For excluding or including network activity events, you can choose from the following fields in the console.
 - **eventName** – You can use any operator with eventName. You can use it to include or exclude any event, such as CreateKey.
 - **errorCode** – You can use it to filter on an error code. Currently, the only supported errorCode is VpceAccessDenied.
 - **vpcEndpointId** – Identifies the VPC endpoint that the operation passed through. You can use any operator with vpcEndpointId.
 - ii. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions.
 - iii. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields.
 - e. To add another event source for which you want to log network activity events, choose **Add network activity event selector**.
 - f. Optionally, expand **JSON view** to see your advanced event selectors as a JSON block.
18. Choose **Insights events** if you want your trail to log CloudTrail Insights events.

In **Event type**, select **Insights events**. You must be logging **Write** management events to log Insights events for **API call rate**. You must be logging **Read** or **Write** management events to log Insights events for **API error rate**.

CloudTrail Insights analyzes management events for unusual activity, and logs events when anomalies are detected. By default, trails don't log Insights events. For more information about Insights events, see [Working with CloudTrail Insights](#). Additional charges apply for logging Insights events. For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Insights events are delivered to a different folder named `/CloudTrail-Insight` of the same S3 bucket that is specified in the **Storage location** area of the trail details page. CloudTrail creates the new prefix for you. For example, if your current destination S3 bucket is named `amzn-s3-demo-bucket/AWSLogs/CloudTrail/`, the S3 bucket name with a new prefix is named `amzn-s3-demo-bucket/AWSLogs/CloudTrail-Insight/`.

19. When you are finished choosing event types to log, choose **Next**.
20. On the **Review and create** page, review your choices. Choose **Edit** in a section to change the trail settings shown in that section. When you are ready to create the trail, choose **Create trail**.

21. The new trail appears on the **Trails** page. In about 5 minutes, CloudTrail publishes log files that show the AWS API calls made in your account. You can see the log files in the S3 bucket that you specified.

If you enabled Insights events for a trail, CloudTrail may take up to 36 hours to begin delivering these events, provided that unusual activity is detected during that time.

 Note

CloudTrail typically delivers logs within an average of about 5 minutes of an API call. This time is not guaranteed. Review the [AWS CloudTrail Service Level Agreement](#) for more information.

If you misconfigure your trail (for example, the S3 bucket is unreachable), CloudTrail will attempt to redeliver the log files to your S3 bucket for 30 days, and these attempted-to-deliver events will be subject to standard CloudTrail charges. To avoid charges on a misconfigured trail, you need to delete the trail.

Configure data event settings using basic event selectors

You can use advanced event selectors to configure all data event types as well as network activity events. Advanced event selectors allow you to create fine-grained selectors to log only those events of interest.

If you use basic event selectors to log data events, you're limited to logging data events for Amazon S3 buckets, AWS Lambda functions, and Amazon DynamoDB tables. You can't filter on the `eventName` field using basic event selectors. You also can't log [network activity events](#).

Data events [Info](#)
Data events show information about the resource operations performed on or within a resource. [Additional charges apply](#)

Basic event selectors are enabled
Switch to advanced data event selectors for fine-grained control over the data events captured by your trail.

Switch to advanced event selectors

Data event: **S3** [Info](#)

Remove

Data event source
Select source of data events to log.

S3 ▲

S3 ✓

Lambda

DynamoDB

Individual bucket selection
Choose Browse to select multiple buckets, then choose to log Read, Write or both event types on all selected buckets.

bucket/prefix

Browse

☒ Read ☒ Write

×

Add bucket

Add data event type

Use the following procedure to configure data event settings using basic event selectors.

To configure data event settings using basic event selectors

1. In **Events**, choose **Data events** to log data events. Additional charges apply for logging data events. For more information, see [AWS CloudTrail Pricing](#).
2. For Amazon S3 buckets:
 - a. For **Data event source**, choose **S3**.

- b. You can choose to log **All current and future S3 buckets**, or you can specify individual buckets or functions. By default, data events are logged for all current and future S3 buckets.

 Note

Keeping the default **All current and future S3 buckets** option enables data event logging for all buckets currently in your AWS account and any buckets you create after you finish creating the trail. It also enables logging of data event activity performed by any IAM identity in your AWS account, even if that activity is performed on a bucket that belongs to another AWS account.

If you are creating a trail for a single Region (done by using the AWS CLI), choosing **All current and future S3 buckets** enables data event logging for all buckets in the same Region as your trail and any buckets you create later in that Region. It will not log data events for Amazon S3 buckets in other Regions in your AWS account.

- c. If you leave the default, **All current and future S3 buckets**, choose to log **Read** events, **Write** events, or both.
- d. To select individual buckets, empty the **Read** and **Write** check boxes for **All current and future S3 buckets**. In **Individual bucket selection**, browse for a bucket on which to log data events. Find specific buckets by typing a bucket prefix for the bucket you want. You can select multiple buckets in this window. Choose **Add bucket** to log data events for more buckets. Choose to log **Read** events, such as GetObject, **Write** events, such as PutObject, or both.

This setting takes precedence over individual settings you configure for individual buckets. For example, if you specify logging **Read** events for all S3 buckets, and then choose to add a specific bucket for data event logging, **Read** is already selected for the bucket you added. You cannot clear the selection. You can only configure the option for **Write**.

To remove a bucket from logging, choose **X**.

3. To add another resource type on which to log data events, choose **Add data event type**.
4. For Lambda functions:
 - a. For **Data event source**, choose **Lambda**.

- b. In **Lambda function**, choose **All regions** to log all Lambda functions, or **Input function as ARN** to log data events on a specific function.

To log data events for all Lambda functions in your AWS account, select **Log all current and future functions**. This setting takes precedence over individual settings you configure for individual functions. All functions are logged, even if all functions are not displayed.

 Note

If you're creating a multi-Region trail, this selection enables data event logging for all functions currently in your AWS account, and any Lambda functions you might create in any Region after you finish creating the trail. If you are creating a trail for a single Region (done by using the AWS CLI), this selection enables data event logging for all functions currently in that Region in your AWS account, and any Lambda functions you might create in that Region after you finish creating the trail. It does not enable data event logging for Lambda functions created in other Regions.

Logging data events for all functions also enables logging of data event activity performed by any IAM identity in your AWS account, even if that activity is performed on a function that belongs to another AWS account.

- c. If you choose **Input function as ARN**, enter the ARN of a Lambda function.

 Note

If you have more than 15,000 Lambda functions in your account, you cannot view or select all functions in the CloudTrail console when creating a trail. You can still select the option to log all functions, even if they are not displayed. If you want to log data events for specific functions, you can manually add a function if you know its ARN. You can also finish creating the trail in the console, and then use the AWS CLI and the **put-event-selectors** command to configure data event logging for specific Lambda functions. For more information, see [Managing trails with the AWS CLI](#).

5. For DynamoDB tables:

- a. For **Data event source**, choose **DynamoDB**.

- b. In **DynamoDB table selection**, choose **Browse** to select a table, or paste in the ARN of a DynamoDB table to which you have access. A DynamoDB table ARN uses the following format:

```
arn:partition:dynamodb:region:account_ID:table/table_name
```

To add another table, choose **Add row**, and browse for a table or paste in the ARN of a table to which you have access.

6. To configure Insights events and other settings for your trail, go back to the preceding procedure in this topic, [???](#).

Next steps

After you create your trail, you can return to the trail to make changes:

- If you haven't already, you can configure CloudTrail to send log files to CloudWatch Logs. For more information, see [Sending events to CloudWatch Logs](#).
- Create a table and use it to run a query in Amazon Athena to analyze your AWS service activity. For more information, see [Creating a Table for CloudTrail Logs in the CloudTrail Console](#) in the [Amazon Athena User Guide](#).
- Add custom tags (key-value pairs) to the trail.
- To create another trail, open the **Trails** page, and choose **Create trail**.

Updating a trail with the CloudTrail console

This section describes how to change trail settings.

To convert a single-Region trail to a multi-Region trail, or update a multi-Region trail to log events in only a single Region, you must use the AWS CLI. For more information about how to convert a single-Region trail to a multi-Region trail, see [Converting a single-Region trail to a multi-Region trail](#). For more information about how to update a multi-Region trail to log events in a single Region, see [Converting a multi-Region trail to a single-Region trail](#).

If you've enabled CloudTrail management events in Amazon Security Lake, you are required to maintain at least one organizational trail that is multi-Region and logs both read and write management events. You cannot update a qualifying trail in such a way that it fails to meet the

Security Lake requirement. For example, by changing the trail to single-Region, or by turning off the logging of read or write management events.

 Note

CloudTrail updates organization trails in member accounts even if a resource validation fails. Examples of validation failures include:

- an incorrect Amazon S3 bucket policy
- an incorrect Amazon SNS topic policy
- inability to deliver to a CloudWatch Logs log group
- insufficient permission to encrypt using a KMS key

A member account with CloudTrail permissions can see any validation failures for an organization trail by viewing the trail's details page on the CloudTrail console, or by running the AWS CLI [get-trail-status](#) command.

To update a trail with the AWS Management Console

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, choose **Trails**, and then choose a trail name.
3. In **General details**, choose **Edit** to change the following settings. You cannot change the name of a trail.
 - **Apply trail to my organization** - Change whether this trail is an AWS Organizations organization trail.

 Note

Only the management account for the organization can convert an organization trail to a non-organization trail, or convert a non-organization trail to an organization trail.

- **Trail log location** - Change the name of the S3 bucket or prefix in which you are storing logs for this trail.

- **Log file SSE-KMS encryption** - Choose to enable or disable encrypting log files with SSE-KMS instead of SSE-S3.
 - **Log file validation** - Choose to enable or disable validation of the integrity of log files.
 - **SNS notification delivery** - Choose to enable or disable Amazon Simple Notification Service (Amazon SNS) notifications that log files have been delivered to the bucket specified for the trail.
- a. To change the trail to an AWS Organizations organization trail, you can choose to enable the trail for all accounts in your organization. For more information, see [Creating a trail for an organization](#).
 - b. To change the specified bucket in **Storage location**, choose **Create new S3 bucket** to create a bucket. When you create a bucket, CloudTrail creates and applies the required bucket policies. If you choose to create a new S3 bucket, your IAM policy needs to include permission for the `s3:PutEncryptionConfiguration` action because by default server-side encryption is enabled for the bucket.

 Note

If you chose **Use existing S3 bucket**, specify a bucket in **Trail log bucket name**, or choose **Browse** to choose a bucket. The bucket policy must grant CloudTrail permission to write to it. For information about manually editing the bucket policy, see [Amazon S3 bucket policy for CloudTrail](#).

To make it easier to find your logs, create a new folder (also known as a *prefix*) in an existing bucket to store your CloudTrail logs. Enter the prefix in **Prefix**.

- c. For **Log file SSE-KMS encryption**, choose **Enabled** if you want to encrypt your log files and digest files using SSE-KMS encryption instead of SSE-S3 encryption. The default is **Enabled**. If you don't enable SSE-KMS encryption, your log files and digest files are encrypted using SSE-S3 encryption. For more information about SSE-KMS encryption, see [Using server-side encryption with AWS Key Management Service \(SSE-KMS\)](#). For more information about SSE-S3 encryption, see [Using Server-Side Encryption with Amazon S3-Managed Encryption Keys \(SSE-S3\)](#).

If you enable SSE-KMS encryption, choose a **New** or **Existing** AWS KMS key. In **AWS KMS Alias**, specify an alias, in the format `alias/MyAliasName`. For more information, see

[Updating a resource to use your KMS key with the console](#). CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

 Note

You can also type the ARN of a key from another account. For more information, see [Updating a resource to use your KMS key with the console](#). The key policy must allow CloudTrail to use the key to encrypt your log files and digest files, and allow the users you specify to read log files or digest files in unencrypted form. For information about manually editing the key policy, see [Configure AWS KMS key policies for CloudTrail](#).

- d. For **Log file validation**, choose **Enabled** to have log digests delivered to your S3 bucket. You can use the digest files to verify that your log files did not change after CloudTrail delivered them. For more information, see [Validating CloudTrail log file integrity](#).
- e. For **SNS notification delivery**, choose **Enabled** to be notified each time a log is delivered to your bucket. CloudTrail stores multiple events in a log file. SNS notifications are sent for every log file, not for every event. For more information, see [Configuring Amazon SNS notifications for CloudTrail](#).

If you enable SNS notifications, for **Create a new SNS topic**, choose **New** to create a topic, or choose **Existing** to use an existing topic. If you are creating multi-Region trail, SNS notifications for log file deliveries from all enabled Regions are sent to the single SNS topic that you create.

If you choose **New**, CloudTrail specifies a name for the new topic for you, or you can type a name. If you choose **Existing**, choose an SNS topic from the drop-down list. You can also enter the ARN of a topic from another Region or from an account with appropriate permissions. For more information, see [Amazon SNS topic policy for CloudTrail](#).

If you create a topic, you must subscribe to the topic to be notified of log file delivery. You can subscribe from the Amazon SNS console. Due to the frequency of notifications, we recommend that you configure the subscription to use an Amazon SQS queue to handle notifications programmatically. For more information, see [Getting started with Amazon SNS](#) in the *Amazon Simple Notification Service Developer Guide*.

4. In **CloudWatch Logs**, choose **Edit** to change settings for sending CloudTrail log files to CloudWatch Logs. Choose **Enabled** in **CloudWatch Logs** to enable sending log files. For more information, see [Sending events to CloudWatch Logs](#).
 - a. If you enable integration with CloudWatch Logs, choose **New** to create a new log group, or **Existing** to use an existing one. If you choose **New**, CloudTrail specifies a name for the new log group for you, or you can type a name.
 - b. If you choose **Existing**, choose a log group from the drop-down list.
 - c. Choose **New** to create a new IAM role for permissions to send logs to CloudWatch Logs. Choose **Existing** to choose an existing IAM role from the drop-down list. The policy statement for the new or existing role is displayed when you expand **Policy document**. For more information about this role, see [Role policy document for CloudTrail to use CloudWatch Logs for monitoring](#).

 Note

- When you configure a trail, you can choose an S3 bucket and SNS topic that belong to another account. However, if you want CloudTrail to deliver events to a CloudWatch Logs log group, you must choose a log group that exists in your current account.
- Only the management account can configure a CloudWatch Logs log group for an organization trail using the console. The delegated administrator can configure a CloudWatch Logs log group using the AWS CLI or CloudTrail `CreateTrail` or `UpdateTrail` API operations.

5. In **Tags**, choose **Edit** to change, add, or delete tags on the trail. You can add up to 50 tag key pairs to help you identify, sort, and control access to your trail. Tags can help you identify both your CloudTrail trails and the Amazon S3 buckets that contain CloudTrail log files. You can then use resource groups for your CloudTrail resources. For more information, see [AWS Resource Groups](#) and [Tags](#).
6. In **Management events**, choose **Edit** to change management event logging settings.
 - a. For **API activity**, choose if you want your trail to log **Read** events, **Write** events, or both. For more information, see [Management events](#).
 - b. Choose **Exclude AWS KMS events** to filter AWS Key Management Service (AWS KMS) events out of your trail. The default setting is to include all AWS KMS events.

The option to log or exclude AWS KMS events is available only if you log management events on your trail. If you choose not to log management events, AWS KMS events are not logged, and you cannot change AWS KMS event logging settings.

AWS KMS actions such as `Encrypt`, `Decrypt`, and `GenerateDataKey` typically generate a large volume (more than 99%) of events. These actions are now logged as **Read** events. Low-volume, relevant AWS KMS actions such as `Disable`, `Delete`, and `ScheduleKey` (which typically account for less than 0.5% of AWS KMS event volume) are logged as **Write** events.

To exclude high-volume events like `Encrypt`, `Decrypt`, and `GenerateDataKey`, but still log relevant events such as `Disable`, `Delete` and `ScheduleKey`, choose to log **Write** management events, and clear the check box for **Exclude AWS KMS events**.

- c. Choose **Exclude Amazon RDS Data API events** to filter Amazon Relational Database Service Data API events out of your trail. The default setting is to include all Amazon RDS Data API events. For more information about Amazon RDS Data API events, see [Logging Data API calls with AWS CloudTrail](#) in the *Amazon RDS User Guide for Aurora*.

7.

 Important

Steps 7-11 are for configuring data events using advanced event selectors, which is the default. Advanced event selectors let you configure more [data event types](#) and offer fine-grained control over which data events your trail captures. If you plan to log network activity events, you must use advanced event selectors. If you are using basic event selectors, see [Updating data event settings with basic event selectors](#), then return to step 12 of this procedure.

In **Data events**, choose **Edit** to change data event logging settings. By default, trails don't log data events. Additional charges apply for logging data events. For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

For **Resource type**, choose the resource type on which you want to log data events. For more information about available resource types, see [Data events](#).

8. Choose a log selector template. You can choose a predefined template, or choose **Custom** to define your own event collection conditions.

You can choose from the following predefined templates:

- **Log all events** – Choose this template to log all events.
- **Log only read events** – Choose this template to log only read events. Read-only events are events that do not change the state of a resource, such as `Get*` or `Describe*` events.
- **Log only write events** – Choose this template to log only write events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events.
- **Log only AWS Management Console events** – Choose this template to log only events originating from the AWS Management Console.
- **Exclude AWS service initiated events** – Choose this template to exclude AWS service events, which have an `eventType` of `AwsServiceEvent`, and events initiated with AWS service-linked roles (SLRs).

 Note

Choosing a predefined template for S3 buckets enables data event logging for all buckets currently in your AWS account and any buckets you create after you finish creating the trail. It also enables logging of data event activity performed by any user or role in your AWS account, even if that activity is performed on a bucket that belongs to another AWS account.

If the trail applies only to one Region, choosing a predefined template that logs all S3 buckets enables data event logging for all buckets in the same Region as your trail and any buckets you create later in that Region. It will not log data events for Amazon S3 buckets in other Regions in your AWS account.

If you're creating a multi-Region trail, choosing a predefined template for Lambda functions enables data event logging for all functions currently in your AWS account, and any Lambda functions you might create in any Region after you finish creating the trail. If you are creating a trail for a single Region (done by using the AWS CLI), this selection enables data event logging for all functions currently in that Region in your AWS account, and any Lambda functions you might create in that Region after you finish creating the trail. It does not enable data event logging for Lambda functions created in other Regions.

Logging data events for all functions also enables logging of data event activity performed by any user or role in your AWS account, even if that activity is performed on a function that belongs to another AWS account.

9. (Optional) In **Selector name**, enter a name to identify your selector. The selector name is a descriptive name for an advanced event selector, such as "Log data events for only two S3 buckets". The selector name is listed as Name in the advanced event selector and is viewable if you expand the **JSON view**.
10. If you selected **Custom**, in **Advanced event selectors** build an expression based on the values of advanced event selector fields.

 Note

Selectors don't support the use of wildcards like *. To match multiple values with a single condition, you may use `StartsWith`, `EndsWith`, `NotStartsWith`, or `NotEndsWith` to explicitly match the beginning or end of the event field.

- a. Choose from the following fields.
 - **readOnly** - `readOnly` can be set to **equals** a value of `true` or `false`. Read-only data events are events that do not change the state of a resource, such as `Get*` or `Describe*` events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events. To log both read and write events, don't add a `readOnly` selector.
 - **eventName** - `eventName` can use any operator. You can use it to include or exclude any data event logged to CloudTrail, such as `PutBucket`, `GetItem`, or `GetSnapshotBlock`.
 - **eventSource** – The event source to include or exclude. This field can use any operator.
 - **eventType** – The event type to include or exclude. For example, you can set this field to **not equals** `AwsServiceEvent` to exclude [AWS service events](#). For a list of event types, see [eventType](#) in [CloudTrail record contents for management, data, and network activity events](#).
 - **sessionCredentialFromConsole** – Include or exclude events originating from an AWS Management Console session. This field can be set to **equals** or **not equals** with a value of `true`.

- **userIdentity.arn** – Include or exclude events for actions taken by specific IAM identities. For more information, see [CloudTrail userIdentity element](#).
- **resources.ARN** – You can use any operator with `resources.ARN`, but if you use **equals** or **does not equal**, the value must exactly match the ARN of a valid resource of the type you've specified in the template as the value of `resources.type`.

 Note

You can't use the `resources.ARN` field to filter resource types that do not have ARNs.

For more information about the ARN formats of data event resources, see [Actions, resources, and condition keys for AWS services](#) in the *Service Authorization Reference*.

- b. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions. For example, to exclude data events for two S3 buckets from data events that are logged on your event data store, you can set the field to **resources.ARN**, set the operator for **does not start with**, and then paste in an S3 bucket ARN for which you do not want to log events.

To add the second S3 bucket, choose **+ Condition**, and then repeat the preceding instruction, pasting in the ARN for or browsing for a different bucket.

For information about how CloudTrail evaluates multiple conditions, see [How CloudTrail evaluates multiple conditions for a field](#).

 Note

You can have a maximum of 500 values for all selectors on an event data store. This includes arrays of multiple values for a selector such as `eventName`. If you have single values for all selectors, you can have a maximum of 500 conditions added to a selector.

- c. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields. For example, do not specify an ARN in one selector to be equal to a value, then specify that the ARN not equal the same value in another selector.

11. To add another resource type on which to log data events, choose **Add data event type**. Repeat steps 3 through this step to configure advanced event selectors for the resource type.
12. In **Network activity events**, choose **Edit** to change network activity event logging settings. By default, trails don't log network activity events. Additional charges apply for logging network activity events. For more information, see [AWS CloudTrail Pricing](#).

To log network activity events, do the following:

- a. From **Network activity event source**, choose the source for network activity events.
 - b. In **Log selector template**, choose a template. You can choose to log all network activity events, log all network activity access denied events, or choose **Custom** to build a custom log selector to filter on multiple fields, such as eventName and vpcEndpointId.
 - c. (Optional) Enter a name to identify the selector. The selector name is listed as **Name** in the advanced event selector and is viewable if you expand the **JSON view**.
 - d. In **Advanced event selectors** build expressions by choosing values for **Field**, **Operator**, and **Value**. You can skip this step if you are using a predefined log template.
 - i. For excluding or including network activity events, you can choose from the following fields in the console.
 - **eventName** – You can use any operator with eventName. You can use it to include or exclude any event, such as CreateKey.
 - **errorCode** – You can use it to filter on an error code. Currently, the only supported errorCode is VpceAccessDenied.
 - **vpcEndpointId** – Identifies the VPC endpoint that the operation passed through. You can use any operator with vpcEndpointId.
 - ii. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions.
 - iii. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields.
 - e. To add another event source for which you want to log network activity events, choose **Add network activity event selector**.
 - f. Optionally, expand **JSON view** to see your advanced event selectors as a JSON block.
13. In **Insights events**, choose **Edit** if you want your trail to log CloudTrail Insights events.

In Event type, select Insights events.

In **Insights events**, choose **API call rate**, **API error rate**, or both. You must be logging **Write** management events to log Insights events for **API call rate**. You must be logging **Read** or **Write** management events to log Insights events for **API error rate**.

CloudTrail Insights analyzes management events for unusual activity, and logs events when anomalies are detected. By default, trails don't log Insights events. For more information about Insights events, see [Working with CloudTrail Insights](#). Additional charges apply for logging Insights events. For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Insights events are delivered to a different folder named `/CloudTrail-Insight` of the same S3 bucket that is specified in the **Storage location** area of the trail details page. CloudTrail creates the new prefix for you. For example, if your current destination S3 bucket is named `amzn-s3-demo-bucket/AWSLogs/CloudTrail/`, the S3 bucket name with a new prefix is named `amzn-s3-demo-bucket/AWSLogs/CloudTrail-Insight/`.

14. When you are finished changing settings on your trail, choose **Update trail**.

Updating data event settings with basic event selectors

You can use advanced event selectors to configure all data event types as well as network activity events. Advanced event selectors allow you to create fine-grained selectors to log only those events of interest.

If you use basic event selectors to log data events, you're limited to logging data events for Amazon S3 buckets, AWS Lambda functions, and Amazon DynamoDB tables. You can't filter on the `eventName` field using basic event selectors. You also can't log [network activity events](#).

Data events [Info](#)

Data events show information about the resource operations performed on or within a resource. [Additional charges apply](#)

Basic event selectors are enabled
Switch to advanced data event selectors for fine-grained control over the data events captured by your trail.

Switch to advanced event selectors

Data event: S3 [Info](#)

Remove

Data event source
Select source of data events to log.

S3 ▲

S3 ✓

Lambda

DynamoDB

Individual bucket selection
Choose Browse to select multiple buckets, then choose to log Read, Write or both event types on all selected buckets.

bucket/prefix

Browse

☒ Read ☒ Write

×

Add bucket

Add data event type

Use the following procedure to configure data event settings using basic event selectors.

1. In **Data events**, choose **Edit** to change data event logging settings. With basic event selectors, you can specify logging data events for Amazon S3 buckets, AWS Lambda functions, DynamoDBtables, or a combination of those resources. Additional data event resource types are supported with advanced event selectors. By default, trails don't log data events. Additional charges apply for logging data events. For more information, see [Data events](#). For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

For Amazon S3 buckets:

- a. For **Data event source**, choose **S3**.

- b. You can choose to log **All current and future S3 buckets**, or you can specify individual buckets or functions. By default, data events are logged for all current and future S3 buckets.

 Note

Keeping the default **All current and future S3 buckets** option enables data event logging for all buckets currently in your AWS account and any buckets you create after you finish creating the trail. It also enables logging of data event activity performed by any user or role in your AWS account, even if that activity is performed on a bucket that belongs to another AWS account.

If the trail applies only to one Region, choosing **All current and future S3 buckets** enables data event logging for all buckets in the same Region as your trail and any buckets you create later in that Region. It will not log data events for Amazon S3 buckets in other Regions in your AWS account.

- c. If you leave the default, **All current and future S3 buckets**, choose to log **Read** events, **Write** events, or both.
- d. To select individual buckets, empty the **Read** and **Write** check boxes for **All current and future S3 buckets**. In **Individual bucket selection**, browse for a bucket on which to log data events. To find specific buckets, type a bucket prefix for the bucket you want. You can select multiple buckets in this window. Choose **Add bucket** to log data events for more buckets. Choose to log **Read** events, such as `GetObject`, **Write** events, such as `PutObject`, or both.

This setting takes precedence over individual settings you configure for individual buckets. For example, if you specify logging **Read** events for all S3 buckets, and then choose to add a specific bucket for data event logging, **Read** is already selected for the bucket you added. You cannot clear the selection. You can only configure the option for **Write**.

To remove a bucket from logging, choose **X**.

2. To add another resource type on which to log data events, choose **Add data event type**.
3. For Lambda functions:
 - a. For **Data event source**, choose **Lambda**.
 - b. In **Lambda function**, choose **All regions** to log all Lambda functions, or **Input function as ARN** to log data events on a specific function.

To log data events for all Lambda functions in your AWS account, select **Log all current and future functions**. This setting takes precedence over individual settings you configure for individual functions. All functions are logged, even if all functions are not displayed.

 Note

If you're creating a multi-Region trail, this selection enables data event logging for all functions currently in your AWS account, and any Lambda functions you might create in any Region after you finish creating the trail. If you are creating a trail for a single Region (done by using the AWS CLI), this selection enables data event logging for all functions currently in that Region in your AWS account, and any Lambda functions you might create in that Region after you finish creating the trail. It does not enable data event logging for Lambda functions created in other Regions.

Logging data events for all functions also enables logging of data event activity performed by any user or role in your AWS account, even if that activity is performed on a function that belongs to another AWS account.

- c. If you choose **Input function as ARN**, enter the ARN of a Lambda function.

 Note

If you have more than 15,000 Lambda functions in your account, you cannot view or select all functions in the CloudTrail console when creating a trail. You can still select the option to log all functions, even if they are not displayed. If you want to log data events for specific functions, you can manually add a function if you know its ARN. You can also finish creating the trail in the console, and then use the AWS CLI and the **put-event-selectors** command to configure data event logging for specific Lambda functions. For more information, see [Managing trails with the AWS CLI](#).

4. To add another resource type on which to log data events, choose **Add data event type**.
5. For DynamoDB tables:
 - a. For **Data event source**, choose **DynamoDB**.

- b. In **DynamoDB table selection**, choose **Browse** to select a table, or paste in the ARN of a DynamoDB table to which you have access. A DynamoDB table ARN is in the following format:

```
arn:partition:dynamodb:region:account_ID:table/table_name
```

To add another table, choose **Add row**, and browse for a table or paste in the ARN of a table to which you have access.

6. To configure Insights events and other settings for your trail, go back to the preceding procedure in this topic, [Updating a trail with the CloudTrail console](#).

Deleting a trail with the CloudTrail console

You can delete trails with the CloudTrail console. If an organization's management account or delegated administrator account deletes an organization trail, the trail is removed from all member accounts of the organization.

Important

While deleting a CloudTrail trail is an irreversible action, CloudTrail does not delete log files in the Amazon S3 bucket for that trail, the Amazon S3 bucket itself, or the CloudWatch log group to which the trail delivers events. Deleting a multi-Region trail will stop logging of events in all AWS Regions enabled in your AWS account. Deleting a single-Region trail will stop logging of events in that Region only. It will not stop logging of events in other Regions even if the trails in those other Regions have identical names to the deleted trail. For information about account closure and deletion of CloudTrail trails, see [AWS account closure and trails](#).

If you've enabled CloudTrail management events in Amazon Security Lake, you are required to maintain at least one organizational trail that is multi-Region and logs both read and write management events. You cannot delete a trail if it is the only trail you have that meets this requirement, unless you turn off CloudTrail management events in Security Lake.

To delete a trail with the CloudTrail console

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. Open the **Trails** page of the CloudTrail console.
3. Choose the trail name.
4. At the top of the trail details page, choose **Delete**.
5. When you are prompted to confirm, choose **Delete** to delete the trail permanently. The trail is removed from the list of trails. Log files that were already delivered to the Amazon S3 bucket are not deleted and continue to incur S3 charges.

Note

Content delivered to Amazon S3 buckets might contain customer content. For more information about removing sensitive data, see [Emptying a bucket](#) and [Deleting a bucket](#) in the *Amazon S3 User Guide*.

Turning off logging for a trail

When you create a trail, logging is turned on automatically. You can turn off logging for a trail from the trail's details page.

Note

When you turn off logging, existing logs are still stored in the trail's Amazon S3 bucket and continue to incur S3 charges. For information on S3 pricing, see [Amazon S3 pricing](#).

To turn off logging for a trail with the CloudTrail console

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, choose **Trails**, and then choose the name of the trail.
3. At the top of the trail details page, choose **Stop logging** to turn off logging for the trail.
4. When you are prompted to confirm, choose **Stop logging**. CloudTrail stops logging activity for that trail.

5. To resume logging for that trail, choose **Start logging** on the trail configuration page.

Creating, updating, and managing trails with the AWS CLI

You can use the AWS CLI to create, update, and manage your trails. When using the AWS CLI, remember that your commands run in the AWS Region configured for your profile. If you want to run the commands in a different Region, either change the default Region for your profile, or use the `--region` parameter with the command.

Note

You need the AWS command line tools to run the AWS Command Line Interface (AWS CLI) commands in this topic. Make sure you have a recent version of the AWS CLI installed. For more information, see the [AWS Command Line Interface User Guide](#). For help with CloudTrail commands at the AWS CLI command line, type `aws cloudtrail help`.

Commonly used commands for trail creation, management, and status

Some of the more commonly used commands for creating and updating trails in CloudTrail include:

- [create-trail](#) to create a trail.
- [update-trail](#) to change the configuration of an existing trail.
- [add-tags](#) to add one or more tags (key-value pairs) to an existing trail.
- [remove-tags](#) to remove one or more tags from a trail.
- [list-tags](#) to return a list of tags associated with a trail.
- [put-event-selectors](#) to add or modify event selectors for a trail.
- [put-insight-selectors](#) to add or modify Insights event selectors for an existing trail, and enable or disable Insights events.
- [start-logging](#) to begin logging events with your trail.
- [stop-logging](#) to pause logging events with your trail.
- [delete-trail](#) to delete a trail. This command does not delete the Amazon S3 bucket that contains the log files for that trail, if any.
- [describe-trails](#) to return information about trails in an AWS Region.

- [get-trail](#) to return settings information for a trail.
- [get-trail-status](#) to return information about the current status of a trail.
- [get-event-selectors](#) to return information about event selectors configured for a trail.
- [get-insight-selectors](#) to return information about Insights event selectors configured for a trail.

Supported commands for creating and updating trails: create-trail and update-trail

The `create-trail` and `update-trail` commands offer a variety of functionality for creating and managing trails, including:

- Creating a trail that receives logs across Regions, or update a trail with the `--is-multi-region-trail` option. In most circumstances, you should create trails that log events in all AWS Regions.
- Creating a trail that receives logs for all AWS accounts in an organization with the `--is-organization-trail` option.
- Converting a multi-Region trail to single-Region trail with the `--no-is-multi-region-trail` option.
- Enabling or disabling log file encryption with the `--kms-key-id` option. The option specifies an AWS KMS key that you already created and to which you have attached a policy that allows CloudTrail to encrypt your logs. For more information, see [Enabling and disabling encryption for CloudTrail log files, digest files and event data stores with the AWS CLI](#).
- Enabling or disabling log file validation with the `--enable-log-file-validation` and `--no-enable-log-file-validation` options. For more information, see [Validating CloudTrail log file integrity](#).
- Specifying a CloudWatch Logs log group and role so that CloudTrail can deliver events to a CloudWatch Logs log group. For more information, see [Monitoring CloudTrail Log Files with Amazon CloudWatch Logs](#).

Deprecated commands: create-subscription and update-subscription

Important

The `create-subscription` and `update-subscription` commands were used to create and update trails, but are deprecated. Do not use these commands. They do not provide full functionality for creating and managing trails.

If you configured automation that uses one or both of these commands, we recommend that you update your code or scripts to use supported commands such as **create-trail**.

Using the **create-trail** command to create a trail

You can run the `create-trail` command to create trails that are specifically configured to meet your business needs. When using the AWS CLI, remember that your commands run in the AWS Region configured for your profile. If you want to run the commands in a different Region, either change the default Region for your profile, or use the `--region` parameter with the command.

Creating a multi-Region trail

A trail can be applied to all AWS Regions that are [enabled](#) in your AWS account, or can be applied to a single Region. A trail that applies to all AWS Regions that are enabled in your AWS account is referred to as a *multi-Region trail*. As a best practice, we recommend creating a multi-Region trail because it captures activity in all enabled Regions.

To create a multi-Region trail, use the `--is-multi-region-trail` option. By default, the `create-trail` command creates a trail that logs events only in the AWS Region where the trail was created. To ensure that you log global service events and capture all management event activity in your AWS account, you should create trails that log events in all AWS Regions.

Note

When you create a trail, if you specify an Amazon S3 bucket that was not created with CloudTrail, you need to attach the appropriate policy. See [Amazon S3 bucket policy for CloudTrail](#).

The following example creates a multi-Region trail with the name *my-trail* and a tag with a key named *Group* with a value of *Marketing* that delivers logs from all enabled Regions in your account to an existing bucket named *amzn-s3-demo-bucket*.

```
aws cloudtrail create-trail --name my-trail --s3-bucket-name amzn-s3-demo-bucket --is-multi-region-trail --tags-list [key=Group,value=Marketing]
```

To confirm that your trail is a multi-Region trail, verify that the `IsMultiRegionTrail` element in the output shows `true`.

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "my-trail",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
  "LogFileValidationEnabled": false,
  "IsMultiRegionTrail": true,
  "IsOrganizationTrail": false,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

Note

Use the `start-logging` command to start logging for your trail.

Start logging for the trail

After the `create-trail` command completes, run the `start-logging` command to start logging for that trail.

Note

When you create a trail with the CloudTrail console, logging is turned on automatically.

The following example starts logging for a trail.

```
aws cloudtrail start-logging --name my-trail
```

This command doesn't return an output, but you can use the `get-trail-status` command to verify that logging has started.

```
aws cloudtrail get-trail-status --name my-trail
```

To confirm that the trail is logging, the `IsLogging` element in the output shows `true`.

```
{
  "LatestDeliveryTime": 1441139757.497,
  "LatestDeliveryAttemptTime": "2015-09-01T20:35:57Z",
  "LatestNotificationAttemptSucceeded": "2015-09-01T20:35:57Z",
}
```



```
"LatestDeliveryAttemptSucceeded": "2015-09-01T20:35:57Z",
  "IsLogging": true,
  "TimeLoggingStarted": "2015-09-01T00:54:02Z",
  "StartLoggingTime": 1441068842.76,
  "LatestDigestDeliveryTime": 1441140723.629,
  "LatestNotificationAttemptTime": "2015-09-01T20:35:57Z",
  "TimeLoggingStopped": ""
}
```

Creating a single-Region trail

The following command creates a single-Region trail. The specified Amazon S3 bucket must already exist and have the appropriate CloudTrail permissions applied. For more information, see [Amazon S3 bucket policy for CloudTrail](#).

```
aws cloudtrail create-trail --name my-trail --s3-bucket-name amzn-s3-demo-bucket
```

The following is example output.

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "my-trail",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
  "LogFileValidationEnabled": false,
  "IsMultiRegionTrail": false,
  "IsOrganizationTrail": false,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

Creating a multi-Region trail that has log file validation enabled

To enable log file validation when using `create-trail`, use the `--enable-log-file-validation` option.

For information about log file validation, see [Validating CloudTrail log file integrity](#).

The following example creates a multi-Region trail that delivers logs to the specified bucket. The command uses the `--enable-log-file-validation` option.

```
aws cloudtrail create-trail --name my-trail --s3-bucket-name amzn-s3-demo-bucket --is-
multi-region-trail --enable-log-file-validation
```

To confirm that log file validation is enabled, the `LogFileValidationEnabled` element in the output shows `true`.

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "my-trail",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
  "LogFileValidationEnabled": true,
  "IsMultiRegionTrail": true,
  "IsOrganizationTrail": false,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

Using the `update-trail` command to update a trail

Important

As of November 22, 2021, AWS CloudTrail changed how trails capture global service events. Now, events created by Amazon CloudFront, AWS Identity and Access Management, and AWS STS are recorded in the Region in which they were created, the US East (N. Virginia) Region, `us-east-1`. This makes how CloudTrail treats these services consistent with that of other AWS global services. To continue receiving global service events outside of US East (N. Virginia), be sure to convert *single-Region trails* using global service events outside of US East (N. Virginia) into *multi-Region trails*. For more information about capturing global service events, see [Enabling and disabling global service event logging](#) later in this section. In contrast, the **Event history** in the CloudTrail console and the **`aws cloudtrail lookup-events`** command will show these events in the AWS Region where they occurred.

You can use the `update-trail` command to change the configuration settings for a trail. You can also use the **`add-tags`** and **`remove-tags`** commands to add and remove tags for a trail. You can only update trails from the AWS Region where the trail was created (its Home Region). When using the AWS CLI, remember that your commands run in the AWS Region configured for your profile. If you want to run the commands in a different Region, either change the default Region for your profile, or use the **`--region`** parameter with the command.

If you've enabled CloudTrail management events in Amazon Security Lake, you are required to maintain at least one organizational trail that is multi-Region and logs both `read` and `write` management events. You cannot update a qualifying trail in such a way that it fails to meet the

Security Lake requirement. For example, by changing the trail to single-Region, or by turning off the logging of read or write management events.

Note

If you use the AWS CLI or one of the AWS SDKs to modify a trail, be sure that the trail's bucket policy is up-to-date. In order for your bucket to automatically receive events from a new AWS Region, the policy must contain the full service name, `cloudtrail.amazonaws.com`. For more information, see [Amazon S3 bucket policy for CloudTrail](#).

Topics

- [Converting a single-Region trail to a multi-Region trail](#)
- [Converting a multi-Region trail to a single-Region trail](#)
- [Enabling and disabling global service event logging](#)
- [Enabling log file validation](#)
- [Disabling log file validation](#)

Converting a single-Region trail to a multi-Region trail

To change an existing single-Region trail to a multi-Region trail, use the `--is-multi-region-trail` option.

```
aws cloudtrail update-trail --name my-trail --is-multi-region-trail
```

To confirm that the trail is now a multi-Region trail, verify that the `IsMultiRegionTrail` element in the output shows `true`.

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "my-trail",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
  "LogFileValidationEnabled": false,
  "IsMultiRegionTrail": true,
  "IsOrganizationTrail": false,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

```
}
```

Converting a multi-Region trail to a single-Region trail

To change an existing multi-Region trail so that it applies only to the Region in which it was created, use the `--no-is-multi-region-trail` option.

```
aws cloudtrail update-trail --name my-trail --no-is-multi-region-trail
```

To confirm that the trail now applies to a single Region, the `IsMultiRegionTrail` element in the output shows `false`.

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "my-trail",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
  "LogFileValidationEnabled": false,
  "IsMultiRegionTrail": false,
  "IsOrganizationTrail": false,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

Enabling and disabling global service event logging

To change a trail so that it does not log global service events, use the `--no-include-global-service-events` option.

```
aws cloudtrail update-trail --name my-trail --no-include-global-service-events
```

To confirm that the trail no longer logs global service events, the `IncludeGlobalServiceEvents` element in the output shows `false`.

```
{
  "IncludeGlobalServiceEvents": false,
  "Name": "my-trail",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
  "LogFileValidationEnabled": false,
  "IsMultiRegionTrail": false,
  "IsOrganizationTrail": false,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

To change a trail so that it logs global service events, use the `--include-global-service-events` option.

Single-Region trails will no longer receive global service events beginning November 22, 2021, unless the trail already appears in US East (N. Virginia) Region, `us-east-1`. To continue capturing global service events, update the trail configuration to a multi-Region trail. For example, this command updates a single-Region trail in US East (Ohio), `us-east-2`, into a multi-Region trail. Replace *myExistingSingleRegionTrailWithGSE* with the appropriate trail name for your configuration.

```
aws cloudtrail --region us-east-2 update-trail --  
name myExistingSingleRegionTrailWithGSE --is-multi-region-trail
```

Because global service events are only available in US East (N. Virginia) beginning November 22, 2021, you can also create a single-Region trail to subscribe to global service events in the US East (N. Virginia) Region, `us-east-1`. The following command creates a single-Region trail in `us-east-1` to receive CloudFront, IAM, and AWS STS events:

```
aws cloudtrail --region us-east-1 create-trail --include-global-service-events --  
name myTrail --s3-bucket-name amzn-s3-demo-bucket
```

Enabling log file validation

To enable log file validation for a trail, use the `--enable-log-file-validation` option. Digest files are delivered to the Amazon S3 bucket for that trail.

```
aws cloudtrail update-trail --name my-trail --enable-log-file-validation
```

To confirm that log file validation is enabled, the `LogFileValidationEnabled` element in the output shows `true`.

```
{  
  "IncludeGlobalServiceEvents": true,  
  "Name": "my-trail",  
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",  
  "LogFileValidationEnabled": true,  
  "IsMultiRegionTrail": false,  
  "IsOrganizationTrail": false,  
  "S3BucketName": "amzn-s3-demo-bucket"  
}
```

Disabling log file validation

To disable log file validation for a trail, use the `--no-enable-log-file-validation` option.

```
aws cloudtrail update-trail --name my-trail-name --no-enable-log-file-validation
```

To confirm that log file validation is disabled, the `LogFileValidationEnabled` element in the output shows `false`.

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "my-trail",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
  "LogFileValidationEnabled": false,
  "IsMultiRegionTrail": false,
  "IsOrganizationTrail": false,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

To validate log files with the AWS CLI, see [Validating CloudTrail log file integrity with the AWS CLI](#).

Managing trails with the AWS CLI

The AWS CLI includes several other commands that help you manage your trails. These commands add tags to trails, get trail status, start and stop logging for trails, and delete a trail. You must run these commands from the same AWS Region where the trail was created (its Home Region). When using the AWS CLI, remember that your commands run in the AWS Region configured for your profile. If you want to run the commands in a different Region, either change the default Region for your profile, or use the `--region` parameter with the command.

Topics

- [Add one or more tags to a trail](#)
- [List tags for one or more trails](#)
- [Remove one or more tags from a trail](#)
- [Retrieving trail settings and the status of a trail](#)
- [Configuring CloudTrail Insights event selectors](#)
- [Configuring advanced event selectors](#)
- [Configuring basic event selectors](#)

- [Stopping and starting logging for a trail](#)
- [Deleting a trail](#)

Add one or more tags to a trail

To add one or more tags to an existing trail, run the **add-tags** command.

The following example adds a tag with the name *Owner* and the value of *Mary* to a trail with the ARN of *arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail* in the US East (Ohio) Region.

```
aws cloudtrail add-tags --resource-id arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail --tags-list Key=Owner,Value=Mary --region us-east-2
```

If successful, this command returns nothing.

List tags for one or more trails

To view the tags associated with one or more existing trails, use the **list-tags** command.

The following example lists the tags for *Trail1* and *Trail2*.

```
aws cloudtrail list-tags --resource-id-list arn:aws:cloudtrail:us-east-2:123456789012:trail/Trail1 arn:aws:cloudtrail:us-east-2:123456789012:trail/Trail2
```

If successful, this command returns output similar to the following.

```
{
  "ResourceTagList": [
    {
      "ResourceId": "arn:aws:cloudtrail:us-east-2:123456789012:trail/Trail1",
      "TagsList": [
        {
          "Value": "Alice",
          "Key": "Name"
        },
        {
          "Value": "Ohio",
          "Key": "Location"
        }
      ]
    }
  ],
}
```

```
{
  "ResourceId": "arn:aws:cloudtrail:us-east-2:123456789012:trail/Trail2",
  "TagsList": [
    {
      "Value": "Bob",
      "Key": "Name"
    }
  ]
}
```

Remove one or more tags from a trail

To remove one or more tags from an existing trail, run the **remove-tags** command.

The following example removes tags with the names *Location* and *Name* from a trail with the ARN of *arn:aws:cloudtrail:us-east-2:123456789012:trail/Trail1* in the US East (Ohio) Region.

```
aws cloudtrail remove-tags --resource-id arn:aws:cloudtrail:us-
east-2:123456789012:trail/Trail1 --tags-list Key=Name Key=Location --region us-east-2
```

If successful, this command returns nothing.

Retrieving trail settings and the status of a trail

Run the `describe-trails` command to retrieve information about trails in an AWS Region. The following example returns information about trails configured in the US East (Ohio) Region.

```
aws cloudtrail describe-trails --region us-east-2
```

If the command succeeds, you see output similar to the following.

```
{
  "trailList": [
    {
      "Name": "my-trail",
      "S3BucketName": "amzn-s3-demo-bucket1",
      "S3KeyPrefix": "my-prefix",
      "IncludeGlobalServiceEvents": true,
      "IsMultiRegionTrail": true,
```



```

    "HomeRegion": "us-east-2"
    "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
    "LogFileValidationEnabled": false,
    "HasCustomEventSelectors": false,
    "SnsTopicName": "my-topic",
    "IsOrganizationTrail": false,
  },
  {
    "Name": "my-special-trail",
    "S3BucketName": "amzn-s3-demo-bucket2",
    "S3KeyPrefix": "example-prefix",
    "IncludeGlobalServiceEvents": false,
    "IsMultiRegionTrail": false,
    "HomeRegion": "us-east-2",
    "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-special-trail",
    "LogFileValidationEnabled": false,
    "HasCustomEventSelectors": true,
    "IsOrganizationTrail": false
  },
  {
    "Name": "my-org-trail",
    "S3BucketName": "amzn-s3-demo-bucket3",
    "S3KeyPrefix": "my-prefix",
    "IncludeGlobalServiceEvents": true,
    "IsMultiRegionTrail": true,
    "HomeRegion": "us-east-1"
    "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-org-trail",
    "LogFileValidationEnabled": false,
    "HasCustomEventSelectors": false,
    "SnsTopicName": "my-topic",
    "IsOrganizationTrail": true
  }
]
}

```

Run the `get-trail` command to retrieve settings information about a specific trail. The following example returns settings information for a trail named *my-trail*.

```
aws cloudtrail get-trail - -name my-trail
```

If successful, this command returns output similar to the following.

```
{
```

```
"Trail": {
  "Name": "my-trail",
  "S3BucketName": "amzn-s3-demo-bucket",
  "S3KeyPrefix": "my-prefix",
  "IncludeGlobalServiceEvents": true,
  "IsMultiRegionTrail": true,
  "HomeRegion": "us-east-2"
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
  "LogFileValidationEnabled": false,
  "HasCustomEventSelectors": false,
  "SnsTopicName": "my-topic",
  "IsOrganizationTrail": false,
}
```

Run the `get-trail-status` command to retrieve the status of a trail. You must either run this command from the AWS Region where it was created (the Home Region), or you must specify that Region by adding the `--region` parameter.

Note

If the trail is an organization trail and you are a member account in the organization in AWS Organizations, you must provide the full ARN of that trail, and not just the name.

```
aws cloudtrail get-trail-status --name my-trail
```

If the command succeeds, you see output similar to the following.

```
{
  "LatestDeliveryTime": 1441139757.497,
  "LatestDeliveryAttemptTime": "2015-09-01T20:35:57Z",
  "LatestNotificationAttemptSucceeded": "2015-09-01T20:35:57Z",
  "LatestDeliveryAttemptSucceeded": "2015-09-01T20:35:57Z",
  "IsLogging": true,
  "TimeLoggingStarted": "2015-09-01T00:54:02Z",
  "StartLoggingTime": 1441068842.76,
  "LatestDigestDeliveryTime": 1441140723.629,
  "LatestNotificationAttemptTime": "2015-09-01T20:35:57Z",
  "TimeLoggingStopped": ""
}
```

In addition to the fields shown in the preceding JSON code, the status contains the following fields if there are Amazon SNS or Amazon S3 errors:

- `LatestNotificationError`. Contains the error emitted by Amazon SNS if a subscription to a topic fails.
- `LatestDeliveryError`. Contains the error emitted by Amazon S3 if CloudTrail cannot deliver a log file to a bucket.

Configuring CloudTrail Insights event selectors

Enable Insights events on a trail by running the **put-insight-selectors**, and specifying `ApiCallRateInsight`, `ApiErrorRateInsight`, or both as the value of the `InsightType` attribute. To view the Insights selector settings for a trail, run the `get-insight-selectors` command. You must either run this command from the AWS Region where the trail was created (the Home Region), or you must specify that Region by adding the **--region** parameter to the command.

Note

To log Insights events for `ApiCallRateInsight`, the trail must log write management events. To log Insights events for `ApiErrorRateInsight`, the trail must log read or write management events.

Example trail that logs Insights events

The following example uses **put-insight-selectors** to create an Insights event selector for a trail named *TrailName3*. This enables Insights event collection for the *TrailName3* trail. The Insights event selector logs both `ApiErrorRateInsight` and `ApiCallRateInsight` Insights event types.

```
aws cloudtrail put-insight-selectors --trail-name TrailName3 --insight-selectors '[{"InsightType": "ApiCallRateInsight"}, {"InsightType": "ApiErrorRateInsight"}]'
```

The example returns the Insights event selector that is configured for the trail.

```
{  
  "InsightSelectors":
```

```
[
  {
    "InsightType": "ApiErrorRateInsight"
  },
  {
    "InsightType": "ApiCallRateInsight"
  }
],
"TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName3"
}
```

Example: Turn off collection of Insights events

The following example uses **put-insight-selectors** to remove the Insights event selector for a trail named *TrailName3*. Clearing the JSON string of Insights selectors disables Insights event collection for the *TrailName3* trail.

```
aws cloudtrail put-insight-selectors --trail-name TrailName3 --insight-selectors '[]'
```

The example returns the now-empty Insights event selector that is configured for the trail.

```
{
  "InsightSelectors": [ ],
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName3"
}
```

Configuring advanced event selectors

You can use advanced event selectors to log [management events](#), [data events](#) for all resource types, and [network activity events](#). In contrast, you can use basic event selectors to log management events and data events for the `AWS::DynamoDB::Table`, `AWS::Lambda::Function`, and `AWS::S3::Object` resource types. You can use either basic event selectors, or advanced event selectors, but not both. If you apply advanced event selectors to a trail that is using basic event selectors, the basic event selectors are overwritten.

To convert a trail to advanced event selectors, run the **get-event-selectors** command to confirm the current event selectors, and then configure the advanced event selectors to match the coverage of the previous event selectors, then add any additional selectors.

You must either run the `get-event-selectors` command from the AWS Region where the trail was created (the Home Region), or you must specify that Region by adding the **--region** parameter.

```
aws cloudtrail get-event-selectors --trail-name TrailName
```

Note

If the trail is an organization trail, and you are signed in with a member account in the organization in AWS Organizations, you must provide the full ARN of the trail, and not just the name.

The following example shows the settings for a trail that is using advanced event selectors to log management events. By default, a trail is configured to log all management events and no data events or network activity events.

```
{
  "TrailARN": "arn:aws:cloudtrail:us-east-1:123456789012:trail/management-events-trail",
  "AdvancedEventSelectors": [
    {
      "Name": "Management events selector",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        }
      ]
    }
  ]
}
```

To create an advanced event selector, run the `put-event-selectors` command. When an event occurs in your account, CloudTrail evaluates the configuration for your trails. If the event matches any advanced event selector for a trail, the trail processes and logs the event. You can configure up to 500 conditions on a trail, including all values specified for all advanced event selectors on your trail. For more information, see [Logging data events](#) and [Logging network activity events](#).

Topics

- [Example trail with specific advanced event selectors](#)

- [Example trail that uses custom advanced event selectors to log Amazon S3 on AWS Outposts data events](#)
- [Example trail that uses advanced event selectors to exclude AWS Key Management Service events](#)
- [Example trail that uses advanced event selectors to exclude Amazon RDS Data API management events](#)

Example trail with specific advanced event selectors

The following example creates custom advanced event selectors for a trail named *TrailName* to include read and write management events (by omitting the `readOnly` selector), `PutObject` and `DeleteObject` data events for all Amazon S3 bucket/prefix combinations except for a bucket named `amzn-s3-demo-bucket`, data events for an AWS Lambda function named `MyLambdaFunction`, and network activity events for AWS KMS access denied events over a VPC endpoint. Because these are custom advanced event selectors, each set of selectors has a descriptive name. Note that a trailing slash is part of the ARN value for S3 buckets.

```
aws cloudtrail put-event-selectors --trail-name TrailName --advanced-event-selectors '[
  {
    "Name": "Log readOnly and writeOnly management events",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Management"] }
    ]
  },
  {
    "Name": "Log PutObject and DeleteObject events for all but one bucket",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Data"] },
      { "Field": "resources.type", "Equals": ["AWS::S3::Object"] },
      { "Field": "eventName", "Equals": ["PutObject","DeleteObject"] },
      { "Field": "resources.ARN", "NotStartsWith": ["arn:aws:s3:::amzn-s3-demo-bucket/"] }
    ]
  },
  {
    "Name": "Log data plane actions on MyLambdaFunction",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Data"] },
      { "Field": "resources.type", "Equals": ["AWS::Lambda::Function"] },
```

```

    { "Field": "resources.ARN", "Equals": ["arn:aws:lambda:us-
east-2:111122223333:function/MyLambdaFunction"] }
  ]
},
{
  "Name": "Audit AccessDenied AWS KMS events over a VPC endpoint",
  "FieldSelectors": [
    { "Field": "eventCategory", "Equals": ["NetworkActivity"]},
    { "Field": "eventSource", "Equals": ["kms.amazonaws.com"]},
    { "Field": "errorCode", "Equals": ["VpceAccessDenied"]}
  ]
}
]'

```

The example returns the advanced event selectors that are configured for the trail.

```

{
  "AdvancedEventSelectors": [
    {
      "Name": "Log readOnly and writeOnly management events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [ "Management" ]
        }
      ]
    },
    {
      "Name": "Log PutObject and DeleteObject events for all but one bucket",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [ "Data" ]
        },
        {
          "Field": "resources.type",
          "Equals": [ "AWS::S3::Object" ]
        },
        {
          "Field": "resources.ARN",
          "NotStartsWith": [ "arn:aws:s3:::amzn-s3-demo-bucket/" ]
        }
      ]
    }
  ]
}

```

```

    },
    {
      "Name": "Log data plane actions on MyLambdaFunction",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [ "Data" ]
        },
        {
          "Field": "resources.type",
          "Equals": [ "AWS::Lambda::Function" ]
        },
        {
          "Field": "eventName",
          "Equals": [ "Invoke" ]
        },
        {
          "Field": "resources.ARN",
          "Equals": [ "arn:aws:lambda:us-east-2:123456789012:function/
MyLambdaFunction" ]
        }
      ]
    },
    {
      "Name": "Audit AccessDenied AWS KMS events over a VPC endpoint",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": ["NetworkActivity"]
        },
        {
          "Field": "eventSource",
          "Equals": ["kms.amazonaws.com"]
        },
        {
          "Field": "errorCode",
          "Equals": ["VpceAccessDenied"]
        }
      ]
    }
  ],
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName"
}

```


Example trail that uses custom advanced event selectors to log Amazon S3 on AWS Outposts data events

The following example shows how to configure your trail to include all data events for all Amazon S3 on AWS Outposts objects in your outpost. In this release, the supported value for S3 on AWS Outposts events for the `resources.type` field is `AWS::S3Outposts::Object`.

```
aws cloudtrail put-event-selectors --trail-name TrailName --region region \
--advanced-event-selectors \
'[
  {
    "Name": "OutpostsEventSelector",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Data"] },
      { "Field": "resources.type", "Equals": ["AWS::S3Outposts::Object"] }
    ]
  }
]'
```

The command returns the following example output.

```
{
  "AdvancedEventSelectors": [
    {
      "Name": "OutpostsEventSelector",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Data"
          ]
        },
        {
          "Field": "resources.type",
          "Equals": [
            "AWS::S3Outposts::Object"
          ]
        }
      ]
    }
  ],
  "TrailARN": "arn:aws:cloudtrail:region:123456789012:trail/TrailName"
}
```

```
}
```

Example trail that uses advanced event selectors to exclude AWS Key Management Service events

The following example creates an advanced event selector for a trail named *TrailName* to include read-only and write-only management events (by omitting the `readOnly` selector), but to exclude AWS Key Management Service (AWS KMS) events. Because AWS KMS events are treated as management events, and there can be a high volume of them, they can have a substantial impact on your CloudTrail bill if you have more than one trail that captures management events.

If you choose not to log management events, AWS KMS events are not logged, and you cannot change AWS KMS event logging settings.

To start logging AWS KMS events to a trail again, remove the `eventSource` selector, and run the command again.

```
aws cloudtrail put-event-selectors --trail-name TrailName \
--advanced-event-selectors '[
  {
    "Name": "Log all management events except KMS events",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Management"] },
      { "Field": "eventSource", "NotEquals": ["kms.amazonaws.com"] }
    ]
  }
]'
```

The example returns the advanced event selectors that are configured for the trail.

```
{
  "AdvancedEventSelectors": [
    {
      "Name": "Log all management events except KMS events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [ "Management" ]
        },
        {
          "Field": "eventSource",
```

```

        "NotEquals": [ "kms.amazonaws.com" ]
      }
    ]
  },
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName"
}

```

To start logging excluded events to a trail again, remove the eventSource selector, as shown in the following command.

```

aws cloudtrail put-event-selectors --trail-name TrailName \
--advanced-event-selectors '
[
  {
    "Name": "Log all management events",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Management"] }
    ]
  }
]'

```

Example trail that uses advanced event selectors to exclude Amazon RDS Data API management events

The following example creates an advanced event selector for a trail named *TrailName* to include read-only and write-only management events (by omitting the readOnly selector), but to exclude Amazon RDS Data API management events. To exclude Amazon RDS Data API management events, specify the Amazon RDS Data API event source in the string value for the eventSource field: `rdsdata.amazonaws.com`.

If you choose not to log management events, Amazon RDS Data API management events are not logged, and you cannot change Amazon RDS Data API event logging settings.

To start logging Amazon RDS Data API management events to a trail again, remove the eventSource selector, and run the command again.

```

aws cloudtrail put-event-selectors --trail-name TrailName \
--advanced-event-selectors '
[
  {

```

```

    "Name": "Log all management events except Amazon RDS Data API management events",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Management"] },
      { "Field": "eventSource", "NotEquals": ["rdsdata.amazonaws.com"] }
    ]
  }
]'

```

The example returns the advanced event selectors that are configured for the trail.

```

{
  "AdvancedEventSelectors": [
    {
      "Name": "Log all management events except Amazon RDS Data API management events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [ "Management" ]
        },
        {
          "Field": "eventSource",
          "NotEquals": [ "rdsdata.amazonaws.com" ]
        }
      ]
    }
  ],
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName"
}

```

To start logging excluded events to a trail again, remove the eventSource selector, as shown in the following command.

```

aws cloudtrail put-event-selectors --trail-name TrailName \
--advanced-event-selectors '
[
  {
    "Name": "Log all management events",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Management"] }
    ]
  }
]'

```

Configuring basic event selectors

You can only use basic event selectors to log management events and data events for the `AWS::DynamoDB::Table`, `AWS::Lambda::Function`, and `AWS::S3::Object` resource types. You can log management events, all data resource types, and network activity events by using advanced event selectors.

You can use either basic event selectors, or advanced event selectors, but not both. If you apply basic event selectors to a trail that is using advanced event selectors, the advanced event selectors are overwritten.

To view the event selector settings for a trail, run the `get-event-selectors` command. You must either run this command from the AWS Region where it was created (the Home Region), or you must specify that Region by using the `--region` parameter.

```
aws cloudtrail get-event-selectors --trail-name TrailName
```

Note

If the trail is an organization trail and you are a member account in the organization in AWS Organizations, you must provide the full ARN of that trail, and not just the name.

The following example shows the settings for a trail that is using basic event selectors to log management events.

```
{
  "EventSelectors": [
    {
      "ExcludeManagementEventSources": [],
      "IncludeManagementEvents": true,
      "DataResources": [],
      "ReadWriteType": "All"
    }
  ],
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName"
}
```

To create an event selector, run the `put-event-selectors` command. If you want to log Insights events on the trail, be sure the event selector enables logging of the Insights types you want

configured your trail. For more information about logging Insights events, see [Working with CloudTrail Insights](#).

When an event occurs in your account, CloudTrail evaluates the configuration for your trails. If the event matches any event selector for a trail, the trail processes and logs the event. You can configure up to 5 event selectors for a trail and up to 250 data resources for a trail. For more information, see [Logging data events](#).

Topics

- [Example trail with specific event selectors](#)
- [Example trail that logs all management and data events](#)
- [Example trail that does not log AWS Key Management Service events](#)
- [Example trail that logs relevant low-volume AWS Key Management Service events](#)
- [Example trail that does not log Amazon RDS data API events](#)

Example trail with specific event selectors

The following example creates an event selector for a trail named *TrailName* to include read-only and write-only management events, data events for two Amazon S3 bucket/prefix combinations, and data events for a single AWS Lambda function named *hello-world-python-function*.

```
aws cloudtrail put-event-selectors --trail-name TrailName --event-selectors
'[{ "ReadWriteType": "All", "IncludeManagementEvents": true, "DataResources":
  [{ "Type": "AWS::S3::Object", "Values": ["arn:aws:s3:::amzn-s3-
demo-bucket/prefix", "arn:aws:s3:::amzn-s3-demo-bucket2/prefix2"] },
{ "Type": "AWS::Lambda::Function", "Values": ["arn:aws:lambda:us-
west-2:999999999999:function:hello-world-python-function"]} ]}]'
```

The example returns the event selector configured for the trail.

```
{
  "EventSelectors": [
    {
      "ExcludeManagementEventSources": [],
      "IncludeManagementEvents": true,
      "DataResources": [
        {
          "Values": [
            "arn:aws:s3:::amzn-s3-demo-bucket/prefix",
```

```

        "arn:aws:s3:::amzn-s3-demo-bucket2/prefix2"
      ],
      "Type": "AWS::S3::Object"
    },
    {
      "Values": [
        "arn:aws:lambda:us-west-2:123456789012:function:hello-world-
python-function"
      ],
      "Type": "AWS::Lambda::Function"
    },
  ],
  "ReadWriteType": "All"
}
],
"TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName"
}

```

Example trail that logs all management and data events

The following example creates an event selector for a trail named *TrailName2* that includes all management events, including read-only and write-only management events, and data events for all Amazon S3 buckets, AWS Lambda functions, and Amazon DynamoDB tables in the AWS account. Because this example uses basic event selectors, it cannot configure logging for S3 events on AWS Outposts, Amazon Managed Blockchain JSON-RPC calls on Ethereum nodes, or other advanced event selector resource types. You also can't log network activity events using basic event selectors. You must use advanced event selectors to log network activity events and data events for all other resource types. For more information, see [Configuring advanced event selectors](#).

Note

If the trail applies only to one Region, only events in that Region are logged, even though the event selector parameters specify all Amazon S3 buckets and Lambda functions. Event selectors apply only to the Regions where the trail is created.

```

aws cloudtrail put-event-selectors --trail-name TrailName2 --event-selectors
' [{"ReadWriteType": "All", "IncludeManagementEvents": true, "DataResources":
[{"Type": "AWS::S3::Object", "Values": ["arn:aws:s3:::"]}, {"Type":

```

```
"AWS::Lambda::Function","Values": ["arn:aws:lambda"]},{ "Type":
"AWS::DynamoDB::Table","Values": ["arn:aws:dynamodb"]}]']
```

The example returns the event selectors configured for the trail.

```
{
  "EventSelectors": [
    {
      "ExcludeManagementEventSources": [],
      "IncludeManagementEvents": true,
      "DataResources": [
        {
          "Values": [
            "arn:aws:s3:::"
          ],
          "Type": "AWS::S3::Object"
        },
        {
          "Values": [
            "arn:aws:lambda"
          ],
          "Type": "AWS::Lambda::Function"
        }
      ],
      "ReadWriteType": "All"
    }
  ],
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName2"
}
```

Example trail that does not log AWS Key Management Service events

The following example creates an event selector for a trail named *TrailName* to include read-only and write-only management events, but to exclude AWS Key Management Service (AWS KMS) events. Because AWS KMS events are treated as management events, and there can be a high volume of them, they can have a substantial impact on your CloudTrail bill if you have

more than one trail that captures management events. The user in this example has chosen to exclude AWS KMS events from every trail except for one. To exclude an event source, add `ExcludeManagementEventSources` to your event selectors, and specify an event source in the string value.

If you choose not to log management events, AWS KMS events are not logged, and you cannot change AWS KMS event logging settings.

To start logging AWS KMS events to a trail again, pass an empty array as the value of `ExcludeManagementEventSources`.

```
aws cloudtrail put-event-selectors --trail-name TrailName --event-selectors '[{"ReadWriteType": "All", "ExcludeManagementEventSources": ["kms.amazonaws.com"], "IncludeManagementEvents": true}]'
```

The example returns the event selector that is configured for the trail.

```
{
  "EventSelectors": [
    {
      "ExcludeManagementEventSources": [ "kms.amazonaws.com" ],
      "IncludeManagementEvents": true,
      "DataResources": [],
      "ReadWriteType": "All"
    }
  ],
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName"
}
```

To start logging AWS KMS events to a trail again, pass an empty array as the value of `ExcludeManagementEventSources`, as shown in the following command.

```
aws cloudtrail put-event-selectors --trail-name TrailName --event-selectors '[{"ReadWriteType": "All", "ExcludeManagementEventSources": [], "IncludeManagementEvents": true}]'
```

Example trail that logs relevant low-volume AWS Key Management Service events

The following example creates an event selector for a trail named *TrailName* to include write-only management events and AWS KMS events. Because AWS KMS events are treated as management events, and there can be a high volume of them, they can have a substantial impact

on your CloudTrail bill if you have more than one trail that captures management events. The user in this example has chosen to include AWS KMS **Write** events, which will include Disable, Delete and ScheduleKey, but no longer include high-volume actions such as Encrypt, Decrypt, and GenerateDataKey (these are now treated as **Read** events).

```
aws cloudtrail put-event-selectors --trail-name TrailName --event-selectors '[{"ReadWriteType": "WriteOnly", "ExcludeManagementEventSources": [], "IncludeManagementEvents": true}]'
```

The example returns the event selector that is configured for the trail. This logs write-only management events, including AWS KMS events.

```
{
  "EventSelectors": [
    {
      "ExcludeManagementEventSources": [],
      "IncludeManagementEvents": true,
      "DataResources": [],
      "ReadWriteType": "WriteOnly"
    }
  ],
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName"
}
```

Example trail that does not log Amazon RDS data API events

The following example creates an event selector for a trail named *TrailName* to include read-only and write-only management events, but to exclude Amazon RDS Data API events. Because Amazon RDS Data API events are treated as management events, and there can be a high volume of them, they can have a substantial impact on your CloudTrail bill if you have more than one trail that captures management events. The user in this example has chosen to exclude Amazon RDS Data API events from every trail except for one. To exclude an event source, add `ExcludeManagementEventSources` to your event selectors, and specify the Amazon RDS Data API event source in the string value: `rdsdata.amazonaws.com`.

If you choose not to log management events, Amazon RDS Data API events are not logged, and you cannot change event logging settings.

To start logging Amazon RDS Data API management events to a trail again, pass an empty array as the value of `ExcludeManagementEventSources`.

```
aws cloudtrail put-event-selectors --trail-name TrailName --event-selectors '[{"ReadWriteType": "All", "ExcludeManagementEventSources": ["rdsdata.amazonaws.com"], "IncludeManagementEvents": true}]'
```

The example returns the event selector that is configured for the trail.

```
{
  "EventSelectors": [
    {
      "ExcludeManagementEventSources": [ "rdsdata.amazonaws.com" ],
      "IncludeManagementEvents": true,
      "DataResources": [],
      "ReadWriteType": "All"
    }
  ],
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName"
}
```

To start logging Amazon RDS Data API management events to a trail again, pass an empty array as the value of `ExcludeManagementEventSources`, as shown in the following command.

```
aws cloudtrail put-event-selectors --trail-name TrailName --event-selectors '[{"ReadWriteType": "All", "ExcludeManagementEventSources": [], "IncludeManagementEvents": true}]'
```

Stopping and starting logging for a trail

The following commands start and stop CloudTrail logging.

```
aws cloudtrail start-logging --name awscloudtrail-example
```

```
aws cloudtrail stop-logging --name awscloudtrail-example
```

Note

Before deleting a bucket, run the stop-logging command to stop delivering events to the bucket. If you don't stop logging, CloudTrail attempts to deliver log files to a bucket with the same name for a limited period of time.

If you stop logging or delete a trail, CloudTrail Insights is disabled on that trail.

Deleting a trail

If you've enabled CloudTrail management events in Amazon Security Lake, you are required to maintain at least one organizational trail that is multi-Region and logs both read and write management events. You cannot delete a trail if it is the only trail you have that meets this requirement, unless you turn off CloudTrail management events in Security Lake.

You can delete a trail with the following command. You can delete a trail only in the Region it was created (the Home Region).

Important

While deleting a CloudTrail trail is an irreversible action, CloudTrail does not delete log files in the Amazon S3 bucket for that trail, the Amazon S3 bucket itself, or the CloudWatch log group to which the trail delivers events. Deleting a multi-Region trail will stop logging of events in all AWS Regions enabled in your AWS account. Deleting a single-Region trail will stop logging of events in that Region only. It will not stop logging of events in other Regions even if the trails in those other Regions have identical names to the deleted trail. For information about account closure and deletion of CloudTrail trails, see [AWS account closure and trails](#).

```
aws cloudtrail delete-trail --name awscloudtrail-example
```

When you delete a trail, you do not delete the Amazon S3 bucket or the Amazon SNS topic associated with it. Use the AWS Management Console, AWS CLI, or service API to delete these resources separately.

Creating multiple trails

You can use CloudTrail log files to troubleshoot operational or security issues in your AWS account. You can create trails for different users, who can create and manage their own trails. You can configure trails to deliver log files to separate S3 buckets or shared S3 buckets.

Note


The first copy of management events in each AWS Region for an account is free. If you create more trails that deliver the same management events to other destinations, those

subsequent deliveries incur CloudTrail costs. For more information about CloudTrail costs, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail trail costs](#).

For example, you might have the following users:

- A security administrator creates a trail in the Europe (Ireland) Region and configures KMS log file encryption. The trail delivers the log files to an S3 bucket in the Europe (Ireland) Region.
- An IT auditor creates a trail in the Europe (Ireland) Region and configures log file integrity validation to ensure the log files have not changed since CloudTrail delivered them. The trail is configured to deliver log files to an S3 bucket in the Europe (Frankfurt) Region
- A developer creates a trail in the Europe (Frankfurt) Region and configures CloudWatch alarms to receive notifications for specific API activity. The trail shares the same S3 bucket as the trail configured for log file integrity.
- Another developer creates a trail in the Europe (Frankfurt) Region and configures SNS. The log files are delivered to a separate S3 bucket in the Europe (Frankfurt) Region.

The following image illustrates this example.

**Note**

You can create up to five trails per AWS Region. A multi-Region trail counts as one trail per Region.

You can use resource-level permissions to manage a user's ability to perform specific operations on CloudTrail.

For example, you might grant one user permission to view trail activity, but restrict the user from starting or stopping logging for a trail. You might grant another user full permission to create and delete trails. This gives you granular control over your trails and user access.

For more information about resource-level permissions, see [Examples: Creating and applying policies for actions on specific trails](#).

For more information about multiple trails, see the [CloudTrail FAQs](#).

Creating a trail for an organization

If you have created an organization in AWS Organizations, you can create a trail that logs all events for all AWS accounts in that organization. This is sometimes called an *organization trail*.

The management account for the organization can assign a [delegated administrator](#) to create new organization trails or manage existing organization trails. For more information on adding a delegated administrator, see [Add a CloudTrail delegated administrator](#).

The management account for the organization can edit an existing trail in their account, and apply it to an organization, making it an organization trail. Organization trails log events for the management account and all member accounts in the organization. For more information about AWS Organizations, see [Organizations Terminology and Concepts](#).

Note

You must sign in with the management account or a delegated administrator account associated with an organization to create an organization trail. You must also have [sufficient permissions](#) for the user or role in the management or delegated administrator account to create the trail. If you don't have sufficient permissions, you won't have the option to apply the trail to an organization.

All organization trails created using the console are multi-Region organization trails that log events from the [enabled](#) AWS Regions in each member account in the organization. To log events in all AWS partitions in your organization, create a multi-Region organization trail in each partition. You can create either a single-Region or multi-Region organization trail by using the AWS CLI. If you create a single-Region trail, you log activity only in the trail's AWS Region (also referred to as the *Home Region*).

Although most AWS Regions are enabled by default for your AWS account, you must manually enable certain Regions (also referred to as *opt-in Regions*). For information about which Regions are enabled by default, see [Considerations before enabling and disabling Regions](#) in the *AWS Account Management Reference Guide*. For the list of Regions CloudTrail supports, see [CloudTrail supported Regions](#).

When you create an organization trail, a copy of the trail with the name that you give it is created in the member accounts that belongs to your organization.

- If the organization trail is for a **single-Region** and the trail's home Region is **not an opt-in Region**, a copy of the trail is created in the organization trail's home Region in each member account.
- If the organization trail is for a **single-Region** and the trail's home Region is **an opt-in Region**, a copy of the trail is created in the organization trail's home Region in the member accounts that have enabled that Region.
- If the organization trail is **multi-Region** and the trail's home Region is **not an opt-in Region**, a copy of the trail is created in each enabled AWS Region in each member account. When a member account enables an opt-in Region, a copy of the multi-Region trail is created in the newly opted in Region for the member account after activation of that Region is complete.
- If the organization trail is **multi-Region** and the home Region is **an opt-in Region**, member accounts will not send activity to the organization trail unless they opt into the AWS Region where the multi-Region trail was created. For example, if you create a multi-Region trail and choose the Europe (Spain) Region as the home Region for the trail, only member accounts that enabled the Europe (Spain) Region for their account will send their account activity to the organization trail.

Note

CloudTrail creates organization trails in member accounts even if a resource validation fails. Examples of validation failures include:

- an incorrect Amazon S3 bucket policy
- an incorrect Amazon SNS topic policy
- inability to deliver to a CloudWatch Logs log group
- insufficient permission to encrypt using a KMS key


A member account with CloudTrail permissions can see any validation failures for an organization trail by viewing the trail's details page on the CloudTrail console, or by running the AWS CLI [get-trail-status](#) command.

Users with CloudTrail permissions in member accounts can see organization trails when they log into the CloudTrail console from their AWS accounts, or when they run AWS CLI commands such as `describe-trails`. However, users in member accounts do not have sufficient permissions to delete organization trails, turn logging on or off, change what types of events are logged, or otherwise change an organization trail in any way.

When you create an organization trail in the console, CloudTrail creates a [service-linked role](#) to perform logging tasks in your organization's member accounts. This role is named **AWSServiceRoleForCloudTrail**, and is required for CloudTrail to log events for an organization. If an AWS account is added to an organization, the organization trail and service-linked role are added to that AWS account, and logging starts for that account automatically in the organization trail. If an AWS account is removed from an organization, the organization trail and service-linked role are deleted from the AWS account that is no longer part of the organization. However, log files for the removed account that were created before the account's removal remain in the Amazon S3 bucket where log files are stored for the trail.

If the management account for an AWS Organizations organization creates an organization trail, but then is subsequently removed as the organization's management account, any organization trail created using their account becomes a non-organization trail.

In the following example, the organization's management account 111111111111 creates a trail named *MyOrganizationTrail* for the organization *o-exampleorgid*. The trail logs activity for all accounts in the organization in the same Amazon S3 bucket. All accounts in the organization can see *MyOrganizationTrail* in their list of trails, but member accounts cannot remove or modify the organization trail. Only the management account or delegated administrator account can change or delete the trail for the organization. Only the management account can remove a member account from an organization. Similarly, by default, only the management account has access to the Amazon S3 bucket for the trail, and the logs contained within it. The high-level bucket structure for log files contains a folder named with the organization ID, and subfolders named with the account IDs for each account in the organization. Events for each member account are logged in the folder that corresponds to the member account ID. If member account 444444444444 is removed from the organization, *MyOrganizationTrail* and the service-linked role no longer appear in AWS account 444444444444, and no further events are logged for that account by the organization trail. However, the 444444444444 folder remains in the Amazon S3 bucket, with all logs created before the removal of the account from the organization.



In this example, the ARN of the trail created in the management account is `aws:cloudtrail:us-east-2:111111111111:trail/MyOrganizationTrail`. This ARN is the ARN for the trail in all member accounts as well.

Organization trails are similar to regular trails in many ways. You can create multiple trails for your organization, and choose whether to create a multi-Region or single-Region organization trail, and what kinds of events you want logged in your organization trail, just as in any other trail. However, there are some differences. For example, when you create a trail in the console and choose whether to log data events for Amazon S3 buckets or AWS Lambda functions, the only resources listed in the CloudTrail console are those for the management account, but you can add the ARNs for resources in member accounts. Data events for specified member account resources are logged without having to manually configure cross-account access to those resources. For more information about logging management events, Insights events, and data events, see [Logging management events](#), [Logging data events](#), and [Working with CloudTrail Insights](#).

Note

In the console, you create a multi-Region trail. It's a recommended best practice to log activity in all enabled Regions in your AWS account, because it helps you keep your AWS environment more secure. To create a single-Region trail, [use the AWS CLI](#).

When you view events in **Event history** for an organization in AWS Organizations, you can view the events only for the AWS account with which you are signed in. For example, if you are signed in with the organization management account, **Event history** shows the last 90 days of management

events for the management account. Organization member account events are not shown in **Event history** for the management account. To view member account events in **Event history**, sign in with the member account.

You can configure other AWS services to further analyze and act upon the event data collected in CloudTrail logs for an organization trail the same way you would for any other trail. For example, you can analyze the data in an organization trail using Amazon Athena. For more information, see [AWS service integrations with CloudTrail logs](#).

Topics

- [Moving from member account trails to organization trails](#)
- [Prepare for creating a trail for your organization](#)
- [Creating a trail for your organization in the console](#)
- [Creating a trail for an organization with the AWS CLI](#)
- [Troubleshooting issues with an organization trail](#)

Moving from member account trails to organization trails

If you already have CloudTrail trails configured for individual member accounts, but want to move to an organization trail to log events in all accounts, you do not want to lose events by deleting individual member account trails before you create an organization trail. But when you have two trails, you incur higher costs because of the additional copy of events delivered to the organization trail.

To help manage costs, but avoid losing events before log delivery starts on the organization trail, consider keeping both your individual member account trails and your organization trail for up to one day. This ensures that the organization trail logs all events, but you incur duplicate event costs only for one day. After the first day, you can stop logging on (or delete) any individual member account trails.

Prepare for creating a trail for your organization

Before you create a trail for your organization, be sure that your organization management account or delegated administrator account is set up correctly for trail creation.

- Your organization must have all features enabled before you can create a trail for it. For more information, see [Enabling All Features in Your Organization](#).

- The management account must have the **AWSServiceRoleForOrganizations** role. This role is created automatically by Organizations when you create your organization, and is required for CloudTrail to log events for an organization. For more information, see [Organizations and service-linked roles](#).
- The user or role that creates the organization trail in the management or delegated administrator account must have sufficient permissions to create an organization trail. You must at least apply either the **AWSCloudTrail_FullAccess** policy, or an equivalent policy, to that role or user. You must also have sufficient permissions in IAM and Organizations to create the service-linked role and enable trusted access. If you choose to create a new S3 bucket for an organization trail using the CloudTrail console, your policy also needs to include the `s3:PutEncryptionConfiguration` action because by default server-side encryption is enabled for the bucket. The following example policy shows the minimum required permissions.

Note

You shouldn't share the **AWSCloudTrail_FullAccess** policy broadly across your AWS account. Instead, you should restrict it to AWS account administrators due to the highly sensitive nature of the information collected by CloudTrail. Users with this role have the ability to turn off or reconfigure the most sensitive and important auditing functions in their AWS accounts. For this reason, you must closely control and monitor access to this policy.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "iam:GetRole",
        "organizations:EnableAWSServiceAccess",
        "organizations:ListAccounts",
        "iam:CreateServiceLinkedRole",
        "organizations:DisableAWSServiceAccess",
        "organizations:DescribeOrganization",
        "organizations:ListAWSServiceAccessForOrganization",
```

```

        "s3:PutEncryptionConfiguration"
      ],
      "Resource": "*"
    }
  ]
}

```

- To use the AWS CLI or the CloudTrail APIs to create an organization trail, you must enable trusted access for CloudTrail in Organizations, and you must manually create an Amazon S3 bucket with a policy that allows logging for an organization trail. For more information, see [Creating a trail for an organization with the AWS CLI](#).
- To use an existing IAM role to add monitoring of an organization trail to Amazon CloudWatch Logs, you must manually modify the IAM role to allow delivery of CloudWatch Logs for member accounts to the CloudWatch Logs group for the management account, as shown in the following example.

Note

You must use an IAM role and CloudWatch Logs log group that exists in your own account. You cannot use an IAM role or CloudWatch Logs log group owned by a different account.

JSON

```

{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "AWSCloudTrailCreateLogStream20141101",
      "Effect": "Allow",
      "Action": [
        "logs:CreateLogStream"
      ],
      "Resource": [
        "arn:aws:logs:us-east-2:111111111111:log-group:CloudTrail/DefaultLogGroupTest:log-stream:111111111111_CloudTrail_us-east-2*",
        "arn:aws:logs:us-east-2:111111111111:log-group:CloudTrail/DefaultLogGroupTest:log-stream:o-exampleorgid_"
      ]
    }
  ]
}

```

```

    },
    {
      "Sid": "AWSCloudTrailPutLogEvents20141101",
      "Effect": "Allow",
      "Action": [
        "logs:PutLogEvents"
      ],
      "Resource": [
        "arn:aws:logs:us-east-2:111111111111:log-group:CloudTrail/DefaultLogGroupTest:log-stream:111111111111_CloudTrail_us-east-2*",
        "arn:aws:logs:us-east-2:111111111111:log-group:CloudTrail/DefaultLogGroupTest:log-stream:o-exampleorgid_"
      ]
    }
  ]
}

```

You can learn more about CloudTrail and Amazon CloudWatch Logs in [Monitoring CloudTrail Log Files with Amazon CloudWatch Logs](#). In addition, consider the limits on CloudWatch Logs and the pricing considerations for the service before deciding to enable the experience for an organization trail. For more information, see [CloudWatch Logs Limits](#) and [Amazon CloudWatch Pricing](#).

- To log data events in your organization trail for specific resources in member accounts, have ready a list of Amazon Resource Names (ARNs) for each of those resources. Member account resources are not displayed in the CloudTrail console when you create a trail; you can browse for resources in the management account on which data event collection is supported, such as S3 buckets. Similarly, if you want to add specific member resources when creating or updating an organization trail at the command line, you need the ARNs for those resources.

Note

Additional charges apply for logging data events. For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

You should also consider reviewing how many trails already exist in the management account and in the member accounts before creating an organization trail. CloudTrail limits the number of trails that can be created in each Region. You cannot exceed this limit in the Region where you create the

organization trail in the management account. However, the trail will be created in the member accounts even if member accounts have reached the limit of trails in a Region. While the first trail of management events in any Region is free, charges apply to additional trails. To reduce the potential cost of an organization trail, consider deleting any unneeded trails in the management and member accounts. For more information about CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Security best practices in organization trails

As a security best practice, we recommend adding the `aws:SourceArn` condition key to resource policies (such as those for S3 buckets, KMS keys, or SNS topics) that you use with an organization trail. The value of `aws:SourceArn` is the organization trail ARN (or ARNs, if you are using the same resource for more than one trail, such as the same S3 bucket to store logs for more than one trail). This ensures that the resource, such as an S3 bucket, accepts only data that is associated with the specific trail. The trail ARN must use the account ID of the management account. The following policy snippet shows an example where more than one trail is using the resource.

```
"Condition": {
  "StringEquals": {
    "aws:SourceArn": ["Trail_ARN_1", ..., "Trail_ARN_n"]
  }
}
```

For information about how to add condition keys to resource policies, see the following:

- [Amazon S3 bucket policy for CloudTrail](#)
- [Configure AWS KMS key policies for CloudTrail](#)
- [Amazon SNS topic policy for CloudTrail](#)

Creating a trail for your organization in the console

To create an organization trail from the CloudTrail console, you must sign in to the console as a user or role in the management or delegated administrator account that has [sufficient permissions](#). If you don't sign in with the management or delegated administrator account, you won't see the option to apply a trail to an organization when you create or edit a trail from the CloudTrail console.

To create an organization trail with the AWS Management Console

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.

You must be signed in using an IAM identity in the management or delegated administrator account with [sufficient permissions](#) to create an organization trail.

2. Choose **Trails**, and then choose **Create trail**.
3. On the **Create Trail** page, for **Trail name**, type a name for your trail. For more information, see [Naming requirements for CloudTrail resources, S3 buckets, and KMS keys](#).
4. Select **Enable for all accounts in my organization**. You only see this option if you sign in to the console with a user or role in the management or delegated administrator account. To successfully create an organization trail, be sure that the user or role has [sufficient permissions](#).
5. For **Storage location**, choose **Create new S3 bucket** to create a bucket. When you create a bucket, CloudTrail creates and applies the required bucket policies.

Note

If you chose **Use existing S3 bucket**, specify a bucket in **Trail log bucket name**, or choose **Browse** to choose a bucket. You can choose a bucket belonging to any account, however, the bucket policy must grant CloudTrail permission to write to it. For information about manually editing the bucket policy, see [Amazon S3 bucket policy for CloudTrail](#).

To make it easier to find your logs, create a new folder (also known as a *prefix*) in an existing bucket to store your CloudTrail logs. Enter the prefix in **Prefix**.

6. For **Log file SSE-KMS encryption**, choose **Enabled** if you want to encrypt your log files and digest files using SSE-KMS encryption instead of SSE-S3 encryption. The default is **Enabled**. If you don't enable SSE-KMS encryption, your log files and digest files are encrypted using SSE-S3 encryption. For more information about SSE-KMS encryption, see [Using server-side encryption with AWS Key Management Service \(SSE-KMS\)](#). For more information about SSE-S3 encryption, see [Using Server-Side Encryption with Amazon S3-Managed Encryption Keys \(SSE-S3\)](#).

If you enable SSE-KMS encryption, choose a **New** or **Existing** AWS KMS key. In **AWS KMS Alias**, specify an alias, in the format `alias/MyAliasName`. For more information, see [Updating a resource to use your KMS key with the console](#).

 Note

You can also type the ARN of a key from another account. For more information, see [Updating a resource to use your KMS key with the console](#). The key policy must allow CloudTrail to use the key to encrypt your log files and digest files, and allow the users you specify to read log files or digest files in unencrypted form. For information about manually editing the key policy, see [Configure AWS KMS key policies for CloudTrail](#).

7. In **Additional settings**, configure the following.
 - a. For **Log file validation**, choose **Enabled** to have log digests delivered to your S3 bucket. You can use the digest files to verify that your log files did not change after CloudTrail delivered them. For more information, see [Validating CloudTrail log file integrity](#).
 - b. For **SNS notification delivery**, choose **Enabled** to be notified each time a log is delivered to your bucket. CloudTrail stores multiple events in a log file. SNS notifications are sent for every log file, not for every event. For more information, see [Configuring Amazon SNS notifications for CloudTrail](#).

If you enable SNS notifications, for **Create a new SNS topic**, choose **New** to create a topic, or choose **Existing** to use an existing topic. If you are creating multi-Region trail, SNS notifications for log file deliveries from all Regions are sent to the single SNS topic that you create.

If you choose **New**, CloudTrail specifies a name for the new topic for you, or you can type a name. If you choose **Existing**, choose an SNS topic from the drop-down list. You can also enter the ARN of a topic from another Region or from an account with appropriate permissions. For more information, see [Amazon SNS topic policy for CloudTrail](#).

If you create a topic, you must subscribe to the topic to be notified of log file delivery. You can subscribe from the Amazon SNS console. Due to the frequency of notifications, we recommend that you configure the subscription to use an Amazon SQS queue to handle notifications programmatically. For more information, see [Getting started with Amazon SNS](#) in the *Amazon Simple Notification Service Developer Guide*.

8. Optionally, configure CloudTrail to send log files to CloudWatch Logs by choosing **Enabled in CloudWatch Logs**. For more information, see [Sending events to CloudWatch Logs](#).

 Note

Only the management account can configure a CloudWatch Logs log group for an organization trail using the console. The delegated administrator can configure a CloudWatch Logs log group using the AWS CLI or CloudTrail `CreateTrail` or `UpdateTrail` API operations.

- a. If you enable integration with CloudWatch Logs, choose **New** to create a new log group, or **Existing** to use an existing one. If you choose **New**, CloudTrail specifies a name for the new log group for you, or you can type a name.
- b. If you choose **Existing**, choose a log group from the drop-down list.
- c. Choose **New** to create a new IAM role for permissions to send logs to CloudWatch Logs. Choose **Existing** to choose an existing IAM role from the drop-down list. The policy statement for the new or existing role is displayed when you expand **Policy document**. For more information about this role, see [Role policy document for CloudTrail to use CloudWatch Logs for monitoring](#).

 Note

When you configure a trail, you can choose an S3 bucket and Amazon SNS topic that belong to another account. However, if you want CloudTrail to deliver events to a CloudWatch Logs log group, you must choose a log group that exists in your current account.

9. For **Tags**, you can add up to 50 tag key pairs to help you identify, sort, and control access to your trail. Tags can help you identify both your CloudTrail trails and the Amazon S3 buckets that contain CloudTrail log files. You can then use resource groups for your CloudTrail resources. For more information, see [AWS Resource Groups](#) and [Tags](#).
10. On the **Choose log events** page, choose the event types that you want to log. For **Management events**, do the following.
 - a. For **API activity**, choose if you want your trail to log **Read** events, **Write** events, or both. For more information, see [Management events](#).

- b. Choose **Exclude AWS KMS events** to filter AWS Key Management Service (AWS KMS) events out of your trail. The default setting is to include all AWS KMS events.

The option to log or exclude AWS KMS events is available only if you log management events on your trail. If you choose not to log management events, AWS KMS events are not logged, and you cannot change AWS KMS event logging settings.

AWS KMS actions such as Encrypt, Decrypt, and GenerateDataKey typically generate a large volume (more than 99%) of events. These actions are now logged as **Read** events. Low-volume, relevant AWS KMS actions such as Disable, Delete, and ScheduleKey (which typically account for less than 0.5% of AWS KMS event volume) are logged as **Write** events.

To exclude high-volume events like Encrypt, Decrypt, and GenerateDataKey, but still log relevant events such as Disable, Delete and ScheduleKey, choose to log **Write** management events, and clear the check box for **Exclude AWS KMS events**.

- c. Choose **Exclude Amazon RDS Data API events** to filter Amazon Relational Database Service Data API events out of your trail. The default setting is to include all Amazon RDS Data API events. For more information about Amazon RDS Data API events, see [Logging Data API calls with AWS CloudTrail](#) in the *Amazon RDS User Guide for Aurora*.
11. To log data events, choose **Data events**. Additional charges apply for logging data events. For more information, see [AWS CloudTrail Pricing](#).

12.

 Important

Steps 12-16 are for configuring data events using advanced event selectors, which is the default. Advanced event selectors let you configure more [resource types](#) and offer fine-grained control over which data events your trail captures. If you plan to log network activity events, you must use advanced event selectors. If you are using basic event selectors, complete the steps in [Configure data event settings using basic event selectors](#), then return to step 17 of this procedure.

For **Resource type**, choose the resource type on which you want to log data events. For more information about available resource types, see [Data events](#).

13. Choose a log selector template. You can choose a predefined template, or choose **Custom** to define your own event collection conditions.

You can choose from the following predefined templates:

- **Log all events** – Choose this template to log all events.
- **Log only read events** – Choose this template to log only read events. Read-only events are events that do not change the state of a resource, such as `Get*` or `Describe*` events.
- **Log only write events** – Choose this template to log only write events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events.
- **Log only AWS Management Console events** – Choose this template to log only events originating from the AWS Management Console.
- **Exclude AWS service initiated events** – Choose this template to exclude AWS service events, which have an `eventType` of `AwsServiceEvent`, and events initiated with AWS service-linked roles (SLRs).

Note

Choosing a predefined template for S3 buckets enables data event logging for all buckets currently in your AWS account and any buckets you create after you finish creating the trail. It also enables logging of data event activity performed by any IAM identity in your AWS account, even if that activity is performed on a bucket that belongs to another AWS account.

If the trail applies only to one Region, choosing a predefined template that logs all S3 buckets enables data event logging for all buckets in the same Region as your trail and any buckets you create later in that Region. It will not log data events for Amazon S3 buckets in other Regions in your AWS account.

If you're creating a multi-Region trail, choosing a predefined template for Lambda functions enables data event logging for all functions currently in your AWS account, and any Lambda functions you might create in any Region after you finish creating the trail. If you are creating a trail for a single Region (done by using the AWS CLI), this selection enables data event logging for all functions currently in that Region in your AWS account, and any Lambda functions you might create in that Region after you finish creating the trail. It does not enable data event logging for Lambda functions created in other Regions.

Logging data events for all functions also enables logging of data event activity performed by any IAM identity in your AWS account, even if that activity is performed on a function that belongs to another AWS account.

14. (Optional) In **Selector name**, enter a name to identify your selector. The selector name is a descriptive name for an advanced event selector, such as "Log data events for only two S3 buckets". The selector name is listed as Name in the advanced event selector and is viewable if you expand the **JSON view**.
15. If you selected **Custom**, in **Advanced event selectors** build an expression based on the values of advanced event selector fields.

 Note

Selectors don't support the use of wildcards like `*`. To match multiple values with a single condition, you may use `StartsWith`, `EndsWith`, `NotStartsWith`, or `NotEndsWith` to explicitly match the beginning or end of the event field.

- a. Choose from the following fields.
 - **readOnly** - `readOnly` can be set to **equals** a value of `true` or `false`. Read-only data events are events that do not change the state of a resource, such as `Get*` or `Describe*` events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events. To log both read and write events, don't add a `readOnly` selector.
 - **eventName** - `eventName` can use any operator. You can use it to include or exclude any data event logged to CloudTrail, such as `PutBucket`, `GetItem`, or `GetSnapshotBlock`.
 - **eventSource** – The event source to include or exclude. This field can use any operator.
 - **eventType** – The event type to include or exclude. For example, you can set this field to **not equals** `AwsServiceEvent` to exclude [AWS service events](#). For a list of event types, see [eventType](#) in [CloudTrail record contents for management, data, and network activity events](#).
 - **sessionCredentialFromConsole** – Include or exclude events originating from an AWS Management Console session. This field can be set to **equals** or **not equals** with a value of `true`.

- **userIdentity.arn** – Include or exclude events for actions taken by specific IAM identities. For more information, see [CloudTrail userIdentity element](#).
- **resources.ARN** – You can use any operator with `resources.ARN`, but if you use **equals** or **does not equal**, the value must exactly match the ARN of a valid resource of the type you've specified in the template as the value of `resources.type`.

 Note

You can't use the `resources.ARN` field to filter resource types that do not have ARNs.

For more information about the ARN formats of data event resources, see [Actions, resources, and condition keys for AWS services](#) in the *Service Authorization Reference*.

- b. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions. For example, to exclude data events for two S3 buckets from data events that are logged on your event data store, you can set the field to **resources.ARN**, set the operator for **does not start with**, and then paste in an S3 bucket ARN for which you do not want to log events.

To add the second S3 bucket, choose **+ Condition**, and then repeat the preceding instruction, pasting in the ARN for or browsing for a different bucket.

For information about how CloudTrail evaluates multiple conditions, see [How CloudTrail evaluates multiple conditions for a field](#).

 Note

You can have a maximum of 500 values for all selectors on an event data store. This includes arrays of multiple values for a selector such as `eventName`. If you have single values for all selectors, you can have a maximum of 500 conditions added to a selector.

- c. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields. For example, do not specify an ARN in one selector to be equal to a value, then specify that the ARN not equal the same value in another selector.

16. To add resource type on which to log data events, choose **Add data event type**. Repeat steps 12 through this step to configure advanced event selectors for the resource type.
17. To log network activity events, choose **Network activity events**. Network activity events enable VPC endpoint owners to record AWS API calls made using their VPC endpoints from a private VPC to the AWS service. Additional charges apply for logging data events. For more information, see [AWS CloudTrail Pricing](#).

To log network activity events, do the following:

- a. From **Network activity event source**, choose the source for network activity events.
 - b. In **Log selector template**, choose a template. You can choose to log all network activity events, log all network activity access denied events, or choose **Custom** to build a custom log selector to filter on multiple fields, such as eventName and vpcEndpointId.
 - c. (Optional) Enter a name to identify the selector. The selector name is listed as **Name** in the advanced event selector and is viewable if you expand the **JSON view**.
 - d. In **Advanced event selectors** build expressions by choosing values for **Field**, **Operator**, and **Value**. You can skip this step if you are using a predefined log template.
 - i. For excluding or including network activity events, you can choose from the following fields in the console.
 - **eventName** – You can use any operator with eventName. You can use it to include or exclude any event, such as CreateKey.
 - **errorCode** – You can use it to filter on an error code. Currently, the only supported errorCode is VpceAccessDenied.
 - **vpcEndpointId** – Identifies the VPC endpoint that the operation passed through. You can use any operator with vpcEndpointId.
 - ii. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions.
 - iii. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields.
 - e. To add another event source for which you want to log network activity events, choose **Add network activity event selector**.
 - f. Optionally, expand **JSON view** to see your advanced event selectors as a JSON block.
18. Choose **Insights events** if you want your trail to log CloudTrail Insights events.

In **Event type**, select **Insights events**. In **Insights events**, choose **API call rate**, **API error rate**, or both. You must be logging **Write** management events to log Insights events for **API call rate**. You must be logging **Read** or **Write** management events to log Insights events for **API error rate**.

CloudTrail Insights analyzes management events for unusual activity, and logs events when anomalies are detected. By default, trails don't log Insights events. For more information about Insights events, see [Working with CloudTrail Insights](#). Additional charges apply for logging Insights events. For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Insights events are delivered to a different folder named `/CloudTrail-Insight` of the same S3 bucket that is specified in the **Storage location** area of the trail details page. CloudTrail creates the new prefix for you. For example, if your current destination S3 bucket is named `amzn-s3-demo-destination-bucket/AWSLogs/CloudTrail/`, the S3 bucket name with a new prefix is named `amzn-s3-demo-destination-bucket/AWSLogs/CloudTrail-Insight/`.

19. When you are finished choosing event types to log, choose **Next**.
20. On the **Review and create** page, review your choices. Choose **Edit** in a section to change the trail settings shown in that section. When you are ready to create the trail, choose **Create trail**.
21. The new trail appears on the **Trails** page. An organization trail might take up to 24 hours to be created in all enabled Regions in all member accounts. The **Trails** page shows the trails in your account from all Regions. In about 5 minutes, CloudTrail publishes log files that show the AWS API calls made in your organization. You can see the log files in the Amazon S3 bucket that you specified.

Note

You can't rename a trail after it has been created. Instead, you can delete the trail and create a new one.

Next steps

After you create your trail, you can return to the trail to make changes:

- Change the configuration of your trail by editing it. For more information, see [Updating a trail with the CloudTrail console](#).
- If needed, configure the Amazon S3 bucket to allow specific users in member accounts to read the log files for the organization. For more information, see [Sharing CloudTrail log files between AWS accounts](#).
- Configure CloudTrail to send log files to CloudWatch Logs. For more information, see [Sending events to CloudWatch Logs](#) and [the CloudWatch Logs item](#) in [Prepare for creating a trail for your organization](#).

 Note

Only the management account can configure a CloudWatch Logs log group for an organization trail.

- Create a table and use it to run a query in Amazon Athena to analyze your AWS service activity. For more information, see [Creating a Table for CloudTrail Logs in the CloudTrail Console](#) in the [Amazon Athena User Guide](#).
- Add custom tags (key-value pairs) to the trail.
- To create another organization trail, return to the **Trails** page and choose **Create trail**.

 Note

When you configure a trail, you can choose an Amazon S3 bucket and SNS topic that belong to another account. However, if you want CloudTrail to deliver events to a CloudWatch Logs log group, you must choose a log group that exists in your current account.

Creating a trail for an organization with the AWS CLI

You can create an organization trail by using the AWS CLI. The AWS CLI is regularly updated with additional functionality and commands. To help ensure success, be sure that you have installed or updated to a recent AWS CLI version before you begin.

Note

The examples in this section are specific to creating and updating organization trails. For examples of using the AWS CLI to manage trails, see [Managing trails with the AWS CLI](#) and [Configuring CloudWatch Logs monitoring with the AWS CLI](#). When creating or updating an organization trail with the AWS CLI, you must use an AWS CLI profile in the management account or delegated administrator account with sufficient permissions. If you are converting an organization trail to a non-organization trail, you must use the management account for the organization.

You must configure the Amazon S3 bucket used for an organization trail with sufficient permissions.

Create or update an Amazon S3 bucket to use to store the log files for an organization trail

You must specify an Amazon S3 bucket to receive the log files for an organization trail. This bucket must have a policy that allows CloudTrail to put the log files for the organization into the bucket.

The following is an example policy for an Amazon S3 bucket named *amzn-s3-demo-bucket*, which is owned by the organization's management account. Replace *amzn-s3-demo-bucket*, *region*, *managementAccountID*, *trailName*, and *o-organizationID* with the values for your organization

This bucket policy contains three statements.

- The first statement allows CloudTrail to call the Amazon S3 `GetBucketAc1` action on the Amazon S3 bucket.
- The second statement allows logging in the event the trail is changed from an organization trail to a trail for that account only.
- The third statement allows logging for an organization trail.

The example policy includes an `aws:SourceArn` condition key for the Amazon S3 bucket policy. The IAM global condition key `aws:SourceArn` helps ensure that CloudTrail writes to the S3 bucket only for a specific trail or trails. In an organization trail, the value of `aws:SourceArn` must be a trail ARN that is owned by the management account, and uses the management account ID.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "AWSCloudTrailAclCheck20150319",
      "Effect": "Allow",
      "Principal": {
        "Service": [
          "cloudtrail.amazonaws.com"
        ]
      },
      "Action": "s3:GetBucketAcl",
      "Resource": "arn:aws:s3:::amzn-s3-demo-bucket",
      "Condition": {
        "StringEquals": {
          "aws:SourceArn":
            "arn:aws:cloudtrail:region:managementAccountID:trail/trailName"
        }
      }
    },
    {
      "Sid": "AWSCloudTrailWrite20150319",
      "Effect": "Allow",
      "Principal": {
        "Service": [
          "cloudtrail.amazonaws.com"
        ]
      },
      "Action": "s3:PutObject",
      "Resource": "arn:aws:s3:::amzn-s3-demo-bucket/
AWSLogs/managementAccountID/*",
      "Condition": {
        "StringEquals": {
          "s3:x-amz-acl": "bucket-owner-full-control",
          "aws:SourceArn":
            "arn:aws:cloudtrail:region:managementAccountID:trail/trailName"
        }
      }
    },
    {
      "Sid": "AWSCloudTrailOrganizationWrite20150319",
```

```

        "Effect": "Allow",
        "Principal": {
            "Service": [
                "cloudtrail.amazonaws.com"
            ]
        },
        "Action": "s3:PutObject",
        "Resource": "arn:aws:s3:::amzn-s3-demo-bucket/AWSLogs/o-  

organizationID/*",
        "Condition": {
            "StringEquals": {
                "s3:x-amz-acl": "bucket-owner-full-control",
                "aws:SourceArn":
"arn:aws:cloudtrail:region:managementAccountID:trail/trailName"
            }
        }
    }
}

```

This example policy does not allow any users from member accounts to access the log files created for the organization. By default, organization log files are accessible only to the management account. For information about how to allow read access to the Amazon S3 bucket for IAM users in member accounts, see [Sharing CloudTrail log files between AWS accounts](#).

Enabling CloudTrail as a trusted service in AWS Organizations

Before you can create an organization trail, you must first enable all features in Organizations. For more information, see [Enabling All Features in Your Organization](#), or run the following command using a profile with sufficient permissions in the management account:

```
aws organizations enable-all-features
```

After you enable all features, you must configure Organizations to trust CloudTrail as a trusted service. .

To create the trusted service relationship between AWS Organizations and CloudTrail, open a terminal or command line and use a profile in the management account. Run the `aws organizations enable-aws-service-access` command, as demonstrated in the following example.

```
aws organizations enable-aws-service-access --service-principal
cloudtrail.amazonaws.com
```

Using create-trail

Creating an organization trail that applies to all Regions

To create an organization trail that applies to all Regions, add the `--is-organization-trail` and `--is-multi-region-trail` options.

Note

When you create an organization trail with the AWS CLI, you must use an AWS CLI profile in the management account or delegated administrator account with sufficient permissions.

The following example creates an organization trail that delivers logs from all Regions to an existing bucket named *amzn-s3-demo-bucket*:

```
aws cloudtrail create-trail --name my-trail --s3-bucket-name amzn-s3-demo-bucket --is-
organization-trail --is-multi-region-trail
```

To confirm that your trail exists in all Regions, the `IsOrganizationTrail` and `IsMultiRegionTrail` parameters in the output are both set to `true`:

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "my-trail",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
  "LogFileValidationEnabled": false,
  "IsMultiRegionTrail": true,
  "IsOrganizationTrail": true,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

Note

Run the `start-logging` command to start logging for your trail. For more information, see [Stopping and starting logging for a trail](#).

Creating an organization trail as a single-Region trail

The following command creates an organization trail that only logs events in a single AWS Region, also known as a single-Region trail. The AWS Region where events are logged is the Region specified in the configuration profile for the AWS CLI.

```
aws cloudtrail create-trail --name my-trail --s3-bucket-name amzn-s3-demo-bucket --is-organization-trail
```

For more information, see [Naming requirements for CloudTrail resources, S3 buckets, and KMS keys](#).

Sample output:

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "my-trail",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
  "LogFileValidationEnabled": false,
  "IsMultiRegionTrail": false,
  "IsOrganizationTrail": true,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

By default, the `create-trail` command creates a single-Region trail that does not enable log file validation.

Note

Run the `start-logging` command to start logging for your trail.

Running `update-trail` to update an organization trail

You can run the `update-trail` command to change the configuration settings for an organization trail, or to apply an existing trail for a single AWS account to an entire organization. Remember that you can run the `update-trail` command only from the Region in which the trail was created.

Note

If you use the AWS CLI or one of the AWS SDKs to update a trail, be sure that the trail's bucket policy is up-to-date. For more information, see [Creating a trail for an organization with the AWS CLI](#).

When you update an organization trail with the AWS CLI, you must use an AWS CLI profile in the management account or delegated administrator account with sufficient permissions. If you want to convert an organization trail to a non-organization trail, you must use the management account for the organization, because the management account is the owner of all organization resources.

CloudTrail updates organization trails in member accounts even if a resource validation fails. Examples of validation failures include:

- an incorrect Amazon S3 bucket policy
- an incorrect Amazon SNS topic policy
- inability to deliver to a CloudWatch Logs log group
- insufficient permission to encrypt using a KMS key

A member account with CloudTrail permissions can see any validation failures for an organization trail by viewing the trail's details page on the CloudTrail console, or by running the AWS CLI [get-trail-status](#) command.

Applying an existing trail to an organization

To change an existing trail so that it also applies to an organization instead of a single AWS account, add the `--is-organization-trail` option, as shown in the following example.

Note

Use the management account to change an existing non-organization trail to an organization trail.

```
aws cloudtrail update-trail --name my-trail --is-organization-trail
```

To confirm that the trail now applies to the organization, the `IsOrganizationTrail` parameter in the output has a value of `true`.

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "my-trail",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
  "LogFileValidationEnabled": false,
  "IsMultiRegionTrail": true,
  "IsOrganizationTrail": true,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

In the preceding example, the trail was configured as a multi-Region trail (`"IsMultiRegionTrail": true`). A trail that applied only to a single Region would show `"IsMultiRegionTrail": false` in the output.

Converting a single-Region organization trail to a multi-Region organization trail

To convert an existing single-Region organization trail to a multi-Region organization trail, add the `--is-multi-region-trail` option as shown in the following example.

```
aws cloudtrail update-trail --name my-trail --is-multi-region-trail
```

To confirm that the trail is now a multi-Region, check that the `IsMultiRegionTrail` parameter in the output has a value of `true`.

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "my-trail",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
  "LogFileValidationEnabled": false,
  "IsMultiRegionTrail": true,
  "IsOrganizationTrail": true,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

Troubleshooting issues with an organization trail

This section provides information on how to troubleshoot issues with an organization trail.

Topics

- [CloudTrail is not delivering events](#)
- [CloudTrail is not sending Amazon SNS notifications for a member account in an organization](#)

CloudTrail is not delivering events

If CloudTrail is not delivering CloudTrail log files to the Amazon S3 bucket

Check if there is an issue with the S3 bucket.

- From the CloudTrail console, check the trail's details page. If there's an issue with the S3 bucket, the details page includes a warning that delivery to the S3 bucket failed.
- From the AWS CLI, run the [get-trail-status](#) command. If there's a failure, the command output includes the LatestDeliveryError field, which displays any Amazon S3 error that CloudTrail encountered when attempting to deliver log files to the designated bucket. This error occurs only when there is a problem with the destination S3 bucket, and does not occur for requests that time out. To resolve the issue, fix the bucket policy so that CloudTrail can write to the bucket; or create a new bucket, and then call update-trail to specify the new bucket. For information about the organization bucket policy, see [Create or update an Amazon S3 bucket to use to store the log files for an organization trail](#).

Note

If you misconfigure your trail (for example, the S3 bucket is unreachable), CloudTrail will attempt to redeliver the log files to your S3 bucket for 30 days, and these attempted-to-deliver events will be subject to standard CloudTrail charges. To avoid charges on a misconfigured trail, you need to delete the trail.

If CloudTrail is not delivering logs to CloudWatch Logs

Check if there is an issue with the configuration of the CloudWatch Logs role policy.

- From the CloudTrail console, check the trail's details page. If there's an issue with CloudWatch Logs, the details page includes a warning that indicates CloudWatch Logs delivery failed.
- From the AWS CLI, run the [get-trail-status](#) command. If there's a failure, the command output includes the LatestCloudWatchLogsDeliveryError field, which displays any CloudWatch

Logs error that CloudTrail encountered when attempting to deliver logs to CloudWatch Logs. To resolve the issue, fix the CloudWatch Logs role policy. For information about the CloudWatch Logs role policy, see [Role policy document for CloudTrail to use CloudWatch Logs for monitoring](#).

If you're not seeing activity for a member account in an organization trail

If you're not seeing activity for a member account in an organization trail, check the following:

- **Check the home Region for the trail to see if it is an opt-in Region**

Although most AWS Regions are enabled by default for your AWS account, you must manually enable certain Regions (also referred to as *opt-in Regions*). For information about which Regions are enabled by default, see [Considerations before enabling and disabling Regions](#) in the *AWS Account Management Reference Guide*. For the list of Regions CloudTrail supports, see [CloudTrail supported Regions](#).

If the organization trail is multi-Region and the home Region is an opt-in Region, member accounts will not send activity to the organization trail unless they opt into the AWS Region where the multi-Region trail was created. For example, if you create a multi-Region trail and choose the Europe (Spain) Region as the home Region for the trail, only member accounts that enabled the Europe (Spain) Region for their account will send their account activity to the organization trail. To resolve the issue, enable the opt-in Region in each member account in your organization. For information about enabling an opt-in Region, see [Enable or disable a Region in your organization](#) in the *AWS Account Management Reference Guide*.

- **Check if the organization resource-based policy conflicts with the CloudTrail service-linked role policy**

CloudTrail uses the service-linked role named [AWSServiceRoleForCloudTrail](#) to support organization trails. This service-linked role allows CloudTrail to perform actions on organization resources, such as `organizations:DescribeOrganization`. If the organization's resource-based policy denies an action that is allowed in the service-linked role policy, CloudTrail will not be able to perform the action even though it is allowed in the service-linked role policy. To resolve the issue, fix the organization's resource-based policy so that it doesn't deny actions that are allowed in the service-linked role policy.

CloudTrail is not sending Amazon SNS notifications for a member account in an organization

When a member account with an AWS Organizations organization trail is not sending Amazon SNS notifications, there could be an issue with the configuration of the SNS topic policy. CloudTrail creates organization trails in member accounts even if a resource validation fails, for example, the organization trail's SNS topic does not include all member account IDs. If the SNS topic policy is incorrect, an authorization failure occurs.

To check whether a trail's SNS topic policy has an authorization failure:

- From the CloudTrail console, check the trail's details page. If there's an authorization failure, the details page includes a warning `SNS authorization failed` and indicates to fix the SNS topic policy.
- From the AWS CLI, run the [get-trail-status](#) command. If there's an authorization failure, the command output includes the `LastNotificationError` field with a value of `AuthorizationError`. To resolve the issue, fix the Amazon SNS topic policy. For information about the Amazon SNS topic policy, see [Amazon SNS topic policy for CloudTrail](#).

For more information about SNS topics and subscribing to them, see [Getting started with Amazon SNS](#) in the *Amazon Simple Notification Service Developer Guide*.

Understanding multi-Region trails and opt-in Regions

A trail can be applied to all AWS Regions that are [enabled](#) in your AWS account, or can be applied to a single Region. A trail that applies to all AWS Regions that are enabled in your AWS account is referred to as a *multi-Region trail*. As a best practice, we recommend creating a multi-Region trail because it captures activity in all enabled Regions. All trails created using the CloudTrail console are multi-Region trails. You can only create a single-Region trail using the AWS CLI or [CreateTrail](#) API operation.

Although most AWS Regions are enabled by default for your AWS account, you must manually enable certain Regions (also referred to as *opt-in Regions*). For information about which Regions are enabled by default, see [Considerations before enabling and disabling Regions](#) in the *AWS Account Management Reference Guide*. For the list of Regions CloudTrail supports, see [CloudTrail supported Regions](#).

Topics

- [What are the advantages of multi-Region trails?](#)
- [What happens when you create a multi-Region trail?](#)
- [What happens when you enable an opt-in Region?](#)
- [What happens when you disable an opt-in Region?](#)

What are the advantages of multi-Region trails?

A multi-Region trail has the following advantages:

- The configuration settings for the trail apply consistently across all [enabled](#) AWS Regions.
- You receive CloudTrail events from all enabled AWS Regions in a single Amazon S3 bucket and, optionally, in a CloudWatch Logs log group.
- You manage trail configurations for all enabled AWS Regions from one location.

What happens when you create a multi-Region trail?

Creating a multi-Region trail, has the following effects:

- CloudTrail delivers log files for account activity from all [enabled](#) AWS Regions to the single Amazon S3 bucket that you specify, and, optionally, to a CloudWatch Logs log group.
- If you configured an Amazon SNS topic for the trail, SNS notifications about log file deliveries in all enabled AWS Regions are sent to that single SNS topic.
- You can see the multi-Region trail in all enabled AWS Regions, but you can only modify the trail in the home Region where it was created.

What happens when you enable an opt-in Region?

After you enable an opt-in Region, CloudTrail creates an identical copy of each multi-Region trail in the opt-in Region that you enabled.

CloudTrail uses a distributed computing model called [eventual consistency](#). Because enabling a Region takes a few minutes to several hours, you may not immediately see all events in the logs for the newly enabled Region. It may take up to several hours for CloudTrail to deliver all logs for the newly enabled Region. During this time, you can view the last 90 days of management events logged in that Region by viewing the CloudTrail [Event History](#), or by running the [aws cloudtrail lookup-events --region <region>](#) command. Event history is active by default in your

AWS account, captures the last 90 days of management events logged in a Region, and does not require a trail.

For information about enabling an opt-in Region for your AWS account, see [Enable or disable a Region for standalone accounts](#) or [Enable or disable a Region in your organization](#).

What happens when you disable an opt-in Region?

Because your account may have activity in the Region you disabled, such as actions by AWS services to remove resources, CloudTrail will continue to capture activity and attempt to deliver events to the S3 bucket for any trails that are not deleted before the Region is disabled.

Copying trail events to CloudTrail Lake

You can copy existing trail events to a CloudTrail Lake event data store to create a point-in-time snapshot of events logged to the trail. Copying trail events does not interfere with the trail's ability to log events and does not modify the trail in any way.

You can copy trail events to an existing event data store configured for CloudTrail events, or you can create a new CloudTrail event data store and choose the **Copy trail events** option as part of event data store creation. For more information about copying trail events to an existing event data store, see [Copy trail events to an existing event data store using the CloudTrail console](#).

For more information about creating a new event data store, see [Create an event data store for CloudTrail events with the console](#).

Copying trail events to a CloudTrail Lake event data store, allows you to run queries on the copied events. CloudTrail Lake queries offer a deeper and more customizable view of events than simple key and value lookups in Event history, or running LookupEvents. For more information on CloudTrail Lake, see [Working with AWS CloudTrail Lake](#).

If you are copying trail events to an organization event data store, you must use the management account for the organization. You cannot copy trail events using the delegated administrator account for an organization.

CloudTrail Lake event data stores incur charges. When you create an event data store, you choose the [pricing option](#) you want to use for the event data store. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention period for the event data store. For information about CloudTrail pricing and managing Lake costs, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

When you copy trail events to a CloudTrail Lake event data store, you incur charges based on the amount of uncompressed data the event data store ingests.

When you copy trail events to CloudTrail Lake, CloudTrail unzips the logs that are stored in gzip (compressed) format and then copies the events contained in the logs to your event data store. The size of the uncompressed data could be greater than the actual S3 storage size. To get a general estimate of the size of the uncompressed data, you can multiply the size of the logs in the S3 bucket by 10.

You can reduce costs by specifying a narrower time range for the copied events. If you are planning to only use the event data store to query your copied events, you can turn off event ingestion to avoid incurring charges on future events. For more information, see [AWS CloudTrail Pricing](#) and [Managing CloudTrail Lake costs](#).

Scenarios

The following table describes some common scenarios for copying trail events and how you accomplish each scenario using the console.

Scenario	How do I accomplish this in the console?
Analyze and query historical trail events in CloudTrail Lake without ingesting new events	Create a new event data store and choose the Copy trail events option as part of event data store creation. When creating the event data store, deselect Ingest events (step 15 of the procedure) to ensure the event data store contains only the historical events for your trail and no future events.
Replace your existing trail with a CloudTrail Lake event data store	Create an event data store with the same event selectors as your trail to ensure that the event data store has the same coverage as your trail. To avoid duplicating events between the source trail and destination event data store, choose a date range for the copied events that is earlier than the creation of the event data store. After your event data store is created, you can turn off logging for the trail to avoid additional charges.

Topics

- [Considerations for copying trail events](#)
- [Required permissions for copying trail events](#)
- [Copy trail events to an existing event data store using the CloudTrail console](#)

Considerations for copying trail events

Consider the following factors when copying trail events.

- When copying trail events, CloudTrail uses the S3 [GetObject](#) API operation to retrieve the trail events in the source S3 bucket. There are some S3 archived storage classes, such as S3 Glacier Flexible Retrieval, S3 Glacier Deep Archive, S3 Outposts, and S3 Intelligent-Tiering Deep Archive tiers that are not accessible by using GetObject. To copy trail events stored in these archived storage classes, you must first restore a copy using the S3 RestoreObject operation. For information about restoring archived objects, see [Restoring Archived Objects](#) in the *Amazon S3 User Guide*.
- When you copy trail events to an event data store, CloudTrail copies all trail events regardless of the configuration of the destination event data store's event types, advanced event selectors, or AWS Region.
- Before copying trail events to an existing event data store, be sure the event data store's pricing option and retention period are configured appropriately for your use case.
 - **Pricing option:** The pricing option determines the cost for ingesting and storing events. For more information about pricing options, see [AWS CloudTrail Pricing](#) and [Event data store pricing options](#).
 - **Retention period:** The retention period determines how long event data is kept in the event data store. CloudTrail only copies trail events that have an eventTime within the event data store's retention period. To determine the appropriate retention period, take the sum of the oldest event you want to copy in days and the number of days you want to retain the events in the event data store (**retention period** = *oldest-event-in-days* + *number-days-to-retain*). For example, if the oldest event you're copying is 45 days old and you want to keep the events in the event data store for a further 45 days, you would set the retention period to 90 days.
- If you are copying trail events to an event data store for investigation and do not want to ingest any future events, you can stop ingestion on the event data store. When creating the event data

store, deselect the **Ingest events** option (step 15 of the [procedure](#)) to ensure the event data store contains only the historical events for your trail and no future events.

- Before copying trail events, disable any access control lists (ACLs) attached to the source S3 bucket, and update the S3 bucket policy for the destination event data store. For more information about updating the S3 bucket policy, see [Amazon S3 bucket policy for copying trail events](#). For more information about disabling ACLs, see [Controlling ownership of objects and disabling ACLs for your bucket](#).
- CloudTrail only copies trail events from Gzip compressed log files that are in the source S3 bucket. CloudTrail does not copy trail events from uncompressed log files, or log files that were compressed using a format other than Gzip.
- To avoid duplicating events between the source trail and destination event data store, choose a time range for the copied events that is earlier than the creation of the event data store.
- By default, CloudTrail only copies CloudTrail events contained in the S3 bucket's `CloudTrail` prefix and the prefixes inside the `CloudTrail` prefix, and does not check prefixes for other AWS services. If you want to copy CloudTrail events contained in another prefix, you must choose the prefix when you copy trail events.
- To copy trail events to an organization event data store, you must use the management account for the organization. You cannot use the delegated administrator account to copy trail events to an organization event data store.

Required permissions for copying trail events

Before copying trail events, ensure you have all the required permissions for your IAM role. You only need to update the IAM role permissions if you choose an existing IAM role to copy trail events. If you choose to create a new IAM role, CloudTrail provides all necessary permissions for the role.

If the source S3 bucket uses a KMS key for data encryption, ensure that the KMS key policy allows CloudTrail to decrypt data in the bucket. If the source S3 bucket uses multiple KMS keys, you must update each key's policy to allow CloudTrail to decrypt the data in the bucket.

Topics

- [IAM permissions for copying trail events](#)
- [Amazon S3 bucket policy for copying trail events](#)
- [KMS key policy for decrypting data in the source S3 bucket](#)

IAM permissions for copying trail events

When copying trail events, you have the option to create a new IAM role, or use an existing IAM role. When you choose a new IAM role, CloudTrail creates an IAM role with the required permissions and no further action is required on your part.

If you choose an existing role, ensure the IAM role's policies allow CloudTrail to copy trail events from the source S3 bucket. This section provides examples of the required IAM role permission and trust policies.

The following example provides the permissions policy, which allows CloudTrail to copy trail events from the source S3 bucket. Replace *amzn-s3-demo-bucket*, *myAccountID*, *region*, *prefix*, and *eventDataStoreId* with the appropriate values for your configuration. The *myAccountID* is the AWS account ID used for CloudTrail Lake, which may not be the same as the AWS account ID for the S3 bucket.

Replace *key-region*, *keyAccountID*, and *keyID* with the values for the KMS key used to encrypt the source S3 bucket. You can omit the `AWSCloudTrailImportKeyAccess` statement if the source S3 bucket does not use a KMS key for encryption.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "AWSCloudTrailImportBucketAccess",
      "Effect": "Allow",
      "Action": ["s3:ListBucket", "s3:GetBucketAcl"],
      "Resource": [
        "arn:aws:s3:::amzn-s3-demo-bucket"
      ],
      "Condition": {
        "StringEquals": {
          "aws:SourceAccount": "myAccountID",
          "aws:SourceArn":
            "arn:aws:cloudtrail:region:myAccountID:eventdatastore/eventDataStoreId"
        }
      }
    },
    {
      "Sid": "AWSCloudTrailImportObjectAccess",
      "Effect": "Allow",
      "Action": ["s3:GetObject"],
```

```

    "Resource": [
      "arn:aws:s3:::amzn-s3-demo-bucket/prefix",
      "arn:aws:s3:::amzn-s3-demo-bucket/prefix/*"
    ],
    "Condition": {
      "StringEquals": {
        "aws:SourceAccount": "myAccountID",
        "aws:SourceArn":
"arn:aws:cloudtrail:region:myAccountID:eventdatastore/eventDataStoreId"
      }
    }
  },
  {
    "Sid": "AWSCloudTrailImportKeyAccess",
    "Effect": "Allow",
    "Action": ["kms:GenerateDataKey", "kms:Decrypt"],
    "Resource": [
      "arn:aws:kms:key-region:keyAccountID:key/keyID"
    ]
  }
]
}

```

The following example provides the IAM trust policy, which allows CloudTrail to assume an IAM role to copy trail events from the source S3 bucket. Replace *myAccountID*, *region*, and *eventDataStoreArn* with the appropriate values for your configuration. The *myAccountID* is the AWS account ID used for CloudTrail Lake, which may not be the same as the AWS account ID for the S3 bucket.

```

{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Principal": {
        "Service": "cloudtrail.amazonaws.com"
      },
      "Action": "sts:AssumeRole",
      "Condition": {
        "StringEquals": {
          "aws:SourceAccount": "myAccountID",
          "aws:SourceArn":
"arn:aws:cloudtrail:region:myAccountID:eventdatastore/eventDataStoreId"
        }
      }
    }
  ]
}

```

```

    }
  }
}
]
}

```

Amazon S3 bucket policy for copying trail events

By default, Amazon S3 buckets and objects are private. Only the resource owner (the AWS account that created the bucket) can access the bucket and objects it contains. The resource owner can grant access permissions to other resources and users by writing an access policy.

Before you copy trail events, you must update the S3 bucket policy to allow CloudTrail to copy trail events from the source S3 bucket.

You can add the following statement to the S3 bucket policy to grant these permissions. Replace *roleArn* and *amzn-s3-demo-bucket* with the appropriate values for your configuration.

```

{
  "Sid": "AWSCloudTrailImportBucketAccess",
  "Effect": "Allow",
  "Action": [
    "s3:ListBucket",
    "s3:GetBucketAcl",
    "s3:GetObject"
  ],
  "Principal": {
    "AWS": "roleArn"
  },
  "Resource": [
    "arn:aws:s3:::amzn-s3-demo-bucket",
    "arn:aws:s3:::amzn-s3-demo-bucket/*"
  ]
},

```

KMS key policy for decrypting data in the source S3 bucket

If the source S3 bucket uses a KMS key for data encryption, ensure the KMS key policy provides CloudTrail with the `kms:Decrypt` and `kms:GenerateDataKey` permissions required to copy trail

events from an S3 bucket with SSE-KMS encryption enabled. If your source S3 bucket uses multiple KMS keys, you must update each key's policy. Updating the KMS key policy allows CloudTrail to decrypt data in the source S3 bucket, run validation checks to ensure that events conform to CloudTrail standards, and copy events into the CloudTrail Lake event data store.

The following example provides the KMS key policy, which allows CloudTrail to decrypt the data in the source S3 bucket. Replace *roleArn*, *amzn-s3-demo-bucket*, *myAccountID*, *region*, and *eventDataStoreId* with the appropriate values for your configuration. The *myAccountID* is the AWS account ID used for CloudTrail Lake, which may not be the same as the AWS account ID for the S3 bucket.

```
{
  "Sid": "AWSCloudTrailImportDecrypt",
  "Effect": "Allow",
  "Action": [
    "kms:Decrypt",
    "kms:GenerateDataKey"
  ],
  "Principal": {
    "AWS": "roleArn"
  },
  "Resource": "*",
  "Condition": {
    "StringLike": {
      "kms:EncryptionContext:aws:s3:arn": "arn:aws:s3:::amzn-s3-demo-bucket/*"
    },
    "StringEquals": {
      "aws:SourceAccount": "myAccountID",
      "aws:SourceArn":
        "arn:aws:cloudtrail:region:myAccountID:eventdatastore/eventDataStoreId"
    }
  }
}
```

Copy trail events to an existing event data store using the CloudTrail console

Use the following procedure to copy trail events to an existing event data store. For information about how to create a new event data store, see [Create an event data store for CloudTrail events with the console](#).

 Note

Before copying trail events to an existing event data store, be sure the event data store's pricing option and retention period are configured appropriately for your use case.

- **Pricing option:** The pricing option determines the cost for ingesting and storing events. For more information about pricing options, see [AWS CloudTrail Pricing](#) and [Event data store pricing options](#).
- **Retention period:** The retention period determines how long event data is kept in the event data store. CloudTrail only copies trail events that have an eventTime within the event data store's retention period. To determine the appropriate retention period, take the sum of the oldest event you want to copy in days and the number of days you want to retain the events in the event data store (**retention period** = *oldest-event-in-days* + *number-days-to-retain*). For example, if the oldest event you're copying is 45 days old and you want to keep the events in the event data store for a further 45 days, you would set the retention period to 90 days.

To copy trail events to an event data store

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. Choose **Trails** in the left navigation pane of the CloudTrail console.
3. On the **Trails** page, choose the trail, and then choose **Copy events to Lake**. If the source S3 bucket for the trail uses a KMS key for data encryption, ensure that the KMS key policy allows CloudTrail to decrypt data in the bucket. If the source S3 bucket uses multiple KMS keys, you must update each key's policy to allow CloudTrail to decrypt data in the bucket. For more information about updating the KMS key policy, see [KMS key policy for decrypting data in the source S3 bucket](#).
4. (Optional) By default, CloudTrail only copies CloudTrail events contained in the S3 bucket's CloudTrail prefix and the prefixes inside the CloudTrail prefix, and does not check prefixes for other AWS services. If you want to copy CloudTrail events contained in another prefix, choose **Enter S3 URI**, and then choose **Browse S3** to browse to the prefix.

The S3 bucket policy must grant CloudTrail access to copy trail events. For more information about updating the S3 bucket policy, see [Amazon S3 bucket policy for copying trail events](#).

5. For **Specify a time range of events**, choose the time range for copying the events. CloudTrail checks the prefix and log file name to verify the name contains a date between the chosen start and end date before attempting to copy trail events. You can choose a **Relative range** or an **Absolute range**. To avoid duplicating events between the source trail and destination event data store, choose a time range that is earlier than the creation of the event data store.

 Note

CloudTrail only copies trail events that have an eventTime within the event data store's retention period. For example, if an event data store's retention period is 90 days, then CloudTrail will not copy any trail events with an eventTime older than 90 days.

- If you choose **Relative range**, you can choose to copy events logged in the last 6 months, 1 year, 2 years, 7 years, or a custom range. CloudTrail copies the events logged within the chosen time period.
 - If you choose **Absolute range**, you can choose a specific start and end date. CloudTrail copies the events that occurred between the chosen start and end dates.
6. For **Delivery location**, choose the destination event data store from the drop-down list.
 7. For **Permissions**, choose from the following IAM role options. If you choose an existing IAM role, verify that the IAM role policy provides the necessary permissions. For more information about updating the IAM role permissions, see [IAM permissions for copying trail events](#).
 - Choose **Create a new role (recommended)** to create a new IAM role. For **Enter IAM role name**, enter a name for the role. CloudTrail automatically creates the necessary permissions for this new role.
 - Choose **Use a custom IAM role ARN** to use a custom IAM role that is not listed. For **Enter IAM role ARN**, enter the IAM ARN.
 - Choose an existing IAM role from the drop-down list.
 8. Choose **Copy events**.
 9. You are prompted to confirm the copy. When you are ready to confirm, choose **Copy trail events to Lake**, and then choose **Copy events**.
 10. On the **Copy details** page, you can see the copy status and review any failures. When a trail event copy completes, its **Copy status** is set to either **Completed** if there were no errors, or **Failed** if errors occurred.

Note

Details shown on the event copy details page are not in real-time. The actual values for details such as **Prefixes copied** may be higher than what is shown on the page. CloudTrail updates the details incrementally over the course of the event copy.

11. If the **Copy status** is **Failed**, fix any errors shown in **Copy failures**, and then choose **Retry copy**. When you retry a copy, CloudTrail resumes the copy at the location where the failure occurred.

For more information about viewing the details of a trail event copy, see [View event copy details with the CloudTrail console](#).

Getting and viewing your CloudTrail log files

After you create a trail and configure it to capture the log files you want, you need to be able to find the log files and interpret the information they contain.

CloudTrail delivers your log files to an Amazon S3 bucket that you specify when you create the trail. CloudTrail typically delivers logs within an average of about 5 minutes of an API call. This time is not guaranteed. Review the [AWS CloudTrail Service Level Agreement](#) for more information. Insights events are typically delivered to your bucket within 30 minutes of unusual activity. After you enable Insights events for the first time, allow up to 36 hours to see the first Insights events, if unusual activity is detected.

Note

If you misconfigure your trail (for example, the S3 bucket is unreachable), CloudTrail will attempt to redeliver the log files to your S3 bucket for 30 days, and these attempted-to-deliver events will be subject to standard CloudTrail charges. To avoid charges on a misconfigured trail, you need to delete the trail.

Topics

- [Finding your CloudTrail log files](#)
- [Downloading your CloudTrail log files](#)

Finding your CloudTrail log files

CloudTrail publishes log files to your S3 bucket in a gzip archive. In the S3 bucket, the log file has a formatted name that includes the following elements:

- The bucket name that you specified when you created trail (found on the Trails page of the CloudTrail console)
- The (optional) prefix you specified when you created your trail
- The string "AWSLogs"
- The account number
- The string "CloudTrail"
- A Region identifier such as us-west-1
- The year the log file was published in YYYY format
- The month the log file was published in MM format
- The day the log file was published in DD format
- An alphanumeric string that disambiguates the file from others that cover the same time period

The following example shows a complete log file object name:

```
amzn-s3-demo-bucket/prefix_name/AWSLogs/Account ID/  
CloudTrail/region/YYYY/MM/DD/file_name.json.gz
```

Note

For organization trails, the log file object name in the S3 bucket includes the organization unit ID in the path, as follows:

```
amzn-s3-demo-bucket/prefix_name/AWSLogs/O-ID/Account ID/  
CloudTrail/Region/YYYY/MM/DD/file_name.json.gz
```

To retrieve a log file, you can use the Amazon S3 console, the Amazon S3 command line interface (CLI), or the API.

To find your log files with the Amazon S3 console

1. Open the Amazon S3 console.
2. Choose the bucket you specified.
3. Navigate through the object hierarchy until you find the log file you want.

All log files have a .gz extension.

You will navigate through an object hierarchy that is similar to the following example, but with a different bucket name, account ID, Region, and date.

```
All Buckets
  amzn-s3-demo-bucket
    AWSLogs
      123456789012
        CloudTrail
          us-west-1
            2014
              06
                20
```

A log file for the preceding object hierarchy will look like the following:

```
123456789012_CloudTrail_us-west-1_20140620T1255ZHdkvFTX0A3Vnhbc.json.gz
```

Note

Although uncommon, you may receive log files that contain one or more duplicate events. In most cases, duplicate events will have the same eventID. For more information about the eventID field, see [CloudTrail record contents for management, data, and network activity events](#).

Downloading your CloudTrail log files

Log files are in JSON format. If you have a JSON viewer add-on installed, you can view the files directly in your browser. Double-click the log file name in the bucket to open a new browser window or tab. The JSON displays in a readable format.

CloudTrail log files are Amazon S3 objects. You can use the Amazon S3 console, the AWS Command Line Interface (CLI), or the Amazon S3 API to retrieve log files.

For more information, see [Amazon S3 objects overview](#) in the *Amazon Simple Storage Service User Guide*.

The following procedure describes how to download a log file with the AWS Management Console.

To download and read a log file

1. Open the Amazon S3 console at <https://console.aws.amazon.com/s3/>.
2. Choose the bucket and choose the log file that you want to download.
3. Choose **Download** or **Download as** and follow the prompts to save the file. This saves the file in compressed format.

Note

Some browsers, such as Chrome, automatically extract the log file for you. If your browser does this for you, skip to step 5.

4. Use a product such as [7-Zip](#) to extract the log file.
5. Open the log file in a text editor such as Notepad++.

For more information about the event fields that can appear in a log file entry, see [CloudTrail record contents for management, data, and network activity events](#).

AWS partners with third-party specialists in logging and analysis to provide solutions that use CloudTrail output. For more information, see [AWS CloudTrail partners](#).

Note

You can also use the **Event history** feature to look up events for create, update, and delete API activity during the last 90 days.

For more information, see [Working with CloudTrail event history](#).

Configuring Amazon SNS notifications for CloudTrail

You can be notified when CloudTrail publishes new log files to your Amazon S3 bucket. You manage notifications using Amazon Simple Notification Service (Amazon SNS).

Notifications are optional. If you want notifications, you configure CloudTrail to send update information to an Amazon SNS topic whenever a new log file has been sent. To receive these notifications, you can use Amazon SNS to subscribe to the topic. As a subscriber you can get updates sent to a Amazon Simple Queue Service (Amazon SQS) queue, which enables you to handle these notifications programmatically.

Topics

- [Configuring CloudTrail to send notifications](#)

Configuring CloudTrail to send notifications

On the CloudTrail console, you can configure a trail to use an Amazon SNS topic by enabling the **SNS notification delivery** option when you [create](#) or [update](#) a trail. If you choose to use a new topic, CloudTrail creates the Amazon SNS topic for you and attaches an appropriate policy, so that CloudTrail has permission to publish to that topic.

With the AWS CLI, you can [create](#) or [update](#) a trail to use an Amazon SNS topic by specifying a value for the `--sns-topic-name` parameter. You can specify the name or the ARN for the Amazon SNS topic.

When you create an SNS topic name, the name must meet the following requirements:

- Between 1 and 256 characters long
- Contain uppercase and lowercase ASCII letters, numbers, underscores, or hyphens

When you configure notifications for a multi-Region trail, notifications from all Regions are sent to the Amazon SNS topic that you specify. If you have one or more Region-specific trails, you must create a separate topic for each Region and subscribe to each individually.

To receive notifications, subscribe to the Amazon SNS topic or topics that CloudTrail uses. You do this with the Amazon SNS console or Amazon SNS CLI commands. For more information, see [Subscribing to an Amazon SNS topic](#) in the *Amazon Simple Notification Service Developer Guide*.

Note

CloudTrail sends a notification when log files are written to the Amazon S3 bucket. An active account can generate a large number of notifications. If you subscribe with email or SMS, you can receive a large volume of messages. We recommend that you subscribe using Amazon Simple Queue Service (Amazon SQS), which lets you handle notifications programmatically. For more information, see [Subscribing an Amazon SQS queue to an Amazon SNS topic \(console\)](#) in the *Amazon Simple Queue Service Developer Guide*.

The Amazon SNS notification consists of a JSON object that includes a Message field. The Message field lists the full path to the log file, as shown in the following example:

```
{
  "s3Bucket": "amzn-s3-demo-bucket", "s3objectKey": ["AWSLogs/123456789012/
CloudTrail/us-east-2/2013/12/13/123456789012_CloudTrail_us-
west-2_20131213T1920Z_LnPgDQnpkSKEsppV.json.gz"]
}
```

If multiple log files are delivered to your Amazon S3 bucket, a notification may contain multiple logs, as shown in the following example:

```
{
  "s3Bucket": "amzn-s3-demo-bucket",
  "s3objectKey": [
    "AWSLogs/123456789012/CloudTrail/us-
east-2/2016/08/11/123456789012_CloudTrail_us-
east-2_20160811T2215Z_kpaMYavMQA9Ahp7L.json.gz",
    "AWSLogs/123456789012/CloudTrail/us-
east-2/2016/08/11/123456789012_CloudTrail_us-
east-2_20160811T2210Z_zqDkyQv3TK8ZdLr0.json.gz",
    "AWSLogs/123456789012/CloudTrail/us-
east-2/2016/08/11/123456789012_CloudTrail_us-
east-2_20160811T2205Z_jaMVRa6JfdLCJYHP.json.gz"
  ]
}
```

If you choose to receive notifications by email, the body of the email consists of the content of the Message field. For information about the JSON structure, see [Fanout to Amazon SQS queues](#) in the *Amazon Simple Notification Service Developer Guide*. Only the Message field shows CloudTrail information. The other fields contain information from the Amazon SNS service.

If you create a trail with the CloudTrail API, you can specify an existing Amazon SNS topic that you want CloudTrail to send notifications to with the [CreateTrail](#) or [UpdateTrail](#) operations. You must make sure that the topic exists and that it has permissions that allow CloudTrail to send notifications to it. See [Amazon SNS topic policy for CloudTrail](#).

Additional resources

For more information about Amazon SNS topics and about subscribing to them, see the [Amazon Simple Notification Service Developer Guide](#).

Using AWS CloudTrail with interface VPC endpoints

If you use Amazon Virtual Private Cloud (Amazon VPC) to host your AWS resources, you can establish a private connection between your VPC and AWS CloudTrail. You can use this connection to enable CloudTrail to communicate with your resources on your VPC without going through the public internet.

Amazon VPC is an AWS service that you can use to launch AWS resources in a virtual network that you define. With a VPC, you have control over your network settings, such the IP address range, subnets, route tables, and network gateways. With VPC endpoints, the routing between the VPC and AWS services is handled by the AWS network, and you can use IAM policies to control access to service resources.

To connect your VPC to CloudTrail, you define an *interface VPC endpoint* for CloudTrail. An interface endpoint is an elastic network interface with a private IP address that serves as an entry point for traffic destined to a supported AWS service. The endpoint provides reliable, scalable connectivity to CloudTrail without requiring an internet gateway, network address translation (NAT) instance, or VPN connection. For more information, see [What is Amazon VPC](#) in the *Amazon VPC User Guide*.

Interface VPC endpoints are powered by AWS PrivateLink, an AWS technology that enables private communication between AWS services using an elastic network interface with private IP addresses. For more information, see [AWS PrivateLink](#).

The following sections are for users of Amazon VPC. For more information, see [Get started with Amazon VPC](#) in the *Amazon VPC User Guide*.

Topics

- [Regions](#)
- [Create a VPC endpoint for CloudTrail](#)
- [Create a VPC endpoint policy for CloudTrail](#)
- [Shared subnets](#)

Regions

AWS CloudTrail supports VPC endpoints and VPC endpoint policies in all AWS Regions in which CloudTrail is supported.

Create a VPC endpoint for CloudTrail

To start using CloudTrail with your VPC, create an interface VPC endpoint for CloudTrail. For more information, see [Access an AWS service using an interface VPC endpoint](#) in the *Amazon VPC User Guide*.

You don't need to change the settings for CloudTrail. CloudTrail calls other AWS services using either public endpoints or private interface VPC endpoints, whichever are in use.

Create a VPC endpoint policy for CloudTrail

A VPC endpoint policy is an IAM resource that you can attach to an interface VPC endpoint. The default endpoint policy gives you full access to CloudTrail APIs through the interface VPC endpoint. To control the access granted to CloudTrail from your VPC, attach a custom endpoint policy to the interface VPC endpoint.

An endpoint policy specifies the following information:

- The principals that can perform actions (AWS accounts, IAM users, and IAM roles).
- The actions that can be performed.
- The resources on which actions can be performed.

For more information about VPC endpoint policies, including how to update a policy, see [Controlling access to services with VPC endpoints](#) in the *Amazon VPC User Guide*.

Following are examples of custom VPC endpoint policies for CloudTrail.

Example policies:

- [Example: Allow all CloudTrail actions](#)
- [Example: Allow specific CloudTrail actions](#)
- [Example: Deny all CloudTrail actions](#)
- [Example: Deny specific CloudTrail actions](#)
- [Example: Allow all CloudTrail actions from a specific VPC](#)
- [Example: Allow all CloudTrail actions from a specific VPC endpoint](#)

Example: Allow all CloudTrail actions

The following example VPC endpoint policy grants access to all CloudTrail actions for all principals on all resources.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Action": "cloudtrail:*",
      "Effect": "Allow",
      "Resource": "*",
      "Principal": "*"
    }
  ]
}
```

Example: Allow specific CloudTrail actions

The following example VPC endpoint policy grants access to perform the `cloudtrail:ListTrails` and `cloudtrail:ListEventDataStores` actions for all principals on all resources.

JSON

```
{
```

```
"Version": "2012-10-17",
"Statement": [
  {
    "Action": ["cloudtrail:ListTrails",
"cloudtrail:ListEventDataStores"],
    "Effect": "Allow",
    "Principal": "*",
    "Resource": "*"
  }
]
```

Example: Deny all CloudTrail actions

The following example VPC endpoint policy denies access to all CloudTrail actions for all principals on all resources.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Action": "cloudtrail:*",
      "Effect": "Deny",
      "Principal": "*",
      "Resource": "*"
    }
  ]
}
```

Example: Deny specific CloudTrail actions

The following example VPC endpoint policy denies the `cloudtrail:CreateTrail` and `cloudtrail:CreateEventDataStore` actions for all principals on all resources.

JSON

```
{
```



```
"Version": "2012-10-17",
"Statement": [
  {
    "Action": ["cloudtrail:CreateTrail",
"cloudtrail:CreateEventDataStore"],
    "Effect": "Deny",
    "Principal": "*",
    "Resource": "*"
  }
]
```

Example: Allow all CloudTrail actions from a specific VPC

The following example VPC endpoint policy grants access to perform all CloudTrail actions for all principals on all resources but only if the requester uses the specified VPC to make the request.

Replace *vpc-id* with your VPC ID.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "cloudtrail:*",
      "Resource": "*",
      "Principal": "*",
      "Condition": {
        "StringEquals": {
          "aws:SourceVpc": "vpc-1234567890abcdef0"
        }
      }
    }
  ]
}
```

Example: Allow all CloudTrail actions from a specific VPC endpoint

The following example VPC endpoint policy grants access to perform all CloudTrail actions for all principals on all resources but only if the requester uses the specified VPC endpoint to make the request. Replace *vpce-endpoint-id* with your VPC endpoint ID.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "cloudtrail:*",
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "aws:SourceVpce": "vpce-1a2b3c4d"
        }
      }
    }
  ]
}
```

Shared subnets

A CloudTrail VPC endpoint, like any other VPC endpoint, can only be created by an owner account in the shared subnet. However, a participant account can use CloudTrail VPC endpoints in subnets that are shared with the participant account. For more information about Amazon VPC sharing, see [Share your VPC with other accounts](#) in the *Amazon VPC User Guide*.

Naming requirements for CloudTrail resources, S3 buckets, and KMS keys

This section provides information about the naming requirements for CloudTrail resources, Amazon S3 buckets, and KMS keys.

Topics

- [CloudTrail resource naming requirements](#)
- [Amazon S3 bucket naming requirements](#)
- [AWS KMS alias naming requirements](#)

CloudTrail resource naming requirements

CloudTrail resource names must meet the following requirements:

- Contain only ASCII letters (a-z, A-Z), numbers (0-9), periods (.), underscores (_), or dashes (-).
- Start with a letter or number, and end with a letter or number.
- Be between 3 and 128 characters.
- Have no adjacent periods, underscores or dashes. Names like my-_namespace and my-\-namespace are invalid.
- Not be in IP address format (for example, 192.168.5.4).

Amazon S3 bucket naming requirements

The Amazon S3 bucket that you use to store CloudTrail log files must have a name that conforms with naming requirements for non-US Standard regions. Amazon S3 defines a bucket name as a series of one or more labels, separated by periods. For a complete list of naming rules, see [Bucket naming rules](#) in the *Amazon Simple Storage Service User Guide*.

The following are some of the rules:

- The bucket name can be between 3 and 63 characters long, and can contain only lower-case characters, numbers, periods, and dashes.
- Each label in the bucket name must start with a lowercase letter or number.
- The bucket name cannot contain underscores, end with a dash, have consecutive periods, or use dashes adjacent to periods.
- The bucket name cannot be formatted as an IP address (198.51.100.24).

Warning

Because S3 allows your bucket to be used as a URL that can be accessed publicly, the bucket name that you choose must be globally unique. If some other account has already

created a bucket with the name that you chose, you must use another name. For more information, see [Bucket restrictions and limitations](#) in the *Amazon Simple Storage Service User Guide*.

AWS KMS alias naming requirements

When you create an AWS KMS key, you can choose an alias to identify it. For example, you might choose the alias "KMS-CloudTrail-us-west-2" to encrypt the logs for a specific trail.

The alias must meet the following requirements:

- Between 1 and 256 characters, inclusive
- Contain alphanumeric characters (A-Z, a-z, 0-9), hyphens (-), forward slashes (/), and underscores (_)
- Cannot begin with **aws**

For more information, see [Creating Keys](#) in the *AWS Key Management Service Developer Guide*.

AWS account closure and trails

AWS CloudTrail continuously monitors and records events for account activity generated by any user, role, or AWS service for an AWS account. Users can create a CloudTrail trail to receive a copy of these events in a S3 bucket that they own.

CloudTrail is a foundational security service, therefore, trails created by users continue to exist and deliver events even after an AWS account is closed, unless a user explicitly deletes the trails in their AWS account prior to closing it. This ensures that if a user reopens a closed account that user has an unbroken record of account activity. It also provides users with visibility into any final account activity, including the deletion and termination of remaining account resources and services.

Before you close your AWS account, consider the following:

- Trails continue to exist even after the post-closure period has passed. The post-closure period refers to the 90 days between when you close your account and when AWS permanently closes your AWS account.

- This behavior also applies to the organization trails that are created by the management account or the delegated administrator, and to multi-Region organization trails that are created in the organization's member accounts.
- For trails that deliver events to an S3 bucket in the same account, trails continue to exist even after the account is closed. However, since the S3 bucket is deleted when the account is closed, trails do not continue to deliver events.
- For trails that deliver events to an S3 bucket in a different account, trails continue to exist even after the account is closed. Trails also continue to deliver events to the S3 bucket if events can be delivered. For example, organization trails continue to deliver events to the S3 bucket if you close a member account in an organization, but you do not close the management account.
- For trails encrypted with AWS KMS keys, trails continue to exist after the account is closed in addition to the KMS keys.

Users have the option to delete trails prior to closing their AWS account, or to contact [AWS Support](#) to request trail deletion after their AWS account has been closed.

For information about closing an AWS account, see [Close an AWS account](#) in the *AWS Account Management Reference Guide*.

Note

If CloudTrail log file validation is enabled, users will continue to receive hourly digest files which indicate if any CloudTrail logs were created or not.

CloudTrail Lake event data stores, CloudTrail Lake channels for integrations, CloudTrail service-linked channels, and resources created for trails (for example, Amazon CloudWatch Logs log groups and Amazon S3 buckets existing in the closed account), follow standard AWS behavior for account closure and are permanently deleted after the post-closure period (typically 90 days).

Configure CloudTrail settings

You can use the **Settings** page on the CloudTrail console to configure and review CloudTrail settings, such as managing delegated administrators for an AWS Organizations organization and viewing any service-linked channels created for your account.

To access the Settings page

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. Choose **Settings** in the left navigation pane of the CloudTrail console.
3. Review and update your settings as needed.

The following settings are available:

- [Organization delegated administrators](#) – If you have an AWS Organizations organization, you can view CloudTrail delegated administrators, add delegated administrators (up to three maximum), and remove delegated administrators. Only the organization's management account can add or remove delegated administrators.

The organization's management account can assign any account within the organization to act as a CloudTrail delegated administrator to manage the organization's trails and event data stores on behalf of the organization.

- [Viewing service-linked channels](#) – You can view any service-linked channels created for your account.

AWS services can create a service-linked channel to receive CloudTrail events on your behalf. The AWS service creating the service-linked channel configures advanced event selectors for the channel and specifies whether the channel applies to all AWS Regions, or a single AWS Region.

Organization delegated administrator

When you use CloudTrail with an AWS Organizations organization, you can assign any account within the organization to act as a CloudTrail delegated administrator to manage the organization's trails and event data stores on behalf of the organization. A delegated administrator is a member

account in an organization that can perform the same administrative tasks (except as [noted](#)) in CloudTrail as the management account.

If you choose a delegated administrator, this member account has administrative permissions on all organization trails and event data stores in the organization. Adding a delegated administrator does not alter the management or operation of the organization's trails or event data stores.

The first time you add a delegated administrator in the CloudTrail console, or by using the AWS CLI or CloudTrail API, CloudTrail checks whether the organization's management account has a service-linked role. If the management account does not have a service-linked role, CloudTrail creates the service-linked role for the management account. For more information about service-linked roles, see [Using service-linked roles for CloudTrail](#).

Note

When you add a delegated administrator using the AWS Organizations CLI or API operation, CloudTrail service-linked roles won't be created automatically if they don't exist. The service-linked roles are only created when you make a call from the management account directly to the CloudTrail service. For example, when you add a delegated administrator or create an organization trail or event data store using the CloudTrail console, AWS CLI or CloudTrail API, the `AWSServiceRoleForCloudTrail` service-linked role is created.

When you add a delegated administrator using the AWS CloudTrail; CLI or API operation, CloudTrail will create both the `AWSServiceRoleForCloudTrail` and the `AWSServiceRoleForCloudTrailEventContext` service-linked roles. For more information, see [Using service-linked roles for CloudTrail](#).

Take note of the following factors that define how the delegated administrator operates in CloudTrail.

The management account remains the owner of any CloudTrail organization resources the delegated administrator creates.

The organization's management account remains the owner of any CloudTrail organization resources the delegated administrator creates, such as trails and event data stores. This provides continuity for the organization in the event the delegated administrator changes.

Removing a delegated administrator account does not delete any CloudTrail organization resources they created.

Organization trails and event data stores created by the delegated administrator are not deleted when you remove the delegated administrator, because the management account always serves as the owner of the CloudTrail organization resources regardless of whether they are created by the delegated administrator or the management account.

An organization can have a maximum of three CloudTrail delegated administrators.

You can have a maximum of three CloudTrail delegated administrators per organization. For more information about removing a delegated administrator, see [Remove a CloudTrail delegated administrator](#).

The following table shows the capabilities of the management account, delegated administrator accounts, and accounts that are members within the AWS Organizations organization.

Capabilities	Management account	Delegated administrator account	Member accounts
Add or remove delegated administrator accounts.	Yes	No	No
Create an organization trail.	Yes	Yes ¹	No
View a list of organization trails.	Yes	Yes	Yes
Update an organization trail.	Yes	Yes ^{1, 2}	No
Delete an organization trail.	Yes	Yes	No
Create an organization event data store for CloudTrail events or AWS Config configuration items.	Yes	Yes	No

Capabilities	Management account	Delegated administrator account	Member accounts
Enable Insights on an organization event data store.	Yes	No	No
Update an organization event data store.	Yes	Yes ²	No
Start and stop event ingestion on an organization event data store.	Yes	Yes	No
Enable Lake query federation on an organization event data store ³ .	Yes	Yes	No
Disable Lake query federation on an organization event data store.	Yes	Yes	No
Delete an organization event data store.	Yes	Yes	No
Copy trail events to an organization event data store.	Yes	No	No
Run queries on organization event data stores.	Yes	Yes	No
View a managed dashboard for an organization event data store.	Yes	No	No
Enable the Highlights dashboard for organization event data stores.	Yes	No	No
Create a widget for a custom dashboard that queries an organization event data store.	Yes	No	No

¹The delegated administrator can only configure a CloudWatch Logs log group using the AWS CLI or CloudTrail `CreateTrail` or `UpdateTrail` API operations. Both the CloudWatch Logs log group and log role must exist in the calling account.

²Only the management account can convert an organization trail or event data store to an account-level trail or event data store, or convert an account-level trail or event data store to an organization trail or event data store. These actions are not allowed for the delegated administrator because organization trails and event data stores only exist in the management account. When an organization trail or event data store is converted to an account-level trail or event data store, only the management account has access to the trail or event data store.

³Only a single delegated administrator account or the management account can enable federation on an organization event data store. Other delegated administrator accounts can query and share information using the [Lake Formation data sharing feature](#). Any delegated administrator account as well as the organization's management account can disable federation.

Topics

- [Required permissions to assign a delegated administrator](#)
- [Add a CloudTrail delegated administrator](#)
- [Remove a CloudTrail delegated administrator](#)

Required permissions to assign a delegated administrator

When assigning a CloudTrail delegated administrator, you must have the permissions to add and remove the delegated administrator in CloudTrail, as well as certain AWS Organizations API actions and IAM permissions listed in the following policy statement.

You can add the following statement to the end of an IAM policy to grant these permissions:

```
{
  "Sid": "Permissions",
  "Effect": "Allow",
  "Action": [
    "cloudtrail:RegisterOrganizationDelegatedAdmin",
    "cloudtrail:DeregisterOrganizationDelegatedAdmin",
    "organizations:RegisterDelegatedAdministrator",
    "organizations:DeregisterDelegatedAdministrator",
    "organizations:ListAWSServiceAccessForOrganization",
```

```
        "iam:CreateServiceLinkedRole",
        "iam:GetRole"
    ],
    "Resource": "*"
}
```

Considerations when using condition keys with policy statements for delegated administrator permissions

You might consider using IAM global condition keys when adding policy statements to add and remove the delegated administrator in CloudTrail for additional security. When doing so, remember to include both service principal names (SPNs) to the condition. For example:

```
{
  "Condition": {
    "StringLike": {
      "iam:AWSServiceName": [
        "context.cloudtrail.amazonaws.com",
        "cloudtrail.amazonaws.com"
      ]
    }
  },
  "Action": "iam:CreateServiceLinkedRole",
  "Resource": "*",
  "Effect": "Allow"
}
```

For more information, see [Identity and Access Management for AWS CloudTrail](#).

Add a CloudTrail delegated administrator

You can add a delegated administrator to manage an organization's CloudTrail resources, such as trails and event data stores.

You can add a CloudTrail delegated administrator for your AWS organization using the CloudTrail console or the AWS CLI.

Before you add a delegated administrator, be sure they have an account in your organization and you are signed in with the management account for your organization. For information about

how to create a new AWS account for your organization, see [Creating an AWS account in your organization](#). For information about how to invite an existing AWS account to your organization, see [Inviting an AWS account to join your organization](#).

CloudTrail console

The following procedure shows you how to add a CloudTrail delegated administrator using the CloudTrail console.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. Choose **Settings** in the left navigation pane of the CloudTrail console.
3. In the **Organization delegated administrators** section, choose **Register administrator**.
4. Enter the twelve-digit AWS account ID of the account that you want to assign as the CloudTrail delegated administrator for the organization's trails and event data stores.
5. Choose **Register administrator**.

AWS CLI

The following example adds a CloudTrail delegated administrator.

```
aws cloudtrail register-organization-delegated-admin  
--member-account-id="memberAccountId"
```

This command produces no output if it's successful.

Remove a CloudTrail delegated administrator

You can remove a CloudTrail delegated administrator using the CloudTrail console or the AWS CLI.

CloudTrail console

The following procedure shows you how to remove a CloudTrail delegated administrator using the CloudTrail console.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.

2. Choose **Settings** in the left navigation pane of the CloudTrail console.
3. In the **Organization delegated administrators** section, choose the delegated administrator that you want to remove.
4. Choose **Remove administrator**.
5. Confirm you want to remove the delegated administrator and then choose **Remove administrator**.

AWS CLI

The following command removes a CloudTrail delegated administrator.

```
aws cloudtrail deregister-organization-delegated-admin  
--delegated-admin-account-id="delegatedAdminAccountId"
```

This command produces no output if it's successful.

Viewing service-linked channels

AWS services can create a service-linked channel to receive CloudTrail events on your behalf. The AWS service creating the service-linked channel configures advanced event selectors for the channel and specifies whether the channel applies to all AWS Regions, or a single AWS Region.

Topics

- [Viewing service-linked channels by using the console](#)
- [Viewing service-linked channels by using the AWS CLI](#)

Viewing service-linked channels by using the console

Using the CloudTrail console, you can view information about any CloudTrail service-linked channels created by AWS services. The table is empty if your account does not have any service-linked channels.

Use the following procedure to view information about a service-linked channel.

1. Choose **Settings** in the left navigation pane of the CloudTrail console.

2. From **Service-linked channels**, choose a service-linked channel to view its details.
3. On the details page, review the configured settings for the service-linked channel.

You can view the following information on the details page.

- **Channel name** - The full name of the channel. The channel name format is `aws-service-channel/AWS_service_name/slc` where *AWS_service_name* represents the name of the AWS service that manages the channel.
- **Channel ARN** - The ARN of the channel, which you can use in a API request to get details about the channel.
- **All regions** - The value is Yes if the channel is configured for all AWS Regions.
- **AWS service** - The name of the AWS service managing the channel.
- **Management events** - Shows any management events configured for the channel.
- **Data events** - Shows any data events configured for the channel.

Viewing service-linked channels by using the AWS CLI

Using the AWS CLI, you can view information about any CloudTrail service-linked channels created by AWS services.

Topics

- [Get a CloudTrail service-linked channel](#)
- [List all CloudTrail service-linked channels](#)
- [AWS service events on service-linked channels](#)

Get a CloudTrail service-linked channel

The following example AWS CLI command returns information about a specific CloudTrail service-linked channel, including the name of the destination AWS service, any advanced selectors configured for the channel, and whether the channel applies to all Regions or a single Region.

You must specify an ARN or the ID suffix of an ARN for `--channel`.

```
aws cloudtrail get-channel --channel EXAMPLE-ee54-4813-92d5-999aeEXAMPLE
```

The following is an example response. In this example, `AWS_service_name` represents the name of the AWS service that created the channel.

```
{
  "ChannelArn": "arn:aws:cloudtrail:us-east-1:111122223333:channel/EXAMPLE-ee54-4813-92d5-999aeEXAMPLE",
  "Name": "aws-service-channel/AWS_service_name/slc",
  "Source": "CloudTrail",
  "SourceConfig": {
    "ApplyToAllRegions": false,
    "AdvancedEventSelectors": [
      {
        "Name": "Management Events Only",
        "FieldSelectors": [
          {
            "Field": "eventCategory",
            "Equals": [
              "Management"
            ]
          }
        ]
      }
    ]
  },
  "Destinations": [
    {
      "Type": "AWS_SERVICE",
      "Location": "AWS_service_name"
    }
  ]
}
```

List all CloudTrail service-linked channels

The following example AWS CLI command returns information about all CloudTrail service-linked channels that were created on your behalf. Optional parameters include `--max-results`, to specify a maximum number of results that you want the command to return on a single page. If there are more results than your specified `--max-results` value, run the command again adding the returned `NextToken` value to get the next page of results.

```
aws cloudtrail list-channels
```

The following is an example response. In this example, `AWS_service_name` represents the name of the AWS service that created the channel.

```
{
  "Channels": [
    {
      "ChannelArn": "arn:aws:cloudtrail:us-east-1:111122223333:channel/EXAMPLE-ee54-4813-92d5-999aeEXAMPLE",
      "Name": "aws-service-channel/AWS_service_name/slc"
    }
  ]
}
```

AWS service events on service-linked channels

The AWS service managing the service-linked channel can initiate actions on the service-linked channel (for example, creating or updating a service-linked channel). CloudTrail logs these actions as [AWS service events](#), and delivers these events to the **Event history**, and any active trails and event data stores configured for management events. For these events, the `eventType` field is `AwsServiceEvent`.

The following is an example log file entry of an AWS service event for creation of a service-linked channel.

```
{
  "eventVersion": "1.08",
  "userIdentity": {
    "accountId": "111122223333",
    "invokedBy": "AWS Internal"
  },
  "eventTime": "2022-08-18T17:11:22Z",
  "eventSource": "cloudtrail.amazonaws.com",
  "eventName": "CreateServiceLinkedChannel",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "AWS Internal",
  "userAgent": "AWS Internal",
  "requestParameters": null,
  "responseElements": null,
}
```



```
"requestID":"564f004c-EXAMPLE",
"eventID":"234f004b-EXAMPLE",
"readOnly":false,
"resources":[
  {
    "accountId":"184434908391",
    "type":"AWS::CloudTrail::Channel",
    "ARN":"arn:aws:cloudtrail:us-east-1:111122223333:channel/7944f0ec-EXAMPLE"
  }
],
"eventType":"AwsServiceEvent",
"managementEvent":true,
"recipientAccountId":"111122223333",
"eventCategory":"Management"
}
```

Understanding CloudTrail events

An event in CloudTrail is the record of an activity in an AWS account. This activity can be an action taken by an IAM identity, or service that is monitorable by CloudTrail. CloudTrail events provide a history of both API and non-API account activity made through the AWS Management Console, AWS SDKs, command line tools, and other AWS services.

CloudTrail log files aren't an ordered stack trace of the public API calls, so events don't appear in any specific order.

There are four types of CloudTrail events:

- [Management events](#)
- [Data events](#)
- [Network activity events](#)
- [Insights events](#)

By default, trails and event data stores log management events, but not data events, network activity events, or Insights events.

All event types use a CloudTrail JSON log format. The log contains information about requests for resources in your account, such as who made the request, the services used, the actions performed, and parameters for the action. The event data is enclosed in a `Records` array.

For information about CloudTrail event record fields for management, data, and network activity events, see [CloudTrail record contents for management, data, and network activity events](#).

For information about CloudTrail event record fields for Insights events for trails, see [CloudTrail record contents for Insights events for trails](#).

For information about CloudTrail event record fields for Insights events for event data stores, see [CloudTrail record contents for Insights events for event data stores](#).

Management events

Management events provide information about management operations that are performed on resources in your AWS account. These are also known as *control plane operations*.

Example management events include:

- Configuring security (for example, AWS Identity and Access Management AttachRolePolicy API operations).
- Registering devices (for example, Amazon EC2 CreateDefaultVpc API operations).
- Configuring rules for routing data (for example, Amazon EC2 CreateSubnet API operations).
- Setting up logging (for example, AWS CloudTrail CreateTrail API operations).

Management events can also include non-API events that occur in your account. For example, when a user signs in to your account, CloudTrail logs the ConsoleLogin event. For more information, see [Non-API events captured by CloudTrail](#).

By default, CloudTrail trails and CloudTrail Lake event data stores log management events. For more information about logging management events, see [Logging management events](#).

The following example shows a single log record of a management event. In this event, an IAM user named Mary_Major ran the **aws cloudtrail start-logging** command to call the CloudTrail [StartLogging](#) action to start the logging process on a trail named myTrail.

```
{
  "eventVersion": "1.09",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "EXAMPLE6E4XEGITWATV6R",
    "arn": "arn:aws:iam::123456789012:user/Mary_Major",
    "accountId": "123456789012",
    "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
    "userName": "Mary_Major",
    "sessionContext": {
      "attributes": {
        "creationDate": "2023-07-19T21:11:57Z",
        "mfaAuthenticated": "false"
      }
    }
  },
  "eventTime": "2023-07-19T21:33:41Z",
  "eventSource": "cloudtrail.amazonaws.com",
  "eventName": "StartLogging",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.0",
  "userAgent": "aws-cli/2.13.5 Python/3.11.4 Linux/4.14.255-314-253.539.amzn2.x86_64
exec-env/CloudShell exe/x86_64.amzn.2 prompt/off command/cloudtrail.start-logging",
```

```

    "requestParameters": {
      "name": "myTrail"
    },
    "responseElements": null,
    "requestID": "9d478fc1-4f10-490f-a26b-EXAMPLE0e932",
    "eventID": "eae87c48-d421-4626-94f5-EXAMPLEac994",
    "readOnly": false,
    "eventType": "AwsApiCall",
    "managementEvent": true,
    "recipientAccountId": "123456789012",
    "eventCategory": "Management",
    "tlsDetails": {
      "tlsVersion": "TLSv1.2",
      "cipherSuite": "ECDHE-RSA-AES128-GCM-SHA256",
      "clientProvidedHostHeader": "cloudtrail.us-east-1.amazonaws.com"
    },
    "sessionCredentialFromConsole": "true"
  }
}

```

In this next example, an IAM user user named Paulo_Santos ran the **aws cloudtrail start-event-data-store-ingestion** command to call the [StartEventDataStoreIngestion](#) action to start ingestion on an event data store.

```

{
  "eventVersion": "1.09",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "EXAMPLEPHCNW5EQV7NA54",
    "arn": "arn:aws:iam::123456789012:user/Paulo_Santos",
    "accountId": "123456789012",
    "accessKeyId": "(AKIAIOSFODNN7EXAMPLE",
    "userName": "Paulo_Santos",
    "sessionContext": {
      "attributes": {
        "creationDate": "2023-07-21T21:55:30Z",
        "mfaAuthenticated": "false"
      }
    }
  },
  "eventTime": "2023-07-21T21:57:28Z",
  "eventSource": "cloudtrail.amazonaws.com",
  "eventName": "StartEventDataStoreIngestion",
  "awsRegion": "us-east-1",

```

```

    "sourceIPAddress": "192.0.2.0",
    "userAgent": "aws-cli/2.13.1 Python/3.11.4 Linux/4.14.255-314-253.539.amzn2.x86_64
exec-env/CloudShell exe/x86_64.amzn.2 prompt/off command/cloudtrail.start-event-data-
store-ingestion",
    "requestParameters": {
        "eventDataStore": "arn:aws:cloudtrail:us-
east-1:123456789012:eventdatastore/2a8f2138-0caa-46c8-a194-EXAMPLE87d41"
    },
    "responseElements": null,
    "requestID": "f62a3494-ba4e-49ee-8e27-EXAMPLE4253f",
    "eventID": "d97ca7e2-04fe-45b4-882d-EXAMPLEa9b2c",
    "readOnly": false,
    "eventType": "AwsApiCall",
    "managementEvent": true,
    "recipientAccountId": "123456789012",
    "eventCategory": "Management",
    "tlsDetails": {
        "tlsVersion": "TLSv1.2",
        "cipherSuite": "ECDHE-RSA-AES128-GCM-SHA256",
        "clientProvidedHostHeader": "cloudtrail.us-east-1.amazonaws.com"
    },
    "sessionCredentialFromConsole": "true"
}

```

Data events

Data events provide information about the resource operations performed on or in a resource. These are also known as *data plane operations*. Data events are often high-volume activities.

Example data events include:

- [Amazon S3 object-level API activity](#) (for example, `GetObject`, `DeleteObject`, and `PutObject` API operations) on objects in S3 buckets.
- AWS Lambda function execution activity (the `Invoke` API).
- CloudTrail [PutAuditEvents](#) activity on a [CloudTrail Lake channel](#) that is used to log events from outside AWS.
- Amazon SNS [Publish](#) and [PublishBatch](#) API operations on topics.

The following table shows the resource types available for trails and event data stores. The **Resource type (console)** column shows the appropriate selection in the console. The

resources.type value column shows the `resources.type` value that you would specify to include data events of that type in your trail or event data store using the AWS CLI or CloudTrail APIs.

For trails, you can use basic or advanced event selectors to log data events for Amazon S3 objects in general purpose buckets, Lambda functions, and DynamoDB tables (shown in the first three rows of the table). You can use only advanced event selectors to log the resource types shown in the remaining rows.

For event data stores, you can use only advanced event selectors to include data events.

Data events supported by AWS CloudTrail

AWS service	Description	Resource type (console)	resources.type value
Amazon RDS	Amazon RDS API activity on a DB Cluster.	RDS Data API - DB Cluster	<code>AWS::RDS::DBCluster</code>
Amazon S3	Amazon S3 object-level API activity (for example, <code>GetObject</code> , <code>DeleteObject</code> , and <code>PutObject</code> API operations) on objects in general purpose buckets.	S3	<code>AWS::S3::Object</code>
Amazon S3	Amazon S3 API activity on access points.	S3 Access Point	<code>AWS::S3::AccessPoint</code>
Amazon S3	Amazon S3 object-level API activity (for example, <code>GetObject</code> , <code>DeleteObject</code> , and <code>PutObject</code> API operations) on	S3 Express	<code>AWS::S3Express::Object</code>

AWS service	Description	Resource type (console)	resources.type value
	objects in directory buckets.		
Amazon S3	Amazon S3 Object Lambda access points API activity , such as calls to CompleteMultipartUpload and GetObject .	S3 Object Lambda	AWS::S3ObjectLambda::AccessPoint
Amazon S3	Amazon FSx API activity on volumes.	FSx Volume	AWS::FSx::Volume
Amazon S3 Tables	Amazon S3 API activity on tables .	S3 table	AWS::S3Tables::Table
Amazon S3 Tables	Amazon S3 API activity on table buckets .	S3 table bucket	AWS::S3Tables::TableBucket
Amazon S3 Vectors	Amazon S3 API activity on vector buckets .	S3 vector bucket	AWS::S3Vectors::VectorBucket
Amazon S3 Vectors	Amazon S3 API activity on vector indexes .	S3 vector index	AWS::S3Vectors::Index
Amazon S3 on Outposts	Amazon S3 on Outposts object-level API activity .	S3 Outposts	AWS::S3Outposts::Object

AWS service	Description	Resource type (console)	resources.type value
Amazon SNS	Amazon SNS Publish API operations on platform endpoints.	SNS platform endpoint	AWS::SNS::PlatformEndpoint
Amazon SNS	Amazon SNS Publish and PublishBatch API operations on topics.	SNS topic	AWS::SNS::Topic
Amazon SQS	Amazon SQS API activity on messages.	SQS	AWS::SQS::Queue
AWS Supply Chain	AWS Supply Chain API activity on an instance.	Supply Chain	AWS::SCN::Instance
Amazon SWF	Amazon SWF API activity on domains .	SWF domain	AWS::SWF::Domain
AWS AppConfig	AWS AppConfig API activity for configuration operations such as calls to StartConfigurationSession and GetLatestConfiguration .	AWS AppConfig	AWS::AppConfig::Configuration
AWS AppSync	AWS AppSync API activity on AppSync GraphQL APIs.	AppSync GraphQL	AWS::AppSync::GraphQLApi

AWS service	Description	Resource type (console)	resources.type value
Amazon Aurora DSQL	Amazon Aurora DSQL API activity on cluster resources.	Amazon Aurora DSQL	AWS::DSQL::Cluster
AWS B2B Data Interchange	B2B Data Interchange API activity for Transformer operations such as calls to GetTransformerJob and StartTransformerJob .	B2B Data Interchange	AWS::B2BI::Transformer
AWS Backup	AWS Backup Search Data API activity on search jobs.	AWS Backup Search Data APIs	AWS::Backup::SearchJob
Amazon Bedrock	Amazon Bedrock API activity on an agent alias.	Bedrock agent alias	AWS::Bedrock::AgentAlias
Amazon Bedrock	Amazon Bedrock API activity on async invocations.	Bedrock async invoke	AWS::Bedrock::AsyncInvoke
Amazon Bedrock	Amazon Bedrock API activity on a flow alias.	Bedrock flow alias	AWS::Bedrock::FlowAlias
Amazon Bedrock	Amazon Bedrock API activity on guardrails.	Bedrock guardrail	AWS::Bedrock::Guardrail

AWS service	Description	Resource type (console)	resources.type value
Amazon Bedrock	Amazon Bedrock API activity on inline agents.	Bedrock Invoke Inline-Agent	AWS::Bedrock::InlineAgent
Amazon Bedrock	Amazon Bedrock API activity on a knowledge base.	Bedrock knowledge base	AWS::Bedrock::KnowledgeBase
Amazon Bedrock	Amazon Bedrock API activity on models.	Bedrock model	AWS::Bedrock::Model
Amazon Bedrock	Amazon Bedrock API activity on prompts.	Bedrock prompt	AWS::Bedrock::PromptVersion
Amazon Bedrock	Amazon Bedrock API activity on sessions.	Bedrock session	AWS::Bedrock::Session
Amazon Bedrock	Amazon Bedrock API activity on flow executions.	Bedrock flow execution	AWS::Bedrock::FlowExecution
Amazon Bedrock	Amazon Bedrock API activity on an automated reasoning policy.	Bedrock automated reasoning policy	AWS::Bedrock::AutomatedReasoningPolicy
Amazon Bedrock	Amazon Bedrock API activity on an automated reasoning policy version.	Bedrock automated reasoning policy version	AWS::Bedrock::AutomatedReasoningPolicyVersion

AWS service	Description	Resource type (console)	resources.type value
Amazon Bedrock	Amazon Bedrock data automation project API activity.	Bedrock Data Automation project	AWS::Bedrock::DataAutomationProject
Amazon Bedrock	Bedrock data automation invocation API activity.	Bedrock Data Automation invocation	AWS::Bedrock::DataAutomationInvocation
Amazon Bedrock	Amazon Bedrock data automation profile API activity.	Bedrock Data Automation profile	AWS::Bedrock::DataAutomationProfile
Amazon Bedrock	Amazon Bedrock blueprint API activity.	Bedrock blueprint	AWS::Bedrock::Blueprint
Amazon Bedrock	Amazon Bedrock Code-Interpreter API activity.	Bedrock-AgentCore Code-Interpreter	AWS::BedrockAgentCore::CodeInterpreter
Amazon Bedrock	Amazon Bedrock Browser API activity.	Bedrock-AgentCore Browser	AWS::BedrockAgentCore::Browser
Amazon Bedrock	Amazon Bedrock Workload Identity API activity.	Bedrock-AgentCore Workload Identity	AWS::BedrockAgentCore::WorkloadIdentity

AWS service	Description	Resource type (console)	resources.type value
Amazon Bedrock	Amazon Bedrock Workload Identity Directory API activity.	Bedrock-AgentCore Workload Identity Directory	AWS::BedrockAgentCore::WorkloadIdentityDirectory
Amazon Bedrock	Amazon Bedrock Token Vault API activity.	Bedrock-AgentCore Token Vault	AWS::BedrockAgentCore::TokenVault
Amazon Bedrock	Amazon Bedrock APIKey CredentialProvider API activity.	Bedrock-AgentCore APIKey CredentialProvider	AWS::BedrockAgentCore::APIKeyCredentialProvider
Amazon Bedrock	Amazon Bedrock Runtime API activity.	Bedrock-AgentCore Runtime	AWS::BedrockAgentCore::Runtime
Amazon Bedrock	Amazon Bedrock Runtime-Endpoint API activity.	Bedrock-AgentCore Runtime-Endpoint	AWS::BedrockAgentCore::RuntimeEndpoint
Amazon Bedrock	Amazon Bedrock Gateway API activity.	Bedrock-AgentCore Gateway	AWS::BedrockAgentCore::Gateway
Amazon Bedrock	Amazon Bedrock Memory API activity.	Bedrock-AgentCore Memory	AWS::BedrockAgentCore::Memory

AWS service	Description	Resource type (console)	resources.type value
Amazon Bedrock	Amazon Bedrock OAuth2 CredentialProvider API activity.	Bedrock-AgentCore-Oauth2-CredentialProvider	AWS::BedrockAgentCore::OAuth2CredentialProvider
Amazon Bedrock	Amazon Bedrock Browser-Custom API activity.	Bedrock-AgentCore-Browser-Custom	AWS::BedrockAgentCore::BrowserCustom
Amazon Bedrock	Amazon Bedrock Code-Interpreter-Custom API activity.	Bedrock-AgentCore-Code-Interpreter-Custom	AWS::BedrockAgentCore::CodeInterpreterCustom
Amazon Bedrock	Amazon Bedrock Tool API activity.	Bedrock Tool	AWS::Bedrock::Tool
AWS Cloud Map	AWS Cloud Map API activity on a namespace .	AWS Cloud Map namespace	AWS::ServiceDiscovery::Namespace
AWS Cloud Map	AWS Cloud Map API activity on a service .	AWS Cloud Map service	AWS::ServiceDiscovery::Service
Amazon CloudFront	CloudFront API activity on a KeyValueStore .	CloudFront KeyValueStore	AWS::CloudFront::KeyValueStore

AWS service	Description	Resource type (console)	resources.type value
AWS CloudTrail	CloudTrail PutAuditEvents activity on a CloudTrail Lake channel that is used to log events from outside AWS.	CloudTrail channel	AWS::CloudTrail::Channel
Amazon CloudWatch	Amazon CloudWatch API activity on metrics.	CloudWatch metric	AWS::CloudWatch::Metric
Amazon CloudWatch Network Flow Monitor	Amazon CloudWatch Network Flow Monitor API activity on monitors.	Network Flow Monitor monitor	AWS::NetworkFlowMonitor::Monitor
Amazon CloudWatch Network Flow Monitor	Amazon CloudWatch Network Flow Monitor API activity on scopes.	Network Flow Monitor scope	AWS::NetworkFlowMonitor::Scope
Amazon CloudWatch RUM	Amazon CloudWatch RUM API activity on app monitors.	RUM app monitor	AWS::RUM::AppMonitor
Amazon CodeGuru Profiler	CodeGuru Profiler API activity on profiling groups.	CodeGuru Profiler profiling group	AWS::CodeGuruProfiler::ProfilingGroup

AWS service	Description	Resource type (console)	resources.type value
Amazon CodeWhisperer	Amazon CodeWhisperer API activity on a customization.	CodeWhisperer customization	AWS::CodeWhisperer::Customization
Amazon CodeWhisperer	Amazon CodeWhisperer API activity on a profile.	CodeWhisperer	AWS::CodeWhisperer::Profile
Amazon Cognito	Amazon Cognito API activity on Amazon Cognito identity pools .	Cognito Identity Pools	AWS::Cognito::IdentityPool
AWS Data Exchange	AWS Data Exchange API activity on assets.	Data Exchange asset	AWS::DataExchange::Asset
Amazon Data Firehose	Amazon Data Firehose delivery stream API activity.	Amazon Data Firehose	AWS::KinesisFirehose::DeliveryStream
AWS Deadline Cloud	Deadline Cloud API activity on fleets.	Deadline Cloud fleet	AWS::Deadline::Fleet
AWS Deadline Cloud	Deadline Cloud API activity on jobs.	Deadline Cloud job	AWS::Deadline::Job
AWS Deadline Cloud	Deadline Cloud API activity on queues.	Deadline Cloud queue	AWS::Deadline::Queue

AWS service	Description	Resource type (console)	resources.type value
AWS Deadline Cloud	Deadline Cloud API activity on workers.	Deadline Cloud worker	AWS::Deadline::Worker

For tables with streams enabled, the `resources` field in the data event contains both `AWS::DynamoDB::Stream` and `AWS::DynamoDB::Table`. If you specify `AWS::DynamoDB::Table` for the `resources.type`, it will log both DynamoDB table and DynamoDB

AWS service	Description	Resource type (console)	resources.type value
	streams events by default. To exclude streams events , add a filter on the eventName field.		
Amazon DynamoDB	Amazon DynamoDB API activity on streams.	DynamoDB Streams	AWS::DynamoDB::Stream
Amazon Elastic Block Store	Amazon Elastic Block Store (EBS) direct APIs, such as PutSnapshotBlock , GetSnapshotBlock , and ListChangedBlocks on Amazon EBS snapshots.	Amazon EBS direct APIs	AWS::EC2::Snapshot
Amazon Elastic Compute Cloud	Amazon EC2 instance connect endpoint API activity.	EC2 instance connect endpoint	AWS::EC2::InstanceConnectEndpoint

AWS service	Description	Resource type (console)	resources.type value
Amazon Elastic Container Service	Amazon Elastic Container Service API activity on a container instance.	ECS container instance	AWS::ECS::ContainerInstance
Amazon Elastic Kubernetes Service	Amazon Elastic Kubernetes Service API activity on dashboards.	Amazon Elastic Kubernetes Service dashboard	AWS::EKS::Dashboard
Amazon EMR	Amazon EMR API activity on a write-ahead log workspace.	EMR write-ahead log workspace	AWS::EMRWAL::Workspace
AWS End User Messaging SMS	AWS End User Messaging SMS API activity on originations on identities.	SMS Voice origination identity	AWS::SMSVoice::OriginationIdentity
AWS End User Messaging SMS	AWS End User Messaging SMS API activity on messages.	SMS Voice message	AWS::SMSVoice::Message
AWS End User Messaging Social	AWS End User Messaging Social API activity on phone number IDs.	Social-Messaging Phone Number Id	AWS::SocialMessaging::PhoneNumberId
AWS End User Messaging Social	AWS End User Messaging Social API activity on Waba IDs.	Social-Messaging Waba ID	AWS::SocialMessaging::WabaId

AWS service	Description	Resource type (console)	resources.type value
Amazon FinSpace	Amazon FinSpace API activity on environments.	FinSpace	AWS::FinSpace::Environment
Amazon GameLift Streams	Amazon GameLift Streams streaming API activity on applications.	GameLift Streams application	AWS::GameLiftStreams::Application
Amazon GameLift Streams	Amazon GameLift Streams streaming API activity on stream groups.	GameLift Streams stream group	AWS::GameLiftStreams::StreamGroup
AWS Glue	AWS Glue API activity on tables that were created by Lake Formation.	Lake Formation	AWS::Glue::Table
Amazon GuardDuty	Amazon GuardDuty API activity for a detector .	GuardDuty detector	AWS::GuardDuty::Detector
AWS HealthImaging	AWS HealthImaging API activity on data stores.	MedicalImaging data store	AWS::MedicalImaging::Datastore
AWS HealthImaging	AWS HealthImaging image set API activity.	MedicalImaging image set	AWS::MedicalImaging::ImageSet
AWS IoT	AWS IoT API activity on certificates .	IoT certificate	AWS::IoT::Certificate

AWS service	Description	Resource type (console)	resources.type value
AWS IoT	AWS IoT API activity on things .	IoT thing	AWS::IoT::Thing
AWS IoT Greengrass Version 2	Greengrass API activity from a Greengrass core device on a component version.  Note Greengrass doesn't log access denied events.	IoT Greengrass component version	AWS::GreengrassV2::ComponentVersion
AWS IoT Greengrass Version 2	Greengrass API activity from a Greengrass core device on a deployment.  Note Greengrass doesn't log access denied events.	IoT Greengrass deployment	AWS::GreengrassV2::Deployment
AWS IoT SiteWise	IoT SiteWise API activity on assets .	IoT SiteWise asset	AWS::IoTSiteWise::Asset

AWS service	Description	Resource type (console)	resources.type value
AWS IoT SiteWise	IoT SiteWise API activity on time series .	IoT SiteWise time series	AWS::IoTSiteWise::TimeSeries
AWS IoT SiteWise Assistant	Sitewise Assistant API activity on conversations.	Sitewise Assistant conversation	AWS::SitewiseAssistant::Conversation
AWS IoT TwinMaker	IoT TwinMaker API activity on an entity .	IoT TwinMaker entity	AWS::IoTTwinMaker::Entity
AWS IoT TwinMaker	IoT TwinMaker API activity on a workspace .	IoT TwinMaker workspace	AWS::IoTTwinMaker::Workspace
Amazon Kendra Intelligent Ranking	Amazon Kendra Intelligent Ranking API activity on rescore execution plans .	Kendra Ranking	AWS::KendraRanking::ExecutionPlan
Amazon Keyspaces (for Apache Cassandra)	Amazon Keyspaces API activity on a table.	Cassandra table	AWS::Cassandra::Table
Amazon Keyspaces (for Apache Cassandra)	Amazon Keyspaces (for Apache Cassandra) API activity on Cassandra CDC streams.	Cassandra CDC streams	AWS::Cassandra::Stream

AWS service	Description	Resource type (console)	resources.type value
Amazon Kinesis Data Streams	Kinesis Data Streams API activity on streams .	Kinesis stream	AWS::Kinesis::Stream
Amazon Kinesis Data Streams	Kinesis Data Streams API activity on stream consumers .	Kinesis stream consumer	AWS::Kinesis::StreamConsumer
Amazon Kinesis Video Streams	Kinesis Video Streams API activity on video streams, such as calls to GetMedia and PutMedia.	Kinesis video stream	AWS::KinesisVideo::Stream
Amazon Kinesis Video Streams	Kinesis Video Streams video signaling channel API activity.	Kinesis video signaling channel	AWS::KinesisVideo::SignalingChannel
AWS Lambda	AWS Lambda function execution activity (the Invoke API).	Lambda	AWS::Lambda::Function
Amazon Location Maps	Amazon Location Maps API activity.	Geo Maps	AWS::GeoMaps::Provider
Amazon Location Places	Amazon Location Places API activity.	Geo Places	AWS::GeoPlaces::Provider
Amazon Location Routes	Amazon Location Routes API activity.	Geo Routes	AWS::GeoRoutes::Provider

AWS service	Description	Resource type (console)	resources.type value
Amazon Machine Learning	Machine Learning API activity on ML models.	Maching Learning MModel	AWS::MachineLearning::MModel
Amazon Managed Blockchain	Amazon Managed Blockchain API activity on a network.	Managed Blockchain network	AWS::ManagedBlockchain::Network
Amazon Managed Blockchain	Amazon Managed Blockchain JSON-RPC calls on Ethereum nodes, such as eth_getBalance or eth_getBlockByNumber .	Managed Blockchain	AWS::ManagedBlockchain::Node
Amazon Managed Blockchain Query	Amazon Managed Blockchain Query API activity.	Managed Blockchain Query	AWS::ManagedBlockchainQuery::QueryAPI
Amazon Managed Workflows for Apache Airflow	Amazon MWAA API activity on environments.	Managed Apache Airflow	AWS::MWAA::Environment
Amazon Neptune Graph	Data API activities, for example queries, algorithms, or vector search, on a Neptune Graph.	Neptune Graph	AWS::NeptuneGraph::Graph

AWS service	Description	Resource type (console)	resources.type value
Amazon One Enterprise	Amazon One Enterprise API activity on a UKey.	Amazon One UKey	AWS::One::UKey
Amazon One Enterprise	Amazon One Enterprise API activity on users.	Amazon One User	AWS::One::User
AWS Payment Cryptography	AWS Payment Cryptography API activity on aliases.	Payment Cryptography Alias	AWS::PaymentCryptography::Alias
AWS Payment Cryptography	AWS Payment Cryptography API activity on keys.	Payment Cryptography Key	AWS::PaymentCryptography::Key
Amazon Pinpoint	Amazon Pinpoint API activity on mobile targeting applications.	Mobile Targeting Application	AWS::Pinpoint::App
AWS Private CA	AWS Private CA Connector for Active Directory API activity.	AWS Private CA Connector for Active Directory	AWS::PCAConnectorAD::Connector
AWS Private CA	AWS Private CA Connector for SCEP API activity.	AWS Private CA Connector for SCEP	AWS::PCAConnectorSCEP::Connector

AWS service	Description	Resource type (console)	resources.type value
Amazon Q Apps	Data API activity on Amazon Q Apps .	Amazon Q Apps	AWS::QApps::QApp
Amazon Q Apps	Data API activity on Amazon Q App sessions.	Amazon Q App Session	AWS::QApps::QAppSession
Amazon Q Business	Amazon Q Business API activity on an application.	Amazon Q Business application	AWS::QBusiness::Application
Amazon Q Business	Amazon Q Business API activity on a data source.	Amazon Q Business data source	AWS::QBusiness::DataSource
Amazon Q Business	Amazon Q Business API activity on an index.	Amazon Q Business index	AWS::QBusiness::Index
Amazon Q Business	Amazon Q Business API activity on a web experience.	Amazon Q Business web experience	AWS::QBusiness::WebExperience
Amazon Q Business	Amazon Q Business integration API activity.	Amazon Q Business integration	AWS::QBusiness::Integration
Amazon Q Developer	Amazon Q Developer API activity on an integration.	Q Developer integration	AWS::QDeveloper::Integration

AWS service	Description	Resource type (console)	resources.type value
Amazon Q Developer	Amazon Q Developer API activity on operational investigations.	AI Ops Investigation Group	AWS::AIOps::InvestigationGroup
Amazon Quick Suite	Amazon Quick Suite API activity on an action connector.	AWS QuickSuite Actions	AWS::QuickSight::ActionConnector
Amazon Quick Suite	Amazon Quick Suite Flow API activity.	AWS::QuickSight::Flow	AWS::QuickSight::Flow
Amazon Quick Suite	Amazon Quick Suite FlowSession API activity.	AWS::QuickSight::FlowSession	AWS::QuickSight::FlowSession
Amazon SageMaker AI	Amazon SageMaker AI InvokeEndpointWithResponseStream activity on endpoints.	SageMaker AI endpoint	AWS::SageMaker::Endpoint
Amazon SageMaker AI	Amazon SageMaker AI API activity on feature stores.	SageMaker AI feature store	AWS::SageMaker::FeatureGroup
Amazon SageMaker AI	Amazon SageMaker AI API activity on experiment trial components .	SageMaker AI metrics experiment trial component	AWS::SageMaker::ExperimentTrialComponent

AWS service	Description	Resource type (console)	resources.type value
Amazon SageMaker AI;	Amazon SageMaker AI MLflow API activity.	SageMaker MLflow	AWS::SageMaker::MlflowTrackingServer
AWS Signer	Signer API activity on signing jobs.	Signer signing job	AWS::Signer::SigningJob
AWS Signer	Signer API activity on signing profiles.	Signer signing profile	AWS::Signer::SigningProfile
Amazon Simple Email Service	Amazon Simple Email Service (Amazon SES) API activity on configuration sets.	SES configuration set	AWS::SES::ConfigurationSet
Amazon Simple Email Service	Amazon Simple Email Service (Amazon SES) API activity on email identities.	SES identity	AWS::SES::EmailIdentity
Amazon Simple Email Service	Amazon Simple Email Service (Amazon SES) API activity on templates.	SES template	AWS::SES::Template
Amazon SimpleDB	Amazon SimpleDB API activity on domains.	SimpleDB domain	AWS::SDB::Domain
AWS Step Functions	Step Functions API activity on activities.	Step Functions	AWS::StepFunctions::Activity

AWS service	Description	Resource type (console)	resources.type value
AWS Step Functions	Step Functions API activity on state machines.	Step Functions state machine	AWS::StepFunctions::StateMachine
AWS Systems Manager	Systems Manager API activity on control channels.	Systems Manager	AWS::SSMMessages::ControlChannel
AWS Systems Manager	Systems Manager API activity on impact assessments.	SSM Impact Assessment	AWS::SSM::ExecutionPreview
AWS Systems Manager	Systems Manager API activity on managed nodes.	Systems Manager managed node	AWS::SSM::ManagedNode
Amazon Timestream	Amazon Timestream Query API activity on databases.	Timestream database	AWS::Timestream::Database
Amazon Timestream	Amazon Timestream API activity on regional endpoints.	Timestream regional endpoint	AWS::Timestream::RegionalEndpoint
Amazon Timestream	Amazon Timestream Query API activity on tables.	Timestream table	AWS::Timestream::Table
Amazon Verified Permissions	Amazon Verified Permissions API activity on a policy store.	Amazon Verified Permissions	AWS::VerifiedPermissions::PolicyStore

AWS service	Description	Resource type (console)	resources.type value
Amazon WorkSpaces Thin Client	WorkSpaces Thin Client API activity on a Device.	Thin Client Device	AWS::ThinClient::Device
Amazon WorkSpaces Thin Client	WorkSpaces Thin Client API activity on an Environment.	Thin Client Environment	AWS::ThinClient::Environment
AWS X-Ray	X-Ray API activity on traces.	X-Ray trace	AWS::XRay::Trace

Data events are not logged by default when you create a trail or event data store. To record CloudTrail data events, you must explicitly add the supported resources or resource types for which you want to collect activity. For more information, see [Creating a trail with the CloudTrail console](#) and [Create an event data store for CloudTrail events with the console](#).

Additional charges apply for logging data events. For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

The following example shows a single log record of a data event for the Amazon SNS Publish action.

```
{
  "eventVersion": "1.09",
  "userIdentity": {
    "type": "AssumedRole",
    "principalId": "EX_PRINCIPAL_ID",
    "arn": "arn:aws:iam::123456789012:user/Bob",
    "accountId": "123456789012",
    "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
    "sessionContext": {
      "sessionIssuer": {
        "type": "Role",
        "principalId": "AKIAIOSFODNN7EXAMPLE",
        "arn": "arn:aws:iam::123456789012:role/Admin",
        "accountId": "123456789012",
```

```

        "userName": "ExampleUser"
      },
      "attributes": {
        "creationDate": "2023-08-21T16:44:05Z",
        "mfaAuthenticated": "false"
      }
    }
  },
  "eventTime": "2023-08-21T16:48:37Z",
  "eventSource": "sns.amazonaws.com",
  "eventName": "Publish",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.0",
  "userAgent": "aws-cli/1.29.16 md/Botocore#1.31.16 ua/2.0 os/
linux#5.4.250-173.369.amzn2int.x86_64 md/arch#x86_64 lang/python#3.8.17 md/
pyimpl#CPython cfg/retry-mode#legacy botocore/1.31.16",
  "requestParameters": {
    "topicArn": "arn:aws:sns:us-east-1:123456789012:ExampleSNSTopic",
    "message": "HIDDEN_DUE_TO_SECURITY_REASONS",
    "subject": "HIDDEN_DUE_TO_SECURITY_REASONS",
    "messageStructure": "json",
    "messageAttributes": "HIDDEN_DUE_TO_SECURITY_REASONS"
  },
  "responseElements": {
    "messageId": "0787cd1e-d92b-521c-a8b4-90434e8ef840"
  },
  "requestID": "0a8ab208-11bf-5e01-bd2d-ef55861b545d",
  "eventID": "bb3496d4-5252-4660-9c28-3c6aebdb21c0",
  "readOnly": false,
  "resources": [{
    "accountId": "123456789012",
    "type": "AWS::SNS::Topic",
    "ARN": "arn:aws:sns:us-east-1:123456789012:ExampleSNSTopic"
  }],
  "eventType": "AwsApiCall",
  "managementEvent": false,
  "recipientAccountId": "123456789012",
  "eventCategory": "Data",
  "tlsDetails": {
    "tlsVersion": "TLSv1.2",
    "cipherSuite": "ECDHE-RSA-AES128-GCM-SHA256",
    "clientProvidedHostHeader": "sns.us-east-1.amazonaws.com"
  }
}

```

```
}
```

The next example shows a single log record of a data event for the Amazon Cognito `GetCredentialsForIdentity` action.

```
{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "Unknown"
  },
  "eventTime": "2023-01-19T16:55:08Z",
  "eventSource": "cognito-identity.amazonaws.com",
  "eventName": "GetCredentialsForIdentity",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.4",
  "userAgent": "aws-cli/2.7.25 Python/3.9.11 Darwin/21.6.0 exe/x86_64 prompt/off
command/cognito-identity.get-credentials-for-identity",
  "requestParameters": {
    "logins": {
      "cognito-idp.us-east-1.amazonaws.com/us-east-1_aaaaaaaa":
"HIDDEN_DUE_TO_SECURITY_REASONS"
    },
    "identityId": "us-east-1:1cf667a2-49a6-454b-9e45-23199EXAMPLE"
  },
  "responseElements": {
    "credentials": {
      "accessKeyId": "ASIAIOSFODNN7EXAMPLE",
      "sessionToken": "aAaAaAaAaAab1111111111EXAMPLE",
      "expiration": "Jan 19, 2023 5:55:08 PM"
    },
    "identityId": "us-east-1:1cf667a2-49a6-454b-9e45-23199EXAMPLE"
  },
  "requestID": "659dfc23-7c4e-4e7c-858a-1abce884d645",
  "eventID": "6ad1c766-5a41-4b28-b5ca-e223ccb00f0d",
  "readOnly": false,
  "resources": [{
    "accountId": "111122223333",
    "type": "AWS::Cognito::IdentityPool",
    "ARN": "arn:aws:cognito-identity:us-east-1:111122223333:identitypool/us-
east-1:2dg778b3-50b7-565c-0f56-34200EXAMPLE"
  }],
  "eventType": "AwsApiCall",
  "managementEvent": false,
```



```
"recipientAccountId": "111122223333",  
"eventCategory": "Data"  
}
```

Network activity events

CloudTrail network activity events enable VPC endpoint owners to record AWS API calls made using their VPC endpoints from a private VPC to the AWS service. Network activity events provide visibility into the resource operations performed within a VPC.

You can log network activity events for the following services:

- AWS AppConfig
- AWS App Mesh
- Amazon Athena
- AWS B2B Data Interchange
- AWS Backup gateway
- Amazon Bedrock
- Billing and Cost Management
- AWS Pricing Calculator
- AWS Cost Explorer
- AWS Cloud Control API
- AWS CloudHSM
- AWS Cloud Map
- AWS CloudFormation
- AWS CloudTrail
- Amazon CloudWatch
- CloudWatch Application Signals
- AWS CodeDeploy
- Amazon Comprehend Medical
- AWS Config
- AWS Data Exports

- Amazon Data Firehose
- AWS Directory Service
- Amazon DynamoDB
- Amazon EC2
- Amazon Elastic Container Service
- Amazon Elastic File System
- Elastic Load Balancing
- Amazon EventBridge
- Amazon EventBridge Scheduler
- Amazon Fraud Detector
- AWS Free Tier
- Amazon FSx
- AWS Glue
- AWS HealthLake
- AWS IoT FleetWise
- AWS IoT Secure Tunneling
- AWS Invoicing
- Amazon Keyspaces (for Apache Cassandra)
- AWS KMS
- AWS Lake Formation
- AWS Lambda
- AWS License Manager
- Amazon Lookout for Equipment
- Amazon Lookout for Vision
- Amazon Personalize
- Amazon Q Business
- Amazon Rekognition
- Amazon Relational Database Service
- Amazon S3

Note

Amazon S3 [Multi-Region Access Points](#) are not supported.

- Amazon SageMaker AI
- AWS Secrets Manager
- Amazon Simple Notification Service
- Amazon Simple Queue Service
- Amazon Simple Workflow Service
- AWS Storage Gateway
- AWS Systems Manager Incident Manager
- Amazon Textract
- Amazon Transcribe
- Amazon Translate
- AWS Transform
- Amazon Verified Permissions
- Amazon WorkMail

Network activity events are not logged by default when you create a trail or event data store. To record CloudTrail network activity events, you must explicitly set the event source for which you want to collect activity. For more information, see [Logging network activity events](#).

Additional charges apply for logging network activity events. For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

The following example shows a successful AWS KMS ListKeys event that traversed a VPC endpoint. The `vpcEndpointId` field shows the ID of the VPC endpoint. The `vpcEndpointAccountId` field shows the account ID of the VPC endpoint owner. In this example, the request was made by the VPC endpoint owner.

```
{
  "eventVersion": "1.09",
  "userIdentity": {
    "type": "AssumedRole",
    "principalId": "ASIAIOSFODNN7EXAMPLE:role-name",
```

```

    "arn": "arn:aws:sts::123456789012:assumed-role/Admin/role-name",
    "accountId": "123456789012",
    "accessKeyId": "ASIAIOSFODNN7EXAMPLE",
    "sessionContext": {
      "sessionIssuer": {
        "type": "Role",
        "principalId": "ASIAIOSFODNN7EXAMPLE",
        "arn": "arn:aws:iam::123456789012:role/Admin",
        "accountId": "123456789012",
        "userName": "Admin"
      },
      "attributes": {
        "creationDate": "2024-06-04T23:10:46Z",
        "mfaAuthenticated": "false"
      }
    },
    "eventTime": "2024-06-04T23:12:50Z",
    "eventSource": "kms.amazonaws.com",
    "eventName": "ListKeys",
    "awsRegion": "us-east-1",
    "sourceIPAddress": "192.0.2.0",
    "requestID": "16bcc089-ac49-43f1-9177-EXAMPLE23731",
    "eventID": "228ca3c8-5f95-4a8a-9732-EXAMPLE60ed9",
    "eventType": "AwsVpceEvent",
    "recipientAccountId": "123456789012",
    "sharedEventID": "a1f3720c-ef19-47e9-a5d5-EXAMPLE8099f",
    "vpceEndpointId": "vpce-EXAMPLE08c1b6b9b7",
    "vpceEndpointAccountId": "123456789012",
    "eventCategory": "NetworkActivity"
  }
}

```

The next example shows an unsuccessful AWS KMS ListKeys event with a VPC endpoint policy violation. Because a VPC policy violation occurred, both the `errorCode` and `errorMessage` fields are present. The account ID in the `recipientAccountId` and `vpceEndpointAccountId` fields is the same, which indicates the event was sent to the VPC endpoint owner. The `accountId` in the `userIdentity` element is not the `vpceEndpointAccountId`, which indicates that the user making the request is not the VPC endpoint owner.

```

{
  "eventVersion": "1.09",
  "userIdentity": {

```

```
    "type": "AWSAccount",
    "principalId": "AKIAIOSFODNN7EXAMPLE",
    "accountId": "777788889999"
  },
  "eventTime": "2024-07-15T23:57:12Z",
  "eventSource": "kms.amazonaws.com",
  "eventName": "ListKeys",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.0",
  "errorCode": "VpceAccessDenied",
  "errorMessage": "The request was denied due to a VPC endpoint policy",
  "requestID": "899003b8-abc4-42bb-ad95-EXAMPLE0c374",
  "eventID": "7c6e3d04-0c3b-42f2-8589-EXAMPLE826c0",
  "eventType": "AwsVpceEvent",
  "recipientAccountId": "123456789012",
  "sharedEventID": "702f74c4-f692-4bfd-8491-EXAMPLEb1ac4",
  "vpceEndpointId": "vpce-EXAMPLE08c1b6b9b7",
  "vpceEndpointAccountId": "123456789012",
  "eventCategory": "NetworkActivity"
}
```

Insights events

CloudTrail Insights events capture unusual API call rate or error rate activity in your AWS account by analyzing CloudTrail management activity. Insights events provide relevant information, such as the associated API, error code, incident time, and statistics, that help you understand and act on unusual activity. Unlike other types of events captured in a CloudTrail trail or event data store, Insights events are logged only when CloudTrail detects changes in your account's API usage or error rate logging that differ significantly from the account's typical usage patterns. For more information, see [Working with CloudTrail Insights](#).

Examples of activity that might generate Insights events include:

- Your account typically logs no more than 20 Amazon S3 `deleteBucket` API calls per minute, but your account starts to log an average of 100 `deleteBucket` API calls per minute. An Insights event is logged at the start of the unusual activity, and another Insights event is logged to mark the end of the unusual activity.
- Your account typically logs 20 calls per minute to the Amazon EC2 `AuthorizeSecurityGroupIngress` API, but your account starts to log zero calls to `AuthorizeSecurityGroupIngress`. An Insights event is logged at the start of the unusual

activity, and ten minutes later, when the unusual activity ends, another Insights event is logged to mark the end of the unusual activity.

- Your account typically logs less than one `AccessDeniedException` error in a seven-day period on the AWS Identity and Access Management API, `DeleteInstanceProfile`. Your account starts to log an average of 12 `AccessDeniedException` errors per minute on the `DeleteInstanceProfile` API call. An Insights event is logged at the start of the unusual error rate activity, and another Insights event is logged to mark the end of the unusual activity.

These examples are provided for illustration purposes only. Your results may vary depending on your use case.

To log CloudTrail Insights events, you must explicitly enable Insights events on a new or existing trail or event data store. For more information about creating a trail, see [Creating a trail with the CloudTrail console](#). For more information about creating an event data store, see [Create an event data store for Insights events with the console](#).

Additional charges apply for Insights events. You will be charged separately if you enable Insights for both trails and event data stores. For more information, see [AWS CloudTrail Pricing](#).

There are two events logged to show unusual activity in CloudTrail Insights: a start event and an end event. The following example shows a single log record of a starting Insights event that occurred when the Application Auto Scaling API `CompleteLifecycleAction` was called an unusual number of times. For Insights events, the value of `eventCategory` is `Insight`. An `insightDetails` block identifies the event state, source, name, Insights type, and context, including statistics and attributions. For more information about the `insightDetails` block, see [CloudTrail record contents for Insights events for trails](#).

```
{
  "eventVersion": "1.08",
  "eventTime": "2023-07-10T01:42:00Z",
  "awsRegion": "us-east-1",
  "eventID": "55ed45c5-0b0c-4228-9fe5-EXAMPLEc3f4d",
  "eventType": "AwsCloudTrailInsight",
  "recipientAccountId": "123456789012",
  "sharedEventID": "979c82fe-14d4-4e4c-aa01-EXAMPLE3acee",
  "insightDetails": {
    "state": "Start",
    "eventSource": "autoscaling.amazonaws.com",
    "eventName": "CompleteLifecycleAction",
    "insightType": "ApiCallRateInsight",
```

```

    "insightContext": {
      "statistics": {
        "baseline": {
          "average": 9.82222E-5
        },
        "insight": {
          "average": 5.0
        },
        "insightDuration": 1,
        "baselineDuration": 10181
      },
      "attributions": [{
        "attribute": "userIdentityArn",
        "insight": [{
          "value": "arn:aws:sts::123456789012:assumed-role/
CodeDeployRole1",
          "average": 5.0
        }, {
          "value": "arn:aws:sts::123456789012:assumed-role/
CodeDeployRole2",
          "average": 5.0
        }, {
          "value": "arn:aws:sts::123456789012:assumed-role/
CodeDeployRole3",
          "average": 5.0
        }
      ]},
      "baseline": [{
        "value": "arn:aws:sts::123456789012:assumed-role/
CodeDeployRole1",
        "average": 9.82222E-5
      }
    ], {
      "attribute": "userAgent",
      "insight": [{
        "value": "codedeploy.amazonaws.com",
        "average": 5.0
      }
    ],
      "baseline": [{
        "value": "codedeploy.amazonaws.com",
        "average": 9.82222E-5
      }
    ]
  }, {
    "attribute": "errorCode",
    "insight": [{

```

```

        "value": "null",
        "average": 5.0
      }],
      "baseline": [{
        "value": "null",
        "average": 9.82222E-5
      }]
    }]
  }
},
"eventCategory": "Insight"
}

```

Logging management events

By default, trails and event data stores log management events and don't include data or Insights events.

Additional charges apply for data or Insights events. For more information, see [AWS CloudTrail Pricing](#).

Contents

- [Management events](#)
- [Read and write events](#)
- [Logging management events with the AWS Management Console](#)
 - [Updating the management event settings for an existing trail](#)
 - [Updating the management event settings for an existing event data store](#)
- [Logging management events with the AWS CLI](#)
 - [Examples: Logging management events for trails](#)
 - [Examples: Logging management events for trails using advanced event selectors](#)
 - [Examples: Logging management events for trails using basic event selectors](#)
 - [Examples: Logging management events for event data stores](#)
 - [Example: Exclude AWS KMS management events](#)
 - [Example: Exclude Amazon RDS management events](#)
 - [Example: Exclude AWS service events and events from AWS Management Console sessions](#)
 - [Example: Exclude management events for a specific IAM identity](#)

- [Logging management events with the AWS SDKs](#)

Management events

Management events provide visibility into management operations that are performed on resources in your AWS account. These are also known as control plane operations. Example management events include:

- Configuring security (for example, IAM AttachRolePolicy API operations)
- Registering devices (for example, Amazon EC2 CreateDefaultVpc API operations)
- Configuring rules for routing data (for example, Amazon EC2 CreateSubnet API operations)
- Setting up logging (for example, AWS CloudTrail CreateTrail API operations)

Management events can also include non-API events that occur in your account. For example, when a user logs in to your account, CloudTrail logs the ConsoleLogin event. For more information, see [Non-API events captured by CloudTrail](#).

By default, trails and event data stores are configured to log management events.

Note

The CloudTrail **Event history** feature supports only management events. You cannot exclude AWS KMS or Amazon RDS Data API events from **Event history**; settings that you apply to a trail or event data store do not apply to **Event history**. For more information, see [Working with CloudTrail event history](#).

Read and write events

When you configure your trail or event data store to log management events, you can specify whether you want read-only events, write-only events, or both.

- **Read**

Read-only events include API operations that read your resources, but don't make changes. For example, read-only events include the Amazon EC2 DescribeSecurityGroups and

DescribeSubnets API operations. These operations return only information about your Amazon EC2 resources and don't change your configurations.

- **Write**

Write-only events include API operations that modify (or might modify) your resources. For example, the Amazon EC2 RunInstances and TerminateInstances API operations modify your instances.

Example: Logging read and write events for separate trails

The following example shows how you can configure trails to split log activity for an account into separate S3 buckets: one bucket receives read-only events and a second bucket receives write-only events.

1. You create a trail and choose an S3 bucket named `amzn-s3-demo-bucket1` to receive log files. You then update the trail to specify that you want **Read** management events.
2. You create a second trail and choose an S3 bucket named `amzn-s3-demo-bucket2` to receive log files. You then update the trail to specify that you want **Write** management events.
3. The Amazon EC2 DescribeInstances and TerminateInstances API operations occur in your account.
4. The DescribeInstances API operation is a read-only event and it matches the settings for the first trail. The trail logs and delivers the event to `amzn-s3-demo-bucket1`.
5. The TerminateInstances API operation is a write-only event and it matches the settings for the second trail. The trail logs and delivers the event to `amzn-s3-demo-bucket2`.

Logging management events with the AWS Management Console

This section describes how to update the management event settings for an existing trail or event data store.

Topics

- [Updating the management event settings for an existing trail](#)
- [Updating the management event settings for an existing event data store](#)

Updating the management event settings for an existing trail

Use the following procedure to update the management event settings for an existing trail.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. Open the **Trails** page of the CloudTrail console and choose the trail name.
3. For **Management events**, choose **Edit**.
 - Choose if you want to log **Read** events, **Write** events, or both.
 - Choose **Exclude AWS KMS events** to filter AWS Key Management Service (AWS KMS) events out of your trail. The default setting is to include all AWS KMS events.

The option to log or exclude AWS KMS events is available only if you log management events on your trail. If you choose not to log management events, AWS KMS events are not logged, and you cannot change AWS KMS event logging settings.

AWS KMS actions such as `Encrypt`, `Decrypt`, and `GenerateDataKey` typically generate a large volume (more than 99%) of events. These actions are now logged as **Read** events. Low-volume, relevant AWS KMS actions such as `Disable`, `Delete`, and `ScheduleKey` (which typically account for less than 0.5% of AWS KMS event volume) are logged as **Write** events.

To exclude high-volume events like `Encrypt`, `Decrypt`, and `GenerateDataKey`, but still log relevant events such as `Disable`, `Delete` and `ScheduleKey`, choose to log **Write** management events, and clear the check box for **Exclude AWS KMS events**.

- Choose **Exclude Amazon RDS Data API events** to filter Amazon Relational Database Service Data API events out of your trail. The default setting is to include all Amazon RDS Data API events. For more information about Amazon RDS Data API events, see [Logging Data API calls with AWS CloudTrail](#) in the *Amazon RDS User Guide for Aurora*.
4. Choose **Save changes** when you are finished.

Updating the management event settings for an existing event data store

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.

2. Open the **Event data stores** page of the CloudTrail console and choose the event data store name.
3. For **Management events**, choose **Edit** and then configure the following settings:
 - a. Choose between **Simple event collection** or **Advanced event collection**:
 - Choose **Simple event collection** if you want to log all events, log only read events, or log only write events. You can choose also to exclude AWS Key Management Service and Amazon RDS Data API management events.
 - Choose **Advanced event collection** if you want to include or exclude management events based on the values of advanced event selector fields, including the `eventName`, `eventType`, `eventSource`, and `userIdentity.arn` fields.
 - b. If you selected **Simple event collection**, choose whether you want to log all events, log only read events, or log only write events. You can also choose to exclude AWS KMS and Amazon RDS management events.
 - c. If you selected **Advanced event collection**, make the following selections:
 - i. In **Log selector template**, choose a predefined template, or **Custom** to build a custom configuration based on advanced event selector field values.

You can choose from the following predefined templates:

- **Log all events** – Choose this template to log all events.
 - **Log only read events** – Choose this template to log only read events. Read-only events are events that do not change the state of a resource, such as `Get*` or `Describe*` events.
 - **Log only write events** – Choose this template to log only write events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events.
 - **Log only AWS Management Console events** – Choose this template to log only events originating from the AWS Management Console.
 - **Exclude AWS service initiated events** – Choose this template to exclude AWS service events, which have an `eventType` of `AwsServiceEvent`, and events initiated with AWS service-linked roles (SLRs).
- ii. (Optional) In **Selector name**, enter a name to identify your selector. The selector name is a descriptive name for an advanced event selector, such as "Log management

events from AWS Management Console sessions". The selector name is listed as Name in the advanced event selector and is viewable if you expand the **JSON view**.

- iii. If you chose **Custom**, in **Advanced event selectors** build an expression based on advanced event selector field values.

 Note

Selectors don't support the use of wildcards like `*`. To match multiple values with a single condition, you may use `StartsWith`, `EndsWith`, `NotStartsWith`, or `NotEndsWith` to explicitly match the beginning or end of the event field.

A. Choose from the following fields.

- **readOnly** – `readOnly` can be set to **equals** a value of `true` or `false`. When it is set to `false`, the event data store logs Write-only management events. Read-only management events are events that do not change the state of a resource, such as `Get*` or `Describe*` events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events. To log both **Read** and **Write** events, don't add a `readOnly` selector.
- **eventName** – `eventName` can use any operator. You can use it to include or exclude any management event, such as `CreateAccessPoint` or `GetAccessPoint`.
- **userIdentity.arn** – Include or exclude events for actions taken by specific IAM identities. For more information, see [CloudTrail userIdentity element](#).
- **sessionCredentialFromConsole** – Include or exclude events originating from an AWS Management Console session. This field can be set to **equals** or **not equals** with a value of `true`.
- **eventSource** – You can use it to include or exclude specific event sources. The `eventSource` is typically a short form of the service name without spaces plus `.amazonaws.com`. For example, you could set `eventSource` **equals** to `ec2.amazonaws.com` to log only Amazon EC2 management events.
- **eventType** – The [eventType](#) to include or exclude. For example, you can set this field to **not equals** `AwsServiceEvent` to exclude [AWS service events](#).

- B. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions.

For information about how CloudTrail evaluates multiple conditions, see [How CloudTrail evaluates multiple conditions for a field](#).

 Note

You can have a maximum of 500 values for all selectors on an event data store. This includes arrays of multiple values for a selector such as `eventName`. If you have single values for all selectors, you can have a maximum of 500 conditions added to a selector.

- C. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields.
- iv. Optionally, expand **JSON view** to see your advanced event selectors as a JSON block.
- d. Choose **Enable Insights events capture** to enable Insights. To enable Insights, you need to set up a [destination event data store](#) to collect Insights events based upon the management event activity in this event data store.

If you choose to enable Insights, do the following.

- i. Choose the destination event store that will log Insights events. The destination event data store will collect Insights events based upon the management event activity in this event data store. For information about how to create the destination event data store, see [To create a destination event data store that logs Insights events](#).
- ii. Choose the Insights types. You can choose **API call rate**, **API error rate**, or both. You must be logging **Write** management events to log Insights events for **API call rate**. You must be logging **Read** or **Write** management events to log Insights events for **API error rate**.

- 4. Choose **Save changes** when you are finished.

Logging management events with the AWS CLI

You can configure your trails or event data stores to log management events using the AWS CLI.

Topics

- [Examples: Logging management events for trails](#)
- [Examples: Logging management events for event data stores](#)

Examples: Logging management events for trails

To view whether your trail is logging management events, run the `get-event-selectors` command.

```
aws cloudtrail get-event-selectors --trail-name TrailName
```

The following example returns the default settings for a trail. By default, trails log all management events, log events from all event sources, and don't log data events.

```
{
  "TrailARN": "arn:aws:cloudtrail:us-east-1:111122223333:trail/TrailName",
  "AdvancedEventSelectors": [
    {
      "Name": "Management events selector",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        }
      ]
    }
  ]
}
```

You can use either basic or advanced event selectors to log management events. You cannot apply both event selectors and advanced event selectors to a trail. If you apply advanced event selectors to a trail, any existing basic event selectors are overwritten. The following sections provide examples of how to log management events using advanced event selectors and basic event selectors.

Topics

- [Examples: Logging management events for trails using advanced event selectors](#)
- [Examples: Logging management events for trails using basic event selectors](#)

Examples: Logging management events for trails using advanced event selectors

The following example creates an advanced event selector for a trail named *TrailName* to include read-only and write-only management events (by omitting the `readOnly` selector), but to exclude AWS Key Management Service (AWS KMS) events. Because AWS KMS events are treated as management events, and there can be a high volume of them, they can have a substantial impact on your CloudTrail bill if you have more than one trail that captures management events.

If you choose not to log management events, AWS KMS events are not logged, and you cannot change AWS KMS event logging settings.

To start logging AWS KMS events to a trail again, remove the `eventSource` selector, and run the command again.

```
aws cloudtrail put-event-selectors --trail-name TrailName \
--advanced-event-selectors '[
  {
    "Name": "Log all management events except KMS events",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Management"] },
      { "Field": "eventSource", "NotEquals": ["kms.amazonaws.com"] }
    ]
  }
]'
```

The example returns the advanced event selectors that are configured for the trail.

```
{
  "AdvancedEventSelectors": [
    {
      "Name": "Log all management events except KMS events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [ "Management" ]
        },
        {
          "Field": "eventSource",
          "NotEquals": [ "kms.amazonaws.com" ]
        }
      ]
    }
  ]
}
```



```
    }
  ],
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName"
}
```

To start logging excluded events to a trail again, remove the `eventSource` selector, as shown in the following command.

```
aws cloudtrail put-event-selectors --trail-name TrailName \
--advanced-event-selectors '
[
  {
    "Name": "Log all management events",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Management"] }
    ]
  }
]'
```

The next example creates an advanced event selector for a trail named *TrailName* to include read-only and write-only management events (by omitting the `readOnly` selector), but to exclude Amazon RDS Data API management events. To exclude Amazon RDS Data API management events, specify the Amazon RDS Data API event source in the string value for the `eventSource` field: `rdodata.amazonaws.com`.

If you choose not to log management events, Amazon RDS Data API management events are not logged, and you cannot change Amazon RDS Data API event logging settings.

To start logging Amazon RDS Data API management events to a trail again, remove the `eventSource` selector, and run the command again.

```
aws cloudtrail put-event-selectors --trail-name TrailName \
--advanced-event-selectors '
[
  {
    "Name": "Log all management events except Amazon RDS Data API management events",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Management"] },
      { "Field": "eventSource", "NotEquals": ["rdodata.amazonaws.com"] }
    ]
  }
]
```

```
]'
```

The example returns the advanced event selectors that are configured for the trail.

```
{
  "AdvancedEventSelectors": [
    {
      "Name": "Log all management events except Amazon RDS Data API management events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [ "Management" ]
        },
        {
          "Field": "eventSource",
          "NotEquals": [ "rdsdata.amazonaws.com" ]
        }
      ]
    }
  ],
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName"
}
```

To start logging excluded events to a trail again, remove the eventSource selector, as shown in the following command.

```
aws cloudtrail put-event-selectors --trail-name TrailName \
--advanced-event-selectors '
[
  {
    "Name": "Log all management events",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Management"] }
    ]
  }
]'
```

Examples: Logging management events for trails using basic event selectors

To configure your trail to log management events, run the `put-event-selectors` command. The following example shows how to configure your trail to include all management events for two S3

objects. You can specify from 1 to 5 event selectors for a trail. You can specify from 1 to 250 data resources for a trail.

Note

The maximum number of S3 data resources is 250, regardless of the number of event selectors.

```
aws cloudtrail put-event-selectors --trail-name TrailName --event-selectors
'[{ "ReadWriteType": "All", "IncludeManagementEvents":true, "DataResources":
[{ "Type": "AWS::S3::Object", "Values": ["arn:aws:s3:::amzn-s3-demo-bucket/prefix",
"arn:aws:s3:::amzn-s3-demo-bucket2/prefix2"] }] }]'
```

The following example returns the event selector configured for the trail.

```
{
  "TrailARN": "arn:aws:cloudtrail:us-east-1:111122223333:trail/TrailName",
  "EventSelectors": [
    {
      "ReadWriteType": "All",
      "IncludeManagementEvents": true,
      "DataResources": [
        {
          "Type": "AWS::S3::Object",
          "Values": [
            "arn:aws:s3:::amzn-s3-demo-bucket/prefix",
            "arn:aws:s3:::amzn-s3-demo-bucket2/prefix2",
          ]
        }
      ]
    },
    "ExcludeManagementEventSources": []
  ]
}
```

To exclude AWS Key Management Service (AWS KMS) events from a trail's logs, run the `put-event-selectors` command and add the attribute `ExcludeManagementEventSources` with a value of `kms.amazonaws.com`. The following example creates an event selector for a trail named *TrailName* to include read-only and write-only management events, but exclude AWS KMS

events. Because AWS KMS can generate a high volume of events, the user in this example might want to limit events to manage the cost of a trail.

```
aws cloudtrail put-event-selectors --trail-name TrailName --event-selectors '[{"ReadWriteType": "All", "ExcludeManagementEventSources": ["kms.amazonaws.com"], "IncludeManagementEvents": true}]'
```

The example returns the event selector configured for the trail.

```
{
  "TrailARN": "arn:aws:cloudtrail:us-east-1:111122223333:trail/TrailName",
  "EventSelectors": [
    {
      "ReadWriteType": "All",
      "IncludeManagementEvents": true,
      "DataResources": [],
      "ExcludeManagementEventSources": [
        "kms.amazonaws.com"
      ]
    }
  ]
}
```

To exclude Amazon RDS Data API management events from a trail's logs, run the `put-event-selectors` command and add the attribute `ExcludeManagementEventSources` with a value of `rdsvdata.amazonaws.com`. The following example creates an event selector for a trail named *TrailName* to include read-only and write-only management events, but exclude Amazon RDS Data API management events. Because Amazon RDS Data API can generate a high volume of management events, the user in this example might want to limit events to manage the cost of a trail.

```
{
  "TrailARN": "arn:aws:cloudtrail:us-east-1:111122223333:trail/TrailName",
  "EventSelectors": [
    {
      "ReadWriteType": "All",
      "IncludeManagementEvents": true,
      "DataResources": [],
      "ExcludeManagementEventSources": [
        "rdsvdata.amazonaws.com"
      ]
    }
  ]
}
```

```
    }  
  ]  
}
```

To start logging AWS KMS or Amazon RDS Data API management events to a trail again, pass an empty string as the value of `ExcludeManagementEventSources`, as shown in the following command.

```
aws cloudtrail put-event-selectors --trail-name TrailName --event-  
selectors '[{"ReadWriteType": "All","ExcludeManagementEventSources":  
[],"IncludeManagementEvents": true}]'
```

To log relevant AWS KMS events to a trail like `Disable`, `Delete` and `ScheduleKey`, but exclude high-volume AWS KMS events like `Encrypt`, `Decrypt`, and `GenerateDataKey`, log write-only management events, and keep the default setting to log AWS KMS events, as shown in the following example.

```
aws cloudtrail put-event-selectors --trail-name TrailName --event-  
selectors '[{"ReadWriteType": "WriteOnly","ExcludeManagementEventSources":  
[],"IncludeManagementEvents": true}]'
```

Examples: Logging management events for event data stores

You log management events for event data stores by configuring advanced event selectors.

The following advanced event selector fields are supported for logging management events on event data stores:

- **eventCategory** – You must set `eventCategory` equal to `Management` to log management events. This is a required field.
- **readOnly** – `readOnly` can be set to `Equals` a value of `true` or `false`. When it is set to `false`, the event data store logs Write-only management events. Read-only management events are events that do not change the state of a resource, such as `Get*` or `Describe*` events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events. To log both **Read** and **Write** events, don't add a `readOnly` selector.
- **eventName** – `eventName` can use any operator. You can use it to include or exclude any management event, such as `CreateAccessPoint` or `GetAccessPoint`. You can use any operator with this field.

- **userIdentity.arn** – Include or exclude events for actions taken by specific IAM identities. For more information, see [CloudTrail userIdentity element](#).
- **sessionCredentialFromConsole** – Include or exclude events originating from an AWS Management Console session. This field can be set to **Equals** or **NotEquals** with a value of `true`.
- **eventSource** – You can use it to include or exclude specific event sources. The `eventSource` is typically a short form of the service name without spaces plus `.amazonaws.com`. For example, you could set `eventSource Equals` to `ec2.amazonaws.com` to log only Amazon EC2 management events.
- **eventType** – The [eventType](#) to include or exclude. For example, you can set this field to `NotEquals AwsServiceEvent` to exclude [AWS service events](#). You can use any operator with this field.

To view whether your event data store includes management events, run the **get-event-data-store** command.

```
aws cloudtrail get-event-data-store
--event-data-store arn:aws:cloudtrail:us-east-1:12345678910:eventdatastore/EXAMPLE-
f852-4e8f-8bd1-bcf6cEXAMPLE
```

The following is an example response. Creation and last updated times are in `timestamp` format.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:12345678910:eventdatastore/
EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE",
  "Name": "myManagementEvents",
  "Status": "ENABLED",
  "AdvancedEventSelectors": [
    {
      "Name": "Management events selector",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        }
      ]
    }
  ]
}
```

```
],
"MultiRegionEnabled": true,
"OrganizationEnabled": false,
"BillingMode": "FIXED_RETENTION_PRICING",
"RetentionPeriod": 2557,
"TerminationProtectionEnabled": true,
"CreatedTimestamp": "2023-02-04T15:56:27.418000+00:00",
"UpdatedTimestamp": "2023-02-04T15:56:27.544000+00:00"
}
```

To create an event data store that includes all management events, you run the **create-event-data-store** command. You do not need to specify any advanced event selectors to include all management events.

```
aws cloudtrail create-event-data-store
--name my-event-data-store
--retention-period 90\
```

The following is an example response.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:12345678910:eventdatastore/EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE",
  "Name": "my-event-data-store",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Default management events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": true,
  "OrganizationEnabled": false,
  "BillingMode": "EXTENDABLE_RETENTION_PRICING",
  "RetentionPeriod": 90,
```

```

    "TerminationProtectionEnabled": true,
    "CreatedTimestamp": "2023-11-13T16:41:57.224000+00:00",
    "UpdatedTimestamp": "2023-11-13T16:41:57.357000+00:00"
  }

```

Examples:

- [Example: Exclude AWS KMS management events](#)
- [Example: Exclude Amazon RDS management events](#)
- [Example: Exclude AWS service events and events from AWS Management Console sessions](#)
- [Example: Exclude management events for a specific IAM identity](#)

Example: Exclude AWS KMS management events

To create an event data store that excludes AWS Key Management Service (AWS KMS) events, run the `create-event-data-store` command and specify that `eventSource` does not equal `kms.amazonaws.com`. The following example creates an event data store that includes read-only and write-only management events, but excludes AWS KMS events.

```

aws cloudtrail create-event-data-store --name event-data-store-name --retention-period
90 --advanced-event-selectors '[
  {
    "Name": "Management events selector",
    "FieldSelectors": [
      {"Field": "eventCategory", "Equals": ["Management"]},
      {"Field": "eventSource", "NotEquals": ["kms.amazonaws.com"]}
    ]
  }
]'

```

The following is an example response.

```

{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:12345678910:eventdatastore/
EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE",
  "Name": "event-data-store-name",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Management events selector",

```



```

        "FieldSelectors": [
            {
                "Field": "eventCategory",
                "Equals": [
                    "Management"
                ]
            },
            {
                "Field": "eventSource",
                "NotEquals": [
                    "kms.amazonaws.com"
                ]
            }
        ]
    },
    "MultiRegionEnabled": true,
    "OrganizationEnabled": false,
    "BillingMode": "EXTENDABLE_RETENTION_PRICING",
    "RetentionPeriod": 90,
    "TerminationProtectionEnabled": true,
    "CreatedTimestamp": "2023-11-13T17:02:02.067000+00:00",
    "UpdatedTimestamp": "2023-11-13T17:02:02.241000+00:00"
}

```

Example: Exclude Amazon RDS management events

To create an event data store that excludes Amazon RDS Data API management events, run the `create-event-data-store` command and specify that `eventSource` does not equal `rdsvdata.amazonaws.com`. The following example creates an event data store that includes read-only and write-only management events, but excludes Amazon RDS Data API events.

```

aws cloudtrail create-event-data-store --name event-data-store-name --retention-period
90 --advanced-event-selectors '[
    {
        "Name": "Management events selector",
        "FieldSelectors": [
            {"Field": "eventCategory", "Equals": ["Management"]},
            {"Field": "eventSource", "NotEquals": ["rdsvdata.amazonaws.com"]}
        ]
    }
]'

```

The following is an example response.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:12345678910:eventdatastore/
EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE",
  "Name": "my-event-data-store",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Management events selector",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        },
        {
          "Field": "eventSource",
          "NotEquals": [
            "rdsdata.amazonaws.com"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": true,
  "OrganizationEnabled": false,
  "BillingMode": "EXTENDABLE_RETENTION_PRICING",
  "RetentionPeriod": 90,
  "TerminationProtectionEnabled": true,
  "CreatedTimestamp": "2023-11-13T17:02:02.067000+00:00",
  "UpdatedTimestamp": "2023-11-13T17:02:02.241000+00:00"
}
```

Example: Exclude AWS service events and events from AWS Management Console sessions

The following example creates an event data store that logs management events but excludes AWS service events and events originating from AWS Management Console sessions.

```
aws cloudtrail create-event-data-store --name event-data-store-name --advanced-event-
selectors '[
  {
```

```

    "Name": "Exclude AWS service and console events",
    "FieldSelectors": [
      {"Field": "eventCategory", "Equals": ["Management"]},
      {"Field": "eventType", "NotEquals": ["AwsServiceEvent"]},
      {"Field": "sessionCredentialFromConsole", "NotEquals": ["true"]}
    ]
  }
]'

```

The following is an example response.

```

{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:12345678910:eventdatastore/
EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE",
  "Name": "event-data-store-name",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Exclude AWS service and console events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        },
        {
          "Field": "eventType",
          "NotEquals": [
            "AwsServiceEvent"
          ]
        },
        {
          "Field": "sessionCredentialFromConsole",
          "NotEquals": [
            "true"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": true,
  "OrganizationEnabled": false,

```

```

    "BillingMode": "EXTENDABLE_RETENTION_PRICING",
    "RetentionPeriod": 366,
    "TerminationProtectionEnabled": true,
    "CreatedTimestamp": "2024-11-13T17:02:02.067000+00:00",
    "UpdatedTimestamp": "2024-11-13T17:02:02.241000+00:00"
  }

```

Example: Exclude management events for a specific IAM identity

The following example creates an event data store that logs management events but excludes events generated by the bucket-scanner-role userIdentity.

```

aws cloudtrail create-event-data-store --name event-data-store-name --advanced-event-
selectors '[
  {
    "Name": "Exclude events generated by bucket-scanner-role userIdentity",
    "FieldSelectors": [
      {"Field": "eventCategory", "Equals": ["Management"]},
      {"Field": "userIdentity.arn", "NotStartsWith":
["arn:aws:sts::123456789012:assumed-role/bucket-scanner-role"]}
    ]
  }
]'

```

The following is an example response.

```

{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/
EXAMPLE-f852-4e8f-8bd1-bcf6cEXAMPLE",
  "Name": "event-data-store-name",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Exclude events generated by bucket-scanner-role userIdentity",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        },
        {
          "Field": "userIdentity.arn",

```

```
        "NotStartsWith": [
            "arn:aws:sts::123456789012:assumed-role/bucket-scanner-role"
        ]
    }
],
"MultiRegionEnabled": true,
"OrganizationEnabled": false,
"BillingMode": "EXTENDABLE_RETENTION_PRICING",
"RetentionPeriod": 366,
"TerminationProtectionEnabled": true,
"CreatedTimestamp": "2024-11-13T17:02:02.067000+00:00",
"UpdatedTimestamp": "2024-11-13T17:02:02.241000+00:00"
}
```

Logging management events with the AWS SDKs

Use the [GetEventSelectors](#) operation to see whether your trail is logging management events for a trail. You can configure your trails to log management events with the [PutEventSelectors](#) operation. For more information, see the [AWS CloudTrail API Reference](#).

Run the [GetEventDataStore](#) operation to see whether your event data store includes management events. You can configure your event data stores to include management events by running the [CreateEventDataStore](#) or [UpdateEventDataStore](#) operations. For more information, see [Create, update, and manage event data stores with the AWS CLI](#) and the [AWS CloudTrail API Reference](#).

Logging data events

This section describes how to log data events using the [CloudTrail console](#) and [AWS CLI](#).

By default, trails and event data stores do not log data events. Additional charges apply for data events. For more information, see [AWS CloudTrail Pricing](#).

Data events provide information about the resource operations performed on or in a resource. These are also known as *data plane operations*. Data events are often high-volume activities.

Example data events include:

- [Amazon S3 object-level API activity](#) (for example, `GetObject`, `DeleteObject`, and `PutObject` API operations) on objects in S3 buckets.

- AWS Lambda function execution activity (the Invoke API).
- CloudTrail [PutAuditEvents](#) activity on a [CloudTrail Lake channel](#) that is used to log events from outside AWS.
- Amazon SNS [Publish](#) and [PublishBatch](#) API operations on topics.

You can use advanced event selectors to create fine-grained selectors, which help you control costs by only logging the specific events of interest for your use cases. For example, you can use advanced event selectors to log specific API calls by adding a filter on the eventName field. For more information, see [Filtering data events by using advanced event selectors](#).

Note

The events that are logged by your trails are available in Amazon EventBridge. For example, if you choose to log data events for S3 objects but not management events, your trail processes and logs only data events for the specified S3 objects. The data events for these S3 objects are available in Amazon EventBridge. For more information, see [AWS service events delivered via CloudTrail](#) in the *Amazon EventBridge User Guide* and the [AWS Events Reference](#).

Contents

- [Data events](#)
 - [Data events supported by AWS CloudTrail](#)
 - [Examples: Logging data events for Amazon S3 objects](#)
 - [Logging data events for S3 objects in other AWS accounts](#)
- [Read-only and write-only events](#)
- [Logging data events with the AWS Management Console](#)
- [Logging data events with the AWS Command Line Interface](#)
 - [Logging data events for trails with the AWS CLI](#)
 - [Log data events for trails by using advanced event selectors](#)
 - [Log all Amazon S3 events for an Amazon S3 bucket by using advanced event selectors](#)
 - [Log Amazon S3 on AWS Outposts events by using advanced event selectors](#)
 - [Log events by using basic event selectors](#)
- [Logging data events for event data stores with the AWS CLI](#)

- [Include all Amazon S3 events for a specific bucket](#)
- [Include Amazon S3 on AWS Outposts events](#)
- [Filtering data events by using advanced event selectors](#)
 - [How CloudTrail evaluates multiple conditions for a field](#)
 - [Example showing multiple conditions for the resources.ARN field](#)
- [AWS CLI examples for filtering data events](#)
 - [Example 1: Filtering on the eventName field](#)
 - [Example 2: Filtering on the resources.ARN and userIdentity.arn fields](#)
 - [Example 3: Filtering on the resources.type and eventName fields to exclude individual objects deleted by an Amazon S3 DeleteObjects event](#)
- [Logging data events for AWS Config compliance](#)
- [Logging data events with the AWS SDKs](#)

Data events

The following table shows the resource types available for trails and event data stores.

The **Resource type (console)** column shows the appropriate selection in the console. The **resources.type value** column shows the `resources.type` value that you would specify to include data events of that type in your trail or event data store using the AWS CLI or CloudTrail APIs.

For trails, you can use basic or advanced event selectors to log data events for Amazon S3 objects in general purpose buckets, Lambda functions, and DynamoDB tables (shown in the first three rows of the table). You can use only advanced event selectors to log the resource types shown in the remaining rows.

For event data stores, you can use only advanced event selectors to include data events.

Data events supported by AWS CloudTrail

AWS service	Description	Resource type (console)	resources.type value
Amazon RDS	Amazon RDS API activity on a DB Cluster.	RDS Data API - DB Cluster	AWS::RDS::DBCluster
Amazon S3	Amazon S3 object-level API activity (for example, GetObject , DeleteObject , and PutObject API operations) on objects in general purpose buckets.	S3	AWS::S3::Object
Amazon S3	Amazon S3 API activity on access points.	S3 Access Point	AWS::S3::AccessPoint
Amazon S3	Amazon S3 object-level API activity (for example, GetObject , DeleteObject , and PutObject API operations) on objects in directory buckets.	S3 Express	AWS::S3Express::Object
Amazon S3	Amazon S3 Object Lambda access points API activity , such as calls to CompleteM	S3 Object Lambda	AWS::S3ObjectLambda::Access Point

AWS service	Description	Resource type (console)	resources.type value
	multipartUpload and GetObject .		
Amazon S3	Amazon FSx API activity on volumes.	FSx Volume	AWS::FSx::Volume
Amazon S3 Tables	Amazon S3 API activity on tables .	S3 table	AWS::S3Tables::Table
Amazon S3 Tables	Amazon S3 API activity on table buckets .	S3 table bucket	AWS::S3Tables::TableBucket
Amazon S3 Vectors	Amazon S3 API activity on vector buckets .	S3 vector bucket	AWS::S3Vectors::VectorBucket
Amazon S3 Vectors	Amazon S3 API activity on vector indexes .	S3 vector index	AWS::S3Vectors::Index
Amazon S3 on Outposts	Amazon S3 on Outposts object-level API activity .	S3 Outposts	AWS::S3Outposts::Object
Amazon SNS	Amazon SNS Publish API operations on platform endpoints.	SNS platform endpoint	AWS::SNS::PlatformEndpoint
Amazon SNS	Amazon SNS Publish and PublishBatch API operations on topics.	SNS topic	AWS::SNS::Topic

AWS service	Description	Resource type (console)	resources.type value
Amazon SQS	Amazon SQS API activity on messages.	SQS	AWS::SQS::Queue
AWS Supply Chain	AWS Supply Chain API activity on an instance.	Supply Chain	AWS::SCN::Instance
Amazon SWF	Amazon SWF API activity on domains .	SWF domain	AWS::SWF::Domain
AWS AppConfig	AWS AppConfig API activity for configuration operations such as calls to StartConfigurationSession and GetLatestConfiguration .	AWS AppConfig	AWS::AppConfig::Configuration
AWS AppSync	AWS AppSync API activity on AppSync GraphQL APIs.	AppSync GraphQL	AWS::AppSync::GraphQLApi
Amazon Aurora DSQL	Amazon Aurora DSQL API activity on cluster resources.	Amazon Aurora DSQL	AWS::DSQL::Cluster

AWS service	Description	Resource type (console)	resources.type value
AWS B2B Data Interchange	B2B Data Interchange API activity for Transformer operations such as calls to <code>GetTransformerJob</code> and <code>StartTransformerJob</code> .	B2B Data Interchange	<code>AWS::B2BI::Transformer</code>
AWS Backup	AWS Backup Search Data API activity on search jobs.	AWS Backup Search Data APIs	<code>AWS::Backup::SearchJob</code>
Amazon Bedrock	Amazon Bedrock API activity on an agent alias.	Bedrock agent alias	<code>AWS::Bedrock::AgentAlias</code>
Amazon Bedrock	Amazon Bedrock API activity on async invocations.	Bedrock async invoke	<code>AWS::Bedrock::AsyncInvoke</code>
Amazon Bedrock	Amazon Bedrock API activity on a flow alias.	Bedrock flow alias	<code>AWS::Bedrock::FlowAlias</code>
Amazon Bedrock	Amazon Bedrock API activity on guardrails.	Bedrock guardrail	<code>AWS::Bedrock::Guardrail</code>
Amazon Bedrock	Amazon Bedrock API activity on inline agents.	Bedrock Invoke Inline-Agent	<code>AWS::Bedrock::InlineAgent</code>

AWS service	Description	Resource type (console)	resources.type value
Amazon Bedrock	Amazon Bedrock API activity on a knowledge base.	Bedrock knowledge base	AWS::Bedrock::KnowledgeBase
Amazon Bedrock	Amazon Bedrock API activity on models.	Bedrock model	AWS::Bedrock::Model
Amazon Bedrock	Amazon Bedrock API activity on prompts.	Bedrock prompt	AWS::Bedrock::PromptVersion
Amazon Bedrock	Amazon Bedrock API activity on sessions.	Bedrock session	AWS::Bedrock::Session
Amazon Bedrock	Amazon Bedrock API activity on flow executions.	Bedrock flow execution	AWS::Bedrock::FlowExecution
Amazon Bedrock	Amazon Bedrock API activity on an automated reasoning policy.	Bedrock automated reasoning policy	AWS::Bedrock::AutomatedReasoningPolicy
Amazon Bedrock	Amazon Bedrock API activity on an automated reasoning policy version.	Bedrock automated reasoning policy version	AWS::Bedrock::AutomatedReasoningPolicyVersion
Amazon Bedrock	Amazon Bedrock data automation project API activity.	Bedrock Data Automation project	AWS::Bedrock::DataAutomationProject

AWS service	Description	Resource type (console)	resources.type value
Amazon Bedrock	Bedrock data automation invocation API activity.	Bedrock Data Automation invocation	AWS::Bedrock::DataAutomationInvocation
Amazon Bedrock	Amazon Bedrock data automation profile API activity.	Bedrock Data Automation profile	AWS::Bedrock::DataAutomationProfile
Amazon Bedrock	Amazon Bedrock blueprint API activity.	Bedrock blueprint	AWS::Bedrock::Blueprint
Amazon Bedrock	Amazon Bedrock Code-Interpreter API activity.	Bedrock-AgentCore Code-Interpreter	AWS::BedrockAgentCore::CodeInterpreter
Amazon Bedrock	Amazon Bedrock Browser API activity.	Bedrock-AgentCore Browser	AWS::BedrockAgentCore::Browser
Amazon Bedrock	Amazon Bedrock Workload Identity API activity.	Bedrock-AgentCore Workload Identity	AWS::BedrockAgentCore::WorkloadIdentity
Amazon Bedrock	Amazon Bedrock Workload Identity Directory API activity.	Bedrock-AgentCore Workload Identity Directory	AWS::BedrockAgentCore::WorkloadIdentityDirectory

AWS service	Description	Resource type (console)	resources.type value
Amazon Bedrock	Amazon Bedrock Token Vault API activity.	Bedrock-AgentCore Token Vault	AWS::BedrockAgentCore::TokenVault
Amazon Bedrock	Amazon Bedrock APIKey CredentialProvider API activity.	Bedrock-AgentCore APIKey CredentialProvider	AWS::BedrockAgentCore::APIKeyCredentialProvider
Amazon Bedrock	Amazon Bedrock Runtime API activity.	Bedrock-AgentCore Runtime	AWS::BedrockAgentCore::Runtime
Amazon Bedrock	Amazon Bedrock Runtime-Endpoint API activity.	Bedrock-AgentCore Runtime-Endpoint	AWS::BedrockAgentCore::RuntimeEndpoint
Amazon Bedrock	Amazon Bedrock Gateway API activity.	Bedrock-AgentCore Gateway	AWS::BedrockAgentCore::Gateway
Amazon Bedrock	Amazon Bedrock Memory API activity.	Bedrock-AgentCore Memory	AWS::BedrockAgentCore::Memory
Amazon Bedrock	Amazon Bedrock OAuth2 CredentialProvider API activity.	Bedrock-AgentCore OAuth2 CredentialProvider	AWS::BedrockAgentCore::OAuth2CredentialProvider

AWS service	Description	Resource type (console)	resources.type value
Amazon Bedrock	Amazon Bedrock Browser-Custom API activity.	Bedrock-AgentCore-Browser-Custom	AWS::BedrockAgentCore::BrowserCustom
Amazon Bedrock	Amazon Bedrock Code-Interpreter-Custom API activity.	Bedrock-AgentCore-Code-Interpreter-Custom	AWS::BedrockAgentCore::CodeInterpreterCustom
Amazon Bedrock	Amazon Bedrock Tool API activity.	Bedrock Tool	AWS::Bedrock::Tool
AWS Cloud Map	AWS Cloud Map API activity on a namespace .	AWS Cloud Map namespace	AWS::ServiceDiscovery::Namespace
AWS Cloud Map	AWS Cloud Map API activity on a service .	AWS Cloud Map service	AWS::ServiceDiscovery::Service
Amazon CloudFront	CloudFront API activity on a KeyValueStore .	CloudFront KeyValueStore	AWS::CloudFront::KeyValueStore
AWS CloudTrail	CloudTrail PutAuditEvents activity on a CloudTrail Lake channel that is used to log events from outside AWS.	CloudTrail channel	AWS::CloudTrail::Channel

AWS service	Description	Resource type (console)	resources.type value
Amazon CloudWatch	Amazon CloudWatch API activity on metrics.	CloudWatch metric	AWS::CloudWatch::Metric
Amazon CloudWatch Network Flow Monitor	Amazon CloudWatch Network Flow Monitor API activity on monitors.	Network Flow Monitor monitor	AWS::NetworkFlowMonitor::Monitor
Amazon CloudWatch Network Flow Monitor	Amazon CloudWatch Network Flow Monitor API activity on scopes.	Network Flow Monitor scope	AWS::NetworkFlowMonitor::Scope
Amazon CloudWatch RUM	Amazon CloudWatch RUM API activity on app monitors.	RUM app monitor	AWS::RUM::AppMonitor
Amazon CodeGuru Profiler	CodeGuru Profiler API activity on profiling groups.	CodeGuru Profiler profiling group	AWS::CodeGuruProfiler::ProfilingGroup
Amazon CodeWhisperer	Amazon CodeWhisperer API activity on a customization.	CodeWhisperer customization	AWS::CodeWhisperer::Customization
Amazon CodeWhisperer	Amazon CodeWhisperer API activity on a profile.	CodeWhisperer	AWS::CodeWhisperer::Profile

AWS service	Description	Resource type (console)	resources.type value
Amazon Cognito	Amazon Cognito API activity on Amazon Cognito identity pools .	Cognito Identity Pools	AWS::Cognito::IdentityPool
AWS Data Exchange	AWS Data Exchange API activity on assets.	Data Exchange asset	AWS::DataExchange::Asset
Amazon Data Firehose	Amazon Data Firehose delivery stream API activity.	Amazon Data Firehose	AWS::KinesisFirehose::DeliveryStream
AWS Deadline Cloud	Deadline Cloud API activity on fleets.	Deadline Cloud fleet	AWS::Deadline::Fleet
AWS Deadline Cloud	Deadline Cloud API activity on jobs.	Deadline Cloud job	AWS::Deadline::Job
AWS Deadline Cloud	Deadline Cloud API activity on queues.	Deadline Cloud queue	AWS::Deadline::Queue
AWS Deadline Cloud	Deadline Cloud API activity on workers.	Deadline Cloud worker	AWS::Deadline::Worker

AWS service	Description	Resource type (console)	resources.type value
Amazon DynamoDB	Amazon DynamoDB item-level API activity on tables (for example, PutItem, DeleteItem , and UpdateItem API operations).  Note For tables with streams enabled, the resources field in the data event contains both AWS::Dyna moDB::Str eam and AWS::Dyna moDB::Tab le . If you specify AWS::Dyna moDB::Tab le for the resources .type , it will log both DynamoDB table and DynamoDB	DynamoDB	AWS::DynamoDB::Table

AWS service	Description	Resource type (console)	resources.type value
	streams events by default. To exclude streams events , add a filter on the eventName field.		
Amazon DynamoDB	Amazon DynamoDB API activity on streams.	DynamoDB Streams	AWS::DynamoDB::Stream
Amazon Elastic Block Store	Amazon Elastic Block Store (EBS) direct APIs, such as PutSnapshotBlock , GetSnapshotBlock , and ListChangedBlocks on Amazon EBS snapshots.	Amazon EBS direct APIs	AWS::EC2::Snapshot
Amazon Elastic Compute Cloud	Amazon EC2 instance connect endpoint API activity.	EC2 instance connect endpoint	AWS::EC2::InstanceConnectEndpoint

AWS service	Description	Resource type (console)	resources.type value
Amazon Elastic Container Service	Amazon Elastic Container Service API activity on a container instance.	ECS container instance	AWS::ECS::ContainerInstance
Amazon Elastic Kubernetes Service	Amazon Elastic Kubernetes Service API activity on dashboards.	Amazon Elastic Kubernetes Service dashboard	AWS::EKS::Dashboard
Amazon EMR	Amazon EMR API activity on a write-ahead log workspace.	EMR write-ahead log workspace	AWS::EMRWAL::Workspace
AWS End User Messaging SMS	AWS End User Messaging SMS API activity on origination identities.	SMS Voice origination identity	AWS::SMSVoice::OriginationIdentity
AWS End User Messaging SMS	AWS End User Messaging SMS API activity on messages.	SMS Voice message	AWS::SMSVoice::Message
AWS End User Messaging Social	AWS End User Messaging Social API activity on phone number IDs.	Social-Messaging Phone Number Id	AWS::SocialMessaging::PhoneNumberId
AWS End User Messaging Social	AWS End User Messaging Social API activity on Waba IDs.	Social-Messaging Waba ID	AWS::SocialMessaging::WabaId

AWS service	Description	Resource type (console)	resources.type value
Amazon FinSpace	Amazon FinSpace API activity on environments.	FinSpace	AWS::FinSpace::Environment
Amazon GameLift Streams	Amazon GameLift Streams streaming API activity on applications.	GameLift Streams application	AWS::GameLiftStreams::Application
Amazon GameLift Streams	Amazon GameLift Streams streaming API activity on stream groups.	GameLift Streams stream group	AWS::GameLiftStreams::StreamGroup
AWS Glue	AWS Glue API activity on tables that were created by Lake Formation.	Lake Formation	AWS::Glue::Table
Amazon GuardDuty	Amazon GuardDuty API activity for a detector .	GuardDuty detector	AWS::GuardDuty::Detector
AWS HealthImaging	AWS HealthImaging API activity on data stores.	MedicalImaging data store	AWS::MedicalImaging::Datastore
AWS HealthImaging	AWS HealthImaging image set API activity.	MedicalImaging image set	AWS::MedicalImaging::ImageSet
AWS IoT	AWS IoT API activity on certificates .	IoT certificate	AWS::IoT::Certificate

AWS service	Description	Resource type (console)	resources.type value
AWS IoT	AWS IoT API activity on things .	IoT thing	AWS::IoT::Thing
AWS IoT Greengrass Version 2	Greengrass API activity from a Greengrass core device on a component version.  Note Greengrass doesn't log access denied events.	IoT Greengrass component version	AWS::GreengrassV2::ComponentVersion
AWS IoT Greengrass Version 2	Greengrass API activity from a Greengrass core device on a deployment.  Note Greengrass doesn't log access denied events.	IoT Greengrass deployment	AWS::GreengrassV2::Deployment
AWS IoT SiteWise	IoT SiteWise API activity on assets .	IoT SiteWise asset	AWS::IoTSiteWise::Asset

AWS service	Description	Resource type (console)	resources.type value
AWS IoT SiteWise	IoT SiteWise API activity on time series .	IoT SiteWise time series	AWS::IoTSiteWise::TimeSeries
AWS IoT SiteWise Assistant	Sitewise Assistant API activity on conversations.	Sitewise Assistant conversation	AWS::SitewiseAssistant::Conversation
AWS IoT TwinMaker	IoT TwinMaker API activity on an entity .	IoT TwinMaker entity	AWS::IoTTwinMaker::Entity
AWS IoT TwinMaker	IoT TwinMaker API activity on a workspace .	IoT TwinMaker workspace	AWS::IoTTwinMaker::Workspace
Amazon Kendra Intelligent Ranking	Amazon Kendra Intelligent Ranking API activity on rescore execution plans .	Kendra Ranking	AWS::KendraRanking::ExecutionPlan
Amazon Keyspaces (for Apache Cassandra)	Amazon Keyspaces API activity on a table.	Cassandra table	AWS::Cassandra::Table
Amazon Keyspaces (for Apache Cassandra)	Amazon Keyspaces (for Apache Cassandra) API activity on Cassandra CDC streams.	Cassandra CDC streams	AWS::Cassandra::Stream

AWS service	Description	Resource type (console)	resources.type value
Amazon Kinesis Data Streams	Kinesis Data Streams API activity on streams .	Kinesis stream	AWS::Kinesis::Stream
Amazon Kinesis Data Streams	Kinesis Data Streams API activity on stream consumers .	Kinesis stream consumer	AWS::Kinesis::StreamConsumer
Amazon Kinesis Video Streams	Kinesis Video Streams API activity on video streams, such as calls to GetMedia and PutMedia.	Kinesis video stream	AWS::KinesisVideo::Stream
Amazon Kinesis Video Streams	Kinesis Video Streams video signaling channel API activity.	Kinesis video signaling channel	AWS::KinesisVideo::SignalingChannel
AWS Lambda	AWS Lambda function execution activity (the Invoke API).	Lambda	AWS::Lambda::Function
Amazon Location Maps	Amazon Location Maps API activity.	Geo Maps	AWS::GeoMaps::Provider
Amazon Location Places	Amazon Location Places API activity.	Geo Places	AWS::GeoPlaces::Provider
Amazon Location Routes	Amazon Location Routes API activity.	Geo Routes	AWS::GeoRoutes::Provider

AWS service	Description	Resource type (console)	resources.type value
Amazon Machine Learning	Machine Learning API activity on ML models.	Maching Learning MModel	AWS::MachineLearning::MModel
Amazon Managed Blockchain	Amazon Managed Blockchain API activity on a network.	Managed Blockchain network	AWS::ManagedBlockchain::Network
Amazon Managed Blockchain	Amazon Managed Blockchain JSON-RPC calls on Ethereum nodes, such as eth_getBalance or eth_getBlockByNumber .	Managed Blockchain	AWS::ManagedBlockchain::Node
Amazon Managed Blockchain Query	Amazon Managed Blockchain Query API activity.	Managed Blockchain Query	AWS::ManagedBlockchainQuery::QueryAPI
Amazon Managed Workflows for Apache Airflow	Amazon MWAA API activity on environments.	Managed Apache Airflow	AWS::MWAA::Environment
Amazon Neptune Graph	Data API activities, for example queries, algorithms, or vector search, on a Neptune Graph.	Neptune Graph	AWS::NeptuneGraph::Graph

AWS service	Description	Resource type (console)	resources.type value
Amazon One Enterprise	Amazon One Enterprise API activity on a UKey.	Amazon One UKey	AWS::One::UKey
Amazon One Enterprise	Amazon One Enterprise API activity on users.	Amazon One User	AWS::One::User
AWS Payment Cryptography	AWS Payment Cryptography API activity on aliases.	Payment Cryptography Alias	AWS::PaymentCryptography::Alias
AWS Payment Cryptography	AWS Payment Cryptography API activity on keys.	Payment Cryptography Key	AWS::PaymentCryptography::Key
Amazon Pinpoint	Amazon Pinpoint API activity on mobile targeting applications.	Mobile Targeting Application	AWS::Pinpoint::App
AWS Private CA	AWS Private CA Connector for Active Directory API activity.	AWS Private CA Connector for Active Directory	AWS::PCAConnectorAD::Connector
AWS Private CA	AWS Private CA Connector for SCEP API activity.	AWS Private CA Connector for SCEP	AWS::PCAConnectorSCEP::Connector

AWS service	Description	Resource type (console)	resources.type value
Amazon Q Apps	Data API activity on Amazon Q Apps .	Amazon Q Apps	AWS::QApps::QApp
Amazon Q Apps	Data API activity on Amazon Q App sessions.	Amazon Q App Session	AWS::QApps::QAppSession
Amazon Q Business	Amazon Q Business API activity on an application.	Amazon Q Business application	AWS::QBusiness::Application
Amazon Q Business	Amazon Q Business API activity on a data source.	Amazon Q Business data source	AWS::QBusiness::DataSource
Amazon Q Business	Amazon Q Business API activity on an index.	Amazon Q Business index	AWS::QBusiness::Index
Amazon Q Business	Amazon Q Business API activity on a web experience.	Amazon Q Business web experience	AWS::QBusiness::WebExperience
Amazon Q Business	Amazon Q Business integration API activity.	Amazon Q Business integration	AWS::QBusiness::Integration
Amazon Q Developer	Amazon Q Developer API activity on an integration.	Q Developer integration	AWS::QDeveloper::Integration

AWS service	Description	Resource type (console)	resources.type value
Amazon Q Developer	Amazon Q Developer API activity on operational investigations.	AI Ops Investigation Group	AWS::AIOps::InvestigationGroup
Amazon Quick Suite	Amazon Quick Suite API activity on an action connector.	AWS QuickSuite Actions	AWS::QuickSight::ActionConnector
Amazon Quick Suite	Amazon Quick Suite Flow API activity.	AWS::QuickSight::Flow	AWS::QuickSight::Flow
Amazon Quick Suite	Amazon Quick Suite FlowSession API activity.	AWS::QuickSight::FlowSession	AWS::QuickSight::FlowSession
Amazon SageMaker AI	Amazon SageMaker AI InvokeEndpointWithResponseStream activity on endpoints.	SageMaker AI endpoint	AWS::SageMaker::Endpoint
Amazon SageMaker AI	Amazon SageMaker AI API activity on feature stores.	SageMaker AI feature store	AWS::SageMaker::FeatureGroup
Amazon SageMaker AI	Amazon SageMaker AI API activity on experiment trial components .	SageMaker AI metrics experiment trial component	AWS::SageMaker::ExperimentTrialComponent

AWS service	Description	Resource type (console)	resources.type value
Amazon SageMaker AI;	Amazon SageMaker AI MLflow API activity.	SageMaker MLflow	AWS::SageMaker::MlflowTrackingServer
AWS Signer	Signer API activity on signing jobs.	Signer signing job	AWS::Signer::SigningJob
AWS Signer	Signer API activity on signing profiles.	Signer signing profile	AWS::Signer::SigningProfile
Amazon Simple Email Service	Amazon Simple Email Service (Amazon SES) API activity on configuration sets.	SES configuration set	AWS::SES::ConfigurationSet
Amazon Simple Email Service	Amazon Simple Email Service (Amazon SES) API activity on email identities.	SES identity	AWS::SES::EmailIdentity
Amazon Simple Email Service	Amazon Simple Email Service (Amazon SES) API activity on templates.	SES template	AWS::SES::Template
Amazon SimpleDB	Amazon SimpleDB API activity on domains.	SimpleDB domain	AWS::SDB::Domain
AWS Step Functions	Step Functions API activity on activities.	Step Functions	AWS::StepFunctions::Activity

AWS service	Description	Resource type (console)	resources.type value
AWS Step Functions	Step Functions API activity on state machines.	Step Functions state machine	AWS::StepFunctions::StateMachine
AWS Systems Manager	Systems Manager API activity on control channels.	Systems Manager	AWS::SSMMessages::ControlChannel
AWS Systems Manager	Systems Manager API activity on impact assessments.	SSM Impact Assessment	AWS::SSM::ExecutionPreview
AWS Systems Manager	Systems Manager API activity on managed nodes.	Systems Manager managed node	AWS::SSM::ManagedNode
Amazon Timestream	Amazon Timestream Query API activity on databases.	Timestream database	AWS::Timestream::Database
Amazon Timestream	Amazon Timestream API activity on regional endpoints.	Timestream regional endpoint	AWS::Timestream::RegionalEndpoint
Amazon Timestream	Amazon Timestream Query API activity on tables.	Timestream table	AWS::Timestream::Table
Amazon Verified Permissions	Amazon Verified Permissions API activity on a policy store.	Amazon Verified Permissions	AWS::VerifiedPermissions::PolicyStore

AWS service	Description	Resource type (console)	resources.type value
Amazon WorkSpaces Thin Client	WorkSpaces Thin Client API activity on a Device.	Thin Client Device	AWS::ThinClient::Device
Amazon WorkSpaces Thin Client	WorkSpaces Thin Client API activity on an Environment.	Thin Client Environment	AWS::ThinClient::Environment
AWS X-Ray	X-Ray API activity on traces .	X-Ray trace	AWS::XRay::Trace

To record CloudTrail data events, you must explicitly add each resource type for which you want to collect activity. For more information, see [Creating a trail with the CloudTrail console](#) and [Create an event data store for CloudTrail events with the console](#).

On a single-Region trail or event data store, you can log data events only for resources that you can access in that Region. Though S3 buckets are global, AWS Lambda functions and DynamoDB tables are regional.

Additional charges apply for logging data events. For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Examples: Logging data events for Amazon S3 objects

Logging data events for all S3 objects in an S3 bucket

The following example demonstrates how logging works when you configure logging of all data events for an S3 bucket named `amzn-s3-demo-bucket`. In this example, the CloudTrail user specified an empty prefix, and the option to log both **Read** and **Write** data events.

1. A user uploads an object to `amzn-s3-demo-bucket`.
2. The `PutObject` API operation is an Amazon S3 object-level API. It is recorded as a data event in CloudTrail. Because the CloudTrail user specified an S3 bucket with an empty prefix, events

that occur on any object in that bucket are logged. The trail or event data store processes and logs the event.

3. Another user uploads an object to `amzn-s3-demo-bucket2`.
4. The `PutObject` API operation occurred on an object in an S3 bucket that wasn't specified for the trail or event data store. The trail or event data store doesn't log the event.

Logging data events for specific S3 objects

The following example demonstrates how logging works when you configure a trail or event data store to log events for specific S3 objects. In this example, the CloudTrail user specified an S3 bucket named `amzn-s3-demo-bucket3`, with the prefix *my-images*, and the option to log only **Write** data events.

1. A user deletes an object that begins with the `my-images` prefix in the bucket, such as `arn:aws:s3:::amzn-s3-demo-bucket3/my-images/example.jpg`.
2. The `DeleteObject` API operation is an Amazon S3 object-level API. It is recorded as a **Write** data event in CloudTrail. The event occurred on an object that matches the S3 bucket and prefix specified in the trail or event data store. The trail or event data store processes and logs the event.
3. Another user deletes an object with a different prefix in the S3 bucket, such as `arn:aws:s3:::amzn-s3-demo-bucket3/my-videos/example.avi`.
4. The event occurred on an object that doesn't match the prefix specified in your trail or event data store. The trail or event data store doesn't log the event.
5. A user calls the `GetObject` API operation for the object, `arn:aws:s3:::amzn-s3-demo-bucket3/my-images/example.jpg`.
6. The event occurred on a bucket and prefix that are specified in the trail or event data store, but `GetObject` is a read-type Amazon S3 object-level API. It is recorded as a **Read** data event in CloudTrail, and the trail or event data store is not configured to log **Read** events. The trail or event data store doesn't log the event.

Note

For trails, if you are logging data events for specific Amazon S3 buckets, we recommend you do not use an Amazon S3 bucket for which you are logging data events to receive log files that you have specified in the data events section for your trail. Using the same

Amazon S3 bucket causes your trail to log a data event each time log files are delivered to your Amazon S3 bucket. Log files are aggregated events delivered at intervals, so this is not a 1:1 ratio of event to log file; the event is logged in the next log file. For example, when CloudTrail delivers logs, the `PutObject` event occurs on the S3 bucket. If the S3 bucket is also specified in the data events section, the trail processes and logs the `PutObject` event as a data event. That action is another `PutObject` event, and the trail processes and logs the event again.

To avoid logging data events for the Amazon S3 bucket where you receive log files if you configure a trail to log all Amazon S3 data events in your AWS account, consider configuring delivery of log files to an Amazon S3 bucket that belongs to another AWS account. For more information, see [Receiving CloudTrail log files from multiple accounts](#).

Logging data events for S3 objects in other AWS accounts

When you configure your trail to log data events, you can also specify S3 objects that belong to other AWS accounts. When an event occurs on a specified object, CloudTrail evaluates whether the event matches any trails in each account. If the event matches the settings for a trail, the trail processes and logs the event for that account. Generally, both API callers and resource owners can receive events.

If you own an S3 object and you specify it in your trail, your trail logs events that occur on the object in your account. Because you own the object, your trail also logs events when other accounts call the object.

If you specify an S3 object in your trail, and another account owns the object, your trail only logs events that occur on that object in your account. Your trail doesn't log events that occur in other accounts.

Example: Logging data events for an Amazon S3 object for two AWS accounts

The following example shows how two AWS accounts configure CloudTrail to log events for the same S3 object.

1. In your account, you want your trail to log data events for all objects in your S3 bucket named `amzn-s3-demo-bucket`. You configure the trail by specifying the S3 bucket with an empty object prefix.

2. Bob has a separate account that has been granted access to the S3 bucket. Bob also wants to log data events for all objects in the same S3 bucket. For his trail, he configures his trail and specifies the same S3 bucket with an empty object prefix.
3. Bob uploads an object to the S3 bucket with the PutObject API operation.
4. This event occurred in his account and it matches the settings for his trail. Bob's trail processes and logs the event.
5. Because you own the S3 bucket and the event matches the settings for your trail, your trail also processes and logs the same event. Because there are now two copies of the event (one logged in Bob's trail, and one logged in yours), CloudTrail charges for two copies of the data event.
6. You upload an object to the S3 bucket.
7. This event occurs in your account and it matches the settings for your trail. Your trail processes and logs the event.
8. Because the event didn't occur in Bob's account, and he doesn't own the S3 bucket, Bob's trail doesn't log the event. CloudTrail charges for only one copy of this data event.

Example: Logging data events for all buckets, including an S3 bucket used by two AWS accounts

The following example shows the logging behavior when **Select all S3 buckets in your account** is enabled for trails that collect data events in an AWS account.

1. In your account, you want your trail to log data events for all S3 buckets. You configure the trail by choosing **Read** events, **Write** events, or both for **All current and future S3 buckets in Data events**.
2. Bob has a separate account that has been granted access to an S3 bucket in your account. He wants to log data events for the bucket to which he has access. He configures his trail to get data events for all S3 buckets.
3. Bob uploads an object to the S3 bucket with the PutObject API operation.
4. This event occurred in his account and it matches the settings for his trail. Bob's trail processes and logs the event.
5. Because you own the S3 bucket and the event matches the settings for your trail, your trail also processes and logs the event. Because there are now two copies of the event (one logged in Bob's trail, and one logged in yours), CloudTrail charges each account for a copy of the data event.

6. You upload an object to the S3 bucket.
7. This event occurs in your account and it matches the settings for your trail. Your trail processes and logs the event.
8. Because the event didn't occur in Bob's account, and he doesn't own the S3 bucket, Bob's trail doesn't log the event. CloudTrail charges for only one copy of this data event in your account.
9. A third user, Mary, has access to the S3 bucket, and runs a `GetObject` operation on the bucket. She has a trail configured to log data events on all S3 buckets in her account. Because she is the API caller, CloudTrail logs a data event in her trail. Though Bob has access to the bucket, he is not the resource owner, so no event is logged in his trail this time. As the resource owner, you receive an event in your trail about the `GetObject` operation that Mary called. CloudTrail charges your account and Mary's account for each copy of the data event: one in Mary's trail, and one in yours.

Read-only and write-only events

When you configure your trail or event data store to log data and management events, you can specify whether you want read-only events, write-only events, or both.

- **Read**

Read events include API operations that read your resources, but don't make changes. For example, read-only events include the Amazon EC2 `DescribeSecurityGroups` and `DescribeSubnets` API operations. These operations return only information about your Amazon EC2 resources and don't change your configurations.

- **Write**

Write events include API operations that modify (or might modify) your resources. For example, the Amazon EC2 `RunInstances` and `TerminateInstances` API operations modify your instances.

Example: Logging read and write events for separate trails

The following example shows how you can configure trails to split log activity for an account into separate S3 buckets: one bucket named `amzn-s3-demo-bucket1` receives read-only events and a second `amzn-s3-demo-bucket2` receives write-only events.

1. You create a trail and choose the S3 bucket named `amzn-s3-demo-bucket1` to receive log files. You then update the trail to specify that you want **Read** management events and data events.
2. You create a second trail and choose the S3 bucket the `amzn-s3-demo-bucket2` to receive log files. You then update the trail to specify that you want **Write** management events and data events.
3. The Amazon EC2 `DescribeInstances` and `TerminateInstances` API operations occur in your account.
4. The `DescribeInstances` API operation is a read-only event and it matches the settings for the first trail. The trail logs and delivers the event to the `amzn-s3-demo-bucket1`.
5. The `TerminateInstances` API operation is a write-only event and it matches the settings for the second trail. The trail logs and delivers the event to the `amzn-s3-demo-bucket2`.

Logging data events with the AWS Management Console

The following procedures describe how to an update existing event data store or trail to log data events by using the AWS Management Console. For information about how to create an event data store to log data events, see [Create an event data store for CloudTrail events with the console](#). For information about how to create a trail to log data events, see [Creating a trail with the console](#).

For trails, the steps for logging data events differ based on whether you're using advanced event selectors or basic event selectors. You can log data events for all resource types using advanced event selectors, but if you use basic event selectors you're limited to logging data events for Amazon S3 buckets and bucket objects, AWS Lambda functions, and Amazon DynamoDB tables.

Updating an existing event data store to log data events using the console

Use the following procedure to update an existing event data store to log data events. For more information about using advanced event selectors, see [Filtering data events by using advanced event selectors](#) in this topic.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. From the navigation pane, under **Lake**, choose **Event data stores**.
3. On the **Event data stores** page, choose the event data store you want to update.

 Note

You can only enable data events on event data stores that contain CloudTrail events. You cannot enable data events on CloudTrail event data stores for AWS Config configuration items, CloudTrail Insights events, or non-AWS events.

4. On the details page, in **Data events**, choose **Edit**.
5. If you are not already logging data events, choose the **Data events** check box.
6. For **Resource type**, choose the resource type on which you want to log data events.
7. Choose a log selector template. You can choose a predefined template, or choose **Custom** to define your own event collection conditions.

You can choose from the following predefined templates:

- **Log all events** – Choose this template to log all events.
 - **Log only read events** – Choose this template to log only read events. Read-only events are events that do not change the state of a resource, such as `Get*` or `Describe*` events.
 - **Log only write events** – Choose this template to log only write events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events.
 - **Log only AWS Management Console events** – Choose this template to log only events originating from the AWS Management Console.
 - **Exclude AWS service initiated events** – Choose this template to exclude AWS service events, which have an `eventType` of `AwsServiceEvent`, and events initiated with AWS service-linked roles (SLRs).
8. (Optional) In **Selector name**, enter a name to identify your selector. The selector name is a descriptive name for an advanced event selector, such as "Log data events for only two S3 buckets". The selector name is listed as `Name` in the advanced event selector and is viewable if you expand the **JSON view**.
 9. If you selected **Custom**, in **Advanced event selectors** build an expression based on the values of advanced event selector fields.

 Note

Selectors don't support the use of wildcards like `*`. To match multiple values with a single condition, you may use `StartsWith`, `EndsWith`, `NotStartsWith`, or `NotEndsWith` to explicitly match the beginning or end of the event field.

a. Choose from the following fields.

- **readOnly** - `readOnly` can be set to **equals** a value of `true` or `false`. Read-only data events are events that do not change the state of a resource, such as `Get*` or `Describe*` events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events. To log both read and write events, don't add a `readOnly` selector.
- **eventName** - `eventName` can use any operator. You can use it to include or exclude any data event logged to CloudTrail, such as `PutBucket`, `GetItem`, or `GetSnapshotBlock`.
- **eventSource** – The event source to include or exclude. This field can use any operator.
- **eventType** – The event type to include or exclude. For example, you can set this field to **not equals** `AwsServiceEvent` to exclude [AWS service events](#). For a list of event types, see [eventType](#) in [CloudTrail record contents for management, data, and network activity events](#).
- **sessionCredentialFromConsole** – Include or exclude events originating from an AWS Management Console session. This field can be set to **equals** or **not equals** with a value of `true`.
- **userIdentity.arn** – Include or exclude events for actions taken by specific IAM identities. For more information, see [CloudTrail userIdentity element](#).
- **resources.ARN** - You can use any operator with `resources.ARN`, but if you use **equals** or **does not equal**, the value must exactly match the ARN of a valid resource of the type you've specified in the template as the value of `resources.type`.

Note

You can't use the `resources.ARN` field to filter resource types that do not have ARNs.

For more information about the ARN formats of data event resources, see [Actions, resources, and condition keys for AWS services](#) in the *Service Authorization Reference*.

- b. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions. For example, to exclude data events for two S3 buckets from data events that are logged on your event data store, you can set the field to **resources.ARN**, set the operator for **does not start with**, and then paste in an S3 bucket ARN for which you do not want to log events.

To add the second S3 bucket, choose **+ Condition**, and then repeat the preceding instruction, pasting in the ARN for or browsing for a different bucket.

For information about how CloudTrail evaluates multiple conditions, see [How CloudTrail evaluates multiple conditions for a field](#).

Note

You can have a maximum of 500 values for all selectors on an event data store. This includes arrays of multiple values for a selector such as `eventName`. If you have single values for all selectors, you can have a maximum of 500 conditions added to a selector.

- c. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields. For example, do not specify an ARN in one selector to be equal to a value, then specify that the ARN not equal the same value in another selector.
10. To add another resource type on which to log data events, choose **Add data event type**. Repeat steps 6 through this step to configure advanced event selectors for another resource type.
 11. After you've reviewed and verified your choices, choose **Save changes**.

Updating an existing trail to log data events with advanced event selectors using the console

In the AWS Management Console, if your trail is using advanced event selectors, you can choose from predefined templates that log all data events on a selected resource. After you choose a log selector template, you can customize the template to include only the data events you most want to see. For more information about using advanced event selectors, see [Filtering data events by using advanced event selectors](#) in this topic.

1. On the **Dashboard** or **Trails** pages of the CloudTrail console, choose the trail you want to update.
2. On the details page, in **Data events**, choose **Edit**.
3. If you are not already logging data events, choose the **Data events** check box.
4. For **Resource type**, choose the resource type on which you want to log data events.
5. Choose a log selector template. You can choose a predefined template, or choose **Custom** to define your own event collection conditions.

You can choose from the following predefined templates:

- **Log all events** – Choose this template to log all events.
- **Log only read events** – Choose this template to log only read events. Read-only events are events that do not change the state of a resource, such as `Get*` or `Describe*` events.
- **Log only write events** – Choose this template to log only write events. Write events add, change, or delete resources, attributes, or artifacts, such as `Put*`, `Delete*`, or `Write*` events.
- **Log only AWS Management Console events** – Choose this template to log only events originating from the AWS Management Console.
- **Exclude AWS service initiated events** – Choose this template to exclude AWS service events, which have an `eventType` of `AwsServiceEvent`, and events initiated with AWS service-linked roles (SLRs).

Note

Choosing a predefined template for S3 buckets enables data event logging for all buckets currently in your AWS account and any buckets you create after you finish creating the trail. It also enables logging of data event activity performed by any user

or role in your AWS account, even if that activity is performed on a bucket that belongs to another AWS account.

If the trail applies only to one Region, choosing a predefined template that logs all S3 buckets enables data event logging for all buckets in the same Region as your trail and any buckets you create later in that Region. It will not log data events for Amazon S3 buckets in other Regions in your AWS account.

If you are creating a trail for all Regions, choosing a predefined template for Lambda functions enables data event logging for all functions currently in your AWS account, and any Lambda functions you might create in any Region after you finish creating the trail. If you are creating a trail for a single Region (for trails, this only can be done by using the AWS CLI), this selection enables data event logging for all functions currently in that Region in your AWS account, and any Lambda functions you might create in that Region after you finish creating the trail. It does not enable data event logging for Lambda functions created in other Regions.

Logging data events for all functions also enables logging of data event activity performed by any user or role in your AWS account, even if that activity is performed on a function that belongs to another AWS account.

6. (Optional) In **Selector name**, enter a name to identify your selector. The selector name is a descriptive name for an advanced event selector, such as "Log data events for only two S3 buckets". The selector name is listed as Name in the advanced event selector and is viewable if you expand the **JSON view**.
7. If you selected **Custom**, in **Advanced event selectors** build an expression based on the values of advanced event selector fields.

 Note

Selectors don't support the use of wildcards like `*`. To match multiple values with a single condition, you may use `StartsWith`, `EndsWith`, `NotStartsWith`, or `NotEndsWith` to explicitly match the beginning or end of the event field.

- a. Choose from the following fields.
 - **readOnly** - `readOnly` can be set to **equals** a value of `true` or `false`. Read-only data events are events that do not change the state of a resource, such as `Get*` or `Describe*` events. Write events add, change, or delete resources, attributes, or

artifacts, such as Put*, Delete*, or Write* events. To log both read and write events, don't add a readOnly selector.

- **eventName** - eventName can use any operator. You can use it to include or exclude any data event logged to CloudTrail, such as PutBucket, GetItem, or GetSnapshotBlock.
- **eventSource** – The event source to include or exclude. This field can use any operator.
- **eventType** – The event type to include or exclude. For example, you can set this field to **not equals** AwsServiceEvent to exclude [AWS service events](#). For a list of event types, see [eventType](#) in [CloudTrail record contents for management, data, and network activity events](#).
- **sessionCredentialFromConsole** – Include or exclude events originating from an AWS Management Console session. This field can be set to **equals** or **not equals** with a value of true.
- **userIdentity.arn** – Include or exclude events for actions taken by specific IAM identities. For more information, see [CloudTrail userIdentity element](#).
- **resources.ARN** - You can use any operator with resources.ARN, but if you use **equals** or **does not equal**, the value must exactly match the ARN of a valid resource of the type you've specified in the template as the value of resources.type.

 Note

You can't use the resources.ARN field to filter resource types that do not have ARNs.

For more information about the ARN formats of data event resources, see [Actions, resources, and condition keys for AWS services](#) in the *Service Authorization Reference*.

- b. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions. For example, to exclude data events for two S3 buckets from data events that are logged on your event data store, you can set the field to **resources.ARN**, set the operator for **does not start with**, and then paste in an S3 bucket ARN for which you do not want to log events.

To add the second S3 bucket, choose **+ Condition**, and then repeat the preceding instruction, pasting in the ARN for or browsing for a different bucket.

For information about how CloudTrail evaluates multiple conditions, see [How CloudTrail evaluates multiple conditions for a field](#).

 Note

You can have a maximum of 500 values for all selectors on an event data store. This includes arrays of multiple values for a selector such as eventName. If you have single values for all selectors, you can have a maximum of 500 conditions added to a selector.

- c. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields. For example, do not specify an ARN in one selector to be equal to a value, then specify that the ARN not equal the same value in another selector.
8. To add another resource type on which to log data events, choose **Add data event type**. Repeat steps 4 through this step to configure advanced event selectors for the resource type.
9. After you've reviewed and verified your choices, choose **Save changes**.

Update an existing trail to log data events with basic event selectors using the console

Use the following procedure to update an existing trail to log data events using basic event selectors.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. Open the **Trails** page of the CloudTrail console and choose the trail name.

 Note

While you can edit an existing trail to log data events, as a best practice, consider creating a separate trail specifically for logging data events.

3. For **Data events**, choose **Edit**.
4. For Amazon S3 buckets:
 - a. For **Data event source**, choose **S3**.

- b. You can choose to log **All current and future S3 buckets**, or you can specify individual buckets or functions. By default, data events are logged for all current and future S3 buckets.

 Note

Keeping the default **All current and future S3 buckets** option enables data event logging for all buckets currently in your AWS account and any buckets you create after you finish creating the trail. It also enables logging of data event activity performed by any user or role in your AWS account, even if that activity is performed on a bucket that belongs to another AWS account.

If you are creating a trail for a single Region (done by using the AWS CLI), selecting the **Select all S3 buckets in your account** option enables data event logging for all buckets in the same Region as your trail and any buckets you create later in that Region. It will not log data events for Amazon S3 buckets in other Regions in your AWS account.

- c. If you leave the default, **All current and future S3 buckets**, choose to log **Read** events, **Write** events, or both.
- d. To select individual buckets, empty the **Read** and **Write** check boxes for **All current and future S3 buckets**. In **Individual bucket selection**, browse for a bucket on which to log data events. To find specific buckets, type a bucket prefix for the bucket you want. You can select multiple buckets in this window. Choose **Add bucket** to log data events for more buckets. Choose to log **Read** events, such as GetObject, **Write** events, such as PutObject, or both.

This setting takes precedence over individual settings you configure for individual buckets. For example, if you specify logging **Read** events for all S3 buckets, and then choose to add a specific bucket for data event logging, **Read** is already selected for the bucket you added. You cannot clear the selection. You can only configure the option for **Write**.

To remove a bucket from logging, choose **X**.

5. To add another resource type on which to log data events, choose **Add data event type**.
6. For Lambda functions:
 - a. For **Data event source**, choose **Lambda**.

- b. In **Lambda function**, choose **All regions** to log all Lambda functions, or **Input function as ARN** to log data events on a specific function.

To log data events for all Lambda functions in your AWS account, select **Log all current and future functions**. This setting takes precedence over individual settings you configure for individual functions. All functions are logged, even if all functions are not displayed.

 Note

If you are creating a trail for all Regions, this selection enables data event logging for all functions currently in your AWS account, and any Lambda functions you might create in any Region after you finish creating the trail. If you are creating a trail for a single Region (done by using the AWS CLI), this selection enables data event logging for all functions currently in that Region in your AWS account, and any Lambda functions you might create in that Region after you finish creating the trail. It does not enable data event logging for Lambda functions created in other Regions.

Logging data events for all functions also enables logging of data event activity performed by any user or role in your AWS account, even if that activity is performed on a function that belongs to another AWS account.

- c. If you choose **Input function as ARN**, enter the ARN of a Lambda function.

 Note

If you have more than 15,000 Lambda functions in your account, you cannot view or select all functions in the CloudTrail console when creating a trail. You can still select the option to log all functions, even if they are not displayed. If you want to log data events for specific functions, you can manually add a function if you know its ARN. You can also finish creating the trail in the console, and then use the AWS CLI and the **put-event-selectors** command to configure data event logging for specific Lambda functions. For more information, see [Managing trails with the AWS CLI](#).

7. To add another resource type on which to log data events, choose **Add data event type**.
8. For DynamoDB tables:
 - a. For **Data event source**, choose **DynamoDB**.

- b. In **DynamoDB table selection**, choose **Browse** to select a table, or paste in the ARN of a DynamoDB table to which you have access. A DynamoDB table ARN uses the following format:

```
arn:partition:dynamodb:region:account_ID:table/table_name
```

To add another table, choose **Add row**, and browse for a table or paste in the ARN of a table to which you have access.

9. Choose **Save changes**.

Logging data events with the AWS Command Line Interface

You can configure your trails or event data stores to log data events using the AWS CLI.

Topics

- [Logging data events for trails with the AWS CLI](#)
- [Logging data events for event data stores with the AWS CLI](#)

Logging data events for trails with the AWS CLI

You can configure your trails to log management and data events using the AWS CLI.

Note

- Be aware that if your account is logging more than one copy of management events, you incur charges. There is always a charge for logging data events. For more information, see [AWS CloudTrail Pricing](#).
- You can use either advanced event selectors or basic event selectors, but not both. If you apply advanced event selectors to a trail, any existing basic event selectors are overwritten.
- If your trail uses basic event selectors, you can only log the following resource types:
 - `AWS::DynamoDB::Table`
 - `AWS::Lambda::Function`
 - `AWS::S3::Object`

To log additional resource types, you'll need to use advanced event selectors. To convert a trail to advanced event selectors, run the **get-event-selectors** command to confirm the current event selectors, and then configure the advanced event selectors to match the coverage of the previous event selectors, then add selectors for any resource types for which you want to log data events.

- You can use advanced event selectors to filter based on the value of the [supported advanced event selector fields](#) supported advanced event selector fields, giving you the ability to log only the data events of interest. For more information about configuring these fields, see [AdvancedFieldSelector](#) in the *AWS CloudTrail API Reference* and [Filtering data events by using advanced event selectors](#) in this guide.

To see whether your trail is logging management and data events, run the [get-event-selectors](#) command.

```
aws cloudtrail get-event-selectors --trail-name TrailName
```

The command returns the event selectors for the trail.

Topics

- [Log data events for trails by using advanced event selectors](#)
- [Log all Amazon S3 events for an Amazon S3 bucket by using advanced event selectors](#)
- [Log Amazon S3 on AWS Outposts events by using advanced event selectors](#)
- [Log events by using basic event selectors](#)

Log data events for trails by using advanced event selectors

Note

If you apply advanced event selectors to a trail, any existing basic event selectors are overwritten. Before configuring advanced event selectors, run the **get-event-selectors** command to confirm the current event selectors, and then configure the advanced event selectors to match the coverage of the previous event selectors, then add selectors for any additional data events you want to log.

The following example creates custom advanced event selectors for a trail named *TrailName* to include read and write management events (by omitting the `readOnly` selector), `PutObject` and `DeleteObject` data events for all Amazon S3 bucket/prefix combinations except for a bucket named `amzn-s3-demo-bucket` and data events for an AWS Lambda function named `MyLambdaFunction`. Because these are custom advanced event selectors, each set of selectors has a descriptive name. Note that a trailing slash is part of the ARN value for S3 buckets.

```
aws cloudtrail put-event-selectors --trail-name TrailName --advanced-event-selectors '[
  {
    "Name": "Log readOnly and writeOnly management events",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Management"] }
    ]
  },
  {
    "Name": "Log PutObject and DeleteObject events for all but one bucket",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Data"] },
      { "Field": "resources.type", "Equals": ["AWS::S3::Object"] },
      { "Field": "eventName", "Equals": ["PutObject","DeleteObject"] },
      { "Field": "resources.ARN", "NotStartsWith": ["arn:aws:s3:::amzn-s3-demo-
bucket/"] }
    ]
  },
  {
    "Name": "Log data plane actions on MyLambdaFunction",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Data"] },
      { "Field": "resources.type", "Equals": ["AWS::Lambda::Function"] },
      { "Field": "resources.ARN", "Equals": ["arn:aws:lambda:us-
east-2:111122223333:function/MyLambdaFunction"] }
    ]
  }
]'
```

The example returns the advanced event selectors that are configured for the trail.

```
{
  "AdvancedEventSelectors": [
    {
      "Name": "Log readOnly and writeOnly management events",
```



```

    "FieldSelectors": [
      {
        "Field": "eventCategory",
        "Equals": [ "Management" ]
      }
    ],
  },
  {
    "Name": "Log PutObject and DeleteObject events for all but one bucket",
    "FieldSelectors": [
      {
        "Field": "eventCategory",
        "Equals": [ "Data" ]
      },
      {
        "Field": "resources.type",
        "Equals": [ "AWS::S3::Object" ]
      },
      {
        "Field": "resources.ARN",
        "NotStartsWith": [ "arn:aws:s3:::amzn-s3-demo-bucket/" ]
      }
    ],
  },
},
{
  "Name": "Log data plane actions on MyLambdaFunction",
  "FieldSelectors": [
    {
      "Field": "eventCategory",
      "Equals": [ "Data" ]
    },
    {
      "Field": "resources.type",
      "Equals": [ "AWS::Lambda::Function" ]
    },
    {
      "Field": "eventName",
      "Equals": [ "Invoke" ]
    },
    {
      "Field": "resources.ARN",
      "Equals": [ "arn:aws:lambda:us-east-2:111122223333:function/
MyLambdaFunction" ]
    }
  ]
}

```

```

    ]
  }
],
"TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName"
}

```

Log all Amazon S3 events for an Amazon S3 bucket by using advanced event selectors

Note

If you apply advanced event selectors to a trail, any existing basic event selectors are overwritten.

The following example shows how to configure your trail to include all data events for all Amazon S3 objects in a specific S3 bucket. The value for S3 events for the `resources.type` field is `AWS::S3::Object`. Because the ARN values for S3 objects and S3 buckets are slightly different, you must add the `StartsWith` operator for `resources.ARN` to capture all events.

```

aws cloudtrail put-event-selectors --trail-name TrailName --region region \
--advanced-event-selectors \
'[
  {
    "Name": "S3EventSelector",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Data"] },
      { "Field": "resources.type", "Equals": ["AWS::S3::Object"] },
      { "Field": "resources.ARN", "StartsWith": ["arn:partition:s3::amzn-s3-
demo-bucket/"] }
    ]
  }
]'

```

The command returns the following example output.

```

{
  "TrailARN": "arn:aws:cloudtrail:region:account_ID:trail/TrailName",
  "AdvancedEventSelectors": [
    {
      "Name": "S3EventSelector",
      "FieldSelectors": [

```

```

        {
            "Field": "eventCategory",
            "Equals": [
                "Data"
            ]
        },
        {
            "Field": "resources.type",
            "Equals": [
                "AWS::S3::Object"
            ]
        },
        {
            "Field": "resources.ARN",
            "StartsWith": [
                "arn:partition:s3::amzn-s3-demo-bucket/"
            ]
        }
    ]
}

```

Log Amazon S3 on AWS Outposts events by using advanced event selectors

Note

If you apply advanced event selectors to a trail, any existing basic event selectors are overwritten.

The following example shows how to configure your trail to include all data events for all Amazon S3 on Outposts objects in your outpost.

```

aws cloudtrail put-event-selectors --trail-name TrailName --region region \
--advanced-event-selectors \
'[
    {
        "Name": "OutpostsEventSelector",
        "FieldSelectors": [
            { "Field": "eventCategory", "Equals": ["Data"] },
            { "Field": "resources.type", "Equals": ["AWS::S3Outposts::Object"] }
        ]
    }
]

```

```
    ]
  }
]'
```

The command returns the following example output.

```
{
  "TrailARN": "arn:aws:cloudtrail:region:account_ID:trail/TrailName",
  "AdvancedEventSelectors": [
    {
      "Name": "OutpostsEventSelector",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Data"
          ]
        },
        {
          "Field": "resources.type",
          "Equals": [
            "AWS::S3Outposts::Object"
          ]
        }
      ]
    }
  ]
}
```

Log events by using basic event selectors

The following is an example result of the **get-event-selectors** command showing basic event selectors. By default, when you create a trail by using the AWS CLI, a trail logs all management events. By default, trails do not log data events.

```
{
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName",
  "EventSelectors": [
    {
      "IncludeManagementEvents": true,
      "DataResources": [],
      "ReadWriteType": "All"
    }
  ]
}
```

```
    }
  ]
}
```

To configure your trail to log management and data events, run the [put-event-selectors](#) command.

The following example shows how to use basic event selectors to configure your trail to include all management and data events for the S3 objects in two S3 bucket prefixes. You can specify from 1 to 5 event selectors for a trail. You can specify from 1 to 250 data resources for a trail.

Note

The maximum number of S3 data resources is 250, if you choose to limit data events by using basic event selectors.

```
aws cloudtrail put-event-selectors --trail-name TrailName --event-selectors
'[{ "ReadWriteType": "All", "IncludeManagementEvents":true, "DataResources":
[{ "Type": "AWS::S3::Object", "Values": ["arn:aws:s3:::amzn-s3-demo-bucket1/prefix",
"arn:aws:s3:::amzn-s3-demo-bucket2/prefix2"] }] }]'
```

The command returns the event selectors that are configured for the trail.

```
{
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/TrailName",
  "EventSelectors": [
    {
      "IncludeManagementEvents": true,
      "DataResources": [
        {
          "Values": [
            "arn:aws:s3:::amzn-s3-demo-bucket1/prefix",
            "arn:aws:s3:::amzn-s3-demo-bucket2/prefix2",
          ],
          "Type": "AWS::S3::Object"
        }
      ],
      "ReadWriteType": "All"
    }
  ]
}
```

```
}
```

Logging data events for event data stores with the AWS CLI

You can configure your event data stores to include data events using the AWS CLI. Use the [create-event-data-store](#) command to create a new event data store to log data events. Use the [update-event-data-store](#) command to update the advanced event selectors for an existing event data store.

You configure advanced event selectors to log data events on an event data store. For a list of supported fields, see [Filtering data events by using advanced event selectors](#).

To see whether your event data store includes data events, run the [get-event-data-store](#) command.

```
aws cloudtrail get-event-data-store --event-data-store EventDataStoreARN
```

The command returns the settings for the event data store.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLE492-301f-4053-ac5e-EXAMPLE6441aa",
  "Name": "ebs-data-events",
  "Status": "ENABLED",
  "AdvancedEventSelectors": [
    {
      "Name": "Log all EBS direct APIs on EBS snapshots",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Data"
          ]
        },
        {
          "Field": "resources.type",
          "Equals": [
            "AWS::EC2::Snapshot"
          ]
        }
      ]
    }
  ]
}
```

```

    ],
    "MultiRegionEnabled": true,
    "OrganizationEnabled": false,
    "BillingMode": "EXTENDABLE_RETENTION_PRICING",
    "RetentionPeriod": 366,
    "TerminationProtectionEnabled": true,
    "CreatedTimestamp": "2023-11-04T15:57:33.701000+00:00",
    "UpdatedTimestamp": "2023-11-20T20:37:34.228000+00:00"
  }
}

```

Topics

- [Include all Amazon S3 events for a specific bucket](#)
- [Include Amazon S3 on AWS Outposts events](#)

Include all Amazon S3 events for a specific bucket

The following example shows how to create an event data store to include all data events for all Amazon S3 objects in a specific general purpose S3 bucket and exclude AWS service events and events generated by the bucket-scanner-role user identity. The value for S3 events for the `resources.type` field is `AWS::S3::Object`. Because the ARN values for S3 objects and S3 buckets are slightly different, you must add the `StartsWith` operator for `resources.ARN` to capture all events.

```

aws cloudtrail create-event-data-store --name "EventDataStoreName" --multi-region-
enabled \
--advanced-event-selectors \
'[
  {
    "Name": "S3EventSelector",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Data"] },
      { "Field": "resources.type", "Equals": ["AWS::S3::Object"] },
      { "Field": "resources.ARN", "StartsWith": ["arn:partition:s3:::amzn-s3-
demo-bucket/"] },
      { "Field": "userIdentity.arn", "NotStartsWith":
["arn:aws:sts::123456789012:assumed-role/bucket-scanner-role"]},
      { "Field": "eventType", "NotEquals": ["AwsServiceEvent"]}
    ]
  }
]'

```

The command returns the following example output.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/
EXAMPLE492-301f-4053-ac5e-EXAMPLE441aa",
  "Name": "EventDataStoreName",
  "Status": "ENABLED",
  "AdvancedEventSelectors": [
    {
      "Name": "S3EventSelector",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Data"
          ]
        },
        {
          "Field": "resources.ARN",
          "StartsWith": [
            "arn:partition:s3::amzn-s3-demo-bucket/"
          ]
        },
        {
          "Field": "resources.type",
          "Equals": [
            "AWS::S3::Object"
          ]
        },
        {
          "Field": "userIdentity.arn",
          "NotStartsWith": [
            "arn:aws:sts::123456789012:assumed-role/bucket-scanner-role"
          ]
        },
        {
          "Field": "eventType",
          "NotEquals": [
            "AwsServiceEvent"
          ]
        }
      ]
    }
  ],
}
```



```

    "MultiRegionEnabled": true,
    "OrganizationEnabled": false,
    "BillingMode": "EXTENDABLE_RETENTION_PRICING",
    "RetentionPeriod": 366,
    "TerminationProtectionEnabled": true,
    "CreatedTimestamp": "2024-11-04T15:57:33.701000+00:00",
    "UpdatedTimestamp": "2024-11-20T20:49:21.766000+00:00"
  }
}

```

Include Amazon S3 on AWS Outposts events

The following example shows how to create an event data store that includes all data events for all Amazon S3 on Outposts objects in your outpost.

```

aws cloudtrail create-event-data-store --name EventDataStoreName \
--advanced-event-selectors \
'[
  {
    "Name": "OutpostsEventSelector",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Data"] },
      { "Field": "resources.type", "Equals": ["AWS::S3Outposts::Object"] }
    ]
  }
]'

```

The command returns the following example output.

```

{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLEb4a8-99b1-4ec2-9258-EXAMPLEc890",
  "Name": "EventDataStoreName",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "OutpostsEventSelector",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Data"
          ]
        }
      ]
    }
  ]
}

```

```

        },
        {
            "Field": "resources.type",
            "Equals": [
                "AWS::S3Outposts::Object"
            ]
        }
    ]
}
],
"MultiRegionEnabled": true,
"OrganizationEnabled": false,
"BillingMode": "EXTENDABLE_RETENTION_PRICING",
"RetentionPeriod": 366,
"TerminationProtectionEnabled": true,
"CreatedTimestamp": "2023-02-20T21:00:17.673000+00:00",
"UpdatedTimestamp": "2023-02-20T21:00:17.820000+00:00"
}

```

Filtering data events by using advanced event selectors

This section describes how you can use advanced event selectors to create fine-grained selectors for logging data events, which can help you control costs by only logging the specific data events of interest.

For example:

- You can include or exclude specific API calls by adding a filter on the `eventName` field.
- You can include or exclude logging for specific resources by adding a filter on the `resources.ARN` field. For example, if you were logging S3 data events, you could exclude logging for the S3 bucket for your trail.
- You can choose to log only write-only events or read-only events by adding a filter on the `readOnly` field.

The following table describes the supported fields for filtering data events. For a list of supported fields for each CloudTrail event type, see [AdvancedEventSelector](#) in the *AWS CloudTrail API Reference*.

Field	Required	Valid operators	Description
eventCategory	Yes	Equals	This field is set to Data to log data events.
resources.type	Yes	Equals	This field is used to select the resource type for which you want to log data events. The Data events table shows the possible values.
readOnly	No	Equals	This is an optional field used to include or exclude data events based on the readOnly value. A value of true logs only read events. A value of false logs only write events. If you do not add this field, CloudTrail logs both read and write events.
eventName	No	EndsWith Equals NotEndsWith NotEquals NotStartsWith StartsWith	This is an optional field used to filter in or filter out any data event logged to CloudTrail, such as PutBucket or GetSnapshotBlock . If you're using the AWS CLI, you can specify multiple values by separating each value with a comma. If you're using the console, you can specify multiple values by creating a condition for each eventName you want to filter on.
resources.ARN	No	EndsWith Equals	This is an optional field used to exclude or include data events for a specific resource by providing the resources.ARN . You can use any operator with

Field	Required	Valid operators	Description
		NotEndsWith NotEquals NotStartsWith StartsWith	<code>resources.ARN</code> , but if you use <code>Equals</code> or <code>NotEquals</code> , the value must exactly match the ARN of a valid resource for the <code>resources.type</code> you've specified. To log all data events for all objects in a specific S3 bucket, use the <code>StartsWith</code> operator, and include only the bucket ARN as the matching value. If you're using the AWS CLI, you can specify multiple values by separating each value with a comma. If you're using the console, you can specify multiple values by creating a condition for each <code>resources.ARN</code> you want to filter on.
eventSource	No	EndsWith Equals NotEndsWith NotEquals NotStartsWith StartsWith	You can use it to include or exclude specific event sources. The <code>eventSource</code> is typically a short form of the service name without spaces plus <code>.amazonaws.com</code> . For example, you could set <code>eventSource Equals ec2.amazonaws.com</code> to log only Amazon EC2 data events.

Field	Required	Valid operators	Description
eventType	No	EndsWith Equals NotEndsWith NotEquals NotStartsWith StartsWith	The eventType to include or exclude. For example, you can set this field to <code>NotEquals AwsServiceEvent</code> to exclude AWS service events .
sessionCredentialFromConsole	No	Equals NotEquals	Include or exclude events originating from an AWS Management Console session. This field can be set to <code>Equals</code> or <code>NotEquals</code> with a value of <code>true</code> .
userIdentity.arn	No	EndsWith Equals NotEndsWith NotEquals NotStartsWith StartsWith	Include or exclude events for actions taken by specific IAM identities. For more information, see CloudTrail userIdentity element .

To log data events using the CloudTrail console, you choose the **Data events** option and then select the **Resource type** of interest when you are creating or updating a trail or event data store. The [Data events](#) table shows the possible resource types you can choose on the CloudTrail console.

Data events [Info](#)

Data events show information about the resource operations performed on or within a resource. [Additional charges apply](#)

Advanced event selectors are enabled [Switch to basic event selectors](#)

Use the following fields for fine-grained control over the data events captured by your trail.

▼ **Data event: S3** [Remove](#)

Resource type
Choose the resource type for which you want to log data events.

S3 ▼

Log selector template

Log all events ▼

Selector name - optional

Enter a name

1,000 character limit

► **JSON view**

[Add data event type](#)

To log data events with the AWS CLI, configure the `--advanced-event-selector` parameter to set the `eventCategory` equal to `Data` and the `resources.type` value equal to the resource type value for which you want to log data events. The [Data events](#) table lists the available resource types.

For example, if you wanted to log data events for all Cognito Identity pools, you'd configure the `--advanced-event-selectors` parameter to look like this:

```
--advanced-event-selectors '[
  {
    "Name": "Log Cognito data events on Identity pools",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Data"] },
      { "Field": "resources.type", "Equals": ["AWS::Cognito::IdentityPool"] }
    ]
  }
]
```

The preceding example logs all Cognito data events on Identity pools. You can further refine the advanced event selectors to filter on the `eventName`, `readOnly`, and `resources.ARN` fields to log specific events of interest or exclude events that aren't of interest.

You can configure advanced event selectors to filter data events based on multiple fields. For example, you can configure advanced event selectors to log all Amazon S3 `PutObject` and `DeleteObject` API calls but exclude event logging for a specific S3 bucket as shown in the following example. Replace *amzn-s3-demo-bucket* with the name of your bucket.

```
--advanced-event-selectors
'[
  {
    "Name": "Log PutObject and DeleteObject events for all but one bucket",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Data"] },
      { "Field": "resources.type", "Equals": ["AWS::S3::Object"] },
      { "Field": "eventName", "Equals": ["PutObject","DeleteObject"] },
      { "Field": "resources.ARN", "NotStartsWith": ["arn:aws:s3:::amzn-s3-demo-
bucket/"] }
    ]
  }
]
```

You can also include multiple conditions for a field. For information on how multiple conditions are evaluated, see [How CloudTrail evaluates multiple conditions for a field](#).

You can use advanced event selectors to log both management and data events. To log data events for multiple resource types, add a field selector statement for each resource type that you want to log data events for.

Note

Trails can use either basic event selectors or advanced event selectors, but not both. If you apply advanced event selectors to a trail, any existing basic event selectors are overwritten. Selectors don't support the use of wildcards like `*`. To match multiple values with a single condition, you may use `StartsWith`, `EndsWith`, `NotStartsWith`, or `NotEndsWith` to explicitly match the beginning or end of the event field.

Topics

- [How CloudTrail evaluates multiple conditions for a field](#)
- [AWS CLI examples for filtering data events](#)

How CloudTrail evaluates multiple conditions for a field

For advanced event selectors, CloudTrail evaluates multiple conditions for a field as follows:

- DESELECT operators are AND'd together. If any of the DESELECT operator conditions are met, the event is not delivered. These are the valid DESELECT operators for advanced event selectors:
 - NotEndsWith
 - NotEquals
 - NotStartsWith
- SELECT operators are OR'd together. These are the valid SELECT operators for advanced event selectors:
 - EndsWith
 - Equals
 - StartsWith
- Combinations of SELECT and DESELECT operators follow the above rules and both groups are AND'd together.

Example showing multiple conditions for the `resources.ARN` field

The following example event selector statement collects data events for the `AWS::S3::Object` resource type and applies multiple conditions on the `resources.ARN` field.

```
{
  "Name": "S3Select",
  "FieldSelectors": [
    {
      "Field": "eventCategory",
      "Equals": [
        "Data"
      ]
    },
    {
      "Field": "resources.type",
      "Equals": [
```



```

        "AWS::S3::Object"
    ],
    },
    {
        "Field": "resources.ARN",
        "Equals": [
            "arn:aws:s3:::amzn-s3-demo-bucket/object1"
        ],
        "StartsWith": [
            "arn:aws:s3:::amzn-s3-demo-bucket/"
        ],
        "EndsWith": [
            "object3"
        ],
        "NotStartsWith": [
            "arn:aws:s3:::amzn-s3-demo-bucket/deselect"
        ],
        "NotEndsWith": [
            "object5"
        ],
        "NotEquals": [
            "arn:aws:s3:::amzn-s3-demo-bucket/object6"
        ]
    }
]
}

```

In the preceding example, Amazon S3 data events for the `AWS::S3::Object` resource will be delivered if:

1. None of these DESELECT operator conditions are met:

- the `resources.ARN` field `NotStartsWith` the value `arn:aws:s3:::amzn-s3-demo-bucket/deselect`
- the `resources.ARN` field `NotEndsWith` the value `object5`
- the `resources.ARN` field `NotEquals` the value `arn:aws:s3:::amzn-s3-demo-bucket/object6`

2. At least one of these SELECT operator conditions is met:

- the `resources.ARN` field `Equals` the value `arn:aws:s3:::amzn-s3-demo-bucket/object1`
- the `resources.ARN` field `StartsWith` the value `arn:aws:s3:::amzn-s3-demo-bucket/`

- the `resources.ARN` field `EndsWith` the value `object3`

Based on the evaluation logic:

1. Data events for `amzn-s3-demo-bucket/object1` will be delivered because it matches the value for the `Equals` operator and doesn't match any of the values for the `NotStartsWith`, `NotEndsWith`, and `NotEquals` operators.
2. Data event for `amzn-s3-demo-bucket/object2` will be delivered because it matches the value for the `StartsWith` operator and doesn't match any of the values for the `NotStartsWith`, `NotEndsWith`, and `NotEquals` operators.
3. Data events for `amzn-s3-demo-bucket1/object3` will be delivered because it matches the `EndsWith` operator and doesn't match any of the values for the `NotStartsWith`, `NotEndsWith`, and `NotEquals` operators.
4. Data events for `arn:aws:s3:::amzn-s3-demo-bucket/deselectObject4` will not be delivered because it matches the condition for the `NotStartsWith` even though it matches the condition for the `StartsWith` operator.
5. Data events for `arn:aws:s3:::amzn-s3-demo-bucket/object5` will not be delivered because it matches the condition for the `NotEndsWith` even though it matches the condition for the `StartsWith` operator.
6. Data events for the `arn:aws:s3:::amzn-s3-demo-bucket/object6` will not be delivered because it matches the condition for the `NotEquals` operator even though it matches the condition for the `StartsWith` operator.

AWS CLI examples for filtering data events

This section provides AWS CLI examples showing how to filter data events on different fields. For additional AWS CLI examples, see [Log data events for trails by using advanced event selectors](#) and [Logging data events for event data stores with the AWS CLI](#).

For information about how to log data events using the console, see [Logging data events with the AWS Management Console](#).

Examples:

- [Example 1: Filtering on the `eventName` field](#)
- [Example 2: Filtering on the `resources.ARN` and `userIdentity.arn` fields](#)

- [Example 3: Filtering on the `resources.type` and `eventName` fields to exclude individual objects deleted by an Amazon S3 `DeleteObjects` event](#)

Example 1: Filtering on the `eventName` field

In the first example, the `--advanced-event-selectors` for a trail are configured to log only the `GetObject`, `PutObject`, and `DeleteObject` API calls for Amazon S3 objects in general purpose buckets.

```
aws cloudtrail put-event-selectors \  
--trail-name trailName \  
--advanced-event-selectors '[  
  {  
    "Name": "Log GetObject, PutObject and DeleteObject S3 data events",  
    "FieldSelectors": [  
      { "Field": "eventCategory", "Equals": ["Data"] },  
      { "Field": "resources.type", "Equals": ["AWS::S3::Object"] },  
      { "Field": "eventName", "Equals": ["GetObject","PutObject","DeleteObject"] }  
    ]  
  }  
]'
```

The next example creates a new event data store that logs data events for EBS Direct APIs but excludes `ListChangedBlocks` API calls. You can use the [update-event-data-store](#) command to update an existing event data store.

```
aws cloudtrail create-event-data-store \  
--name "eventDataStoreName"  
--advanced-event-selectors '[  
  {  
    "Name": "Log all EBS Direct API data events except ListChangedBlocks",  
    "FieldSelectors": [  
      { "Field": "eventCategory", "Equals": ["Data"] },  
      { "Field": "resources.type", "Equals": ["AWS::EC2::Snapshot"] },  
      { "Field": "eventName", "NotEquals": ["ListChangedBlocks"] }  
    ]  
  }  
]'
```

Example 2: Filtering on the `resources.ARN` and `userIdentity.arn` fields

The following example shows how to include all data events for all Amazon S3 objects in a specific general purpose S3 bucket but exclude events generated by the `bucket-scanner-role` `userIdentity`. The value for S3 events for the `resources.type` field is `AWS::S3::Object`. Because the ARN values for S3 objects and S3 buckets are slightly different, you must add the `StartsWith` operator for `resources.ARN`.

```
aws cloudtrail put-event-selectors \
--trail-name trailName \
--advanced-event-selectors \
'[
  {
    "Name": "S3EventSelector",
    "FieldSelectors": [
      { "Field": "eventCategory", "Equals": ["Data"] },
      { "Field": "resources.type", "Equals": ["AWS::S3::Object"] },
      { "Field": "resources.ARN", "StartsWith": ["arn:partition:s3::amzn-s3-
demo-bucket/"] },
      { "Field": "userIdentity.arn", "NotStartsWith":
["arn:aws:sts::123456789012:assumed-role/bucket-scanner-role"]}
    ]
  }
]
```

Example 3: Filtering on the `resources.type` and `eventName` fields to exclude individual objects deleted by an Amazon S3 DeleteObjects event

The following example shows how to include all data events for all Amazon S3 objects in a specific general purpose Amazon S3 bucket but exclude the individual objects deleted by the `DeleteObject` operation. The value for S3 events for the `resources.type` field is `AWS::S3::Object`. The value for the event name is `DeleteObject`.

```
aws cloudtrail put-event-selectors \
--trail-name trailName \
--advanced-event-selectors \

{
  "Name": "Exclude Events for DeleteObject operation",
  "FieldSelectors": [
    {
      "Field": "eventCategory",
```

```

    "Equals": [
      "Data"
    ],
  },
  {
    "Field": "resources.type",
    "Equals": [
      "AWS::S3::Object"
    ]
  },
  {
    "Field": "eventName",
    "NotEquals": [
      "DeleteObject"
    ]
  }
]
},
{
  "Name": "Exclude DeleteObject Events for individual objects deleted by
DeleteObjects Operation",
  "FieldSelectors": [
    {
      "Field": "eventCategory",
      "Equals": [
        "Data"
      ]
    },
    {
      "Field": "resources.type",
      "Equals": [
        "AWS::S3::Object"
      ]
    },
    {
      "Field": "eventName",
      "Equals": [
        "DeleteObject"
      ]
    },
    {
      "Field": "eventType",
      "NotEquals": [
        "AwsServiceEvent"
      ]
    }
  ]
}

```

```
]
  }
]
}
] (edited)
```

Logging data events for AWS Config compliance

If you are using AWS Config conformance packs to help your enterprise maintain compliance with formalized standards such as those required by Federal Risk and Authorization Management Program (FedRAMP) or National Institute of Standards and Technology (NIST), conformance packs for compliance frameworks generally require you to log data events for Amazon S3 buckets, at minimum. Conformance packs for compliance frameworks include a [managed rule](#) called [cloudtrail-s3-dataevents-enabled](#) that checks for S3 data event logging in your account. Many conformance packs that are not associated with compliance frameworks also require S3 data event logging. The following are examples of conformance packs that include this rule.

- [Operational Best Practices for AWS Well-Architected Framework Security Pillar](#)
- [Operational Best Practices for FDA Title 21 CFR Part 11](#)
- [Operational Best Practices for FFIEC](#)
- [Operational Best Practices for FedRAMP\(Moderate\)](#)
- [Operational Best Practices for HIPAA Security](#)
- [Operational Best Practices for K-ISMS](#)
- [Operational Best Practices for Logging](#)

For a full list of sample conformance packs available in AWS Config, see [Conformance pack sample templates](#) in the *AWS Config Developer Guide*.

Logging data events with the AWS SDKs

Run the [GetEventSelectors](#) operation to see whether your trail is logging data events. You can configure your trails to log data events by running the [PutEventSelectors](#) operation. For more information, see the [AWS CloudTrail API Reference](#).

Run the [GetEventDataStore](#) operation to see whether your event data store is logging data events. You can configure your event data stores to include data events by running the [CreateEventDataStore](#) or [UpdateEventDataStore](#) operations and specifying advanced event

selectors. For more information, see [Create, update, and manage event data stores with the AWS CLI](#) and the [AWS CloudTrail API Reference](#).

Logging network activity events

CloudTrail network activity events enable VPC endpoint owners to record AWS API calls made using their VPC endpoints from a private VPC to the AWS service. Network activity events provide visibility into the resource operations performed within a VPC. For example, logging network activity events can help VPC endpoint owners detect when credentials from outside their organization attempt to access their VPC endpoints.

You can log network activity events for the following services:

- AWS AppConfig
- AWS App Mesh
- Amazon Athena
- AWS B2B Data Interchange
- AWS Backup gateway
- Amazon Bedrock
- Billing and Cost Management
- AWS Pricing Calculator
- AWS Cost Explorer
- AWS Cloud Control API
- AWS CloudHSM
- AWS Cloud Map
- AWS CloudFormation
- AWS CloudTrail
- Amazon CloudWatch
- CloudWatch Application Signals
- AWS CodeDeploy
- Amazon Comprehend Medical
- AWS Config
- AWS Data Exports

- Amazon Data Firehose
- AWS Directory Service
- Amazon DynamoDB
- Amazon EC2
- Amazon Elastic Container Service
- Amazon Elastic File System
- Elastic Load Balancing
- Amazon EventBridge
- Amazon EventBridge Scheduler
- Amazon Fraud Detector
- AWS Free Tier
- Amazon FSx
- AWS Glue
- AWS HealthLake
- AWS IoT FleetWise
- AWS IoT Secure Tunneling
- AWS Invoicing
- Amazon Keyspaces (for Apache Cassandra)
- AWS KMS
- AWS Lake Formation
- AWS Lambda
- AWS License Manager
- Amazon Lookout for Equipment
- Amazon Lookout for Vision
- Amazon Personalize
- Amazon Q Business
- Amazon Rekognition
- Amazon Relational Database Service
- Amazon S3

Note

Amazon S3 [Multi-Region Access Points](#) are not supported.

- Amazon SageMaker AI
- AWS Secrets Manager
- Amazon Simple Notification Service
- Amazon Simple Queue Service
- Amazon Simple Workflow Service
- AWS Storage Gateway
- AWS Systems Manager Incident Manager
- Amazon Textract
- Amazon Transcribe
- Amazon Translate
- AWS Transform
- Amazon Verified Permissions
- Amazon WorkMail

You can configure both trails and event data stores to log network activity events.

By default, trails and event data stores do not log network activity events. Additional charges apply for network activity events. For more information, see [AWS CloudTrail Pricing](#).

Contents

- [Advanced event selector fields for network activity events](#)
- [Logging network activity events with the AWS Management Console](#)
 - [Update an existing trail to log network activity events](#)
 - [Update an existing event data store to log network activity events](#)
- [Logging network activity events with the AWS Command Line Interface](#)
 - [Examples: Logging network activity events for trails](#)
 - [Example: Log network activity events for CloudTrail operations](#)
 - [Example: Log VpceAccessDenied events for AWS KMS](#)

- [Example: Log VpceAccessDenied events for Amazon S3](#)
- [Example: Log EC2 VpceAccessDenied events over a specific VPC endpoint](#)
- [Example: Log all management events and network activity events for multiple event sources](#)
- [Examples: Logging network activity events for event data stores](#)
 - [Example: Log all network activity events for CloudTrail operations](#)
 - [Example: Log VpceAccessDenied events for AWS KMS](#)
 - [Example: Log EC2 VpceAccessDenied events over a specific VPC endpoint](#)
 - [Example: Log VpceAccessDenied events for Amazon S3](#)
 - [Example: Log all management events and network activity events for multiple event sources](#)
- [Logging events with the AWS SDKs](#)

Advanced event selector fields for network activity events

You configure advanced event selectors to log network activity events by specifying the event source for which you want to log activity. You can configure advanced event selectors using the AWS SDKs, AWS CLI, or CloudTrail console.

The following advanced event selector fields are required to log network activity events:

- **eventCategory** – To log network activity events, the value must be `NetworkActivity`. **eventCategory** can only use the `Equals` operator.
- **eventSource** – The event source for which you want to log network activity events. **eventSource** can only use the `Equals` operator. If you want to log network activity events for multiple event sources, you must create a separate field selector for each event source.

Valid values include:

- `appconfig.amazonaws.com`
- `application-signals.amazonaws.com`
- `appmesh.amazonaws.com`
- `athena.amazonaws.com`
- `b2bi.amazonaws.com`
- `backup-gateway.amazonaws.com`

- `bcm-data-exports.amazonaws.com`
- `bcm-pricing-calculator.amazonaws.com`
- `bedrock.amazonaws.com`
- `billing.amazonaws.com`
- `cassandra.amazonaws.com`
- `ce.amazonaws.com`
- `cloudcontrolapi.amazonaws.com`
- `cloudformation.amazonaws.com`
- `cloudhsm.amazonaws.com`
- `cloudtrail.amazonaws.com`
- `codedeploy.amazonaws.com`
- `comprehend.amazonaws.com`
- `comprehendmedical.amazonaws.com`
- `config.amazonaws.com`
- `ds.amazonaws.com`
- `dynamodb.amazonaws.com`
- `ec2.amazonaws.com`
- `ecs.amazonaws.com`
- `elasticfilesystem.amazonaws.com`
- `elasticloadbalancing.amazonaws.com`
- `events.amazonaws.com`
- `firehose.amazonaws.com`
- `frauddetector.amazonaws.com`
- `freetier.amazonaws.com`
- `fsx.amazonaws.com`
- `glue.amazonaws.com`
- `healthlake.amazonaws.com`
- `invoicing.amazonaws.com`
- `iotfleetwise.amazonaws.com`
- `iotsecuredtunneling.amazonaws.com`

- kms.amazonaws.com
- lakeformation.amazonaws.com
- lambda.amazonaws.com
- license-manager.amazonaws.com
- lookoutequipment.amazonaws.com
- lookoutvision.amazonaws.com
- monitoring.amazonaws.com
- personalize.amazonaws.com
- qbusiness.amazonaws.com
- rds.amazonaws.com
- rekognition.amazonaws.com
- rolesanywhere.amazonaws.com
- s3.amazonaws.com
- sagemaker.amazonaws.com
- scheduler.amazonaws.com
- secretsmanager.amazonaws.com
- servicediscovery.amazonaws.com
- sns.amazonaws.com
- sqs.amazonaws.com
- ssm-contacts.amazonaws.com
- storagegateway.amazonaws.com
- swf.amazonaws.com
- textract.amazonaws.com
- transcribe.amazonaws.com
- transcribestreaming.amazonaws.com
- transform.amazonaws.com
- translate.amazonaws.com
- user-subscriptions.amazonaws.com
- verifiedpermissions.amazonaws.com
- voiceid.amazonaws.com

- `workmail.amazonaws.com`
- `workmailmessageflow.amazonaws.com`

The following advanced event selector fields are optional:

- `eventName` – The requested action that you want to filter on. For example, `CreateKey` or `ListKeys`. `eventName` can use any operator.
- `errorCode` – The requested error code that you want to filter on. Currently, the only valid `errorCode` is `VpceAccessDenied`. You can use only the `Equals` operator with `errorCode`.
- `vpcEndpointId` – Identifies the VPC endpoint that the operation passed through. You can use any operator with `vpcEndpointId`.

Network activity events are not logged by default when you create a trail or event data store. To record CloudTrail network activity events, you must explicitly configure each event source for which you want to collect activity.

Additional charges apply for logging network activity events. For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

Logging network activity events with the AWS Management Console

You can update an existing trail or event data store to log network activity events using the console.

Topics

- [Update an existing trail to log network activity events](#)
- [Update an existing event data store to log network activity events](#)

Update an existing trail to log network activity events

Use the following procedure to update an existing trail to log network activity events.

Note

Additional charges apply for logging network activity events. For CloudTrail pricing, see [AWS CloudTrail Pricing](#).

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the left navigation pane of the CloudTrail console, open the **Trails** page, and choose a trail name.
3. If your trail is logging data events using basic event selectors, you'll need to switch to advanced event selectors to log network activity events.

Take these steps to switch to advanced event selectors:

- a. In the **Data events** area, take note of the current data event selectors. Switching to advanced event selectors will clear out any existing data event selectors.
 - b. Choose **Edit** and then choose **Switch to advanced event selectors**.
 - c. Reapply your data event selections using advanced event selectors. For more information, see [Updating an existing trail to log data events with advanced event selectors using the console](#).
4. In **Network activity events**, choose **Edit**.

To log network activity events, take the following steps:

- a. From **Network activity event source**, choose the source for network activity events.
- b. In **Log selector template**, choose a template. You can choose to log all network activity events, log all network activity access denied events, or choose **Custom** to build a custom log selector to filter on multiple fields, such as `eventName` and `vpcEndpointId`.
- c. (Optional) Enter a name to identify the selector. The selector name is listed as **Name** in the advanced event selector and is viewable if you expand the **JSON view**.
- d. In **Advanced event selectors** build expressions by choosing values for **Field**, **Operator**, and **Value**. You can skip this step if you are using a predefined log template.
 - i. For excluding or including network activity events, you can choose from the following fields in the console.
 - **eventName** – You can use any operator with `eventName`. You can use it to include or exclude any event, such as `CreateKey`.
 - **errorCode** – You can use it to filter on an error code. Currently, the only supported `errorCode` is `VpceAccessDenied`.

- **vpcEndpointId** – Identifies the VPC endpoint that the operation passed through. You can use any operator with **vpcEndpointId**.
 - ii. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions.
 - iii. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields.
 - e. To add another event source for which you want to log network activity events, choose **Add network activity event selector**.
 - f. Optionally, expand **JSON view** to see your advanced event selectors as a JSON block.
5. Choose **Save changes** to save your changes.

Update an existing event data store to log network activity events

Use the following procedure to update an existing event data store to log network activity events.

Note

You can only log network activity events on event data stores of type **CloudTrail events**.

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the left navigation pane of the CloudTrail console, under **Lake**, choose **Event data stores**.
3. Choose the event data store name.
4. In **Network activity events**, choose **Edit**.

To log network activity events, take the following steps:

- a. From **Network activity event source**, choose the source for network activity events.
- b. In **Log selector template**, choose a template. You can choose to log all network activity events, log all network activity access denied events, or choose **Custom** to build a custom log selector to filter on multiple fields, such as **eventName** and **vpcEndpointId**.
- c. (Optional) Enter a name to identify the selector. The selector name is listed as **Name** in the advanced event selector and is viewable if you expand the **JSON view**.

- d. In **Advanced event selectors** build expressions by choosing values for **Field**, **Operator**, and **Value**. You can skip this step if you are using a predefined log template.
 - i. For excluding or including network activity events, you can choose from the following fields in the console.
 - **eventName** – You can use any operator with eventName. You can use it to include or exclude any event, such as CreateKey.
 - **errorCode** – You can use it to filter on an error code. Currently, the only supported errorCode is VpceAccessDenied.
 - **vpcEndpointId** – Identifies the VPC endpoint that the operation passed through. You can use any operator with vpcEndpointId.
 - ii. For each field, choose **+ Condition** to add as many conditions as you need, up to a maximum of 500 specified values for all conditions.
 - iii. Choose **+ Field** to add additional fields as required. To avoid errors, do not set conflicting or duplicate values for fields.
 - e. To add another event source for which you want to log network activity events, choose **Add network activity event selector**.
 - f. Optionally, expand **JSON view** to see your advanced event selectors as a JSON block.
5. Choose **Save changes** to save your changes.

Logging network activity events with the AWS Command Line Interface

You can configure your trails or event data stores to log network activity events using the AWS CLI.

Topics

- [Examples: Logging network activity events for trails](#)
- [Examples: Logging network activity events for event data stores](#)

Examples: Logging network activity events for trails

You can configure your trails to log network activity events using the AWS CLI. Run the [put-event-selectors](#) command to configure the advanced event selectors for your trail.

To see whether your trail is logging network activity events, run the [get-event-selectors](#) command.

Topics

- [Example: Log network activity events for CloudTrail operations](#)
- [Example: Log VpceAccessDenied events for AWS KMS](#)
- [Example: Log VpceAccessDenied events for Amazon S3](#)
- [Example: Log EC2 VpceAccessDenied events over a specific VPC endpoint](#)
- [Example: Log all management events and network activity events for multiple event sources](#)

Example: Log network activity events for CloudTrail operations

The following example shows how to configure your trail to include all network activity events for CloudTrail API operations, such as `CreateTrail` and `CreateEventDataStore` calls. The value for the `eventSource` field is `cloudtrail.amazonaws.com`.

```
aws cloudtrail put-event-selectors /
--trail-name TrailName /
--region region /
--advanced-event-selectors '[
    {
        "Name": "Audit all CloudTrail API calls through VPC endpoints",
        "FieldSelectors": [
            {
                "Field": "eventCategory",
                "Equals": ["NetworkActivity"]
            },
            {
                "Field": "eventSource",
                "Equals": ["cloudtrail.amazonaws.com"]
            }
        ]
    }
]
```

The command returns the following example output.

```
{
  "TrailARN": "arn:aws:cloudtrail:us-east-1:111122223333:trail/TrailName",
  "AdvancedEventSelectors": [
    {
      "Name": "Audit all CloudTrail API calls through VPC endpoints",
```

```

    "FieldSelectors": [
      {
        "Field": "eventCategory",
        "Equals": [
          "NetworkActivity"
        ]
      },
      {
        "Field": "eventSource",
        "Equals": [
          "cloudtrail.amazonaws.com"
        ]
      }
    ]
  }
]
}

```

Example: Log VpceAccessDenied events for AWS KMS

The following example shows how to configure your trail to include VpceAccessDenied events for AWS KMS. This example sets the errorCode field equal to VpceAccessDenied events and the eventSource field equal to kms.amazonaws.com.

```

aws cloudtrail put-event-selectors \
--region region /
--trail-name TrailName /
--advanced-event-selectors '[
  {
    "Name": "Audit AccessDenied AWS KMS events through VPC endpoints",
    "FieldSelectors": [
      {
        "Field": "eventCategory",
        "Equals": ["NetworkActivity"]
      },
      {
        "Field": "eventSource",
        "Equals": ["kms.amazonaws.com"]
      },
      {
        "Field": "errorCode",
        "Equals": ["VpceAccessDenied"]
      }
    ]
  }
]

```

```
    }
  ]
}
```

The command returns the following example output.

```
{
  "TrailARN": "arn:aws:cloudtrail:us-east-1:111122223333:trail/TrailName",
  "AdvancedEventSelectors": [
    {
      "Name": "Audit AccessDenied AWS KMS events through VPC endpoints",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "NetworkActivity"
          ]
        },
        {
          "Field": "eventSource",
          "Equals": [
            "kms.amazonaws.com"
          ]
        },
        {
          "Field": "errorCode",
          "Equals": [
            "VpceAccessDenied"
          ]
        }
      ]
    }
  ]
}
```

Example: Log VpceAccessDenied events for Amazon S3

The following example shows how to configure your trail to include VpceAccessDenied events for Amazon S3. This example sets the errorCode field equal to VpceAccessDenied events and the eventSource field equal to s3.amazonaws.com.

```
aws cloudtrail put-event-selectors \  
--region region /  
--trail-name TrailName /  
--advanced-event-selectors '[  
  {  
    "Name": "Log S3 access denied network activity events",  
    "FieldSelectors": [  
      {  
        "Field": "eventCategory",  
        "Equals": ["NetworkActivity"]  
      },  
      {  
        "Field": "eventSource",  
        "Equals": ["s3.amazonaws.com"]  
      },  
      {  
        "Field": "errorCode",  
        "Equals": ["VpceAccessDenied"]  
      }  
    ]  
  }  
'
```

The command returns the following example output.

```
{  
  "TrailARN": "arn:aws:cloudtrail:us-east-1:111122223333:trail/TrailName",  
  "AdvancedEventSelectors": [  
    {  
      "Name": "Log S3 access denied network activity events",  
      "FieldSelectors": [  
        {  
          "Field": "eventCategory",  
          "Equals": [  
            "NetworkActivity"  
          ]  
        },  
        {  
          "Field": "eventSource",  
          "Equals": [  
            "s3.amazonaws.com"  
          ]  
        }  
      ],  
    }  
  ],  
}
```

```

        {
            "Field": "errorCode",
            "Equals": [
                "VpceAccessDenied"
            ]
        }
    ]
}

```

Example: Log EC2 VpceAccessDenied events over a specific VPC endpoint

The following example shows how to configure your trail to include VpceAccessDenied events for Amazon EC2 for a specific VPC endpoint. This example sets the errorCode field equal to VpceAccessDenied events, the eventSource field equal to ec2.amazonaws.com, and the vpcEndpointId equal to the VPC endpoint of interest.

```

aws cloudtrail put-event-selectors \
--region region /
--trail-name TrailName /
--advanced-event-selectors '[
    {
        "Name": "Audit AccessDenied EC2 events over a specific VPC endpoint",
        "FieldSelectors": [
            {
                "Field": "eventCategory",
                "Equals": ["NetworkActivity"]
            },
            {
                "Field": "eventSource",
                "Equals": ["ec2.amazonaws.com"]
            },
            {
                "Field": "errorCode",
                "Equals": ["VpceAccessDenied"]
            },
            {
                "Field": "vpcEndpointId",
                "Equals": ["vpce-example8c1b6b9b7"]
            }
        ]
    }
]

```

```
]'
```

The command returns the following example output.

```
{
  "TrailARN": "arn:aws:cloudtrail:us-east-1:111122223333:trail/TrailName",
  "AdvancedEventSelectors": [
    {
      "Name": "Audit AccessDenied EC2 events over a specific VPC endpoint",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "NetworkActivity"
          ]
        },
        {
          "Field": "eventSource",
          "Equals": [
            "ec2.amazonaws.com"
          ]
        },
        {
          "Field": "errorCode",
          "Equals": [
            "VpceAccessDenied"
          ]
        },
        {
          "Field": "vpcEndpointId",
          "Equals": [
            "vpce-example8c1b6b9b7"
          ]
        }
      ]
    }
  ]
}
```

Example: Log all management events and network activity events for multiple event sources

The following example configures a trail to log management events and all network activity events for the CloudTrail, Amazon EC2, AWS KMS, AWS Secrets Manager, and Amazon S3 event sources.

```
aws cloudtrail put-event-selectors \  
--region region /  
--trail-name TrailName /  
--advanced-event-selectors '[  
  {  
    "Name": "Log all management events",  
    "FieldSelectors": [  
      {  
        "Field": "eventCategory",  
        "Equals": ["Management"]  
      }  
    ]  
  },  
  {  
    "Name": "Log all network activity events for CloudTrail APIs",  
    "FieldSelectors": [  
      {  
        "Field": "eventCategory",  
        "Equals": ["NetworkActivity"]  
      },  
      {  
        "Field": "eventSource",  
        "Equals": ["cloudtrail.amazonaws.com"]  
      }  
    ]  
  },  
  {  
    "Name": "Log all network activity events for EC2",  
    "FieldSelectors": [  
      {  
        "Field": "eventCategory",  
        "Equals": ["NetworkActivity"]  
      },  
      {  
        "Field": "eventSource",  
        "Equals": ["ec2.amazonaws.com"]  
      }  
    ]  
  },  
  {  
    "Name": "Log all network activity events for KMS",  
    "FieldSelectors": [  
      {
```

```

        "Field": "eventCategory",
        "Equals": ["NetworkActivity"]
    },
    {
        "Field": "eventSource",
        "Equals": ["kms.amazonaws.com"]
    }
]
},
{
    "Name": "Log all network activity events for S3",
    "FieldSelectors": [
        {
            "Field": "eventCategory",
            "Equals": ["NetworkActivity"]
        },
        {
            "Field": "eventSource",
            "Equals": ["s3.amazonaws.com"]
        }
    ]
},
{
    "Name": "Log all network activity events for Secrets Manager",
    "FieldSelectors": [
        {
            "Field": "eventCategory",
            "Equals": ["NetworkActivity"]
        },
        {
            "Field": "eventSource",
            "Equals": ["secretsmanager.amazonaws.com"]
        }
    ]
}
]
'
```

The command returns the following example output.

```

{
    "TrailARN": "arn:aws:cloudtrail:us-east-1:123456789012:trail/TrailName",
    "AdvancedEventSelectors": [
        {
```



```

        "Name": "Log all management events",
        "FieldSelectors": [
            {
                "Field": "eventCategory",
                "Equals": [
                    "Management"
                ]
            }
        ]
    },
    {
        "Name": "Log all network activity events for CloudTrail APIs",
        "FieldSelectors": [
            {
                "Field": "eventCategory",
                "Equals": [
                    "NetworkActivity"
                ]
            },
            {
                "Field": "eventSource",
                "Equals": [
                    "cloudtrail.amazonaws.com"
                ]
            }
        ]
    },
    {
        "Name": "Log all network activity events for EC2",
        "FieldSelectors": [
            {
                "Field": "eventCategory",
                "Equals": [
                    "NetworkActivity"
                ]
            },
            {
                "Field": "eventSource",
                "Equals": [
                    "ec2.amazonaws.com"
                ]
            }
        ]
    }
],

```

```
{
  "Name": "Log all network activity events for KMS",
  "FieldSelectors": [
    {
      "Field": "eventCategory",
      "Equals": [
        "NetworkActivity"
      ]
    },
    {
      "Field": "eventSource",
      "Equals": [
        "kms.amazonaws.com"
      ]
    }
  ]
},
{
  "Name": "Log all network activity events for S3",
  "FieldSelectors": [
    {
      "Field": "eventCategory",
      "Equals": [
        "NetworkActivity"
      ]
    },
    {
      "Field": "eventSource",
      "Equals": [
        "s3.amazonaws.com"
      ]
    }
  ]
},
{
  "Name": "Log all network activity events for Secrets Manager",
  "FieldSelectors": [
    {
      "Field": "eventCategory",
      "Equals": [
        "NetworkActivity"
      ]
    }
  ],
}
```

```
        "Field": "eventSource",
        "Equals": [
            "secretsmanager.amazonaws.com"
        ]
    }
}
]
```

Examples: Logging network activity events for event data stores

You can configure your event data stores to include network activity events using the AWS CLI. Use the [create-event-data-store](#) command to create a new event data store to log network activity events. Use the [update-event-data-store](#) command to update the advanced event selectors for an existing event data store.

To see whether your event data store includes network activity events, run the [get-event-data-store](#) command.

```
aws cloudtrail get-event-data-store --event-data-store EventDataStoreARN
```

Topics

- [Example: Log all network activity events for CloudTrail operations](#)
- [Example: Log VpceAccessDenied events for AWS KMS](#)
- [Example: Log EC2 VpceAccessDenied events over a specific VPC endpoint](#)
- [Example: Log VpceAccessDenied events for Amazon S3](#)
- [Example: Log all management events and network activity events for multiple event sources](#)

Example: Log all network activity events for CloudTrail operations

The following example shows how to create an event data store that includes all network activity events related to CloudTrail operations, such as calls to `CreateTrail` and `CreateEventDataStore`. The value for the `eventSource` field is set to `cloudtrail.amazonaws.com`.

```
aws cloudtrail create-event-data-store \  
--name "EventDataStoreName" \  

```

```
--advanced-event-selectors '[
  {
    "Name": "Audit all CloudTrail API calls over VPC endpoint",
    "FieldSelectors": [
      {
        "Field": "eventCategory",
        "Equals": ["NetworkActivity"]
      },
      {
        "Field": "eventSource",
        "Equals": ["cloudtrail.amazonaws.com"]
      }
    ]
  }
]
```

The command returns the following example output.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLE492-301f-4053-ac5e-EXAMPLE441aa",
  "Name": "EventDataStoreName",
  "Status": "ENABLED",
  "AdvancedEventSelectors": [
    {
      "Name": "Audit all CloudTrail API calls over VPC endpoint",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "NetworkActivity"
          ]
        },
        {
          "Field": "eventSource",
          "Equals": [
            "cloudtrail.amazonaws.com"
          ]
        }
      ]
    }
  ],
  "MultiRegionEnabled": true,
```

```

    "OrganizationEnabled": false,
    "RetentionPeriod": 366,
    "TerminationProtectionEnabled": true,
    "CreatedTimestamp": "2024-05-20T21:00:17.673000+00:00",
    "UpdatedTimestamp": "2024-05-20T21:00:17.820000+00:00"
  }

```

Example: Log VpceAccessDenied events for AWS KMS

The following example shows how to create an event data store to include VpceAccessDenied events for AWS KMS. This example sets the `errorCode` field equal to VpceAccessDenied events and the `eventSource` field equal to `kms.amazonaws.com`.

```

aws cloudtrail create-event-data-store \
--name EventDataStoreName \
--advanced-event-selectors '[
  {
    "Name": "Audit AccessDenied AWS KMS events over VPC endpoints",
    "FieldSelectors": [
      {
        "Field": "eventCategory",
        "Equals": ["NetworkActivity"]
      },
      {
        "Field": "eventSource",
        "Equals": ["kms.amazonaws.com"]
      },
      {
        "Field": "errorCode",
        "Equals": ["VpceAccessDenied"]
      }
    ]
  }
]'

```

The command returns the following example output.

```

{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLEb4a8-99b1-4ec2-9258-EXAMPLEc890",
  "Name": "EventDataStoreName",
  "Status": "CREATED",

```

```

    "AdvancedEventSelectors": [
      {
        "Name": "Audit AccessDenied AWS KMS events over VPC endpoints",
        "FieldSelectors": [
          {
            "Field": "eventCategory",
            "Equals": [
              "NetworkActivity"
            ]
          },
          {
            "Field": "eventSource",
            "Equals": [
              "kms.amazonaws.com"
            ]
          },
          {
            "Field": "errorCode",
            "Equals": [
              "VpceAccessDenied"
            ]
          }
        ]
      }
    ],
    "MultiRegionEnabled": true,
    "OrganizationEnabled": false,
    "RetentionPeriod": 366,
    "TerminationProtectionEnabled": true,
    "CreatedTimestamp": "2024-05-20T21:00:17.673000+00:00",
    "UpdatedTimestamp": "2024-05-20T21:00:17.820000+00:00"
  }
}

```

Example: Log EC2 VpceAccessDenied events over a specific VPC endpoint

The following example shows how to create an event data store to include VpceAccessDenied events for Amazon EC2 for a specific VPC endpoint. This example sets the errorCode field equal to VpceAccessDenied events, the eventSource field equal to ec2.amazonaws.com, and the vpcEndpointId equal to the VPC endpoint of interest.

```

aws cloudtrail create-event-data-store \
--name EventDataStoreName \
--advanced-event-selectors '[

```

```
{
  "Name": "Audit AccessDenied EC2 events over a specific VPC endpoint",
  "FieldSelectors": [
    {
      "Field": "eventCategory",
      "Equals": ["NetworkActivity"]
    },
    {
      "Field": "eventSource",
      "Equals": ["ec2.amazonaws.com"]
    },
    {
      "Field": "errorCode",
      "Equals": ["VpceAccessDenied"]
    },
    {
      "Field": "vpcEndpointId",
      "Equals": ["vpce-example8c1b6b9b7"]
    }
  ]
}
```

The command returns the following example output.

```
{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLEb4a8-99b1-4ec2-9258-EXAMPLEc890",
  "Name": "EventDataStoreName",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Audit AccessDenied EC2 events over a specific VPC endpoint",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "NetworkActivity"
          ]
        },
        {
          "Field": "eventSource",
          "Equals": [
```

```

        "ec2.amazonaws.com"
      ],
    },
    {
      "Field": "errorCode",
      "Equals": [
        "VpceAccessDenied"
      ]
    },
    {
      "Field": "vpcEndpointId",
      "Equals": [
        "vpce-example8c1b6b9b7"
      ]
    }
  ]
}
],
"MultiRegionEnabled": true,
"OrganizationEnabled": false,
"RetentionPeriod": 366,
"TerminationProtectionEnabled": true,
"CreatedTimestamp": "2024-05-20T21:00:17.673000+00:00",
"UpdatedTimestamp": "2024-05-20T21:00:17.820000+00:00"
}

```

Example: Log VpceAccessDenied events for Amazon S3

The following example shows how to create an event data store to include VpceAccessDenied events for Amazon S3. This example sets the errorCode field equal to VpceAccessDenied events and the eventSource field equal to s3.amazonaws.com.

```

aws cloudtrail create-event-data-store \
--name EventDataStoreName \
--advanced-event-selectors '[
  {
    "Name": "Log S3 access denied network activity events",
    "FieldSelectors": [
      {
        "Field": "eventCategory",
        "Equals": ["NetworkActivity"]
      },
      {

```



```

        "Field": "eventSource",
        "Equals": ["s3.amazonaws.com"]
    },
    {
        "Field": "errorCode",
        "Equals": ["VpceAccessDenied"]
    }
]
}'

```

The command returns the following example output.

```

{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLEb4a8-99b1-4ec2-9258-EXAMPLEc890",
  "Name": "EventDataStoreName",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Log S3 access denied network activity events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "NetworkActivity"
          ]
        },
        {
          "Field": "eventSource",
          "Equals": [
            "s3.amazonaws.com"
          ]
        },
        {
          "Field": "errorCode",
          "Equals": [
            "VpceAccessDenied"
          ]
        }
      ]
    }
  ],
}
],

```

```

    "MultiRegionEnabled": true,
    "OrganizationEnabled": false,
    "RetentionPeriod": 366,
    "TerminationProtectionEnabled": true,
    "CreatedTimestamp": "2024-05-20T21:00:17.673000+00:00",
    "UpdatedTimestamp": "2024-05-20T21:00:17.820000+00:00"
  }

```

Example: Log all management events and network activity events for multiple event sources

The following examples updates an event data store that is currently logging only management events to also log network activity events for multiple event sources. To update an event data store to add new event selectors, run the `get-event-data-store` command to return the current advanced event selectors. Then, run the `update-event-data-store` command and pass in the `--advanced-event-selectors` that includes the current selectors plus any new selectors. To log network activity events for multiple event sources, include one selector for each event source that you want to log.

```

aws cloudtrail update-event-data-store \
--event-data-store arn:aws:cloudtrail:us-east-1:123456789012:eventdatastore/EXAMPLE-
f852-4e8f-8bd1-bcf6cEXAMPLE \
--advanced-event-selectors '[
  {
    "Name": "Log all management events",
    "FieldSelectors": [
      {
        "Field": "eventCategory",
        "Equals": ["Management"]
      }
    ]
  },
  {
    "Name": "Log all network activity events for CloudTrail APIs",
    "FieldSelectors": [
      {
        "Field": "eventCategory",
        "Equals": ["NetworkActivity"]
      },
      {
        "Field": "eventSource",
        "Equals": ["cloudtrail.amazonaws.com"]
      }
    ]
  }
]

```

```
]
},
{
  "Name": "Log all network activity events for EC2",
  "FieldSelectors": [
    {
      "Field": "eventCategory",
      "Equals": ["NetworkActivity"]
    },
    {
      "Field": "eventSource",
      "Equals": ["ec2.amazonaws.com"]
    }
  ]
},
{
  "Name": "Log all network activity events for KMS",
  "FieldSelectors": [
    {
      "Field": "eventCategory",
      "Equals": ["NetworkActivity"]},
    {
      "Field": "eventSource",
      "Equals": ["kms.amazonaws.com"]
    }
  ]
},
{
  "Name": "Log all network activity events for S3",
  "FieldSelectors": [
    {
      "Field": "eventCategory",
      "Equals": ["NetworkActivity"]
    },
    {
      "Field": "eventSource",
      "Equals": ["s3.amazonaws.com"]
    }
  ]
},
{
  "Name": "Log all network activity events for Secrets Manager",
  "FieldSelectors": [
    {
```

```

        "Field": "eventCategory",
        "Equals": ["NetworkActivity"]
    },
    {
        "Field": "eventSource",
        "Equals": ["secretsmanager.amazonaws.com"]
    }
]
}'

```

The command returns the following example output.

```

{
  "EventDataStoreArn": "arn:aws:cloudtrail:us-east-1:111122223333:eventdatastore/EXAMPLEb4a8-99b1-4ec2-9258-EXAMPLEc890",
  "Name": "EventDataStoreName",
  "Status": "CREATED",
  "AdvancedEventSelectors": [
    {
      "Name": "Log all management events",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "Management"
          ]
        }
      ]
    },
    {
      "Name": "Log all network activity events for CloudTrail APIs",
      "FieldSelectors": [
        {
          "Field": "eventCategory",
          "Equals": [
            "NetworkActivity"
          ]
        },
        {
          "Field": "eventSource",
          "Equals": [
            "cloudtrail.amazonaws.com"
          ]
        }
      ]
    }
  ]
}

```

```

        ]
    }
}
],
{
    "Name": "Log all network activity events for EC2",
    "FieldSelectors": [
        {
            "Field": "eventCategory",
            "Equals": [
                "NetworkActivity"
            ]
        },
        {
            "Field": "eventSource",
            "Equals": [
                "ec2.amazonaws.com"
            ]
        }
    ]
},
{
    "Name": "Log all network activity events for KMS",
    "FieldSelectors": [
        {
            "Field": "eventCategory",
            "Equals": [
                "NetworkActivity"
            ]
        },
        {
            "Field": "eventSource",
            "Equals": [
                "kms.amazonaws.com"
            ]
        }
    ]
},
{
    "Name": "Log all network activity events for S3",
    "FieldSelectors": [
        {
            "Field": "eventCategory",
            "Equals": [

```

```

        "NetworkActivity"
      ]
    },
    {
      "Field": "eventSource",
      "Equals": [
        "s3.amazonaws.com"
      ]
    }
  ],
},
{
  "Name": "Log all network activity events for Secrets Manager",
  "FieldSelectors": [
    {
      "Field": "eventCategory",
      "Equals": [
        "NetworkActivity"
      ]
    },
    {
      "Field": "eventSource",
      "Equals": [
        "secretsmanager.amazonaws.com"
      ]
    }
  ]
}
],
"MultiRegionEnabled": true,
"OrganizationEnabled": false,
"RetentionPeriod": 366,
"TerminationProtectionEnabled": true,
"CreatedTimestamp": "2024-11-20T21:00:17.673000+00:00",
"UpdatedTimestamp": "2024-11-20T21:00:17.820000+00:00"
}

```

Logging events with the AWS SDKs

Run the [GetEventSelectors](#) operation to see whether your trail is logging network activity events. You can configure your trails to log network activity events by running the [PutEventSelectors](#) operation. For more information, see the [AWS CloudTrail API Reference](#).

Run the [GetEventDataStore](#) operation to see whether your event data store is logging network activity events. You can configure your event data stores to include network activity events by running the [CreateEventDataStore](#) or [UpdateEventDataStore](#) operations and specifying advanced event selectors. For more information, see [Create, update, and manage event data stores with the AWS CLI](#) and the [AWS CloudTrail API Reference](#).

Enrich CloudTrail events by adding resource tag keys and IAM global condition keys

You can enrich CloudTrail management events and data events by adding resource tag keys, principal tag keys, and IAM global condition keys when you create or update an event data store. This allows you to categorize, search, and analyze CloudTrail events based on the business context, such as cost allocation and financial management, operations, and data security requirements. You can analyze events by running queries in CloudTrail Lake. You can also choose to [federate](#) your event data store and run queries in Amazon Athena. You can add resource tag keys and IAM global condition keys to an event data store using the [CloudTrail console](#), [AWS CLI](#), and SDKs.

Note

Resource tags that you add after resource creation or updates might experience a delay before those tags are reflected in CloudTrail events. CloudTrail events for resource deletions might not include tag information.

IAM global condition keys will always be visible in the output of a query, but might not be visible to the resource owner.

When you add resource tag keys to enriched events, CloudTrail includes the selected tag keys associated with the resources that were involved in the API call.

When you add IAM global condition keys to an event data store, CloudTrail includes information about the selected condition keys that were evaluated during the authorization process, including additional details about the principal, session, and the request itself.

Note

Configuring CloudTrail to include a condition key or principal tag does not mean that this condition key or principal tag will be present in every event. For example, if you've set up CloudTrail to include a specific global condition key but you don't see it in a particular

event, this indicates that the key wasn't relevant to the IAM policy evaluation for that action.

After you add resource tag keys or IAM condition keys, CloudTrail includes a `eventContext` field in CloudTrail events that provides the selected contextual information for the API action.

There are some exceptions when the event will not include the `eventContext` field, including the following:

- API events related to deleted resources might or might not have resource tags.
- The `eventContext` field will not have data for delayed events, and will not be present for events that were updated after the API call. For example, if there is a delay or outage for Amazon EventBridge, tags for events might remain out of date for some time after the outage is resolved. Some AWS services will experience longer delays. For more information, see [Resource tag updates in CloudTrail for enriched events](#).
- If you modify or delete the `AWSServiceRoleForCloudTrailEventContext` service-linked role used for enriched events, CloudTrail will not populate any resource tags into `eventContext`.

Note

The `eventContext` field is only present in events for event data stores that are configured to include resource tag keys, principal tag keys, and IAM global condition keys. Events delivered to **Event history**, Amazon EventBridge, viewable with the AWS CLI `lookup-events` command, and delivered to trails, will not include the `eventContext` field.

Topics

- [AWS services supporting resource tags](#)
- [AWS services supporting IAM global condition keys](#)
- [Event examples](#)

AWS services supporting resource tags

All AWS services support resource tags. For more information, see [Services that support the AWS Resource Groups Tagging API](#).

Resource tag updates in CloudTrail for enriched events

When configured to do so, CloudTrail captures information about resource tags and uses them to provide information in enriched events. When working with resource tags, there are certain conditions in which a resource tag might not be accurately reflected at the time of the system request for events. During standard operation, tags applied at resource creation time are always present and will experience minimal or no delays. However, the following services are expected to have delays in resource tag changes appearing in CloudTrail events:

- Amazon Chime Voice Connector
- AWS CloudTrail
- AWS CodeConnections
- Amazon DynamoDB
- Amazon ElastiCache
- Amazon Keyspaces (for Apache Cassandra)
- Amazon Kinesis
- Amazon Lex
- Amazon MemoryDB
- Amazon S3
- Amazon Security Lake
- AWS Direct Connect
- AWS IAM Identity Center
- AWS Key Management Service
- AWS Lambda
- AWS Marketplace Vendor Insights
- AWS Organizations
- AWS Payment Cryptography
- Amazon Simple Queue Service

Service outages can also cause delays in updates to resource tag information. In the event of a service outage delay, subsequent CloudTrail events will include an addendum field that includes

information about the resource tag change. This additional information will be used as specified to provide enriched CloudTrail events.

AWS services supporting IAM global condition keys

The following AWS services support IAM global condition keys for enriched events:

- AWS Certificate Manager
- AWS CloudTrail
- Amazon CloudWatch
- Amazon CloudWatch Logs
- AWS CodeBuild
- AWS CodeCommit
- AWS CodeDeploy
- Amazon Cognito Sync
- Amazon Comprehend
- Amazon Comprehend Medical
- Amazon Connect Voice ID
- AWS Control Tower
- Amazon Data Firehose
- Amazon Elastic Block Store
- Elastic Load Balancing
- AWS End User Messaging Social
- Amazon EventBridge
- Amazon EventBridge Scheduler
- Amazon Data Firehose
- Amazon FSx
- AWS HealthImaging
- AWS IoT Events
- AWS IoT FleetWise
- AWS IoT SiteWise

- AWS IoT TwinMaker
- AWS IoT Wireless
- Amazon Kendra
- AWS KMS
- AWS Lambda
- AWS License Manager
- Amazon Lookout for Equipment
- Amazon Lookout for Vision
- AWS Network Firewall
- AWS Payment Cryptography
- Amazon Personalize
- AWS Proton
- Amazon Rekognition
- Amazon SageMaker AI
- AWS Secrets Manager
- Amazon Simple Email Service (Amazon SES)
- Amazon Simple Notification Service (Amazon SNS)
- Amazon SQS
- AWS Step Functions
- AWS Storage Gateway
- Amazon SWF
- AWS Supply Chain
- Amazon Timestream
- Amazon Timestream for InfluxDB
- Amazon Transcribe
- AWS Transfer Family
- AWS Trusted Advisor
- Amazon WorkSpaces
- AWS X-Ray

Supported IAM global condition keys for enriched events

The following table lists the supported IAM global condition keys for CloudTrail enriched events, with example values:

Global Condition Keys and Sample Values

Key	Example value
aws:FederatedProvider	" <i>IdP</i> "
aws:TokenIssueTime	" <i>123456789</i> "
aws:MultiFactorAuthAge	"99"
aws:MultiFactorAuthPresent	" <i>true</i> "
aws:SourceIdentity	" <i>UserName</i> "
aws:PrincipalAccount	"111122223333"
aws:PrincipalArn	"arn:aws:iam:: <i>555555555555:role/myRole</i> "
aws:PrincipalIsAWSService	" <i>false</i> "
aws:PrincipalOrgID	" <i>o-rganization</i> "
aws:PrincipalOrgPaths	[" <i>o-rganization/path-of-org</i> "]
aws:PrincipalServiceName	" <i>cloudtrail.amazonaws.com</i> "
aws:PrincipalServiceNamesList	[" <i>cloudtrail.amazonaws.com</i> ", " <i>s3.amazonaws.com</i> "]
aws:PrincipalType	" <i>AssumedRole</i> "
aws:userid	" <i>userid</i> "
aws:username	" <i>username</i> "
aws:RequestedRegion	<i>us-east-2</i> "

Key	Example value
aws:SecureTransport	<i>"true"</i>
aws:ViaAWSService	<i>"false"</i>
aws:CurrentTime	<i>"2025-04-30 15:30:00 "</i>
aws:EpochTime	<i>"1746049800 "</i>
aws:SourceAccount	<i>"111111111111 "</i>
aws:SourceOrgID	<i>"o-rganization "</i>

Event examples

In the following example, the eventContext field includes IAM global condition key `aws:ViaAWSService` with a value of `false`, which indicates the API call was not made by an AWS service.

```
{
  "eventVersion": "1.11",
  "userIdentity": {
    "type": "AssumedRole",
    "principalId": "ASIAIOSFODNN7EXAMPLE",
    "arn": "arn:aws:sts::123456789012:assumed-role/admin",
    "accountId": "123456789012",
    "accessKeyId": "ASIAIOSFODNN7EXAMPLE",
    "sessionContext": {
      "sessionIssuer": {
        "type": "Role",
        "principalId": "ASIAIOSFODNN7EXAMPLE",
        "arn": "arn:aws:iam::123456789012:role/admin",
        "accountId": "123456789012",
        "userName": "admin"
      },
      "attributes": {
        "creationDate": "2025-01-22T22:05:56Z",
        "mfaAuthenticated": "false"
      }
    }
  }
}
```

```

    },
    "eventTime": "2025-01-22T22:06:16Z",
    "eventSource": "cloudtrail.amazonaws.com",
    "eventName": "GetTrailStatus",
    "awsRegion": "us-east-1",
    "sourceIPAddress": "192.168.0.0",
    "userAgent": "Mozilla/5.0 (Macintosh; Intel Mac OS X 10.15; rv:133.0)
    Gecko/20100101 Firefox/133.0",
    "requestParameters": {
        "name": "arn:aws:cloudtrail:us-east-1:123456789012:trail/myTrail"
    },
    "responseElements": null,
    "requestID": "d09c4dd2-5698-412b-be7a-example1a23",
    "eventID": "9cb5f426-7806-46e5-9729-exampled135d",
    "readOnly": true,
    "eventType": "AwsApiCall",
    "managementEvent": true,
    "recipientAccountId": "123456789012",
    "eventCategory": "Management",
    "tlsDetails": {
        "tlsVersion": "TLSv1.3",
        "cipherSuite": "TLS_AES_128_GCM_SHA256",
        "clientProvidedHostHeader": "cloudtrail.us-east-1.amazonaws.com"
    },
    "sessionCredentialFromConsole": "true",
    "eventContext": {
        "requestContext": {
            "aws:ViaAWSService": "false"
        },
        "tagContext": {}
    }
}

```

CloudTrail record contents for management, data, and network activity events

This page describes the record contents of a management, data, or network activity event.

The body of the record contains fields that help you determine the requested action as well as when and where the request was made. When the value of **Optional** is **True**, the field is only present when it applies to the service, API, or event type. An **Optional** value of **False** means that

the field is either always present, or that its presence does not depend on the service, API, or event type. An example is `responseElements`, which is present in events for actions that make changes (create, update, or delete actions).

Note

Fields for enriched events such as `eventContext` are only available for management events and data events. They are not available for network events.

eventTime

The date and time the request was completed, in coordinated universal time (UTC). An event's time stamp comes from the local host that provides the service API endpoint on which the API call was made. For example, a **CreateBucket** API event that is run in the US West (Oregon) Region would get its time stamp from the time on an AWS host running the Amazon S3 endpoint, `s3.us-west-2.amazonaws.com`. In general, AWS services use Network Time Protocol (NTP) to synchronize their system clocks.

Since: 1.0

Optional: False

eventVersion

The version of the log event format. The current version is 1.11.

The `eventVersion` value is a major and minor version in the form *major_version.minor_version*. For example, you can have an `eventVersion` value of `1.10`, where 1 is the major version, and 10 is the minor version.

CloudTrail increments the major version if a change is made to the event structure that is not backward-compatible. This includes removing a JSON field that already exists, or changing how the contents of a field are represented (for example, a date format). CloudTrail increments the minor version if a change adds new fields to the event structure. This can occur if new information is available for some or all existing events, or if new information is available only for new event types. Applications can ignore new fields to stay compatible with new minor versions of the event structure.

If CloudTrail introduces new event types, but the structure of the event is otherwise unchanged, the event version does not change.

To be sure that your applications can parse the event structure, we recommend that you perform an equal-to comparison on the major version number. To be sure that fields that are expected by your application exist, we also recommend performing a greater-than-or-equal-to comparison on the minor version. There are no leading zeroes in the minor version. You can interpret both *major_version* and *minor_version* as numbers, and perform comparison operations.

Since: 1.0

Optional: False

userIdentity

Information about the IAM identity that made a request. For more information, see [CloudTrail *userIdentity* element](#).

Since: 1.0

Optional: False

eventSource

The service that the request was made to. This name is typically a short form of the service name without spaces plus `.amazonaws.com`. For example:

- AWS CloudFormation is `cloudformation.amazonaws.com`.
- Amazon EC2 is `ec2.amazonaws.com`.
- Amazon Simple Workflow Service is `swf.amazonaws.com`.

This convention has some exceptions. For example, the eventSource for Amazon CloudWatch is `monitoring.amazonaws.com`.

Since: 1.0

Optional: False

eventName

The requested action, which is one of the actions in the API for that service.

Since: 1.0

Optional: False

awsRegion

The AWS Region that the request was made to, such as us-east-2. See [CloudTrail supported Regions](#).

Since: 1.0

Optional: False

sourceIPAddress

The IP address that the request was made from. For actions that originate from the service console, the address reported is for the underlying customer resource, not the console web server. For services in AWS, only the DNS name is displayed.

Note

For events originated by AWS, this field is usually AWS Internal/#, where # is a number used for internal purposes.

Since: 1.0

Optional: False

userAgent

The agent through which the request was made, such as the AWS Management Console, an AWS service, the AWS SDKs or the AWS CLI.

This field has a maximum size of 1 KB; content exceeding that limit is truncated. For event data stores configured to have a maximum event size of 1 MB, the field content is only truncated if the event payload exceeds 1 MB and the maximum field size is exceeded.

The following are example values:

- lambda.amazonaws.com – The request was made with AWS Lambda.

- `aws-sdk-java` – The request was made with the AWS SDK for Java.
- `aws-sdk-ruby` – The request was made with the AWS SDK for Ruby.
- `aws-cli/1.3.23 Python/2.7.6 Linux/2.6.18-164.el5` – The request was made with the AWS CLI installed on Linux.

Note

For events originated by AWS, if CloudTrail knows which AWS service made the call, this field is the event source of the calling service (for example, `ec2.amazonaws.com`). Otherwise, this field is `AWS Internal/#`, where `#` is a number used for internal purposes.

Since: 1.0

Optional: True

errorCode

The AWS service error if the request returns an error. For an example that shows this field, see [Error code and message log example](#).

This field has a maximum size of 1 KB; content exceeding that limit is truncated. For event data stores configured to have a maximum event size of 1 MB, the field content is only truncated if the event payload exceeds 1 MB and the maximum field size is exceeded.

For network activity events, when there is a VPC endpoint policy violation, the error code is `VpceAccessDenied`.

Since: 1.0

Optional: True

errorMessage

If the request returns an error, the description of the error. This message includes messages for authorization failures. CloudTrail captures the message logged by the service in its exception handling. For an example, see [Error code and message log example](#).

This field has a maximum size of 1 KB; content exceeding that limit is truncated. For event data stores configured to have a maximum event size of 1 MB, the field content is only truncated if the event payload exceeds 1 MB and the maximum field size is exceeded.

For network activity events, when there is a VPC endpoint policy violation, the `errorMessage` will always be the following message: The request was denied due to a VPC endpoint policy. For more information about access denied events for VPC endpoint policy violations, see [Access denied error message examples](#) in the *IAM User Guide*. For an example network activity event showing a VPC endpoint policy violation, see [Network activity events](#) in this guide.

 Note

Some AWS services provide the `errorCode` and `errorMessage` as top-level fields in the event. Other AWS services provide error information as part of `responseElements`.

Since: 1.0

Optional: True

requestParameters

The parameters, if any, that were sent with the request. These parameters are documented in the API reference documentation for the appropriate AWS service. This field has a maximum size of 100 KB. When the field size exceeds 100 KB, the `requestParameters` content is omitted. For event data stores configured to have a maximum event size of 1 MB, the field content is only omitted if the event payload exceeds 1 MB and the maximum field size is exceeded.

Since: 1.0

Optional: False

responseElements

The response elements, if any, for actions that make changes (create, update, or delete actions). For `readOnly` APIs, this field is `null`. If the action

doesn't return response elements, this field is null. The response elements for actions are documented in the API reference documentation for the appropriate AWS service.

This field has a maximum size of 100 KB. When the field size exceeds 100 KB, the `responseElements` content is omitted. For event data stores configured to have a maximum event size of 1 MB, the field content is only omitted if the event payload exceeds 1 MB and the maximum field size is exceeded.

The `responseElements` value is useful to help you trace a request with AWS Support. Both `x-amz-request-id` and `x-amz-id-2` contain information that helps you trace a request with Support. These values are the same as those that the service returns in the response to the request that initiates the events, so you can use them to match the event to the request.

Since: 1.0

Optional: False

additionalEventData

Additional data about the event that was not part of the request or response. This field has a maximum size of 28 KB. When the field size exceeds 28 KB, the `additionalEventData` content is omitted. For event data stores configured to have a maximum event size of 1 MB, the field content is only omitted if the event payload exceeds 1 MB and the maximum field size is exceeded.

The content of `additionalEventData` is variable. For example, for [AWS Management Console sign-in events](#), `additionalEventData` could include the `MFAUsed` field with a value of Yes if the request was made by a root or IAM user using multi-factor authentication (MFA).

Since: 1.0

Optional: True

requestID

The value that identifies the request. The service being called generates this value. This field has a maximum size of 1 KB; content exceeding that limit is truncated. For event data stores

configured to have a maximum event size of 1 MB, the field content is only truncated if the event payload exceeds 1 MB and the maximum field size is exceeded.

Since: 1.01

Optional: True

eventID

GUID generated by CloudTrail to uniquely identify each event. You can use this value to identify a single event. For example, you can use the ID as a primary key to retrieve log data from a searchable database.

Since: 1.01

Optional: False

eventType

Identifies the type of event that generated the event record. This can be the one of the following values:

- `AwsApiCall` – An API was called.
- [AwsServiceEvent](#) – The service generated an event related to your trail. For example, this can occur when another account made a call with a resource that you own.
- `AwsConsoleAction` – An action was taken in the console that was not an API call.
- [AwsConsoleSignIn](#) – A user in your account (root, IAM, federated, SAML, or SwitchRole) signed in to the AWS Management Console.
- [AwsVpceEvents](#) – CloudTrail network activity events enable VPC endpoint owners to record AWS API calls made using their VPC endpoints from a private VPC to the AWS service. To record network activity events, the VPC endpoint owner must enable network activity events for the event source.

Since: 1.02

Optional: False

apiVersion

Identifies the API version associated with the `AwsApiCall` `eventType` value.

Since: 1.01

Optional: True

managementEvent

A Boolean value that identifies whether the event is a management event. `managementEvent` is shown in an event record if `eventVersion` is 1.06 or higher, and the event type is one of the following:

- `AwsApiCall`
- `AwsConsoleAction`
- `AwsConsoleSignIn`
- `AwsServiceEvent`

Since: 1.06

Optional: True

readOnly

Identifies whether this operation is a read-only operation. This can be one of the following values:

- `true` – The operation is read-only (for example, `DescribeTrails`).
- `false` – The operation is write-only (for example, `DeleteTrail`).

Since: 1.01

Optional: True

resources

A list of resources accessed in the event. The field can contain the following information:

- Resource ARNs
- Account ID of the resource owner
- Resource type identifier in the format: `AWS::aws-service-name::data-type-name`

For example, when an AssumeRole event is logged, the resources field can appear like the following:

- ARN: `arn:aws:iam::123456789012:role/myRole`
- Account ID: 123456789012
- Resource type identifier: `AWS::IAM::Role`

For example logs with the resources field, see [AWS STS API Event in CloudTrail Log File](#) in the *IAM User Guide* or [Logging AWS KMS API Calls](#) in the *AWS Key Management Service Developer Guide*.

Since: 1.01

Optional: True

recipientAccountId

Represents the account ID that received this event. The recipientAccountId may be different from the [CloudTrail userIdentity element](#) accountId. This can occur in cross-account resource access. For example, if a KMS key, also known as an [AWS KMS key](#), was used by a separate account to call the [Encrypt API](#), the accountId and recipientAccountId values will be the same for the event delivered to the account that made the call, but the values will be different for the event that is delivered to the account that owns the KMS key.

Since: 1.02

Optional: True

serviceEventDetails

Identifies the service event, including what triggered the event and the result. For more information, see [AWS service events](#). This field has a maximum size of 100 KB. When the field size exceeds 100 KB, the serviceEventDetails content is omitted. For event data stores configured to have a maximum event size of 1 MB, the field content is only omitted if the event payload exceeds 1 MB and the maximum field size is exceeded.

Since: 1.05

Optional: True

sharedEventID

GUID generated by CloudTrail to uniquely identify CloudTrail events from the same AWS action that is sent to different AWS accounts.

For example, when an account uses an [AWS KMS key](#) that belongs to another account, the account that used the KMS key and the account that owns the KMS key receive separate CloudTrail events for the same action. Each CloudTrail event delivered for this AWS action shares the same sharedEventID, but also has a unique eventID and recipientAccountID.

For more information, see [Example sharedEventID](#).

Note

The sharedEventID field is present only when CloudTrail events are delivered to multiple accounts. If the caller and owner are the same AWS account, CloudTrail sends only one event, and the sharedEventID field is not present.

Since: 1.03

Optional: True

vpcEndpointId

Identifies the VPC endpoint in which requests were made from a VPC to another AWS service, such as Amazon EC2.

Note

For events originated by AWS and through an AWS service's VPC, this field is usually AWS Internal or the service name.

Since: 1.04

Optional: True

vpcEndpointAccountId

Identifies the AWS account ID of the VPC endpoint owner for the corresponding endpoint for which a request has traversed.

Note

For events originated by AWS and through an AWS service's VPC, this field is usually `AWS Internal` or the service name.

Since: 1.09

Optional: True

eventCategory

Shows the event category. The event category is used in [LookupEvents](#) calls to filter on management events.

- For management events, the value is `Management`.
- For data events, the value is `Data`.
- For network activity events, the value is `NetworkActivity`.

Since: 1.07

Optional: False

addendum

If an event delivery was delayed, or additional information about an existing event becomes available after the event is logged, an addendum field shows information about why the event was delayed. If information was missing from an existing event, the addendum field includes the missing information and a reason for why it was missing. Contents include the following.

- **reason** - The reason that the event or some of its contents were missing. Values can be any of the following.
 - **DELIVERY_DELAY** – There was a delay delivering events. This could be caused by high network traffic, connectivity issues, or a CloudTrail service issue.

- **UPDATED_DATA** – A field in the event record was missing or had an incorrect value.
- **SERVICE_OUTAGE** – A service that logs events to CloudTrail had an outage, and couldn't log events to CloudTrail. This is exceptionally rare.
- **updatedFields** - The event record fields that are updated by the addendum. This is only provided if the reason is `UPDATED_DATA`.
- **originalRequestID** - The original unique ID of the request. This is only provided if the reason is `UPDATED_DATA`.
- **originalEventID** - The original event ID. This is only provided if the reason is `UPDATED_DATA`.

Since: 1.08

Optional: True

sessionCredentialFromConsole

String with a value of `true` or `false` that shows whether or not an event originated from an AWS Management Console session. This field is not shown unless the value is `true`, meaning that the client that was used to make the API call was either a proxy or an external client. If a proxy client was used, the `tlsDetails` event field is not shown.

Since: 1.08

Optional: True

eventContext

This field is present in enriched events recorded for event data stores that were configured to include resource tag keys or IAM global condition keys. For more information, see [Enrich CloudTrail events by adding resource tag keys and IAM global condition keys](#).

Contents include the following:

- **requestContext** – Includes information about the IAM global condition keys that were evaluated during the authorization process, including additional details about the principal, session, network, and the request itself.
- **tagContext** – Includes the tags associated with the resources that were involved in the API call as well as tags associated with IAM principals such as roles or users. For more information, see [Controlling access for IAM principals](#).

API events related to deleted resources will not have resource tags.

 Note

The `eventContext` field is only present in events for event data stores that are configured to include resource tag keys and IAM global condition keys. Events delivered to **Event history**, Amazon EventBridge, viewable with the AWS CLI `lookup-events` command, and delivered to trails, will not include the `eventContext` field.

Since: 1.11

Optional: True

edgeDeviceDetails

Shows information about edge devices that are targets of a request. Currently, [S3 Outposts](#) device events include this field. This field has a maximum size of 28 KB; content exceeding that limit is truncated. For event data stores configured to have a maximum event size of 1 MB, the field content is only truncated if the event payload exceeds 1 MB and the maximum field size is exceeded.

Since: 1.08

Optional: True

tlsDetails

Shows information about the Transport Layer Security (TLS) version, cipher suites, and the fully qualified domain name (FQDN) of the client-provided host name used in the service API call, which is typically the FQDN of the service endpoint. CloudTrail still logs partial TLS details if expected information is missing or empty. For example, if the TLS version and cipher suite are present, but the `HOST` header is empty, available TLS details are still logged in the CloudTrail event.

- **tlsVersion** - The TLS version of a request.
- **cipherSuite** - The cipher suite (combination of security algorithms used) of a request.
- **clientProvidedHostHeader** - The client-provided host name used in the service API call, which is typically the FQDN of the service endpoint.

Note

There are some cases when the `tlsDetails` field is not present in an event record.

- The `tlsDetails` field is not present if the API call was made by an AWS service on your behalf. The `invokedBy` field in the `userIdentity` element identifies the AWS service that made the API call.
- If `sessionCredentialFromConsole` is present with a value of `true`, `tlsDetails` is present in an event record only if an external client was used to make the API call.

Since: 1.08

Optional: True

Field truncation order for maximum event size of 1 MB

You can expand the maximum event size from 256 KB up to 1 MB when you create or update an event data store using the [CloudTrail console](#), [AWS CLI](#), and SDKs.

Expanding the event size is helpful for analyzing and troubleshooting events because it allows you to see the full contents of fields that would normally get truncated or omitted.

When the event payload exceeds 1 MB, CloudTrail truncates fields in the following order:


- `annotation`
- `requestID`
- `additionalEventData`
- `serviceEventDetails`
- `userAgent`
- `errorCode`
- `eventContext`
- `responseElements`
- `requestParameters`
- `errorMessage`

If an event payload cannot be reduced to under 1 MB even after truncation, an error will occur.

Example sharedEventID

The following is an example that describes how CloudTrail delivers two events for the same action:

1. Alice has AWS account (111111111111) and creates an AWS KMS key. She is the owner of this KMS key.
2. Bob has AWS account (222222222222). Alice gives Bob permission to use the KMS key.
3. Each account has a trail and a separate bucket.
4. Bob uses the KMS key to call the Encrypt API.
5. CloudTrail sends two separate events.
 - One event is sent to Bob. The event shows that he used the KMS key.
 - One event is sent to Alice. The event shows that Bob used the KMS key.
 - The events have the same `sharedEventID`, but the `eventID` and `recipientAccountID` are unique.



CloudTrail record contents for Insights events for trails

AWS CloudTrail Insights event records for trails include fields that are different from other CloudTrail events in their JSON structure, sometimes called *payload*. CloudTrail Insights events for trails contain the following fields:

- **eventVersion** – The version of the event.

Since: 1.07

Optional: False

- **eventType** – The event type. The value is always `AwsCloudTrailInsight` for Insights events.

Since: 1.07

Optional: False

- **eventID** – GUID generated by CloudTrail to uniquely identify each event. You can use this value to identify a single event. For example, you can use the ID as a primary key to retrieve log data from a searchable database.

Since: 1.07

Optional: False

- **eventTime** – The time the Insights event started or stopped, in coordinated universal time (UTC).

Since: 1.07

Optional: False

- **awsRegion** – The AWS Region where the Insights event occurred, such as `us-east-2`.

Since: 1.07

Optional: False

- **recipientAccountId** – Represents the account ID that received this event.

Since: 1.07

Optional: True

- **sharedEventID** – A GUID that is generated by CloudTrail Insights to uniquely identify an Insights event. `sharedEventID` is common between the start and the end Insights events, and helps to connect both events to uniquely identify unusual activity. You can think of the `sharedEventID` as the overall Insights event ID.

Since: 1.07

Optional: False

- **insightDetails** – A CloudTrail Insights event record for a trail includes an `insightDetails` block that contains information about the underlying triggers of an Insights event, such as event source, user identities, user agents, historical averages or *baselines*, statistics, API name, and whether the event is the start or end of the Insights event.

Since: 1.07

Optional: False

- **state** – Whether the event is the starting or ending Insights event. The value can be `Start` or `End`.

Since: 1.07

Optional: False

- **eventSource** – The AWS service that was the source of the unusual activity, such as `ec2.amazonaws.com`.

Since: 1.07

Optional: False

- **eventName** – The name of the Insights event, typically the name of the API that was the source of the unusual activity.

Since: 1.07

Optional: False

- **insightType** – The type of Insights event. This value can be `ApiCallRateInsight` or `ApiErrorRateInsight`.

Since: 1.07

Optional: False

- **errorCode** – The error code of the unusual activity. See also `errorCode` in [CloudTrail record contents for management, data, and network activity events](#).

Since: 1.07

Optional: True

- **insightContext** – Information about the AWS tools (called *user agents*), IAM users and roles (called *user identities*), and error codes associated with the events that CloudTrail analyzed to generate the Insights event. This element also includes statistics that show how the unusual activity in an Insights event compares to *baseline*, or normal, activity.

Since: 1.07

Optional: False

- **statistics** – Includes data about the *baseline*, or typical average rate of calls to or errors on the subject API by an account as measured during the baseline period, the average rate of calls or errors that triggered the Insights event, the duration, in minutes, of the Insights event, and the duration, in minutes, of the baseline measuring period.

Since: 1.07

Optional: False

- **baseline** – The API calls or errors per minute during the baseline duration on the Insights event's subject API for the account, calculated over the seven days preceding the start of the Insights event.

Since: 1.07

Optional: False

- **average** – The historic average of API calls or errors per minute during the seven days preceding the Insights activity start time.

Since: 1.07

Optional: False

- **insight** – For a starting Insights event, this value is the average number of API calls or errors per minute during the start of the unusual activity. For an ending Insights event,

this value is the average number of API calls or errors per minute over the duration of the unusual activity.

Since: 1.07

Optional: False

- **average** – The average number of API calls or errors logged per minute during the unusual activity period.

Since: 1.07

Optional: False

- **insightDuration** – The duration, in minutes, of an Insights event (the time period from the start to the end of unusual activity on the subject API). `insightDuration` occurs in both starting and ending Insights events.

Since: 1.07

Optional: False

- **baselineDuration** – The duration, in minutes, of the baseline period (the time period that normal activity is measured on the subject API). `baselineDuration` is at minimum the seven days (10080 minutes) preceding an Insights event. This field occurs in both starting and ending Insights events. The ending time of `baselineDuration` measurement is always the start of an Insights event.

Since: 1.07

Optional: False

- **attributions** – Includes information about the user identities, user agents, and error codes correlated with unusual and baseline activity. A maximum of five user identities, five user agents, and five error codes are captured in an Insights event `attributions` block, sorted by an average of the count of activity, in descending order from highest to lowest.

Since: 1.07

Optional: True

- **attribute** – Contains the attribute type. Value can be `userIdentityArn`, `userAgent`, or `errorCode`. If present, these values will appear only once in an individual attribute.

Different attribute values can have different `userIdentityArn`, `userAgent`,

or `errorCode` values, but each attribute instance will contain only one value for `userIdentityArn`, `userAgent`, or `errorCode`.

Since: 1.07

Optional: False

- **insight** – A block that shows up to the top five attribute values that contributed to the API calls or errors made during the unusual activity period, in descending order from largest number of API calls or errors to smallest. It also shows the average number of API calls or errors made by the attribute values during the unusual activity period.

Since: 1.07

Optional: False

- **value** – The attribute that contributed to the API calls or errors made during the unusual activity period.

Since: 1.07

Optional: False False

- **average** – The number of API calls or errors per minute during the unusual activity period for the attribute in the `value` field.

Since: 1.07

Optional: False False

- **baseline** – A block that shows up to the top five attribute values that contributed the most to the API calls or errors during the normal activity period, in descending order from largest number of API calls or errors to smallest. It also shows the average number of API calls or errors made by the attribute values during the normal activity period.

Since: 1.07

Optional: False False

- **value** – The attribute that contributed to the API calls or errors during the normal activity period.

Since: 1.07

Optional: False False

- **average** – The historic average of API calls or errors per minute during the seven days preceding the Insights activity start time for the attribute in the `value` field.

Since: 1.07**Optional:False** False

- **eventCategory** – The category of the event. The value is always `Insight` for Insights events.

Since: 1.07**Optional:** False

Example insightDetails block

The following is an example of an Insights event `insightDetails` block for an Insights event that occurred when the Application Auto Scaling API `CompleteLifecycleAction` was called an unusual number of times. For an example of a full Insights event, see [Insights events](#).

This example is from a starting Insights event, indicated by `"state": "Start"`. The top user identities that called the APIs associated with the Insights event, `CodeDeployRole1`, `CodeDeployRole2`, and `CodeDeployRole3`, are shown in the `attributions` block, along with their average API call rates for this Insights event, and the baseline for the `CodeDeployRole1` role. The `attributions` block also shows that the user agent is `codedeploy.amazonaws.com`, meaning the top user identities used the AWS CodeDeploy console to run the API calls.

Because there are no error codes associated with the events that were analyzed to generate the Insights event (the value is `null`), the `insight` average for the error code is the same as the overall `insight` average for the entire Insights event, shown in the `statistics` block.

```
"insightDetails": {
  "state": "Start",
  "eventSource": "autoscaling.amazonaws.com",
  "eventName": "CompleteLifecycleAction",
  "insightType": "ApiCallRateInsight",
  "insightContext": {
    "statistics": {
      "baseline": {
        "average": 0.0000882145
```

```

    },
    "insight": {
      "average": 0.6
    },
    "insightDuration": 5,
    "baselineDuration": 11336
  },
  "attributions": [
    {
      "attribute": "userIdentityArn",
      "insight": [
        {
          "value": "arn:aws:sts::012345678901:assumed-role/
CodeDeployRole1",
          "average": 0.2
        },
        {
          "value": "arn:aws:sts::012345678901:assumed-role/
CodeDeployRole2",
          "average": 0.2
        },
        {
          "value": "arn:aws:sts::012345678901:assumed-role/
CodeDeployRole3",
          "average": 0.2
        }
      ],
      "baseline": [
        {
          "value": "arn:aws:sts::012345678901:assumed-role/
CodeDeployRole1",
          "average": 0.0000882145
        }
      ]
    },
    {
      "attribute": "userAgent",
      "insight": [
        {
          "value": "codedeploy.amazonaws.com",
          "average": 0.6
        }
      ],
      "baseline": [

```

```

        {
            "value": "codedeploy.amazonaws.com",
            "average": 0.0000882145
        }
    ],
    },
    {
        "attribute": "errorCode",
        "insight": [
            {
                "value": "null",
                "average": 0.6
            }
        ],
        "baseline": [
            {
                "value": "null",
                "average": 0.0000882145
            }
        ]
    }
]
}
}

```

CloudTrail record contents for Insights events for event data stores

AWS CloudTrail Insights event records for event data stores include fields that are different from other CloudTrail events in their JSON structure, sometimes called *payload*. A CloudTrail Insights event record for an event data store includes the following fields:

Note

The `insightValue`, `insightAverage`, `baselineValue`, and `baselineAverage` fields within the `attributions` field of `insightContext` will begin to be deprecated on June 23, 2025.

- **eventVersion** – The version of the log event format.

Optional: False

- **eventCategory** – The category of the event. The value is always `Insight` for Insights events.

Optional: False

- **eventType** – The event type. The value is always `AwsCloudTrailInsight` for Insights events.

Optional: False

- **eventID** – GUID generated by CloudTrail to uniquely identify each event. You can use this value to identify a single event. For example, you can use the ID as a primary key to retrieve log data from a searchable database.

Optional: False

- **eventTime** – The time the Insights event started or stopped, in coordinated universal time (UTC).

Optional: False

- **awsRegion** – The AWS Region where the Insights event occurred, such as `us-east-2`.

Optional: False

- **recipientAccountId** – Represents the account ID that received this event.

Optional: True

- **sharedEventID** – A GUID that is generated by CloudTrail Insights to uniquely identify an Insights event. `sharedEventID` is common between the start and the end Insights events, and helps to connect both events to uniquely identify unusual activity. You can think of the `sharedEventID` as the overall Insights event ID.

Optional: False

- **addendum** – If an event delivery was delayed, or additional information about an existing event becomes available after the event is logged, an addendum field shows information about why the event was delayed. If information was missing from an existing event, the addendum field includes the missing information and a reason for why it was missing. See also addendum in [CloudTrail record contents for management, data, and network activity events](#).

Optional: True

- **insightSource** – The source event data store that collected the management events that were analyzed.

Optional: False

- **insightState** – Whether the event is the starting or ending Insights event. The value can be Start or End.

Optional: False

- **insightEventSource** – The AWS service that was the source of the unusual activity, such as `ec2.amazonaws.com`.

Optional: False

- **insightEventName** – The name of the Insights event, typically the name of the API that was the source of the unusual activity.

Optional: False

- **insightErrorCode** – The error code of the unusual activity. See also `errorCode` in [CloudTrail record contents for management, data, and network activity events](#).

Optional: True

- **insightType** – The type of Insights event. This value can be `ApiCallRateInsight` or `ApiErrorRateInsight`.

Optional: False

- **insightContext** – Contains information about the underlying trigger of an Insights event, such as user identity, user agent, historical average or *baseline*, and Insights duration and average.

Optional: False

- **baselineAverage** – The average number of API calls or errors per minute during the baseline duration on the Insights event's subject API for the account, calculated over the seven days preceding the start of the Insights event.

Optional: False

- **insightAverage** – For a starting Insights event, this value is the average number of API calls or errors per minute during the start of the unusual activity. For an ending Insights event, this value is the average number of API calls or errors per minute over the duration of the unusual activity.

Optional: False

- **baselineDuration** – The duration, in minutes, of the baseline period (the time period that normal activity is measured on the subject API). `baselineDuration` is at minimum the seven days (10080 minutes) preceding an Insights event. This field occurs in both starting and ending Insights events. The ending time of `baselineDuration` measurement is always the start of an Insights event.

Optional: False

- **insightDuration** – The duration, in minutes, of an Insights event (the time period from the start to the end of unusual activity on the subject API). `insightDuration` occurs in both starting and ending Insights events.

Optional: False

- **attributions** – Includes information about the user identity, user agent, or error code correlated with unusual and baseline activity.

Optional: True

 Note

The `insightValue`, `insightAverage`, `baselineValue`, and `baselineAverage` fields within the `attributions` field of `insightContext` will begin to be deprecated on June 23, 2025.

- **attribute** – Contains the attribute type. Value can be `userIdentityArn`, `userAgent`, or `errorCode`. If present, these values will appear only once in an individual attribute. Different attribute values can have different `userIdentityArn`, `userAgent`, or `errorCode` values, but each attribute instance will contain only one value for `userIdentityArn`, `userAgent`, or `errorCode`.

Optional: False

- **insightValue** – The top attribute value that occurred on the API calls or errors made during the unusual activity period.

Optional: False

- **insightAverage** – The number of API calls or errors per minute during the unusual activity period for the attribute in the `insightValue` field.

Optional: False

- **baselineValue** – The top attribute value that contributed to the API calls or errors logged during the normal activity period.

Optional: False

- **baselineAverage** – The historic average of API calls or errors per minute during the seven days preceding the Insights activity start time for the attribute in the `baselineValue` field.

Optional: False

- **insight** – The top five attribute values that contributed to the API calls or errors made during the unusual activity period. It also shows the average number of API calls or errors made by the attribute during the unusual activity period.

Optional: False

- **value** – The attribute that contributed to the API calls or errors made during the unusual activity period.

Optional: False

- **average** – The average number of API calls or errors per minute during the unusual activity period for the attribute in the `value` field.

Optional: False

- **baseline** – The top five attribute values that contributed the most to the API calls or errors during the normal activity period. It also shows the average number of API calls or errors logged by the attribute value during the normal activity period.

Optional: False

- **value** – The attribute that contributed to the API calls or errors during the normal activity period.

Optional: False

- **average** – The historic average of API calls or errors per minute during the seven days preceding the Insights activity start time for the attribute in the `value` field.

Optional: False

CloudTrail userIdentity element

AWS Identity and Access Management (IAM) provides different types of identities. The `userIdentity` element contains details about the type of IAM identity that made the request, and which credentials were used. If temporary credentials were used, the element shows how the credentials were obtained.

Contents

- [Examples](#)
- [Fields](#)
- [Values for AWS STS APIs with SAML and web identity federation](#)
- [AWS STS source identity](#)

Examples

`userIdentity` with IAM user credentials

The following example shows the `userIdentity` element of a simple request made with the credentials of the IAM user named Alice.

```
"userIdentity": {  
  "type": "IAMUser",  
  "principalId": "AIDAJ45Q7YFFAREXAMPLE",  
  "arn": "arn:aws:iam::123456789012:user/Alice",  
  "accountId": "123456789012",  
  "accessKeyId": "",  
  "userName": "Alice"  
}
```

`userIdentity` with temporary security credentials

The following example shows a `userIdentity` element for a request made with temporary security credentials obtained by assuming an IAM role. The element contains additional details about the role that was assumed to get credentials.

```
"userIdentity": {  
  "type": "AssumedRole",
```

```

    "principalId": "AROAI DPPEZS35WEXAMPLE:AssumedRoleSessionName",
    "arn": "arn:aws:sts::123456789012:assumed-role/RoleToBeAssumed/MySessionName",
    "accountId": "123456789012",
    "accessKeyId": "",
    "sessionContext": {
      "sessionIssuer": {
        "type": "Role",
        "principalId": "AROAI DPPEZS35WEXAMPLE",
        "arn": "arn:aws:iam::123456789012:role/RoleToBeAssumed",
        "accountId": "123456789012",
        "userName": "RoleToBeAssumed"
      },
      "attributes": {
        "mfaAuthenticated": "false",
        "creationDate": "20131102T010628Z"
      }
    }
  }
}

```

userIdentity for a request made on behalf of an IAM Identity Center user

The following example shows a `userIdentity` element for a request made on behalf of an IAM Identity Center user.

```

"userIdentity": {
  "type": "IdentityCenterUser",
  "accountId": "123456789012",
  "onBehalfOf": {
    "userId": "544894e8-80c1-707f-60e3-3ba6510dfac1",
    "identityStoreArn": "arn:aws:identitystore::123456789012:identitystore/d-9067642ac7"
  },
  "credentialId": "EXAMPLEVHULjJdTUDPJfofVa1sufHDoj7aYc0YcxFV1lWR_Whr1fEXAMPLE"
}

```

To learn more about how you can use `userId`, `identityStoreArn`, and `credentialId`, see [Identifying the user and session in IAM Identity Center user-initiated CloudTrail events](#) in the *IAM Identity Center User Guide*.

Fields

The following fields can appear in a `userIdentity` element.

type

The type of the identity. The following values are possible:

- **Root** – The request was made with your AWS account credentials. If the `userIdentity` type is **Root**, and you set an alias for your account, the `userName` field contains your account alias. For more information, see [Your AWS account ID and its alias](#).
- **IAMUser** – The request was made with the credentials of an IAM user.
- **AssumedRole** – The request was made with temporary security credentials that were obtained with a role by making a call to the AWS Security Token Service (AWS STS) [AssumeRole](#) API. This can include [roles for Amazon EC2](#) and cross-account API access.
- **Role** – The request was made with a persistent IAM identity that has specific permissions. The issuer of the role sessions is always the role. For more information about roles, see [Roles terms and concepts](#) in the *IAM User Guide*.
- **FederatedUser** – The request was made with temporary security credentials obtained from a call to the AWS STS [GetFederationToken](#) API. The `sessionIssuer` element indicates if the API was called with root or IAM user credentials.

For more information about temporary security credentials, see [Temporary Security Credentials](#) in the *IAM User Guide*.

- **Directory** – The request was made to a directory service, and the type is unknown. Directory services include the following: Amazon WorkDocs and Amazon Quick Suite.
- **AWSAccount** – The request was made by another AWS account
- **AWSService** – The request was made by an AWS account that belongs to an AWS service. For example, AWS Elastic Beanstalk assumes an IAM role in your account to call other AWS services on your behalf.
- **IdentityCenterUser** – The request was made on behalf of an IAM Identity Center user.
- **Unknown** – The request was made with an identity type that CloudTrail can't determine.

Optional: False

AWSAccount and **AWSService** appear for type in your logs when there is cross-account access using an IAM role that you own.

Example: Cross-account access initiated by another AWS account

1. You own an IAM role in your account.

2. Another AWS account switches to that role to assume the role for your account.
3. Because you own the IAM role, you receive a log that shows the other account assumed the role. The type is `AWSAccount`. For an example log entry, see [AWS STS API event in CloudTrail log file](#).

Example: Cross-account access initiated by an AWS service

1. You own an IAM role in your account.
2. An AWS account owned by an AWS service assumes that role.
3. Because you own the IAM role, you receive a log that shows the AWS service assumed the role. The type is `AWSService`.

`userName`

The friendly name of the identity that made the call. The value that appears in `userName` is based on the value in `type`. The following table shows the relationship between `type` and `userName`:

<code>type</code>	<code>userName</code>	Description
Root (no alias set)	Not present	If you haven't set up an alias for your AWS account, the <code>userName</code> field doesn't appear. For more information about account aliases, see Your AWS account ID and its alias . Note that the <code>userName</code> field can't contain <code>Root</code> , because <code>Root</code> is an identity type and not a user name.
Root (alias set)	The account alias	For more information about AWS account aliases, see Your AWS account ID and its alias .
<code>IAMUser</code>	The user name of the IAM user	
<code>AssumedRole</code>	Not present	For the <code>AssumedRole</code> type, you can find the <code>userName</code> field in <code>sessionContext</code> as part

type	userName	Description
		of the sessionIssuer element. For an example entry, see Examples .
Role	User-defined	The <code>sessionContext</code> and <code>sessionIssuer</code> section contains information about the identity that issued the session for the role.
FederatedUser	Not present	The <code>sessionContext</code> and <code>sessionIssuer</code> section contains information about the identity that issued the session for the federated user.
Directory	Can be present	For example, the value can be the account alias or email address of the associated AWS account ID .
AWSService	Not present	
AWSAccount	Not present	
IdentityCenterUser	Not present*	The <code>onBehalfOf</code> section contains information about the IAM Identity Center user ID and identity store ARN for which the call was made. To learn more about how you can use these two fields, see Identifying the user and session in IAM Identity Center user-initiated CloudTrail events in the IAM Identity Center User Guide. * IAM Identity Center emits the <code>userName</code> field under the <code>additionalEventData</code> element in two sign-in CloudTrail events. For more information, see Username in sign-in CloudTrail events in the IAM Identity Center User Guide.
Unknown	Can be present	For example, the value can be the account alias or email address of the associated AWS account ID .

Note

The `userName` field contains the string `HIDDEN_DUE_TO_SECURITY_REASONS` when the recorded event is a console sign-in failure caused by incorrect user name input. CloudTrail does not record the contents in this case because the text could contain sensitive information, as in the following examples:

- A user accidentally types a password in the user name field.
- A user clicks the link for one AWS account's sign-in page, but then types the account number for a different one.
- A user accidentally types the account name of a personal email account, a bank sign-in identifier, or some other private ID.

Optional: True

principalId

A unique identifier for the entity that made the call. For requests made with temporary security credentials, this value includes the session name that is passed to the `AssumeRole`, `AssumeRoleWithWebIdentity`, or `GetFederationToken` API call.

Optional: True

arn

The Amazon Resource Name (ARN) of the principal that made the call. The last section of the `arn` contains the user or role that made the call.

Optional: True

accountId

The account that owns the entity that granted permissions for the request. If the request was made with temporary security credentials, this is the account that owns the IAM user or role used to obtain credentials.

If the request was made with an IAM Identity Center authorized access token, this is the account that owns the IAM Identity Center instance.

Optional: True

accessKeyId

The access key ID that was used to sign the request. If the request was made with temporary security credentials, this is the access key ID of the temporary credentials. For security reasons, `accessKeyId` might not be present, or might be displayed as an empty string.

Optional: True

sessionContext

If the request was made with temporary security credentials, `sessionContext` provides information about the session created for those credentials. You create a session when you call any API that returns temporary credentials. Users also create sessions when they work in the console and make requests with APIs that include [multi-factor authentication](#). The following attributes can appear in `sessionContext`:

- `sessionIssuer` – If a user make a request with temporary security credentials, `sessionIssuer` provides information about how the user obtained credentials. For example, if the they obtained temporary security credentials by assuming a role, this element provides information about the assumed role. If they obtained credentials with root or IAM user credentials to call AWS STS `GetFederationToken`, the element provides information about the root account or IAM user. This element has the following attributes:
 - `type` – The source of the temporary security credentials, such as `Root`, `IAMUser`, or `Role`.
 - `userName` – The friendly name of the user or role that issued the session. The value that appears depends on the `sessionIssuer` identity type. The following table shows the relationship between `sessionIssuer type` and `userName`:

sessionIssuer type	userName	Description
Root (no alias set)	Not present	If you have not set up an alias for your account, the <code>userName</code> field does not appear. For more information about AWS account aliases, see Your AWS account ID and its alias . Note that the <code>userName</code> field can't contain <code>Root</code> , because <code>Root</code> is an identity type, not a user name.

sessionIssuer type	userName	Description
Root (alias set)	The account alias	For more information about AWS account aliases, see Your AWS account ID and its alias .
IAMUser	The user name of the IAM user	This also applies when a federated user is using a session issued by IAMUser.
Role	The role name	A role assumed by an IAM user, AWS service, or web identity federated user in a role session.

- `principalId` – The internal ID of the entity used to get credentials.
- `arn` – The ARN of the source (account, IAM user, or role) that was used to get temporary security credentials.
- `accountId` – The account that owns the entity that was used to get credentials.
- `webIdFederationData` – If the request was made with temporary security credentials obtained by [web identity federation](#), `webIdFederationData` lists information about the identity provider.

This element has the following attributes:

- `federatedProvider` – The principal name of the identity provider (for example, `www.amazon.com` for Login with Amazon or `accounts.google.com` for Google).
- `attributes` – The application ID and user ID as reported by the provider (for example, `www.amazon.com:app_id` and `www.amazon.com:user_id` for Login with Amazon).

Note

The omission of this field or presence of this field with an empty value signifies that there is no information about the identity provider.

- `assumedRoot` – The value is `true` for a temporary session when a management account or delegated administrator calls AWS STS [AssumedRoot](#). For more information, see [Track privileged tasks in CloudTrail](#) in the *IAM User Guide*. This is an optional field.
- `attributes` – The attributes for the session.

- `creationDate` – The date and time when the temporary security credentials were issued. Represented in ISO 8601 basic notation.
- `mfaAuthenticated` – The value is `true` if the root user or IAM user who used their credentials for the request also authenticated with an MFA device; otherwise, `false`.
- `sourceIdentity` – See [AWS STS source identity](#) in this topic. The `sourceIdentity` field occurs in events when users assume an IAM role to perform an action. `sourceIdentity` identifies the original user identity making the request, whether that user's identity is an IAM user, an IAM role, a user authenticated through SAML-based federation, or a user authenticated through OpenID Connect (OIDC)-compliant web identity federation. For more information about configuring AWS STS to collect source identity information, see [Monitor and control actions taken with assumed roles](#) in the *IAM User Guide*.
- `ec2RoleDelivery` – The value is `1.0` if the credentials were provided by Amazon EC2 Instance Metadata Service Version 1 (IMDSv1). The value is `2.0` if the credentials were provided using the new IMDS scheme.

AWS credentials provided by the Amazon EC2 Instance Metadata Service (IMDS) include an `ec2:RoleDelivery` IAM context key. This context key makes it easy to enforce use of the new scheme on a service-by-service or resource-by-resource basis by using the context key as a condition in IAM policies, resource policies, or AWS Organizations service control policies. For more information, see [Instance metadata and user data](#) in the *Amazon EC2 User Guide*.

Optional: True

invokedBy

The name of the AWS service that made the request, when a request is made by an AWS service such as Amazon EC2 Auto Scaling or AWS Elastic Beanstalk. This field is only present when a request is made by an AWS service. This includes requests made by services using forward access sessions (FAS), AWS service principals, service-linked roles, or service roles used by an AWS service.

Optional: True

onBehalfOf

If the request was made by an IAM Identity Center caller, `onBehalfOf` provides information about the IAM Identity Center user ID and identity store ARN for which the call was made. This element has the following attributes:

- `userId` – The ID of the IAM Identity Center user who the call was made on behalf of.

- `identityStoreArn` – The ARN of the IAM Identity Center identity store that the call was made on behalf of.

Optional: True

`inScopeOf`

If the request was made in scope of an AWS service, such as Lambda or Amazon ECS, it provides information about the resource or credentials related to the request. This element can contain the following attributes:

- `sourceArn` – The ARN of the resource that invoked the service-to-service request.
- `sourceAccount` – The owner account ID for the `sourceArn`. It appears together with `sourceArn`.
- `issuerType` – The resource type of `credentialsIssuedTo`. For example, `AWS::Lambda::Function`.
- `credentialsIssuedTo` – The resource related to the environment where the credentials were issued.

Optional: True

`credentialId`

The credential ID for the request. This is only set when the caller uses a bearer token, such as an IAM Identity Center authorized access token.

Optional: True

Values for AWS STS APIs with SAML and web identity federation

AWS CloudTrail supports logging AWS Security Token Service (AWS STS) API calls made with Security Assertion Markup Language (SAML) and web identity federation. When a user makes a call to the [AssumeRoleWithSAML](#) and [AssumeRoleWithWebIdentity](#) APIs, CloudTrail records the call and delivers the event to your Amazon S3 bucket.

The `userIdentity` element for these APIs contains the following values.

`type`

The identity type.

- `SAMLUser` – The request was made with SAML assertion.
- `WebIdentityUser` – The request was made by a web identity federation provider.

principalId

A unique identifier for the entity that made the call.

- For `SAMLUser`, this is a combination of the `saml:namequalifier` and `saml:sub` keys.
- For `WebIdentityUser`, this is a combination of the issuer, application ID, and user ID.

userName

The name of the identity that made the call.

- For `SAMLUser`, this is the `saml:sub` key.
- For `WebIdentityUser`, this is the user ID.

identityProvider

The principal name of the external identity provider. This field appears only for `SAMLUser` or `WebIdentityUser` types.

- For `SAMLUser`, this is the `saml:namequalifier` key for the SAML assertion.
- For `WebIdentityUser`, this is the issuer name of the web identity federation provider. This can be a provider that you configured, such as the following:
 - `cognito-identity.amazon.com` for Amazon Cognito
 - `www.amazon.com` for Login with Amazon
 - `accounts.google.com` for Google
 - `graph.facebook.com` for Facebook

The following is an example `userIdentity` element for the `AssumeRoleWithWebIdentity` action.

```
"userIdentity": {
  "type": "WebIdentityUser",
  "principalId": "accounts.google.com:application-id.apps.googleusercontent.com:user-id",
  "userName": "user-id",
  "identityProvider": "accounts.google.com"
}
```

For example logs of how the `userIdentity` element appears for `SAMLUser` and `WebIdentityUser` types, see [Logging IAM and AWS STS API calls with AWS CloudTrail](#).

AWS STS source identity

An IAM administrator can configure AWS Security Token Service to require that users specify their identity when they use temporary credentials to assume roles. The `sourceIdentity` field occurs in events when users assume an IAM role or perform any actions with the assumed role.

The `sourceIdentity` field identifies the original user identity making the request, whether that user's identity is an IAM user, an IAM role, a user authenticated by using SAML-based federation, or a user authenticated by using OpenID Connect (OIDC)-compliant web identity federation. After the IAM administrator configures AWS STS, CloudTrail logs `sourceIdentity` information in the following events and locations within the event record:

- The AWS STS `AssumeRole`, `AssumeRoleWithSAML`, or `AssumeRoleWithWebIdentity` calls that a user identity makes when it assumes a role. `sourceIdentity` is found in the `requestParameters` block of the AWS STS calls.
- The AWS STS `AssumeRole`, `AssumeRoleWithSAML`, or `AssumeRoleWithWebIdentity` calls that a user identity makes if it uses a role to assume another role, known as [role chaining](#). `sourceIdentity` is found in the `requestParameters` block of the AWS STS calls.
- The AWS service API calls that the user identity makes while assuming a role and using the temporary credentials assigned by AWS STS. In service API events, `sourceIdentity` is found in the `sessionContext` block. For example, if a user identity creates a new S3 bucket, `sourceIdentity` occurs in the `sessionContext` block of the `CreateBucket` event.

For more information about how to configure AWS STS to collect source identity information, see [Monitor and control actions taken with assumed roles](#) in the *IAM User Guide*. For more information about AWS STS events that are logged to CloudTrail, see [Logging IAM and AWS STS API calls with AWS CloudTrail](#) in the *IAM User Guide*.

The following are example snippets of events that show the `sourceIdentity` field.

Example `requestParameters` section

In the following example event snippet, a user makes an AWS STS `AssumeRole` request, and sets a source identity, represented here by *source-identity-value-set*. The user assumes a

role represented by the role ARN `arn:aws:iam::123456789012:role/Assumed_Role`. The `sourceIdentity` field is in the `requestParameters` block of the event.

```
"eventVersion": "1.05",
  "userIdentity": {
    "type": "AWSAccount",
    "principalId": "AIDAJ45Q7YFFAREXAMPLE",
    "accountId": "123456789012"
  },
  "eventTime": "2020-04-02T18:20:53Z",
  "eventSource": "sts.amazonaws.com",
  "eventName": "AssumeRole",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "203.0.113.64",
  "userAgent": "aws-cli/1.16.96 Python/3.6.0 Windows/10 botocore/1.12.86",
  "requestParameters": {
    "roleArn": "arn:aws:iam::123456789012:role/Assumed_Role",
    "roleSessionName": "Test1",
    "sourceIdentity": "source-identity-value-set",
  },
```

Example responseElements section

In the following example event snippet, a user makes an AWS STS AssumeRole request to assume a role named `Developer_Role`, and sets a source identity, `Admin`. The user assumes a role represented by the role ARN `arn:aws:iam::111122223333:role/Developer_Role`. The `sourceIdentity` field is shown in both the `requestParameters` and `responseElements` blocks of the event. The temporary credentials used to assume the role, the session token string, and the assumed role ID, session name, and session ARN are shown in the `responseElements` block, along with the source identity.

```
"requestParameters": {
  "roleArn": "arn:aws:iam::111122223333:role/Developer_Role",
  "roleSessionName": "Session_Name",
  "sourceIdentity": "Admin"
},
"responseElements": {
  "credentials": {
    "accessKeyId": "ASIAIOSFODNN7EXAMPLE",
    "expiration": "Jan 22, 2021 12:46:28 AM",
    "sessionToken": "XXYYaz...
                    EXAMPLE_SESSION_TOKEN"
```

```

        XXyYaZAz"
    },
    "assumedRoleUser": {
        "assumedRoleId": "AR0ACKCEVSQ6C2EXAMPLE:Session_Name",
        "arn": "arn:aws:sts::111122223333:assumed-role/Developer_Role/Session_Name"
    },
    "sourceIdentity": "Admin"
}
...

```

Example sessionContext section

In the following example event snippet, a user is assuming a role named DevRole to call an AWS service API. The user sets a source identity, represented here by *source-identity-value-set*. The sourceIdentity field is in the sessionContext block, within the userIdentity block of the event.

```

{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "AssumedRole",
    "principalId": "AR0AJ45Q7YFFAREXAMPLE: Dev1",
    "arn": "arn: aws: sts: : 123456789012: assumed-role/DevRole/Dev1",
    "accountId": "123456789012",
    "accessKeyId": "ASIAIOSFODNN7EXAMPLE",
    "sessionContext": {
      "sessionIssuer": {
        "type": "Role",
        "principalId": "AR0AJ45Q7YFFAREXAMPLE",
        "arn": "arn: aws: iam: : 123456789012: role/DevRole",
        "accountId": "123456789012",
        "userName": "DevRole"
      },
      "webIdFederationData": {},
      "attributes": {
        "mfaAuthenticated": "false",
        "creationDate": "2021-02-21T23: 46: 28Z"
      }
    },
    "sourceIdentity": "source-identity-value-set"
  }
}

```

Non-API events captured by CloudTrail

In addition to logging AWS API calls, CloudTrail captures other related events that might have a security or compliance impact on your AWS account or that might help you troubleshoot operational problems.

- [AWS service events](#) – CloudTrail supports logging non-API service events. These events are created by AWS services but are not directly triggered by a request to a public AWS API. For these events, the `eventType` field is `AwsServiceEvent`.
- [AWS Management Console sign-in events](#) – CloudTrail logs attempts to sign in to the AWS Management Console, the AWS Discussion Forums, and the AWS Support Center. All IAM user and root user sign-in events, as well as all federated user sign-in events, generate records in CloudTrail. For sign-in events, the `eventType` field is `AwsConsoleSignIn`.

AWS service events

CloudTrail supports logging non-API service events. These events are created by AWS services but are not directly triggered by a request to a public AWS API. For these events, the `eventType` field is `AwsServiceEvent`.

The following is an example scenario of an AWS service event when a customer managed key is automatically rotated in AWS Key Management Service (AWS KMS). For more information about rotating KMS keys, see [Rotating KMS keys](#).

```
{
  "eventVersion": "1.08",
  "userIdentity": {
    "accountId": "111122223333",
    "invokedBy": "AWS Internal"
  },
  "eventTime": "2021-01-14T01:41:59Z",
  "eventSource": "kms.amazonaws.com",
  "eventName": "RotateKey",
  "awsRegion": "us-west-2",
  "sourceIPAddress": "AWS Internal",
  "userAgent": "AWS Internal",
  "requestParameters": null,
  "responseElements": null,
  "eventID": "a24b3967-ddad-417f-9b22-2332b918db06",
  "readOnly": false,
```



```
"resources": [
  {
    "accountId": "111122223333",
    "type": "AWS::KMS::Key",
    "ARN": "arn:aws:kms:us-west-2:111122223333:key/1234abcd-12ab-34cd-56ef-1234567890ab"
  }
],
"eventType": "AwsServiceEvent",
"recipientAccountId": "111122223333",
"serviceEventDetails": {
  "rotationType": "AUTOMATIC",
  "keyId": "1234abcd-12ab-34cd-56ef-1234567890ab"
},
"eventCategory": "Management"
}
```

AWS Management Console sign-in events

CloudTrail logs attempts to sign in to the AWS Management Console, the AWS Discussion Forums, and the AWS Support Center. All IAM user and root user sign-in events, as well as all federated user sign-in events, generate records in CloudTrail log files. For information about finding and viewing logs, see [Finding your CloudTrail log files](#) and [Downloading your CloudTrail log files](#).

You can use [AWS User Notifications](#) to set up delivery channels to get notified about AWS CloudTrail events. You receive a notification when an event matches a rule that you specify. You can receive notifications for events through multiple channels, including email, [Amazon Q Developer in chat applications](#) chat notifications, or [AWS Console Mobile Application](#) push notifications. You can also see notifications in the [Console Notifications Center](#). User Notifications supports aggregation, which can reduce the number of notifications you receive during specific events.

Note

The Region recorded in a ConsoleLogin event varies based on the user type and whether you use a global or regional endpoint to sign in.

- If you sign in as the root user, CloudTrail records the event in us-east-1.
- If you sign in with an IAM user and use the global endpoint, CloudTrail records the Region of the ConsoleLogin event as follows:

- If an account alias cookie is present in the browser, CloudTrail records the ConsoleLogin event in one of the following regions: us-east-2, eu-north-1, or ap-southeast-2. This is because the console proxy redirects the user based on the latency from the user sign-in location.
- If an account alias cookie is not present in the browser, CloudTrail records the ConsoleLogin event in us-east-1. This is because the console proxy redirects back to the global sign-in.
- If you sign in with an IAM user and use a [Regional endpoint](#), CloudTrail records the ConsoleLogin event in the appropriate Region for the endpoint. For more information about AWS Sign-In endpoints, see [AWS Sign-In endpoints and quotas](#).

Topics

- [Example event records for IAM users](#)
- [Example event records for root users](#)
- [Example event records for federated users](#)

Example event records for IAM users

The following examples show event records for several IAM user sign-in scenarios.

Topics

- [IAM user, successful sign-in without MFA](#)
- [IAM user, successful sign-in with MFA](#)
- [IAM user, unsuccessful sign-in](#)
- [IAM user, sign-in process checks for MFA \(single MFA device type\)](#)
- [IAM user, sign-in process checks for MFA \(multiple MFA device types\)](#)

IAM user, successful sign-in without MFA

The following record shows that a user named Anaya successfully signed in to the AWS Management Console without using multi-factor authentication (MFA).

```
{  
  "eventVersion": "1.08",
```

```

    "userIdentity": {
      "type": "IAMUser",
      "principalId": "EXAMPLE6E4XEGITWATV6R",
      "arn": "arn:aws:iam::999999999999:user/Anaya",
      "accountId": "999999999999",
      "userName": "Anaya"
    },
    "eventTime": "2023-07-19T21:44:40Z",
    "eventSource": "signin.amazonaws.com",
    "eventName": "ConsoleLogin",
    "awsRegion": "us-east-1",
    "sourceIPAddress": "192.0.2.0",
    "userAgent": "Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:102.0) Gecko/20100101
Firefox/102.0",
    "requestParameters": null,
    "responseElements": {
      "ConsoleLogin": "Success"
    },
    "additionalEventData": {
      "LoginTo": "https://console.aws.amazon.com/console/home?hashArgs=
%23&isauthcode=true&state=hashArgsFromTB_us-east-1_examplee9aba7f8",
      "MobileVersion": "No",
      "MFAUsed": "No"
    },
    "eventID": "e1bf1000-86a4-4a78-81d7-EXAMPLE83102",
    "readOnly": false,
    "eventType": "AwsConsoleSignIn",
    "managementEvent": true,
    "recipientAccountId": "999999999999",
    "eventCategory": "Management",
    "tlsDetails": {
      "tlsVersion": "TLSv1.3",
      "cipherSuite": "TLS_AES_128_GCM_SHA256",
      "clientProvidedHostHeader": "us-east-1.signin.aws.amazon.com"
    }
  }
}

```

IAM user, successful sign-in with MFA

The following record shows that an IAM user named Anaya successfully signed in to the AWS Management Console using multi-factor authentication (MFA).

```
{
```

```

    "eventVersion": "1.08",
    "userIdentity": {
      "type": "IAMUser",
      "principalId": "EXAMPLE6E4XEGITWATV6R",
      "arn": "arn:aws:iam::999999999999:user/Anaya",
      "accountId": "999999999999",
      "userName": "Anaya"
    },
    "eventTime": "2023-07-19T22:01:30Z",
    "eventSource": "signin.amazonaws.com",
    "eventName": "ConsoleLogin",
    "awsRegion": "us-east-1",
    "sourceIPAddress": "192.0.2.0",
    "userAgent": "Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:102.0) Gecko/20100101
Firefox/102.0",
    "requestParameters": null,
    "responseElements": {
      "ConsoleLogin": "Success"
    },
    "additionalEventData": {
      "LoginTo": "https://console.aws.amazon.com/console/home?hashArgs=
%23&isauthcode=true&state=hashArgsFromTB_us-east-1_examplebde32f3c9",
      "MobileVersion": "No",
      "MFAIdentifier": "arn:aws:iam::999999999999:mfa/mfa-device",
      "MFAUsed": "Yes"
    },
    "eventID": "e1f76697-5beb-46e8-9cfc-EXAMPLEbde31",
    "readOnly": false,
    "eventType": "AwsConsoleSignIn",
    "managementEvent": true,
    "recipientAccountId": "999999999999",
    "eventCategory": "Management",
    "tlsDetails": {
      "tlsVersion": "TLSv1.3",
      "cipherSuite": "TLS_AES_128_GCM_SHA256",
      "clientProvidedHostHeader": "us-east-1.signin.aws.amazon.com"
    }
  }
}

```

IAM user, unsuccessful sign-in

The following record shows an unsuccessful sign-in attempt from an IAM user named Paulo.

```
{
```

```

    "eventVersion": "1.08",
    "userIdentity": {
      "type": "IAMUser",
      "principalId": "EXAMPLE6E4XEGITWATV6R",
      "accountId": "123456789012",
      "accessKeyId": "",
      "userName": "Paulo"
    },
    "eventTime": "2023-07-19T22:01:20Z",
    "eventSource": "signin.amazonaws.com",
    "eventName": "ConsoleLogin",
    "awsRegion": "us-east-1",
    "sourceIPAddress": "192.0.2.0",
    "userAgent": "Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:102.0) Gecko/20100101
Firefox/102.0",
    "errorMessage": "Failed authentication",
    "requestParameters": null,
    "responseElements": {
      "ConsoleLogin": "Failure"
    },
    "additionalEventData": {
      "LoginTo": "https://console.aws.amazon.com/console/home?hashArgs=
%23&isauthcode=true&state=hashArgsFromTB_us-east-1_examplebde32f3c9",
      "MobileVersion": "No",
      "MFAUsed": "Yes"
    },
    "eventID": "66c97220-2b7d-43b6-a7a0-EXAMPLEbae9c",
    "readOnly": false,
    "eventType": "AwsConsoleSignIn",
    "managementEvent": true,
    "recipientAccountId": "123456789012",
    "eventCategory": "Management",
    "tlsDetails": {
      "tlsVersion": "TLSv1.3",
      "cipherSuite": "TLS_AES_128_GCM_SHA256",
      "clientProvidedHostHeader": "us-east-1.signin.aws.amazon.com"
    }
  }
}

```

IAM user, sign-in process checks for MFA (single MFA device type)

The following shows that the sign-process checked whether multi-factor authentication (MFA) is required for an IAM user during sign-in. In this example, the `mfaType` value is `U2F` MFA, which

indicates that the IAM user enabled either a single MFA device or multiple MFA devices of the same type (U2F MFA).

```
{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "EXAMPLE6E4XEGITWATV6R",
    "accountId": "123456789012",
    "accessKeyId": "",
    "userName": "Alice"
  },
  "eventTime": "2023-07-19T22:01:26Z",
  "eventSource": "signin.amazonaws.com",
  "eventName": "CheckMfa",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.0",
  "userAgent": "Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:102.0) Gecko/20100101 Firefox/102.0",
  "requestParameters": null,
  "responseElements": {
    "CheckMfa": "Success"
  },
  "additionalEventData": {
    "MfaType": "Virtual MFA"
  },
  "eventID": "7d8a0746-b2e7-44f5-9917-EXAMPLEfb77c",
  "readOnly": false,
  "eventType": "AwsConsoleSignIn",
  "managementEvent": true,
  "recipientAccountId": "123456789012",
  "eventCategory": "Management",
  "tlsDetails": {
    "tlsVersion": "TLSv1.3",
    "cipherSuite": "TLS_AES_128_GCM_SHA256",
    "clientProvidedHostHeader": "us-east-1.signin.aws.amazon.com"
  }
}
```

IAM user, sign-in process checks for MFA (multiple MFA device types)

The following shows that the sign-process checked whether multi-factor authentication (MFA) is required for an IAM user during sign-in. In this example, the `mfaType` value is `Multiple MFA Devices`, which indicates that the IAM user enabled multiple MFA device types.

```
{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "EXAMPLE6E4XEGITWATV6R",
    "accountId": "123456789012",
    "accessKeyId": "",
    "userName": "Mary"
  },
  "eventTime": "2023-07-19T23:10:09Z",
  "eventSource": "signin.amazonaws.com",
  "eventName": "CheckMfa",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.0",
  "userAgent": "Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:102.0) Gecko/20100101 Firefox/102.0",
  "requestParameters": null,
  "responseElements": {
    "CheckMfa": "Success"
  },
  "additionalEventData": {
    "MfaType": "Multiple MFA Devices"
  },
  "eventID": "19bd1a1c-76b1-4806-9d8f-EXAMPLE02a96",
  "readOnly": false,
  "eventType": "AwsConsoleSignIn",
  "managementEvent": true,
  "recipientAccountId": "123456789012",
  "eventCategory": "Management",
  "tlsDetails": {
    "tlsVersion": "TLSv1.3",
    "cipherSuite": "TLS_AES_128_GCM_SHA256",
    "clientProvidedHostHeader": "signin.aws.amazon.com"
  }
}
```

Example event records for root users

The following examples show event records for several root user sign-in scenarios. When you sign-in using the root user, CloudTrail records the ConsoleLogin event in us-east-1.

Topics

- [Root user, successful sign-in without MFA](#)
- [Root user, successful sign-in with MFA](#)
- [Root user, unsuccessful sign-in](#)
- [Root user, MFA changed](#)
- [Root user, password changed](#)

Root user, successful sign-in without MFA

The following shows a successful sign-in event for a root user not using multi-factor authentication (MFA).

```
{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "Root",
    "principalId": "111122223333",
    "arn": "arn:aws:iam::111122223333:root",
    "accountId": "111122223333",
    "accessKeyId": ""
  },
  "eventTime": "2023-07-12T13:35:31Z",
  "eventSource": "signin.amazonaws.com",
  "eventName": "ConsoleLogin",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.0",
  "userAgent": "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML,
like Gecko) Chrome/114.0.0.0 Safari/537.36",
  "requestParameters": null,
  "responseElements": {
    "ConsoleLogin": "Success"
  },
  "additionalEventData": {
```



```

      "LoginTo": "https://console.aws.amazon.com/console/home?hashArgs=%23&isauthcode=true&nc2=h_ct&src=header-signin&state=hashArgsFromTB_ap-southeast-2_example80afacd389",
      "MobileVersion": "No",
      "MFAUsed": "No"
    },
    "eventID": "4217cc13-7328-4820-a90c-EXAMPLE8002e6",
    "readOnly": false,
    "eventType": "AwsConsoleSignIn",
    "managementEvent": true,
    "recipientAccountId": "111122223333",
    "eventCategory": "Management",
    "tlsDetails": {
      "tlsVersion": "TLSv1.3",
      "cipherSuite": "TLS_AES_128_GCM_SHA256",
      "clientProvidedHostHeader": "signin.aws.amazon.com"
    }
  }
}

```

Root user, successful sign-in with MFA

The following shows a successful sign-in event for a root user using multi-factor authentication (MFA).

```

{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "Root",
    "principalId": "444455556666",
    "arn": "arn:aws:iam::444455556666:root",
    "accountId": "444455556666",
    "accessKeyId": ""
  },
  "eventTime": "2023-07-13T03:04:43Z",
  "eventSource": "signin.amazonaws.com",
  "eventName": "ConsoleLogin",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.0",
  "userAgent": "Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/114.0.0.0 Safari/537.36",
  "requestParameters": null,
  "responseElements": {
    "ConsoleLogin": "Success"
  }
}

```

```

    },
    "additionalEventData": {
      "LoginTo": "https://ap-southeast-1.console.aws.amazon.com/ec2/home?region=ap-southeast-1&state=hashArgs%3Ainstances%3Av%3D3%3B%24case%3Dtags%3Atrue%255C%2Cclient%3Afalse%3B%24regex%3Dtags%3Afalse%255C%2Cclient%3Afalse&isauthcode=true",
      "MobileVersion": "No",
      "MFAIdentifier": "arn:aws:iam::444455556666:mfa/root-account-mfa-device",
      "MFAUsed": "Yes"
    },
    "eventID": "e0176723-ea76-4275-83a3-EXAMPLEf03fb",
    "readOnly": false,
    "eventType": "AwsConsoleSignIn",
    "managementEvent": true,
    "recipientAccountId": "444455556666",
    "eventCategory": "Management",
    "tlsDetails": {
      "tlsVersion": "TLSv1.3",
      "cipherSuite": "TLS_AES_128_GCM_SHA256",
      "clientProvidedHostHeader": "signin.aws.amazon.com"
    }
  }
}

```

Root user, unsuccessful sign-in

The following shows an unsuccessful sign-in event for a root user not using MFA.

```

{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "Root",
    "principalId": "123456789012",
    "arn": "arn:aws:iam::123456789012:root",
    "accountId": "123456789012",
    "accessKeyId": ""
  },
  "eventTime": "2023-07-16T04:33:40Z",
  "eventSource": "signin.amazonaws.com",
  "eventName": "ConsoleLogin",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.0",
  "userAgent": "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/111.0.0.0 Safari/537.36",
  "errorMessage": "Failed authentication",
  "requestParameters": null,

```

```

    "responseElements": {
      "ConsoleLogin": "Failure"
    },
    "additionalEventData": {
      "LoginTo": "https://us-east-1.console.aws.amazon.com/billing/home?region=us-east-1&state=hashArgs%23%2Faccount&isauthcode=true",
      "MobileVersion": "No",
      "MFAUsed": "No"
    },
    "eventID": "f28d4329-5050-480b-8de0-EXAMPLE07329",
    "readOnly": false,
    "eventType": "AwsConsoleSignIn",
    "managementEvent": true,
    "recipientAccountId": "123456789012",
    "eventCategory": "Management",
    "tlsDetails": {
      "tlsVersion": "TLSv1.3",
      "cipherSuite": "TLS_AES_128_GCM_SHA256",
      "clientProvidedHostHeader": "signin.aws.amazon.com"
    }
  }
}

```

Root user, MFA changed

The following shows an example event for a root user changing multi-factor authentication (MFA) settings.

```

{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "Root",
    "principalId": "111122223333",
    "arn": "arn:aws:iam::111122223333:root",
    "accountId": "111122223333",
    "accessKeyId": "EXAMPLE4XX3IEV4PFQTH",
    "userName": "AWS_ROOT_USER",
    "sessionContext": {
      "sessionIssuer": {},
      "webIdFederationData": {},
      "attributes": {
        "creationDate": "2023-07-15T03:51:12Z",
        "mfaAuthenticated": "false"
      }
    }
  }
}

```

```

    }
  },
  "eventTime": "2023-07-15T04:37:08Z",
  "eventSource": "iam.amazonaws.com",
  "eventName": "EnableMFADevice",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.0",
  "userAgent": "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML,
like Gecko) Chrome/111.0.0.0 Safari/537.36",
  "requestParameters": {
    "userName": "AWS_ROOT_USER",
    "serialNumber": "arn:aws:iam::111122223333:mfa/root-account-mfa-device"
  },
  "responseElements": null,
  "requestID": "9b45cd4c-a598-41e7-9170-EXAMPLE535f0",
  "eventID": "b4f18d55-d36f-49a0-afcb-EXAMPLEc026b",
  "readOnly": false,
  "eventType": "AwsApiCall",
  "managementEvent": true,
  "recipientAccountId": "111122223333",
  "eventCategory": "Management",
  "sessionCredentialFromConsole": "true"
}

```

Root user, password changed

The following shows an example event for a root user changing their password.

```

{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "Root",
    "principalId": "444455556666",
    "arn": "arn:aws:iam::444455556666:root",
    "accountId": "444455556666",
    "accessKeyId": "EXAMPLEA0TKEG44KPW5P",
    "sessionContext": {
      "sessionIssuer": {},
      "webIdFederationData": {},
      "attributes": {
        "creationDate": "2022-11-25T13:01:14Z",
        "mfaAuthenticated": "false"
      }
    }
  }
}

```

```
  },
  "eventTime": "2022-11-25T13:01:14Z",
  "eventSource": "iam.amazonaws.com",
  "eventName": "ChangePassword",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.0",
  "userAgent": "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML,
like Gecko) Chrome/111.0.0.0 Safari/537.36",
  "requestParameters": null,
  "responseElements": null,
  "requestID": "c64254c2-e4ff-49c0-900e-EXAMPLE9e6d2",
  "eventID": "d059176c-4f4d-4a9e-b8d7-EXAMPLE2b7b3",
  "readOnly": false,
  "eventType": "AwsApiCall",
  "managementEvent": true,
  "recipientAccountId": "444455556666",
  "eventCategory": "Management"
}
```

Example event records for federated users

The following examples show event records for federated users. Federated users are given temporary security credentials to access AWS resources through an [AssumeRole](#) request.

The following shows an example event for a federation encryption request. The original access key ID is provided in the `accessKeyId` field of the `userIdentity` element. The `accessKeyId` field in the `responseElements` contains a new access key ID if the requested `sessionDuration` is passed in the encryption request, otherwise it contains the value of the original access key ID.

Note

In this example, the `mfaAuthenticated` value is `false` and the `MFAUsed` value is `No` because the request was made by a federated user. These fields will only be set to `true` if the request was made by an IAM user or root user using MFA.

```
{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "AssumedRole",
    "principalId": "EXAMPLEUU4MH70YK5ZCOA:JohnDoe",
```

```

    "arn": "arn:aws:sts::123456789012:assumed-role/roleName/JohnDoe",
    "accountId": "123456789012",
    "accessKeyId": "originalAccessKeyId",
    "sessionContext": {
      "sessionIssuer": {
        "type": "Role",
        "principalId": "EXAMPLEUU4MH70YK5ZCOA",
        "arn": "arn:aws:iam::123456789012:role/roleName",
        "accountId": "123456789012",
        "userName": "roleName"
      },
      "webIdFederationData": {},
      "attributes": {
        "creationDate": "2023-09-25T21:30:39Z",
        "mfaAuthenticated": "false"
      }
    },
    "eventTime": "2023-09-25T21:30:39Z",
    "eventSource": "signin.amazonaws.com",
    "eventName": "GetSigninToken",
    "awsRegion": "us-east-1",
    "sourceIPAddress": "192.0.2.0",
    "userAgent": "Java/1.8.0_382",
    "requestParameters": null,
    "responseElements": {
      "credentials": {
        "accessKeyId": "accessKeyId"
      },
      "GetSigninToken": "Success"
    },
    "additionalEventData": {
      "MobileVersion": "No",
      "MFAUsed": "No"
    },
    "eventID": "1d66615b-a417-40da-a38e-EXAMPLE8c89b",
    "readOnly": false,
    "eventType": "AwsConsoleSignIn",
    "managementEvent": true,
    "recipientAccountId": "123456789012",
    "eventCategory": "Management",
    "tlsDetails": {
      "tlsVersion": "TLSv1.3",
      "cipherSuite": "TLS_AES_128_GCM_SHA256",

```

```

    "clientProvidedHostHeader": "us-east-1.signin.aws.amazon.com"
  }
}

```

The following shows a successful sign-in event for a federated user; not using multi-factor authentication (MFA).

```

{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "AssumedRole",
    "principalId": "EXAMPLEPHCNW7ZCASLJOH:JohnDoe",
    "arn": "arn:aws:sts::123456789012:assumed-role/RoLeName/JohnDoe",
    "accountId": "123456789012",
    "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
    "sessionContext": {
      "sessionIssuer": {
        "type": "Role",
        "principalId": "EXAMPLEPHCNW7ZCASLJOH",
        "arn": "arn:aws:iam::123456789012:role/RoLeName",
        "accountId": "123456789012",
        "userName": "RoLeName"
      },
      "webIdFederationData": {},
      "attributes": {
        "creationDate": "2023-09-22T16:15:47Z",
        "mfaAuthenticated": "false"
      }
    }
  },
  "eventTime": "2023-09-22T16:15:47Z",
  "eventSource": "signin.amazonaws.com",
  "eventName": "ConsoleLogin",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.0",
  "userAgent": "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/116.0.0.0 Safari/537.36",
  "requestParameters": null,
  "responseElements": {
    "ConsoleLogin": "Success"
  },
  "additionalEventData": {
    "MobileVersion": "No",

```

```
    "MFAUsed": "No"
  },
  "eventID": "b73f1ec6-c064-4cd3-ba83-EXAMPLE441d7",
  "readOnly": false,
  "eventType": "AwsConsoleSignIn",
  "managementEvent": true,
  "recipientAccountId": "123456789012",
  "eventCategory": "Management",
  "tlsDetails": {
    "tlsVersion": "TLSv1.3",
    "cipherSuite": "TLS_AES_128_GCM_SHA256",
    "clientProvidedHostHeader": "us-east-1.signin.aws.amazon.com"
  }
}
```


Working with CloudTrail log files

You can perform more advanced tasks with your CloudTrail files.

- Monitor CloudTrail log files by sending them to CloudWatch Logs.
- Share log files between accounts.
- Use the AWS CloudTrail Processing Library to write log processing applications in Java.
- Validate your log files to verify that they have not changed after delivery by CloudTrail.

When an event occurs in your account, CloudTrail evaluates whether the event matches the settings for your trails. Only events that match your trail settings are delivered to your Amazon S3 bucket and Amazon CloudWatch Logs log group.

You can configure multiple trails differently so that the trails process and log only the events that you specify. For example, one trail can log read-only data and management events, so that all read-only events are delivered to one S3 bucket. Another trail can log only write-only data and management events, so that all write-only events are delivered to a separate S3 bucket.

You can also configure your trails to have one trail log and deliver all management events to one S3 bucket, and configure another trail to log and deliver all data events to another S3 bucket.

You can configure your trails to log the following:

- **[Data events](#)**: These events provide visibility into the resource operations performed on or within a resource. These are also known as data plane operations.
- **[Management events](#)**: Management events provide visibility into management operations that are performed on resources in your AWS account. These are also known as control plane operations. Management events can also include non-API events that occur in your account. For example, when a user logs in to your account, CloudTrail logs the ConsoleLogin event. For more information, see [Non-API events captured by CloudTrail](#).
- **[Network activity events](#)**: CloudTrail network activity events enable VPC endpoint owners to record AWS API calls made using their VPC endpoints from a private VPC to the AWS service. Network activity events provide visibility into the resource operations performed within a VPC.
- **[Insights events](#)**: Insights events capture unusual activity that is detected in your account. If you have Insights events enabled, and CloudTrail detects unusual activity, Insights events are logged to the destination S3 bucket for your trail, but in a different folder. You can also see the type

of Insights event and the incident time period when you view Insights events on the CloudTrail console. Unlike other types of events captured in a CloudTrail trail, Insights events are logged only when CloudTrail detects changes in your account's API usage that differ significantly from the account's typical usage patterns.

Insights events are generated only for management APIs. For more information, see [Working with CloudTrail Insights](#).

Note

CloudTrail typically delivers logs within an average of about 5 minutes of an API call. This time is not guaranteed. Review the [AWS CloudTrail Service Level Agreement](#) for more information.

If you misconfigure your trail (for example, the S3 bucket is unreachable), CloudTrail will attempt to redeliver the log files to your S3 bucket for 30 days, and these attempted-to-deliver events will be subject to standard CloudTrail charges. To avoid charges on a misconfigured trail, you need to delete the trail.

Topics

- [Receiving CloudTrail log files from multiple Regions](#)
- [Managing data consistency in CloudTrail](#)
- [Monitoring CloudTrail Log Files with Amazon CloudWatch Logs](#)
- [Receiving CloudTrail log files from multiple accounts](#)
- [Sharing CloudTrail log files between AWS accounts](#)
- [Validating CloudTrail log file integrity](#)
- [CloudTrail log file examples](#)
- [Using the CloudTrail Processing Library](#)

Receiving CloudTrail log files from multiple Regions

When you create a multi-Region trail, CloudTrail logs events from all Regions enabled in your account. CloudTrail delivers log files to the same S3 bucket and CloudWatch Logs log group. As

long as CloudTrail has permissions to write to an S3 bucket, the bucket for a multi-Region trail does not have to be in the trail's home Region.

Although most AWS Regions are enabled by default for your AWS account, you must manually enable certain Regions (also referred to as *opt-in Regions*). For information about which Regions are enabled by default, see [Considerations before enabling and disabling Regions](#) in the *AWS Account Management Reference Guide*. For the list of Regions CloudTrail supports, see [CloudTrail supported Regions](#).

After you enable an opt-in Region, CloudTrail creates an identical copy of each multi-Region trail in the opt-in Region that you enabled. For more information, see [What happens when you enable an opt-in Region?](#).

If you later disable an opt-in Region, the copy of the multi-Region trail in that Region will remain. Because your account may have activity in the Region you disabled, such as actions by AWS services to remove resources, CloudTrail will continue to capture activity and attempt to deliver events to the S3 bucket for any trails that are not deleted before the Region is disabled.

To convert an existing single-Region trail to a multi-Region trail, you must use the AWS CLI.

To change an existing trail so that it applies to all enabled Regions, add the `--is-multi-region-trail` option to the [update-trail](#) command.

```
aws cloudtrail update-trail --name my-trail --is-multi-region-trail
```

To confirm that the trail is now a multi-Region trail, verify that the `IsMultiRegionTrail` element in the output shows `true`.

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "my-trail",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/my-trail",
  "LogFileValidationEnabled": false,
  "IsMultiRegionTrail": true,
  "IsOrganizationTrail": false,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

For more information, see the following resources:

- [Understanding multi-Region trails and opt-in Regions](#)

- [Creating a trail for your AWS account](#)
- [CloudTrail FAQs](#)

Managing data consistency in CloudTrail

CloudTrail uses a distributed computing model called [eventual consistency](#). Any change that you make to your CloudTrail configuration (or other AWS services), including tags used in [attribute-based access control \(ABAC\)](#), takes time to become visible from all possible endpoints. Some of the delay results from the time it takes to send the data from server to server, and from Region to Region around the world. CloudTrail also uses caching to improve performance, but in some cases this can add time. The change might not be visible until the previously cached data times out.

You must design your applications to account for these potential delays. Ensure that they work as expected, even when a change made in one location is not instantly visible at another. Such changes include [enabling an opt-in Region](#), creating or updating trails or event data stores, updating event selectors, and starting or stopping logging. When you create or update a trail or event data store, CloudTrail delivers logs to the S3 bucket or event data store based on the last known configuration until the changes propagate to all locations.

For more information about how this affects other AWS services, see the following resources:

- **Amazon DynamoDB:** [What is the consistency model of DynamoDB?](#) in the *DynamoDB FAQ*, and [Read consistency](#) in the *Amazon DynamoDB Developer Guide*.
- **Amazon EC2:** [Eventual consistency](#) in the *Amazon Elastic Compute Cloud API Reference*.
- **Amazon EMR:** [Ensuring Consistency When Using Amazon S3 and Amazon Elastic MapReduce for ETL Workflows](#) in the *AWS Big Data Blog*.
- **AWS Identity and Access Management (IAM):** [Changes that I make are not always immediately visible](#) in the *IAM User Guide*.
- **Amazon Redshift:** [Managing data consistency](#) in the *Amazon Redshift Database Developer Guide*.
- **Amazon S3:** [Amazon S3 data consistency model](#) in the *Amazon Simple Storage Service User Guide*.

Monitoring CloudTrail Log Files with Amazon CloudWatch Logs

You can use [Amazon CloudWatch Logs](#) to monitor, store, and access your log files from CloudTrail.

CloudWatch Logs enables you to centralize the logs from all of your systems, applications, and AWS services that you use, in a single, highly scalable service. You can then easily view them, search them for specific error codes or patterns, filter them based on specific fields, or archive them securely for future analysis. CloudWatch Logs enables you to see all of your logs, regardless of their source, as a single and consistent flow of events ordered by time.

Complete the following steps to configure CloudTrail with CloudWatch Logs to monitor your trail logs and be notified when specific activity occurs.

1. Configure your trail to send log events to CloudWatch Logs.
2. Define CloudWatch Logs metric filters to evaluate log events for matches in terms, phrases, or values. For example, you can monitor for ConsoleLogin events.
3. Assign CloudWatch metrics to the metric filters.
4. Create CloudWatch alarms that are triggered according to thresholds and time periods that you specify. You can configure alarms to send notifications when alarms are triggered, so that you can take action.
5. You can also configure CloudWatch to automatically perform an action in response to an alarm.

Standard pricing for Amazon CloudWatch and Amazon CloudWatch Logs applies. For more information, see [Amazon CloudWatch Pricing](#).

For more information about the Regions in which you can configure your trails to send logs to CloudWatch Logs, see [Amazon CloudWatch Logs Regions and Quotas](#) in the *AWS General Reference*.

Topics

- [Sending events to CloudWatch Logs](#)
- [Creating CloudWatch alarms for CloudTrail events: examples](#)
- [Stopping CloudTrail from sending events to CloudWatch Logs](#)
- [CloudWatch log group and log stream naming for CloudTrail](#)
- [Role policy document for CloudTrail to use CloudWatch Logs for monitoring](#)

Sending events to CloudWatch Logs

When you configure your trail to send events to CloudWatch Logs, CloudTrail sends only the events that match your trail settings. For example, if you configure your trail to log data events only, your

trail sends data events only to your CloudWatch Logs log group. CloudTrail supports sending data, Insights, and management events to CloudWatch Logs. For more information, see [Working with CloudTrail log files](#).

Note

Only the management account can configure a CloudWatch Logs log group for an organization trail using the console. The delegated administrator can configure a CloudWatch Logs log group using the AWS CLI or CloudTrail `CreateTrail` or `UpdateTrail` API operations.

To send events to a CloudWatch Logs log group:

- Make sure you have sufficient permissions to create or specify an IAM role. For more information, see [Granting permission to view and configure Amazon CloudWatch Logs information on the CloudTrail console](#).
- If you're configuring the CloudWatch Logs log group using the AWS CLI, make sure you have sufficient permissions to create a CloudWatch Logs log stream in the log group you specify and to deliver CloudTrail events to that log stream. For more information, see [Creating a policy document](#).
- Create a new trail or specify an existing one. For more information, see [Creating and updating a trail with the console](#).
- Create a log group or specify an existing one.
- Specify an IAM role. If you are modifying an existing IAM role for an organization trail, you must manually update the policy to allow logging for the organization trail. For more information, see [this policy example](#) and [Creating a trail for an organization](#).
- Attach a role policy or use the default.

Contents

- [Configuring CloudWatch Logs monitoring with the console](#)
 - [Creating a log group or specifying an existing log group](#)
 - [Specifying an IAM role](#)
 - [Viewing events in the CloudWatch console](#)
- [Configuring CloudWatch Logs monitoring with the AWS CLI](#)

- [Creating a log group](#)
- [Creating a role](#)
- [Creating a policy document](#)
- [Updating the trail](#)
- [Limitation](#)

Configuring CloudWatch Logs monitoring with the console

You can use the AWS Management Console to configure your trail to send events to CloudWatch Logs for monitoring.

Creating a log group or specifying an existing log group

CloudTrail uses a CloudWatch Logs log group as a delivery endpoint for log events. You can create a log group or specify an existing one.

To create or specify a log group for an existing trail

1. Make sure you log in with an administrative user or role with sufficient permissions to configure CloudWatch Logs integration. For more information, see [Granting permission to view and configure Amazon CloudWatch Logs information on the CloudTrail console](#).

Note

Only the management account can configure a CloudWatch Logs log group for an organization trail using the console. The delegated administrator can configure a CloudWatch Logs log group using the AWS CLI or CloudTrail `CreateTrail` or `UpdateTrail` API operations.

2. Open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
3. Choose the trail name. If you choose a multi-Region trail, you will be redirected to the Region in which the trail was created. You can create a log group or choose an existing log group in the same Region as the trail.

 Note

A multi-Region trail sends log files from all enabled Regions in your AWS account to the CloudWatch Logs log group that you specify.

4. In **CloudWatch Logs**, choose **Edit**.
5. For **CloudWatch Logs**, choose **Enabled**.
6. For **Log group name**, choose **New** to create a new log group, or **Existing** to use an existing one. If you choose **New**, CloudTrail specifies a name for the new log group for you, or you can type a name. For more information about naming, see [CloudWatch log group and log stream naming for CloudTrail](#).
7. If you choose **Existing**, choose a log group from the drop-down list.
8. For **Role name**, choose **New** to create a new IAM role for permissions to send logs to CloudWatch Logs. Choose **Existing** to choose an existing IAM role from the drop-down list. The policy statement for the new or existing role is displayed when you expand **Policy document**. For more information about this role, see [Role policy document for CloudTrail to use CloudWatch Logs for monitoring](#).

 Note

When you configure a trail, you can choose an S3 bucket and SNS topic that belong to another account. However, if you want CloudTrail to deliver events to a CloudWatch Logs log group, you must choose a log group that exists in your current account.

9. Choose **Save changes**.

Specifying an IAM role

You can specify a role for CloudTrail to assume to deliver events to the log stream.

To specify a role

1. By default, the `CloudTrail_CloudWatchLogs_Role` is specified for you. The default role policy has the required permissions to create a CloudWatch Logs log stream in a log group that you specify, and to deliver CloudTrail events to that log stream.

Note

If you want to use this role for a log group for an organization trail, you must manually modify the policy after you create the role. For more information, see [this policy example](#) and [Creating a trail for an organization](#).

- a. To verify the role, go to the AWS Identity and Access Management console at <https://console.aws.amazon.com/iam/>.
 - b. Choose **Roles** and then choose the **CloudTrail_CloudWatchLogs_Role**.
 - c. From the **Permissions** tab, expand the policy to view its contents.
2. You can specify another role, but you must attach the required role policy to the existing role if you want to use it to send events to CloudWatch Logs. For more information, see [Role policy document for CloudTrail to use CloudWatch Logs for monitoring](#).

Viewing events in the CloudWatch console

After you configure your trail to send events to your CloudWatch Logs log group, you can view the events in the CloudWatch console. CloudTrail typically delivers events to your log group within an average of about 5 minutes of an API call. This time is not guaranteed. Review the [AWS CloudTrail Service Level Agreement](#) for more information.

To view events in the CloudWatch console

1. Open the CloudWatch console at <https://console.aws.amazon.com/cloudwatch/>.
2. In the left navigation pane, under **Logs**, choose **Log groups**.
3. Choose the log group that you specified for your trail.
4. Choose the log stream that you want to view.
5. To see the details of the event that your trail logged, choose an event.

Note

The **Time (UTC)** column in the CloudWatch console shows when the event was delivered to your log group. To see the actual time that the event was logged by CloudTrail, see the `eventTime` field.

Configuring CloudWatch Logs monitoring with the AWS CLI

You can use the AWS CLI to configure CloudTrail to send events to CloudWatch Logs for monitoring.

Creating a log group

1. If you don't have an existing log group, create a CloudWatch Logs log group as a delivery endpoint for log events using the CloudWatch Logs `create-log-group` command.

```
aws logs create-log-group --log-group-name name
```

The following example creates a log group named `CloudTrail/logs`:

```
aws logs create-log-group --log-group-name CloudTrail/logs
```

2. Retrieve the log group Amazon Resource Name (ARN).

```
aws logs describe-log-groups
```

Creating a role

Create a role for CloudTrail that enables it to send events to the CloudWatch Logs log group. The IAM `create-role` command takes two parameters: a role name and a file path to an assume role policy document in JSON format. The policy document that you use gives `AssumeRole` permissions to CloudTrail. The `create-role` command creates the role with the required permissions.

To create the JSON file that will contain the policy document, open a text editor and save the following policy contents in a file called `assume_role_policy_document.json`.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "",
      "Effect": "Allow",
      "Principal": {
        "Service": "cloudtrail.amazonaws.com"
      },
      "Action": "sts:AssumeRole"
    }
  ]
}
```

Run the following command to create the role with AssumeRole permissions for CloudTrail.

```
aws iam create-role --role-name role_name --assume-role-policy-document file://<path to  
assume_role_policy_document>.json
```

When the command completes, take a note of the role ARN in the output.

Creating a policy document

Create the following role policy document for CloudTrail. This document grants CloudTrail the permissions required to create a CloudWatch Logs log stream in the log group you specify and to deliver CloudTrail events to that log stream.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "AWSCloudTrailCreateLogStream2014110",
      "Effect": "Allow",
      "Action": [
        "logs:CreateLogStream"
      ]
    }
  ]
}
```

```

    ],
    "Resource": [
        "arn:aws:logs:us-east-1:111111111111:log-
group:log_group_name:log-stream:111111111111_CloudTrail_us-east-1*"
    ]
},
{
    "Sid": "AWSCloudTrailPutLogEvents20141101",
    "Effect": "Allow",
    "Action": [
        "logs:PutLogEvents"
    ],
    "Resource": [
        "arn:aws:logs:us-east-1:111111111111:log-
group:log_group_name:log-stream:111111111111_CloudTrail_us-east-1*"
    ]
}
]
}

```

Save the policy document in a file called `role-policy-document.json`.

If you're creating a policy that might be used for organization trails as well, you will need to configure it slightly differently. For example, the following policy grants CloudTrail the permissions required to create a CloudWatch Logs log stream in the log group you specify and to deliver CloudTrail events to that log stream for both trails in the AWS account 111111111111 and for organization trails created in the 111111111111 account that are applied to the AWS Organizations organization with the ID of *o-exampleorgid*:

JSON

```

{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "AWSCloudTrailCreateLogStream20141101",
            "Effect": "Allow",
            "Action": [
                "logs:CreateLogStream"
            ],
            "Resource": [

```

```

        "arn:aws:logs:us-east-2:111111111111:log-group:CloudTrail/
DefaultLogGroupTest:log-stream:111111111111_CloudTrail_us-east-2*",
        "arn:aws:logs:us-east-2:111111111111:log-group:CloudTrail/
DefaultLogGroupTest:log-stream:o-aa111bb222_*"
    ]
},
{
    "Sid": "AWSCloudTrailPutLogEvents20141101",
    "Effect": "Allow",
    "Action": [
        "logs:PutLogEvents"
    ],
    "Resource": [
        "arn:aws:logs:us-east-2:111111111111:log-group:CloudTrail/
DefaultLogGroupTest:log-stream:111111111111_CloudTrail_us-east-2*",
        "arn:aws:logs:us-east-2:111111111111:log-group:CloudTrail/
DefaultLogGroupTest:log-stream:o-aa111bb222_*"
    ]
}
]
}

```

For more information about organization trails, see [Creating a trail for an organization](#).

Run the following command to apply the policy to the role.

```
aws iam put-role-policy --role-name role_name --policy-name cloudtrail-policy --policy-
document file://<path to role-policy-document>.json
```

Updating the trail

Update the trail with the log group and role information using the CloudTrail `update-trail` command.

```
aws cloudtrail update-trail --name trail_name --cloud-watch-logs-log-group-
arn log_group_arn --cloud-watch-logs-role-arn role_arn
```

For more information about the AWS CLI commands, see the [AWS CloudTrail Command Line Reference](#).

Limitation

CloudWatch Logs and EventBridge each [allow a maximum event size of 256 KB](#). Although most service events have a maximum size of 256 KB, some services still have events that are larger. CloudTrail does not send these events to CloudWatch Logs or EventBridge.

Starting with CloudTrail event version 1.05, events have a maximum size of 256 KB. This is to help prevent exploitation by malicious actors, and allow events to be consumed by other AWS services, such as CloudWatch Logs and EventBridge.

Creating CloudWatch alarms for CloudTrail events: examples

This topic describes how to configure alarms for CloudTrail events, and includes examples.

Topics

- [Prerequisites](#)
- [Create a metric filter and create an alarm](#)
- [Example security group configuration changes](#)
- [Example AWS Management Console sign-in failures](#)
- [Example: IAM policy changes](#)
- [Configuring notifications for CloudWatch Logs alarms](#)

Prerequisites

Before you can use the examples in this topic, you must:

- Create a trail with the console or CLI.
- Create a log group, which you can do as part of creating a trail. For more information about creating a trail, see [Creating a trail with the CloudTrail console](#).
- Specify or create an IAM role that grants CloudTrail the permissions to create a CloudWatch Logs log stream in the log group that you specify and to deliver CloudTrail events to that log stream. The default `CloudTrail_CloudWatchLogs_Role` does this for you.

For more information, see [Sending events to CloudWatch Logs](#). Examples in this section are performed in the Amazon CloudWatch Logs console. For more information about how to create

metric filters and alarms, see [Creating metrics from log events using filters](#) and [Using Amazon CloudWatch alarms](#) in the *Amazon CloudWatch User Guide*.

Create a metric filter and create an alarm

To create an alarm, you must first create a metric filter, and then configure an alarm based on the filter. The procedures are shown for all examples. For more information about syntax for metric filters and patterns for CloudTrail log events, see the JSON-related sections of [Filter and pattern syntax](#) in the *Amazon CloudWatch Logs User Guide*.

Example security group configuration changes

Follow this procedure to create an Amazon CloudWatch alarm that is triggered when configuration changes occur on security groups.

Create a metric filter

1. Open the CloudWatch console at <https://console.aws.amazon.com/cloudwatch/>.
2. In the navigation pane, under **Logs**, choose **Log groups**.
3. In the list of log groups, choose the log group that you created for your trail.
4. From the **Metric filters** or **Actions** menu, choose **Create metric filter**.
5. On the **Define pattern** page, in **Create filter pattern**, enter the following for **Filter pattern**.

```
{ ($.eventName = AuthorizeSecurityGroupIngress) || ($.eventName =
  AuthorizeSecurityGroupEgress) || ($.eventName = RevokeSecurityGroupIngress) ||
  ($.eventName = RevokeSecurityGroupEgress) || ($.eventName = CreateSecurityGroup)
  || ($.eventName = DeleteSecurityGroup) }
```

6. In **Test pattern**, leave defaults. Choose **Next**.
7. On the **Assign metric** page, for **Filter name**, enter **SecurityGroupEvents**.
8. In **Metric details**, turn on **Create new**, and then enter **CloudTrailMetrics** for **Metric namespace**.
9. For **Metric name**, type **SecurityGroupEventCount**.
10. For **Metric value**, type **1**.
11. Leave **Default value** blank.
12. Choose **Next**.

13. On the **Review and create** page, review your choices. Choose **Create metric filter** to create the filter, or choose **Edit** to go back and change values.

Create an alarm

After you create the metric filter, the CloudWatch Logs log group details page for your CloudTrail trail log group opens. Follow this procedure to create an alarm.

1. On the **Metric filters** tab, find the metric filter you created in [the section called “Create a metric filter”](#). Fill the check box for the metric filter. In the **Metric filters** bar, choose **Create alarm**.
2. For **Specify metric and conditions**, enter the following.
 - a. For **Graph**, the line is set at **1** based on other settings you make when you create your alarm.
 - b. For **Metric name**, keep the current metric name, **SecurityGroupEventCount**.
 - c. For **Statistic**, keep the default, **Sum**.
 - d. For **Period**, keep the default, **5 minutes**.
 - e. In **Conditions**, for **Threshold type**, choose **Static**.
 - f. For **Whenever *metric_name* is**, choose **Greater/Equal**.
 - g. For the threshold value, enter **1**.
 - h. In **Additional configuration**, leave defaults. Choose **Next**.
3. On the **Configure actions** page, choose **Notification**, and then choose **In alarm**, which indicates that the action is taken when the threshold of 1 change event in 5 minutes is crossed, and **SecurityGroupEventCount** is in an alarm state.
 - a. For **Send a notification to the following SNS topic**, choose **Create new topic**.
 - b. Enter **SecurityGroupChanges_CloudWatch_Alarms_Topic** as the name for the new Amazon SNS topic.
 - c. In **Email endpoints that will receive the notification**, enter the email addresses of users whom you want to receive notifications if this alarm is raised. Separate email addresses with commas.

Each email recipient will receive an email asking them to confirm that they want to be subscribed to the Amazon SNS topic.

- d. Choose **Create topic**.
4. For this example, skip the other action types. Choose **Next**.
5. On the **Add name and description** page, enter a friendly name for the alarm, and a description. For this example, enter **Security group configuration changes** for the name, and **Raises alarms if security group configuration changes occur** for the description. Choose **Next**.
6. On the **Preview and create** page, review your choices. Choose **Edit** to make changes, or choose **Create alarm** to create the alarm.

After you create the alarm, CloudWatch opens the **Alarms** page. The alarm's **Actions** column shows **Pending confirmation** until all email recipients on the SNS topic have confirmed that they want to subscribe to SNS notifications.

Example AWS Management Console sign-in failures

Follow this procedure to create an Amazon CloudWatch alarm that is triggered when there are three or more AWS Management Console sign-in failures during a five minute period.

Create a metric filter

1. Open the CloudWatch console at <https://console.aws.amazon.com/cloudwatch/>.
2. In the navigation pane, under **Logs**, choose **Log groups**.
3. In the list of log groups, choose the log group that you created for your trail.
4. From the **Metric filters** or **Actions** menu, choose **Create metric filter**.
5. On the **Define pattern** page, in **Create filter pattern**, enter the following for **Filter pattern**.

```
{ ($.eventName = ConsoleLogin) && ($.errorMessage = "Failed authentication") }
```

6. In **Test pattern**, leave defaults. Choose **Next**.
7. On the **Assign metric** page, for **Filter name**, enter **ConsoleSignInFailures**.
8. In **Metric details**, turn on **Create new**, and then enter **CloudTrailMetrics** for **Metric namespace**.
9. For **Metric name**, type **ConsoleSigninFailureCount**.
10. For **Metric value**, type **1**.
11. Leave **Default value** blank.

12. Choose **Next**.
13. On the **Review and create** page, review your choices. Choose **Create metric filter** to create the filter, or choose **Edit** to go back and change values.

Create an alarm

After you create the metric filter, the CloudWatch Logs log group details page for your CloudTrail trail log group opens. Follow this procedure to create an alarm.

1. On the **Metric filters** tab, find the metric filter you created in [the section called "Create a metric filter"](#). Fill the check box for the metric filter. In the **Metric filters** bar, choose **Create alarm**.
2. On the **Create Alarm** page, in **Specify metric and conditions**, enter the following.
 - a. For **Graph**, the line is set at **3** based on other settings you make when you create your alarm.
 - b. For **Metric name**, keep the current metric name, **ConsoleSigninFailureCount**.
 - c. For **Statistic**, keep the default, **Sum**.
 - d. For **Period**, keep the default, **5 minutes**.
 - e. In **Conditions**, for **Threshold type**, choose **Static**.
 - f. For **Whenever *metric_name* is**, choose **Greater/Equal**.
 - g. For the threshold value, enter **3**.
 - h. In **Additional configuration**, leave defaults. Choose **Next**.
3. On the **Configure actions** page, for **Notification**, choose **In alarm**, which indicates that the action is taken when the threshold of 3 change events in 5 minutes is crossed, and **ConsoleSigninFailureCount** is in an alarm state.
 - a. For **Send a notification to the following SNS topic**, choose **Create new topic**.
 - b. Enter **ConsoleSignInFailures_CloudWatch_Alarms_Topic** as the name for the new Amazon SNS topic.
 - c. In **Email endpoints that will receive the notification**, enter the email addresses of users whom you want to receive notifications if this alarm is raised. Separate email addresses with commas.

Each email recipient will receive an email asking them to confirm that they want to be subscribed to the Amazon SNS topic.

- d. Choose **Create topic**.
4. For this example, skip the other action types. Choose **Next**.
5. On the **Add name and description** page, enter a friendly name for the alarm, and a description. For this example, enter **Console sign-in failures** for the name, and **Raises alarms if more than 3 console sign-in failures occur in 5 minutes** for the description. Choose **Next**.
6. On the **Preview and create** page, review your choices. Choose **Edit** to make changes, or choose **Create alarm** to create the alarm.

After you create the alarm, CloudWatch opens the **Alarms** page. The alarm's **Actions** column shows **Pending confirmation** until all email recipients on the SNS topic have confirmed that they want to subscribe to SNS notifications.

Example: IAM policy changes

Follow this procedure to create an Amazon CloudWatch alarm that is triggered when an API call is made to change an IAM policy.

Create a metric filter

1. Open the CloudWatch console at <https://console.aws.amazon.com/cloudwatch/>.
2. In the navigation pane, choose **Logs**.
3. In the list of log groups, choose the log group that you created for your trail.
4. Choose **Actions**, and then choose **Create metric filter**.
5. On the **Define pattern** page, in **Create filter pattern**, enter the following for **Filter pattern**.

```
{($.eventName=DeleteGroupPolicy)||($.eventName=DeleteRolePolicy)||
($.eventName=DeleteUserPolicy)||($.eventName=PutGroupPolicy)||
($.eventName=PutRolePolicy)||($.eventName=PutUserPolicy)||
($.eventName=CreatePolicy)||($.eventName=DeletePolicy)||
($.eventName=CreatePolicyVersion)||($.eventName=DeletePolicyVersion)||
($.eventName=AttachRolePolicy)||($.eventName=DetachRolePolicy)||
($.eventName=AttachUserPolicy)||($.eventName=DetachUserPolicy)||
($.eventName=AttachGroupPolicy)||($.eventName=DetachGroupPolicy)}
```

6. In **Test pattern**, leave defaults. Choose **Next**.
7. On the **Assign metric** page, for **Filter name**, enter **IAMPolicyChanges**.
8. In **Metric details**, turn on **Create new**, and then enter **CloudTrailMetrics** for **Metric namespace**.
9. For **Metric name**, type **IAMPolicyEventCount**.
10. For **Metric value**, type **1**.
11. Leave **Default value** blank.
12. Choose **Next**.
13. On the **Review and create** page, review your choices. Choose **Create metric filter** to create the filter, or choose **Edit** to go back and change values.

Create an alarm

After you create the metric filter, the CloudWatch Logs log group details page for your CloudTrail trail log group opens. Follow this procedure to create an alarm.

1. On the **Metric filters** tab, find the metric filter you created in [the section called "Create a metric filter"](#). Fill the check box for the metric filter. In the **Metric filters** bar, choose **Create alarm**.
2. On the **Create Alarm** page, in **Specify metric and conditions**, enter the following.
 - a. For **Graph**, the line is set at **1** based on other settings you make when you create your alarm.
 - b. For **Metric name**, keep the current metric name, **IAMPolicyEventCount**.
 - c. For **Statistic**, keep the default, **Sum**.
 - d. For **Period**, keep the default, **5 minutes**.
 - e. In **Conditions**, for **Threshold type**, choose **Static**.
 - f. For **Whenever *metric_name* is**, choose **Greater/Equal**.
 - g. For the threshold value, enter **1**.
 - h. In **Additional configuration**, leave defaults. Choose **Next**.
 - i.
3. On the **Configure actions** page, for **Notification**, choose **In alarm**, which indicates that the action is taken when the threshold of 1 change event in 5 minutes is crossed, and **IAMPolicyEventCount** is in an alarm state.

- a. For **Send a notification to the following SNS topic**, choose **Create new topic**.
- b. Enter **IAM_Policy_Changes_CloudWatch_Alarms_Topic** as the name for the new Amazon SNS topic.
- c. In **Email endpoints that will receive the notification**, enter the email addresses of users whom you want to receive notifications if this alarm is raised. Separate email addresses with commas.

Each email recipient will receive an email asking them to confirm that they want to be subscribed to the Amazon SNS topic.

- d. Choose **Create topic**.
4. For this example, skip the other action types. Choose **Next**.
 5. On the **Add name and description** page, enter a friendly name for the alarm, and a description. For this example, enter **IAM Policy Changes** for the name, and **Raises alarms if IAM policy changes occur** for the description. Choose **Next**.
 6. On the **Preview and create** page, review your choices. Choose **Edit** to make changes, or choose **Create alarm** to create the alarm.

After you create the alarm, CloudWatch opens the **Alarms** page. The alarm's **Actions** column shows **Pending confirmation** until all email recipients on the SNS topic have confirmed that they want to subscribe to SNS notifications.

Configuring notifications for CloudWatch Logs alarms

You can configure CloudWatch Logs to send a notification whenever an alarm is triggered for CloudTrail. Doing so enables you to respond quickly to critical operational events captured in CloudTrail events and detected by CloudWatch Logs. CloudWatch uses Amazon Simple Notification Service (SNS) to send email. For more information, see [Setting up Amazon SNS notifications](#) in the *CloudWatch User Guide*.

Stopping CloudTrail from sending events to CloudWatch Logs

You can stop sending AWS CloudTrail events to Amazon CloudWatch Logs by updating a trail to disable CloudWatch Logs settings.

Stop sending events to CloudWatch Logs (console)

To stop sending CloudTrail events to CloudWatch Logs

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, choose **Trails**.
3. Choose the name of the trail for which you want to disable CloudWatch Logs integration.
4. In **CloudWatch Logs**, choose **Edit**.
5. Clear the **Enabled** check box.
6. Choose **Save changes**.

Stop sending events to CloudWatch Logs (CLI)

You can remove the CloudWatch Logs log group as a delivery endpoint by running the [update-trail](#) command. The following command clears the log group and role from the trail configuration by replacing the values for the log group ARN and CloudWatch Logs role ARN with empty values.

```
aws cloudtrail update-trail --name trail_name --cloud-watch-logs-log-group-arn="" --  
cloud-watch-logs-role-arn=""
```

CloudWatch log group and log stream naming for CloudTrail

Amazon CloudWatch will display the log group that you created for CloudTrail events alongside any other log groups you have in a Region. We recommend that you use a log group name that helps you easily distinguish the log group from others. For example, **CloudTrail/logs**.

Follow these guidelines when naming a log group:

- Log group names must be unique within a Region for an AWS account.
- Log group names can be between 1 and 512 characters long.
- Log group names consist of the following characters: a-z, A-Z, 0-9, '_' (underscore), '-' (hyphen), '/' (forward slash), '.' (period), and '#' (number sign).

When CloudTrail creates the log stream for the log group, it names the log stream according to the following format: *account_ID*_CloudTrail_*trail_region*.

Note

If the volume of CloudTrail logs is large, multiple log streams may be created to deliver log data to your log group. When there are multiple log streams, CloudTrail names each log stream according to the following format:

account_ID_CloudTrail_trail_region_number.

For more information about CloudWatch log groups, see [Working with log groups and log streams](#) in the *Amazon CloudWatch Logs User Guide* and [CreateLogGroup](#) in the *Amazon CloudWatch Logs API Reference*.

Role policy document for CloudTrail to use CloudWatch Logs for monitoring

This section describes the permissions policy required for the CloudTrail role to send log events to CloudWatch Logs. You can attach a policy document to a role when you configure CloudTrail to send events, as described in [Sending events to CloudWatch Logs](#). You can also create a role using IAM. For more information, see [Creating a role to delegate permissions to an AWS service](#) or [Creating an IAM role \(AWS CLI\)](#).

The following example policy document contains the permissions required to create a CloudWatch log stream in the log group that you specify and to deliver CloudTrail events to that log stream in the US East (Ohio) Region. (This is the default policy for the default IAM role CloudTrail_CloudWatchLogs_Role.)

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "AWSCloudTrailCreateLogStream2014110",
      "Effect": "Allow",
      "Action": [
        "logs:CreateLogStream"
      ],
      "Resource": [
```

```

        "arn:aws:logs:us-east-2:111122223333:log-
group:log_group_name:log-stream:CloudTrail_log_stream_name_prefix*"
    ],
    {
        "Sid": "AWSCloudTrailPutLogEvents20141101",
        "Effect": "Allow",
        "Action": [
            "logs:PutLogEvents"
        ],
        "Resource": [
            "arn:aws:logs:us-east-2:111122223333:log-
group:log_group_name:log-stream:CloudTrail_log_stream_name_prefix*"
        ]
    }
]
}

```

If you're creating a policy that might be used for organization trails as well, you will need to modify it from the default policy created for the role. For example, the following policy grants CloudTrail the permissions required to create a CloudWatch Logs log stream in the log group you specify as the value of *log_group_name*, and to deliver CloudTrail events to that log stream for both trails in the AWS account 111111111111 and for organization trails created in the 111111111111 account that are applied to the AWS Organizations organization with the ID of *o-exampleorgid*:

JSON

```

{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "AWSCloudTrailCreateLogStream20141101",
            "Effect": "Allow",
            "Action": [
                "logs:CreateLogStream"
            ],
            "Resource": [
                "arn:aws:logs:us-east-2:111111111111:log-
group:log_group_name:log-stream:111111111111_CloudTrail_us-east-2*",
                "arn:aws:logs:us-east-2:111111111111:log-
group:log_group_name:log-stream:o-exampleorgid_*"
            ]
        }
    ]
}

```



```

    ]
  },
  {
    "Sid": "AWSCloudTrailPutLogEvents20141101",
    "Effect": "Allow",
    "Action": [
      "logs:PutLogEvents"
    ],
    "Resource": [
      "arn:aws:logs:us-east-2:111111111111:log-
group:log_group_name:log-stream:111111111111_CloudTrail_us-east-2*",
      "arn:aws:logs:us-east-2:111111111111:log-
group:log_group_name:log-stream:o-exampleorgid_*"
    ]
  }
]
}

```

For more information about organization trails, see [Creating a trail for an organization](#).

Receiving CloudTrail log files from multiple accounts

You can have CloudTrail deliver log files from multiple AWS accounts into a single Amazon S3 bucket. For example, you have four AWS accounts with account IDs 111111111111, 222222222222, 333333333333, and 444444444444, and you want to configure CloudTrail to deliver log files from all four of these accounts to a bucket belonging to account 111111111111. To accomplish this, complete the following steps in order:

1. Create a trail in the account where the destination bucket will belong (111111111111 in this example). Do not create a trail for any other accounts yet.

For instructions, see [Creating a trail with the console](#).

2. Update the bucket policy on your destination bucket to grant cross-account permissions to CloudTrail.

For instructions, see [Setting bucket policy for multiple accounts](#).

3. Create a trail in the other accounts (222222222222, 333333333333, and 444444444444 in this example) for which you want to log activity. When you create the trail in each

account, specify the Amazon S3 bucket belonging to the account that you specified in step 1 (111111111111 in this example). For instructions, see [Create trails in additional accounts](#).

 Note

If you choose to enable SSE-KMS encryption, the KMS key policy must allow CloudTrail to use the key to encrypt your log files and digest files, and allow the users you specify to read log files or digest files in unencrypted form. For information about manually editing the key policy, see [Configure AWS KMS key policies for CloudTrail](#).

Redacting bucket owner account IDs for data events called by other accounts

Historically, if CloudTrail data events were enabled in the AWS account of an Amazon S3 data event API caller, CloudTrail showed the account ID of the S3 bucket owner in the data event (such as PutObject). This occurred even if the bucket owner account did not have S3 data events enabled.

Now, CloudTrail removes the account ID of the S3 bucket owner in the `resources` block if both of the following conditions are met:

- The data event API call is from a different AWS account than the Amazon S3 bucket owner.
- The API caller received an AccessDenied error that was only for the caller account.

The owner of the resource on which the API call was made still receives the full event.

The following event record snippets are an example of the expected behavior. In the `Historic` snippet, the account ID 123456789012 of the S3 bucket owner is shown to an API caller from a different account. In the example of current behavior, the account ID of the bucket owner is not shown.

```
# Historic

"resources": [
  {
    "type": "AWS::S3::Object",
    "ARNPrefix": "arn:aws:s3:::amzn-s3-demo-bucket2/"
  },
]
```

```
{
  "accountId": "123456789012",
  "type": "AWS::S3::Bucket",
  "ARN": "arn:aws:s3:::amzn-s3-demo-bucket2"
}
```

The following is the current behavior.

```
# Current

"resources": [
  {
    "type": "AWS::S3::Object",
    "ARNPrefix": "arn:aws:s3:::amzn-s3-demo-bucket2/"
  },
  {
    "accountId": "",
    "type": "AWS::S3::Bucket",
    "ARN": "arn:aws:s3:::amzn-s3-demo-bucket2"
  }
]
```

Topics

- [Setting bucket policy for multiple accounts](#)
- [Create trails in additional accounts](#)

Setting bucket policy for multiple accounts

For a bucket to receive log files from multiple accounts, its bucket policy must grant CloudTrail permission to write log files from all the accounts you specify. This means that you must modify the bucket policy on your destination bucket to grant CloudTrail permission to write log files from each specified account.

Note

For security reasons, unauthorized users cannot create a trail that includes AWSLogs/ as the S3KeyPrefix parameter.

To modify bucket permissions so that files can be received from multiple accounts

1. Sign in to the AWS Management Console using the account that owns the bucket (111111111111 in this example) and open the Amazon S3 console.
2. Choose the bucket where CloudTrail delivers your log files and then choose **Permissions**.
3. For **Bucket policy**, choose **Edit**.
4. Modify the existing policy to add a line for each additional account whose log files you want delivered to this bucket. See the following example policy and note the underlined Resource line specifying a second account ID. As a security best practice, add an `aws:SourceArn` condition key to the Amazon S3 bucket policy. This helps prevent unauthorized access to your S3 bucket. If you have existing trails, be sure to add one or more condition keys.

Note

An AWS account ID is a twelve-digit number, including leading zeros.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "AWSCloudTrailAclCheck20131101",
      "Effect": "Allow",
      "Principal": {
        "Service": "cloudtrail.amazonaws.com"
      },
      "Action": "s3:GetBucketAcl",
      "Resource": "arn:aws:s3:::amzn-s3-demo-bucket",
      "Condition": {
        "StringEquals": {
          "aws:SourceArn": [
            "arn:aws:cloudtrail:region:111111111111:trail/primaryTrailName",
            "arn:aws:cloudtrail:region:222222222222:trail/secondaryTrailName"
          ]
        }
      }
    }
  ]
}
```

```

    }
  },
  {
    "Sid": "AWSCloudTrailWrite20131101",
    "Effect": "Allow",
    "Principal": {
      "Service": "cloudtrail.amazonaws.com"
    },
    "Action": "s3:PutObject",
    "Resource": [
      "arn:aws:s3:::amzn-s3-demo-  
bucket/optionalLogFilePrefix/AWSLogs/111111111111/*",
      "arn:aws:s3:::amzn-s3-demo-  
bucket/optionalLogFilePrefix/AWSLogs/222222222222/*"
    ],
    "Condition": {
      "StringEquals": {
        "aws:SourceArn": [
          "arn:aws:cloudtrail:region:111111111111:trail/primaryTrailName",
          "arn:aws:cloudtrail:region:222222222222:trail/secondaryTrailName"
        ],
        "s3:x-amz-acl": "bucket-owner-full-control"
      }
    }
  }
]
}

```

Create trails in additional accounts

You can use the console or the AWS CLI to create trails in additional AWS accounts and aggregate their log files to one Amazon S3 bucket. Alternatively, you could create an organization trail to log all AWS accounts that are part of an organization in AWS Organizations. For more information, see [Creating a trail for an organization](#).

Using the console to create trails in additional AWS accounts

You can use the CloudTrail console to create trails in additional accounts.

1. Sign in to AWS Management Console with the account for which you want to create a trail. Follow the steps in [Creating a trail with the console](#) to create a trail using the console.
2. For **Storage location**, choose **Use existing S3 bucket**. Use the text box to enter the name of the bucket you're using to store log files across accounts.

Note

The bucket policy must grant CloudTrail permission to write to it. For information about manually editing the bucket policy, see [Setting bucket policy for multiple accounts](#).

Storage location [Info](#)

☐ Create new S3 bucket
Create a bucket to store logs for the trail.

☒ Use existing S3 bucket
Choose an existing bucket to store logs for this trail.

Trail log bucket name

Enter a new S3 bucket name and folder (prefix) to store your logs. Bucket names must be globally unique.

[Browse](#)

Prefix - optional

Logs will be stored in cross-account-bucket-name/cross-account-bucket-prefix/

3. For **Prefix**, enter the prefix you are using to store log files across accounts. If you choose to use a prefix that is different from what you specified in your bucket policy, you must edit the bucket policy on your destination bucket to allow CloudTrail to write log files to your bucket using this new prefix.

Using the CLI to create a trail in additional AWS accounts

You can use the AWS command line tools to create trails in additional accounts and aggregate their log files to one Amazon S3 bucket. For more information about these tools, see [cloudtrail](#) in the *AWS CLI Command Reference*.

Create a trail by using the **create-trail** command, specifying the following:

- **--name** specifies the name of the trail.

- `--s3-bucket-name` specifies the Amazon S3 bucket you are using to store log files across accounts.
- `--s3-prefix` specifies a prefix for the log file delivery path (optional).
- `--is-multi-region-trail` specifies that this trail will log events in all AWS Regions in the partition in which you are working.

You can create one trail for each Region in which an account is running AWS resources.

The following example command shows how to create a trail for your additional accounts by using the AWS CLI. To have log files for these account delivered to the bucket you created in your first account (111111111111 in this example), specify the bucket name in the `--s3-bucket-name` option. Amazon S3 bucket names are globally unique.

```
aws cloudtrail create-trail --name my-trail --s3-bucket-name amzn-s3-demo-bucket --is-multi-region-trail
```

When you run the command, you will see output similar to the following:

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "AWSCloudTrailExample",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:222222222222:trail/my-trail",
  "LogFileValidationEnabled": false,
  "IsMultiRegionTrail": true,
  "IsOrganizationTrail": false,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

For more information about using CloudTrail from the AWS command line tools, see the [CloudTrail command line reference](#).

Sharing CloudTrail log files between AWS accounts

This section explains how to share CloudTrail log files between multiple AWS accounts. The approach you use to share logs between AWS accounts depends on the configuration of your S3 bucket. These are the options for sharing log files:

- [Bucket owner enforced](#) – [S3 Object Ownership](#) is an Amazon S3 bucket-level setting that you can use to control ownership of objects uploaded to your bucket and to disable or enable access

control lists (ACLs). By default, Object Ownership is set to the **Bucket owner enforced** setting and all ACLs are disabled. When ACLs are disabled, the bucket owner owns all the objects in the bucket and manages access to data exclusively using access management policies. When the **Bucket owner enforced** option is set, access is managed through the bucket policy, eliminating the need for users to assume a role.

- [Assume a role to share log files](#) – If you haven't chosen the **Bucket owner enforced** setting, users will need to assume a role to access the log files in your S3 bucket.

Share log files between accounts by assuming a role

Note

This section applies only to Amazon S3 buckets that are not using the **Bucket owner enforced** setting.

This section explains how to share CloudTrail log files between multiple AWS accounts by assuming a role and describes the scenarios for sharing log files.

- **Scenario 1:** Grant read-only access to the accounts that generated the log files that have been placed into your Amazon S3 bucket.
- **Scenario 2:** Grant access to all of the log files in your Amazon S3 bucket to a third-party account that can analyze the log files for you.

To grant read-only access to the log files in your Amazon S3 bucket

1. [Create an IAM role](#) for each account you want to share log files with. You must be an administrator to grant permission.

When you create the role, do the following:

- Choose the **Another AWS account** option.
- Enter the twelve-digit account ID of the account to be granted access.
- Check the **Require MFA** box if you want the user to provide multi-factor authentication before assuming the role.
- Choose the **AmazonS3ReadOnlyAccess** policy.

Note

By default, the **AmazonS3ReadOnlyAccess** policy grants retrieval and list rights to all Amazon S3 buckets within your account.

For details about permissions management for IAM roles, see [IAM roles](#) in the IAM User Guide.

2. [Create an access policy](#) that grants read-only access to the account you want to share the log files with.
3. Instruct each account to [assume a role](#) to retrieve the log files.

To grant read-only access to the log files with a third-party account

1. [Create an IAM role](#) for the third-party account you want to share log files with. You must be an administrator to grant permission.

When you create the role, do the following:

- Choose the **Another AWS account** option.
- Enter the twelve-digit account ID of the account to be granted access.
- Enter an external ID that provides additional control over who can assume the role. For more information, see [How to Use an External ID When Granting Access to Your AWS Resources to a Third Party](#) in the *IAM User Guide*.
- Choose the **AmazonS3ReadOnlyAccess** policy.

Note

By default, the **AmazonS3ReadOnlyAccess** policy grants retrieval and list rights to all Amazon S3 buckets within your account.

2. [Create an access policy](#) that grants read-only access to the third-party account you want to share the log files with.
3. Instruct the third-party account to [assume a role](#) to retrieve the log files.

The following sections provide more detail about these steps.

Topics

- [Creating an access policy to grant access to accounts you own](#)
- [Creating an access policy to grant access to a third party](#)
- [Assuming a role](#)
- [Stop sharing CloudTrail log files between AWS accounts](#)

Creating an access policy to grant access to accounts you own

As the Amazon S3 bucket owner, you have full control over the Amazon S3 bucket to which CloudTrail writes log files for the other accounts. You want to share each business unit's log files back to business unit that created them. But, you don't want a unit to be able to read any other unit's log files.

For example, to share account B's log files with account B but not with account C, you must create a new IAM role in your account that specifies that account B is a trusted account. This role trust policy specifies that account B is trusted to assume the role created by your account, and should look like the following example. The trust policy is automatically created if you create the role by using the console. If you use the SDK to create the role, you must supply the trust policy as a parameter to the `CreateRole` API. If you use the CLI to create the role, you must specify the trust policy in the `create-role` CLI command.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "",
      "Effect": "Allow",
      "Principal": {
        "AWS": "arn:aws:iam::111122223333:root"
      },
      "Action": "sts:AssumeRole"
    }
  ]
}
```

You must also create an access policy to specify that account B can read from only the location to which B wrote its log files. The access policy will look something like the following. Note that the **Resource** ARN includes the twelve-digit account ID for account B, and the prefix you specified, if any, when you turned on CloudTrail for account B during the aggregation process. For more information about specifying a prefix, see [Create trails in additional accounts](#).

Important

You must ensure that the prefix in the access policy is exactly the same as the prefix that you specified when you turned on CloudTrail for account B. If it is not, then you must edit the IAM role access policy in your account to incorporate the actual prefix for account B. If the prefix in the role access policy is not exactly the same as the prefix you specified when you turned on CloudTrail in account B, then account B will not be able to access its log files.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:Get*",
        "s3:List*"
      ],
      "Resource": "arn:aws:s3:::amzn-s3-demo-bucket/prefix/AWSLogs/account-B-id/*"
    },
    {
      "Effect": "Allow",
      "Action": [
        "s3:Get*",
        "s3:List*"
      ],
      "Resource": "arn:aws:s3:::amzn-s3-demo-bucket"
    }
  ]
}
```

Use the preceding process for any additional accounts.

After you create roles for each account and specify the appropriate trust and access policies, and after an IAM user in each account has been granted access by the administrator of that account, an IAM user in accounts B or C can programmatically assume the role.

For more information, see [Assuming a role](#).

Creating an access policy to grant access to a third party

You must create a separate IAM role for a third-party account. When you create the role, AWS automatically creates the trust relationship, which specifies that third-party account will be trusted to assume the role. The access policy for the role specifies what actions that account can take. For more information about creating roles, see [Create an IAM role](#).

For example, the trust relationship created by AWS specifies that the third-party account (account Z in this example) is trusted to assume the role that you've created. The following is an example trust policy:

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "",
      "Effect": "Allow",
      "Principal": {
        "AWS": "arn:aws:iam::111122223333:root"
      },
      "Action": "sts:AssumeRole"
    }
  ]
}
```

If you specified an external ID when you created the role for the third-party account, your access policy contains an added Condition element that tests the unique ID assigned by that account. The test is performed when the role is assumed. The following example access policy has a Condition element.

For more information, see [How to use an external ID when granting access to your AWS resources to a third party](#) in the *IAM User Guide*.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Sid": "",
    "Effect": "Allow",
    "Principal": {"AWS": "arn:aws:iam::111111111111:root"},
    "Action": "sts:AssumeRole",
    "Condition": {"StringEquals": {"sts:ExternalId": "external-ID-issued-by-account-Z"}}
  }]
}
```

You must also create an access policy for your account to specify that the third-party account can read all logs from the Amazon S3 bucket. The access policy should look something like the following example. The wild card (*) at the end of the Resource value indicates that the third-party account can access any log file in the S3 bucket to which it has been granted access.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:Get*",
        "s3:List*"
      ],
      "Resource": "arn:aws:s3:::amzn-s3-demo-bucket/*"
    }
  ]
}
```

```
    },
    {
      "Effect": "Allow",
      "Action": [
        "s3:Get*",
        "s3:List*"
      ],
      "Resource": "arn:aws:s3:::amzn-s3-demo-bucket"
    }
  ]
}
```

After you create a role for the third-party account and specify the appropriate trust relationship and access policy, an IAM user in the third-party account must programmatically assume the role to be able to read log files from the bucket. For more information, see [Assuming a role](#).

Assuming a role

You must designate a separate IAM user to assume each role you create in each account. You must then ensure that each IAM user has appropriate permissions.

IAM users and roles

After you create the necessary roles and policies, you must designate an IAM user in each of the account with which you want to share files. Each IAM user programmatically assumes the appropriate role to access the log files. When a user assumes a role, AWS returns temporary security credentials to that user. They can then make requests to list, retrieve, copy, or delete log files depending on the permissions granted by the access policy associated with the role.

For more information about working with IAM identities, see [IAM Identities \(users, user groups, and roles\)](#).

The primary difference in the access policy that you create for each IAM role in each scenario.

- In scenario 1, the access policy limits each account to reading only its own log files. For more information, see [Creating an access policy to grant access to accounts you own](#).
- In scenario 2, the access policy allows a third-party it to read all the log files that are aggregated in the Amazon S3 bucket. For more information, see [Creating an access policy to grant access to a third party](#).

Creating permissions policies for IAM users

To perform the actions permitted by a role, the IAM user must have permission to call the AWS STS [AssumeRole](#) API. You must edit the policy for each user to grant them the appropriate permissions. To do this, you set a **Resource** element in the policy that you attach to the IAM user. The following example shows a policy for an IAM user in another account that allows that user to assume a role named Test created earlier by Account A.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "sts:AssumeRole"
      ],
      "Resource": "arn:aws:iam::111122223333:role/Test"
    }
  ]
}
```

To edit a customer managed policy (console)

1. Sign in to the AWS Management Console and open the IAM console at <https://console.aws.amazon.com/iam/>.
2. In the navigation pane, choose **Policies**.
3. In the list of policies, choose the policy name of the policy to edit. You can use the search box to filter the list of policies.
4. Choose the **Permissions** tab, and then choose **Edit**.
5. Do one of the following:
 - Choose the **Visual** option to change your policy without understanding JSON syntax. You can make changes to the service, actions, resources, or optional conditions for each permission block in your policy. You can also import a policy to add additional permissions to the bottom of your policy. When you are finished making changes, choose **Next** to continue.

- Choose the **JSON** option to modify your policy by typing or pasting text in the JSON text box. You can also import a policy to add additional permissions to the bottom of your policy. Resolve any security warnings, errors, or general warnings generated during [policy validation](#), and then choose **Next**.

 Note

You can switch between the **Visual** and **JSON** editor options any time. However, if you make changes or choose **Next** in the **Visual** editor, IAM might restructure your policy to optimize it for the visual editor. For more information, see [Policy restructuring](#) in the *IAM User Guide*.

6. On the **Review and save** page, review **Permissions defined in this policy** and then choose **Save changes** to save your work.
7. If the managed policy already has the maximum of five versions, choosing **Save changes** displays a dialog box. To save your new version, the oldest non-default version of the policy is removed and replaced with this new version. Optionally, you can set the new version as the default policy version.

Choose **Save changes** to save your new policy version.

Calling AssumeRole

A user can assume a role by creating an application that calls the AWS STS [AssumeRole](#) API and passes the role session name, the Amazon Resource Number (ARN) of the role to assume, and an optional external ID. The role session name is defined by the account that created the role to assume. The external ID, if any, is defined by the third-party account and passed to owning account for inclusion during role creation. For more information, see [How to Use an External ID When Granting Access to Your AWS Resources to a Third Party](#) in the *IAM User Guide*. You can retrieve the ARN from the Account A by opening the IAM console.

To find the ARN Value in Account A with the IAM console

1. Choose **Roles**
2. Choose the role you want to examine.
3. Look for the **Role ARN** in the **Summary** section.

The AssumeRole API returns temporary credentials to use to access resources in owning account. In this example, the resources you want to access are the Amazon S3 bucket and the log files that the bucket contains. The temporary credentials have the permissions that you defined in the role access policy.

The following Python example (using the [AWS SDK for Python \(Boto\)](#)) shows how to call AssumeRole and how to use the temporary security credentials returned to list all Amazon S3 buckets controlled by Account A.

```
def list_buckets_from_assumed_role(user_key, assume_role_arn, session_name):
    """
    Assumes a role that grants permission to list the Amazon S3 buckets in the account.
    Uses the temporary credentials from the role to list the buckets that are owned
    by the assumed role's account.

    :param user_key: The access key of a user that has permission to assume the role.
    :param assume_role_arn: The Amazon Resource Name (ARN) of the role that
                           grants access to list the other account's buckets.
    :param session_name: The name of the STS session.
    """
    sts_client = boto3.client(
        "sts", aws_access_key_id=user_key.id, aws_secret_access_key=user_key.secret
    )
    try:
        response = sts_client.assume_role(
            RoleArn=assume_role_arn, RoleSessionName=session_name
        )
        temp_credentials = response["Credentials"]
        print(f"Assumed role {assume_role_arn} and got temporary credentials.")
    except ClientError as error:
        print(
            f"Couldn't assume role {assume_role_arn}. Here's why: "
            f"{error.response['Error']['Message']}"
        )
        raise

# Create an S3 resource that can access the account with the temporary credentials.
s3_resource = boto3.resource(
    "s3",
    aws_access_key_id=temp_credentials["AccessKeyId"],
    aws_secret_access_key=temp_credentials["SecretAccessKey"],
    aws_session_token=temp_credentials["SessionToken"],
)
```

```
print(f"Listing buckets for the assumed role's account:")
try:
    for bucket in s3_resource.buckets.all():
        print(bucket.name)
except ClientError as error:
    print(
        f"Couldn't list buckets for the account. Here's why: "
        f"{error.response['Error']['Message']}"
    )
    raise
```

Stop sharing CloudTrail log files between AWS accounts

To stop sharing log files to another AWS account, delete the role that you created for that account. For information about how to delete a role, see [Deleting roles or instance profiles](#).

Validating CloudTrail log file integrity

To determine whether a log file was modified, deleted, or unchanged after CloudTrail delivered it, you can use CloudTrail log file integrity validation. This feature is built using industry standard algorithms: SHA-256 for hashing and SHA-256 with RSA for digital signing. This makes it computationally infeasible to modify, delete or forge CloudTrail log files without detection. You can use the AWS CLI to validate the files in the location where CloudTrail delivered them.

Why use it?

Validated log files are invaluable in security and forensic investigations. For example, a validated log file enables you to assert positively that the log file itself has not changed, or that particular user credentials performed specific API activity. The CloudTrail log file integrity validation process also lets you know if a log file has been deleted or changed, or assert positively that no log files were delivered to your account during a given period of time.

How it works

When you enable log file integrity validation, CloudTrail creates a hash for every log file that it delivers. Every hour, CloudTrail also creates and delivers a file that references the log files for the last hour and contains a hash of each. This file is called a digest file. CloudTrail signs each digest

file using the private key of a public and private key pair. After delivery, you can use the public key to validate the digest file. CloudTrail uses different key pairs for each AWS Region.

The digest files are delivered to the same Amazon S3 bucket associated with your trail as your CloudTrail log files. If your log files are delivered from all Regions or from multiple accounts into a single Amazon S3 bucket, CloudTrail will deliver the digest files from those Regions and accounts into the same bucket.

The digest files are put into a folder separate from the log files. This separation of digest files and log files enables you to enforce granular security policies and permits existing log processing solutions to continue to operate without modification. Each digest file also contains the digital signature of the previous digest file if one exists. The signature for the current digest file is in the metadata properties of the digest file Amazon S3 object. For more information about digest file contents, see [CloudTrail digest file structure](#).

Storing log and digest files

You can store the CloudTrail log files and digest files in Amazon S3 or Amazon Glacier securely, durably and inexpensively for an indefinite period of time. To enhance the security of the digest files stored in Amazon S3, you can use [Amazon S3 MFA Delete](#).

Enabling validation and validating files

To enable log file integrity validation, you can use the AWS Management Console, the AWS CLI, or CloudTrail API. Enabling log file integrity validation allows CloudTrail to deliver digest log files to your Amazon S3 bucket, but does not validate the integrity of the files. For more information, see [Enabling log file integrity validation for CloudTrail](#).

To validate the integrity of CloudTrail log files, you can use the AWS CLI or create your own solution. The AWS CLI will validate files in the location where CloudTrail delivered them. If you want to validate logs that you have moved to a different location, either in Amazon S3 or elsewhere, you can create your own validation tools.

For information on validating logs by using the AWS CLI, see [Validating CloudTrail log file integrity with the AWS CLI](#). For information on developing custom implementations of CloudTrail log file validation, see [Custom implementations of CloudTrail log file integrity validation](#).

Enabling log file integrity validation for CloudTrail

You can enable log file integrity validation by using the AWS Management Console, AWS Command Line Interface (AWS CLI), or CloudTrail API. CloudTrail starts delivering digest files in about an hour.

AWS Management Console

To enable log file integrity validation with the CloudTrail console, choose **Yes** for the **Enable log file validation** option when you create or update a trail. By default, this feature is enabled for new trails. For more information, see [Creating and updating a trail with the console](#).

AWS CLI

To enable log file integrity validation with the AWS CLI, use the `--enable-log-file-validation` option with the [create-trail](#) or [update-trail](#) commands. To disable log file integrity validation, use the `--no-enable-log-file-validation` option.

Example

The following `update-trail` command enables log file validation and starts delivering digest files to the Amazon S3 bucket for the specified trail.

```
aws cloudtrail update-trail --name your-trail-name --enable-log-file-validation
```

CloudTrail API

To enable log file integrity validation with the CloudTrail API, set the `EnableLogFileValidation` request parameter to `true` when calling `CreateTrail` or `UpdateTrail`.

For more information, see [CreateTrail](#) and [UpdateTrail](#) in the [AWS CloudTrail API Reference](#).

Validating CloudTrail log file integrity with the AWS CLI

To validate logs with the AWS Command Line Interface, use the CloudTrail `validate-logs` command. The command uses the digest files delivered to your Amazon S3 bucket to perform the validation. For information about digest files, see [CloudTrail digest file structure](#).

The AWS CLI allows you to detect the following types of changes:

- Modification or deletion of CloudTrail log files
- Modification or deletion of CloudTrail digest files
- Modification or deletion of both of the above

Note

The AWS CLI validates only log files that are referenced by digest files. For more information, see [Checking whether a particular file was delivered by CloudTrail](#).

Prerequisites

To validate log file integrity with the AWS CLI, the following conditions must be met:

- You must have online connectivity to AWS.
- You must have read access to the Amazon S3 bucket that contains the digest and log files.
- The digest and log files must not have been moved from the original Amazon S3 location where CloudTrail delivered them.
- The role executing the command must have permissions to call `ListObjects`, `GetObject`, and `GetBucketLocation` for each S3 bucket referenced by the trail.

Note

Log files that have been downloaded to local disk cannot be validated with the AWS CLI. For guidance on creating your own tools for validation, see [Custom implementations of CloudTrail log file integrity validation](#).

validate-logs

Syntax

The following is the syntax for `validate-logs`. Optional parameters are shown in brackets.

```
aws cloudtrail validate-logs --trail-arn <trailARN> --start-time <start-time> [--end-time <end-time>] [--s3-bucket <amzn-s3-demo-bucket>] [--s3-prefix <prefix>] [--account-id <account-id>] [--verbose]
```

Note

The `validate-logs` command is Region specific. You must specify the `--region` global option to validate logs for a specific AWS Region.

Options

The following are the command-line options for `validate-logs`. The `--trail-arn` and `--start-time` options are required. The `--account-id` option is additionally required for organizational trails.

--start-time

Specifies that log files delivered on or after the specified UTC timestamp value will be validated.
Example: `2015-01-08T05:21:42Z`.

--end-time

Optionally specifies that log files delivered on or before the specified UTC timestamp value will be validated. The default value is the current UTC time (`Date.now()`). Example: `2015-01-08T12:31:41Z`.

Note

For the time range specified, the `validate-logs` command checks only the log files that are referenced in their corresponding digest files. No other log files in the Amazon S3 bucket are checked. For more information, see [Checking whether a particular file was delivered by CloudTrail](#).

--s3-bucket

Optionally specifies the Amazon S3 bucket where the digest files are stored. If a bucket name is not specified, the AWS CLI will retrieve it by calling `DescribeTrails()`.

--s3-prefix

Optionally specifies the Amazon S3 prefix where the digest files are stored. If not specified, the AWS CLI will retrieve it by calling `DescribeTrails()`.

Note

You should use this option only if your current prefix is different from the prefix that was in use during the time range that you specify.

--account-id

Optionally specifies the account for validating logs. This parameter is required for organization trails for validating logs for the specific account inside an organization.

--trail-arn

Specifies the Amazon Resource Name (ARN) of the trail to be validated. The format of a trail ARN follows.

```
arn:aws:cloudtrail:us-east-2:111111111111:trail/MyTrailName
```

Note

To obtain the trail ARN for a trail, you can use the `describe-trails` command before running `validate-logs`.

You may want to specify the bucket name and prefix in addition to the trail ARN if log files have been delivered to more than one bucket in the time range that you specified, and you want to restrict the validation to the log files in only one of the buckets.

--verbose

Optionally outputs validation information for every log or digest file in the specified time range. The output indicates whether the file remains unchanged or has been modified or deleted. In non-verbose mode (the default), information is returned only for those cases in which there was a validation failure.

Example

The following example validates log files from the specified start time to the present, using the Amazon S3 bucket configured for the current trail and specifying verbose output.

```
aws cloudtrail validate-logs --start-time 2015-08-27T00:00:00Z --end-time
2015-08-28T00:00:00Z --trail-arn arn:aws:cloudtrail:us-east-2:111111111111:trail/my-
trail-name --verbose
```

How validate-logs works

The `validate-logs` command starts by validating the most recent digest file in the specified time range. First, it verifies that the digest file has been downloaded from the location to which it claims to belong. In other words, if the CLI downloads digest file `df1` from the S3 location `p1`, `validate-logs` will verify that `p1 == df1.digestS3Bucket + '/' + df1.digestS3Object`.

If the signature of the digest file is valid, it checks the hash value of each of the logs referenced in the digest file. The command then goes back in time, validating the previous digest files and their referenced log files in succession. It continues until the specified value for `start-time` is reached, or until the digest chain ends. If a digest file is missing or not valid, the time range that cannot be validated is indicated in the output.

Validation results

Validation results begin with a summary header in the following format:

```
Validating log files for trail trail_ARN between time_stamp and time_stamp
```

Each line of the main output contains the validation results for a single digest or log file in the following format:

```
<Digest file | Log file> <S3 path> <Validation Message>
```

The following table describes the possible validation messages for log and digest files.

File Type	Validation Message	Description
Digest file	valid	The digest file signature is valid. The log files it references can be checked. This message is included only in verbose mode.

File Type	Validation Message	Description
Digest file	INVALID: has been moved from its original location	The S3 bucket or S3 object from which the digest file was retrieved do not match the S3 bucket or S3 object locations that are recorded in the digest file itself.
Digest file	INVALID: invalid format	The format of the digest file is invalid. The log files corresponding to the time range that the digest file represents cannot be validated.
Digest file	INVALID: not found	The digest file was not found. The log files corresponding to the time range that the digest file represents cannot be validated.
Digest file	INVALID: public key not found for fingerprint <i>fingerprint</i>	The public key corresponding to the fingerprint recorded in the digest file was not found. The digest file cannot be validated.
Digest file	INVALID: signature verification failed	The digest file signature is not valid. Because the digest file is not valid, the log files it references cannot be validated, and no assertions can be made about the API activity in them.
Digest file	INVALID: Unable to load PKCS #1 key with fingerprint <i>fingerprint</i>	Because the DER encoded public key in PKCS #1 format having the specified fingerprint could not be loaded, the digest file cannot be validated.
Log file	valid	The log file has been validated and has not been modified since the time of delivery. This message is included only in verbose mode.

File Type	Validation Message	Description
Log file	INVALID: hash value doesn't match	The hash for the log file does not match. The log file has been modified after delivery by CloudTrail.
Log file	INVALID: invalid format	The format of the log file is invalid. The log file cannot be validated.
Log file	INVALID: not found	The log file was not found and cannot be validated.

The output includes summary information about the results returned.

Example outputs

Verbose

The following example `validate-logs` command uses the `--verbose` flag and produces the sample output that follows. [...] indicates the sample output has been abbreviated.

```
aws cloudtrail validate-logs --trail-arn arn:aws:cloudtrail:us-east-2:111111111111:trail/example-trail-name --start-time 2015-08-31T22:00:00Z --end-time 2015-09-01T19:17:29Z --verbose
```

```
Validating log files for trail arn:aws:cloudtrail:us-east-2:111111111111:trail/example-trail-name between 2015-08-31T22:00:00Z and 2015-09-01T19:17:29Z
```

```
Digest file      s3://amzn-s3-demo-bucket/AWSLogs/111111111111/CloudTrail-Digest/us-east-2/2015/09/01/111111111111_CloudTrail-Digest_us-east-2_example-trail-name_us-east-2_20150901T201728Z.json.gz valid
```

```
Log file        s3://amzn-s3-demo-bucket/AWSLogs/111111111111/CloudTrail/us-east-2/2015/09/01/111111111111_CloudTrail_us-east-2_20150901T1925Z_WZZw1RymnjCRjxXc.json.gz valid
```

```
Log file        s3://amzn-s3-demo-bucket/AWSLogs/111111111111/CloudTrail/us-east-2/2015/09/01/111111111111_CloudTrail_us-east-2_20150901T1915Z_P0uvV87nu6pfAV2W.json.gz valid
```

```
Log file        s3://amzn-s3-demo-bucket/AWSLogs/111111111111/CloudTrail/us-east-2/2015/09/01/111111111111_CloudTrail_us-east-2_20150901T1930Z_l2QgXhAKVm1QXiIA.json.gz valid
```

```
Log file      s3://amzn-s3-demo-bucket/AWSLogs/111111111111/
CloudTrail/us-east-2/2015/09/01/111111111111_CloudTrail_us-
east-2_20150901T1920Z_eQJteBBrfpBCq0qw.json.gz valid
Log file      s3://amzn-s3-demo-bucket/AWSLogs/111111111111/
CloudTrail/us-east-2/2015/09/01/111111111111_CloudTrail_us-
east-2_20150901T1950Z_9g5A6qlR2B5KaRdq.json.gz valid
Log file      s3://amzn-s3-demo-bucket/AWSLogs/111111111111/
CloudTrail/us-east-2/2015/09/01/111111111111_CloudTrail_us-
east-2_20150901T1920Z_i4DNCC12BuXd6Ru7.json.gz valid
Log file      s3://amzn-s3-demo-bucket/AWSLogs/111111111111/
CloudTrail/us-east-2/2015/09/01/111111111111_CloudTrail_us-
east-2_20150901T1915Z_Sg5caf2RH6Jdx0EJ.json.gz valid
Digest file   s3://amzn-s3-demo-bucket/AWSLogs/111111111111/CloudTrail-Digest/us-
east-2/2015/09/01/111111111111_CloudTrail-Digest_us-east-2_example-trail-name_us-
east-2_20150901T191728Z.json.gz valid
Log file      s3://amzn-s3-demo-bucket/AWSLogs/111111111111/
CloudTrail/us-east-2/2015/09/01/111111111111_CloudTrail_us-
east-2_20150901T1910Z YYSFiuFQk4nrtnEW.json.gz valid
[...]
Log file      s3://amzn-s3-demo-bucket/AWSLogs/144218288521/
CloudTrail/us-east-2/2015/09/01/144218288521_CloudTrail_us-
east-2_20150901T1055Z_0Sfy6m9f6iBzmoPF.json.gz valid
Log file      s3://amzn-s3-demo-bucket/AWSLogs/144218288521/
CloudTrail/us-east-2/2015/09/01/144218288521_CloudTrail_us-
east-2_20150901T1040Z_lLa3QzVLp0ed7igR.json.gz valid

Digest file   s3://amzn-s3-demo-bucket/AWSLogs/144218288521/CloudTrail-Digest/us-
east-2/2015/09/01/144218288521_CloudTrail-Digest_us-east-2_example-trail-name_us-
east-2_20150901T101728Z.json.gz INVALID: signature verification failed

Digest file   s3://amzn-s3-demo-bucketAWSLogs/144218288521/CloudTrail-Digest/us-
east-2/2015/09/01/144218288521_CloudTrail-Digest_us-east-2_example-trail-name_us-
east-2_20150901T091728Z.json.gz valid
Log file      s3://amzn-s3-demo-bucket/AWSLogs/144218288521/
CloudTrail/us-east-2/2015/09/01/144218288521_CloudTrail_us-
east-2_20150901T0830Z_eaFv03dwHo4NCqqc.json.gz valid
Digest file   s3://amzn-s3-demo-bucket/AWSLogs/144218288521/CloudTrail-Digest/us-
east-2/2015/09/01/144218288521_CloudTrail-Digest_us-east-2_example-trail-name_us-
east-2_20150901T081728Z.json.gz valid
Digest file   s3://amzn-s3-demo-bucket/AWSLogs/144218288521/CloudTrail-Digest/us-
east-2/2015/09/01/144218288521_CloudTrail-Digest_us-east-2_example-trail-name_us-
east-2_20150901T071728Z.json.gz valid
[...]
```

```

Log file      s3://amzn-s3-demo-bucket/AWSLogs/111111111111/
CloudTrail/us-east-2/2015/08/31/111111111111_CloudTrail_us-
east-2_20150831T2245Z_mBJkE05kNcDnVhGh.json.gz valid
Log file      s3://amzn-s3-demo-bucket/AWSLogs/111111111111/
CloudTrail/us-east-2/2015/08/31/111111111111_CloudTrail_us-
east-2_20150831T2225Z_IQ6kXy8sKU03RSPR.json.gz valid
Log file      s3://amzn-s3-demo-bucket/AWSLogs/111111111111/
CloudTrail/us-east-2/2015/08/31/111111111111_CloudTrail_us-
east-2_20150831T2230Z_eRPVRTxHQ5498ROA.json.gz valid
Log file      s3://amzn-s3-demo-bucket/AWSLogs/111111111111/
CloudTrail/us-east-2/2015/08/31/111111111111_CloudTrail_us-
east-2_20150831T2255Z_IlWawYZGvTWB5vYN.json.gz valid
Digest file   s3://amzn-s3-demo-bucket/AWSLogs/111111111111/CloudTrail-Digest/us-
east-2/2015/08/31/111111111111_CloudTrail-Digest_us-east-2_example-trail-name_us-
east-2_20150831T221728Z.json.gz valid

```

Results requested for 2015-08-31T22:00:00Z to 2015-09-01T19:17:29Z

Results found for 2015-08-31T22:17:28Z to 2015-09-01T20:17:28Z:

22/23 digest files valid, 1/23 digest files INVALID

63/63 log files valid

Non-verbose

The following example `validate-logs` command does not use the `--verbose` flag. In the sample output that follows, one error was found. Only the header, error, and summary information are returned.

```

aws cloudtrail validate-logs --trail-arn arn:aws:cloudtrail:us-
east-2:111111111111:trail/example-trail-name --start-time 2015-08-31T22:00:00Z --end-
time 2015-09-01T19:17:29Z

```

Validating log files for trail arn:aws:cloudtrail:us-east-2:111111111111:trail/example-trail-name between 2015-08-31T22:00:00Z and 2015-09-01T19:17:29Z

```

Digest file s3://amzn-s3-demo-bucket/AWSLogs/144218288521/CloudTrail-Digest/us-
east-2/2015/09/01/144218288521_CloudTrail-Digest_us-east-2_example-trail-name_us-
east-2_20150901T101728Z.json.gz INVALID: signature verification failed

```

Results requested for 2015-08-31T22:00:00Z to 2015-09-01T19:17:29Z

Results found for 2015-08-31T22:17:28Z to 2015-09-01T20:17:28Z:

```
22/23 digest files valid, 1/23 digest files INVALID
63/63 log files valid
```

Checking whether a particular file was delivered by CloudTrail

To check if a particular file in your bucket was delivered by CloudTrail, run `validate-logs` in verbose mode for the time period that includes the file. If the file appears in the output of `validate-logs`, then the file was delivered by CloudTrail.

CloudTrail digest file structure

Each digest file contains the names of the log files that were delivered to your Amazon S3 bucket during the last hour, the hash values for those log files, and the digital signature of the previous digest file. The signature for the current digest file is stored in the metadata properties of the digest file object. The digital signatures and hashes are used for validating the integrity of the log files and of the digest file itself.

Digest file location

Digest files are delivered to an Amazon S3 bucket location that follows this syntax.

```
s3://amzn-s3-demo-bucket/optional-prefix/AWSLogs/aws-account-id/CloudTrail-Digest/
    region/digest-end-year/digest-end-month/digest-end-date/
    aws-account-id_CloudTrail-Digest_region_trail-
    name_region_digest_end_timestamp.json.gz
```

Note

For organization trails, the bucket location also includes the organization unit ID, as follows:

```
s3://amzn-s3-demo-bucket/optional-prefix/AWSLogs/O-ID/aws-account-id/CloudTrail-
Digest/
    region/digest-end-year/digest-end-month/digest-end-date/
    aws-account-id_CloudTrail-Digest_region_trail-
    name_region_digest_end_timestamp.json.gz
```

Sample digest file contents

The following example digest file contains information for a CloudTrail log.

```
{
  "awsAccountId": "111122223333",
  "digestStartTime": "2015-08-17T14:01:31Z",
  "digestEndTime": "2015-08-17T15:01:31Z",
  "digestS3Bucket": "amzn-s3-demo-bucket",
  "digestS3Object": "AWSLogs/111122223333/CloudTrail-Digest/us-
east-2/2015/08/17/111122223333_CloudTrail-Digest_us-east-2_your-trail-name_us-
east-2_20150817T150131Z.json.gz",
  "digestPublicKeyFingerprint": "31e8b5433410dfb61a9dc45cc65b22ff",
  "digestSignatureAlgorithm": "SHA256withRSA",
  "newestEventTime": "2015-08-17T14:52:27Z",
  "oldestEventTime": "2015-08-17T14:42:27Z",
  "previousDigestS3Bucket": "amzn-s3-demo-bucket",
  "previousDigestS3Object": "AWSLogs/111122223333/CloudTrail-Digest/us-
east-2/2015/08/17/111122223333_CloudTrail-Digest_us-east-2_your-trail-name_us-
east-2_20150817T140131Z.json.gz",
  "previousDigestHashValue":
"97fb791cf91ffc440d274f8190dbdd9aa09c34432aba82739df18b6d3c13df2d",
  "previousDigestHashAlgorithm": "SHA-256",
  "previousDigestSignature":
"50887ccffad4c002b97caa37cc9dc626e3c680207d41d27fa5835458e066e0d3652fc4dfc30937e4d5f4cc7f796e7",
  "logFiles": [
    {
      "s3Bucket": "amzn-s3-demo-bucket",
      "s3Object": "AWSLogs/111122223333/CloudTrail/us-
east-2/2015/08/17/111122223333_CloudTrail_us-
east-2_20150817T1445Z_9nYN7gp2eWAJHIfT.json.gz",
      "hashValue": "9bb6196fc6b84d6f075a56548fec262bd99ba3c2de41b618e5b6e22c1fc71f6",
      "hashAlgorithm": "SHA-256",
      "newestEventTime": "2015-08-17T14:52:27Z",
      "oldestEventTime": "2015-08-17T14:42:27Z"
    }
  ]
}
```

Digest file field descriptions

The following are descriptions for each field in the digest file:

`awsAccountId`

The AWS account ID for which the digest file has been delivered.

`digestStartTime`

The starting UTC time range that the digest file covers, taking as a reference the time in which log files have been delivered by CloudTrail. This means that if the time range is [Ta, Tb], the digest will contain all the log files delivered to the customer between Ta and Tb.

`digestEndTime`

The ending UTC time range that the digest file covers, taking as a reference the time in which log files have been delivered by CloudTrail. This means that if the time range is [Ta, Tb], the digest will contain all the log files delivered to the customer between Ta and Tb.

`digestS3Bucket`

The name of the Amazon S3 bucket to which the current digest file has been delivered.

`digestS3Object`

The Amazon S3 object key (that is, the Amazon S3 bucket location) of the current digest file. The first two Regions in the string show the Region from which the digest file was delivered. The last Region (after `your-trail-name`) is the home Region of the trail. The home Region is the Region in which the trail was created. In the case of a multi-Region trail, this can be different from the Region from which the digest file was delivered.

`newestEventTime`

The UTC time of the most recent event among all of the events in the log files in the digest.

`oldestEventTime`

The UTC time of the oldest event among all of the events in the log files in the digest.

Note

If the digest file is delivered late, the value of `oldestEventTime` will be earlier than the value of `digestStartTime`.

`previousDigestS3Bucket`

The Amazon S3 bucket to which the previous digest file was delivered.

`previousDigestS3Object`

The Amazon S3 object key (that is, the Amazon S3 bucket location) of the previous digest file.

`previousDigestHashValue`

The hexadecimal encoded hash value of the uncompressed contents of the previous digest file.

`previousDigestHashAlgorithm`

The name of the hash algorithm that was used to hash the previous digest file.

`publicKeyFingerprint`

The hexadecimal encoded fingerprint of the public key that matches the private key used to sign this digest file. You can retrieve the public keys for the time range corresponding to the digest file by using the AWS CLI or the CloudTrail API. Of the public keys returned, the one whose fingerprint matches this value can be used for validating the digest file. For information about retrieving public keys for digest files, see the AWS CLI [list-public-keys](#) command or the CloudTrail [ListPublicKeys](#) API.

Note

CloudTrail uses different private/public key pairs per Region. Each digest file is signed with a private key unique to its Region. Therefore, when you validate a digest file from a particular Region, you must look in the same Region for its corresponding public key.

`digestSignatureAlgorithm`

The algorithm used to sign the digest file.

`logFiles.s3Bucket`

The name of the Amazon S3 bucket for the log file.

`logFiles.s3Object`

The Amazon S3 object key of the current log file.

`logFiles.newestEventTime`

The UTC time of the most recent event in the log file. This time also corresponds to the time stamp of the log file itself.

`logFiles.oldestEventTime`

The UTC time of the oldest event in the log file.

`logFiles.hashValue`

The hexadecimal encoded hash value of the uncompressed log file content.

`logFiles.hashAlgorithm`

The hash algorithm used to hash the log file.

Starting digest file

When log file integrity validation is started, a starting digest file will be generated. A starting digest file will also be generated when log file integrity validation is restarted (by either disabling and then reenabling log file integrity validation, or by stopping logging and then restarting logging with validation enabled). In a starting digest file, the following fields relating to the previous digest file will be null:

- previousDigestS3Bucket
- previousDigestS3Object
- previousDigestHashValue
- previousDigestHashAlgorithm
- previousDigestSignature

'Empty' digest files

CloudTrail will deliver a digest file even when there has been no API activity in your account during the one hour period that the digest file represents. This can be useful when you need to assert that no log files were delivered during the hour reported by the digest file.

The following example shows the contents of a digest file that recorded an hour when no API activity occurred. Note that the `logFiles: [ ]` field at the end of the digest file contents is empty.

```
{
  "awsAccountId": "111122223333",
  "digestStartTime": "2015-08-20T17:01:31Z",
  "digestEndTime": "2015-08-20T18:01:31Z",
  "digestS3Bucket": "amzn-s3-demo-bucket",
  "digestS3Object": "AWSLogs/111122223333/CloudTrail-Digest/us-east-2/2015/08/20/111122223333_CloudTrail-Digest_us-east-2_example-trail-name_us-east-2_20150820T180131Z.json.gz",
  "digestPublicKeyFingerprint": "31e8b5433410dfb61a9dc45cc65b22ff",
  "digestSignatureAlgorithm": "SHA256withRSA",
  "newestEventTime": null,
  "oldestEventTime": null,
  "previousDigestS3Bucket": "amzn-s3-demo-bucket",
  "previousDigestS3Object": "AWSLogs/111122223333/CloudTrail-Digest/us-east-2/2015/08/20/111122223333_CloudTrail-Digest_us-east-2_example-trail-name_us-east-2_20150820T170131Z.json.gz",
  "previousDigestHashValue":
    "ed96c4bac9eaa8fe9716ca0e515da51938be651b1db31d781956416a9d05cdfa",
  "previousDigestHashAlgorithm": "SHA-256",
  "previousDigestSignature":
    "82705525fb0fe7f919f9434e5b7138cb41793c776c7414f3520c0242902daa8cc8286b29263d2627f2f259471c745",
  "logFiles": [ ]
}
```

Signature of the digest file

The signature information for a digest file is located in two object metadata properties of the Amazon S3 digest file object. Each digest file has the following metadata entries:

- `x-amz-meta-signature`

The hexadecimal encoded value of the digest file signature. The following is an example signature:

```
3be472336fa2989ef34de1b3c1bf851f59eb030eaff3e2fb6600a082a23f4c6a82966565b994f9de4a5989d053d9d
28f1cc237f372264a51b611c01da429565def703539f4e71009051769469231bc22232fa260df02740047af532229
05d3ffcb5d2dd5dc28f8bb5b7993938e8a5f912a82b448a367ecb2ec0f198ba71e23eb0b97278cf65f3c8d1e652c
```

- `x-amz-meta-signature-algorithm`

The following shows an example value of the algorithm used to generate the digest signature:

SHA256withRSA

Digest file chaining

The fact that each digest file contains a reference to its previous digest file enables a "chaining" that permits validation tools like the AWS CLI to detect if a digest file has been deleted. It also allows the digest files in a specified time range to be successively inspected, starting with the most recent first.

Note

When you disable log file integrity validation, the chain of digest files is broken after one hour. CloudTrail will not create digest files for log files that were delivered during a period in which log file integrity validation was disabled. For example, if you enable log file integrity validation at noon on January 1, disable it at noon on January 2, and re-enable it at noon on January 10, digest files will not be created for the log files delivered from noon on January 2 to noon on January 10. The same applies whenever you stop CloudTrail logging or delete a trail.

If your trail's [S3 bucket policy](#) is misconfigured or CloudTrail experiences an unexpected service disruption, you might not receive all or some digest files. To confirm if your trail has any digest delivery errors, run the [get-trail-status](#) command and check the `LatestDigestDeliveryError` parameter for errors. After the delivery issue is resolved (for example, by fixing the bucket policy), CloudTrail will attempt to redeliver any missing digest files. During the redelivery period, the digest files might be delivered out of order, so the chain might temporarily appear to be broken.

If logging is stopped or the trail is deleted, CloudTrail will deliver a final digest file. This digest file can contain information for any remaining log files that cover events up to and including the `StopLogging` event.

Custom implementations of CloudTrail log file integrity validation

Because CloudTrail uses industry standard, openly available cryptographic algorithms and hash functions, you can create your own tools to validate the integrity of CloudTrail log files. When log file integrity validation is enabled, CloudTrail delivers digest files to your Amazon S3 bucket. You can use these files to implement your own validation solution. For more information about digest files, see [CloudTrail digest file structure](#).

This topic describes how digest files are signed, and then details the steps that you will need to take to implement a solution that validates the digest files and the log files that they reference.

Understanding how CloudTrail digest files are signed

CloudTrail digest files are signed with RSA digital signatures. For each digest file, CloudTrail does the following:

1. Creates a string for data signing based on designated digest file fields (described in the next section).
2. Gets a private key unique to the Region.
3. Passes the SHA-256 hash of the string and the private key to the RSA signing algorithm, which produces a digital signature.
4. Encodes the byte code of the signature into hexadecimal format.
5. Puts the digital signature into the `x-amz-meta-signature` metadata property of the Amazon S3 digest file object.

Contents of the data signing string

The following CloudTrail objects are included in the string for data signing:

- The ending timestamp of the digest file in UTC extended format (for example, 2015-05-08T07:19:37Z)
- The current digest file S3 path
- The hexadecimal-encoded SHA-256 hash of the current digest file
- The hexadecimal-encoded signature of the previous digest file

The format for calculating this string and an example string are provided later in this document.

Custom validation implementation steps

When implementing a custom validation solution, you will need to validate the digest file first, and then the log files that it references.

Validate the digest file

To validate a digest file, you need its signature, the public key whose private key was used to signed it, and a data signing string that you compute.

1. Get the digest file.
2. Verify that the digest file has been retrieved from its original location.
3. Get the hexadecimal-encoded signature of the digest file.
4. Get the hexadecimal-encoded fingerprint of the public key whose private key was used to sign the digest file.
5. Retrieve the public keys for the time range corresponding to the digest file.
6. From among the public keys retrieved, choose the public key whose fingerprint matches the fingerprint in the digest file.
7. Using the digest file hash and other digest file fields, recreate the data signing string used to verify the digest file signature.
8. Validate the signature by passing in the SHA-256 hash of the string, the public key, and the signature as parameters to the RSA signature verification algorithm. If the result is true, the digest file is valid.

Validate the log files

If the digest file is valid, validate each of the log files that the digest file references.

1. To validate the integrity of a log file, compute its SHA-256 hash value on its uncompressed content and compare the results with the hash for the log file recorded in hexadecimal in the digest. If the hashes match, the log file is valid.
2. By using the information about the previous digest file that is included in the current digest file, validate the previous digest files and their corresponding log files in succession.

The following sections describe these steps in detail.

A. Get the digest file

The first steps are to get the most recent digest file, verify that you have retrieved it from its original location, verify its digital signature, and get the fingerprint of the public key.

1. Using S3 [GetObject](#) or the AmazonS3Client class (for example), get the most recent digest file from your Amazon S3 bucket for the time range that you want to validate.
2. Check that the S3 bucket and S3 object used to retrieve the file match the S3 bucket S3 object locations that are recorded in the digest file itself.
3. Next, get the digital signature of the digest file from the `x-amz-meta-signature` metadata property of the digest file object in Amazon S3.
4. In the digest file, get the fingerprint of the public key whose private key was used to sign the digest file from the `digestPublicKeyFingerprint` field.

B. Retrieve the public key for validating the digest file

To get the public key to validate the digest file, you can use either the AWS CLI or the CloudTrail API. In both cases, you specify a time range (that is, a start time and end time) for the digest files that you want to validate. One or more public keys may be returned for the time range that you specify. The returned keys may have validity time ranges that overlap.

Note

Because CloudTrail uses different private/public key pairs per Region, each digest file is signed with a private key unique to its Region. Therefore, when you validate a digest file from a particular Region, you must retrieve its public key from the same Region.

Use the AWS CLI to retrieve public keys

To retrieve public keys for digest files by using the AWS CLI, use the `cloudtrail list-public-keys` command. The command has the following format:

```
aws cloudtrail list-public-keys [--start-time <start-time>] [--end-time <end-time>]
```

The start-time and end-time parameters are UTC timestamps and are optional. If not specified, the current time is used, and the currently active public key or keys are returned.

Sample Response

The response will be a list of JSON objects representing the key (or keys) returned:

```
{
  "publicKeyList": [
    {
      "ValidityStartTime": "1436317441.0",
      "ValidityEndTime": "1438909441.0",
      "Value": "MIIBCgKCAQEAn11L2YZ9h7onug2ILi1MwyHiMRsTQjfWE
+pHVRLk1QjfwHirG+lp0a8NrwQ/r7Ah5bNL6Hepzn0U9XTDSfmmnP97mqyc7z/upfZdS/AHhYcGaz7n6Wc/
RRBU6VmiPCrAUojuSk6/GjvA8i0PFsYDuBtviXarvuLPlrT9kAd4Lb+rFfR5peEgBEkh1zc5HuW07S0y
+KunqxX6jQBnXGMtxmPBPP0FylgWGndFtks/4YSKcgqwH0YDcawP9GGGDAeCIqPWIXDLG1j0jRRzWfCmD0iJUkz8vTsn4ho
      "Fingerprint": "8eba5db5bea9b640d1c96a77256fe7f2"
    },
    {
      "ValidityStartTime": "1434589460.0",
      "ValidityEndTime": "1437181460.0",
      "Value": "MIIBCgKCAQEApfYL2FiZhpn74LNWVUzhR
+VheYhwhYm8w0n5Gf6i95y1W5kBAWKVEmnAQG7BvS5g9SMqFDQx52fW7NwV44IvfJ2xGXT
+wT+DgR6ZQ+6yxskQNqV5YcXj4Aa5Zz4jJfsYjDu02MDTZNIzNvBNzaBJ+r2WIWAJ/
Xq54kyF63B6WE38vKuDE7nSd1FqQuEoNBFLPInvgggYe2Ym1Refe2z71wNcJ2kY
+q0h1BSHrSM8RWuJIw7MXwF9iQncg9jYzU1NJomozQzAG5wSRfbplcCYNY40xvGd/aAm00m+Y
+XFMrKwtLCwseHPvj843qVno6x4BJN9bpWnoPo9sdsbGoiK3QIDAQAB",
    }
  ]
}
```

```

        "Fingerprint": "8933b39ddc64d26d8e14ffbf6566fee4"
    },
    {
        "ValidityStartTime": "1434589370.0",
        "ValidityEndTime": "1437181370.0",
        "Value":
            "MIIBIjANBgqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEAqlzPJbvZJ42UdcmlfPUqXYNf0s6I8lCfao/
            t0s8CmzP0EdtLWugB9xoIUz78qVhDKIqxbaG4jWHfJBi0SSFBM0lt8cdVo4TnRa7oG9io5pysS6DJhBBaEXsicufsiFJR
            +wrUNh8RSLxL4k6G1+BhLX20tJkZ/erT97tDGBujAelqseGg3vPZbTx9SMf0LN65PdLFudLP7Gat0Z9p5jw/
            rjpc1Kfo9Bfc3heeBxWGKwBB0KnFAaN9V57p0aosCvPKmHd9bg7jsQkI9Xp22IzGLsTFJZYVA3KiTAE1DMu80iFXPHEq9hK
            +1utKVEiLkR2disdCmPTK0VQIDAQAB",
        "Fingerprint": "31e8b5433410dfb61a9dc45cc65b22ff"
    }
]
}

```

Use the CloudTrail API to retrieve public keys

To retrieve public keys for digest files by using the CloudTrail API, pass in start time and end time values to the `ListPublicKeys` API. The `ListPublicKeys` API returns the public keys whose private keys were used to sign digest files within the specified time range. For each public key, the API also returns the corresponding fingerprint.

ListPublicKeys

This section describes the request parameters and response elements for the `ListPublicKeys` API.

Note

The encoding for the binary fields for `ListPublicKeys` is subject to change.

Request Parameters

Name	Description
<code>StartTime</code>	Optionally specifies, in UTC, the start of the time range to look up public keys for CloudTrail digest files. If <code>StartTime</code> is not specified, the current time is used, and the current public key is returned.

Name	Description
	Type: DateTime
EndTime	Optionally specifies, in UTC, the end of the time range to look up public keys for CloudTrail digest files. If EndTime is not specified, the current time is used. Type: DateTime

Response Elements

PublicKeyList, an array of PublicKey objects that contains:

Name	Description
Value	The DER encoded public key value in PKCS #1 format. Type: Blob
ValidityStartTime	The starting time of validity of the public key. Type: DateTime
ValidityEndTime	The ending time of validity of the public key. Type: DateTime
Fingerprint	The fingerprint of the public key. The fingerprint can be used to identify the public key that you must use to validate the digest file. Type: String

C. Choose the public key to use for validation

From among the public keys retrieved by `list-public-keys` or `ListPublicKeys`, choose the public key returned whose fingerprint matches the fingerprint recorded in the `digestPublicKeyFingerprint` field of the digest file. This is the public key that you will use to validate the digest file.

D. Recreate the data signing string

Now that you have the signature of the digest file and associated public key, you need to calculate the data signing string. After you have calculated the data signing string, you will have the inputs needed to verify the signature.

The data signing string has the following format:

```
Data_To_Sign_String =  
  Digest_End_Timestamp_in_UTC_Extended_format + '\n' +  
  Current_Digest_File_S3_Path + '\n' +  
  Hex(Sha256(current-digest-file-content)) + '\n' +  
  Previous_digest_signature_in_hex
```

An example Data_To_Sign_String follows.

```
2015-08-12T04:01:31Z  
amzn-s3-demo-bucket/AWSLogs/111122223333/CloudTrail-Digest/us-  
east-2/2015/08/12/111122223333_us-east-2_CloudTrail-Digest_us-  
east-2_20150812T040131Z.json.gz  
4ff08d7c6ecd6eb313257e839645d20363ee3784a2328a7d76b99b53cc9bcacd  
6e8540b83c3ac86a0312d971a225361d28ed0af20d70c211a2d405e32abf529a8145c2966e3bb47362383a52441545e  
d4c7c09dd152b84e79099ce7a9ec35d2b264eb92eb6e090f1e5ec5d40ec8a0729c02ff57f9e30d5343a8591638f8b79  
98b0aee2c1c8af74ec620261529265e83a9834ebef6054979d3e9a6767dfa6fdb4ae153436c567d6ae208f988047ccf
```

After you recreate this string, you can validate the digest file.

E. Validate the digest file

Pass the SHA-256 hash of the recreated data signing string, digital signature, and public key to the RSA signature verification algorithm. If the output is true, the signature of the digest file is verified and the digest file is valid.

F. Validate the log files

After you have validated the digest file, you can validate the log files it references. The digest file contains the SHA-256 hashes of the log files. If one of the log files was modified after CloudTrail delivered it, the SHA-256 hashes will change, and the signature of digest file will not match.

The following shows how validate the log files:

1. Do an S3 `Get` of the log file using the S3 location information in the digest file's `logFiles.s3Bucket` and `logFiles.s3Object` fields.
2. If the S3 `Get` operation is successful, iterate through the log files listed in the digest file's `logFiles` array using the following steps:
 - a. Retrieve the original hash of the file from the `logFiles.hashValue` field of the corresponding log in the digest file.
 - b. Hash the uncompressed contents of the log file with the hashing algorithm specified in `logFiles.hashAlgorithm`.
 - c. Compare the hash value that you generated with the one for the log in the digest file. If the hashes match, the log file is valid.

G. Validate additional digest and log files

In each digest file, the following fields provide the location and signature of the previous digest file:

- `previousDigestS3Bucket`
- `previousDigestS3Object`
- `previousDigestSignature`

Use this information to visit previous digest files sequentially, validating the signature of each and the log files that they reference by using the steps in the previous sections. The only difference is that for previous digest files, you do not need to retrieve the digital signature from the digest file object's Amazon S3 metadata properties. The signature for the previous digest file is provided for you in the `previousDigestSignature` field.

You can go back until the starting digest file is reached, or until the chain of digest files is broken, whichever comes first.

Validating digest and log files offline

When validating digest and log files offline, you can generally follow the procedures described in the previous sections. However, you must take into account the following areas:

Handling the most recent digest file

The digital signature of the most recent (that is, "current") digest file is in the Amazon S3 metadata properties of the digest file object. In an offline scenario, the digital signature for the current digest file will not be available.

Two possible ways of handling this are:

- Since the digital signature for the previous digest file is in the current digest file, start validating from the next-to-last digest file. With this method, the most recent digest file cannot be validated.
- As a preliminary step, obtain the signature for the current digest file from the digest file object's metadata properties and then store it securely offline. This would allow the current digest file to be validated in addition to the previous files in the chain.

Path resolution

Fields in the downloaded digest files like `s3Object` and `previousDigestS3Object` will still be pointing to Amazon S3 online locations for log files and digest files. An offline solution must find a way to reroute these to the current path of the downloaded log and digest files.

Public keys

In order to validate offline, all of the public keys that you need for validating log files in a given time range must first be obtained online (by calling `ListPublicKeys`, for example) and then stored securely offline. This step must be repeated whenever you want to validate additional files outside the initial time range that you specified.

Sample validation snippet

The following sample snippet provides skeleton code for validating CloudTrail digest and log files. The skeleton code is online/offline agnostic; that is, it is up to you to decide whether to implement it with or without online connectivity to AWS. The suggested implementation uses the [Java Cryptography Extension \(JCE\)](#) and [Bouncy Castle](#) as a security provider.

The sample snippet shows:

- How to create the data signing string used to validate the digest file signature.
- How to verify the digest file signature.

- How to verify the log file hashes.
- A code structure for validating a chain of digest files.

```
import java.util.Arrays;
import java.security.MessageDigest;
import java.security.KeyFactory;
import java.security.PublicKey;
import java.security.Security;
import java.security.Signature;
import java.security.spec.X509EncodedKeySpec;
import org.json.JSONObject;
import org.bouncycastle.jce.provider.BouncyCastleProvider;
import org.apache.commons.codec.binary.Hex;

public class DigestFileValidator {

    public void validateDigestFile(String digestS3Bucket, String digestS3Object, String
digestSignature) {

        // Using the Bouncy Castle provider as a JCE security provider - http://
www.bouncycastle.org/
        Security.addProvider(new BouncyCastleProvider());

        // Load the digest file from S3 (using Amazon S3 Client) or from your local
copy
        JSONObject digestFile = loadDigestFileInMemory(digestS3Bucket, digestS3Object);

        // Check that the digest file has been retrieved from its original location
        if (!digestFile.getString("digestS3Bucket").equals(digestS3Bucket) ||
            !digestFile.getString("digestS3Object").equals(digestS3Object)) {
            System.err.println("Digest file has been moved from its original
location.");
        } else {
            // Compute digest file hash
            MessageDigest messageDigest = MessageDigest.getInstance("SHA-256");
            messageDigest.update(convertToByteArray(digestFile));
            byte[] digestFileHash = messageDigest.digest();
            messageDigest.reset();

            // Compute the data to sign
            String dataToSign = String.format("%s%n%s/%s%n%s%n%s",
```

```

        digestFile.getString("digestEndTime"),
        digestFile.getString("digestS3Bucket"),
digestFile.getString("digestS3Object"), // Constructing the S3 path of the digest file
as part of the data to sign
        Hex.encodeHexString(digestFileHash),
        digestFile.getString("previousDigestSignature"));

byte[] signatureContent = Hex.decodeHex(digestSignature);

/*
    NOTE:
    To find the right public key to verify the signature, call CloudTrail
ListPublicKey API to get a list
    of public keys, then match by the publicKeyFingerprint in the digest
file. Also, the public key bytes
    returned from ListPublicKey API are DER encoded in PKCS#1 format:

    PublicKeyInfo ::= SEQUENCE {
        algorithm      AlgorithmIdentifier,
        PublicKey      BIT STRING
    }

    AlgorithmIdentifier ::= SEQUENCE {
        algorithm      OBJECT IDENTIFIER,
        parameters    ANY DEFINED BY algorithm OPTIONAL
    }
*/
pkcs1PublicKeyBytes =
getPublicKey(digestFile.getString("digestPublicKeyFingerprint"));

// Transform the PKCS#1 formatted public key to x.509 format.
RSAPublicKey rsaPublicKey = RSAPublicKey.getInstance(pkcs1PublicKeyBytes);
AlgorithmIdentifier rsaEncryption = new
AlgorithmIdentifier(PKCS0bjectIdentifiers.rsaEncryption, null);
SubjectPublicKeyInfo publicKeyInfo = new
SubjectPublicKeyInfo(rsaEncryption, rsaPublicKey);

// Create the PublicKey object needed for the signature validation
PublicKey publicKey = KeyFactory.getInstance("RSA",
"BC").generatePublic(new X509EncodedKeySpec(publicKeyInfo.getEncoded()));

// Verify signature
Signature signature = Signature.getInstance("SHA256withRSA", "BC");
signature.initVerify(publicKey);

```

```
signature.update(dataToSign.getBytes("UTF-8"));

if (signature.verify(signatureContent)) {
    System.out.println("Digest file signature is valid, validating log
files...");
    for (int i = 0; i < digestFile.getJSONArray("logFiles").length(); i++)
    {

        JSONObject logFileMetadata =
digestFile.getJSONArray("logFiles").getJSONObject(i);

        // Compute log file hash
        byte[] logFileContent = loadUncompressedLogFileInMemory(
                                logFileMetadata.getString("s3Bucket"),
                                logFileMetadata.getString("s3Object")
                                );
        messageDigest.update(logFileContent);
        byte[] logFileHash = messageDigest.digest();
        messageDigest.reset();

        // Retrieve expected hash for the log file being processed
        byte[] expectedHash =
Hex.decodeHex(logFileMetadata.getString("hashValue"));

        boolean signaturesMatch = Arrays.equals(expectedHash, logFileHash);
        if (!signaturesMatch) {
            System.err.println(String.format("Log file: %s/%s hash doesn't
match.\tExpected: %s Actual: %s",
                                logFileMetadata.getString("s3Bucket"),
logFileMetadata.getString("s3Object"),
                                Hex.encodeHexString(expectedHash),
Hex.encodeHexString(logFileHash)));
        } else {
            System.out.println(String.format("Log file: %s/%s hash match",
                                logFileMetadata.getString("s3Bucket"),
logFileMetadata.getString("s3Object")));
        }
    }

    } else {
        System.err.println("Digest signature failed validation.");
    }

    System.out.println("Digest file validation completed.");
```

```
        if (chainValidationIsEnabled()) {
            // This enables the digests' chain validation
            validateDigestFile(
                digestFile.getString("previousDigestS3Bucket"),
                digestFile.getString("previousDigestS3Object"),
                digestFile.getString("previousDigestSignature"));
        }
    }
}
```

CloudTrail log file examples

CloudTrail monitors events for your account. If you create a trail, it delivers those events as log files to your Amazon S3 bucket. If you create an event data store in CloudTrail Lake, events are logged to your event data store. Event data stores do not use S3 buckets.

Topics

- [CloudTrail log file name format](#)
- [Log file examples](#)

CloudTrail log file name format

CloudTrail uses the following file name format for the log file objects that it delivers to your Amazon S3 bucket:

```
AccountID_CloudTrail_RegionName_YYYYMMDDTHHmmZ_UniqueString.FileNameFormat
```

- The YYYY, MM, DD, HH, and mm are the digits of the year, month, day, hour, and minute when the log file was delivered. Hours are in 24-hour format. The Z indicates that the time is in UTC.

Note

A log file delivered at a specific time can contain records written at any point before that time.

- The 16-character UniqueString component of the log file name is there to prevent overwriting of files. It has no meaning, and log processing software should ignore it.
- FileNameFormat is the encoding of the file. Currently, this is json.gz, which is a JSON text file in compressed gzip format.

Example CloudTrail Log File Name

```
111122223333_CloudTrail_us-east-2_20150801T0210Z_Mu0Ks0htH1ar15ZZ.json.gz
```

Log file examples

A log file contains one or more records. The following examples are snippets of logs that show the records for an action that started the creation of a log file.

For information about CloudTrail event record fields, see [CloudTrail record contents for management, data, and network activity events](#).

Contents

- [Amazon EC2 log examples](#)
- [IAM log examples](#)
- [Error code and message log example](#)
- [CloudTrail Insights event log example](#)

Amazon EC2 log examples

Amazon Elastic Compute Cloud (Amazon EC2) provides resizable computing capacity in the AWS Cloud. You can launch virtual servers, configure security and networking, and manage storage. Amazon EC2 can also scale up or down quickly to handle changes in requirements or spikes in popularity, thereby reducing your need to forecast server traffic. For more information, see the [Amazon EC2 User Guide](#).

The following example shows that an IAM user named Mateo ran the **aws ec2 start-instances** command to call the Amazon EC2 [StartInstances](#) action for instances i-EXAMPLE56126103cb and i-EXAMPLEaff4840c22.

```
{"Records": [{  
    "eventVersion": "1.08",
```

```

    "userIdentity": {
      "type": "IAMUser",
      "principalId": "EXAMPLE6E4XEGITWATV6R",
      "arn": "arn:aws:iam::123456789012:user/Mateo",
      "accountId": "123456789012",
      "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
      "userName": "Mateo",
      "sessionContext": {
        "sessionIssuer": {},
        "webIdFederationData": {},
        "attributes": {
          "creationDate": "2023-07-19T21:11:57Z",
          "mfaAuthenticated": "false"
        }
      }
    },
    "eventTime": "2023-07-19T21:17:28Z",
    "eventSource": "ec2.amazonaws.com",
    "eventName": "StartInstances",
    "awsRegion": "us-east-1",
    "sourceIPAddress": "192.0.2.0",
    "userAgent": "aws-cli/2.13.5 Python/3.11.4 Linux/4.14.255-314-253.539.amzn2.x86_64
exec-env/CloudShell exe/x86_64.amzn.2 prompt/off command/ec2.start-instances",
    "requestParameters": {
      "instancesSet": {
        "items": [
          {
            "instanceId": "i-EXAMPLE56126103cb"
          },
          {
            "instanceId": "i-EXAMPLEaff4840c22"
          }
        ]
      }
    },
    "responseElements": {
      "requestId": "e4336db0-149f-4a6b-844d-EXAMPLEb9d16",
      "instancesSet": {
        "items": [
          {
            "instanceId": "i-EXAMPLEaff4840c22",
            "currentState": {
              "code": 0,
              "name": "pending"
            }
          }
        ]
      }
    }
  }
}

```

```

        },
        "previousState": {
            "code": 80,
            "name": "stopped"
        }
    },
    {
        "instanceId": "i-EXAMPLE56126103cb",
        "currentState": {
            "code": 0,
            "name": "pending"
        },
        "previousState": {
            "code": 80,
            "name": "stopped"
        }
    }
]
}
},
"requestID": "e4336db0-149f-4a6b-844d-EXAMPLEb9d16",
"eventID": "e755e09c-42f9-4c5c-9064-EXAMPLE228c7",
"readOnly": false,
"eventType": "AwsApiCall",
"managementEvent": true,
"recipientAccountId": "123456789012",
"eventCategory": "Management",
"tlsDetails": {
    "tlsVersion": "TLSv1.2",
    "cipherSuite": "ECDHE-RSA-AES128-GCM-SHA256",
    "clientProvidedHostHeader": "ec2.us-east-1.amazonaws.com"
},
"sessionCredentialFromConsole": "true"
}]}
```

The following example shows that an IAM user named Nikki ran the **aws ec2 stop-instances** command to call the Amazon EC2 [StopInstances](#) action to stop two instances.

```

{"Records": [{
    "eventVersion": "1.08",
    "userIdentity": {
        "type": "IAMUser",
        "principalId": "EXAMPLE6E4XEGITWATV6R",
```

```

    "arn": "arn:aws:iam::777788889999:user/Nikki",
    "accountId": "777788889999",
    "accessKeyId": "AKIAI44QH8DHBEXAMPLE",
    "userName": "Nikki",
    "sessionContext": {
      "sessionIssuer": {},
      "webIdFederationData": {},
      "attributes": {
        "creationDate": "2023-07-19T21:11:57Z",
        "mfaAuthenticated": "false"
      }
    }
  },
  "eventTime": "2023-07-19T21:14:20Z",
  "eventSource": "ec2.amazonaws.com",
  "eventName": "StopInstances",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.0",
  "userAgent": "aws-cli/2.13.5 Python/3.11.4 Linux/4.14.255-314-253.539.amzn2.x86_64
exec-env/CloudShell exe/x86_64.amzn.2 prompt/off command/ec2.stop-instances",
  "requestParameters": {
    "instancesSet": {
      "items": [
        {
          "instanceId": "i-EXAMPLE56126103cb"
        },
        {
          "instanceId": "i-EXAMPLEaaff4840c22"
        }
      ]
    },
    "force": false
  },
  "responseElements": {
    "requestId": "c308a950-e43e-444e-afc1-EXAMPLE73e49",
    "instancesSet": {
      "items": [
        {
          "instanceId": "i-EXAMPLE56126103cb",
          "currentState": {
            "code": 64,
            "name": "stopping"
          },
          "previousState": {

```

```

        "code": 16,
        "name": "running"
      }
    },
    {
      "instanceId": "i-EXAMPLEaaff4840c22",
      "currentState": {
        "code": 64,
        "name": "stopping"
      },
      "previousState": {
        "code": 16,
        "name": "running"
      }
    }
  ]
}
},
"requestID": "c308a950-e43e-444e-afc1-EXAMPLE73e49",
"eventID": "9357a8cc-a0eb-46a1-b67e-EXAMPLE19b14",
"readOnly": false,
"eventType": "AwsApiCall",
"managementEvent": true,
"recipientAccountId": "777788889999",
"eventCategory": "Management",
"tlsDetails": {
  "tlsVersion": "TLSv1.2",
  "cipherSuite": "ECDHE-RSA-AES128-GCM-SHA256",
  "clientProvidedHostHeader": "ec2.us-east-1.amazonaws.com"
},
"sessionCredentialFromConsole": "true"
}]}
```

The following example shows that an IAM user named Arnav ran the **aws ec2 create-key-pair** command to call the [CreateKeyPair](#) action. Note that the responseElements contain a hash of the key pair and that AWS removed the key material.

```

{"Records": [{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "AIDA60N6E4XEGIEXAMPLE",
    "arn": "arn:aws:iam::444455556666:user/Arnav",
```

```

    "accountId": "444455556666",
    "accessKeyId": "AKIAI44QH8DHBEXAMPLE",
    "userName": "Arnav",
    "sessionContext": {
      "sessionIssuer": {},
      "webIdFederationData": {},
      "attributes": {
        "creationDate": "2023-07-19T21:11:57Z",
        "mfaAuthenticated": "false"
      }
    }
  },
  "eventTime": "2023-07-19T21:19:22Z",
  "eventSource": "ec2.amazonaws.com",
  "eventName": "CreateKeyPair",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.0",
  "userAgent": "aws-cli/2.13.5 Python/3.11.4 Linux/4.14.255-314-253.539.amzn2.x86_64
exec-env/CloudShell exe/x86_64.amzn.2 prompt/off command/ec2.create-key-pair",
  "requestParameters": {
    "keyName": "my-key",
    "keyType": "rsa",
    "keyFormat": "pem"
  },
  "responseElements": {
    "requestId": "9aa4938f-720f-4f4b-9637-EXAMPLE9a196",
    "keyName": "my-key",
    "keyFingerprint":
"1f:51:ae:28:bf:89:e9:d8:1f:25:5d:37:2d:7d:b8:ca:9f:f5:f1:6f",
    "keyPairId": "key-abcd12345eEXAMPLE",
    "keyMaterial": "<sensitiveDataRemoved>"
  },
  "requestID": "9aa4938f-720f-4f4b-9637-EXAMPLE9a196",
  "eventID": "2ae450ff-e72b-4de1-87b0-EXAMPLE5227cb",
  "readOnly": false,
  "eventType": "AwsApiCall",
  "managementEvent": true,
  "recipientAccountId": "444455556666",
  "eventCategory": "Management",
  "tlsDetails": {
    "tlsVersion": "TLSv1.2",
    "cipherSuite": "ECDHE-RSA-AES128-GCM-SHA256",
    "clientProvidedHostHeader": "ec2.us-east-1.amazonaws.com"
  },

```

```
"sessionCredentialFromConsole": "true"
}}}
```

IAM log examples

AWS Identity and Access Management (IAM) is a web service that helps you securely control access to AWS resources. With IAM, you can centrally manage permissions that control which AWS resources users can access. You use IAM to control who is authenticated (signed in) and authorized (has permissions) to use resources. For more information, see the [IAM User Guide](#).

The following example shows that the IAM user named Mary ran the **aws iam create-user** command to call the [CreateUser](#) action to create a new user named Richard.

```
{
  "Records": [
    {
      "eventVersion": "1.08",
      "userIdentity": {
        "type": "IAMUser",
        "principalId": "AIDA60N6E4XEGITEXAMPLE",
        "arn": "arn:aws:iam::888888888888:user/Mary",
        "accountId": "888888888888",
        "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
        "userName": "Mary",
        "sessionContext": {
          "sessionIssuer": {},
          "webIdFederationData": {},
          "attributes": {
            "creationDate": "2023-07-19T21:11:57Z",
            "mfaAuthenticated": "false"
          }
        }
      },
      "eventTime": "2023-07-19T21:25:09Z",
      "eventSource": "iam.amazonaws.com",
      "eventName": "CreateUser",
      "awsRegion": "us-east-1",
      "sourceIPAddress": "192.0.2.0",
      "userAgent": "aws-cli/2.13.5 Python/3.11.4 Linux/4.14.255-314-253.539.amzn2.x86_64 exec-env/CloudShell exe/x86_64.amzn.2 prompt/off command/iam.create-user",
      "requestParameters": {
        "userName": "Richard"
      },
      "responseElements": {
```

```

    "user": {
      "path": "/",
      "arn": "arn:aws:iam::888888888888:user/Richard",
      "userId": "AIDA60N6E4XEP7EXAMPLE",
      "createDate": "Jul 19, 2023 9:25:09 PM",
      "userName": "Richard"
    }
  },
  "requestID": "2d528c76-329e-410b-9516-EXAMPLE565dc",
  "eventID": "ba0801a1-87ec-4d26-be87-EXAMPLE75bbb",
  "readOnly": false,
  "eventType": "AwsApiCall",
  "managementEvent": true,
  "recipientAccountId": "888888888888",
  "eventCategory": "Management",
  "tlsDetails": {
    "tlsVersion": "TLSv1.2",
    "cipherSuite": "ECDHE-RSA-AES128-GCM-SHA256",
    "clientProvidedHostHeader": "iam.amazonaws.com"
  },
  "sessionCredentialFromConsole": "true"
}]}
```

The following example shows that the IAM user named Paulo ran the **aws iam add-user-to-group** command to call the [AddUserToGroup](#) action to add a user named Jane to the Admin group.

```

{"Records": [{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "AIDA60N6E4XEGIEEXAMPLE",
    "arn": "arn:aws:iam::555555555555:user/Paulo",
    "accountId": "555555555555",
    "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
    "userName": "Paulo",
    "sessionContext": {
      "sessionIssuer": {},
      "webIdFederationData": {},
      "attributes": {
        "creationDate": "2023-07-19T21:11:57Z",
        "mfaAuthenticated": "false"
      }
    }
  }
}]}
```



```

    },
    "eventTime": "2023-07-19T21:25:09Z",
    "eventSource": "iam.amazonaws.com",
    "eventName": "AddUserToGroup",
    "awsRegion": "us-east-1",
    "sourceIPAddress": "192.0.2.0",
    "userAgent": "aws-cli/2.13.5 Python/3.11.4 Linux/4.14.255-314-253.539.amzn2.x86_64
exec-env/CloudShell exe/x86_64.amzn.2 prompt/off command/iam.add-user-to-group",
    "requestParameters": {
        "groupName": "Admin",
        "userName": "Jane"
    },
    },
    "responseElements": null,
    "requestID": "ecd94349-b36f-44bf-b6f5-EXAMPLE9c463",
    "eventID": "2939ba50-1d26-4a5a-83bd-EXAMPLE85850",
    "readOnly": false,
    "eventType": "AwsApiCall",
    "managementEvent": true,
    "recipientAccountId": "555555555555",
    "eventCategory": "Management",
    "tlsDetails": {
        "tlsVersion": "TLSv1.2",
        "cipherSuite": "ECDHE-RSA-AES128-GCM-SHA256",
        "clientProvidedHostHeader": "iam.amazonaws.com"
    },
    },
    "sessionCredentialFromConsole": "true"
  ]}]

```

The following example shows that the IAM user named Saanvi ran the **aws iam create-role** command to call the [CreateRole](#) action to create a role.

```

{"Records": [{
  "eventVersion": "1.08",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "AIDA60N6E4XEGITEXAMPLE",
    "arn": "arn:aws:iam::777777777777:user/Saanvi",
    "accountId": "777777777777",
    "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
    "userName": "Saanvi",
    "sessionContext": {
      "sessionIssuer": {},
      "webIdFederationData": {},

```

```

        "attributes": {
            "creationDate": "2023-07-19T21:11:57Z",
            "mfaAuthenticated": "false"
        }
    },
    "eventTime": "2023-07-19T21:29:12Z",
    "eventSource": "iam.amazonaws.com",
    "eventName": "CreateRole",
    "awsRegion": "us-east-1",
    "sourceIPAddress": "192.0.2.0",
    "userAgent": "aws-cli/2.13.5 Python/3.11.4 Linux/4.14.255-314-253.539.amzn2.x86_64
exec-env/CloudShell exe/x86_64.amzn.2 prompt/off command/iam.create-role",
    "requestParameters": {
        "roleName": "TestRole",
        "description": "Allows EC2 instances to call AWS services on your behalf.",
        "assumeRolePolicyDocument": "{\"Version\":\"2012-10-17\",          \"Statement
\": [{\"Effect\":\"Allow\", \"Action\": [\"sts:AssumeRole\"], \"Principal\": {\"Service\":
[\"ec2.amazonaws.com\"]}]}]"
    },
    "responseElements": {
        "role": {
            "assumeRolePolicyDocument": "policy-statement",
            "arn": "arn:aws:iam::777777777777:role/TestRole",
            "roleId": "AROA6ON6E4XEFFEXAMPLE",
            "createDate": "Jul 19, 2023 9:29:12 PM",
            "roleName": "TestRole",
            "path": "/"
        }
    },
    "requestID": "ff38f36e-ebd3-425b-9939-EXAMPLE1bbe",
    "eventID": "9da77cd0-493f-4c89-8852-EXAMPLEa887c",
    "readOnly": false,
    "eventType": "AwsApiCall",
    "managementEvent": true,
    "recipientAccountId": "777777777777",
    "eventCategory": "Management",
    "tlsDetails": {
        "tlsVersion": "TLSv1.2",
        "cipherSuite": "ECDHE-RSA-AES128-GCM-SHA256",
        "clientProvidedHostHeader": "iam.amazonaws.com"
    },
    "sessionCredentialFromConsole": "true"

```

```
}}}
```

Error code and message log example

The following example shows that the IAM user named Terry ran the **aws cloudtrail update-trail** command to call the [UpdateTrail](#) action to update a trail named myTrail2, but the trail name was not found. The log shows this error in the **errorCode** and **errorMessage** elements.

```
{
  "Records": [
    {
      "eventVersion": "1.09",
      "userIdentity": {
        "type": "IAMUser",
        "principalId": "AIDA60N6E4XEGIEEXAMPLE",
        "arn": "arn:aws:iam::111122223333:user/Terry",
        "accountId": "111122223333",
        "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
        "userName": "Terry",
        "sessionContext": {
          "attributes": {
            "creationDate": "2023-07-19T21:11:57Z",
            "mfaAuthenticated": "false"
          }
        }
      },
      "eventTime": "2023-07-19T21:35:03Z",
      "eventSource": "cloudtrail.amazonaws.com",
      "eventName": "UpdateTrail",
      "awsRegion": "us-east-1",
      "sourceIPAddress": "192.0.2.0",
      "userAgent": "aws-cli/2.13.0 Python/3.11.4 Linux/4.14.255-314-253.539.amzn2.x86_64 exec-env/CloudShell exe/x86_64.amzn.2 prompt/off command/cloudtrail.update-trail",
      "errorCode": "TrailNotFoundException",
      "errorMessage": "Unknown trail: arn:aws:cloudtrail:us-east-1:111122223333:trail/myTrail2 for the user: 111122223333",
      "requestParameters": {
        "name": "myTrail2",
        "isMultiRegionTrail": true
      },
      "responseElements": null,
      "requestID": "28d2faaf-3319-4649-998d-EXAMPLE72818",
      "eventID": "694d604a-d190-4470-8dd1-EXAMPLEe20c1",
      "readOnly": false,
      "eventType": "AwsApiCall",
    }
  ]
}
```

```

    "managementEvent": true,
    "recipientAccountId": "111122223333",
    "eventCategory": "Management",
    "tlsDetails": {
      "tlsVersion": "TLSv1.2",
      "cipherSuite": "ECDHE-RSA-AES128-GCM-SHA256",
      "clientProvidedHostHeader": "cloudtrail.us-east-1.amazonaws.com"
    },
    "sessionCredentialFromConsole": "true"
  ]}]

```

CloudTrail Insights event log example

The following example shows a CloudTrail Insights event log. An Insights event is actually a pair of events that mark the start and end of a period of unusual write management API activity or error response activity. The state field shows whether the event was logged at the start or end of the period of unusual activity. The event name, UpdateInstanceInformation, is the same name as the AWS Systems Manager API for which CloudTrail analyzed management events to determine that unusual activity occurred. Although the start and end events have unique eventID values, they also have a sharedEventID value that is used by the pair. The Insights event shows the baseline, or the normal pattern of activity, the insight, or average unusual activity that triggered the start Insights event, and in the end event, the insight value for the average unusual activity over the duration of the Insights event. For more information about CloudTrail Insights, see [Working with CloudTrail Insights](#).

```

{
  "Records": [{
    "eventVersion": "1.08",
    "eventTime": "2023-01-02T02:51:00Z",
    "awsRegion": "us-east-1",
    "eventID": "654a30ff-b0f3-4527-81b6-EXAMPLEf2393",
    "eventType": "AwsCloudTrailInsight",
    "recipientAccountId": "123456789012",
    "sharedEventID": "bcbfc274-8559-4a56-beb0-EXAMPLEa6c34",
    "insightDetails": {
      "state": "Start",
      "eventSource": "ssm.amazonaws.com",
      "eventName": "UpdateInstanceInformation",
      "insightType": "ApiCallRateInsight",
      "insightContext": {
        "statistics": {

```

```

        "baseline": {
            "average": 84.410596421
        },
        "insight": {
            "average": 669
        }
    }
},
"eventCategory": "Insight"
},
{
    "eventVersion": "1.08",
    "eventTime": "2023-01-02T00:22:00Z",
    "awsRegion": "us-east-1",
    "eventID": "258de2fb-e2a9-4fb5-aeb2-EXAMPLE449a4",
    "eventType": "AwsCloudTrailInsight",
    "recipientAccountId": "123456789012",
    "sharedEventID": "8b74a7bc-d5d3-4d19-9d60-EXAMPLE08b51",
    "insightDetails": {
        "state": "End",
        "eventSource": "ssm.amazonaws.com",
        "eventName": "UpdateInstanceInformation",
        "insightType": "ApiCallRateInsight",
        "insightContext": {
            "statistics": {
                "baseline": {
                    "average": 74.156423842
                },
                "insight": {
                    "average": 657
                },
                "insightDuration": 1
            }
        }
    },
    "eventCategory": "Insight"
}]
}

```

Using the CloudTrail Processing Library

The CloudTrail Processing Library is a Java library that provides an easy way to process AWS CloudTrail logs. You provide configuration details about your CloudTrail SQS queue and write code to process events. The CloudTrail Processing Library does the rest. It polls your Amazon SQS queue, reads and parses queue messages, downloads CloudTrail log files, parses events in the log files, and passes the events to your code as Java objects.

The CloudTrail Processing Library is highly scalable and fault-tolerant. It handles parallel processing of log files so that you can process as many logs as needed. It handles network failures related to network timeouts and inaccessible resources.

The following topic shows you how to use the CloudTrail Processing Library to process CloudTrail logs in your Java projects.

The library is provided as an Apache-licensed open-source project, available on GitHub: <https://github.com/aws/aws-cloudtrail-processing-library>. The library source includes sample code that you can use as a base for your own projects.

Topics

- [Minimum requirements](#)
- [Processing CloudTrail logs](#)
- [Advanced topics](#)
- [Additional resources](#)

Minimum requirements

To use the CloudTrail Processing Library, you must have the following:

- [AWS SDK for Java 1.11.830](#)
- [Java 1.8 \(Java SE 8\)](#)

Processing CloudTrail logs

To process CloudTrail logs in your Java application:

1. [Adding the CloudTrail Processing Library to your project](#)

2. [Configuring the CloudTrail Processing Library](#)
3. [Implementing the events processor](#)
4. [Instantiating and running the processing executor](#)

Adding the CloudTrail Processing Library to your project

To use the CloudTrail Processing Library, add it to your Java project's classpath.

Contents

- [Adding the library to an Apache Ant project](#)
- [Adding the library to an Apache Maven project](#)
- [Adding the library to an Eclipse project](#)
- [Adding the library to an IntelliJ project](#)

Adding the library to an Apache Ant project

To add the CloudTrail Processing Library to an Apache Ant project

1. Download or clone the CloudTrail Processing Library source code from GitHub:
 - <https://github.com/aws/aws-cloudtrail-processing-library>
2. Build the .jar file from source as described in the [README](#):

```
mvn clean install -Dgpg.skip=true
```

3. Copy the resulting .jar file into your project and add it to your project's `build.xml` file. For example:

```
<classpath>
  <pathelement path="${classpath}"/>
  <pathelement location="lib/aws-cloudtrail-processing-library-1.6.1.jar"/>
</classpath>
```

Adding the library to an Apache Maven project

The CloudTrail Processing Library is available for [Apache Maven](#). You can add it to your project by writing a single dependency in your project's `pom.xml` file.

To add the CloudTrail Processing Library to a Maven project

- Open your Maven project's `pom.xml` file and add the following dependency:

```
<dependency>
  <groupId>com.amazonaws</groupId>
  <artifactId>aws-cloudtrail-processing-library</artifactId>
  <version>1.6.1</version>
</dependency>
```

Adding the library to an Eclipse project

To add the CloudTrail Processing Library to an Eclipse project

1. Download or clone the CloudTrail Processing Library source code from GitHub:
 - <https://github.com/aws/aws-cloudtrail-processing-library>
2. Build the `.jar` file from source as described in the [README](#):

```
mvn clean install -Dgpg.skip=true
```

3. Copy the built `aws-cloudtrail-processing-library-1.6.1.jar` to a directory in your project (typically `lib`).
4. Right-click your project's name in the Eclipse **Project Explorer**, choose **Build Path**, and then choose **Configure**
5. In the **Java Build Path** window, choose the **Libraries** tab.
6. Choose **Add JARs...** and navigate to the path where you copied `aws-cloudtrail-processing-library-1.6.1.jar`.
7. Choose **OK** to complete adding the `.jar` to your project.

Adding the library to an IntelliJ project

To add the CloudTrail Processing Library to an IntelliJ project

1. Download or clone the CloudTrail Processing Library source code from GitHub:

- <https://github.com/aws/aws-cloudtrail-processing-library>

2. Build the .jar file from source as described in the [README](#):

```
mvn clean install -Dpgp.skip=true
```

3. From **File**, choose **Project Structure**.
4. Choose **Modules** and then choose **Dependencies**.
5. Choose **+ JARS or Directories** and then go to the path where you built the `aws-cloudtrail-processing-library-1.6.1.jar`.
6. Choose **Apply** and then choose **OK** to complete adding the .jar to your project.

Configuring the CloudTrail Processing Library

You can configure the CloudTrail Processing Library by creating a classpath properties file that is loaded at runtime, or by creating a `ClientConfiguration` object and setting options manually.

Providing a properties file

You can write a classpath properties file that provides configuration options to your application. The following example file shows the options you can set:

```
# AWS access key. (Required)
accessKey = your_access_key

# AWS secret key. (Required)
secretKey = your_secret_key

# The SQS URL used to pull CloudTrail notification from. (Required)
sqsUrl = your_sqs_queue_url

# The SQS end point specific to a region.
sqsRegion = us-east-1

# A period of time during which Amazon SQS prevents other consuming components
```

```
# from receiving and processing that message.
visibilityTimeout = 60

# The S3 region to use.
s3Region = us-east-1

# Number of threads used to download S3 files in parallel. Callbacks can be
# invoked from any thread.
threadCount = 1

# The time allowed, in seconds, for threads to shut down after
# AWSCloudTrailEventProcessingExecutor.stop() is called. If they are still
# running beyond this time, they will be forcibly terminated.
threadTerminationDelaySeconds = 60

# The maximum number of AWSCloudTrailClientEvents sent to a single invocation
# of processEvents().
maxEventsPerEmit = 10

# Whether to include raw event information in CloudTrailDeliveryInfo.
enableRawEventInfo = false

# Whether to delete SQS message when the CloudTrail Processing Library is unable to
# process the notification.
deleteMessageUponFailure = false
```

The following parameters are required:

- `sqsUrl` – Provides the URL from which to pull your CloudTrail notifications. If you don't specify this value, the `AWSCloudTrailProcessingExecutor` throws an `IllegalStateException`.
- `accessKey` – A unique identifier for your account, such as `AKIAIOSFODNN7EXAMPLE`.
- `secretKey` – A unique identifier for your account, such as `wJalrXUtnFEMI/K7MDENG/bPxrFcCYEXAMPLEKEY`.

The `accessKey` and `secretKey` parameters provide your AWS credentials to the library so the library can access AWS on your behalf.

Defaults for the other parameters are set by the library. For more information, see the [AWS CloudTrail Processing Library Reference](#).

Creating a ClientConfiguration

Instead of setting options in the classpath properties, you can provide options to the `AWSCloudTrailProcessingExecutor` by initializing and setting options on a `ClientConfiguration` object, as shown in the following example:

```
ClientConfiguration basicConfig = new ClientConfiguration(  
    "http://sqs.us-east-1.amazonaws.com/123456789012/queue2",  
    new DefaultAWSCredentialsProviderChain());  
  
basicConfig.setEnableRawEventInfo(true);  
basicConfig.setThreadCount(4);  
basicConfig.setnEventsPerEmit(20);
```

Implementing the events processor

To process CloudTrail logs, you must implement an `EventsProcessor` that receives the CloudTrail log data. The following is an example implementation:

```
public class SampleEventsProcessor implements EventsProcessor {  
  
    public void process(List<CloudTrailEvent> events) {  
        int i = 0;  
        for (CloudTrailEvent event : events) {  
            System.out.println(String.format("Process event %d : %s", i++,  
event.getEventData()));  
        }  
    }  
}
```

When implementing an `EventsProcessor`, you implement the `process()` callback that the `AWSCloudTrailProcessingExecutor` uses to send you CloudTrail events. Events are provided in a list of `CloudTrailClientEvent` objects.

The `CloudTrailClientEvent` object provides a `CloudTrailEvent` and `CloudTrailEventMetadata` that you can use to read the CloudTrail event and delivery information.

This simple example prints the event information for each event passed to `SampleEventsProcessor`. In your own implementation, you can process logs as you see fit. The

`AWSCloudTrailProcessingExecutor` continues to send events to your `EventsProcessor` as long as it has events to send and is still running.

Instantiating and running the processing executor

After you write an `EventsProcessor` and set configuration values for the CloudTrail Processing Library (either in a properties file or by using the `ClientConfiguration` class), you can use these elements to initialize and use an `AWSCloudTrailProcessingExecutor`.

To use `AWSCloudTrailProcessingExecutor` to process CloudTrail events

1. Instantiate an `AWSCloudTrailProcessingExecutor.Builder` object. Builder's constructor takes an `EventsProcessor` object and a classpath properties file name.
2. Call the Builder's `build()` factory method to configure and obtain an `AWSCloudTrailProcessingExecutor` object.
3. Use the `AWSCloudTrailProcessingExecutor`'s `start()` and `stop()` methods to begin and end CloudTrail event processing.

```
public class SampleApp {
    public static void main(String[] args) throws InterruptedException {
        AWSCloudTrailProcessingExecutor executor = new
            AWSCloudTrailProcessingExecutor.Builder(new SampleEventsProcessor(),
                "/myproject/cloudtrailprocessing.properties").build();

        executor.start();
        Thread.sleep(24 * 60 * 60 * 1000); // let it run for a while (optional)
        executor.stop(); // optional
    }
}
```

Advanced topics

Topics

- [Filtering the events to process](#)
- [Processing data events](#)
- [Reporting progress](#)
- [Handling errors](#)

Filtering the events to process

By default, all logs in your Amazon SQS queue's S3 bucket and all events that they contain are sent to your EventsProcessor. The CloudTrail Processing Library provides optional interfaces that you can implement to filter the sources used to obtain CloudTrail logs and to filter the events that you are interested in processing.

SourceFilter

You can implement the `SourceFilter` interface to choose whether you want to process logs from a provided source. `SourceFilter` declares a single callback method, `filterSource()`, that receives a `CloudTrailSource` object. To keep events from a source from being processed, return `false` from `filterSource()`.

The CloudTrail Processing Library calls the `filterSource()` method after the library polls for logs on the Amazon SQS queue. This occurs before the library starts event filtering or processing for the logs.

The following is an example implementation:

```
public class SampleSourceFilter implements SourceFilter{
    private static final int MAX_RECEIVED_COUNT = 3;

    private static List<String> accountIDs ;
    static {
        accountIDs = new ArrayList<>();
        accountIDs.add("123456789012");
        accountIDs.add("234567890123");
    }

    @Override
    public boolean filterSource(CloudTrailSource source) throws CallbackException {
        source = (SQSBasedSource) source;
        Map<String, String> sourceAttributes = source.getSourceAttributes();

        String accountId = sourceAttributes.get(
            SourceAttributeKeys.ACCOUNT_ID.getAttributeKey());

        String receivedCount = sourceAttributes.get(
            SourceAttributeKeys.APPROXIMATE_RECEIVE_COUNT.getAttributeKey());

        int approximateReceivedCount = Integer.parseInt(receivedCount);
```

```
        return approximateReceivedCount <= MAX_RECEIVED_COUNT &&  
        accountIDs.contains(accountId);  
    }  
}
```

If you don't provide your own `SourceFilter`, then `DefaultSourceFilter` is used, which allows all sources to be processed (it always returns `true`).

EventFilter

You can implement the `EventFilter` interface to choose whether a CloudTrail event is sent to your `EventsProcessor`. `EventFilter` declares a single callback method, `filterEvent()`, that receives a `CloudTrailEvent` object. To keep the event from being processed, return `false` from `filterEvent()`.

The CloudTrail Processing Library calls the `filterEvent()` method after the library polls for logs on the Amazon SQS queue and after source filtering. This occurs before the library starts event processing for the logs.

See the following example implementation:

```
public class SampleEventFilter implements EventFilter{  
  
    private static final String EC2_EVENTS = "ec2.amazonaws.com";  
  
    @Override  
    public boolean filterEvent(CloudTrailClientEvent clientEvent) throws  
        CallbackException {  
        CloudTrailEvent event = clientEvent.getEvent();  
  
        String eventSource = event.getEventSource();  
        String eventName = event.getEventName();  
  
        return eventSource.equals(EC2_EVENTS) && eventName.startsWith("Delete");  
    }  
}
```

If you don't provide your own `EventFilter`, then `DefaultEventFilter` is used, which allows all events to be processed (it always returns `true`).

Processing data events

When CloudTrail processes data events, it preserves numbers in their original format, whether that is an integer (int) or a float (a number that contains a decimal). In events that have integers in the fields of a data event, CloudTrail historically processed these numbers as floats. Currently, CloudTrail processes numbers in these fields by keeping their original format.

As a best practice, to avoid breaking your automations, be flexible in any code or automation that you are using to process or filter CloudTrail data events, and allow both int and float formatted numbers. For best results, use version 1.4.0 or higher of the CloudTrail Processing Library.

The following example snippet shows a float formatted number, 2.0, for the desiredCount parameter in the ResponseParameters block of a data event.

```
"eventName": "CreateService",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "000.00.00.00",
  "userAgent": "console.amazonaws.com",
  "requestParameters": {
    "clientToken": "EXAMPLE",
    "cluster": "default",
    "desiredCount": 2.0
  }
...

```

The following example snippet shows an int formatted number, 2, for the desiredCount parameter in the ResponseParameters block of a data event.

```
"eventName": "CreateService",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "000.00.00.00",
  "userAgent": "console.amazonaws.com",
  "requestParameters": {
    "clientToken": "EXAMPLE",
    "cluster": "default",
    "desiredCount": 2
  }
...

```

Reporting progress

Implement the `ProgressReporter` interface to customize the reporting of CloudTrail Processing Library progress. `ProgressReporter` declares two methods: `reportStart()` and `reportEnd()`, which are called at the beginning and end of the following operations:

- Polling messages from Amazon SQS
- Parsing messages from Amazon SQS
- Processing an Amazon SQS source for CloudTrail logs
- Deleting messages from Amazon SQS
- Downloading a CloudTrail log file
- Processing a CloudTrail log file

Both methods receive a `ProgressStatus` object that contains information about the operation that was performed. The `progressState` member holds a member of the `ProgressState` enumeration that identifies the current operation. This member can contain additional information in the `progressInfo` member. Additionally, any object that you return from `reportStart()` is passed to `reportEnd()`, so you can provide contextual information such as the time when the event began processing.

The following is an example implementation that provides information about how long an operation took to complete:

```
public class SampleProgressReporter implements ProgressReporter {
    private static final Log logger =
        LoggerFactory.getLog(DefaultProgressReporter.class);

    @Override
    public Object reportStart(ProgressStatus status) {
        return new Date();
    }

    @Override
    public void reportEnd(ProgressStatus status, Object startDate) {
        System.out.println(status.getProgressState().toString() + " is " +
            status.getProgressInfo().isSuccess() + " , and latency is " +
            Math.abs(((Date) startDate).getTime()-new Date().getTime()) + "
            milliseconds.");
    }
}
```



```
}
```

If you don't implement your own `ProgressReporter`, then `DefaultExceptionHandler`, which prints the name of the state being run, is used instead.

Handling errors

The `ExceptionHandler` interface allows you to provide special handling when an exception occurs during log processing. `ExceptionHandler` declares a single callback method, `handleException()`, which receives a `ProcessingLibraryException` object with context about the exception that occurred.

You can use the passed-in `ProcessingLibraryException`'s `getStatus()` method to find out what operation was executed when the exception occurred and get additional information about the status of the operation. `ProcessingLibraryException` is derived from Java's standard `Exception` class, so you can also retrieve information about the exception by invoking any of the exception methods.

See the following example implementation:

```
public class SampleExceptionHandler implements ExceptionHandler{
    private static final Log logger =
        LogFactory.getLog(DefaultProgressReporter.class);

    @Override
    public void handleException(ProcessingLibraryException exception) {
        ProgressStatus status = exception.getStatus();
        ProgressState state = status.getProgressState();
        ProgressInfo info = status.getProgressInfo();

        System.err.println(String.format(
            "Exception. Progress State: %s. Progress Information: %s.", state, info));
    }
}
```

If you don't provide your own `ExceptionHandler`, then `DefaultExceptionHandler`, which prints a standard error message, is used instead.

Note

If the `deleteMessageUponFailure` parameter is `true`, the CloudTrail Processing Library does not distinguish general exceptions from processing errors and may delete queue messages.

1. For example, you use the `SourceFilter` to filter messages by timestamp.
2. However, you don't have the required permissions to access the S3 bucket that receives the CloudTrail log files. Because you don't have the required permissions, an `AmazonServiceException` is thrown. The CloudTrail Processing Library wraps this in a `CallbackException`.
3. The `DefaultExceptionHandler` logs this as an error, but does not identify the root cause, which is that you don't have the required permissions. The CloudTrail Processing Library considers this a processing error and deletes the message, even if the message includes a valid CloudTrail log file.

If you want to filter messages with `SourceFilter`, verify that your `ExceptionHandler` can distinguish service exceptions from processing errors.

Additional resources

For more information about the CloudTrail Processing Library, see the following:

- [CloudTrail Processing Library](#) GitHub project, which includes [sample](#) code that demonstrates how to implement a CloudTrail Processing Library application.
- [CloudTrail Processing Library Java Package Documentation](#).

Security in AWS CloudTrail

Cloud security at AWS is the highest priority. As an AWS customer, you benefit from a data center and network architecture that is built to meet the requirements of the most security-sensitive organizations.

Security is a shared responsibility between AWS and you. The [shared responsibility model](#) describes this as security *of* the cloud and security *in* the cloud:

- **Security of the cloud** – AWS is responsible for protecting the infrastructure that runs AWS services in the AWS Cloud. AWS also provides you with services that you can use securely. Third-party auditors regularly test and verify the effectiveness of our security as part of the [AWS compliance programs](#). To learn about the compliance programs that apply to AWS CloudTrail, see [AWS Services in Scope by Compliance Program](#).
- **Security in the cloud** – Your responsibility is determined by the AWS service that you use. You are also responsible for other factors including the sensitivity of your data, your company's requirements, and applicable laws and regulations.

This documentation helps you understand how to apply the shared responsibility model when using CloudTrail. The following topics show you how to configure CloudTrail to meet your security and compliance objectives. You also learn how to use other AWS services that help you to monitor and secure your CloudTrail resources.

Topics

- [Data protection in AWS CloudTrail](#)
- [Identity and Access Management for AWS CloudTrail](#)
- [Compliance validation for AWS CloudTrail](#)
- [Resilience in AWS CloudTrail](#)
- [Infrastructure security in AWS CloudTrail](#)
- [Cross-service confused deputy prevention](#)
- [Security best practices in AWS CloudTrail](#)
- [Encrypting CloudTrail log files, digest files, and event data stores with AWS KMS keys \(SSE-KMS\)](#)

Data protection in AWS CloudTrail

The AWS [shared responsibility model](#) applies to data protection in AWS CloudTrail. As described in this model, AWS is responsible for protecting the global infrastructure that runs all of the AWS Cloud. You are responsible for maintaining control over your content that is hosted on this infrastructure. You are also responsible for the security configuration and management tasks for the AWS services that you use. For more information about data privacy, see the [Data Privacy FAQ](#). For information about data protection in Europe, see the [AWS Shared Responsibility Model and GDPR](#) blog post on the *AWS Security Blog*.

For data protection purposes, we recommend that you protect AWS account credentials and set up individual users with AWS IAM Identity Center or AWS Identity and Access Management (IAM). That way, each user is given only the permissions necessary to fulfill their job duties. We also recommend that you secure your data in the following ways:

- Use multi-factor authentication (MFA) with each account.
- Use SSL/TLS to communicate with AWS resources. We require TLS 1.2 and recommend TLS 1.3.
- Set up API and user activity logging with AWS CloudTrail. For information about using CloudTrail trails to capture AWS activities, see [Working with CloudTrail trails](#) in the *AWS CloudTrail User Guide*.
- Use AWS encryption solutions, along with all default security controls within AWS services.
- Use advanced managed security services such as Amazon Macie, which assists in discovering and securing sensitive data that is stored in Amazon S3.
- If you require FIPS 140-3 validated cryptographic modules when accessing AWS through a command line interface or an API, use a FIPS endpoint. For more information about the available FIPS endpoints, see [Federal Information Processing Standard \(FIPS\) 140-3](#).

We strongly recommend that you never put confidential or sensitive information, such as your customers' email addresses, into tags or free-form text fields such as a **Name** field. This includes when you work with CloudTrail or other AWS services using the console, API, AWS CLI, or AWS SDKs. Any data that you enter into tags or free-form text fields used for names may be used for billing or diagnostic logs. If you provide a URL to an external server, we strongly recommend that you do not include credentials information in the URL to validate your request to that server.

By default, CloudTrail event log files and digest files are encrypted using Amazon S3 server-side encryption (SSE). You can also choose to encrypt your log files and digest files with an AWS Key

Management Service (AWS KMS) key. You can store your log files in your bucket for as long as you want. You can also define Amazon S3 lifecycle rules to archive or delete log files automatically. If you want notifications about log file delivery and validation, you can set up Amazon SNS notifications.

The following security best practices also address data protection in CloudTrail:

- [Encrypting CloudTrail log files, digest files, and event data stores with AWS KMS keys \(SSE-KMS\)](#)
- [Amazon S3 bucket policy for CloudTrail](#)
- [Validating CloudTrail log file integrity](#)
- [Sharing CloudTrail log files between AWS accounts](#)

Because CloudTrail logs files are stored in a bucket or buckets in Amazon S3, you should also review the data protection information in the Amazon Simple Storage Service User Guide. For more information, see [Data protection in Amazon S3](#).

Identity and Access Management for AWS CloudTrail

AWS Identity and Access Management (IAM) is an AWS service that helps an administrator securely control access to AWS resources. IAM administrators control who can be *authenticated* (signed in) and *authorized* (have permissions) to use CloudTrail resources. IAM is an AWS service that you can use with no additional charge.

Topics

- [Audience](#)
- [Authenticating with identities](#)
- [Managing access using policies](#)
- [How AWS CloudTrail works with IAM](#)
- [Identity-based policy examples for AWS CloudTrail](#)
- [AWS CloudTrail resource-based policy examples](#)
- [Amazon S3 bucket policy for CloudTrail](#)
- [Amazon S3 bucket policy for CloudTrail Lake query results](#)
- [Amazon SNS topic policy for CloudTrail](#)
- [Troubleshooting AWS CloudTrail identity and access](#)

- [Using service-linked roles for CloudTrail](#)
- [AWS managed policies for AWS CloudTrail](#)

Audience

How you use AWS Identity and Access Management (IAM) differs based on your role:

- **Service user** - request permissions from your administrator if you cannot access features (see [Troubleshooting AWS CloudTrail identity and access](#))
- **Service administrator** - determine user access and submit permission requests (see [How AWS CloudTrail works with IAM](#))
- **IAM administrator** - write policies to manage access (see [Identity-based policy examples for AWS CloudTrail](#))

Authenticating with identities

Authentication is how you sign in to AWS using your identity credentials. You must be authenticated as the AWS account root user, an IAM user, or by assuming an IAM role.

You can sign in as a federated identity using credentials from an identity source like AWS IAM Identity Center (IAM Identity Center), single sign-on authentication, or Google/Facebook credentials. For more information about signing in, see [How to sign in to your AWS account](#) in the *AWS Sign-In User Guide*.

For programmatic access, AWS provides an SDK and CLI to cryptographically sign requests. For more information, see [AWS Signature Version 4 for API requests](#) in the *IAM User Guide*.

AWS account root user

When you create an AWS account, you begin with one sign-in identity called the AWS account *root user* that has complete access to all AWS services and resources. We strongly recommend that you don't use the root user for everyday tasks. For tasks that require root user credentials, see [Tasks that require root user credentials](#) in the *IAM User Guide*.

Federated identity

As a best practice, require human users to use federation with an identity provider to access AWS services using temporary credentials.

A *federated identity* is a user from your enterprise directory, web identity provider, or AWS Directory Service that accesses AWS services using credentials from an identity source. Federated identities assume roles that provide temporary credentials.

For centralized access management, we recommend AWS IAM Identity Center. For more information, see [What is IAM Identity Center?](#) in the *AWS IAM Identity Center User Guide*.

IAM users and groups

An *IAM user* is an identity with specific permissions for a single person or application. We recommend using temporary credentials instead of IAM users with long-term credentials. For more information, see [Require human users to use federation with an identity provider to access AWS using temporary credentials](#) in the *IAM User Guide*.

An *IAM group* specifies a collection of IAM users and makes permissions easier to manage for large sets of users. For more information, see [Use cases for IAM users](#) in the *IAM User Guide*.

IAM roles

An *IAM role* is an identity with specific permissions that provides temporary credentials. You can assume a role by [switching from a user to an IAM role \(console\)](#) or by calling an AWS CLI or AWS API operation. For more information, see [Methods to assume a role](#) in the *IAM User Guide*.

IAM roles are useful for federated user access, temporary IAM user permissions, cross-account access, cross-service access, and applications running on Amazon EC2. For more information, see [Cross account resource access in IAM](#) in the *IAM User Guide*.

Managing access using policies

You control access in AWS by creating policies and attaching them to AWS identities or resources. A policy defines permissions when associated with an identity or resource. AWS evaluates these policies when a principal makes a request. Most policies are stored in AWS as JSON documents. For more information about JSON policy documents, see [Overview of JSON policies](#) in the *IAM User Guide*.

Using policies, administrators specify who has access to what by defining which **principal** can perform **actions** on what **resources**, and under what **conditions**.

By default, users and roles have no permissions. An IAM administrator creates IAM policies and adds them to roles, which users can then assume. IAM policies define permissions regardless of the method used to perform the operation.

Identity-based policies

Identity-based policies are JSON permissions policy documents that you attach to an identity (user, group, or role). These policies control what actions identities can perform, on which resources, and under what conditions. To learn how to create an identity-based policy, see [Define custom IAM permissions with customer managed policies](#) in the *IAM User Guide*.

Identity-based policies can be *inline policies* (embedded directly into a single identity) or *managed policies* (standalone policies attached to multiple identities). To learn how to choose between managed and inline policies, see [Choose between managed policies and inline policies](#) in the *IAM User Guide*.

Resource-based policies

Resource-based policies are JSON policy documents that you attach to a resource. Examples include IAM *role trust policies* and Amazon S3 *bucket policies*. In services that support resource-based policies, service administrators can use them to control access to a specific resource. You must [specify a principal](#) in a resource-based policy.

Resource-based policies are inline policies that are located in that service. You can't use AWS managed policies from IAM in a resource-based policy.

Other policy types

AWS supports additional policy types that can set the maximum permissions granted by more common policy types:

- **Permissions boundaries** – Set the maximum permissions that an identity-based policy can grant to an IAM entity. For more information, see [Permissions boundaries for IAM entities](#) in the *IAM User Guide*.
- **Service control policies (SCPs)** – Specify the maximum permissions for an organization or organizational unit in AWS Organizations. For more information, see [Service control policies](#) in the *AWS Organizations User Guide*.
- **Resource control policies (RCPs)** – Set the maximum available permissions for resources in your accounts. For more information, see [Resource control policies \(RCPs\)](#) in the *AWS Organizations User Guide*.
- **Session policies** – Advanced policies passed as a parameter when creating a temporary session for a role or federated user. For more information, see [Session policies](#) in the *IAM User Guide*.

Multiple policy types

When multiple types of policies apply to a request, the resulting permissions are more complicated to understand. To learn how AWS determines whether to allow a request when multiple policy types are involved, see [Policy evaluation logic](#) in the *IAM User Guide*.

How AWS CloudTrail works with IAM

Before you use IAM to manage access to CloudTrail, learn what IAM features are available to use with CloudTrail.

IAM features you can use with AWS CloudTrail

IAM feature	CloudTrail support
Identity-based policies	Yes
Resource-based policies	Partial
Policy actions	Yes
Policy resources	Yes
Policy condition keys (service-specific)	No
ACLs	No
ABAC (tags in policies)	Yes
Temporary credentials	Yes
Forward access sessions (FAS)	Yes
Service roles	Yes
Service-linked roles	Yes

To get a high-level view of how CloudTrail and other AWS services work with most IAM features, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Identity-based policies for CloudTrail

Supports identity-based policies: Yes

Identity-based policies are JSON permissions policy documents that you can attach to an identity, such as an IAM user, group of users, or role. These policies control what actions users and roles can perform, on which resources, and under what conditions. To learn how to create an identity-based policy, see [Define custom IAM permissions with customer managed policies](#) in the *IAM User Guide*.

With IAM identity-based policies, you can specify allowed or denied actions and resources as well as the conditions under which actions are allowed or denied. To learn about all of the elements that you can use in a JSON policy, see [IAM JSON policy elements reference](#) in the *IAM User Guide*.

Identity-based policy examples for CloudTrail

To view examples of CloudTrail identity-based policies, see [Identity-based policy examples for AWS CloudTrail](#).

Resource-based policies within CloudTrail

Supports resource-based policies: Partial

Resource-based policies are JSON policy documents that you attach to a resource. Examples of resource-based policies are *IAM role trust policies* and *Amazon S3 bucket policies*. In services that support resource-based policies, service administrators can use them to control access to a specific resource. For the resource where the policy is attached, the policy defines what actions a specified principal can perform on that resource and under what conditions. You must [specify a principal](#) in a resource-based policy. Principals can include accounts, users, roles, federated users, or AWS services.

To enable cross-account access, you can specify an entire account or IAM entities in another account as the principal in a resource-based policy. For more information, see [Cross account resource access in IAM](#) in the *IAM User Guide*.

CloudTrail supports the following types of resource-based policies:

- Resource-based policies on channels used for CloudTrail Lake integrations with event sources outside of AWS. The resource-based policy for the channel defines which principal entities (accounts, users, roles, and federated users) can call `PutAuditEvents` on the channel to deliver events to the destination event data store. For more information about creating integrations with CloudTrail Lake, see [Create an integration with an event source outside of AWS](#).

- Resource-based policies to control which principals can perform actions on your event data store. You can use resource-based policies to provide cross-account access to your event data stores.
- Resource-based policies on dashboards to allow CloudTrail to refresh a CloudTrail Lake dashboard at the interval you define when you set a refresh schedule for a dashboard. For more information, see [Set a refresh schedule for a custom dashboard with the CloudTrail console](#).

Examples

To view examples of CloudTrail resource-based policies, see [AWS CloudTrail resource-based policy examples](#).

Policy actions for CloudTrail

Supports policy actions: Yes

Administrators can use AWS JSON policies to specify who has access to what. That is, which **principal** can perform **actions** on what **resources**, and under what **conditions**.

The **Action** element of a JSON policy describes the actions that you can use to allow or deny access in a policy. Include actions in a policy to grant permissions to perform the associated operation.

To see a list of CloudTrail actions, see [Actions Defined by AWS CloudTrail](#) in the *Service Authorization Reference*.

Policy actions in CloudTrail use the following prefix before the action:

```
cloudtrail
```

For example, to grant someone permission to list tags for a trail with the `ListTags` API operation, you include the `cloudtrail:ListTags` action in their policy. Policy statements must include either an **Action** or **NotAction** element. CloudTrail defines its own set of actions that describe tasks that you can perform with this service.

To specify multiple actions in a single statement, separate them with commas as follows:

```
"Action": [  
    "cloudtrail:AddTags",  
    "cloudtrail:ListTags",
```

```
"cloudtrail:RemoveTags"
```

You can specify multiple actions using wildcards (*). For example, to specify all actions that begin with the word Get, include the following action:

```
"Action": "cloudtrail:Get*"
```

Policy resources for CloudTrail

Supports policy resources: Yes

Administrators can use AWS JSON policies to specify who has access to what. That is, which **principal** can perform **actions** on what **resources**, and under what **conditions**.

The Resource JSON policy element specifies the object or objects to which the action applies. As a best practice, specify a resource using its [Amazon Resource Name \(ARN\)](#). For actions that don't support resource-level permissions, use a wildcard (*) to indicate that the statement applies to all resources.

```
"Resource": ""
```

To see a list of CloudTrail resource types and their ARNs, see [Resources Defined by AWS CloudTrail](#) in the *Service Authorization Reference*. To learn with which actions you can specify the ARN of each resource, see [Actions Defined by AWS CloudTrail](#).

In CloudTrail, there are four resource types: trails, event data stores, dashboards, and channels. Each resource has a unique Amazon Resource Name (ARN) associated with it. In a policy, you use an ARN to identify the resource that the policy applies to. CloudTrail does not currently support other resource types, which are sometimes referred to as subresources.

The CloudTrail trail resource has the following ARN:

```
arn:${Partition}:cloudtrail:${Region}:${Account}:trail/{TrailName}
```

The CloudTrail event data store resource has the following ARN:

```
arn:${Partition}:cloudtrail:${Region}:${Account}:eventdatastore/{EventDataStoreId}
```

The CloudTrail dashboard resource has the following ARN:

```
arn:${Partition}:cloudtrail:${Region}:${Account}:dashboard/{DashboardName}
```

The CloudTrail channel resource has the following ARN:

```
arn:${Partition}:cloudtrail:${Region}:${Account}:channel/{ChannelId}
```

For more information about the format of ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#).

For example, for an AWS account with the ID *123456789012*, to specify a trail named *My-Trail* that exists in the US East (Ohio) Region in your statement, use the following ARN:

```
"Resource": "arn:aws:cloudtrail:us-east-2:123456789012:trail/My-Trail"
```

To specify all trails that belong to a specific account in that AWS Region, use the wildcard (*):

```
"Resource": "arn:aws:cloudtrail:us-east-2:123456789012:trail/*"
```

Some CloudTrail actions, such as those for creating resources, can't be performed on a specific resource. In those cases, you must use the wildcard (*).

```
"Resource": "*"
```

Many CloudTrail API actions involve multiple resources. For example, `CreateTrail` requires an Amazon S3 bucket for storing log files, so a user must have permissions to write to the bucket. To specify multiple resources in a single statement, separate the ARNs with commas.

```
"Resource": [  
    "resource1",  
    "resource2"
```

Policy condition keys for CloudTrail

Supports service-specific policy condition keys: No

Administrators can use AWS JSON policies to specify who has access to what. That is, which **principal** can perform **actions** on what **resources**, and under what **conditions**.

The `Condition` element specifies when statements execute based on defined criteria. You can create conditional expressions that use [condition operators](#), such as equals or less than, to match the condition in the policy with values in the request. To see all AWS global condition keys, see [AWS global condition context keys](#) in the *IAM User Guide*.

CloudTrail doesn't define its own condition keys, but it supports using some global condition keys. To see all AWS global condition keys, see [AWS Global Condition Context Keys](#) in the *IAM User Guide*.

To see a list of CloudTrail condition keys, see [Condition Keys for AWS CloudTrail](#) in the *Service Authorization Reference*. To learn with which actions and resources you can use a condition key, see [Actions Defined by AWS CloudTrail](#).

ACLs in CloudTrail

Supports ACLs: No

Access control lists (ACLs) control which principals (account members, users, or roles) have permissions to access a resource. ACLs are similar to resource-based policies, although they do not use the JSON policy document format.

ABAC with CloudTrail

Supports ABAC (tags in policies): Yes

Attribute-based access control (ABAC) is an authorization strategy that defines permissions based on attributes called tags. You can attach tags to IAM entities and AWS resources, then design ABAC policies to allow operations when the principal's tag matches the tag on the resource.

To control access based on tags, you provide tag information in the [condition element](#) of a policy using the `aws:ResourceTag/key-name`, `aws:RequestTag/key-name`, or `aws:TagKeys` condition keys.

If a service supports all three condition keys for every resource type, then the value is **Yes** for the service. If a service supports all three condition keys for only some resource types, then the value is **Partial**.

For more information about ABAC, see [Define permissions with ABAC authorization](#) in the *IAM User Guide*. To view a tutorial with steps for setting up ABAC, see [Use attribute-based access control \(ABAC\)](#) in the *IAM User Guide*.

You can attach tags to CloudTrail resources or pass tags in a request to CloudTrail. For more information about tagging CloudTrail resources, see [Creating a trail with the CloudTrail console](#) and [Creating, updating, and managing trails with the AWS CLI](#).

Using temporary credentials with CloudTrail

Supports temporary credentials: Yes

Temporary credentials provide short-term access to AWS resources and are automatically created when you use federation or switch roles. AWS recommends that you dynamically generate temporary credentials instead of using long-term access keys. For more information, see [Temporary security credentials in IAM](#) and [AWS services that work with IAM](#) in the *IAM User Guide*.

Forward access sessions for CloudTrail

Supports forward access sessions (FAS): Yes

Forward access sessions (FAS) use the permissions of the principal calling an AWS service, combined with the requesting AWS service to make requests to downstream services. For policy details when making FAS requests, see [Forward access sessions](#).

Service roles for CloudTrail

Supports service roles: Yes

A service role is an [IAM role](#) that a service assumes to perform actions on your behalf. An IAM administrator can create, modify, and delete a service role from within IAM. For more information, see [Create a role to delegate permissions to an AWS service](#) in the *IAM User Guide*.

Warning

Changing the permissions for a service role might break CloudTrail functionality. Edit service roles only when CloudTrail provides guidance to do so.

Service-linked roles for CloudTrail

Supports service-linked roles: Yes

A service-linked role is a type of service role that is linked to an AWS service. The service can assume the role to perform an action on your behalf. Service-linked roles appear in your AWS

account and are owned by the service. An IAM administrator can view, but not edit the permissions for service-linked roles.

CloudTrail supports a service-linked role for integration with AWS Organizations. This role is required for the creation of an organization trail or event data store. Organization trails and event data stores log events for all AWS accounts in an organization. For more information about creating or managing CloudTrail service-linked roles, see [Using service-linked roles for CloudTrail](#).

Identity-based policy examples for AWS CloudTrail

By default, users and roles don't have permission to create or modify CloudTrail resources. To grant users permission to perform actions on the resources that they need, an IAM administrator can create IAM policies.

To learn how to create an IAM identity-based policy by using these example JSON policy documents, see [Create IAM policies \(console\)](#) in the *IAM User Guide*.

For details about actions and resource types defined by CloudTrail, including the format of the ARNs for each of the resource types, see [Actions, Resources, and Condition Keys for AWS CloudTrail](#) in the *Service Authorization Reference*.

Topics

- [Policy best practices](#)
- [Example: Allowing and denying actions for a specified trail](#)
- [Examples: Creating and applying policies for actions on specific trails](#)
- [Examples: Denying access to create or delete event data stores based on tags](#)
- [Using the CloudTrail console](#)
- [Allow users to view their own permissions](#)
- [Granting custom permissions for CloudTrail users](#)

Policy best practices

Identity-based policies determine whether someone can create, access, or delete CloudTrail resources in your account. These actions can incur costs for your AWS account. When you create or edit identity-based policies, follow these guidelines and recommendations:

- **Get started with AWS managed policies and move toward least-privilege permissions** – To get started granting permissions to your users and workloads, use the *AWS managed policies*

that grant permissions for many common use cases. They are available in your AWS account. We recommend that you reduce permissions further by defining AWS customer managed policies that are specific to your use cases. For more information, see [AWS managed policies](#) or [AWS managed policies for job functions](#) in the *IAM User Guide*.

- **Apply least-privilege permissions** – When you set permissions with IAM policies, grant only the permissions required to perform a task. You do this by defining the actions that can be taken on specific resources under specific conditions, also known as *least-privilege permissions*. For more information about using IAM to apply permissions, see [Policies and permissions in IAM](#) in the *IAM User Guide*.
- **Use conditions in IAM policies to further restrict access** – You can add a condition to your policies to limit access to actions and resources. For example, you can write a policy condition to specify that all requests must be sent using SSL. You can also use conditions to grant access to service actions if they are used through a specific AWS service, such as AWS CloudFormation. For more information, see [IAM JSON policy elements: Condition](#) in the *IAM User Guide*.
- **Use IAM Access Analyzer to validate your IAM policies to ensure secure and functional permissions** – IAM Access Analyzer validates new and existing policies so that the policies adhere to the IAM policy language (JSON) and IAM best practices. IAM Access Analyzer provides more than 100 policy checks and actionable recommendations to help you author secure and functional policies. For more information, see [Validate policies with IAM Access Analyzer](#) in the *IAM User Guide*.
- **Require multi-factor authentication (MFA)** – If you have a scenario that requires IAM users or a root user in your AWS account, turn on MFA for additional security. To require MFA when API operations are called, add MFA conditions to your policies. For more information, see [Secure API access with MFA](#) in the *IAM User Guide*.

For more information about best practices in IAM, see [Security best practices in IAM](#) in the *IAM User Guide*.

CloudTrail doesn't have service-specific context keys that you can use in the `Condition` element of policy statements.

Example: Allowing and denying actions for a specified trail

The following example demonstrates a policy that allows users with the policy to view the status and configuration of a trail and start and stop logging for a trail named *My-First-Trail*. This trail was created in the US East (Ohio) Region (its home Region) in the AWS account with the ID *123456789012*.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "cloudtrail:StartLogging",
        "cloudtrail:StopLogging",
        "cloudtrail:GetTrail",
        "cloudtrail:GetTrailStatus",
        "cloudtrail:GetEventSelectors"
      ],
      "Resource": [
        "arn:aws:cloudtrail:us-east-2:123456789012:trail/My-First-Trail"
      ]
    }
  ]
}
```

The following example demonstrates a policy that explicitly denies CloudTrail actions for any trail not named *My-First-Trail*.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": [
        "cloudtrail:*"
      ],
      "NotResource": [
        "arn:aws:cloudtrail:us-east-2:123456789012:trail/My-First-Trail"
      ]
    }
  ]
}
```

Examples: Creating and applying policies for actions on specific trails

You can use permissions and policies to control a user's ability to perform specific actions on CloudTrail trails.

For example, you don't want users of your company's developer group to start or stop logging on a specific trail. However, you might want to grant them permission to perform the `DescribeTrails` and `GetTrailStatus` actions on the trail. You want the users of the developer group to perform the `StartLogging` or `StopLogging` actions on trails that they manage.

You can create two policy statements and attach them to the developer group you create in IAM. For more information about groups in IAM, see [IAM Groups](#) in the *IAM User Guide*.

In the first policy, you deny the `StartLogging` and `StopLogging` actions for the trail ARN that you specify. In the following example, the trail ARN is `arn:aws:cloudtrail:us-east-2:123456789012:trail/Example-Trail`.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "Stmt1446057698000",
      "Effect": "Deny",
      "Action": [
        "cloudtrail:StartLogging",
        "cloudtrail:StopLogging"
      ],
      "Resource": [
        "arn:aws:cloudtrail:us-east-2:123456789012:trail/Example-Trail"
      ]
    }
  ]
}
```

In the second policy, the `DescribeTrails` and `GetTrailStatus` actions are allowed on all CloudTrail resources:

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "Stmt1446072643000",
      "Effect": "Allow",
      "Action": [
        "cloudtrail:DescribeTrails",
        "cloudtrail:GetTrail",
        "cloudtrail:GetTrailStatus"
      ],
      "Resource": [
        "*"
      ]
    }
  ]
}
```

If a user of the developer group tries to start or stop logging on the trail that you specified in the first policy, that user gets an access denied exception. Users of the developer group can start and stop logging on trails that they create and manage.

The following examples show that the configured developer group in an AWS CLI profile named `devgroup`. First, a user of `devgroup` runs the `describe-trails` command.

```
$ aws --profile devgroup cloudtrail describe-trails
```

The command complete successfully with the following output:

```
{
  "trailList": [
    {
      "IncludeGlobalServiceEvents": true,
      "Name": "Default",
      "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/Example-Trail",
      "IsMultiRegionTrail": false,
      "S3BucketName": "amzn-s3-demo-bucket",

```

```
        "HomeRegion": "us-east-2"
      }
    ]
  }
}
```

The user then runs the `get-trail-status` command on the trail that you specified in the first policy.

```
$ aws --profile devgroup cloudtrail get-trail-status --name Example-Trail
```

The command complete successfully with the following output:

```
{
  "LatestDeliveryTime": 1449517556.256,
  "LatestDeliveryAttemptTime": "2015-12-07T19:45:56Z",
  "LatestNotificationAttemptSucceeded": "",
  "LatestDeliveryAttemptSucceeded": "2015-12-07T19:45:56Z",
  "IsLogging": true,
  "TimeLoggingStarted": "2015-12-07T19:36:27Z",
  "StartLoggingTime": 1449516987.685,
  "StopLoggingTime": 1449516977.332,
  "LatestNotificationAttemptTime": "",
  "TimeLoggingStopped": "2015-12-07T19:36:17Z"
}
```

Next, a user in the `devgroup` group runs the `stop-logging` command on the same trail.

```
$ aws --profile devgroup cloudtrail stop-logging --name Example-Trail
```

The command returns an access denied exception, such as the following:

```
A client error (AccessDeniedException) occurred when calling the StopLogging operation:
Unknown
```

The user runs the `start-logging` command on the same trail.

```
$ aws --profile devgroup cloudtrail start-logging --name Example-Trail
```

Again the command returns an access denied exception, such as the following:

A client error (AccessDeniedException) occurred when calling the StartLogging operation: Unknown

Examples: Denying access to create or delete event data stores based on tags

In the following policy example, permission to create an event data store with `CreateEventDataStore` is denied if at least one of the following conditions aren't met:

- The event data store doesn't have a tag key of `stage` applied to itself
- The value of the stage tag isn't `alpha`, `beta`, `gamma`, or `prod`.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Deny",
      "Action": "cloudtrail:CreateEventDataStore",
      "Resource": "*",
      "Condition": {
        "Null": {
          "aws:RequestTag/stage": "true"
        }
      }
    },
    {
      "Effect": "Deny",
      "Action": "cloudtrail:CreateEventDataStore",
      "Resource": "*",
      "Condition": {
        "ForAnyValue:StringNotEquals": {
          "aws:RequestTag/stage": [
            "alpha",
            "beta",
            "gamma",
            "prod"
          ]
        }
      }
    }
  ]
}
```

```
    }  
  ]  
}
```

In the following policy example, permission to delete an event data store with `DeleteEventDataStore` is denied if the event data store has a stage tag with a value of `prod`. A policy like this one can help protect an event data store from accidental deletion.

JSON

```
{  
  "Version": "2012-10-17",  
  "Statement": [  
    {  
      "Effect": "Deny",  
      "Action": "cloudtrail:DeleteEventDataStore",  
      "Resource": "*",  
      "Condition": {  
        "StringEquals": {  
          "aws:ResourceTag/stage": "prod"  
        }  
      }  
    }  
  ]  
}
```

Using the CloudTrail console

To access the AWS CloudTrail console, you must have a minimum set of permissions. These permissions must allow you to list and view details about the CloudTrail resources in your AWS account. If you create an identity-based policy that is more restrictive than the minimum required permissions, the console won't function as intended for entities (users or roles) with that policy.

You don't need to allow minimum console permissions for users that are making calls only to the AWS CLI or the AWS API. Instead, allow access to only the actions that match the API operation that they're trying to perform.

Granting permissions for CloudTrail administration

To allow IAM roles or users to administer a CloudTrail resource, such as a trail, event data store, or channel, you must grant explicit permissions to perform the actions associated with CloudTrail tasks. In most situations, you can use an AWS managed policy that contains predefined permissions.

Note

The permissions you grant to users to perform CloudTrail administration tasks aren't the same as the permissions that CloudTrail requires to deliver log files to Amazon S3 buckets or send notifications to Amazon SNS topics. For more information about those permissions, see [Amazon S3 bucket policy for CloudTrail](#).

If you configure integration with Amazon CloudWatch Logs, CloudTrail also requires a role that it can assume to deliver events to an Amazon CloudWatch Logs log group. You must create the role that CloudTrail uses. For more information, see [Granting permission to view and configure Amazon CloudWatch Logs information on the CloudTrail console](#) and [Sending events to CloudWatch Logs](#).

The following AWS managed policies are available for CloudTrail:

- [AWSCloudTrail_FullAccess](#) – This policy provides full access to CloudTrail actions on CloudTrail resources, such as trails, event data stores, and channels. This policy provides the required permissions to create, update, and delete CloudTrail trails, event data stores, and channels.

This policy also provides permissions to manage the Amazon S3 bucket, the log group for CloudWatch Logs, and an Amazon SNS topic for a trail. However, the `AWSCloudTrail_FullAccess` managed policy doesn't provide permissions to delete the Amazon S3 bucket, the log group for CloudWatch Logs, or an Amazon SNS topic. For information about managed policies for other AWS services, see the [AWS Managed Policy Reference Guide](#).

Note

The **`AWSCloudTrail_FullAccess`** policy isn't intended to be shared broadly across your AWS account. Users with this role can turn off or reconfigure the most sensitive and important auditing functions in their AWS accounts. For this reason, you must only apply

this policy to account administrators. You must closely control and monitor use of this policy.

- [AWSCloudTrail_ReadOnlyAccess](#) – This policy grants permissions to view the CloudTrail console, including recent events and event history. This policy also allows you to view existing trails, event data stores, and channels. Roles and users with this policy can [download the event history](#), but they can't create or update trails, event data stores, or channels.

To provide access, add permissions to your users, groups, or roles:

- Users and groups in AWS IAM Identity Center:

Create a permission set. Follow the instructions in [Create a permission set](#) in the *AWS IAM Identity Center User Guide*.

- Users managed in IAM through an identity provider:

Create a role for identity federation. Follow the instructions in [Create a role for a third-party identity provider \(federation\)](#) in the *IAM User Guide*.

- IAM users:
 - Create a role that your user can assume. Follow the instructions in [Create a role for an IAM user](#) in the *IAM User Guide*.
 - (Not recommended) Attach a policy directly to a user or add a user to a user group. Follow the instructions in [Adding permissions to a user \(console\)](#) in the *IAM User Guide*.

Additional resources

To learn more about using IAM to give identities, such as users and roles, access to resources in your account, see [Getting set up with IAM](#) and [Access management for AWS resources](#) in the *IAM User Guide*.

You don't need to allow minimum console permissions for users that are making calls only to the AWS CLI or the AWS API. Instead, allow access to only the actions that match the API operation that you're trying to perform.

Allow users to view their own permissions

This example shows how you might create a policy that allows IAM users to view the inline and managed policies that are attached to their user identity. This policy includes permissions to complete this action on the console or programmatically using the AWS CLI or AWS API.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "ViewOwnUserInfo",
      "Effect": "Allow",
      "Action": [
        "iam:GetUserPolicy",
        "iam:ListGroupsForUser",
        "iam:ListAttachedUserPolicies",
        "iam:ListUserPolicies",
        "iam:GetUser"
      ],
      "Resource": ["arn:aws:iam::*:user/${aws:username}"]
    },
    {
      "Sid": "NavigateInConsole",
      "Effect": "Allow",
      "Action": [
        "iam:GetGroupPolicy",
        "iam:GetPolicyVersion",
        "iam:GetPolicy",
        "iam:ListAttachedGroupPolicies",
        "iam:ListGroupPolicies",
        "iam:ListPolicyVersions",
        "iam:ListPolicies",
        "iam:ListUsers"
      ],
      "Resource": "*"
    }
  ]
}
```

Granting custom permissions for CloudTrail users

CloudTrail policies grant permissions to users who work with CloudTrail. If you need to grant different permissions to users, you can attach a CloudTrail policy to an IAM group or to a user. You

can edit the policy to include or exclude specific permissions. You can also create your own custom policy. Policies are JSON documents that define the actions a user is allowed to perform and the resources that the user is allowed to perform those actions on. For specific examples, see [Example: Allowing and denying actions for a specified trail](#) and [Examples: Creating and applying policies for actions on specific trails](#).

Contents

- [Read-only access](#)
- [Full access](#)
- [Granting permission to view AWS Config information on the CloudTrail console](#)
- [Granting permission to view and configure Amazon CloudWatch Logs information on the CloudTrail console](#)
- [Additional information](#)

Read-only access

The following example shows a policy that grants read-only access to CloudTrail trails. This is equivalent to the managed policy **AWSCloudTrail_ReadOnlyAccess**. It grants users permission to see trail information, but not to create or update trails.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "cloudtrail:Get*",
        "cloudtrail:Describe*",
        "cloudtrail:List*",
        "cloudtrail:LookupEvents"
      ],
      "Resource": "*"
    }
  ]
}
```

In the policy statements, the **Effect** element specifies whether the actions are allowed or denied. The **Action** element lists the specific actions that the user is allowed to perform. The **Resource** element lists the AWS resources the user is allowed to perform those actions on. For policies that control access to CloudTrail actions, the **Resource** element is usually set to `*`, a wildcard that means "all resources."

The values in the **Action** element correspond to the APIs that the services support. The actions are preceded by `cloudtrail:` to indicate that they refer to CloudTrail actions. You can use the `*` wildcard character in the **Action** element, such as in the following examples:

- **"Action":** `["cloudtrail:*Logging"]`

This allows all CloudTrail actions that end with "Logging" (`StartLogging`, `StopLogging`).

- **"Action":** `["cloudtrail:*"]`

This allows all CloudTrail actions, but not actions for other AWS services.

- **"Action":** `["*"]`

This allows all AWS actions. This permission is suitable for a user who acts as an AWS administrator for your account.

The read-only policy doesn't grant user permission for the `CreateTrail`, `UpdateTrail`, `StartLogging`, and `StopLogging` actions. Users with this policy are not allowed to create trails, update trails, or turn logging on and off. For the list of CloudTrail actions, see the [AWS CloudTrail API Reference](#).

Full access

The following example shows a policy that grants full access to CloudTrail. This is equivalent to the managed policy **AWSCloudTrail_FullAccess**. It grants users the permission to perform all CloudTrail actions. It also lets users log data events in Amazon S3 and AWS Lambda, manage files in Amazon S3 buckets, manage how CloudWatch Logs monitors CloudTrail log events, and manage Amazon SNS topics in the account that the user is associated with.

Important

The **AWSCloudTrail_FullAccess** policy or equivalent permissions are not intended to be shared broadly across your AWS account. Users with this role or equivalent access have the ability to disable or reconfigure the most sensitive and important auditing functions in their

AWS accounts. For this reason, this policy should be applied only to account administrators, and use of this policy should be closely controlled and monitored.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "sns:AddPermission",
        "sns:CreateTopic",
        "sns:SetTopicAttributes",
        "sns:GetTopicAttributes"
      ],
      "Resource": [
        "arn:aws:sns:*:*:aws-cloudtrail-logs*"
      ]
    },
    {
      "Effect": "Allow",
      "Action": [
        "sns:ListTopics"
      ],
      "Resource": "*"
    },
    {
      "Effect": "Allow",
      "Action": [
        "s3:CreateBucket",
        "s3:PutBucketPolicy"
      ],
      "Resource": [
        "arn:aws:s3:::amzn-s3-demo-logging-bucket1*"
      ]
    },
    {
      "Effect": "Allow",
      "Action": [
        "s3:ListAllMyBuckets",
```

```

        "s3:GetBucketLocation",
        "s3:GetBucketPolicy"
    ],
    "Resource": "*"
},
{
    "Effect": "Allow",
    "Action": "cloudtrail:*",
    "Resource": "*"
},
{
    "Effect": "Allow",
    "Action": [
        "logs:CreateLogGroup"
    ],
    "Resource": [
        "arn:aws:logs:*:*:log-group:aws-cloudtrail-logs*"
    ]
},
{
    "Effect": "Allow",
    "Action": [
        "iam:ListRoles",
        "iam:GetRolePolicy",
        "iam:GetUser"
    ],
    "Resource": "*"
},
{
    "Effect": "Allow",
    "Action": [
        "iam:PassRole"
    ],
    "Resource": "*",
    "Condition": {
        "StringEquals": {
            "iam:PassedToService": "cloudtrail.amazonaws.com"
        }
    }
},
{
    "Effect": "Allow",
    "Action": [
        "kms:CreateKey",

```

```

        "kms:CreateAlias",
        "kms:ListKeys",
        "kms:ListAliases"
    ],
    "Resource": "*"
},
{
    "Effect": "Allow",
    "Action": [
        "lambda:ListFunctions"
    ],
    "Resource": "*"
},
{
    "Effect": "Allow",
    "Action": [
        "dynamodb:ListGlobalTables",
        "dynamodb:ListTables"
    ],
    "Resource": "*"
}
]
}

```

Granting permission to view AWS Config information on the CloudTrail console

You can view event information on the CloudTrail console, including resources that are related to that event. For these resources, you can choose the AWS Config icon to view the timeline for that resource in the AWS Config console. Attach this policy to your users to grant them read-only AWS Config access. The policy doesn't grant them permission to change settings in AWS Config.

JSON

```

{
    "Version": "2012-10-17",
    "Statement": [{
        "Effect": "Allow",
        "Action": [
            "config:Get*",
            "config:Describe*",
            "config:List*"

```

```
    ],
    "Resource": "*"
  }]
}
```

For more information, see [Viewing resources referenced with AWS Config](#).

Granting permission to view and configure Amazon CloudWatch Logs information on the CloudTrail console

You can view and configure delivery of events to CloudWatch Logs in the CloudTrail console if you have sufficient permissions. These are permissions that may be beyond those granted for CloudTrail administrators. Attach this policy to administrators who will configure and manage CloudTrail integration with CloudWatch Logs. The policy doesn't grant them permissions in CloudTrail or in CloudWatch Logs directly, but instead grants the permissions required to create and configure the role CloudTrail will assume to successfully deliver events to your CloudWatch Logs group.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Effect": "Allow",
    "Action": [
      "iam:CreateRole",
      "iam:PutRolePolicy",
      "iam:AttachRolePolicy",
      "iam:ListRoles",
      "iam:GetRolePolicy",
      "iam:GetUser"
    ],
    "Resource": "*"
  }]
}
```

For more information, see [Monitoring CloudTrail Log Files with Amazon CloudWatch Logs](#).

Additional information

To learn more about using IAM to give identities, such as users and roles, access to resources in your account, see [Getting started](#) and [Access management for AWS resources](#) in the *IAM User Guide*.

AWS CloudTrail resource-based policy examples

This section provides example resource-based policies for CloudTrail Lake dashboards, event data stores, and channels.

CloudTrail supports the following types of resource-based policies:

- Resource-based policies on channels used for CloudTrail Lake integrations with event sources outside of AWS. The resource-based policy for the channel defines which principal entities (accounts, users, roles, and federated users) can call `PutAuditEvents` on the channel to deliver events to the destination event data store. For more information about creating integrations with CloudTrail Lake, see [Create an integration with an event source outside of AWS](#).
- Resource-based policies to control which principals can perform actions on your event data store. You can use resource-based policies to provide cross-account access to your event data stores.
- Resource-based policies on dashboards to allow CloudTrail to refresh a CloudTrail Lake dashboard at the interval you define when you set a refresh schedule for a dashboard. For more information, see [Set a refresh schedule for a custom dashboard with the CloudTrail console](#).

Examples:

- [Resource-based policy examples for channels](#)
- [Resource-based policy examples for event data stores](#)
- [Resource-based policy example for a dashboard](#)

Resource-based policy examples for channels

The resource-based policy for the channel defines which principal entities (accounts, users, roles, and federated users) can call `PutAuditEvents` on the channel to deliver events to the destination event data store.

The information required for the policy is determined by the integration type.

- For a direction integration, CloudTrail requires the policy to contain the partner's AWS account IDs, and requires you to enter the unique external ID provided by the partner. CloudTrail automatically adds the partner's AWS account IDs to the resource policy when you create an integration using the CloudTrail console. Refer to the [partner's documentation](#) to learn how to get the AWS account numbers required for the policy.
- For a solution integration, you must specify at least one AWS account ID as principal, and can optionally enter an external ID to prevent against confused deputy.

The following are requirements for the resource-based policy:

- The policy contains at least one statement. The policy can have a maximum of 20 statements.
- Each statement contains at least one principal. A principal is an account, user, role, or federated user. A statement can have a maximum of 50 principals.
- The resource ARN defined in the policy must match the channel ARN the policy is attached to.
- The policy contains only one action: `cloudtrail:data:PutAuditEvents`

The channel owner can call the `PutAuditEvents` API on the channel unless the policy denies the owner access to the resource.

Topics

- [Example: Providing channel access to principals](#)
- [Example: Using an external ID to prevent against confused deputy](#)

Example: Providing channel access to principals

The following example grants permissions to the principals with the ARNs `arn:aws:iam::111122223333:root`, `arn:aws:iam::444455556666:root`, and `arn:aws:iam::123456789012:root` to call the [PutAuditEvents](#) API on the CloudTrail channel with the ARN `arn:aws:cloudtrail:us-east-1:777788889999:channel/EXAMPLE-80b5-40a7-ae65-6e099392355b`.

JSON

```
{  
  "Version": "2012-10-17",
```

```

    "Statement":
    [
      {
        "Sid": "ChannelPolicy",
        "Effect": "Allow",
        "Principal":
        {
          "AWS":
          [
            "arn:aws:iam::111122223333:root",
            "arn:aws:iam::444455556666:root",
            "arn:aws:iam::123456789012:root"
          ]
        },
        "Action": "cloudtrail-data:PutAuditEvents",
        "Resource": "arn:aws:cloudtrail:us-east-1:777788889999:channel/
EXAMPLE-80b5-40a7-ae65-6e099392355b"
      }
    ]
  }
}

```

Example: Using an external ID to prevent against confused deputy

The following example uses an external ID to address and prevent against [confused deputy](#). The confused deputy problem is a security issue where an entity that doesn't have permission to perform an action can coerce a more-privileged entity to perform the action.

The integration partner creates the external ID to use in the policy. Then, it provides the external ID to you as part of creating the integration. The value can be any unique string, such as a passphrase or account number.

The example grants permissions to the principals with the ARNs `arn:aws:iam::111122223333:root`, `arn:aws:iam::444455556666:root`, and `arn:aws:iam::123456789012:root` to call the [PutAuditEvents](#) API on the CloudTrail channel resource if the call to the PutAuditEvents API includes the external ID value defined in the policy.

JSON

```
{
```

```
"Version": "2012-10-17",
"Statement":
[
  {
    "Sid": "ChannelPolicy",
    "Effect": "Allow",
    "Principal":
    {
      "AWS":
      [
        "arn:aws:iam::111122223333:root",
        "arn:aws:iam::444455556666:root",
        "arn:aws:iam::123456789012:root"
      ]
    },
    "Action": "cloudtrail-data:PutAuditEvents",
    "Resource": "arn:aws:cloudtrail:us-east-1:777788889999:channel/
EXAMPLE-80b5-40a7-ae65-6e099392355b"
  }
]
```

Resource-based policy examples for event data stores

Resource-based policies allow you to control which principals can perform actions on your event data store.

You can use resource-based policies to provide cross-account access to allow selected principals to query your event data store, list and cancel queries, and view query results.

For CloudTrail Lake dashboard, resource-based policies are used to allow CloudTrail to run queries on your event data stores to populate the data for the dashboard's widgets when the dashboard is refreshed. CloudTrail Lake gives you the option to attach a default resource-based policy to your event data stores when you [create a custom dashboard](#) or [enable the Highlights dashboard](#) on the CloudTrail console.

The following actions are supported in resource-based policies for event data stores:

- `cloudtrail:StartQuery`
- `cloudtrail:CancelQuery`
- `cloudtrail:ListQueries`

- `cloudtrail:DescribeQuery`
- `cloudtrail:GetQueryResults`
- `cloudtrail:GenerateQuery`
- `cloudtrail:GenerateQueryResultsSummary`
- `cloudtrail:GetEventDataStore`

When you [create](#) or [update](#) an event data store, or manage dashboards on the CloudTrail console, you're given the option to add a resource-based policy to your event data store. You can also run the [put-resource-policy](#) command to attach a resource-based policy to an event data store.

A resource-based policy consists of one or more statements. For example, it can include one statement that allows CloudTrail to query the event data store for a dashboard and another statement that allows cross-account access to query the event data store. You can [update](#) an existing event data store's resource-based policy from the event data store's details page on the CloudTrail console.

For [organization event data stores](#), CloudTrail creates a [default resource-based policy](#) that lists the actions that the delegated administrator accounts are allowed to perform on organization event data stores. The permissions in this policy are derived from the delegated administrator permissions in AWS Organizations. This policy is updated automatically following changes to the organization event data store or to the organization (for example, a CloudTrail delegated administrator account is registered or removed).

Examples:

- [Example: Allow CloudTrail to run queries to refresh a dashboard](#)
- [Example: Allow other accounts to query an event data store and view query results](#)

Example: Allow CloudTrail to run queries to refresh a dashboard

To populate the data on a CloudTrail Lake dashboard during a refresh, you need to allow CloudTrail to run queries on your behalf. To do this, attach a resource-based policy to each event data store associated with a dashboard widget that includes a statement that allows CloudTrail to perform the `StartQuery` operation to populate the data for the widget.

The following are the requirements for the statement:

- The only Principal is `cloudtrail.amazonaws.com`.

- The only Action allowed is `cloudtrail:StartQuery`.
- The Condition only includes the dashboard ARN(s) and AWS account ID. For `AWS:SourceArn`, you can provide an array of dashboard ARNs.

The following example policy includes a statement that allows CloudTrail to run queries on an event data store for two custom dashboards named `example-dashboard1` and `example-dashboard2` and the Highlights dashboard named `AWSCloudTrail-Highlights` for account `123456789012`.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Principal": {
        "Service": "cloudtrail.amazonaws.com"
      },
      "Action": [
        "cloudtrail:StartQuery"
      ],
      "Resource": "arn:aws:cloudtrail:us-east-1:123456789012:dashboard/*",
      "Condition": {
        "StringLike": {
          "AWS:SourceArn": [
            "arn:aws:cloudtrail:us-east-1:123456789012:dashboard/example-dashboard1",
            "arn:aws:cloudtrail:us-east-1:123456789012:dashboard/example-dashboard2",
            "arn:aws:cloudtrail:us-east-1:123456789012:dashboard/AWSCloudTrail-Highlights"
          ],
          "AWS:SourceAccount": "123456789012"
        }
      }
    }
  ]
}
```

```
}
```

Example: Allow other accounts to query an event data store and view query results

You can use resource-based policies to provide cross-account access to your event data stores to allow other accounts to run queries on your event data stores.

The following example policy includes a statement that allows root users in accounts 111122223333, 777777777777, 999999999999, and 111111111111 to run queries and get query results on the event data store owned by account ID 555555555555.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "policy1",
      "Effect": "Allow",
      "Principal": {
        "AWS": [
          "arn:aws:iam::111122223333:root",
          "arn:aws:iam::777777777777:root",
          "arn:aws:iam::999999999999:root",
          "arn:aws:iam::111111111111:root"
        ]
      },
      "Action": [
        "cloudtrail:StartQuery",
        "cloudtrail:GetEventDataStore",
        "cloudtrail:GetQueryResults"
      ],
      "Resource": "arn:aws:cloudtrail:us-east-1:555555555555:eventdatastore/example80-699f-4045-a7d2-730dbf313ccf"
    }
  ]
}
```

Resource-based policy example for a dashboard

You can set a refresh schedule for a CloudTrail Lake dashboard, which allows CloudTrail to refresh the dashboard on your behalf at the interval you define when you set the refresh schedule. To do this, you need to attach a resource-based policy to the dashboard to allow CloudTrail to perform the `StartDashboardRefresh` operation on your dashboard.

The following are requirements for the resource-based policy:

- The only Principal is `cloudtrail.amazonaws.com`.
- The only Action allowed in the policy is `cloudtrail:StartDashboardRefresh`.
- The Condition only includes the dashboard ARN and AWS account ID.

The following example policy allows CloudTrail to refresh a dashboard named `exampleDash` for account `123456789012`.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Principal": {
        "Service": "cloudtrail.amazonaws.com"
      },
      "Action": [
        "cloudtrail:StartDashboardRefresh"
      ],
      "Resource": "arn:aws:cloudtrail:us-east-1:123456789012:dashboard/*",
      "Condition": {
        "StringEquals": {
          "AWS:SourceArn": "arn:aws:cloudtrail:us-east-1:123456789012:dashboard/exampleDash",
          "AWS:SourceAccount": "123456789012"
        }
      }
    }
  ]
}
```



```
}  
]  
}
```

Amazon S3 bucket policy for CloudTrail

By default, Amazon S3 buckets and objects are private. Only the resource owner (the AWS account that created the bucket) can access the bucket and objects it contains. The resource owner can grant access permissions to other resources and users by writing an access policy.

To create or modify an Amazon S3 bucket to receive log files for an organization trail, you must change the bucket policy. For more information, see [Creating a trail for an organization with the AWS CLI](#).

To deliver log files to an S3 bucket, CloudTrail must have the required permissions, and it cannot be configured as a [Requester Pays](#) bucket.

CloudTrail adds the following fields in the policy for you:

- The allowed SIDs
- The bucket name
- The service principal name for CloudTrail
- The name of the folder where the log files are stored, including the bucket name, a prefix (if you specified one), and your AWS account ID

As a security best practice, add an `aws:SourceArn` condition key to the Amazon S3 bucket policy. The IAM global condition key `aws:SourceArn` helps ensure that CloudTrail writes to the S3 bucket only for a specific trail or trails. The value of `aws:SourceArn` is always the ARN of the trail (or array of trail ARNs) that is using the bucket to store logs. Be sure to add the `aws:SourceArn` condition key to S3 bucket policies for existing trails.

Note

If you misconfigure your trail (for example, the S3 bucket is unreachable), CloudTrail will attempt to redeliver the log files to your S3 bucket for 30 days, and these attempted-to-deliver events will be subject to standard CloudTrail charges. To avoid charges on a misconfigured trail, you need to delete the trail.

The following policy allows CloudTrail to write log files to the bucket from supported AWS Regions. Replace *amzn-s3-demo-bucket*, *[optionalPrefix]/*, *myAccountID*, *region*, and *trailName* with the appropriate values for your configuration.

S3 bucket policy

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "AWSCloudTrailAclCheck20150319",
      "Effect": "Allow",
      "Principal": {"Service": "cloudtrail.amazonaws.com"},
      "Action": "s3:GetBucketAcl",
      "Resource": "arn:aws:s3:::amzn-s3-demo-bucket",
      "Condition": {
        "StringEquals": {
          "aws:SourceArn":
            "arn:aws:cloudtrail:region:myAccountID:trail/trailName"
        }
      }
    },
    {
      "Sid": "AWSCloudTrailWrite20150319",
      "Effect": "Allow",
      "Principal": {"Service": "cloudtrail.amazonaws.com"},
      "Action": "s3:PutObject",
      "Resource": "arn:aws:s3:::amzn-s3-demo-bucket/[optionalPrefix]/AWSLogs/myAccountID/*",
      "Condition": {
        "StringEquals": {
          "s3:x-amz-acl": "bucket-owner-full-control",
          "aws:SourceArn":
            "arn:aws:cloudtrail:region:myAccountID:trail/trailName"
        }
      }
    }
  ]
}
```

For more information about AWS Regions, see [CloudTrail supported Regions](#).

Contents

- [Specifying an existing bucket for CloudTrail log delivery](#)
- [Receiving log files from other accounts](#)
- [Create or update an Amazon S3 bucket to use to store the log files for an organization trail](#)
- [Troubleshooting the Amazon S3 bucket policy](#)
 - [Common Amazon S3 policy configuration errors](#)
 - [Changing a prefix for an existing bucket](#)
- [Additional resources](#)

Specifying an existing bucket for CloudTrail log delivery

If you specified an existing S3 bucket as the storage location for log file delivery, you must attach a policy to the bucket that allows CloudTrail to write to the bucket.

Note

As a best practice, use a dedicated S3 bucket for CloudTrail logs.

To add the required CloudTrail policy to an Amazon S3 bucket

1. Open the Amazon S3 console at <https://console.aws.amazon.com/s3/>.
2. Choose the bucket where you want CloudTrail to deliver your log files, and then choose **Permissions**.
3. Choose **Edit**.
4. Copy the [S3 bucket policy](#) to the **Bucket Policy Editor** window. Replace the placeholders in italics with the names of your bucket, prefix, and account number. If you specified a prefix when you created your trail, include it here. The prefix is an optional addition to the S3 object key that creates a folder-like organization in your bucket.

Note

If the existing bucket already has one or more policies attached, add the statements for CloudTrail access to that policy or policies. Evaluate the resulting set of permissions to be sure that they are appropriate for the users who will access the bucket.

Receiving log files from other accounts

You can configure CloudTrail to deliver log files from multiple AWS accounts to a single S3 bucket. For more information, see [Receiving CloudTrail log files from multiple accounts](#).

Create or update an Amazon S3 bucket to use to store the log files for an organization trail

You must specify an Amazon S3 bucket to receive the log files for an organization trail. This bucket must have a policy that allows CloudTrail to put the log files for the organization into the bucket.

The following is an example policy for an Amazon S3 bucket named *amzn-s3-demo-bucket*, which is owned by the organization's management account. Replace *amzn-s3-demo-bucket*, *region*, *managementAccountID*, *trailName*, and *o-organizationID* with the values for your organization

This bucket policy contains three statements.

- The first statement allows CloudTrail to call the Amazon S3 `GetBucketAcl` action on the Amazon S3 bucket.
- The second statement allows logging in the event the trail is changed from an organization trail to a trail for that account only.
- The third statement allows logging for an organization trail.

The example policy includes an `aws:SourceArn` condition key for the Amazon S3 bucket policy. The IAM global condition key `aws:SourceArn` helps ensure that CloudTrail writes to the S3 bucket only for a specific trail or trails. In an organization trail, the value of `aws:SourceArn` must be a trail ARN that is owned by the management account, and uses the management account ID.

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "AWSCloudTrailAclCheck20150319",
      "Effect": "Allow",
      "Principal": {
        "Service": [
          "cloudtrail.amazonaws.com"
        ]
      },
      "Action": "s3:GetBucketAcl",
      "Resource": "arn:aws:s3:::amzn-s3-demo-bucket",
      "Condition": {
        "StringEquals": {
          "aws:SourceArn":
            "arn:aws:cloudtrail:region:managementAccountID:trail/trailName"
        }
      }
    },
    {
      "Sid": "AWSCloudTrailWrite20150319",
      "Effect": "Allow",
      "Principal": {
        "Service": [
          "cloudtrail.amazonaws.com"
        ]
      },
      "Action": "s3:PutObject",
      "Resource": "arn:aws:s3:::amzn-s3-demo-bucket/
AWSLogs/managementAccountID/*",
      "Condition": {
        "StringEquals": {
          "s3:x-amz-acl": "bucket-owner-full-control",
          "aws:SourceArn":
            "arn:aws:cloudtrail:region:managementAccountID:trail/trailName"
        }
      }
    },
    {
      "Sid": "AWSCloudTrailOrganizationWrite20150319",
```

```

        "Effect": "Allow",
        "Principal": {
            "Service": [
                "cloudtrail.amazonaws.com"
            ]
        },
        "Action": "s3:PutObject",
        "Resource": "arn:aws:s3:::amzn-s3-demo-bucket/AWSLogs/o-
organizationID/*",
        "Condition": {
            "StringEquals": {
                "s3:x-amz-acl": "bucket-owner-full-control",
                "aws:SourceArn":
                    "arn:aws:cloudtrail:region:managementAccountID:trail/trailName"
            }
        }
    }
}

```

This example policy does not allow any users from member accounts to access the log files created for the organization. By default, organization log files are accessible only to the management account. For information about how to allow read access to the Amazon S3 bucket for IAM users in member accounts, see [Sharing CloudTrail log files between AWS accounts](#).

Troubleshooting the Amazon S3 bucket policy

The following sections describe how to troubleshoot the S3 bucket policy.

Note

If you misconfigure your trail (for example, the S3 bucket is unreachable), CloudTrail will attempt to redeliver the log files to your S3 bucket for 30 days, and these attempted-to-deliver events will be subject to standard CloudTrail charges. To avoid charges on a misconfigured trail, you need to delete the trail.

Common Amazon S3 policy configuration errors

When you create a new bucket as part of creating or updating a trail, CloudTrail attaches the required permissions to your bucket. The bucket policy uses the service principal name, "cloudtrail.amazonaws.com", which allows CloudTrail to deliver logs for all Regions.

If CloudTrail is not delivering logs for a Region, it's possible that your bucket has an older policy that specifies CloudTrail account IDs for each Region. This policy gives CloudTrail permission to deliver logs only for the Regions specified.

As a best practice, update the policy to use a permission with the CloudTrail service principal. To do this, replace the account ID ARNs with the service principal name: "cloudtrail.amazonaws.com". This gives CloudTrail permission to deliver logs for current and new Regions. As a security best practice, add an `aws:SourceArn` or `aws:SourceAccount` condition key to the Amazon S3 bucket policy. This helps prevent unauthorized account access to your S3 bucket. If you have existing trails, be sure to add one or more condition keys. The following example shows a recommended policy configuration. Replace *amzn-s3-demo-bucket*, *[optionalPrefix]/*, *myAccountID*, *region*, and *trailName* with the appropriate values for your configuration.

Example Example bucket policy with service principal name

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "AWSCloudTrailAclCheck20150319",
      "Effect": "Allow",
      "Principal": {"Service": "cloudtrail.amazonaws.com"},
      "Action": "s3:GetBucketAcl",
      "Resource": "arn:aws:s3:::amzn-s3-demo-bucket",
      "Condition": {
        "StringEquals": {
          "aws:SourceArn":
            "arn:aws:cloudtrail:region:myAccountID:trail/trailName"
        }
      }
    },
    {
```

```

        "Sid": "AWSCloudTrailWrite20150319",
        "Effect": "Allow",
        "Principal": {"Service": "cloudtrail.amazonaws.com"},
        "Action": "s3:PutObject",
        "Resource": "arn:aws:s3:::amzn-s3-demo-
bucket/[optionalPrefix]/AWSLogs/myAccountID/*",
        "Condition": {"StringEquals": {
            "s3:x-amz-acl": "bucket-owner-full-control",
            "aws:SourceArn":
"arn:aws:cloudtrail:region:myAccountID:trail/trailName"
        }}
    }
}

```

Changing a prefix for an existing bucket

If you try to add, modify, or remove a log file prefix for an S3 bucket that receives logs from a trail, you might see the error: **There is a problem with the bucket policy**. A bucket policy with an incorrect prefix can prevent your trail from delivering logs to the bucket. To resolve this issue, use the Amazon S3 console to update the prefix in the bucket policy, and then use the CloudTrail console to specify the same prefix for the bucket in the trail.

To update the log file prefix for an Amazon S3 bucket

1. Open the Amazon S3 console at <https://console.aws.amazon.com/s3/>.
2. Choose the bucket for which you want to modify the prefix, and then choose **Permissions**.
3. Choose **Edit**.
4. In the bucket policy, under the `s3:PutObject` action, edit the Resource entry to add, modify, or remove the log file *prefix* as needed.

```

"Action": "s3:PutObject",
  "Resource": "arn:aws:s3:::amzn-s3-demo-bucket/prefix/AWSLogs/myAccountID/*",

```

5. Choose **Save**.
6. Open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
7. Choose your trail and for **Storage location**, click the pencil icon to edit the settings for your bucket.

8. For **S3 bucket**, choose the bucket with the prefix you are changing.
9. For **Log file prefix**, update the prefix to match the prefix that you entered in the bucket policy.
10. Choose **Save**.

Additional resources

For more information about S3 buckets and policies, see [Using bucket policies](#) in the *Amazon Simple Storage Service User Guide*.

Amazon S3 bucket policy for CloudTrail Lake query results

By default, Amazon S3 buckets and objects are private. Only the resource owner (the AWS account that created the bucket) can access the bucket and objects it contains. The resource owner can grant access permissions to other resources and users by writing an access policy.

To deliver CloudTrail Lake query results to an S3 bucket, CloudTrail must have the required permissions, and it cannot be configured as a [Requester Pays](#) bucket.

CloudTrail adds the following fields in the policy for you:

- The allowed SIDs
- The bucket name
- The service principal name for CloudTrail

As a security best practice, add an `aws:SourceArn` condition key to the Amazon S3 bucket policy. The IAM global condition key `aws:SourceArn` helps ensure that CloudTrail writes to the S3 bucket only for the event data store.

The following policy allows CloudTrail to deliver query results to the bucket from supported AWS Regions. Replace *amzn-s3-demo-bucket*, *myAccountID*, and *myQueryRunningRegion* with the appropriate values for your configuration. The *myAccountID* is the AWS account ID used for CloudTrail, which may not be the same as the AWS account ID for the S3 bucket.

Note

If your bucket policy includes a statement for a KMS key, we recommend using a fully qualified KMS key ARN. If you use a KMS key alias instead, AWS KMS resolves the key within

the requester's account. This behavior can result in data that's encrypted with a KMS key that belongs to the requester, and not the bucket owner.

If this is an organization event data store, the event data store ARN must include the AWS account ID for the management account. This is because the management account maintains ownership of all organization resources.

S3 bucket policy

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "AWSCloudTrailLake1",
      "Effect": "Allow",
      "Principal": {"Service": "cloudtrail.amazonaws.com"},
      "Action": [
        "s3:PutObject*",
        "s3:Abort*"
      ],
      "Resource": [
        "arn:aws:s3:::amzn-s3-demo-bucket",
        "arn:aws:s3:::amzn-s3-demo-bucket/*"
      ],
      "Condition": {
        "StringEquals": {
          "aws:sourceAccount": "111111111111"
        },
        "ArnLike": {
          "aws:sourceArn": "arn:aws:cloudtrail:us-
east-1:111111111111:eventdatastore/*"
        }
      }
    },
    {
      "Sid": "AWSCloudTrailLake2",
      "Effect": "Allow",
      "Principal": {"Service": "cloudtrail.amazonaws.com"},
      "Action": "s3:GetBucketAcl",
```

```
    "Resource": "arn:aws:s3:::amzn-s3-demo-bucket",
    "Condition": {
      "StringEquals": {
        "aws:sourceAccount": "111111111111"
      },
      "ArnLike": {
        "aws:sourceArn": "arn:aws:cloudtrail:us-east-1:111111111111:eventdatastore/*"
      }
    }
  }
]
```

Contents

- [Specifying an existing bucket for CloudTrail Lake query results](#)
- [Additional resources](#)

Specifying an existing bucket for CloudTrail Lake query results

If you specified an existing S3 bucket as the storage location for CloudTrail Lake query results delivery, you must attach a policy to the bucket that allows CloudTrail to deliver the query results to the bucket.

Note

As a best practice, use a dedicated S3 bucket for CloudTrail Lake query results.

To add the required CloudTrail policy to an Amazon S3 bucket

1. Open the Amazon S3 console at <https://console.aws.amazon.com/s3/>.
2. Choose the bucket where you want CloudTrail to deliver your Lake query results, and then choose **Permissions**.
3. Choose **Edit**.
4. Copy the [S3 bucket policy for query results](#) to the **Bucket Policy Editor** window. Replace the placeholders in italics with the names of your bucket, Region, and account ID.

Note

If the existing bucket already has one or more policies attached, add the statements for CloudTrail access to that policy or policies. Evaluate the resulting set of permissions to be sure that they are appropriate for the users who access the bucket.

Additional resources

For more information about S3 buckets and policies, see [Using bucket policies](#) in the *Amazon Simple Storage Service User Guide*.

Amazon SNS topic policy for CloudTrail

To send notifications to an SNS topic, CloudTrail must have the required permissions. CloudTrail automatically attaches the required permissions to the topic when you create an Amazon SNS topic as part of creating or updating a trail in the CloudTrail console.

Important

As a security best practice, to restrict access to your SNS topic, we strongly recommend that after you create or update a trail to send SNS notifications, you manually edit the IAM policy that is attached to the SNS topic to add condition keys. For more information, see [the section called “Security best practice for SNS topic policy”](#) in this topic.

CloudTrail adds the following statement to the policy for you with the following fields:

- The allowed SIDs.
- The service principal name for CloudTrail.
- The SNS topic, including Region, account ID, and topic name.

The following policy allows CloudTrail to send notifications about log file delivery from supported Regions. For more information, see [CloudTrail supported Regions](#). This is the default policy that is attached to a new or existing SNS topic policy when you create or update a trail, and choose to enable SNS notifications.

SNS topic policy

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "AWSCloudTrailSNSPolicy20131101",
      "Effect": "Allow",
      "Principal": {
        "Service": "cloudtrail.amazonaws.com"
      },
      "Action": "SNS:Publish",
      "Resource": "arn:aws:sns:us-east-1:111111111111:SNSTopicName"
    }
  ]
}
```

To use an AWS KMS-encrypted Amazon SNS topic to send notifications, you must also enable compatibility between the event source (CloudTrail) and the encrypted topic by adding the following statement to the policy of the AWS KMS key.

KMS key policy

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Principal": {
        "Service": "cloudtrail.amazonaws.com"
      },
      "Action": [
        "kms:GenerateDataKey*",
        "kms:Decrypt"
      ],
      "Resource": "*"
    }
  ]
}
```

```
}  
  ]  
}
```

For more information, see [Enable Compatibility between Event Sources from AWS Services and Encrypted Topics](#).

Contents

- [Security best practice for SNS topic policy](#)
- [Specifying an existing topic for sending notifications](#)
- [Troubleshooting the SNS topic policy](#)
 - [CloudTrail is not sending notifications for a Region](#)
 - [CloudTrail is not sending notifications for a member account in an organization](#)
- [Additional resources](#)

Security best practice for SNS topic policy

By default, the IAM policy statement that CloudTrail attaches to your Amazon SNS topic allows the CloudTrail service principal to publish to an SNS topic, identified by an ARN. To help prevent an attacker from gaining access to your SNS topic, and sending notifications on behalf of CloudTrail to topic recipients, manually edit your CloudTrail SNS topic policy to add an `aws:SourceArn` condition key to the policy statement attached by CloudTrail. The value of this key is the ARN of the trail, or an array of trail ARNs that are using the SNS topic. Because it includes both the specific trail ID and the ID of the account that owns the trail, it restricts SNS topic access to only those accounts that have permission to manage the trail. Before you add condition keys to your SNS topic policy, get the SNS topic name from your trail's settings in the CloudTrail console.

The `aws:SourceAccount` condition key is also supported, but is not recommended.

To add the `aws:SourceArn` condition key to your SNS topic policy

1. Open the Amazon SNS console at <https://console.aws.amazon.com/sns/v3/home>.
2. In the navigation pane, choose **Topics**.
3. Choose the SNS topic that is shown in your trail settings, and then choose **Edit**.
4. Expand **Access policy**.

5. In the **Access policy** JSON editor, look for a block that resembles the following example.

```
{
  "Sid": "AWSCloudTrailSNSPolicy20150319",
  "Effect": "Allow",
  "Principal": {
    "Service": "cloudtrail.amazonaws.com"
  },
  "Action": "SNS:Publish",
  "Resource": "arn:aws:sns:us-west-2:111122223333:aws-cloudtrail-logs-111122223333-61bbe496"
}
```

6. Add a new block for a condition, `aws:SourceArn`, as shown in the following example. The value of `aws:SourceArn` is the ARN of the trail about which you are sending notifications to SNS.

```
{
  "Sid": "AWSCloudTrailSNSPolicy20150319",
  "Effect": "Allow",
  "Principal": {
    "Service": "cloudtrail.amazonaws.com"
  },
  "Action": "SNS:Publish",
  "Resource": "arn:aws:sns:us-west-2:111122223333:aws-cloudtrail-logs-111122223333-61bbe496",
  "Condition": {
    "StringEquals": {
      "aws:SourceArn": "arn:aws:cloudtrail:us-west-2:123456789012:trail/Trail3"
    }
  }
}
```

7. When you are finished editing the SNS topic policy, choose **Save changes**.

To add the `aws:SourceAccount` condition key to your SNS topic policy

1. Open the Amazon SNS console at <https://console.aws.amazon.com/sns/v3/home>.
2. In the navigation pane, choose **Topics**.
3. Choose the SNS topic that is shown in your trail settings, and then choose **Edit**.
4. Expand **Access policy**.

5. In the **Access policy** JSON editor, look for a block that resembles the following example.

```
{
  "Sid": "AWSCloudTrailSNSPolicy20150319",
  "Effect": "Allow",
  "Principal": {
    "Service": "cloudtrail.amazonaws.com"
  },
  "Action": "SNS:Publish",
  "Resource": "arn:aws:sns:us-west-2:111122223333:aws-cloudtrail-logs-111122223333-61bbe496"
}
```

6. Add a new block for a condition, `aws:SourceAccount`, as shown in the following example. The value of `aws:SourceAccount` is the ID of the account that owns the CloudTrail trail. This example restricts access to the SNS topic to only those users who can sign in to the AWS account 123456789012.

```
{
  "Sid": "AWSCloudTrailSNSPolicy20150319",
  "Effect": "Allow",
  "Principal": {
    "Service": "cloudtrail.amazonaws.com"
  },
  "Action": "SNS:Publish",
  "Resource": "arn:aws:sns:us-west-2:111122223333:aws-cloudtrail-logs-111122223333-61bbe496",
  "Condition": {
    "StringEquals": {
      "aws:SourceAccount": "123456789012"
    }
  }
}
```

7. When you are finished editing the SNS topic policy, choose **Save changes**.

Specifying an existing topic for sending notifications

You can manually add the permissions for an Amazon SNS topic to your topic policy in the Amazon SNS console and then specify the topic in the CloudTrail console.

To manually update an SNS topic policy

1. Open the Amazon SNS console at <https://console.aws.amazon.com/sns/v3/home>.
2. Choose **Topics** and then choose the topic.
3. Choose **Edit** and then scroll down to **Access policy**.
4. Add the statement from [SNS topic policy](#) with the appropriate values for the Region, account ID, and topic name.
5. If your topic is an encrypted topic, you must allow CloudTrail to have `kms:GenerateDataKey*` and the `kms:Decrypt` permissions. For more information, see [Encrypted SNS topic KMS key policy](#).
6. Choose **Save changes**.
7. Return to the CloudTrail console and specify the topic for the trail.

Troubleshooting the SNS topic policy

The following sections describe how to troubleshoot the SNS topic policy.

Scenarios:

- [CloudTrail is not sending notifications for a Region](#)
- [CloudTrail is not sending notifications for a member account in an organization](#)

CloudTrail is not sending notifications for a Region

When you create a new topic as part of creating or updating a trail, CloudTrail attaches the required permissions to your topic. The topic policy uses the service principal name, `"cloudtrail.amazonaws.com"`, which allows CloudTrail to send notifications for all Regions.

If CloudTrail is not sending notifications for a Region, it's possible that your topic has an older policy that specifies CloudTrail account IDs for each Region. This type of policy gives CloudTrail permission to send notifications only for the Regions specified.

As a best practice, update the policy to use a permission with the CloudTrail service principal. To do this, replace the account ID ARNs with the service principal name: `"cloudtrail.amazonaws.com"`.

The following example policy gives CloudTrail permission to send notifications for current and new Regions:

Example topic policy with service principal name

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Sid": "AWSCloudTrailSNSPolicy20131101",
    "Effect": "Allow",
    "Principal": {"Service": "cloudtrail.amazonaws.com"},
    "Action": "SNS:Publish",
    "Resource": "arn:aws:sns:us-west-2:123456789012:myTopic"
  }]
}
```

Verify that the policy has the correct values:

- In the Resource field, specify the account number of the topic owner. For topics that you create, specify your account number.
- Specify the appropriate values for the Region and SNS topic name.

CloudTrail is not sending notifications for a member account in an organization

When a member account with an AWS Organizations organization trail is not sending Amazon SNS notifications, there could be an issue with the configuration of the SNS topic policy. CloudTrail creates organization trails in member accounts even if a resource validation fails, for example, the organization trail's SNS topic does not include all member account IDs. If the SNS topic policy is incorrect, an authorization failure occurs.

To check whether a trail's SNS topic policy has an authorization failure:

- From the CloudTrail console, check the trail's details page. If there's an authorization failure, the details page includes a warning `SNS authorization failed` and indicates to fix the SNS topic policy.
- From the AWS CLI, run the [get-trail-status](#) command. If there's an authorization failure, the command output includes the `LastNotificationError` field with a value of `AuthorizationError`.

Additional resources

For more information about SNS topics and subscribing to them, see the [Amazon Simple Notification Service Developer Guide](#).

Troubleshooting AWS CloudTrail identity and access

Use the following information to help you diagnose and fix common issues that you might encounter when working with CloudTrail and IAM.

Topics

- [I am not authorized to perform an action in CloudTrail](#)
- [I am not authorized to perform iam:PassRole](#)
- [I want to allow people outside of my AWS account to access my CloudTrail resources](#)
- [I am not authorized to perform iam:PassRole](#)
- [I am getting a NoManagementAccountSLRExistsException exception when I try to create an organization trail or event data store](#)

I am not authorized to perform an action in CloudTrail

If you receive an error that you're not authorized to perform an action, your policies must be updated to allow you to perform the action.

The following example error occurs when the mateojackson IAM user tries to use the console to view details about a fictional *my-example-widget* resource but doesn't have the fictional `cloudtrail:GetWidget` permissions.

```
User: arn:aws:iam::123456789012:user/mateojackson is not authorized to perform:
cloudtrail:GetWidget on resource: my-example-widget
```

In this case, the policy for the mateojackson user must be updated to allow access to the *my-example-widget* resource by using the `cloudtrail:GetWidget` action.

If you need help, contact your AWS administrator. Your administrator is the person who provided you with your sign-in credentials.

If the AWS Management Console tells you that you're not authorized to perform an action, then you must contact your administrator for assistance. Your administrator is the person that provided you with your sign-in credentials.

The following example error occurs when the `mateojackson` IAM user tries to use the console to view details about a trail but doesn't have either the appropriate CloudTrail managed policy (**`AWSCloudTrail_FullAccess`** or **`AWSCloudTrail_ReadOnlyAccess`**) or the equivalent permissions applied to his account.

```
User: arn:aws:iam::123456789012:user/mateojackson is not authorized to perform:
cloudtrail:GetTrailStatus on resource: My-Trail
```

In this case, Mateo asks his administrator to update his policies to allow him to access trail information and status in the console.

If you sign in with an IAM user or role that has the **`AWSCloudTrail_FullAccess`** managed policy or its equivalent permissions, and you can't configure AWS Config or Amazon CloudWatch Logs integration with a trail, you might be missing the required permissions for integration with those services. For more information, see [Granting permission to view AWS Config information on the CloudTrail console](#) and [Granting permission to view and configure Amazon CloudWatch Logs information on the CloudTrail console](#).

I am not authorized to perform `iam:PassRole`

If you receive an error that you're not authorized to perform the `iam:PassRole` action, your policies must be updated to allow you to pass a role to CloudTrail.

Some AWS services allow you to pass an existing role to that service instead of creating a new service role or service-linked role. To do this, you must have permissions to pass the role to the service.

The following example error occurs when an IAM user named `marymajor` tries to use the console to perform an action in CloudTrail. However, the action requires the service to have permissions that are granted by a service role. Mary does not have permissions to pass the role to the service.

```
User: arn:aws:iam::123456789012:user/marymajor is not authorized to perform:
iam:PassRole
```

In this case, Mary's policies must be updated to allow her to perform the `iam:PassRole` action.

If you need help, contact your AWS administrator. Your administrator is the person who provided you with your sign-in credentials.

I want to allow people outside of my AWS account to access my CloudTrail resources

You can create a role and share CloudTrail information between multiple AWS accounts. For more information, see [Sharing CloudTrail log files between AWS accounts](#).

You can create a role that users in other accounts or people outside of your organization can use to access your resources. You can specify who is trusted to assume the role. For services that support resource-based policies or access control lists (ACLs), you can use those policies to grant people access to your resources.

To learn more, consult the following:

- To learn whether CloudTrail supports these features, see [How AWS CloudTrail works with IAM](#).
- To learn how to provide access to your resources across AWS accounts that you own, see [Providing access to an IAM user in another AWS account that you own](#) in the *IAM User Guide*.
- To learn how to provide access to your resources to third-party AWS accounts, see [Providing access to AWS accounts owned by third parties](#) in the *IAM User Guide*.
- To learn how to provide access through identity federation, see [Providing access to externally authenticated users \(identity federation\)](#) in the *IAM User Guide*.
- To learn the difference between using roles and resource-based policies for cross-account access, see [Cross account resource access in IAM](#) in the *IAM User Guide*.

I am not authorized to perform iam:PassRole

If you receive an error that you're not authorized to perform the `iam:PassRole` action, your policies must be updated to allow you to pass a role to CloudTrail.

Some AWS services allow you to pass an existing role to that service instead of creating a new service role or service-linked role. To do this, you must have permissions to pass the role to the service.

The following example error occurs when an IAM user named `marymajor` tries to use the console to perform an action in CloudTrail. However, the action requires the service to have permissions that are granted by a service role. Mary does not have permissions to pass the role to the service.

```
User: arn:aws:iam::123456789012:user/marymajor is not authorized to perform:
iam:PassRole
```

In this case, Mary's policies must be updated to allow her to perform the `iam:PassRole` action.

If you need help, contact your AWS administrator. Your administrator is the person who provided you with your sign-in credentials.

I am getting a `NoManagementAccountSLRExistsException` exception when I try to create an organization trail or event data store

The `NoManagementAccountSLRExistsException` exception is thrown when the management account does not have a service-linked role.

When you add a delegated administrator using the AWS Organizations CLI or API operation, CloudTrail service-linked roles won't be created automatically if they don't exist. The service-linked roles are only created when you make a call from the management account directly to the CloudTrail service. For example, when you add a delegated administrator or create an organization trail or event data store using the CloudTrail console, AWS CLI or CloudTrail API, the `AWSServiceRoleForCloudTrail` service-linked role is created.

When you add a delegated administrator using the AWS CloudTrail; CLI or API operation, CloudTrail will create both the `AWSServiceRoleForCloudTrail` and the `AWSServiceRoleForCloudTrailEventContext` service-linked roles.

When you use your organization's management account to add a delegated administrator or create an organization trail or event data store in the CloudTrail console, or by using the AWS CLI or CloudTrail API, CloudTrail automatically creates the `AWSServiceRoleForCloudTrail` service-linked role for your management account if it does not already exist. For more information, see [Using service-linked roles for CloudTrail](#).

If you haven't added a delegated administrator, use the CloudTrail console, AWS CLI or CloudTrail API to add the delegated administrator. For more information about adding a delegated administrator, see [Add a CloudTrail delegated administrator](#) and [RegisterOrganizationDelegatedAdmin](#) (API).

If you've already added the delegated administrator, use the management account to create the organization trail or event data store in the CloudTrail console, or by using the AWS CLI or CloudTrail API. For more information about creating an organization trail, see [Creating a trail](#)

for your organization in the console, [Creating a trail for an organization with the AWS CLI](#), and [CreateTrail](#) (API).

Using service-linked roles for CloudTrail

AWS CloudTrail uses AWS Identity and Access Management (IAM) [service-linked roles](#). A service-linked role is a unique type of IAM role that is linked directly to CloudTrail. Service-linked roles are predefined by CloudTrail and include all the permissions that the service requires to call other AWS services on your behalf.

Topics

- [Using roles for creating and managing CloudTrail organization trails and CloudTrail Lake organization event data stores in CloudTrail](#)
- [Supported Regions for CloudTrail service-linked roles](#)
- [Using roles for creating and managing CloudTrail event context in CloudTrail](#)
- [Supported Regions for CloudTrail service-linked roles](#)

Using roles for creating and managing CloudTrail organization trails and CloudTrail Lake organization event data stores in CloudTrail

AWS CloudTrail uses AWS Identity and Access Management (IAM) [service-linked roles](#). A service-linked role is a unique type of IAM role that is linked directly to CloudTrail. Service-linked roles are predefined by CloudTrail and include all the permissions that the service requires to call other AWS services on your behalf.

A service-linked role makes setting up CloudTrail easier because you don't have to manually add the necessary permissions. CloudTrail defines the permissions of its service-linked roles, and unless defined otherwise, only CloudTrail can assume its roles. The defined permissions include the trust policy and the permissions policy, and that permissions policy cannot be attached to any other IAM entity.

You can delete a service-linked role only after first deleting their related resources. This protects your CloudTrail resources because you can't inadvertently remove permission to access the resources.

For information about other services that support service-linked roles, see [AWS services that work with IAM](#) and look for the services that have **Yes** in the **Service-linked roles** column. Choose a **Yes** with a link to view the service-linked role documentation for that service.

Service-linked role permissions for CloudTrail

CloudTrail uses the service-linked role named **AWSServiceRoleForCloudTrail** – This service linked role is used for supporting organization trails and organization event data stores.

The AWSServiceRoleForCloudTrail service-linked role trusts the following services to assume the role:

- `cloudtrail.amazonaws.com`

The role permissions policy named `CloudTrailServiceRolePolicy` allows CloudTrail to complete the following actions on the specified resources:

- Actions on all CloudTrail resources:
 - `All`
- Actions on all AWS Organizations resources:
 - `organizations:DescribeAccount`
 - `organizations:DescribeOrganization`
 - `organizations:ListAccounts`
 - `organizations:ListAWSServiceAccessForOrganization`
- Actions on all Organizations resources for the CloudTrail service principal to list the delegated administrators for the organization:
 - `organizations:ListDelegatedAdministrators`
- Actions for [disabling Lake federation](#) on an organization event data store:
 - `glue>DeleteTable`
 - `lakeformation:DeRegisterResource`

You must configure permissions to allow your users, groups, or roles to create, edit, or delete a service-linked role. For more information, see [Service-linked role permissions](#) in the *IAM User Guide*.

For more information about the managed policy associated with `AWSServiceRoleForCloudTrail`, see [AWS managed policies for AWS CloudTrail](#).

Creating a service-linked role for CloudTrail

You don't need to manually create a service-linked role. When you create an organization trail or organization event data store, or add a delegated administrator in the CloudTrail console, in the AWS Management Console, the AWS CLI, or the AWS API, CloudTrail creates the service-linked role for you.

If you delete this service-linked role, and then need to create it again, you can use the same process to recreate the role in your account. When you create an organization trail or organization event data store, or add a delegated administrator in the CloudTrail console,, CloudTrail creates the service-linked role for you again.

Editing a service-linked role for CloudTrail

CloudTrail does not allow you to edit the `AWSServiceRoleForCloudTrail` service-linked role. After you create a service-linked role, you cannot change the name of the role because various entities might reference the role. However, you can edit the description of the role using IAM. For more information, see [Editing a service-linked role](#) in the *IAM User Guide*.

Deleting a service-linked role for CloudTrail

You don't need to manually delete the `AWSServiceRoleForCloudTrail` role. If an AWS account is removed from an Organizations organization, the `AWSServiceRoleForCloudTrail` role is automatically removed from that AWS account. You cannot detach or remove policies from the `AWSServiceRoleForCloudTrail` service-linked role in an organization management account without removing the account from the organization.

You can also use the IAM console, the AWS CLI or the AWS API to manually delete the service-linked role. To do this, you must first manually clean up the resources for your service-linked role, and then you can manually delete it.

Note

If the CloudTrail service is using the role when you try to delete the resources, then deletion might fail. If that happens, wait for a few minutes and try the operation again.

To remove a resource being used by the `AWSServiceRoleForCloudTrail` role, you can do one of the following:

- Remove the AWS account from the organization in Organizations.

- Update the trail so that it is no longer an organization trail. For more information, see [Updating a trail with the CloudTrail console](#).
- Update the event data store so that it is no longer an organization event data store. For more information, see [Update an event data store with the console](#).
- Delete the trail. For more information, see [Deleting a trail with the CloudTrail console](#).
- Delete the event data store. For more information, see [Delete an event data store with the console](#).

To manually delete the service-linked role using IAM

Use the IAM console, the AWS CLI, or the AWS API to delete the `AWSServiceRoleForCloudTrail` service-linked role. For more information, see [Deleting a service-linked role](#) in the *IAM User Guide*.

Supported Regions for CloudTrail service-linked roles

CloudTrail supports using service-linked roles in all of the AWS Regions where CloudTrail and Organizations are both available. For more information, see [AWS Regions and endpoints](#) in the *AWS General Reference*.

Using roles for creating and managing CloudTrail event context in CloudTrail

AWS CloudTrail uses AWS Identity and Access Management (IAM) [service-linked roles](#). A service-linked role is a unique type of IAM role that is linked directly to CloudTrail. Service-linked roles are predefined by CloudTrail and include all the permissions that the service requires to call other AWS services on your behalf.

A service-linked role makes setting up CloudTrail easier because you don't have to manually add the necessary permissions. CloudTrail defines the permissions of its service-linked roles, and unless defined otherwise, only CloudTrail can assume its roles. The defined permissions include the trust policy and the permissions policy, and that permissions policy cannot be attached to any other IAM entity.

You can delete a service-linked role only after first deleting their related resources. This protects your CloudTrail resources because you can't inadvertently remove permission to access the resources.

For information about other services that support service-linked roles, see [AWS services that work with IAM](#) and look for the services that have **Yes** in the **Service-linked roles** column. Choose a **Yes** with a link to view the service-linked role documentation for that service.

Service-linked role permissions for CloudTrail

CloudTrail uses the service-linked role named **AWSServiceRoleForCloudTrailEventContext** – This service linked role is used for managing CloudTrail Event Context and EventBridge rules.

The AWSServiceRoleForCloudTrailEventContext service-linked role trusts the following services to assume the role:

- `context.cloudtrail.amazonaws.com`

The role permissions policy named CloudTrailEventContext allows CloudTrail to complete the following actions on the specified resources:

- Actions on resource tags:
 - `tag:GetResources`
- Actions on all Amazon EventBridge resources for the CloudTrail service principal to create rules:
 - `events:PutRule`
- Actions on all Amazon EventBridge resources for the CloudTrail service principal to manage the rules it creates:
 - `events:PutTargets`
 - `events>DeleteRule`
 - `events:RemoveTargets`
 - `events:RemoveTargets`
- Actions on all Amazon EventBridge resources for the CloudTrail service principal to describe the rules it creates:
 - `events:DescribeRule`
 - `events:DeRegisterResource`
- Actions on all Amazon EventBridge resources:
 - `events:ListRules`

You must configure permissions to allow your users, groups, or roles to create, edit, or delete a service-linked role. For more information, see [Service-linked role permissions](#) in the *IAM User Guide*.

For more information about the managed policy associated with AWSServiceRoleForCloudTrailEventContext, see [AWS managed policies for AWS CloudTrail](#).

Creating a service-linked role for CloudTrail

You don't need to manually create a service-linked role. When you begin using the context event feature in the AWS Management Console, the AWS CLI, or the AWS API, CloudTrail creates the service-linked role for you.

If you delete this service-linked role, and then need to create it again, you can use the same process to recreate the role in your account. When you begin using the context event feature, CloudTrail creates the service-linked role for you again.

Editing a service-linked role for CloudTrail

CloudTrail does not allow you to edit the `AWSServiceRoleForCloudTrailEventContext` service-linked role. After you create a service-linked role, you cannot change the name of the role because various entities might reference the role. However, you can edit the description of the role using IAM. For more information, see [Editing a service-linked role](#) in the *IAM User Guide*.

Deleting the `AWSServiceRoleForCloudTrailEventContext` service-linked role for CloudTrail

If you no longer need to use a feature or service that requires the `AWSServiceRoleForCloudTrailEventContext` service-linked role, we recommend that you delete that role. That way you don't have an unused entity that is not actively monitored or maintained. However, you must clean up the resources for your service-linked role before you can manually delete it by removing the `TagContext` key from event data stores.

Note

If the CloudTrail service is using the role when you try to delete the resources, then the deletion might fail. If that happens, wait for a few minutes and try the operation again.

To delete CloudTrail resources used by the `AWSServiceRoleForCloudTrailEventContext` service linked role

1. At the terminal or command line, run the **put-event-configuration** command for the event store from which you want to remove the `TagContext` key. For example, to remove the `TagContext` key from an event store in the `111122223333` account in the US East (Ohio) Region with an ARN of `arn:aws:cloudtrail:us-east-2:111122223333:eventdatastore/a1b2c3d4-5678-90ab-cdef-EXAMPLE11111`

where TagContext is the only context key selector, you would use the **put-event-configuration** command with no value specified for `--context-key-selectors`:

```
aws cloudtrail put-event-configuration --event-data-store arn:aws:cloudtrail:us-east-2:111122223333:eventdatastore/a1b2c3d4-5678-90ab-cdef-EXAMPLE11111 --max-event-size Large --context-key-selectors
```

2. Repeat this command for every data store in every Region in the partition. For more information, see [Identify AWS resources with Amazon Resource Names \(ARNs\)](#).

To manually delete the service-linked role using IAM

Use the IAM console, the AWS CLI, or the AWS API to delete the `AWSServiceRoleForCloudTrailEventContext` service-linked role. For more information, see [Deleting a service-linked role](#) in the *IAM User Guide*.

Supported Regions for CloudTrail service-linked roles

CloudTrail supports using service-linked roles in all of the Regions where CloudTrail and EventBridge are available. For more information, see [AWS Regions and endpoints](#).

AWS managed policies for AWS CloudTrail

To add permissions to users, groups, and roles, it is easier to use AWS managed policies than to write policies yourself. It takes time and expertise to [create IAM customer managed policies](#) that provide your team with only the permissions they need. To get started quickly, you can use AWS managed policies. These policies cover common use cases and are available in your AWS account. For more information about AWS managed policies, see [AWS managed policies](#) in the *IAM User Guide*.

AWS services maintain and update AWS managed policies. You can't change the permissions in AWS managed policies. Services occasionally add additional permissions to an AWS managed policy to support new features. This type of update affects all identities (users, groups, and roles) where the policy is attached. Services are most likely to update an AWS managed policy when a new feature is launched or when new operations become available. Services do not remove permissions from an AWS managed policy, so policy updates won't break your existing permissions.

Additionally, AWS supports managed policies for job functions that span multiple services. For example, the **ReadOnlyAccess** AWS managed policy provides read-only access to all AWS services

and resources. When a service launches a new feature, AWS adds read-only permissions for new operations and resources. For a list and descriptions of job function policies, see [AWS managed policies for job functions](#) in the *IAM User Guide*.

AWS managed policy: `AWSCloudTrail_FullAccess`

A user identity that has the [AWSCloudTrail_FullAccess](#) policy attached to its role has full administrative access in CloudTrail.

For a JSON listing of the policy details, see [AWSCloudTrail_FullAccess](#) in the *AWS Managed Policy reference guide*.

AWS managed policy: `AWSCloudTrail_ReadOnlyAccess`

A user identity that has the [AWSCloudTrail_ReadOnlyAccess](#) policy attached to its role can perform read-only actions in CloudTrail, such as `Get*`, `List*`, and `Describe*` actions on trails, CloudTrail Lake event data stores, or Lake queries.

For a JSON listing of the policy details, see [AWSCloudTrail_ReadOnlyAccess](#) in the *AWS Managed Policy reference guide*.

AWS managed policy: `AWSServiceRoleForCloudTrail`

The [CloudTrailServiceRolePolicy](#) policy allows AWS CloudTrail to perform actions on organization trails and organization event data stores on your behalf. The policy includes required AWS Organizations permissions for describing and listing the organization accounts and delegated administrators in an AWS Organizations organization.

This policy additionally includes the required AWS Glue and AWS Lake Formation permissions to [disable Lake federation](#) on an organization event data store.

This policy is attached to the **AWSServiceRoleForCloudTrail** service-linked role that allows CloudTrail to perform actions on your behalf. You cannot attach this policy to your users, groups, or roles.

For a JSON listing of the policy details, see [CloudTrailServiceRolePolicy](#) in the *AWS Managed Policy reference guide*.

AWS managed policy: CloudTrailEventContext

The [CloudTrailEventContext](#) policy allows AWS CloudTrail to manage CloudTrail Event Context and EventBridge rules on your behalf. The policy includes required EventBridge permissions for creating, managing, and describing the rules it creates for you.

This policy is attached to the **AWSServiceRoleForCloudTrailEventContext** service-linked role that allows CloudTrail to perform actions on your behalf. You cannot attach this policy to your users, groups, or roles.

For a JSON listing of the policy details, see [CloudTrailEventContext](#) in the *AWS Managed Policy reference guide*.

CloudTrail updates to AWS managed policies

View details about updates to AWS managed policies for CloudTrail. For automatic alerts about changes to this page, subscribe to the RSS feed on the CloudTrail [Document history](#) page.

Change	Description	Date
CloudTrailEventContext – New policy used by the AWSServiceRoleForCloudTrailEventContext service linked role	Added a new policy and role used for the CloudTrail enriched events feature.	May 19, 2025
CloudTrailServiceRolePolicy – Update to an existing policy	Updated policy to allow the following actions on an organization event data store when federation is disabled: • glue:DeleteTable • lakeformation:DeregisterResource	November 26, 2023
AWSCloudTrail_ReadOnlyAccess – Update to an existing policy	CloudTrail changed the name of the AWSCloudTrailReadOnlyAccess policy to AWSCloudT	June 6, 2022

Change	Description	Date
	<code>trail_ReadOnlyAccess</code> . Also, the scope of permissions in the policy has been reduced to CloudTrail actions. It no longer includes Amazon S3, AWS KMS, or AWS Lambda action permissions.	
CloudTrail started tracking changes	CloudTrail started tracking changes for its AWS managed policies.	June 6, 2022

Compliance validation for AWS CloudTrail

Third-party auditors assess the security and compliance of AWS CloudTrail as part of multiple AWS compliance programs. These include SOC, PCI, FedRAMP, HIPAA, and others.

To learn whether an AWS service is within the scope of specific compliance programs, see [AWS services in Scope by Compliance Program](#) and choose the compliance program that you are interested in. For general information, see [AWS Compliance Programs](#).

You can download third-party audit reports using AWS Artifact. For more information, see [Downloading Reports in AWS Artifact](#).

Your compliance responsibility when using AWS services is determined by the sensitivity of your data, your company's compliance objectives, and applicable laws and regulations. For more information about your compliance responsibility when using AWS services, see [AWS Security Documentation](#).

Resilience in AWS CloudTrail

The AWS global infrastructure is built around AWS Regions and Availability Zones. AWS Regions provide multiple physically separated and isolated Availability Zones, which are connected with low-latency, high-throughput, and highly redundant networking. With Availability Zones, you can design and operate applications and databases that automatically fail over between Availability

Zones without interruption. Availability Zones are more highly available, fault tolerant, and scalable than traditional single or multiple data center infrastructures. If you specifically need to replicate your CloudTrail log files over greater geographic distances, you can use [Cross-Region Replication](#) for your trail Amazon S3 buckets, which enables automatic, asynchronous copying of objects across buckets in different AWS Regions.

For more information about AWS Regions and Availability Zones, see [AWS Global Infrastructure](#).

In addition to the AWS global infrastructure, CloudTrail offers several features to help support your data resiliency and backup needs.

Trails and event data stores that log events in all AWS Regions

When you create a multi-Region trail, CloudTrail creates trails with identical configurations in all enabled AWS Regions in your account.

When you create a multi-Region event data store, CloudTrail collects events that occur in all AWS Regions in your account.

Versioning, lifecycle configuration, and object lock protection for CloudTrail log data

Because CloudTrail uses Amazon S3 buckets to store log files, you can also use the features provided by Amazon S3 to help support your data resiliency and backup needs. For more information, see [Resilience in Amazon S3](#).

Infrastructure security in AWS CloudTrail

As a managed service, AWS CloudTrail is protected by AWS global network security. For information about AWS security services and how AWS protects infrastructure, see [AWS Cloud Security](#). To design your AWS environment using the best practices for infrastructure security, see [Infrastructure Protection](#) in *Security Pillar AWS Well-Architected Framework*.

You use AWS published API calls to access CloudTrail through the network. Clients must support the following:

- Transport Layer Security (TLS). We require TLS 1.2 and recommend TLS 1.3.
- Cipher suites with perfect forward secrecy (PFS) such as DHE (Ephemeral Diffie-Hellman) or ECDHE (Elliptic Curve Ephemeral Diffie-Hellman). Most modern systems such as Java 7 and later support these modes.

The following security best practices also address infrastructure security in CloudTrail:

- [Consider Amazon VPC endpoints for trail access.](#)
- Consider Amazon VPC endpoints for Amazon S3 bucket access. For more information, see [Controlling access from VPC endpoints with bucket policies.](#)
- Identify and audit all Amazon S3 buckets that contain CloudTrail log files. Consider using tags to help identify both your CloudTrail trails and the Amazon S3 buckets that contain CloudTrail log files. You can then use resource groups for your CloudTrail resources. For more information, see [AWS Resource Groups.](#)

Cross-service confused deputy prevention

The confused deputy problem is a security issue where an entity that doesn't have permission to perform an action can coerce a more-privileged entity to perform the action. In AWS, cross-service impersonation can result in the confused deputy problem. Cross-service impersonation can occur when one service (the *calling service*) calls another service (the *called service*). The calling service can be manipulated to use its permissions to act on another customer's resources in a way it should not otherwise have permission to access. To prevent this, AWS provides tools that help you protect your data for all services with service principals that have been given access to resources in your account.

We recommend using the [aws:SourceArn](#) and [aws:SourceAccount](#) global condition context keys in resource policies to limit the permissions that AWS CloudTrail gives another service to the resource. Use `aws:SourceArn` if you want only one resource to be associated with the cross-service access. Use `aws:SourceAccount` if you want to allow any resource in that account to be associated with the cross-service use.

The most effective way to protect against the confused deputy problem is to use the `aws:SourceArn` global condition context key with the full ARN of the resource. If you don't know the full ARN of the resource or if you are specifying multiple resources, use the `aws:SourceArn` global context condition key with wildcards (*) for the unknown portions of the ARN. For example, `"arn:aws:cloudtrail:*:AccountID:trail/*"`. When you include a wildcard, you must also use the `StringLike` condition operator.

The value of `aws:SourceArn` must be the ARN of the trail, event data store, or channel that is using the resource.

The following example shows how you can use the `aws:SourceArn` and `aws:SourceAccount` global condition context keys in CloudTrail to prevent the confused deputy problem: [Amazon S3 bucket policy for CloudTrail Lake query results](#).

Security best practices in AWS CloudTrail

AWS CloudTrail provides a number of security features to consider as you develop and implement your own security policies. The following best practices are general guidelines and don't represent a complete security solution. Because these best practices might not be appropriate or sufficient for your environment, treat them as helpful considerations rather than prescriptions.

Topics

- [CloudTrail detective security best practices](#)
- [CloudTrail preventative security best practices](#)

CloudTrail detective security best practices

Create a trail

For an ongoing record of events in your AWS account, you must create a trail. Although CloudTrail provides 90 days of event history information for management events in the CloudTrail console without creating a trail, it is not a permanent record, and it does not provide information about all possible types of events. For an ongoing record, and for a record that contains all the event types you specify, you must create a trail, which delivers log files to an Amazon S3 bucket that you specify.

To help manage your CloudTrail data, consider creating one trail that logs management events in all AWS Regions, and then creating additional trails that log specific event types for resources, such as Amazon S3 bucket activity or AWS Lambda functions.

The following are some steps you can take:

- [Create a trail for your AWS account](#).
- [Create a trail for an organization](#).

Create a multi-Region trail

To obtain a complete record of events taken by an IAM identity, or service in your AWS account, create a multi-Region trail. Multi-Region trails log events in all AWS Regions that are [enabled](#) in your AWS account. By logging events in all enabled AWS Regions, you ensure that you capture activity in all enabled Regions in your AWS account. This includes logging [global service events](#), which are logged to an AWS Region specific to that service. All trails created using the CloudTrail console are multi-Region trails.

The following are some steps you can take:

- [Create a trail for your AWS account.](#)
- [Convert an existing single-Region trail](#) to a multi-Region trail.
- Implement ongoing detective controls to help ensure all trails created are logging events in all AWS Regions by using the [multi-region-cloud-trail-enabled](#) rule in AWS Config.

Enable CloudTrail log file integrity

Validated log files are especially valuable in security and forensic investigations. For example, a validated log file enables you to assert positively that the log file itself has not changed, or that particular IAM identity credentials performed specific API activity. The CloudTrail log file integrity validation process also lets you know if a log file has been deleted or changed, or assert positively that no log files were delivered to your account during a given period of time. CloudTrail log file integrity validation uses industry standard algorithms: SHA-256 for hashing and SHA-256 with RSA for digital signing. This makes it computationally unfeasible to modify, delete or forge CloudTrail log files without detection. For more information, see [Enabling validation and validating files](#).

Integrate with Amazon CloudWatch Logs

CloudWatch Logs allows you to monitor and receive alerts for specific events captured by CloudTrail. The events sent to CloudWatch Logs are those configured to be logged by your trail, so make sure you have configured your trail or trails to log the event types (management events data events and/or network activity events) that you are interested in monitoring.

For example, you can monitor key security and network-related management events, such as [failed AWS Management Console sign-in events](#).

The following are some steps you can take:

- Review example [CloudWatch Logs integrations for CloudTrail](#).

- Configure your trail to [send events to CloudWatch Logs](#).
- Consider implementing ongoing detective controls to help ensure all trails are sending events to CloudWatch Logs for monitoring by using the [cloud-trail-cloud-watch-logs-enabled](#) rule in AWS Config.

Use Amazon GuardDuty

Amazon GuardDuty is a threat detection service that helps you protect your accounts, containers, workloads, and the data within your AWS environment. By using machine learning (ML) models, and anomaly and threat detection capabilities, GuardDuty continuously monitors different log sources to identify, and prioritize potential security risks and malicious activities in your environment.

For example, GuardDuty will detect potential credential exfiltration in case it detects credentials that were created exclusively for an Amazon EC2 instance through an instance launch role but are being used from another account within AWS. For more information, see the [Amazon GuardDuty User Guide](#).

Use AWS Security Hub

Monitor your usage of CloudTrail as it relates to security best practices by using [AWS Security Hub](#). Security Hub uses detective *security controls* to evaluate resource configurations and *security standards* to help you comply with various compliance frameworks. For more information about using Security Hub to evaluate CloudTrail resources, see [AWS CloudTrail controls](#) in the *AWS Security Hub User Guide*.

CloudTrail preventative security best practices

The following best practices for CloudTrail can help prevent security incidents.

Log to a dedicated and centralized Amazon S3 bucket

CloudTrail log files are an audit log of actions taken by an IAM identity or an AWS service. The integrity, completeness and availability of these logs is crucial for forensic and auditing purposes. By logging to a dedicated and centralized Amazon S3 bucket, you can enforce strict security controls, access, and segregation of duties.

The following are some steps you can take:

- Create a separate AWS account as a log archive account. If you use AWS Organizations, enroll this account in the organization, and consider [creating an organization trail](#) to log data for all AWS accounts in your organization.
- If you do not use Organizations but want to log data for multiple AWS accounts, [create a trail](#) to log activity in this log archive account. Restrict access to this account to only trusted administrative users who should have access to account and auditing data.
- As part of creating a trail, whether it is an organization trail or a trail for a single AWS account, create a dedicated Amazon S3 bucket to store log files for this trail.
- If you want to log activity for more than one AWS account, [modify the bucket policy](#) to allow logging and storing log files for all AWS accounts that you want to log AWS account activity.
- If you are not using an organization trail, create trails in all of your AWS accounts, specifying the Amazon S3 bucket in the log archive account.

Use server-side encryption with AWS KMS managed keys

By default, the log files delivered by CloudTrail to your S3 bucket are encrypted by using [server-side encryption with a KMS key \(SSE-KMS\)](#). To use SSE-KMS with CloudTrail, you create and manage an [AWS KMS key](#), also known as a KMS key.

Note

If you use SSE-KMS and log file validation, and you have modified your Amazon S3 bucket policy to only allow SSE-KMS encrypted files, you will not be able to create trails that utilize that bucket unless you modify your bucket policy to specifically allow AES256 encryption, as shown in the following example policy line.

```
"StringNotEquals": { "s3:x-amz-server-side-encryption": ["aws:kms", "AES256"] }
```

The following are some steps you can take:

- [Review the advantages of encrypting your log files with SSE-KMS.](#)
- [Create a KMS key to use for encrypting log files.](#)
- [Configure log file encryption for your trails.](#)
- Consider implementing ongoing detective controls to help ensure all trails are encrypting log files with SSE-KMS by using the [cloud-trail-encryption-enabled](#) rule in AWS Config.

Add a condition key to the default Amazon SNS topic policy

When you configure a trail to send notifications to Amazon SNS, CloudTrail adds a policy statement to your SNS topic access policy that allows CloudTrail to send content to an SNS topic. As a security best practice, we recommend adding an `aws:SourceArn` (or optionally `aws:SourceAccount`) condition key to the Amazon SNS topic policy statement. This helps prevent unauthorized account access to your SNS topic. For more information, see [Amazon SNS topic policy for CloudTrail](#).

Implement least privilege access to Amazon S3 buckets where you store log files

CloudTrail trails log events to an Amazon S3 bucket that you specify. These log files contain an audit log of actions taken by IAM identities and AWS services. The integrity and completeness of these log files are crucial for auditing and forensic purposes. In order to help ensure that integrity, you should adhere to the principle of least privilege when creating or modifying access to any Amazon S3 bucket used for storing CloudTrail log files.

Take the following steps:

- Review the [Amazon S3 bucket policy](#) for any and all buckets where you store log files and adjust it if necessary to remove any unnecessary access. This bucket policy will be generated for you if you create a trail using the CloudTrail console, but can also be created and managed manually.
- As a security best practice, be sure to manually add a `aws:SourceArn` condition key to the bucket policy. For more information, see [Amazon S3 bucket policy for CloudTrail](#).
- If you are using the same Amazon S3 bucket to store log files for multiple AWS accounts, follow the guidance for [receiving log files for multiple accounts](#).
- If you are using an organization trail, make sure you follow the guidance for [organization trails](#), and review the example policy for an Amazon S3 bucket for an organization trail in [Creating a trail for an organization with the AWS CLI](#).
- Review the [Amazon S3 security documentation](#) and the [example walkthrough for securing a bucket](#).

Enable MFA delete on the Amazon S3 bucket where you store log files

When you configure multi-factor authentication (MFA), attempts to change the versioning state of bucket, or delete an object version in a bucket, require additional authentication. This way, even if a user acquires the password of an IAM user with permissions to permanently delete Amazon S3 objects, you can still prevent operations that could compromise your log files.

The following are some steps you can take:

- Review the [MFA delete](#) guidance in the *Amazon Simple Storage Service User Guide*.
- [Add an Amazon S3 bucket policy to require MFA](#).

Note

You cannot use MFA delete with lifecycle configurations. For more information about lifecycle configurations and how they interact with other configurations, see Lifecycle and other bucket configurations *Amazon Simple Storage Service User Guide*.

Configure object lifecycle management on the Amazon S3 bucket where you store log files

The CloudTrail trail default is to store log files indefinitely in the Amazon S3 bucket configured for the trail. You can use the [Amazon S3 object lifecycle management rules](#) to define your own retention policy to better meet your business and auditing needs. For example, you might want to archive log files that are more than a year old to Amazon Glacier, or delete log files after a certain amount of time has passed.

Note

Lifecycle configuration on multi-factor authentication (MFA)-enabled buckets is not supported.

Limit access to the AWSCloudTrail_FullAccess policy

Users with the [AWSCloudTrail_FullAccess](#) policy have the ability to disable or reconfigure the most sensitive and important auditing functions in their AWS accounts. This policy is not intended to be shared or applied broadly to IAM identities in your AWS account. Limit application of this policy to as few individuals as possible, those you expect to act as AWS account administrators.

Encrypting CloudTrail log files, digest files, and event data stores with AWS KMS keys (SSE-KMS)

By default, the log files and digest files delivered by CloudTrail to your bucket are encrypted by using [server-side encryption with a KMS key \(SSE-KMS\)](#). If you don't enable SSE-KMS encryption, your log files and digest files are encrypted using [SSE-S3 encryption](#).

Note

If you're using an existing S3 bucket with an [S3 bucket Key](#), CloudTrail must be allowed permission in the key policy to use the AWS KMS actions `GenerateDataKey` and `DescribeKey`. If `cloudtrail.amazonaws.com` is not granted those permissions in the key policy, you cannot create or update a trail.

To use SSE-KMS with CloudTrail, you create and manage a [AWS KMS key](#). You attach a policy to the key that determines which users can use the key for encrypting and decrypting CloudTrail log files and digest files. The decryption is seamless through S3. When authorized users of the key read CloudTrail log files or digest files, S3 manages the decryption, and the authorized users are able to read the files in unencrypted form.

This approach has the following advantages:

- You can create and manage the KMS key yourself.
- You can use a single KMS key to encrypt and decrypt log files and digest files for multiple accounts across all Regions.
- You have control over who can use your key for encrypting and decrypting CloudTrail log files and digest files. You can assign permissions for the key to the users in your organization according to your requirements.
- You have enhanced security. With this feature, to read log files or digest files, the following permissions are required:
 - A user must have S3 read permissions for the bucket that contains the log files and digest files.
 - A user must also have a policy or role applied that allows decrypt permissions by the KMS key policy.

- Because S3 automatically decrypts the log files and digest files for requests from users authorized to use the KMS key, SSE-KMS encryption for the files is backward-compatible with applications that read CloudTrail log data.

Note

The KMS key that you choose must be created in the same AWS Region as the Amazon S3 bucket that receives your log files and digest files. For example, if the log files and digest files will be stored in a bucket in the US East (Ohio) Region, you must create or choose a KMS key that was created in that Region. To verify the Region for an Amazon S3 bucket, inspect its properties in the Amazon S3 console.

By default, event data stores are encrypted by CloudTrail. You have the option to use your own KMS key for encryption when you create or update an event data store.

Enabling log file encryption

Note

If you create a KMS key in the CloudTrail console, CloudTrail adds the required KMS key policy sections for you. Follow these procedures if you created a key in the IAM console or AWS CLI and you need to manually add the required policy sections.

To enable SSE-KMS encryption for CloudTrail log files, perform the following high-level steps:

1. Create a KMS key.
 - For information about creating a KMS key with the AWS Management Console, see [Creating Keys](#) in the *AWS Key Management Service Developer Guide*.
 - For information about creating a KMS key with the AWS CLI, see [create-key](#).

Note

The KMS key that you choose must be in the same Region as the S3 bucket that receives your log files and digest files. To verify the Region for an S3 bucket, inspect the bucket's properties in the S3 console.

2. Add policy sections to the key that enable CloudTrail to encrypt and users to decrypt log files and digest files.
 - For information about what to include in the policy, see [Configure AWS KMS key policies for CloudTrail](#).

Warning

Be sure to include decrypt permissions in the policy for all users who need to read log files or digest files. If you do not perform this step before adding the key to your trail configuration, users without decrypt permissions cannot read encrypted files until you grant them those permissions.

- For information about editing a policy with the IAM console, see [Editing a Key Policy](#) in the *AWS Key Management Service Developer Guide*.
 - For information about attaching a policy to a KMS key with the AWS CLI, see [put-key-policy](#).
3. Update your trail or event data store to use the KMS key whose policy you modified for CloudTrail.
 - To update a trail or event data store using the CloudTrail console, see [Updating a resource to use your KMS key with the console](#).
 - To update a trail or event data store using the AWS CLI, see [Enabling and disabling encryption for CloudTrail log files, digest files and event data stores with the AWS CLI](#).

CloudTrail also supports AWS KMS multi-Region keys. For more information about multi-Region keys, see [Using multi-Region keys](#) in the *AWS Key Management Service Developer Guide*.

The next section describes the policy sections that your KMS key policy requires for use with CloudTrail.

Granting permissions to create a KMS key

You can grant users permission to create an AWS KMS key with the [AWSKeyManagementServicePowerUser](#) policy.

To grant permission to create a KMS key

1. Open the IAM console at <https://console.aws.amazon.com/iam/>.
2. Choose the group or user that you want to give permission.
3. Choose the **Permissions** tab.
4. From the **Add permissions** list, choose **Attach policies**.
5. Search for **AWSKeyManagementServicePowerUser**, choose the policy, and then choose **Attach policies**.

The user now has permission to create a KMS key. For more information about creating policies, see [Creating IAM policies](#) in the *IAM User Guide*.

Configure AWS KMS key policies for CloudTrail

You can create an AWS KMS key in three ways:

- The CloudTrail console
- The AWS Management console
- The AWS CLI

Note

If you create a KMS key in the CloudTrail console, CloudTrail adds the required KMS key policy for you. You do not need to manually add the policy statements. See [Default KMS key policy created in CloudTrail console](#).

If you create a KMS key in the AWS Management Console or the AWS CLI, you must add policy sections to the key so that you can use it with CloudTrail. The policy must allow CloudTrail to use the key to encrypt your log files, digest files, and event data stores, and allow the users you specify to read log files and digest files in unencrypted form.

See the following resources:

- To create a KMS key with the AWS CLI, see [create-key](#).
- To edit a KMS key policy for CloudTrail, see [Editing a Key Policy](#) in the *AWS Key Management Service Developer Guide*.
- For technical details on how CloudTrail uses AWS KMS, see [How AWS CloudTrail uses AWS KMS](#).

Topics

- [Required KMS key policy sections for use with CloudTrail](#)
- [Granting encrypt permissions for trails](#)
- [Granting encrypt permissions for event data stores](#)
- [Granting decrypt permissions for trails](#)
- [Granting decrypt permissions for event data stores](#)
- [Enable CloudTrail to describe KMS key properties](#)
- [Default KMS key policy created in CloudTrail console](#)

Required KMS key policy sections for use with CloudTrail

If you created a KMS key with the AWS Management console or the AWS CLI, then you must, at minimum, add the following statements to your KMS key policy for it to work with CloudTrail.

Topics

- [Required KMS key policy elements for trails](#)
- [Required KMS key policy elements for event data stores](#)

Required KMS key policy elements for trails

1. Grant permissions to encrypt CloudTrail log and digest files. For more information, see [Granting encrypt permissions for trails](#).
2. Grant permissions to decrypt CloudTrail log and digest files. For more information, see [Granting decrypt permissions for trails](#). If you are using an existing S3 bucket with an [S3 Bucket Key](#), `kms:Decrypt` permissions are required to create or update a trail with SSE-KMS encryption enabled.

3. Enable CloudTrail to describe KMS key properties. For more information, see [Enable CloudTrail to describe KMS key properties](#).

As a security best practice, add an `aws:SourceArn` condition key to the KMS key policy. The IAM global condition key `aws:SourceArn` helps ensure that CloudTrail uses the KMS key only for a specific trail or trails. The value of `aws:SourceArn` is always the trail ARN (or array of trail ARNs) that is using the KMS key. Be sure to add the `aws:SourceArn` condition key to KMS key policies for existing trails.

The `aws:SourceAccount` condition key is also supported, but not recommended. The value of `aws:SourceAccount` is the account ID of the trail owner, or for organization trails, the management account ID.

Important

When you add the new sections to your KMS key policy, do not change any existing sections in the policy.

If encryption is enabled on a trail, and the KMS key is disabled, or the KMS key policy is not correctly configured for CloudTrail, CloudTrail cannot deliver logs.

Required KMS key policy elements for event data stores

1. Grant permissions to encrypt a CloudTrail Lake event data store. For more information, see [Granting encrypt permissions for event data stores](#).
2. Grant permissions to decrypt a CloudTrail Lake event data store. For more information, see [Granting decrypt permissions for event data stores](#).

When you create an event data store and encrypt it with a KMS key, or run queries on an event data store that you're encrypting with a KMS key, you should have write access to the KMS key. The KMS key policy must have access to CloudTrail, and the KMS key should be manageable by users who run operations (such as queries) on the event data store.

3. Enable CloudTrail to describe KMS key properties. For more information, see [Enable CloudTrail to describe KMS key properties](#).

The `aws:SourceArn` and `aws:SourceAccount` condition keys are not supported in KMS key policies for event data stores.

Important

When you add the new sections to your KMS key policy, do not change any existing sections in the policy.

If encryption is enabled on an event data store, and the KMS key is disabled or deleted, or the KMS key policy is not correctly configured for CloudTrail, CloudTrail cannot deliver events to your event data store.

Granting encrypt permissions for trails

Example Allow CloudTrail to encrypt log files and digest files on behalf of specific accounts

CloudTrail needs explicit permission to use the KMS key to encrypt log files and digest files on behalf of specific accounts. To specify an account, add the following required statement to your KMS key policy and replace *account-id*, *region*, and *trailName* with the appropriate values for your configuration. You can add additional account IDs to the EncryptionContext section to enable those accounts to use CloudTrail to use your KMS key to encrypt log files and digest files.

As a security best practice, add an `aws:SourceArn` condition key to the KMS key policy for a trail. The IAM global condition key `aws:SourceArn` helps ensure that CloudTrail uses the KMS key only for a specific trail or trails.

```
{
  "Sid": "AllowCloudTrailEncryptLogs",
  "Effect": "Allow",
  "Principal": {
    "Service": "cloudtrail.amazonaws.com"
  },
  "Action": "kms:GenerateDataKey*",
  "Resource": "*",
  "Condition": {
    "StringEquals": {
      "aws:SourceArn": "arn:aws:cloudtrail:region:account-id:trail/trail-name"
    },
    "StringLike": {
      "kms:EncryptionContext:aws:cloudtrail:arn": "arn:aws:cloudtrail:*:account-id:trail/*"
    }
  }
}
```

```
}
```

Example

The following example policy statement illustrates how another account can use your KMS key to encrypt CloudTrail log files and digest files.

Scenario

- Your KMS key is in account **111111111111**.
- Both you and account **222222222222** will encrypt logs.

In the policy, you add one or more accounts that encrypt with your key to the CloudTrail **EncryptionContext**. This restricts CloudTrail to using your key to encrypt log files and digest files only for the accounts that you specify. When you give the root of account **222222222222** permission to encrypt log files and digest files, it delegates permission to the account administrator to encrypt the necessary permissions to other users in that account. The account administrator does this by changing the policies associated with those IAM users.

As a security best practice, add an `aws:SourceArn` condition key to the KMS key policy. The IAM global condition key `aws:SourceArn` helps ensure that CloudTrail uses the KMS key only for the specified trails. This condition isn't supported in KMS key policies for event data stores.

KMS key policy statement:

```
{
  "Sid": "EnableCloudTrailEncryptPermissions",
  "Effect": "Allow",
  "Principal": {
    "Service": "cloudtrail.amazonaws.com"
  },
  "Action": "kms:GenerateDataKey*",
  "Resource": "*",
  "Condition": {
    "StringLike": {
      "kms:EncryptionContext:aws:cloudtrail:arn": [
        "arn:aws:cloudtrail:*:111111111111:trail/*",
        "arn:aws:cloudtrail:*:222222222222:trail/*"
      ]
    },
    "StringEquals": {
```



```
    "aws:SourceArn": "arn:aws:cloudtrail:region:account-id:trail/trail-name"
  }
}
```

For more information about editing a KMS key policy for use with CloudTrail, see [Editing a key policy](#) in the AWS Key Management Service Developer Guide.

Granting encrypt permissions for event data stores

A policy for a KMS key used to encrypt a CloudTrail Lake event data store cannot use the condition keys `aws:SourceArn` or `aws:SourceAccount`. The following is an example of a KMS key policy for an event data store.

```
{
  "Sid": "AllowCloudTrailEncryptEds",
  "Effect": "Allow",
  "Principal": {
    "Service": "cloudtrail.amazonaws.com"
  },
  "Action": [
    "kms:GenerateDataKey",
    "kms:Decrypt"
  ],
  "Resource": "*"
}
```

Granting decrypt permissions for trails

Before you add your KMS key to your CloudTrail configuration, it is important to give decrypt permissions to all users who require them. Users who have encrypt permissions but no decrypt permissions cannot read encrypted logs. If you are using an existing S3 bucket with an [S3 Bucket Key](#), `kms:Decrypt` permissions are required to create or update a trail with SSE-KMS encryption enabled.

Enable CloudTrail log decrypt permissions

Users of your key must be given explicit permissions to read the log files that CloudTrail has encrypted. To enable users to read encrypted logs, add the following required statement to your KMS key policy, modifying the `Principal` section to add a line for every principal that you want to be able decrypt by using your KMS key.

```
{
  "Sid": "EnableCloudTrailLogDecryptPermissions",
  "Effect": "Allow",
  "Principal": {
    "AWS": "arn:aws:iam::account-id:user/username"
  },
  "Action": "kms:Decrypt",
  "Resource": "*",
  "Condition": {
    "Null": {
      "kms:EncryptionContext:aws:cloudtrail:arn": "false"
    }
  }
}
```

The following is an example policy that is required to allow the CloudTrail service principal to decrypt trail logs.

```
{
  "Sid": "AllowCloudTrailDecryptTrail",
  "Effect": "Allow",
  "Principal": {
    "Service": "cloudtrail.amazonaws.com"
  },
  "Action": "kms:Decrypt",
  "Resource": "*"
}
```

Allow users in your account to decrypt trail logs with your KMS key

Example

This policy statement illustrates how to allow a user or role in your account to use your key to read the encrypted logs in your account's S3 bucket.

Example Scenario

- Your KMS key, S3 bucket, and IAM user Bob are in account *111111111111*.
- You give IAM user Bob permission to decrypt CloudTrail logs in the S3 bucket.

In the key policy, you enable CloudTrail log decrypt permissions for IAM user Bob.

KMS key policy statement:

```
{
  "Sid": "EnableCloudTrailLogDecryptPermissions",
  "Effect": "Allow",
  "Principal": {
    "AWS": "arn:aws:iam::111111111111:user/Bob"
  },
  "Action": "kms:Decrypt",
  "Resource": "arn:aws:kms:region:account-id:key/key-id",
  "Condition": {
    "Null": {
      "kms:EncryptionContext:aws:cloudtrail:arn": "false"
    }
  }
}
```

Allow users in other accounts to decrypt trail logs with your KMS key

You can allow users in other accounts to use your KMS key to decrypt trail logs. The changes required to your key policy depend on whether the S3 bucket is in your account or in another account.

Allow users of a bucket in a different account to decrypt logs

Example

This policy statement illustrates how to allow an IAM user or role in another account to use your key to read encrypted logs from an S3 bucket in the other account.

Scenario

- Your KMS key is in account **111111111111**.
- The IAM user Alice and S3 bucket are in account **222222222222**.

In this case, you give CloudTrail permission to decrypt logs under account **222222222222**, and you give Alice's IAM user policy permission to use your key **KeyA**, which is in account **111111111111**.

KMS key policy statement:

```
{
```

```

{
  "Sid": "EnableEncryptedCloudTrailLogReadAccess",
  "Effect": "Allow",
  "Principal": {
    "AWS": [
      "arn:aws:iam::222222222222:root"
    ]
  },
  "Action": "kms:Decrypt",
  "Resource": "arn:aws:kms:region:111111111111:key/key-id",
  "Condition": {
    "Null": {
      "kms:EncryptionContext:aws:cloudtrail:arn": "false"
    }
  }
}

```

Alice's IAM user policy statement:

JSON

```

{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "kms:Decrypt",
      "Resource": "arn:aws:kms:us-west-2:111111111111:key/KeyA"
    }
  ]
}

```

Allow users in a different account to decrypt trail logs from your bucket

Example

This policy illustrates how another account can use your key to read encrypted logs from your S3 bucket.

Example Scenario

- Your KMS key and S3 bucket are in account **111111111111**.

- The user who reads logs from your bucket is in account **222222222222**.

To enable this scenario, you enable decrypt permissions for the IAM role **CloudTrailReadRole** in your account, and then give the other account permission to assume that role.

KMS key policy statement:

```
{
  "Sid": "EnableEncryptedCloudTrailLogReadAccess",
  "Effect": "Allow",
  "Principal": {
    "AWS": [
      "arn:aws:iam::111111111111:role/CloudTrailReadRole"
    ]
  },
  "Action": "kms:Decrypt",
  "Resource": "arn:aws:kms:region:account-id:key/key-id",
  "Condition": {
    "Null": {
      "kms:EncryptionContext:aws:cloudtrail:arn": "false"
    }
  }
}
```

CloudTrailReadRole trust entity policy statement:

JSON

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "Allow CloudTrail access",
      "Effect": "Allow",
      "Principal": {
        "AWS": "arn:aws:iam::222222222222:root"
      },
      "Action": "sts:AssumeRole"
    }
  ]
}
```

For information about editing a KMS key policy for use with CloudTrail, see [Editing a Key Policy](#) in the *AWS Key Management Service Developer Guide*.

Granting decrypt permissions for event data stores

A decrypt policy for a KMS key that is used with a CloudTrail Lake event data store is similar to the following. The user or role ARNs specified as values for `Principal` need decrypt permissions to create or update event data stores, run queries, or get query results.

```
{
  "Sid": "EnableUserKeyPermissionsEds"
  "Effect": "Allow",
  "Principal": {
    "AWS": "arn:aws:iam::account-id:user/username"
  },
  "Action": [
    "kms:Decrypt",
    "kms:GenerateDataKey"
  ],
  "Resource": "*"
}
```

The following is an example policy that is required to allow the CloudTrail service principal to decrypt an event data store.

```
{
  "Sid": "AllowCloudTrailDecryptEds",
  "Effect": "Allow",
  "Principal": {
    "Service": "cloudtrail.amazonaws.com"
  },
  "Action": "kms:Decrypt",
  "Resource": "*"
}
```

Enable CloudTrail to describe KMS key properties

CloudTrail requires the ability to describe the properties of the KMS key. To enable this functionality, add the following required statement as is to your KMS key policy. This statement does not grant CloudTrail any permissions beyond the other permissions that you specify.

As a security best practice, add an `aws:SourceArn` condition key to the KMS key policy. The IAM global condition key `aws:SourceArn` helps ensure that CloudTrail uses the KMS key only for a specific trail or trails.

```
{
  "Sid": "AllowCloudTrailAccess",
  "Effect": "Allow",
  "Principal": {
    "Service": "cloudtrail.amazonaws.com"
  },
  "Action": "kms:DescribeKey",
  "Resource": "arn:aws:kms:region:account-id:key/key-id",
  "Condition": {
    "StringEquals": {
      "aws:SourceArn": "arn:aws:cloudtrail:region:account-id:trail/trail-name"
    }
  }
}
```

For more information about editing KMS key policies, see [Editing a Key Policy](#) in the *AWS Key Management Service Developer Guide*.

Default KMS key policy created in CloudTrail console

If you create an AWS KMS key in the CloudTrail console, the following policies are automatically created for you. The policy allows these permissions:

- Allows AWS account (root) permissions for the KMS key.
- Allows CloudTrail to encrypt log files and digest files under the KMS key and describe the KMS key.
- Allows all users in the specified accounts to decrypt log files and digest files.
- Allows all users in the specified account to create a KMS alias for the KMS key.
- Enables cross-account log decryption for the account ID of the account that created the trail.

Topics

- [Default KMS key policy for trails](#)
- [Default KMS key policy for CloudTrail Lake event data stores](#)

Default KMS key policy for trails

The following is the default policy created for a AWS KMS key that you use with a trail.

Note

The policy includes a statement to allow cross accounts to decrypt log files and digest files with the KMS key.

JSON

```
{
  "Version": "2012-10-17",
  "Id": "Key policy created by CloudTrail",
  "Statement": [
    {
      "Sid": "Enable IAM user permissions",
      "Effect": "Allow",
      "Principal": {
        "AWS": [
          "arn:aws:iam::111111111111:root",
          "arn:aws:iam::111111111111:user/username"
        ]
      },
      "Action": "kms:*",
      "Resource": "*"
    },
    {
      "Sid": "Allow CloudTrail to encrypt logs",
      "Effect": "Allow",
      "Principal": {
        "Service": "cloudtrail.amazonaws.com"
      },
      "Action": "kms:GenerateDataKey*",
      "Resource": "*",
      "Condition": {
        "StringEquals": {
          "aws:SourceArn": "arn:aws:cloudtrail:us-east-1:111111111111:trail/trail-name"
        },
        "StringLike": {
```



```

        "kms:EncryptionContext:aws:cloudtrail:arn":
"arn:aws:cloudtrail:*:111111111111:trail/*"
    }
}
},
{
    "Sid": "Allow CloudTrail to describe key",
    "Effect": "Allow",
    "Principal": {
        "Service": "cloudtrail.amazonaws.com"
    },
    "Action": "kms:DescribeKey",
    "Resource": "*"
},
{
    "Sid": "Allow principals in the account to decrypt log files",
    "Effect": "Allow",
    "Principal": {
        "AWS": "*"
    },
    "Action": [
        "kms:Decrypt",
        "kms:ReEncryptFrom"
    ],
    "Resource": "*",
    "Condition": {
        "StringEquals": {
            "kms:CallerAccount": "111111111111"
        },
        "StringLike": {
            "kms:EncryptionContext:aws:cloudtrail:arn":
"arn:aws:cloudtrail:*:111111111111:trail/*"
        }
    }
},
{
    "Sid": "Enable cross account log decryption",
    "Effect": "Allow",
    "Principal": {
        "AWS": "*"
    },
    "Action": [
        "kms:Decrypt",
        "kms:ReEncryptFrom"
    ]
}

```

```

    ],
    "Resource": "*",
    "Condition": {
        "StringEquals": {
            "kms:CallerAccount": "111111111111"
        },
        "StringLike": {
            "kms:EncryptionContext:aws:cloudtrail:arn":
"arn:aws:cloudtrail:*:111111111111:trail/*"
        }
    }
}
]
}

```

Default KMS key policy for CloudTrail Lake event data stores

The following is the default policy created for a AWS KMS key that you use with an event data store in CloudTrail Lake.

JSON

```

{
    "Version": "2012-10-17",
    "Id": "Key policy created by CloudTrail",
    "Statement": [
        {
            "Sid": "The key created by CloudTrail to encrypt event data stores.  
Created ${new Date().toUTCString()}",
            "Effect": "Allow",
            "Principal": {
                "Service": "cloudtrail.amazonaws.com"
            },
            "Action": [
                "kms:GenerateDataKey",
                "kms:Decrypt"
            ],
            "Resource": "*"
        },
        {
            "Sid": "Enable IAM user permissions",
            "Effect": "Allow",

```

```

    "Principal": {
      "AWS": "arn:aws:iam::111111111111:root"
    },
    "Action": "kms:*",
    "Resource": "*"
  },
  {
    "Sid": "Enable user to have permissions",
    "Effect": "Allow",
    "Principal": {
      "AWS" : "arn:aws:sts::111111111111:assumed-role/example-role-name"
    },
    "Action": [
      "kms:Decrypt",
      "kms:GenerateDataKey"
    ],
    "Resource": "*"
  }
]
}

```

Updating a resource to use your KMS key with the console

On the CloudTrail console, update a trail or an event data store to use an KMS key. Be aware that using your own KMS key incurs AWS KMS costs for encryption and decryption. For more information, see [AWS Key Management Service Pricing](#).

Topics

- [Update a trail to use a KMS key](#)
- [Update an event data store to use a KMS key](#)

Update a trail to use a KMS key

To update a trail to use the AWS KMS key that you modified for CloudTrail, complete the following steps in the CloudTrail console.

Note

If you are using an existing S3 bucket with an [S3 Bucket Key](#), CloudTrail must be allowed permission in the key policy to use the AWS KMS actions `GenerateDataKey` and

DescribeKey. If `cloudtrail.amazonaws.com` is not granted those permissions in the key policy, you cannot create or update a trail.

To update a trail using the AWS CLI, see [Enabling and disabling encryption for CloudTrail log files, digest files and event data stores with the AWS CLI](#).

To update a trail to use your KMS key

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. Choose **Trails** and then choose a trail name.
3. In **General details**, choose **Edit**.
4. For **Log file SSE-KMS encryption**, choose **Enabled** if you want to encrypt your log files and digest files using SSE-KMS encryption instead of SSE-S3 encryption. The default is **Enabled**. If you don't enable SSE-KMS encryption, your log files and digest files are encrypted using SSE-S3 encryption. For more information about SSE-KMS encryption, see [Using server-side encryption with AWS Key Management Service \(SSE-KMS\)](#). For more information about SSE-S3 encryption, see [Using Server-Side Encryption with Amazon S3-Managed Encryption Keys \(SSE-S3\)](#).

Choose **Existing** to update your trail with your AWS KMS key. Choose a KMS key that is in the same Region as the S3 bucket that receives your log files. To verify the Region for an S3 bucket, view its properties in the S3 console.

Note

You can also type the ARN of a key from another account. For more information, see [Updating a resource to use your KMS key with the console](#). The key policy must allow CloudTrail to use the key to encrypt your log files and digest files, and allow the users you specify to read log files or digest files in unencrypted form. For information about manually editing the key policy, see [Configure AWS KMS key policies for CloudTrail](#).

In **AWS KMS Alias**, specify the alias for which you changed the policy for use with CloudTrail, in the format `alias/MyAliasName`. For more information, see [Updating a resource to use your KMS key with the console](#).

You can type the alias name, ARN, or the globally unique key ID. If the KMS key belongs to another account, verify that the key policy has permissions that enable you to use it. The value can be one of the following formats:

- **Alias Name:** `alias/MyAliasName`
- **Alias ARN:** `arn:aws:kms:region:123456789012:alias/MyAliasName`
- **Key ARN:**
`arn:aws:kms:region:123456789012:key/12345678-1234-1234-1234-123456789012`
- **Globally unique key ID:** `12345678-1234-1234-1234-123456789012`

5. Choose **Update trail**.

 Note

If the KMS key that you chose is disabled or is pending deletion, you cannot save the trail with that KMS key. You can enable the KMS key or choose another one. For more information, see [Key state: Effect on your KMS key](#) in the *AWS Key Management Service Developer Guide*.

Update an event data store to use a KMS key

To update an event data store to use the AWS KMS key that you modified for CloudTrail, complete the following steps in the CloudTrail console.

To update an event data store by using the AWS CLI, see [Update an event data store with the AWS CLI](#).

 Important

Disabling or deleting the KMS key, or removing CloudTrail permissions on the key, prevents CloudTrail from ingesting events into the event data store, and prevents users from querying data in the event data store that was encrypted with the key. After you associate an event data store with a KMS key, the KMS key cannot be removed or changed. Before you disable or delete a KMS key that you are using with an event data store, delete or back up your event data store.

To update an event data store to use your KMS key

1. Sign in to the AWS Management Console and open the CloudTrail console at <https://console.aws.amazon.com/cloudtrail/>.
2. In the navigation pane, choose **Event data stores** in **Lake**. Choose an event data store to update.
3. In **General details**, choose **Edit**.
4. For **Encryption**, if it is not already enabled, choose **Use my own AWS KMS key** to encrypt your event data store with your own KMS key.

Choose **Existing** to update your event data store with your KMS key. Choose a KMS key that is in the same Region as the event data store. A key from another account is not supported.

In **Enter AWS KMS Alias**, specify the alias for which you changed the policy for use with CloudTrail, in the format `alias/MyAliasName`. For more information, see [Updating a resource to use your KMS key with the console](#).

You can choose an alias, or use the globally unique key ID. The value can be one of the following formats:

- **Alias Name:** `alias/MyAliasName`
 - **Alias ARN:** `arn:aws:kms:region:123456789012:alias/MyAliasName`
 - **Key ARN:**
`arn:aws:kms:region:123456789012:key/12345678-1234-1234-1234-123456789012`
 - **Globally unique key ID:** `12345678-1234-1234-1234-123456789012`
5. Choose **Save changes**.

Note

If the KMS key that you chose is disabled or is pending deletion, you cannot save the event data store configuration with that KMS key. You can enable the KMS key, or choose a different key. For more information, see [Key state: Effect on your KMS key](#) in the *AWS Key Management Service Developer Guide*.

Enabling and disabling encryption for CloudTrail log files, digest files and event data stores with the AWS CLI

This topic describes how to enable and disable SSE-KMS encryption for CloudTrail log files, digest files, and event data stores by using the AWS CLI. For background information, see [Encrypting CloudTrail log files, digest files, and event data stores with AWS KMS keys \(SSE-KMS\)](#).

Topics

- [Enabling encryption for CloudTrail log files, digest files, and event data stores by using the AWS CLI](#)
- [Disabling encryption for log files and digest files by using the AWS CLI](#)

Enabling encryption for CloudTrail log files, digest files, and event data stores by using the AWS CLI

- [Enable log file and digest file encryption for a trail](#)
- [Enable encryption for an event data store](#)

Enable encryption for log files and digest files for a trail

1. Create a key with the AWS CLI. The key that you create must be in the same Region as the S3 bucket that receives your CloudTrail log files. For this step, you use the AWS KMS [create-key](#) command.
2. Get the existing key policy so that you can modify it for use with CloudTrail. You can retrieve the key policy with the AWS KMS [get-key-policy](#) command.
3. Add required sections to the key policy so that CloudTrail can encrypt and users can decrypt your log files and digest files. Be sure that all users who read the log files are granted decrypt permissions. Do not change existing sections of the policy. For information about the policy sections to include, see [Configure AWS KMS key policies for CloudTrail](#).
4. Attach the modified JSON policy file to the key by using the AWS KMS [put-key-policy](#) command.
5. Run the CloudTrail `create-trail` or `update-trail` command with the `--kms-key-id` parameter. This command enables encryption of log files and digest files.

```
aws cloudtrail update-trail --name Default --kms-key-id alias/MyKmsKey
```

The `--kms-key-id` parameter specifies the key whose policy you modified for CloudTrail. It can be any one of the following formats:

- **Alias Name.** Example: `alias/MyAliasName`
- **Alias ARN.** Example: `arn:aws:kms:us-east-2:123456789012:alias/MyAliasName`
- **Key ARN.** Example: `arn:aws:kms:us-east-2:123456789012:key/12345678-1234-1234-1234-123456789012`
- **Globally unique key ID.** Example: `12345678-1234-1234-1234-123456789012`

The following is an example response:

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "Default",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/Default",
  "LogFileValidationEnabled": false,
  "KmsKeyId": "arn:aws:kms:us-east-2:123456789012:key/12345678-1234-1234-1234-123456789012",
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

The presence of the `KmsKeyId` element indicates that encryption for your log files has been enabled. If log file validation has been enabled (indicated by the `LogFileValidationEnabled` element being set to true), this also indicates that encryption has been enabled for your digest files. The encrypted log files and digest files should appear in the S3 bucket configured for the trail within approximately 5 minutes.

Enable encryption for an event data store

1. Create a key with the AWS CLI. The key that you create must be in the same Region as the event data store. For this step, run the AWS KMS [create-key](#) command.
2. Get the existing key policy to edit for use with CloudTrail. You can get the key policy by running the AWS KMS [get-key-policy](#) command.

3. Add required sections to the key policy so that CloudTrail can encrypt and users can decrypt your event data store. Be sure that all users who read the event data store are granted decrypt permissions. Do not change existing sections of the policy. For information about the policy sections to include, see [Configure AWS KMS key policies for CloudTrail](#).
4. Attach the edited JSON policy file to the key by running the AWS KMS [put-key-policy](#) command.
5. Run the CloudTrail `create-event-data-store` or `update-event-data-store` command, and add the `--kms-key-id` parameter. This command enables encryption of the event data store.

```
aws cloudtrail update-event-data-store --name my-event-data-store --kms-key-id  
alias/MyKmsKey
```

The `--kms-key-id` parameter specifies the key whose policy you modified for CloudTrail. It can be any one of the following four formats:

- **Alias Name.** Example: `alias/MyAliasName`
- **Alias ARN.** Example: `arn:aws:kms:us-east-2:123456789012:alias/MyAliasName`
- **Key ARN.** Example: `arn:aws:kms:us-east-1:123456789012:key/12345678-1234-1234-1234-123456789012`
- **Globally unique key ID.** Example: `12345678-1234-1234-1234-123456789012`

The following is an example response:

```
{  
  "Name": "my-event-data-store",  
  "ARN": "arn:aws:cloudtrail:us-east-1:12345678910:eventdatastore/  
EXAMPLEf852-4e8f-8bd1-bcf6cEXAMPLE",  
  "RetentionPeriod": "90",  
  "KmsKeyId": "arn:aws:kms:us-  
east-1:123456789012:key/12345678-1234-1234-1234-123456789012"  
  "MultiRegionEnabled": false,  
  "OrganizationEnabled": false,  
  "TerminationProtectionEnabled": true,  
  "AdvancedEventSelectors": [{  
    "Name": "Select all external events",  
    "FieldSelectors": [{  
      "Field": "eventCategory",
```

```
        "Equals": [
            "ActivityAuditLog"
        ]
    }
}
```

The presence of the `KmsKeyId` element indicates that encryption for event data store has been enabled.

Disabling encryption for log files and digest files by using the AWS CLI

To stop encrypting log files and digest files for a trail, run `update-trail` and pass an empty string to the `kms-key-id` parameter:

```
aws cloudtrail update-trail --name my-test-trail --kms-key-id ""
```

The following is an example response:

```
{
  "IncludeGlobalServiceEvents": true,
  "Name": "Default",
  "TrailARN": "arn:aws:cloudtrail:us-east-2:123456789012:trail/Default",
  "LogFileValidationEnabled": false,
  "S3BucketName": "amzn-s3-demo-bucket"
}
```

The absence of the `KmsKeyId` value indicates that encryption for log files and digest files is no longer enabled.

Important

You cannot stop encryption for an event data store.

How AWS CloudTrail uses AWS KMS

This section describes how AWS KMS works with a CloudTrail trail that is encrypted with an SSE-KMS key.

⚠ Important

AWS CloudTrail and Amazon S3 support only [symmetric AWS KMS keys](#). You cannot use an [asymmetric KMS key](#) to encrypt your CloudTrail Logs. For help determining whether a KMS key is symmetric or asymmetric, see [Identify different key types](#) in the *AWS Key Management Service Developer Guide*.

You do not pay a key usage charge when CloudTrail reads or writes log files encrypted with an SSE-KMS key. However, you pay a key usage charge when you access CloudTrail log files encrypted with an SSE-KMS key. For information about AWS KMS pricing, see [AWS Key Management Service Pricing](#). For information about CloudTrail pricing, see [AWS CloudTrail pricing](#).

Understanding when your KMS key is used for your trail

Encrypting CloudTrail log files with AWS KMS builds on the Amazon S3 feature called server-side encryption with an AWS KMS key (SSE-KMS). To learn more about SSE-KMS, see [Using server-side encryption with AWS KMS keys \(SSE-KMS\)](#) in the *Amazon Simple Storage Service User Guide*.

When you configure AWS CloudTrail to use SSE-KMS to encrypt your log files, CloudTrail and Amazon S3 use your AWS KMS keys when you perform certain actions with those services. The following sections explain when and how those services can use your KMS key, and provide additional information that you can use to validate this explanation.

Actions that cause CloudTrail and Amazon S3 to use your KMS key

- [You configure CloudTrail to encrypt log files with your AWS KMS key](#)
- [CloudTrail puts a log file into your S3 bucket](#)
- [You get an encrypted log file from your S3 bucket](#)

You configure CloudTrail to encrypt log files with your AWS KMS key

When you [update your CloudTrail configuration to use your KMS key](#), CloudTrail sends a [GenerateDataKey](#) request to AWS KMS to verify that the KMS key exists and that CloudTrail has permission to use it for encryption. CloudTrail does not use the resulting data key.

The GenerateDataKey request includes the following information for the [encryption context](#):

- The [Amazon Resource Name \(ARN\)](#) of the CloudTrail trail

- The ARN of the S3 bucket and path where the CloudTrail log files are delivered

The `GenerateDataKey` request results in an entry in your CloudTrail logs similar to the following example. When you see a log entry like this one, you can determine that CloudTrail called the AWS KMS `GenerateDataKey` operation for a specific trail. AWS KMS created the data key under a specific KMS key.

```
{
  "eventVersion": "1.09",
  "userIdentity": {
    "type": "AWSService",
    "invokedBy": "cloudtrail.amazonaws.com"
  },
  "eventTime": "2024-12-06T20:14:46Z",
  "eventSource": "kms.amazonaws.com",
  "eventName": "GenerateDataKey",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "cloudtrail.amazonaws.com",
  "userAgent": "cloudtrail.amazonaws.com",
  "requestParameters": {
    "keySpec": "AES_256",
    "keyId": "arn:aws:kms:us-east-1:123456789012:key/example1-6736-4661-bf00-exampleeb770",
    "encryptionContext": {
      "aws:cloudtrail:arn": "arn:aws:cloudtrail:us-east-1:123456789012:trail/management-events",
      "aws:s3:arn": "arn:aws:s3:::amzn-s3-demo-logging-bucket-123456789012-9af1fb49/AWSLogs/123456789012/CloudTrail/us-east-1/2024/12/06/123456789012_CloudTrail_us-east-1_20241206T2010Z_T0500LMG1hIQ1png.json.gz"
    }
  },
  "responseElements": null,
  "requestID": "a0555e85-7e8a-4765-bd8f-2222295558e1",
  "eventID": "e4f3557e-7dbd-4e37-a00a-d86c137d1111",
  "readOnly": true,
  "resources": [
    {
      "accountId": "123456789012",
      "type": "AWS::KMS::Key",
      "ARN": "arn:aws:kms:us-east-1:123456789012:key/example1-6736-4661-bf00-exampleeb770"
    }
  ]
}
```

```
    }],  
    "eventType": "AwsApiCall",  
    "managementEvent": true,  
    "recipientAccountId": "123456789012",  
    "sharedEventID": "ce71d6be-0846-498e-851f-111a1af9078f",  
    "eventCategory": "Management"  
}
```

CloudTrail puts a log file into your S3 bucket

Each time CloudTrail puts a log file into your S3 bucket, Amazon S3 sends a [GenerateDataKey](#) request to AWS KMS on behalf of CloudTrail. In response to this request, AWS KMS generates a unique data key and then sends Amazon S3 two copies of the data key, one in plaintext and one that is encrypted with the specified KMS key. Amazon S3 uses the plaintext data key to encrypt the CloudTrail log file and then removes the plaintext data key from memory as soon as possible after use. Amazon S3 stores the encrypted data key as metadata with the encrypted CloudTrail log file.

The `GenerateDataKey` request includes the following information for the [encryption context](#):

- The [Amazon Resource Name \(ARN\)](#) of the CloudTrail trail
- The ARN of the S3 object (the CloudTrail log file)

Each `GenerateDataKey` request results in an entry in your CloudTrail logs similar to the following example. When you see a log entry like this one, you can determine that CloudTrail called the AWS KMS `GenerateDataKey` operation for a specific trail to protect a specific log file. AWS KMS created the data key under the specified KMS key, shown twice in the same log entry.

```
{  
  "eventVersion": "1.09",  
  "userIdentity": {  
    "type": "AWSService",  
    "invokedBy": "cloudtrail.amazonaws.com"  
  },  
  "eventTime": "2024-12-06T21:49:28Z",  
  "eventSource": "kms.amazonaws.com",  
  "eventName": "GenerateDataKey",  
  "awsRegion": "us-east-1",  
  "sourceIPAddress": "cloudtrail.amazonaws.com",  
  "userAgent": "cloudtrail.amazonaws.com",  
  "requestParameters": {
```

```

    "encryptionContext": {
      "aws:cloudtrail:arn": "arn:aws:cloudtrail:us-east-1::trail/insights-trail",
      "aws:s3:arn": "arn:aws:s3:::amzn-s3-demo-logging-
bucket1-123456789012-7867ab0c/AWSLogs/123456789012/CloudTrail/us-
east-1/2024/12/06/123456789012_CloudTrail_us-
east-1_20241206T2150Z_hVXmrJzjZk2wAM2V.json.gz"
    },
    "keySpec": "AES_256",
    "keyId": "arn:aws:kms:us-east-1:123456789012:key/example9-16ef-48ba-9163-
example67a5a"
  },
  "responseElements": null,
  "requestID": "11117d14-9232-414a-b3d1-01bab4dc9f99",
  "eventID": "999e9a50-512c-4e2a-84a3-111a5f511111",
  "readOnly": true,
  "resources": [
    {
      "accountId": "123456789012",
      "type": "AWS::KMS::Key",
      "ARN": "arn:aws:kms:us-east-1:123456789012:key/example9-16ef-48ba-9163-
example67a5a"
    }
  ],
  "eventType": "AwsApiCall",
  "managementEvent": true,
  "recipientAccountId": "123456789012",
  "sharedEventID": "5e663acc-b7fd-4cdd-8328-0eff862952fa",
  "eventCategory": "Management"
}

```

You get an encrypted log file from your S3 bucket

Each time you get an encrypted CloudTrail log file from your S3 bucket, Amazon S3 sends a [Decrypt](#) request to AWS KMS on your behalf to decrypt the log file's encrypted data key. In response to this request, AWS KMS uses your KMS key to decrypt the data key and then sends the plaintext data key to Amazon S3. Amazon S3 uses the plaintext data key to decrypt the CloudTrail log file and then removes the plaintext data key from memory as soon as possible after use.

The Decrypt request includes the following information for the [encryption context](#):

- The [Amazon Resource Name \(ARN\)](#) of the CloudTrail trail
- The ARN of the S3 object (the CloudTrail log file)

Each Decrypt request results in an entry in your CloudTrail logs similar to the following example. When you see a log entry like this one, you can determine that an assumed role called the AWS KMS Decrypt operation for a specific trail and a specific log file. AWS KMS decrypted the data key under a specific KMS key.

```
{
  "eventVersion": "1.09",
  "userIdentity": {
    "type": "AssumedRole",
    "principalId": "AIDACKCEVSQ6C2EXAMPLE",
    "arn": "arn:aws:sts::123456789012:assumed-role/Admin",
    "accountId": "123456789012",
    "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
    "sessionContext": {
      "sessionIssuer": {
        "type": "Role",
        "principalId": "AIDACKCEVSQ6C2EXAMPLE",
        "arn": "arn:aws:iam::123456789012:role/Admin",
        "accountId": "123456789012",
        "userName": "Admin"
      },
      "attributes": {
        "creationDate": "2024-12-06T22:04:04Z",
        "mfaAuthenticated": "false"
      }
    },
    "invokedBy": "AWS Internal"
  },
  "eventTime": "2024-12-06T22:26:34Z",
  "eventSource": "kms.amazonaws.com",
  "eventName": "Decrypt",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "AWS Internal",
  "userAgent": "AWS Internal",
  "requestParameters": {
    "encryptionContext": {
      "aws:cloudtrail:arn": "arn:aws:cloudtrail:us-east-1:123456789012:trail/insights-trail",
      "aws:s3:arn": "arn:aws:s3:::amzn-s3-demo-logging-bucket1-123456789012-7867ab0c/AWSLogs/123456789012/CloudTrail/us-east-1/2024/12/06/123456789012_CloudTrail_us-east-1_20241206T0000Z_aAAsHbGBdye3jp2R.json.gz"
    }
  },
}
```

```
    "encryptionAlgorithm": "SYMMETRIC_DEFAULT"
  },
  "responseElements": null,
  "requestID": "1ab2d2d2-111a-2222-a59b-11a2b3832b53",
  "eventID": "af4d4074-2849-4b3d-1a11-a1aaa111a111",
  "readOnly": true,
  "resources": [
    {
      "accountId": "123456789012",
      "type": "AWS::KMS::Key",
      "ARN": "arn:aws:kms:us-east-1:123456789012:key/example9-16ef-48ba-9163-  
example67a5a"
    }
  ],
  "eventType": "AwsApiCall",
  "managementEvent": true,
  "recipientAccountId": "123456789012",
  "eventCategory": "Management",
  "sessionCredentialFromConsole": "true"
}
```


Document history

The following table describes the important changes to the documentation for AWS CloudTrail. For notification about updates to this documentation, you can subscribe to an RSS feed.

- **API version:** 2013-11-01
-

Change	Description	Date
Added functionality	You can now log additional CloudTrail network activity events. For more information, see Network activity events .	October 15, 2025
Added functionality	You can now log additional CloudTrail data events for Amazon Bedrock Amazon Elastic Container Service, and Amazon Quick Suite. For more information, see Data events .	October 15, 2025
Added functionality	You can now log additional CloudTrail network activity events. For more information, see Network activity events .	September 15, 2025
Added functionality	You can now log additional CloudTrail data events for Amazon Q Business, Amazon Quick Suite, Amazon SageMaker AI, Amazon Bedrock, Amazon Elastic Compute Cloud, and Amazon Kinesis Video Streams. For	September 12, 2025

more information, see [Data events](#).

[Added functionality](#)

You can now log additional CloudTrail data events for Amazon Aurora DSQL, Amazon Bedrock, Amazon Elastic Kubernetes Service, Amazon S3, and Amazon Keyspaces (for Apache Cassandra). For more information, see [Data events](#).

July 1, 2025

[Added service support](#)

This release supports Logging Multi-party approval API calls. For more information, see [CloudTrail supported services and integrations](#).

June 17, 2025

[Added functionality](#)

Logging Amazon S3 data event DeleteObject operations now includes information about all individual objects deleted by the call. You can choose to filter out this additional information. For more information, see [AWS CLI examples for filtering data events](#).

June 9, 2025

[Added functionality](#)

You can now log network activity events for additional services. For more information, see [Network activity events](#).

May 30, 2025

[New functionality](#)

You can now enrich CloudTrail management events and data events in order to enhance results when you categorize, search, and analyze CloudTrail events. For more information, see [Enrich CloudTrail events by adding resource tag keys and IAM global condition keys](#).

May 29, 2025

[New functionality](#)

Added documentation and policy information for the `AWSServiceRoleForCloudTrailEventContext` service linked role. For more information, see [Using roles for creating and managing CloudTrail event context in CloudTrail](#).

May 29, 2025

[Added functionality](#)

You can now encrypt both log files and digest files with AWS KMS keys (SSE-KMS). For more information, see [Encrypting CloudTrail log files with AWS KMS keys \(SSE-KMS\)](#).

May 22, 2025

[Added functionality](#)

You can now use additional advanced event selectors and predefined templates to log data events to your trail. For more information, see [Data events](#).

April 10, 2025

Added functionality	You can now log network activity events for AWS Lambda and Amazon Comprehend. For more information, see Network activity events .	April 10, 2025
Added functionality	You can now log CloudTrail data events on Amazon Simple Email Service configuration sets, email identities, and templates. For more information, see Data events .	April 10, 2025
Added functionality	AWS CloudTrail now supports VPC endpoint policies. For more information, see Using AWS CloudTrail with Amazon VPC endpoints .	April 9, 2025
Added functionality	You can now log CloudTrail network activity events for AWS IoT FleetWise.	April 8, 2025
Added functionality	You can now log CloudTrail data events on Amazon Bedrock sessions by using advanced event selectors. For more information, see Data events .	March 19, 2025

Updated documentation	Updated the SQL schema for CloudTrail Lake Insights events. Added new topics to describe the Insights event record fields for trails and event data stores . For more information about the supported SQL schema for CloudTrail Lake Insights events, see Supported schema for CloudTrail Insights event record fields .	March 13, 2025
Added functionality	You can now log CloudTrail data events on Amazon GameLift Streams applications and stream groups by using advanced event selectors. For more information, see Data events .	March 7, 2025
Added service support	This release supports Managed integrations for AWS IoT Device Management. For more information, see AWS service topics for CloudTrail .	March 3, 2025
Added functionality	You can now log CloudTrail data events on Amazon Pinpoint mobile targeting applications by using advanced event selectors. For more information, see Data events .	February 24, 2025

General availability of network activity events	Network activity events are now generally available. For more information, see Logging network activity events .	February 13, 2025
Updated documentation	Added Understanding multi-Region trails and opt-in Regions topic to describe multi-Region trails and opt-in Regions.	February 10, 2025
Added functionality	You can now log CloudTrail data events on Amazon Timestream regional endpoints by using advanced event selectors. For more information, see Data events .	January 31, 2025
Added functionality	You can now log CloudTrail data events on Amazon Bedrock prompts and AWS Step Functions activities by using advanced event selectors. For more information, see Data events .	January 24, 2025
Updated documentation	Added Optimize CloudTrail Lake queries topic to provide guidance about how to optimize CloudTrail Lake queries to improve performance and reliability. This topic covers specific optimization techniques as well as workarounds for common query failures.	January 22, 2025

New Region support	CloudTrail expanded support to a new Region, the Mexico (Central) Region. For more information, see CloudTrail supported Regions .	January 13, 2025
New Region support	CloudTrail expanded support to a new Region, the Asia Pacific (Thailand) Region. For more information, see CloudTrail supported Regions .	January 7, 2025
Added functionality	You can now log CloudTrail data events on AWS Backup search jobs by using advanced event selectors. For more information, see Data events .	December 30, 2024
Updated documentation	Converted the Logging Insights events topic into a chapter named Working with CloudTrail Insights . The chapter includes new sections about Insights events costs and viewing Insights events for event data stores .	December 23, 2024
Support for IPv6	CloudTrail adds support for IPv6.	December 20, 2024
Added functionality	You can now log CloudTrail data events on AWS Signer signing jobs and profiles by using advanced event selectors. For more information, see Data events .	December 20, 2024

Updated documentation	Updated CloudTrail supported services and integrations section to include descriptions of the AWS Config, AWS Audit Manager, and Amazon Athena integrations with CloudTrail Lake.	December 18, 2024
Added service support	This release supports AWS Migration Hub Journeys. For more information, see AWS service topics for CloudTrail and Logging AWS Migration Hub Journeys API calls with AWS CloudTrail .	December 3, 2024
Added service support	This release supports Oracle Database@AWS. For more information, see AWS service topics for CloudTrail and Logging Oracle Database@AWS API Calls with AWS CloudTrail .	December 1, 2024
Added service support	This release supports AWS Security Incident Response. For more information, see AWS service topics for CloudTrail and Logging AWS Security Incident Response API calls using AWS CloudTrail .	December 1, 2024

Added functionality

CloudTrail Lake adds support for custom dashboards, the Highlights dashboard, and new managed dashboards. You can create custom dashboards and add up to 10 widgets to each custom dashboard. You can enable the Highlights dashboard to view an at-a-glance overview of the AWS activity collected by the event data stores in your account. For more information, see [CloudTrail Lake dashboards](#).

November 21, 2024

Added functionality

CloudTrail Lake adds support for resource-based policies on event data stores. You can use resource-based policies to provide cross-account access to allow selected principals to query your event data store, list and cancel queries, and view query results. For more information, see [Resource-based policy examples for event data stores](#).

November 21, 2024

Added functionality

You can now log CloudTrail data events on AWS AppSync GraphQL APIs by using advanced event selectors. For more information, see [Data events](#).

November 19, 2024

Added functionality	You can now log CloudTrail data events on AWS IoT SiteWise Assistant conversations by using advanced event selectors. For more information, see Data events .	November 18, 2024
Added functionality	You can now log CloudTrail data events on AWS End User Messaging SMS messages by using advanced event selectors. For more information, see Data events .	November 15, 2024
Added functionality	Added support for assumedRoot field for the sessionContext of the userIdentity element. For more information, see CloudTrail userIdentity element in this guide and Track privileged tasks in CloudTrail in the <i>IAM User Guide</i> .	November 14, 2024
General availability of CloudTrail Lake query assistant	The CloudTrail Lake query assistant is now generally available. The query assistant allows you to create SQL queries from natural language prompts in English. For more information, see Create CloudTrail Lake queries from natural language prompts .	November 12, 2024

Added functionality

Introducing a preview feature for CloudTrail Lake queries that uses generative artificial intelligence (generative AI) capabilities to summarize query results. For more information, see [Summarize query results in natural language](#).

November 12, 2024

Added functionality

November 11, 2024

You can now configure additional advanced event selector fields for CloudTrail Lake event data stores, which gives you greater control over which CloudTrail events are ingested into your event data stores. You can filter management events on the following advanced event selector fields: `eventName` (new), `eventSource`, `eventType` (new), `readOnly`, `sessionCredentialFromConsole` (new), and `userIdentity.arn` (new). You can filter data events on the following advanced event selector fields: `eventName`, `eventSource` (new), `eventType` (new), `resources.type`, `resources.ARN`, `readOnly`, `sessionCredentialFromConsole` (new), and `userIdentity.arn` (new). For more information, see [Create an event data store for CloudTrail events with the console](#) (steps 16 and 17).

Updated event version	Updated eventVersion to 1.11 and added inScopeOf field for the userIdentity element. For more information, see CloudTrail userIdentity element .	October 29, 2024
Added service support	This release supports AWS End User Messaging SMS. For more information, see AWS service topics for CloudTrail and Logging AWS End User Messaging SMS API calls using AWS CloudTrail .	October 22, 2024
Added functionality	You can now log CloudTrail data events on AWS End User Messaging SMS origination identities by using advanced event selectors. For more information, see Data events .	October 22, 2024
Added service support	This release supports AWS End User Messaging Social. For more information, see AWS service topics for CloudTrail and Logging AWS End User Messaging Social API calls using AWS CloudTrail .	October 10, 2024

[Added functionality](#)

You can now log CloudTrail data events on AWS End User Messaging Social phone number IDs by using advanced event selectors. For more information, see [Data events](#).

October 10, 2024

[Added functionality](#)

You can now log CloudTrail data events on Amazon Bedrock models and AWS Data Exchange assets by using advanced event selectors. For more information, see [Data events](#).

September 27, 2024

[Added functionality](#)

You can now configure trails and event data stores to log CloudTrail network activity events (in preview). Network activity events enable VPC endpoint owners to record AWS API calls made using their VPC endpoints from a private VPC to the AWS service. This release supports network activity events logging for the following event sources: `cloudtrail.amazonaws.com` , `ec2.amazonaws.com` , `kms.amazonaws.com` , and `secretsmanager.amazonaws.com` . For more information, see [Logging network activity events](#).

September 24, 2024

Added service support	This release supports AWS Directory Service Data. For more information, see AWS service topics for CloudTrail and Logging AWS Directory Service Data API calls using AWS CloudTrail .	September 18, 2024
New Region support	CloudTrail expanded support to a new Region, the Asia Pacific (Malaysia) Region. For more information, see CloudTrail supported Regions .	August 22, 2024
Added functionality	You can now log CloudTrail data events on Amazon CloudWatch RUM app monitors by using advanced event selectors. For more information, see Data events .	July 25, 2024
Added functionality	You can now control access to trails using tags. For more information, see ABAC with CloudTrail .	July 23, 2024
Added functionality	You can now log CloudTrail data events on Amazon One Enterprise users and UKeys by using advanced event selectors. For more information, see Data events .	July 23, 2024

[Added functionality](#)

You can now log CloudTrail data events on Amazon Bedrock flow aliases and guardrails, and Amazon S3 object-level API activity on directory buckets by using advanced event selectors. For more information, see [Data events](#).

July 9, 2024

[Added functionality](#)

You can now log CloudTrail data events on AWS Payment Cryptography keys and aliases by using advanced event selectors. For more information, see [Data events](#).

July 5, 2024

[Added functionality](#)

Introducing a preview feature for CloudTrail Lake queries that uses generative artificial intelligence (generative AI) capabilities to produce a SQL query from an English language prompt. For more information, see [Create CloudTrail Lake queries from English language prompts](#).

June 11, 2024

[Added functionality](#)

You can now log CloudTrail data events on Amazon CloudWatch metrics, Amazon Machine Learning ML models, and AWS Private CA by using advanced event selectors. For more information, see [Data events](#).

June 5, 2024

Updated documentation	Added section to describe how to filter data events by using advanced event selectors. For more information, see Filtering data events by using advanced event selectors .	May 29, 2024
Added functionality	You can now log CloudTrail data events on Amazon Kinesis Data Streams streams and stream consumers by using advanced event selectors. For more information, see Data events .	May 21, 2024
Updated documentation	Updated the CloudTrail Lake supported Regions page to add the Asia Pacific (Hyderabad) Region (ap-south-2), the Europe (Zurich) Region (eu-central-2), and the Israel (Tel Aviv) Region (il-central-1).	May 16, 2024
Added functionality	You can now log CloudTrail data events on AWS Step Functions state machines by using advanced event selectors. For more information, see Data events .	May 16, 2024

[Updated documentation](#)

Added section about viewing CloudTrail cost and usage using AWS Cost Explorer. For more information, see [Viewing your CloudTrail cost and usage with AWS Cost Explorer](#).

May 14, 2024

[Added functionality](#)

You can now log CloudTrail data events on Amazon Q Apps by using advanced event selectors. For more information, see [Data events](#).

May 1, 2024

[Updated documentation](#)

General organizational improvements to user guide sections and page titles, which includes the following:

- Changed title of CloudTrail log event reference page to [Understanding CloudTrail events](#) and added descriptions of management events, data events, and Insights events.
- Changed title of Settings page to [Configure CloudTrail settings](#).
- Moved [Logging data events](#), [Logging management events](#), and [Logging Insights events](#) pages to the Understanding CloudTrail events section.
- Moved [CloudTrail log file examples](#) page to the [CloudTrail log files](#) section.
- Added separate pages to list the AWS CLI commands for CloudTrail Lake [event data stores](#), [queries](#), and [integrations](#).

April 10, 2024

[Updated documentation](#)

Updated the [CloudTrail Lake supported Regions](#) page to add the Europe (Spain) Region (eu-south-2).

April 10, 2024

Added service support	This release supports AWS Control Catalog. For more information, see AWS service topics for CloudTrail and Logging AWS Control Catalog API calls using AWS CloudTrail .	April 8, 2024
Added service support	This release supports AWS Deadline Cloud. For more information, see AWS service topics for CloudTrail .	April 2, 2024
Updated event version	The AWS CloudTrail event version is now 1.10. For more information, see CloudTrail record contents .	March 26, 2024
Added service support	This release supports AWS Billing Conductor. For more information, see AWS service topics for CloudTrail and Logging AWS Billing Conductor API calls using AWS CloudTrail .	March 12, 2024
Added functionality	You can now log CloudTrail data events on AWS X-Ray traces and AWS Systems Manager managed nodes by using advanced event selectors. For more information, see Data events .	March 7, 2024

Added functionality	You can now log CloudTrail data events on Amazon Simple Workflow Service (Amazon SWF) domains by using advanced event selectors. For more information, see Data events .	February 14, 2024
Added functionality	CloudTrail added the <code>ListInsightsMetricData</code> API. The <code>ListInsightsMetricData</code> API returns Insights metrics data for trails that have enabled Insights. For more information, see ListInsightsMetricData in the <i>AWS CloudTrail API Reference</i> .	February 6, 2024
Added functionality	You can now log CloudTrail data events for AWS IoT, AWS IoT SiteWise, and AWS AppConfig by using advanced event selectors. For more information, see Data events .	January 4, 2024
Added functionality	You can now log CloudTrail data events for AWS IoT Greengrass by using advanced event selectors. For more information, see Data events .	December 22, 2023
New Region support	CloudTrail expanded support to a new Region, the Canada West (Calgary) Region. For more information, see CloudTrail supported Regions .	December 20, 2023

Added functionality	You can now log CloudTrail data events for Amazon Keyspaces (for Apache Cassandra), AWS IoT TwinMaker, Amazon RDS, and AWS Supply Chain by using advanced event selectors. For more information, see Data events .	December 20, 2023
Updated AWS managed policy	Updated the CloudTrail ServiceRolePolicy managed policy to allow the following actions on an organization event data store when federation is disabled: <code>glue:DeleteTable</code> and <code>lakeformation:DeregisterResource</code> .	November 26, 2023
Added functionality	You can now federate a CloudTrail Lake event data store to see the metadata associated with the event data store in the AWS Glue Data Catalog and run SQL queries on the event data using Amazon Athena. The table metadata stored in the AWS Glue Data Catalog lets the Athena query engine know how to find, read, and process the data that you want to query. For more information, see Federate an event data store .	November 26, 2023

Added functionality

You can now log CloudTrail data events for AWS Cloud Map by using advanced event selectors. For more information, see [Logging data events](#).

November 16, 2023

Added functionality

You can now log CloudTrail data events on Amazon SQS messages by using advanced event selectors. For more information, see [Logging data events](#).

November 16, 2023

Added functionality

CloudTrail Lake now offers two pricing options for event data stores: one-year extendable retention pricing and seven-year retention pricing. The pricing option determines the cost for ingesting and storing events, and the default and maximum retention period for the event data store. Before this release, all event data stores used the seven-year retention pricing option. You can switch an event data store from using the seven-year retention pricing option to using the one-year extendable retention pricing by using the [CloudTrail console](#), [AWS CLI](#), or the [UpdateEventDataStore](#) API operation. For more information about pricing options, see [AWS CloudTrail Pricing](#) and [Event data store pricing options](#).

November 15, 2023

Added functionality

You can now collect Insights events in CloudTrail Lake. AWS CloudTrail Insights help AWS users identify and respond to unusual activity associated with API call rates and API error rates by continuously analyzing CloudTrail management events. To collect Insights events in CloudTrail Lake, you need a source event data store that logs management events and enables Insights and a destination event data store that collects Insights events based upon unusual management event activity in the source event data store. For more information, see [Create an event data store for CloudTrail Insights events](#) and [Logging Insights events](#).

November 9, 2023

Added service support

This release supports AWS Launch Wizard. For more information, see [AWS service topics for CloudTrail](#) and [Logging AWS Launch Wizard API calls using AWS CloudTrail](#).

November 8, 2023

Added service support	This release supports Amazon Bedrock. For more information, see AWS service topics for CloudTrail and Log Amazon Bedrock API calls using AWS CloudTrail .	October 23, 2023
Added functionality	You can now log CloudTrail data events on Amazon CodeWhisperer customizations by using advanced event selectors. For more information, see Logging data events .	October 18, 2023
Added functionality	You can now log CloudTrail data events on Amazon Timestream databases and tables by using advanced event selectors. For more information, see Logging data events .	September 28, 2023
Added functionality	You can now log CloudTrail data events on Amazon SNS topics and platform endpoints by using advanced event selectors. For more information, see Logging data events .	September 28, 2023

[Updated documentation](#)

Added table to show the tasks that the management account, delegated administrator accounts, and member accounts within an AWS Organizations organization can perform in CloudTrail. For more information, see [Organization delegated administrator](#).

September 25, 2023

[Added service support](#)

This release supports AWS Marketplace Agreements. For more information, see [AWS service topics for CloudTrail](#) and [Logging Agreements API Calls using AWS CloudTrail](#).

September 1, 2023

[Added functionality](#)

You can now log CloudTrail data events on Amazon Kinesis video streams and Amazon SageMaker AI endpoints by using advanced event selectors. For more information, see [Logging data events](#).

August 31, 2023

[Added service support](#)

This release supports AWS Application Transformation Service. AWS Application Transformation Service is a backend service used by services like AWS Microservice Extractor for .NET. For more information, see [CloudTrail supported services and integrations](#).

August 26, 2023

Added functionality	You can now log CloudTrail data events on AWS Private CA Connector for Active Directory by using advanced event selectors. For more information, see Logging data events .	August 24, 2023
Updated documentation	Added new CloudTrail Lake scenarios to show how to create event data stores, view CloudTrail Lake dashboards, copy trail events to an event data store, view and run sample queries, and save query results to an Amazon S3 bucket using the AWS Management Console. For more information, see Scenarios for CloudTrail Lake	August 16, 2023
New Region support	CloudTrail expanded support to a new Region, the Israel (Tel Aviv) Region. For more information, see CloudTrail supported Regions .	August 1, 2023
Added service support	This release supports AWS HealthImaging. For more information, see CloudTrail supported services and integrations and Logging AWS HealthImaging API calls using AWS CloudTrail .	July 26, 2023

Added functionality	You can now log CloudTrail data events on AWS HealthImaging data stores by using advanced event selectors. For more information, see Logging data events .	July 26, 2023
Added functionality	You can now log CloudTrail data events on AWS Systems Manager control channels and Amazon Managed Blockchain networks by using advanced event selectors. For more information, see Logging data events .	June 21, 2023
Added functionality	You can now verify your CloudTrail Lake saved query results using the aws cloudtrail verify-query-results command. For more information, see Validate saved query results with the AWS CLI .	June 21, 2023
Added service support	This release supports Amazon Verified Permissions. For more information, see CloudTrail supported services and integrations and Logging Amazon Verified Permissions API calls using AWS CloudTrail .	June 13, 2023

Added functionality	You can now use CloudTrail Lake dashboards to visualize the events in an event data store. For more information, see View Lake dashboards .	June 13, 2023
Added functionality	You can now log CloudTrail data events on Amazon Verified Permissions policy stores by using advanced event selectors. For more information, see Logging data events .	June 13, 2023
Added functionality	You can now log CloudTrail data events on an Amazon CodeWhisperer profile by using advanced event selectors. For more information, see Logging data events .	June 6, 2023
Added functionality	You can now start and stop event ingestion on CloudTrail event data stores. For information about stopping event ingestion using the console, see Stop an event data store from ingesting events . For information about stopping event ingestion using the AWS CLI, see Stop ingestion on an event data store .	June 2, 2023

Added functionality	You can now log CloudTrail data events on an Amazon EMR write-ahead log workspace by using advanced event selectors. For more information, see Logging data events .	May 31, 2023
Added service support	This release supports Amazon Security Lake. For more information, see CloudTrail supported services and integrations and Logging Amazon Security Lake API calls using AWS CloudTrail .	May 30, 2023
Updated event version	The eventVersion is now 1.09.	May 23, 2023
Updated documentation	Updated CloudTrail userIdentity element topic to include an example and field descriptions for a request made on behalf of an IAM Identity Center user. For more information, see CloudTrail userIdentity element .	May 23, 2023
Updated documentation	This update supports the following patch release for the CloudTrail Processing Library: aws-cloudtrail-processing-library-1.6.1.jar. For more information, see Using the CloudTrail Processing Library and the CloudTrail Processing Library on GitHub.	May 23, 2023

Added functionality	CloudTrail Lake now supports all Presto functions and operators. For more information, see CloudTrail Lake SQL constraints .	May 9, 2023
Added functionality	You can now log CloudTrail data events on an Amazon GuardDuty detector by using advanced event selectors. For more information, see Logging data events and Logging Amazon GuardDuty API calls with AWS CloudTrail .	March 30, 2023
Updated documentation	Added new section about creating user-defined cost allocation tags for event data stores. For more information, see Creating user-defined cost allocation tags for CloudTrail Lake event data stores .	March 24, 2023
Added service support	This release supports AWS Telco Network Builder (AWS TNB). For more information, see CloudTrail supported services and integrations and Logging AWS Telco Network Builder API calls using AWS CloudTrail .	February 21, 2023

Added functionality	You can now log CloudTrail data events on Amazon Cognito identity pools by using advanced event selectors. For more information, see Logging data events .	February 15, 2023
Updated documentation	Added new section about the learning resources available for CloudTrail Lake. For more information, see Learning resources .	February 9, 2023
Added functionality	You can now create CloudTrail Lake integrations with event sources outside of AWS. You can log and store user activity data from any source in your hybrid environments, such as in-house or SaaS applications hosted on-premises or in the cloud, virtual machines, or containers. For more information, see Create an integration with an event source outside of AWS .	January 31, 2023
Added functionality	You can now log CloudTrail data events on CloudTrail PutAuditEvents activity on a CloudTrail Lake channel by using advanced event selectors. For more information, see Logging data events .	January 31, 2023

New Region support	CloudTrail expanded support to a new Region, the Asia Pacific (Melbourne) Region. For more information, see CloudTrail supported Regions .	January 24, 2023
Updated documentation	Added new section about managing data consistency in CloudTrail, see Managing data consistency in CloudTrail .	January 18, 2023
Added functionality	You can now log CloudTrail data events on Amazon SageMaker AI feature stores by using advanced event selectors. For more information, see Logging data events .	December 27, 2022
Added service support	This release supports AWS Marketplace Discovery. See AWS CloudTrail Supported Services and Integrations .	December 15, 2022
Added functionality	You can now log CloudTrail data events on Amazon SageMaker AI metrics experiment trial components by using advanced event selectors. For more information, see Logging data events .	December 15, 2022

Added functionality	You can now create an event data store to include AWS Config configuration items, and use the event data store to investigate non-compliant changes to your production environments. For more information, see Create an event data store for AWS Config configuration items .	November 28, 2022
New Region support	CloudTrail expanded support to a new Region, the Asia Pacific (Hyderabad) Region. For more information, see CloudTrail supported Regions .	November 22, 2022
Added functionality	You can now log CloudTrail data events on Amazon FinSpace environments by using advanced event selectors. For more information, see Logging data events .	November 18, 2022
New Region support	CloudTrail expanded support to a new Region, the Europe (Spain) Region. For more information, see CloudTrail supported Regions .	November 16, 2022
New Region support	CloudTrail expanded support to a new Region, the Europe (Zurich) Region. For more information, see CloudTrail supported Regions .	November 9, 2022

[Added functionality](#)

The management account for an AWS Organizations organization can now add a delegated administrator to manage the organization's CloudTrail trails and event data stores. For more information, see [Organization delegated administrator](#).

November 7, 2022

[Added functionality](#)

You can now enable AWS Key Management Service encryption for a CloudTrail Lake event data store. For more information, see [Create an event data store](#).

November 7, 2022

[Added functionality](#)

You can now save CloudTrail Lake query results to an Amazon S3 bucket when you run a query. For more information about running a query, see [Run a query and save query results](#). For more information about downloading query results, see [Get and download saved query results](#).

October 21, 2022

[Added functionality](#)

You can now copy CloudTrail trail events to a CloudTrail Lake event data store. For more information, see [Copying trail events to CloudTrail Lake](#).

September 19, 2022

Updated documentation	Added list of supported Amazon CloudWatch metrics for CloudTrail Lake. For more information, see Supported CloudWatch metrics .	September 16, 2022
Added functionality	You can now view CloudTrail service-linked channels using the AWS CLI. For more information, see Viewing service-linked channels for CloudTrail by using the AWS CLI .	September 9, 2022
New Region support	CloudTrail expanded support to a new Region, the Middle East (UAE) Region. For more information, see CloudTrail supported Regions .	August 30, 2022
Changed functionality	CloudTrail has changed the name of the managed policy <code>AWSCloudTrailReadOnlyAccess</code> to <code>AWSCloudTrail_ReadOnlyAccess</code> . Permissions in this policy have been scoped down. By default, the policy no longer grants permission to list all Amazon S3 buckets, AWS Lambda functions, or AWS KMS aliases. For more information, see Read-only access .	June 6, 2022

[Changed functionality](#)

As a security best practice, you can now add an `aws:SourceArn` or `aws:SourceAccount` condition key to an `s3:GetBucketAcl` ACL checking block in Amazon S3 bucket policies. For more information, see [Configure Amazon S3 bucket policies for CloudTrail](#).

May 11, 2022

[Changed functionality](#)

Starting Feb 24, 2022, AWS CloudTrail began changing the `userAgent` and `sourceIPAddress` field values in any event that originated from an AWS Management Console session where a proxy client was used. For these events, CloudTrail replaces the values of the `userAgent` and `sourceIPAddress` fields with `AWS Internal`. CloudTrail made this change to standardize how it logs information for service actions across all AWS services. For more information, see [CloudTrail record contents](#).

April 12, 2022

[Added service support](#)

This release supports Amazon GameSparks. See [AWS CloudTrail Supported Services and Integrations](#).

March 24, 2022

Added service support

This release supports AWS App Mesh Envoy Management Service. See [AWS CloudTrail Supported Services and Integrations](#).

March 18, 2022

Updated documentation

New query examples have been added for CloudTrail Lake, a new feature that lets you run fine-grained, multiple-field SQL queries on your events. Also, a new field, `BytesScanned`, has been added to the query metadata results of `DescribeQuery` and `GetQueryResults` operations. For more information, see [Working with CloudTrail Lake](#).

March 4, 2022

[Changed functionality](#)

CloudTrail now removes the account ID of the Amazon S3 bucket owner in the `resources` block of a data event if both of the following conditions are met: the data event API call is from a different AWS account than the Amazon S3 bucket owner, and the API caller received an `AccessDenied` error that was only for the caller account. For more information, see [Redacting bucket owner account IDs for data events called by other accounts](#).

March 3, 2022

[Updated documentation](#)

This update supports the following release for the CloudTrail Processing Library: Added support for implementing a custom S3 manager, event logging to log file parsing-related exceptions, support for parsing an optional `errorCode` field in `insightDetails`, and updated the account ID parsing regex to accept non-numerical values. For more information, see [Using the CloudTrail Processing Library](#) and the [CloudTrail Processing Library](#) on GitHub.

January 28, 2022

Added functionality	CloudTrail introduces CloudTrail Lake, a new feature that lets you run fine-grained, multiple-field SQL queries on your events. Events are aggregated into event data stores, which are immutable collections of events based on criteria that you select by applying advanced event selectors. For more information, see Working with CloudTrail Lake .	January 5, 2022
New Region support	CloudTrail expanded support to a new Region, the Asia Pacific (Jakarta) Region. For more information, see CloudTrail supported Regions .	December 13, 2021
Added service support	This release supports Amazon WorkSpaces Web. See AWS CloudTrail Supported Services and Integrations .	December 3, 2021
Added functionality	You can now log CloudTrail data events on AWS Glue tables created by Lake Formation by using advanced event selectors. For more information, see Logging data events .	November 30, 2021

Changed functionality	As a security best practice, you can now add an <code>aws:SourceArn</code> or <code>aws:SourceAccount</code> condition key to AWS KMS key policies and Amazon S3 bucket policies. For more information, see Configure AWS KMS key policies for CloudTrail and Configure Amazon S3 bucket policies for CloudTrail .	November 15, 2021
Added service support	This release supports AWS Resilience Hub. See AWS CloudTrail Supported Services and Integrations .	November 10, 2021
Added functionality	A new CloudTrail Insights event type is available: error rate Insights events. An error rate Insights event captures unusual activity on an error that occurs on APIs called in your account. For more information, see Logging Insights events for trails .	November 10, 2021
Added functionality	You can now log CloudTrail data events on DynamoDB streams by using advanced event selectors. For more information, see Logging data events .	September 22, 2021

Added functionality	You can now log data events on Amazon S3 access points. You can log Amazon S3 access point data events by using advanced event selectors. For more information, see Logging data events.	August 24, 2021
Changed functionality	When you configure a trail to send notifications to Amazon SNS, CloudTrail adds a policy statement to your SNS topic access policy that allows CloudTrail to send content to an SNS topic. As a security best practice, we recommend adding an <code>aws:SourceArn</code> or <code>aws:SourceAccount</code> condition key to the CloudTrail policy statement. For more information, see Amazon SNS topic policy for CloudTrail.	August 16, 2021
Added service support	This release supports Amazon Route 53 Application Recovery Controller. See AWS CloudTrail Supported Services and Integrations.	July 27, 2021
Added functionality	You can now log data events on Amazon EBS direct APIs run on EBS snapshots. You can log Amazon EBS direct API data events by using advanced event selectors. For more information, see Logging data events.	July 27, 2021

[Changed functionality](#)

When CloudTrail processes data events, it preserves numbers in their original format, whether that is an integer (int) or a float. In events that have integers in the fields of a data event, CloudTrail historically processed these numbers as floats. Now, CloudTrail keeps the original format of integers in data events. For more information, see [Using the CloudTrail Processing Library](#).

July 13, 2021

[Added functionality](#)

You can now exclude Amazon RDS Data API management events from your trails. For more information, see [Logging management events for trails](#).

July 1, 2021

[Added service support](#)

This release supports AWS BugBust. See [AWS CloudTrail Supported Services and Integrations](#).

June 24, 2021

[Added service support](#)

This release supports Amazon Managed Grafana and Amazon Managed Service for Prometheus. See [AWS CloudTrail Supported Services and Integrations](#).

June 2, 2021

Added service support	This release supports AWS App Runner. See AWS CloudTrail Supported Services and Integrations .	May 18, 2021
Added service support	This release supports AWS Systems Manager Incident Manager. See AWS CloudTrail Supported Services and Integrations .	May 10, 2021
Updated documentation	This update describes data event logging requirements for AWS Config conformance packs, especially for compliance frameworks such as HIPAA or FedRAMP. For more information, see Logging data events .	May 7, 2021
Added service support	This release supports Service Quotas and Amazon EBS direct APIs. See AWS CloudTrail Supported Services and Integrations .	April 13, 2021
Added functionality	After an IAM administrator configures AWS STS , CloudTrail logs sourceIdentity information in events when users assume an IAM role, or perform any actions with the assumed role. For more information, see CloudTrail userIdentity Element .	April 13, 2021

[Updated documentation](#)

This update documents limits, in kilobytes (KB), for content in some CloudTrail event record fields. For more information, see [CloudTrail record contents](#).

April 8, 2021

[Added functionality](#)

After an IAM administrator configures [AWS STS](#), CloudTrail logs sourceIdentity information in events when users assume an IAM role, or perform any actions with the assumed role. For more information, see [CloudTrail userIdentity Element](#).

April 6, 2021

[Added functionality](#)

You can now log data events on Amazon DynamoDB tables. You can log DynamoDB data events by using either event selectors or advanced event selectors. For more information, see [Logging data events](#).

March 23, 2021

[Added service support](#)

This release supports Amazon Managed Workflows for Apache Airflow. See [AWS CloudTrail Supported Services and Integrations](#).

March 22, 2021

Added functionality	You can now log data events on S3 Object Lambda access points if you have opted in to use advanced event selectors . For more information, see Logging data events .	March 18, 2021
Added service support	This release supports AWS Fault Injection Simulator. See AWS CloudTrail Supported Services and Integrations .	March 15, 2021
Added functionality	You can now log data events on Ethereum nodes in Amazon Managed Blockchain if you have opted in to use advanced event selectors. For more information, see Logging data events .	March 1, 2021
Added service support	This release supports Amazon Managed Blockchain and the preview of Ethereum for Managed Blockchain. See AWS CloudTrail Supported Services and Integrations .	February 4, 2021
Added service support	This release supports AWS Amplify. See AWS CloudTrail Supported Services and Integrations .	February 3, 2021
Added service support	This release supports Amazon Lookout for Metrics. See AWS CloudTrail Supported Services and Integrations .	February 1, 2021

Updated documentation	This update supports the following patch release for the CloudTrail Processing Library: Update the .jar file references in the user guide to use the latest version, aws-cloudtrail-processing-library-1.4.0.jar. For more information, see Using the CloudTrail Processing Library and the CloudTrail Processing Library on GitHub.	January 12, 2021
Added functionality	You can now log data events on Amazon S3 on AWS Outposts. For more information, see Logging data events .	December 21, 2020
Added service support	This release supports Amazon Lookout for Equipment, AWS Well-Architected Tool, and Amazon Location Service. See AWS CloudTrail Supported Services and Integrations .	December 16, 2020
Added service support	This release supports AWS IoT Greengrass V2. See AWS CloudTrail Supported Services and Integrations .	December 15, 2020
Added service support	This release supports Amazon EMR on EKS. See AWS CloudTrail Supported Services and Integrations .	December 10, 2020

Added service support	This release supports AWS Audit Manager and Amazon HealthLake. See AWS CloudTrail Supported Services and Integrations .	December 8, 2020
Added service support	This release supports Amazon Lookout for Vision. See AWS CloudTrail Supported Services and Integrations .	December 1, 2020
Updated event version	The AWS CloudTrail event version is now 1.08. Version 1.08 introduces new fields for CloudTrail. For more information, see CloudTrail record contents .	November 24, 2020
Added functionality	AWS CloudTrail introduces advanced event selectors for data events. Advanced event selectors allow finer-grained control over the data events that you log to your trail. You can include or exclude data events for specific AWS resources, and select specific APIs on those resources to log to your trail. For more information, see Logging data events .	November 24, 2020
Added service support	This release supports AWS Network Firewall. See AWS CloudTrail Supported Services and Integrations .	November 17, 2020

Added service support	This release supports AWS Trusted Advisor. See AWS CloudTrail Supported Services and Integrations .	October 22, 2020
Updated documentation	Added two new examples of event records for root user sign-in events. For more information, see AWS Console sign-in events .	October 13, 2020
Changed functionality	Permissions in the <code>AWSCloudTrail_FullAccess</code> policy have been narrowed. This policy no longer allows you to delete Amazon SNS topics or Amazon S3 buckets, and the <code>getObject</code> action has been removed. For more information, see Granting custom permissions for CloudTrail users .	September 29, 2020
Updated documentation	This update supports the following patch release for the CloudTrail Processing Library: Update the .jar file references in the user guide to use the latest version, <code>aws-cloudtrail-processing-library-1.3.0.jar</code> . For more information, see Using the CloudTrail Processing Library and the CloudTrail Processing Library on GitHub.	August 28, 2020

Added service support	This release supports AWS Outposts. See AWS CloudTrail Supported Services and Integrations .	August 28, 2020
Added functionality	AWS CloudTrail Insights introduces attribution fields for CloudTrail Insights events. Attribution fields show the top user identities, user agents, and error codes that are associated with the anomalous activity that triggers Insights events. For comparison, attribution fields also show the top user identities, user agents, and error codes associated with normal, or baseline, activity. For more information, see Logging Insights events .	August 13, 2020
Added functionality	The AWS CloudTrail console has a new look that's designed to make it easier to use. The AWS CloudTrail User Guide has been updated with changes to procedures for how to perform tasks in the console, such as creating trails, updating trails, and downloading event history.	August 13, 2020
Added service support	This release supports Amazon Interactive Video Service. See AWS CloudTrail Supported Services and Integrations .	July 15, 2020

Added service support	This release supports Amazon Honeycode. See AWS CloudTrail Supported Services and Integrations .	June 24, 2020
Added service support	This release supports Amazon Macie. See AWS CloudTrail Supported Services and Integrations .	May 19, 2020
Added service support	This release supports Amazon Kendra. See AWS CloudTrail Supported Services and Integrations .	May 13, 2020
Added service support	This release supports AWS IoT SiteWise. See AWS CloudTrail Supported Services and Integrations .	April 29, 2020
Added Region support	This release supports an additional Region: Europe (Milan). See AWS CloudTrail Supported Regions .	April 28, 2020
Added service and Region support	This release supports Amazon AppFlow. See AWS CloudTrail Supported Services and Integrations . Support has also been added for the Africa (Cape Town) Region. See AWS CloudTrail Supported Regions .	April 22, 2020

Added functionality

High-volume AWS KMS actions such as Encrypt, Decrypt, and GenerateDataKey are now logged as **Read** events. If you choose to log all AWS KMS events on your trail, and also choose to log **Write** management events, your trail logs relevant AWS KMS actions like Disable, Delete and ScheduleKey .

April 7, 2020

Added service support

This release supports Amazon CodeGuru Reviewer. See [AWS CloudTrail Supported Services and Integrations](#).

February 7, 2020

Added service support

This release supports Amazon Managed Apache Cassandra Service. See [AWS CloudTrail Supported Services and Integrations](#).

January 17, 2020

Added service support

This release supports Amazon Connect. See [AWS CloudTrail Supported Services and Integrations](#).

December 13, 2019

Updated documentation	This update supports the following patch release for the CloudTrail Processing Library: Update the .jar file references in the user guide to use the latest version, aws-cloudtrail-processing-library-1.2.0.jar. For more information, see Using the CloudTrail Processing Library and the CloudTrail Processing Library on GitHub.	November 21, 2019
Added functionality	This release supports AWS CloudTrail Insights for helping you detect unusual activity in your account. See Logging Insights events for Trails .	November 20, 2019
Added functionality	This release adds an option for filtering AWS Key Management Service events out of a trail. See Creating a Trail .	November 20, 2019
Added service support	This release supports AWS CodeStar Notifications. See AWS CloudTrail Supported Services and Integrations .	November 7, 2019
Added functionality	This release supports adding tags when you create a trail in CloudTrail, whether you use the CloudTrail console or API. This release adds two new APIs, <code>GetTrail</code> and <code>ListTrails</code> .	November 1, 2019

Added service support	This release supports AWS App Mesh. See AWS CloudTrail Supported Services and Integrations .	October 17, 2019
Added service support	This release supports Amazon Translate. See AWS CloudTrail Supported Services and Integrations .	October 17, 2019
Documentation update	The Unsupported Services topic has been restored and updated to include only those AWS services that do not currently log events in CloudTrail. See CloudTrail Unsupported Services .	October 7, 2019
Documentation update	The documentation has been updated with changes to the <code>AWSCloudTrailFullAccess</code> policy. A policy example that shows equivalent permissions to <code>AWSCloudTrailFullAccess</code> has been updated to restrict the resources on which the <code>iam:PassRole</code> action can act to those matching the following condition statement: <code>"iam:PassedToService": "cloudtrail.amazonaws.com"</code> . See AWS CloudTrail Identity-Based Policy Examples .	September 24, 2019

Documentation update	The documentation has been updated with a new topic, Managing CloudTrail Costs , to help you get the log data you need out of CloudTrail while staying within a budget.	September 3, 2019
Added service support	This release supports AWS Control Tower. See AWS CloudTrail Supported Services and Integrations .	August 13, 2019
Added Region support	This release supports an additional Region: Middle East (Bahrain). See AWS CloudTrail Supported Regions .	July 29, 2019
Documentation update	The documentation has been updated with information about security for CloudTrail. See Security in AWS CloudTrail .	July 3, 2019
Added service support	This release supports AWS Ground Station. See AWS CloudTrail Supported Services and Integrations .	June 6, 2019
Added service support	This release supports AWS IoT Things Graph. See AWS CloudTrail Supported Services and Integrations .	June 4, 2019
Added service support	This release supports Amazon WorkSpaces Applications. See AWS CloudTrail Supported Services and Integrations .	April 25, 2019

Added Region support	This release supports an additional Region: Asia Pacific (Hong Kong). See AWS CloudTrail Supported Regions .	April 24, 2019
Added service support	This release supports Amazon Managed Service for Apache Flink. See AWS CloudTrail Supported Services and Integrations .	March 22, 2019
Added service support	This release supports AWS Backup. See AWS CloudTrail Supported Services and Integrations .	February 4, 2019
Added service support	This release supports Amazon WorkLink. See AWS CloudTrail Supported Services and Integrations .	January 23, 2019
Added service support	This release supports AWS Cloud9. See AWS CloudTrail Supported Services and Integrations .	January 21, 2019
Added service support	This release supports AWS Elemental MediaLive. See AWS CloudTrail Supported Services and Integrations .	January 19, 2019
Added service support	This release supports Amazon Comprehend. See AWS CloudTrail Supported Services and Integrations .	January 18, 2019

Added service support	This release supports AWS Elemental MediaPackage. See AWS CloudTrail Supported Services and Integrations .	December 21, 2018
Added Region support	This release supports an additional Region: EU (Stockholm). See AWS CloudTrail Supported Regions .	December 11, 2018
Documentation update	The documentation has been updated with information about supported and unsupported services. See AWS CloudTrail Supported Services and Integrations .	December 3, 2018
Added service support	This release supports AWS Resource Access Manager (AWS RAM). See AWS CloudTrail Supported Services and Integrations .	November 20, 2018
Updated functionality	This release supports creating a trail in CloudTrail that logs events for all AWS accounts in an organization in AWS Organizations. See Creating a Trail for an Organization .	November 19, 2018
Added service support	This release supports Amazon Pinpoint SMS and Voice API. See AWS CloudTrail Supported Services and Integrations .	November 16, 2018

Added service support	This release supports AWS IoT Greengrass. See AWS CloudTrail Supported Services and Integrations .	October 29, 2018
Updated documentation	This update supports the following patch release for the CloudTrail Processing Library: Update the .jar file references in the user guide to use the latest version, aws-cloudtrail-processing-library-1.1.3.jar. For more information, see Using the CloudTrail Processing Library and the CloudTrail Processing Library on GitHub.	October 18, 2018
Added functionality	This release supports using additional filters in Event history . See Viewing CloudTrail Events in the CloudTrail Console .	October 18, 2018
Added functionality	This release supports using Amazon Virtual Private Cloud (Amazon VPC) to establish a private connection between your VPC and AWS CloudTrail. See Using AWS CloudTrail with Interface VPC Endpoints .	August 9, 2018
Added service support	This release supports Amazon Data Lifecycle Manager. See AWS CloudTrail Supported Services and Integrations .	July 24, 2018

Added service support	This release supports Amazon MQ. See AWS CloudTrail Supported Services and Integrations .	July 19, 2018
Added service support	This release supports AWS Mobile CLI. See AWS CloudTrail Supported Services and Integrations .	June 29, 2018
AWS CloudTrail documentation history notification available through RSS feed	You can now receive notification about updates to the AWS CloudTrail documentation by subscribing to an RSS feed.	June 29, 2018

Earlier updates

The following table describes the documentation release history of AWS CloudTrail prior to June 29, 2018.

Change	Description	Release Date
Added service support	This release supports Amazon RDS Performance Insights. For more information, see CloudTrail Supported Services and Integrations .	June 21, 2018
Added functionality	This release supports logging all CloudTrail management events in Event history. For more information, see Working with CloudTrail event history .	June 14, 2018
Added service support	This release supports AWS Billing and Cost Management. See CloudTrail supported services and integrations .	June 7, 2018

Change	Description	Release Date
Added service support	This release supports Amazon Elastic Container Service for Kubernetes (Amazon EKS). See CloudTrail supported services and integrations .	June 5, 2018
Updated documentation	This update supports the following patch release for the CloudTrail Processing Library: Update the .jar file references in the user guide to use the latest version, aws-cloudtrail-processing-library-1.1.2.jar. For more information, see Using the CloudTrail Processing Library and the CloudTrail Processing Library on GitHub.	May 16, 2018
Added service support	This release supports AWS Billing and Cost Management. See CloudTrail supported services and integrations .	June 7, 2018
Added service support	This release supports Amazon Elastic Container Service for Kubernetes (Amazon EKS). See CloudTrail supported services and integrations .	June 5, 2018
Updated documentation	This update supports the following patch release for the CloudTrail Processing Library: Update the .jar file references in the user guide to use the latest version, aws-cloudtrail-processing-library-1.1.2.jar. For more information, see Using the CloudTrail Processing Library and the CloudTrail Processing Library on GitHub.	May 16, 2018

Change	Description	Release Date
Added service support	This release supports AWS X-Ray. See CloudTrail supported services and integrations .	April 25, 2018
Added service support	This release supports AWS IoT Analytics. See CloudTrail supported services and integrations .	April 23, 2018
Added service support	This release supports Secrets Manager. See CloudTrail supported services and integrations .	April 10, 2018
Added service support	This release supports Amazon Rekognition. See CloudTrail supported services and integrations .	April 6, 2018
Added service support	This release supports AWS Private Certificate Authority (PCA). See CloudTrail supported services and integrations .	April 4, 2018
Added functionality	This release supports making it easier to search CloudTrail log files with Amazon Athena. You can automatically create tables for querying logs directly from the CloudTrail console, and use those tables to run queries in Athena. For more information, see CloudTrail supported services and integrations and Creating a Table for CloudTrail Logs in the CloudTrail Console .	March 15, 2018
Added service support	This release supports AWS AppSync. See CloudTrail supported services and integrations .	February 13, 2018
Added Region support	This release supports an additional Region: Asia Pacific (Osaka) (ap-northeast-3). See CloudTrail supported Regions .	February 12, 2018
Added service support	This release supports AWS Shield. See CloudTrail supported services and integrations .	February 12, 2018

Change	Description	Release Date
Added service support	This release supports Amazon SageMaker AI. See CloudTrail supported services and integrations .	January 11, 2018
Added service support	This release supports AWS Batch. See CloudTrail supported services and integrations .	January 10, 2018
Added functionality	This release supports extending the amount of account activity that is available in CloudTrail event history to 90 days. You can also customize the display of columns to improve the view of your CloudTrail events. For more information, see Working with CloudTrail event history .	December 12, 2017
Added service support	This release supports Amazon WorkMail. See CloudTrail supported services and integrations .	December 12, 2017
Added service support	This release supports Alexa for Business, AWS Elemental MediaConvert, and AWS Elemental MediaStore. See CloudTrail supported services and integrations .	December 1, 2017
Added functionality and documentation	This release supports logging data events for AWS Lambda functions. For more information, see Logging data events.	November 30, 2017
Added functionality and documentation	This release supports logging data events for AWS Lambda functions. For more information, see Logging data events.	November 30, 2017

Change	Description	Release Date
Added functionality and documentation	This release supports the following updates to the CloudTrail Processing Library: • Add support for Boolean identification of management events. • Update the CloudTrail event version to 1.06. For more information, see Using the CloudTrail Processing Library and the CloudTrail Processing Library on GitHub.	November 30, 2017
Added service support	This release supports AWS Glue. See CloudTrail supported services and integrations .	November 7, 2017
New documentation	This release adds a new topic, Quotas in AWS CloudTrail .	October 19, 2017
Updated documentation	This release updates the documentation of APIs supported in CloudTrail event history for Amazon Athena, AWS CodeBuild, Amazon Elastic Container Registry, and AWS Migration Hub.	October 13, 2017
Added service support	This release supports Amazon Chime. See CloudTrail supported services and integrations .	September 27, 2017
Added functionality and documentation	This release supports configuring data event logging for all Amazon S3 buckets in your AWS account. See Logging data events .	September 20, 2017
Added service support	This release supports Amazon Lex. See CloudTrail supported services and integrations .	August 15, 2017
Added service support	This release supports AWS Migration Hub. See CloudTrail supported services and integrations .	August 14, 2017

Change	Description	Release Date
Added functionality and documentation	This release supports CloudTrail being enabled by default for all AWS accounts. The past seven days of account activity are available in CloudTrail event history, and the most recent events appear on the console dashboard. The feature formerly known as API activity history has been replaced by Event history .	August 14, 2017
Added functionality and documentation	This release supports downloading events from the CloudTrail console on the API activity history page. You can download events in JSON or CSV format. For more information, see Downloading events .	July 27, 2017
Added functionality	This release supports logging Amazon S3 object level API operations in two additional Regions, Europe (London) and Canada (Central). For more information, see Working with CloudTrail log files .	July 19, 2017
Added service support	This release supports looking up APIs for Amazon CloudWatch Events in the CloudTrail API activity history feature.	June 27, 2017

Change	Description	Release Date
Added functionality and documentation	This release supports additional APIs in the CloudTrail API activity history feature for the following services: • AWS CloudHSM • Amazon Cognito • Amazon DynamoDB • Amazon EC2 • Kinesis • AWS Storage Gateway	June 27, 2017
Added service support	This release supports AWS CodeStar. See CloudTrail supported services and integrations.	June 14, 2017

Change	Description	Release Date
Added functionality and documentation	This release supports the following updates to the CloudTrail Processing Library: • Add support for different formats for SQS messages from the same SQS queue to identify CloudTrail log files. The following formats are supported: • Notifications that CloudTrail sends to an SNS topic • Notifications that Amazon S3 sends to an SNS topic • Notifications that Amazon S3 sends directly to an SQS queue • Add support for the <code>deleteMessageUponFailure</code> property, which you can use to delete messages that can't be processed. For more information, see Using the CloudTrail Processing Library and the CloudTrail Processing Library on GitHub.	June 1, 2017
Added service support	This release supports Amazon Athena. See CloudTrail supported services and integrations .	May 19, 2017
Added functionality	This release supports sending data events to Amazon CloudWatch Logs. For more information about configuring your trail to log data events, see Data events. For more information about sending events to CloudWatch Logs, see Monitoring CloudTrail Log Files with Amazon CloudWatch Logs.	May 9, 2017

Change	Description	Release Date
Added service support	This release supports the AWS Marketplace Metering Service. See CloudTrail supported services and integrations .	May 2, 2017
Added service support	This release supports Amazon Quick Suite. See CloudTrail supported services and integrations .	April 28, 2017
Added functionality and documentation	This release supports an updated console experience for creating new trails. You can now configure a new trail to log management and data events. For more information, see Creating a trail with the CloudTrail console .	April 11, 2017
Added documentation	If CloudTrail is not delivering logs to your S3 bucket or sending SNS notifications from some Regions in your account, you may need to update the policies. To learn more about updating your S3 bucket policy, see Common Amazon S3 policy configuration errors. To learn more about updating your SNS topic policy, see CloudTrail is not sending notifications for a Region.	March 31, 2017
Added service support	This release supports AWS Organizations. See CloudTrail supported services and integrations .	February 27, 2017
Added functionality and documentation	This release supports an updated console experience for configuring trails for logging management and data events. For more information, see Working with CloudTrail log files .	February 10, 2017
Added service support	This release supports Amazon Cloud Directory. See CloudTrail supported services and integrations .	January 26, 2017

Change	Description	Release Date
Added functionality and documentation	This release supports looking up APIs for AWS CodeCommit, Amazon GameLift Servers, and AWS Managed Services in the CloudTrail API activity history.	January 26, 2017
Added functionality	This release supports integration with the AWS Health Dashboard. You can use the AWS Health Dashboard to identify if your trails are unable to deliver logs to an SNS topic or S3 bucket. This can occur when there is an issue with the policy for the S3 bucket or SNS topic. AWS Health Dashboard notifies you about the affected trails and recommends ways to fix the policy. For more information, see the AWS Health User Guide.	January 24, 2017
Added functionality and documentation	This release supports filtering by event source in the CloudTrail console. Event source shows the AWS service to which the request was made. For more information, see Viewing recent management events with the console.	January 12, 2017
Added service support	This release supports AWS CodeCommit. See CloudTrail supported services and integrations .	January 11, 2017
Added service support	This release supports Amazon Lightsail. See CloudTrail supported services and integrations .	December 23, 2016
Added service support	This release supports AWS Managed Services. See CloudTrail supported services and integrations .	December 21, 2016
Added Region support	This release supports the Europe (London) Region. See CloudTrail supported Regions .	December 13, 2016

Change	Description	Release Date
Added Region support	This release supports the Canada (Central) Region. See CloudTrail supported Regions .	December 8, 2016
Added service support	This release supports AWS CodeBuild. See CloudTrail supported services and integrations. This release supports AWS Health. See CloudTrail supported services and integrations. This release supports AWS Step Functions. See CloudTrail supported services and integrations.	December 1, 2016
Added service support	This release supports Amazon Polly. See CloudTrail supported services and integrations .	November 30, 2016
Added service support	This release supports AWS OpsWorks for Chef Automate. See CloudTrail supported services and integrations .	November 23, 2016
Added functionality and documentation	This release supports configuring your trail to log read-only, write-only, or all events. CloudTrail supports logging Amazon S3 object level API operations such as <code>GetObject</code> , <code>PutObject</code> , and <code>DeleteObject</code> . You can configure your trails to log object level API operations. For more information, see Working with CloudTrail log files.	November 21, 2016
Added functionality and documentation	This release supports additional values for the <code>userIdentity</code> element: <code>AWSAccount</code> and <code>AWSService</code> . For more information, see the Fields for <code>userIdentity</code> .	November 16, 2016

Change	Description	Release Date
Added service support	This release supports Application Auto Scaling. See CloudTrail supported services and integrations .	October 31, 2016
Added Region support	This release supports the US East (Ohio) Region. See CloudTrail supported Regions .	October 17, 2016
Added functionality and documentation	This release supports logging non-API AWS service events. For more information, see AWS service events .	September 23, 2016
Added functionality and documentation	This release supports using the CloudTrail console to view resource types that are supported by AWS Config. For more information, see Viewing resources referenced with AWS Config .	July 7, 2016
Added service support	This release supports AWS Service Catalog. See CloudTrail supported services and integrations .	July 6, 2016
Added service support	This release supports Amazon Elastic File System (Amazon EFS). See CloudTrail supported services and integrations .	June 28, 2016
Added Region support	This release supports one additional Region: ap-south-1 (Asia Pacific (Mumbai)). See CloudTrail supported Regions .	June 27, 2016
Added service support	This release supports AWS Application Discovery Service. See CloudTrail supported services and integrations .	May 12, 2016
Added service support	This release supports CloudWatch Logs in the South America (São Paulo) Region. For more information, see Monitoring CloudTrail Log Files with Amazon CloudWatch Logs .	May 6, 2016
Added service support	This release supports AWS WAF. See CloudTrail supported services and integrations .	April 28, 2016

Change	Description	Release Date
Added service support	This release supports AWS Support. See CloudTrail supported services and integrations .	April 21, 2016
Added service support	This release supports Amazon Inspector. See CloudTrail supported services and integrations .	April 20, 2016
Added service support	This release supports AWS IoT. See CloudTrail supported services and integrations .	April 11, 2016
Added functionality and documentation	This release supports logging AWS Security Token Service (AWS STS) API calls made with Security Assertion Markup Language (SAML) and web identity federation. For more information, see Values for AWS STS APIs with SAML and web identity federation .	March 28, 2016
Added service support	This release supports AWS Certificate Manager. See CloudTrail supported services and integrations .	March 25, 2016
Added service support	This release supports Amazon Data Firehose. See CloudTrail supported services and integrations .	March 17, 2016
Added service support	This release supports Amazon CloudWatch Logs. See CloudTrail supported services and integrations .	March 10, 2016
Added service support	This release supports Amazon Cognito. See CloudTrail supported services and integrations .	February 18, 2016
Added service support	This release supports AWS Database Migration Service. See CloudTrail supported services and integrations .	February 4, 2016
Added service support	This release supports Amazon GameLift Servers (Amazon GameLift Servers). See CloudTrail supported services and integrations .	January 27, 2016

Change	Description	Release Date
Added service support	This release supports Amazon CloudWatch Events. See CloudTrail supported services and integrations .	January 16, 2016
Added Region support	This release supports one additional Region: ap-northeast-2 (Asia Pacific (Seoul)). See CloudTrail supported Regions .	January 6, 2016
Added service support	This release supports Amazon Elastic Container Registry (Amazon ECR). See CloudTrail supported services and integrations .	December 21, 2015
Added functionality and documentation	This release supports turning on CloudTrail across all Regions and support for multiple trails per Region. For more information, see Working with CloudTrail trails .	December 17, 2015
Added service support	This release supports Amazon Machine Learning. See CloudTrail supported services and integrations .	December 10, 2015
Added functionality and documentation	This release supports log file encryption, log file integrity validation, and tagging. For more information, see Encrypting CloudTrail log files, digest files, and event data stores with AWS KMS keys (SSE-KMS) , Validating CloudTrail log file integrity , and Updating a trail with the CloudTrail console .	October 1, 2015
Added service support	This release supports Amazon OpenSearch Service. See CloudTrail supported services and integrations .	October 1, 2015
Added service support	This release supports Amazon S3 bucket level events. See CloudTrail supported services and integrations .	September 1, 2015
Added service support	This release supports AWS Device Farm. See CloudTrail supported services and integrations .	July 13, 2015

Change	Description	Release Date
Added service support	This release supports Amazon API Gateway. See CloudTrail supported services and integrations .	July 9, 2015
Added service support	This release supports CodePipeline. See CloudTrail supported services and integrations .	July 9, 2015
Added service support	This release supports Amazon DynamoDB. See CloudTrail supported services and integrations .	May 28, 2015
Added service support	This release supports CloudWatch Logs in the US West (N. California) Region. For more information about CloudTrail support for CloudWatch Logs monitoring, see Monitoring CloudTrail Log Files with Amazon CloudWatch Logs .	May 19, 2015
Added service support	This release supports AWS Directory Service. See CloudTrail supported services and integrations .	May 14, 2015
Added service support	This release supports Amazon Simple Email Service (Amazon SES). See CloudTrail supported services and integrations .	May 7, 2015
Added service support	This release supports Amazon Elastic Container Service. See CloudTrail supported services and integrations .	April 9, 2015
Added service support	This release supports AWS Lambda. See CloudTrail supported services and integrations .	April 9, 2015
Added service support	This release supports Amazon WorkSpaces. See CloudTrail supported services and integrations .	April 9, 2015

Change	Description	Release Date
	This release supports the lookup of AWS activity captured by CloudTrail (CloudTrail events). You can look up and filter events in your account related to creation, modification, or deletion. To look up these events, you can use the CloudTrail console, the AWS Command Line Interface (AWS CLI), or the AWS SDK. For more information, see Working with CloudTrail event history .	March 12, 2015
Added service support and new documentation	This release supports Amazon CloudWatch Logs in the Asia Pacific (Singapore), Asia Pacific (Sydney), Asia Pacific (Tokyo), and Europe (Frankfurt) Regions. For more information, see Sending events to CloudWatch Logs .	March 5, 2015
New documentation	A new section that describes CloudTrail support for AWS Security Token Service (AWS STS) regional endpoints has been added to the CloudTrail Concepts page.	February 17, 2015
Added service support	This release supports Amazon Route 53. See CloudTrail supported services and integrations .	February 11, 2015
Added service support	This release supports AWS Config. See CloudTrail supported services and integrations .	February 10, 2015
Added service support	This release supports AWS CloudHSM. See CloudTrail supported services and integrations .	January 8, 2015
Added service support	This release supports AWS CodeDeploy. See CloudTrail supported services and integrations .	December 17, 2014
Added service support	This release supports AWS Storage Gateway. See CloudTrail supported services and integrations .	December 16, 2014

Change	Description	Release Date
Added Region support	This release supports one additional Region: us-gov-west-1 (AWS GovCloud (US-West)). See CloudTrail supported Regions .	December 16, 2014
Added service support	This release supports Amazon Glacier. See CloudTrail supported services and integrations .	December 11, 2014
Added service support	This release supports AWS Data Pipeline. See CloudTrail supported services and integrations .	December 2, 2014
Added service support	This release supports AWS Key Management Service. See CloudTrail supported services and integrations .	November 12, 2014
New documentation	A new section, Monitoring CloudTrail Log Files with Amazon CloudWatch Logs , has been added to the guide. It describes how to use Amazon CloudWatch Logs to monitor CloudTrail log events.	November 10, 2014
New documentation	A new section, Using the CloudTrail Processing Library , has been added to the guide. It provides information about how to write a CloudTrail log processor in Java using the AWS CloudTrail Processing Library.	November 5, 2014
Added service support	This release supports Amazon Elastic Transcoder. See CloudTrail supported services and integrations .	October 27, 2014
Added Region support	This release supports one additional region: eu-central-1 (Europe (Frankfurt)). See CloudTrail supported Regions .	October 23, 2014
Added service support	This release supports Amazon CloudSearch. See CloudTrail supported services and integrations .	October 16, 2014

Change	Description	Release Date
Added service support	This release supports Amazon Simple Notification Service. See CloudTrail supported services and integrations .	October 09, 2014
Added service support	This release supports Amazon ElastiCache. See CloudTrail supported services and integrations .	September 15, 2014
Added service support	This release supports Amazon WorkDocs. See CloudTrail supported services and integrations .	August 27, 2014
Added new content	This release includes a topic that discusses logging sign-in events. See AWS Management Console sign-in events .	July 24, 2014
Added new content	The eventVersion element for this release has been upgraded to version 1.02 and three new fields have been added. See CloudTrail record contents for management, data, and network activity events .	July 18, 2014
Added service support	This release supports Auto Scaling (see CloudTrail supported services and integrations).	July 17, 2014
Added Region support	This release supports three additional Regions: ap-southeast-1 (Asia Pacific (Singapore)), ap-northeast-1 (Asia Pacific (Tokyo)), sa-east-1 (South America (São Paulo)). See CloudTrail supported Regions .	June 30, 2014
Additional service support	This release supports Amazon Redshift. See CloudTrail supported services and integrations .	June 10, 2014
Added service support	This release supports OpsWorks. See CloudTrail supported services and integrations .	June 5, 2014
Added service support	This release supports Amazon CloudFront. See CloudTrail supported services and integrations .	May 28, 2014

Change	Description	Release Date
Added Region support	This release supports three additional Regions: us-west-1 (US West (N. California)), eu-west-1 (Europe (Ireland)), ap-southeast-2 (Asia Pacific (Sydney)). See CloudTrail supported Regions .	May 13, 2014
Added service support	This release supports Amazon Simple Workflow Service. See CloudTrail supported services and integrations .	May 9, 2014
Added new content	This release includes topics that discuss sharing log files between accounts. See Sharing CloudTrail log files between AWS accounts .	May 2, 2014
Added service support	This release supports Amazon CloudWatch. See CloudTrail supported services and integrations .	April 28, 2014
Added service support	This release supports Amazon Kinesis. See CloudTrail supported services and integrations .	April 22, 2014
Added service support	This release supports AWS Direct Connect. See CloudTrail supported services and integrations .	April 11, 2014
Added service support	This release supports Amazon EMR. See CloudTrail supported services and integrations .	April 4, 2014
Added service support	This release supports Elastic Beanstalk. See CloudTrail supported services and integrations .	April 2, 2014
Additional service support	This release supports AWS CloudFormation. See CloudTrail supported services and integrations .	March 7, 2014
New guide	This release introduces AWS CloudTrail.	November 13, 2013