

---

# MySQL Proxy Release Notes

## Abstract

This document contains release notes for the changes in each release of MySQL Proxy.

For additional MySQL Proxy documentation, see [MySQL Proxy](#).

Updates to these notes occur as new product features are added, so that everybody can follow the development process. If a recent version is listed here that you cannot find on the download page (<http://dev.mysql.com/downloads/>), the version has not yet been released.

The documentation included in source and binary distributions may not be fully up to date with respect to release note entries because integration of the documentation occurs at release build time. For the most up-to-date release notes, please refer to the online documentation instead.

For legal information, see the [Legal Notices](#).

For help with using MySQL, please visit either the [MySQL Forums](#) or [MySQL Mailing Lists](#), where you can discuss your issues with other MySQL users.

For additional documentation on MySQL products, including translations of the documentation into other languages, and downloadable versions in variety of formats, including HTML and PDF formats, see the [MySQL Documentation Library](#).

Document generated on: 2016-04-04 (revision: 8592)

## Table of Contents

Preface and Legal Notices .....	1
Changes in MySQL Proxy 0.8.5 (2014-09-05) .....	3
Changes in MySQL Proxy 0.8.4 (2014-01-10) .....	3
Changes in MySQL Proxy 0.8.3 (2012-08-20) .....	4
Changes in MySQL Proxy 0.8.2 (2011-08-18) .....	5
Changes in MySQL Proxy 0.8.1 (2010-09-13) .....	6
Changes in MySQL Proxy 0.8.0 (2010-01-21) .....	6
Changes in MySQL Proxy 0.7.2 (2009-06-30) .....	7
Changes in MySQL Proxy 0.7.1 (2009-05-15) .....	8
Changes in MySQL Proxy 0.7.0 (Not Released) .....	8
Changes in MySQL Proxy 0.6.1 (2008-02-06) .....	10
Changes in MySQL Proxy 0.6.0 (2007-09-11) .....	10
Changes in MySQL Proxy 0.5.1 (2007-06-30) .....	11
Changes in MySQL Proxy 0.5.0 (2007-06-19) .....	12

## Preface and Legal Notices

This document contains release notes for the changes in each release of MySQL Proxy.

## Legal Notices

Copyright © 1997, 2013, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

#### Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

#### Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

This documentation is NOT distributed under a GPL license. Use of this documentation is subject to the following terms:

You may create a printed copy of this documentation solely for your own personal use. Conversion to other formats is allowed as long as the actual content is not altered or edited in any way. You shall not publish or distribute this documentation in any form or on any media, except if you distribute the documentation in a manner similar to how Oracle disseminates it (that is, electronically for download on a Web site with the software) or on a CD-ROM or similar medium, provided however that the documentation is disseminated together with the software on the same medium. Any other use, such as any dissemination of printed copies or use of this documentation, in whole or in part, in another publication, requires the prior written consent from an authorized representative of Oracle. Oracle and/or its affiliates reserve any and all rights to this documentation not expressly granted above.

## Changes in MySQL Proxy 0.8.5 (2014-09-05)

- [Functionality Added or Changed](#)
- [Bugs Fixed](#)

### Functionality Added or Changed

- As of this release, the admin-server's listening port is logged if `log-level` is set to `message`, `info`, or `debug`.

### Bugs Fixed

- The `network_mysqlld_proto_password_check()` function raised an assertion. (Bug #71165)
- Specifying a directory name as the value of the `--admin-lua-script` option failed to produce an error (the value must be a file name).
- A stored function that used cursors caused the client to hang when the function was used in a nonprepared statement.

## Changes in MySQL Proxy 0.8.4 (2014-01-10)

- [Functionality Added or Changed](#)
- [Bugs Fixed](#)

### Functionality Added or Changed

- The `admin` plugin now rejects empty passwords.

### Bugs Fixed

- Building with `automake` 1.13 is now supported. (Bug #17776451)
- A too-strict test for protocol state resulted in writing excessive log output. (Bug #17434833)
- Chassis log rotation functions did not work on Windows. (Bug #17275852)
- Calls to `network_address_set_address()` returned a malformed value on Windows. (Bug #16664004)

- MySQL Proxy `libtool-archive .la` files were inadvertently included with distributions. (Bug #14773448)
- MySQL Proxy could fail to connect to the IPv6 loopback address. (Bug #14677085)
- MySQL Proxy crashed when started with an unknown option. (Bug #14665885)
- The `connected_clients` value was incremented even if the backend was down. (Bug #66399, Bug #16389293)
- If MySQL Proxy was configured to listen on a Unix socket file, it failed to remove the file when exiting, causing the next Proxy instance to fail at startup. (Bug #60781, Bug #14198411)
- Incorrect README files were included in distributions.
- MySQL Proxy blocked port 4040.
- A memory leak resulted from a missing callback to the memory-free function.

## Changes in MySQL Proxy 0.8.3 (2012-08-20)

- [Functionality Added or Changed](#)
- [Bugs Fixed](#)

### Functionality Added or Changed

- Added support for extracting pluggable authentication protocol information. In the Lua API, added these values: `con.client.challenge.auth_plugin_name`, `con.client.response.auth_plugin_name`.
- Added initial support for the Windows authentication plugin.
- Added support for making connections to backends and clients using IPv6 addresses.
- Added timeouts for connect, read, and write operations through `--proxy-connect-timeout`, `--proxy-read-timeout`, and `--proxy-write-timeout` options.

### Bugs Fixed

- Fixed a lockup under very high load.
- Fixed excessive buffering of `LOAD DATA LOCAL INFILE` data.
- Fixed `abort()` in `COM_CHANGE_USER+auth-method-switch`.
- Fixed handling of a missing trailing `\0` in MySQL 5.5.7 through MySQL 5.5.10 in the auth-method name.
- Fixed a crash if `COM_BINLOG_DUMP` was used with `rw-splitting.lua`.
- Fixed the default `plugin_dir` value for 64-bit Unix systems (`lib64/` versus `lib/`).
- Fixed a crash if the `--max-open-files` value was invalid on Win32.
- Fixed crash if the `configfile` value contained invalid characters. In the C API, added `chassis_keyfile_to_options_with_error()` and deprecated `chassis_keyfile_to_options()`.

- Fixed the length of `auth-plugin-data` in the client authentication response packet.
- Fixed handling of capability flags in the client authentication response. In the C API, `network_mysql_auth_response_new()` needs the server-side capabilities. In the Lua API, added these values: `con.client.challenge` (mirrors `con.server.challenge`), `con.client.response.server_capabilities`, `con.server.challenge.server_capabilities`.

## Changes in MySQL Proxy 0.8.2 (2011-08-18)

MySQL Proxy 0.8.2 is a maintenance release and focuses on these areas:

- Adding the protocol changes of MySQL 5.5 and later
- Removing the “admin” plugin from the list of default plugins, as it requires configuration since 0.8.1
- [Note to Windows Users](#)
- [Functionality Added or Changed](#)
- [Bugs Fixed](#)

### Note to Windows Users

- The Microsoft Visual C++ runtime libraries are now a requirement for running MySQL Proxy. Users that do not have these libraries must download and install the Microsoft Visual C++ 2008 Service Pack 1 Redistributable Package MFC Security Update. For the current Proxy version, use the following link to obtain the package:

<http://www.microsoft.com/download/en/details.aspx?id=26368>

(Bug #12836100)

### Functionality Added or Changed

- Removed the “admin” plugin from the list of default plugins, as it requires configuration since 0.8.1.
- Added support for `OUT` parameters in prepared statements in stored procedures with MySQL 5.5.
- Added support for decoding *all* data types of the row-based replication protocol.
- Added support for binary log checksums.

### Bugs Fixed

- Fixed handling of stored procedures with cursors with MySQL 5.5. (Bug #61998)
- A crash occurred if the file named with the `--defaults-file` option did not exist.

The first characters of log messages were stripped. (Bug #59790)

- A memory leak occurred if connection pooling was used. (Bug #56620)
- A bogus timestamp log was produced if state tracking was not compiled in.
- A crash could occur if run under Valgrind.
- Fixed handling of “used columns” with row-based replication.

## Changes in MySQL Proxy 0.8.1 (2010-09-13)

- [Functionality Added or Changed](#)
- [Bugs Fixed](#)

### Functionality Added or Changed

- Allow interception of `LOAD DATA INFILE` and `SHOW ERRORS` statements.
- The unused `network_mysql_com_query_result_track_state()` function has been deprecated.
- `chassis_set_fdlimit()` has been deprecated in favor of `chassis_fdlimit_set()`.
- Shutdown hooks were added to free the global memory of third-party libraries such as `openssl`.
- `con->in_load_data_local` has been removed.

### Bugs Fixed

- The admin plugin had an undocumented default value for `--admin-password`. (Bug #53429)
- Use of `LOAD DATA LOCAL INFILE` caused the connection between the client and MySQL Proxy to abort. (Bug #51864)
- If the backend MySQL server went down, and then the clock on the MySQL Proxy host went backward (for example, during daylight saving time adjustments), Proxy stopped forwarding queries to the backend. (Bug #50806)
- `network_address_set_address()`  $\rightarrow$  `network_address_set_address_ip()` called `gethostbyname()` which was not reentrant. This meant that a MySQL Proxy plugin needed to guard all calls to `network_address_set_address()` with a mutex. `network_address_set_address()` has been modified to be thread safe. (Bug #49099)
- The hard limit was fixed for the case where the fdlimit was set. (Bug #48120)
- MySQL Proxy returned an error message with a nonstandard SQL State when all backends were down:

```
"#07000(proxy) all backends are down"
```

This caused issues for clients with “retry” logic, as they could not handle these “custom” SQL States. (Bug #45417)

- If MySQL Proxy used a UNIX socket, it did not remove the socket file at termination time. (Bug #38415)
- The `--proxy-read-only-backend-addresses` option did not work. (Bug #38341, Bug #11749171)
- When running `configure` to build, the error message relating to the `lua` libraries could be misleading. The wording and build advice have been updated.

## Changes in MySQL Proxy 0.8.0 (2010-01-21)

- [Functionality Added or Changed](#)
- [Bugs Fixed](#)

### Functionality Added or Changed

- The `--no-daemon` has been renamed to The `--daemon`. By default, MySQL Proxy now starts in foreground mode. Use the `--daemon` option to override this and start in daemon mode.

### Bugs Fixed

- A memory leak occurred in MySQL Proxy if clients older than MySQL 4.1 connected to it. (Bug #50993)
- A segmentation fault occurred in MySQL Proxy if clients older than MySQL 4.1 connected to it. (Bug #48641)
- MySQL Proxy would load a configuration file with unsafe permissions, which could permit password information to be exposed through the file. MySQL Proxy now refuses to load a configuration file with unsafe permissions. (Bug #47589)

- Several supplied scripts were updated to account for flag and structure changes:

- `active-transactions.lua` was updated to use the `resultset_is_needed` flag.
- `ro-balance.lua` was updated to use the `resultset_is_needed` flag and updated `proxy.connection.dst.name` structure.
- `rw-splitting.lua` was updated to use the `resultset_is_needed` flag and updated `proxy.connections` structure.

(Bug #47349, Bug #45408, Bug #47345, Bug #43424, Bug #42841, Bug #46141)

- The line numbers provided in stack traces were off by one. (Bug #47348)
- MySQL Proxy accepted more than one address in the value of the `--proxy-backend-addresses` option. You should specify one `--proxy-backend-addresses` option for each backend address. (Bug #47273)
- MySQL Proxy returned the wrong version string internally from the `proxy.PROXY_VERSION` constant. (Bug #45996)
- MySQL Proxy could stop accepting network packets if it received a large number of packets. The listen queue has been extended to permit a larger backlog. (Bug #45878, Bug #43278)
- Due to a memory leak, memory usage for each new connection to the proxy increased, leading to very high consumption. (Bug #45272)
- MySQL Proxy failed to work with certain versions of MySQL, including MySQL 5.1.15, where a change in the MySQL protocol existed. Now Proxy denies `COM_CHANGE_USER` commands when it is connected to MySQL 5.1.14 to 5.1.17 servers by sending back an error: `COM_CHANGE_USER is broken on 5.1.14-.17, please upgrade the MySQL Server`. (Bug #45167)

References: See also Bug #25371.

- Logging to `syslog` with the `--log-use-syslog` option did not work. (Bug #36431)
- MySQL Proxy could incorrectly insert `NULL` values into the returned result set, even though non-`NULL` values were returned in the original query. (Bug #35729)
- MySQL Proxy raised an error when processing query packets larger than 16MB. (Bug #35202)

## Changes in MySQL Proxy 0.7.2 (2009-06-30)

### Bugs Fixed

- On Windows, MySQL Proxy might not find the required modules during initialization. The core code has been updated to find the components correctly, and the Lua-based C modules are prefixed with `lua-` and Lua plugins with `plugin-`. (Bug #45833)

## Changes in MySQL Proxy 0.7.1 (2009-05-15)

### Bugs Fixed

- Due to a memory leak, memory usage for each new connection to the proxy increased, leading to very high consumption. (Bug #45272)
- The port number was reported incorrectly in `proxy.connection.client.address`. (Bug #43313)
- Result sets with more than 250 fields could cause MySQL Proxy to crash. (Bug #43078)
- MySQL Proxy was unable to increase its own maximum number of open files according to the limit specified by the `--max-open-files` option, if the limit was less than 8192. When set to debug level, Proxy now reports the open files limit and when the limit has been updated. (Bug #42783)
- MySQL Proxy crashed when connecting to a MySQL 4.0 server. Now it generates an error message instead. (Bug #38601)
- When using the `rw-splitting.lua` script, you could get an error when talking to the backend server:

```
2008-07-28 18:00:30: (critical) (read_query) [string
"/usr/local/share/mysql-proxy/rw-splitting.l..."]:218: bad argument #1 to 'ipairs' (table
expected, got userdata)
```

This led to Proxy closing the connection to the configured MySQL backend. (Bug #38419)

- When using MySQL Proxy with multiple backends, failure of one backend caused Proxy to disconnect all backends and stop routing requests. (Bug #34793)

## Changes in MySQL Proxy 0.7.0 (Not Released)

- [Functionality Added or Changed](#)
- [Bugs Fixed](#)

### Functionality Added or Changed

- Support for using a configuration file, in addition to the command-line options, has been added. To specify such a file, use the `--defaults-file=file_name` command-line option. See [MySQL Proxy Command Options](#). (Bug #30206)
- A number of the internal structures developed for use with Lua scripts that work with MySQL Proxy have been updated and harmonized to make their meaning and contents easier to use and consistent across multiple locations.
- The address information has been updated. Instead of a combined `ip:port` structure that you had to parse to extract the individual information, you can now access that information directly. For example, instead of structures providing a single `.address` item, you now have these items: `name` (the combined `ip:port`), `address` (the IP address), and `port` (port number). In addition, all addresses now supply both the `src` (source) and `dst` (destination) socket information for both ends of connections.

Some familiar structures have been updated to accommodate this information:



- `proxy.connection.client.address` is `proxy.connection.client.src.name`
- `proxy.connection.server.address` is `proxy.connection.server.dst.name`
- `proxy.backends` is now in `proxy.global.backends` The `.address` field of each backend is an address-object as described earlier. For example, `proxy.backends[1].address` is `proxy.global.backends[1].dst.name`.
- The `read_auth()` and `read_handshake()` functions no longer receive an `auth` parameter. Instead, all the data is available in the connection tables.

In `read_handshake()`, you access the information through the global `proxy.connection` table:

0.6	0.7
<code>auth.thread_id</code>	<code>proxy.connection.server.thread_id</code>
<code>auth.mysql_version</code>	<code>proxy.connection.server.mysql_version</code>
<code>auth.server_addr</code>	<code>proxy.connection.server.dst.name</code>
<code>auth.client_addr</code>	<code>proxy.connection.client.src.name</code>
<code>auth.scramble</code>	<code>proxy.connection.server.scramble_buffer</code>

In `read_auth()`, you can use the following:

0.6	0.7
<code>auth.username</code>	<code>proxy.connection.client.username</code>
<code>auth.password</code>	<code>proxy.connection.client.scrambled_password</code>
<code>auth.default_db</code>	<code>proxy.connection.client.default_db</code>
<code>auth.server_addr</code>	<code>proxy.connection.server.dst.name</code>
<code>auth.client_addr</code>	<code>proxy.connection.client.src.name</code>

- In the `proxy.queries:append()` function, a third parameter is an (optional) table with options specific to the this packet. Specifically, if you want to have access to the result set in the `read_query_result()` hook, you must set the `resultset_is_needed` flag:

```
proxy.queries:append( 1, ..., { resultset_is_needed = true } )
```

For more information, see [proxy.queries](#).

- `proxy.backends` is now in `proxy.global.backends`.

## Bugs Fixed

- **Security Enhancement:** Accessing MySQL Proxy using a client or backend from earlier than MySQL 4.1 resulted in Proxy aborting with an assertion. This is because Proxy supports only MySQL 4.1 or higher. Proxy now reports a fault. (Bug #31419)
- MySQL Proxy was configured with the `LUA_PATH` and `LUA_CPATH` directory locations according to the build host rather than the execution host. In addition, during installation, certain Lua source files could be installed into the incorrect locations. (Bug #44877, Bug #44497)
- Using MySQL Proxy with very large return data sets from queries could cause a crash, with or without manipulation of the data set within the Lua engine. (Bug #39332)

- MySQL Proxy terminated if a submitted packet was smaller than expected by the protocol. (Bug #36743)
- When using MySQL Proxy in a master-master replication scenario, Proxy failed to identify failure in one of the replication masters and did not redirect connections to the other master. (Bug #35295)

## Changes in MySQL Proxy 0.6.1 (2008-02-06)

### Functionality Added or Changed

- Fixed assertions on write errors.
- Fixed sending fake server-greetings in `connect_server()`.
- Fixed error handling for socket functions on Windows.
- Added new features to `run-tests.lua`.

## Changes in MySQL Proxy 0.6.0 (2007-09-11)

- [Functionality Added or Changed](#)
- [Bugs Fixed](#)

### Functionality Added or Changed

- When using read/write splitting and the `rw-splitting.lua` example script, connecting a second user to the proxy returns an error message. (Bug #30867)
- Added support in `read_query_result()` to overwrite the result set.
- By default, MySQL Proxy now starts in daemon mode. Use the new `--no-daemon` option to override this. Added the `--pid-file` option for writing the process ID to a file after becoming a daemon.
- Added hooks for `read_auth()`, `read_handshake()` and `read_auth_result()`.
- Added handling of `proxy.connection.backend_ndx` in `connect_server()` and `read_query()` to support read/write splitting.
- Added support for `proxy.response.packets`.
- Added test cases.
- Added `--no-proxy` to disable the proxy.
- Added support for listening UNIX sockets.
- Added a global Lua-scope `proxy.global.*`.
- Added connection pooling.

### Bugs Fixed

- Fixed an assertion on `COM_BINLOG_DUMP`. (Bug #29764)
- Fixed an assertion on result-packets like `[field-len | fields | EOF | ERR]`. (Bug #29732)
- Fixed an assertion at `COM_SHUTDOWN`.

Fixed an assertion that MySQL Proxy raised at login time if a client specified no password and no default database. (Bug #29719)

- Fixed a crash if `proxy.connection` is used in `connect_server()`.
- Fixed the `glib2` check to require at least `glib2` 2.6.0.
- Fixed an assertion at connect time when all backends are down.
- Fixed connection stalling if `read_query_result()` raised an assertion.
- Fixed length encoding on `proxy.resultsets`.
- Fixed compilation on win32.
- Fixed an assertion when connecting to MySQL 6.0.1.
- Fixed decoding of length-encoded ints for 3-byte notation.
- Fixed `inj.resultset.affected_rows` on `SELECT` queries.
- Fixed handling of (SQL) `NULL` in result sets.
- Fixed a memory leak when `proxy.response.*` is used.

## Changes in MySQL Proxy 0.5.1 (2007-06-30)

- [Functionality Added or Changed](#)
- [Bugs Fixed](#)

### Functionality Added or Changed

- Added `resultset.affected_rows` and `resultset.insert_id`.
- Changed `--proxy.profiling` to `--proxy-skip-profiling`.
- Added missing dependency to `libmysqlclient-dev` to the `INSTALL` file.
- Added `inj.query_time` and `inj.response_time` into the Lua scripts.
- Added support for pre-4.1 passwords in a 4.1 connection.
- Added script examples for rewriting and injection.
- Added `proxy.VERSION`.
- Added support for UNIX sockets.
- Added protection against duplicate result sets from a script.

### Bugs Fixed

- Fixed mysql check in `configure` to die when `mysql.h` isn't detected.
- Fixed handling of duplicate ERR on `COM_CHANGE_USER` in MySQL 5.1.18+.
- Fixed a compile error with MySQL 4.1.x on missing `COM_STMT_*`.

- Fixed a crash on fields longer than 250 bytes when the result set is inspected.
- Fixed a warning if `connect_server()` is not provided.
- Fixed an assertion when an error occurs at initial script exec time.
- Fixed an assertion when `read_query_result()` is not provided when `PROXY_SEND_QUERY` is used.

## Changes in MySQL Proxy 0.5.0 (2007-06-19)

This is the first beta release.

### Bugs Fixed

- Added `automake/autoconf` support.
- Added `CMake` support.